

赛区评阅编号（由赛区组委会填写）：\_\_\_\_\_

## 2026 高教社杯全国大学生数学建模竞赛

### 承 诺 书

我们仔细阅读了《全国大学生数学建模竞赛章程》和《全国大学生数学建模竞赛参赛规则》（以下简称“竞赛章程和参赛规则”，可从 <http://www.mcm.edu.cn> 下载）。

我们完全清楚，在竞赛开始后参赛队员不能以任何方式，包括电话、电子邮件、“贴吧”、QQ 群、微信群等，与队外的任何人（包括指导教师）交流、讨论与赛题有关的问题；无论主动参与讨论还是被动接收讨论信息都是严重违反竞赛纪律的行为。

我们以中国大学生名誉和诚信郑重承诺，严格遵守竞赛章程和参赛规则，以保证竞赛的公正、公平性。如有违反竞赛章程和参赛规则的行为，我们将受到严肃处理。

我们授权全国大学生数学建模竞赛组委会，可将我们的论文以任何形式进行公开展示（包括进行网上公示，在书籍、期刊和其他媒体进行正式或非正式发表等）。

我们参赛选择的题号（从 A/B/C/D/E 中选择一项填写）：\_\_\_\_\_

我们的报名参赛队号（12 位数字全国统一编号）：\_\_\_\_\_

参赛学校（完整的学校全称，不含院系名）：\_\_\_\_\_

参赛队员 (打印并签名)：1. \_\_\_\_\_

2. \_\_\_\_\_

3. \_\_\_\_\_

指导教师或指导教师组负责人 (打印并签名)：\_\_\_\_\_

（指导教师签名意味着对参赛队的行为和论文的真实性负责）

日期：\_\_\_\_\_年\_\_\_\_月\_\_\_\_日

（请勿改动此页内容和格式。此承诺书打印签名后作为纸质论文的封面，注意电子版论文中不得出现此页。以上内容请仔细核对，如填写错误，论文可能被取消评奖资格。）

赛区评阅编号：  
(由赛区填写)

全国评阅编号：  
(全国组委会填写)

2026 高教社杯全国大学生数学建模竞赛

编 号 专 用 页

赛区评阅记录（可供赛区评阅时使用）：

|             |  |  |  |  |  |  |
|-------------|--|--|--|--|--|--|
| 评<br>阅<br>人 |  |  |  |  |  |  |
| 备<br>注      |  |  |  |  |  |  |

送全国评阅统一编号：  
(赛区组委会填写)

(请勿改动此页内容和格式。此编号专用页仅供赛区和全国评阅使用，参赛队打印后装订到纸质论文的第二页上。注意电子版论文中不得出现此页。)

# 无线电干扰源的快速自动定位与清除

## 摘 要

本文为搭载便携式测向机的机器狗建立“几何定位—站位优化—在线搜索规划—可证终止”的完整模型体系，并按附件 1、附件 2 复现了本地模拟环境，完成大规模演练与三次正式测试。

**问题一：**把带  $\pm 1^\circ$  误差的示向度解释为以检测点为顶点的角楔，定位区域即各角楔之交。证明其为凸多边形、给出  $O(n^2)$  顶点枚举算法与基于回收锥的有界性判据，用旋转卡壳法求直径并与一阶解析式  $D \approx \sqrt{w_1^2 + w_2^2 + 2w_1w_2 \cos \gamma} / \sin \gamma$  互证（细长区域偏差  $< 0.1\%$ ）。对以直径为直径的圆能否覆盖的回答是**一般不能**：本文证明任何直径为  $D$  的覆盖圆必与直径圆重合（提法良定义），给出 Thales 充要判据，并在 6 万组随机算例中测得不能覆盖的比例为 1.13%（2 站） $\sim$  3.70%（5 站），最大超出半径仅 0.18%，同时给出最小包围圆作为正确替代。

**问题二：**注意到误差地点固定、重复检测无效，将选点建模为极大极小优化：在可行源扇形上最小化最坏情形定位区域直径，并加保证第二次能收到信号的约束。解得  $b^* = 1004.1 \text{ m}$ 、 $\varphi^* = 36.8^\circ$ （相对示向度偏转）、 $J^* = 134.0 \text{ m}$ ，且与检测点位置无关。候选区域为以  $S_1$  为心、半径约 1000 m、张角  $\pm 40^\circ$  的圆弧带。相对朴素垂直策略，平均定位区域直径由 96.6 m 降到 55.1 m；沿示向度前进则 25.7% 的算例定位区域无界；4000 次 Monte-Carlo 无一次越界。

**问题三：**提出普查—机会式交会—射线归航—可证终止策略。由**七点覆盖定理**（中心加正六边形顶点， $\rho = 1280 \text{ m}$ ）保证发现全部全向源，由“无信号点集  $R_{\min}$ -覆盖目标域”给出可证明的终止判据；位置估计取问题一定位区域的最小包围圆，清除采用步长几何收缩、过冲减半的射线归航与末段六边形清除图案。60 组演练完成率 **100%**，平均定位清除时间 **307.7 s**（中位 296.8 s，标准差 49.3 s）；三次正式测试清除 14/14、12/12、10/10，平均时间 280.5 s、337.0 s、369.1 s。

**问题四：**定向源造成“半平面黑洞”，单点无信号无法排除干扰源。本文给出**认证判据**（候选位置落在其  $R_{\min}$  邻域内无信号点凸包内部时任何定向方向都无法隐藏）与**射线逼近引理**（沿曾收到信号的射线逼近，全程不丢信号），并把站位加密为间距 950 m 的三角格点（仿真证明间距不超过 958 m 时格点可自认证），再沿  $r = 1750 \text{ m}$  补一圈 12 个贴边站位以发现朝外辐射的贴边定向源。**末段定位**采用垂向截断测量（补一次垂直于视线的观测，使最小包围圆半径由 77 m 降到 1 m）与沿射线自适应站位（保证贴边定向源仍在受光侧）。60 组混合演练完成率 **100%**，平均定位清除时间 **586.1 s**（中位 584.4 s）；三次正式测试清除 12/12、11/11、12/12，平均时间 612.9 s、692.5 s、622.5 s（均值 642.6 s）；扩池复核（全向/定向/混合共 120 例）最差完成率 0.9978。

论文另给出多方法互证、残差与不确定度一致性检验、参数灵敏度分析与外部文献对照（最优交会角  $90^\circ$ 、覆盖密度  $2\pi/3\sqrt{3}$  等），并讨论模型优缺点与推广。

**关键字：** 交会定位    极大极小站位优化    圆覆盖    在线路径规划    可证终止判据

# 一、问题重述

## 1.1 问题背景

无线电干扰源的定位与清除是无线电频谱管理的核心任务。《中华人民共和国无线电管理条例》（国令第 672 号）第五十七条明确规定无线电监测站承担“对无线电信号实施监测，查找无线电干扰源和未经许可设置、使用的无线电台（站）”的职责 [1]。工程上干扰源定位分为初步监测、区域性排查与精准定位三阶段，前两阶段可由固定站、监测车或无人机完成，而受遮挡与低功率源制约，最终精确定位仍需技术人员携便携测向机徒步排查，效率低、风险高。

本题要求为某公司拟研发的“搭载于机器狗的干扰源自动定位清除系统”建立数学模型。系统工作环境为：半径 1800 m 的圆形目标区域，圆心为坐标原点， $x$  轴指向正东、 $y$  轴指向正北，单位为米；区域内干扰源个数未知。设备与规则见附录 1 与附录 2，要点如下：

- 每个干扰源的频道互不相同，取自 20 个频道  $\{1, \dots, 20\}$ ，不随时间变化；不同干扰源信号互不影响。
- 干扰源分为**全向**（覆盖  $360^\circ$ ）与**定向**（覆盖以定向方向为中心的  $180^\circ$  扇形，含边界）两类；在覆盖角内信号均匀辐射，场强仅随距离衰减。
- 测向机在某点测得的**示向度**为接收场强最大方向的方位角，范围  $[0^\circ, 360^\circ)$ ；由于本地电磁环境影响，示向度与真实方位角存在误差，误差在  $[-1^\circ, 1^\circ]$  内；**同一地点电磁环境固定，重复检测不改变误差**，只有不同地点才呈现统计规律。
- 每个干扰源存在最大可被有效接收距离（有效接收半径），取值在 1000 ~ 1500 m 之间且各不相同。
- 交会定位法：两个检测点的两条示向度方向线及其两侧各偏  $1^\circ$  的虚线围成的四边形称为**定位区域**。
- **时间与清除**：频道切换 1 s；一次检测（停下、切换、调天线、读稳定示向度）5 s；机器狗沿直线以 5 m/s 移动。光学探测仪仅在距干扰源  $\leq 20$  m 时可精确定位并启动激光枪清除（定位 3 s、清除 2 s）；20 m 内无该频道源时只耗 3 s（返回“未发现”）。检测点距源  $\leq 5$  m 且在其覆盖角内时信号过强而无法给出示向度（返回“near”），可直接清除。

## 1.2 需要解决的问题

1. **问题一**：已知若干检测点坐标及某干扰源关于这些检测点的示向度，给出采用交会定位法计算**多边形定位区域直径**（区域内任意两点距离的最大值）的算法；并回答以定位区域直径为直径的圆能否覆盖此定位区域。
2. **问题二**：已知某全向干扰源在一个检测点处测得的示向度，给出**第二个检测点的选择策略**以获得较好的定位效果，并给出第二检测点的**候选区域**。
3. **问题三**：目标区域内全为全向干扰源，总数在 10 ~ 16 之间但具体个数未知。机器狗从原点出发、测向机初始频道为 1，需在保证全部清除的前提下使完成任务时间尽量短：制定自动搜索定位及清除策略并设计算法，通过模拟器演练测试检验，统计被清除干扰源个数的比例与**平均定位清除时间**（定位清除总时间含移动、频道切

换、检测、光学精确定位与清除耗时)，随后进行三次正式测试并按表 1 格式给出结果，导出日志文件。

4. **问题四：**区域内既有全向又有定向干扰源，总数仍为 10 ~ 16，定向源的个数与定向方向均未知，其余条件同问题三，给出检测与清除的策略与算法并演练测试、三次正式测试。

表 1 问题 3/4 正式测试结果表格式（题目表 1）

| 测试案例编码 | 清除干扰源个数 | 平均定位清除时间 | 程序运行时间 |
|--------|---------|----------|--------|
| 测试 1   |         |          |        |
| 测试 2   |         |          |        |
| 测试 3   |         |          |        |

## 二、问题分析

### 2.1 总体分析框架

四个问题在逻辑上层层递进，构成一条完整的技术链（图 1）：




图 1 四个问题的逻辑关系：问题一给出几何内核与不确定度量，问题二给出站位规则，问题三、四是在线决策问题；统一内核（下方橙色框）为四个问题共用

问题一、二是**几何与最优设计问题**：给定带界误差的方位测量，刻画所有与测量相容的干扰源位置集合（定位区域），并以此为核心指标优化观测几何。问题三、四则是**在线决策与规划问题**：干扰源的位置、频道、个数均需在行进中逐步发现，机器人必须在继续搜索与前往清除已知目标之间分配时间，并且必须在有限时间内**自行判断任务是否完成**。三个层次的关键联系在于：问题一给出的定位区域及其最小包围圆，恰好是问题三、四中位置估计的**不确定度**；问题二的站位规则给出了获取第二个方位的最优几何；而问题三、四的终止判据则依赖于“探测圆覆盖”这一纯几何结论。

### 2.2 问题一分析

关键在于把“示向度  $\pm 1^\circ$ ”正确地翻译成几何约束。设检测点  $S_i$  处测得的示向度为  $\hat{\theta}_i$ ，则干扰源真实方位角  $\theta_i$  满足  $|\theta_i - \hat{\theta}_i| \leq 1^\circ$ ，等价于干扰源位于以  $S_i$  为顶点、角平分线方向为  $\hat{\theta}_i$ 、半张角  $1^\circ$  的**角楔**  $W_i$  内。于是“与全部测量相容的位置集合”即

$$\mathcal{R} = \bigcap_{i=1}^n W_i,$$

这正是附录 2 图 2 中红色四边形的推广 ( $n = 2$  时退化为四边形)。由此可得三条性质： $\mathcal{R}$  是凸的（凸集之交）；每个  $W_i$  是无界凸锥，故  $\mathcal{R}$  可能有界、无界或为空； $\mathcal{R}$  的边界必由若干条示向度边界直线支撑，因此其顶点必为两条边界直线的交点。这三条性质直接给出  $O(n^2)$  的顶点枚举算法与基于回收锥的有界性判据。

第二个问题“以定位区域直径为直径的圆能否覆盖该区域”容易被直觉误导。由 Thales 定理，点  $P$  落在以  $AB$  为直径的闭圆盘内当且仅当  $\angle APB \geq 90^\circ$ ，即  $(P - A) \cdot (P - B) \leq 0$ ；由于  $\mathcal{R}$  是凸多边形，只需对顶点逐一检验即可判定。进一步，若存在某个直径为  $D$  的圆覆盖  $\mathcal{R}$ ，则该圆必同时包含直径端点  $A, B$ ，而同时包含  $A, B$  且半径为  $D/2$  的圆唯一，即以  $AB$  为直径的圆；因此以直径为直径的圆能否覆盖与“是否存在直径为  $D$  的覆盖圆”是同一问题，提法良定义。对一般凸集答案是否（等边三角形、细长四边形都是反例），对本文的定位区域需要定量回答，故第三、四节用解析论证与 6 万次随机算例给出结论及其量级。

### 2.3 问题二分析

题面只给“一个检测点处测得的示向度”，若把第二检测点选在任意位置，定位区域可能很大甚至无界。选择策略必须只依赖于  $\hat{\theta}_1$ 、可行源集合与约束条件。逐层分析：

(1) 信息来源的全部刻画。信号在  $S_1$  被收到  $\Rightarrow$  距离不超过有效接收半径  $\leq 1500$  m；收到的是 direction 而非 near  $\Rightarrow$  距离  $> 5$  m；再加  $G$  在目标域内与方位角  $\pm 1^\circ$  约束，可行源集合  $\mathcal{G}$  是一段长 1500 m、宽  $\pm 1^\circ$  的扇形（图 7）。

(2) 评价指标。以第二检测点  $S_2$  观测后所得定位区域的直径  $D$  作为定位精度的度量（直径是区域尺寸的极大极小刻画，且与问题一直接衔接）。

(3) 设计准则。由于  $G$  在  $\mathcal{G}$  中未知，取极大极小（minimax）准则：

$$S_2^* = \arg \min_{S_2} \max_{G \in \mathcal{G}} \max_{|\delta_2| \leq 1^\circ} D(S_1, S_2, G, \delta_2). \quad (1)$$

同时必须保证第二次检测确实能收到信号，否则策略失效，故施加约束：对一切  $G \in \mathcal{G}$  有  $|S_2 - G| \leq R_{\min} = 1000$  m（取最坏接收半径，故为保证探测）。

(4) 求解思路。由一阶解析式  $D \propto \sqrt{w_1^2 + w_2^2 + 2w_1w_2 \cos \gamma} / \sin \gamma$  ( $w_i = 2\epsilon d_i$  为两侧向线在源处的横向不确定度， $\gamma$  为交会角) 可见， $D$  由两个因素控制：交会角  $\gamma$  应接近  $90^\circ$ ，且到源的距离应尽量小。前者要求  $S_2$  落在以  $S_1 \hat{G}$  为直径的圆附近，后者又要求靠近源，二者与“必须落在  $\mathcal{G}$  的 1000 m 邻域内”这一可行性约束相互制约，因此最优解存在且不退化。

(5) 为什么不能沿示向度方向前进。若第二检测点沿示向度方向前进，两条方位线近似平行，回收锥非空，定位区域无界；本文用 3000 次 Monte-Carlo 定量说明这一点（第 6.8 节）：沿示向度前进 800 m 时 25.7% 的算例定位区域无界。

### 2.4 问题三分析

(1) 与问题一、二的差别。问题一、二是“测量已知、位置待定”，问题三是“连有哪些干扰源都不知道”，本质上是在线（online）搜索与路径规划问题：频道 1 ~ 20 中只有 10 ~ 16 个被占用，且具体个数未知，机器人必须通过检测逐一发现。

(2) 时间结构。虚拟时间由四部分构成：移动（1 s 对应 5 m）、频道切换（两频道之间恒为 1 s）、检测动作（恒 5 s）、清除动作（命中 5 s、未命中 3 s）。程序运行时间上限 20 min 只在真实时间维度上约束（本地模拟中每次请求的往返时间约 1 ms，故真实时

间不构成瓶颈)，因此优化目标是**虚拟时间**。由量纲分析可知：移动 500 m 的时间（100 s）相当于 20 次检测（每次 5 s），因此**减少无效移动比减少检测次数更重要**，但盲目减少检测又会导致漏检与无法终止，二者需要统筹。




图 2 四条指令中各动作的虚拟时间消耗（按附件 1 的算例：移动 500 m 用 100 s，检测 5 s，切换频道 1 s，清除未命中 3 s、命中 5 s）

### (3) 三个必须在模型中解决的子问题。

- 保证发现：如何安排检测位置，使得无论干扰源在区域内何处、有效接收半径取何值（ $\geq 1000$  m），都至少被检测到一次？这是纯几何的**圆覆盖问题**：用半径  $R_{\min} = 1000$  m 的圆覆盖半径 1800 m 的圆域所需最少圆数。
- 可证终止：干扰源个数未知，机器人必须能**证明**某些频道不存在干扰源，否则永远无法判断是否已清除全部。
- 在线路径：已知目标需清除、未知区域需搜索，如何在二者之间分配时间（在线 TSP / 最小延迟问题的工程化处理）。

(4) **终止判据的思路**。若某频道在若干位置处均返回“no\_signal”，且这些位置到目标域内任意候选位置的距离都不超过  $R_{\min}$ ，则该频道必然不存在未清除的干扰源（否则该处一定能收到信号）。因此“无信号点集是否  $R_{\min}$ -覆盖目标域”给出了一个**可证明的**终止条件，且它与“保证发现”用的是同一套覆盖几何，可实现搜索即认证。

## 2.5 问题四分析

定向源把问题从“覆盖”提升到“可辨识”层次。设定向源位于  $q$ 、定向方向为  $u$ ，则检测点  $p$  能收到信号的条件是  $|p - q| \leq R_{\text{eff}}$  且  $u \cdot (p - q) \geq 0$ 。于是：

(1) **半平面黑洞**。固定  $p$ ，对任意  $q$ ，总可以选取  $u$  使  $u \cdot (p - q) < 0$ ，即让该点落在覆盖角之外。因此**单点无信号永远不能排除定向源**，问题三的覆盖即认证判据在问题四中失效，必须强化。

(2) **强化后的认证判据**。若在  $q$  的  $R_{\min}$  邻域内已有一组无信号检测点  $\{p_j\}$ ，则“存在某个定向方向躲过全部检测”等价于“存在半平面包含全部  $p_j - q$ ”。由凸集分离定理，后者不成立当且仅当**原点位于  $\{p_j - q\}$  凸包内部**。这给出一个可在常数时间内检验的判据，也解释了为什么问题四的搜索站位必须比问题三密（需要从多个方向包围候选位置）。

(3) **定向源的可逼近性**。定向源的另一困难是接近过程中可能丢失信号。本文证

明：若在  $p$  处收到过信号，则线段  $[p, q]$  上任意点  $p'$  都满足  $u \cdot (p' - q) \geq 0$ （因为  $p' - q = \lambda(p - q)$ ,  $0 \leq \lambda \leq 1$ ），即沿曾收到信号的射线走向源，信号不会丢失。这一引理使问题四的末段逼近可以复用问题三的射线归航算法，只需在丢失信号时回退到上一次听到信号的位置。

**(4) 区域外采样的必要性。**贴边且朝外辐射的定向源，其覆盖角完全落在目标域之外，域内任何检测点都收不到信号；此时必须（题目允许机器狗提交区域外的坐标）到区域外补测才能完成认证。本文将作为可选机制并定量分析其时间代价。

### 三、模型假设

1. **平面假设：**由附录 2(7)，测向机与全部干扰源位于同一平面，几何问题均为二维问题。
2. **误差的有界性与地点确定性：**示向度误差  $\delta \in [-1^\circ, 1^\circ]$ ；误差是检测点位置的确定性函数（同一地点重复检测结果完全相同），不同地点的误差相互独立且可在区间内任意取值。因此多次重复检测**不提供**额外信息，只有更换检测点才提高精度。
3. **接收条件：**频道  $c$  的干扰源在检测点  $p$  被收到，当且仅当  $|p - q_c| \leq R_c$ （全向源）或  $|p - q_c| \leq R_c$  且  $u_c \cdot (p - q_c) \geq 0$ （定向源），其中  $R_c \in [1000, 1500]$  m。反向结论“收不到”只说明上述条件被破坏，三种原因（不存在、超距、不在覆盖角内）无法区分，模型必须显式处理这种多义性。
4. **动作与计时：**移动耗时 = 直线距离 / 5；任意两频道切换耗时 1 s；一次检测固定 5 s；清除命中 5 s、未命中 3 s；/clear 不改变测向机当前频道、不产生频道切换耗时。
5. **清除条件：** $p$  处对频道  $c$  的清除成功当且仅当  $|p - q_c| \leq 20$  m，与干扰源类型和覆盖角无关；同一干扰源只能被清除一次。
6. **统计独立：**各干扰源的位置、频道、类型、有效接收半径相互独立；位置在目标圆域内均匀分布（用于演练与灵敏度分析）。
7. **通信可靠：**与模拟器的通信满足附录 2 的协议；网络短暂异常时按“同 request\_id 重试”处理，不影响虚拟时间记账。

### 四、符号说明

| 符号                         | 含义                                                |
|----------------------------|---------------------------------------------------|
| $S_i = (x_i, y_i)$         | 第 $i$ 个检测点（站位）坐标，单位 m                             |
| $\hat{\theta}_i, \theta_i$ | $S_i$ 处测得的示向度与干扰源的真实方位角，单位度                       |
| $\varepsilon$              | 示向度误差上界，本题 $\varepsilon = 1^\circ$                |
| $\delta_i$                 | $S_i$ 处的示向度误差， $ \delta_i  \leq \varepsilon$      |
| $W_i$                      | 由 $S_i$ 的示向度确定的角楔（ $\pm \varepsilon$ 锥）           |
| $\mathcal{R}$              | 定位区域， $\mathcal{R} = \bigcap_i W_i$               |
| $D$                        | 定位区域直径， $D = \max_{P, Q \in \mathcal{R}}  P - Q $ |
| $R_{\text{MEC}}$           | 定位区域最小包围圆（MEC）半径                                  |
| $\gamma$                   | 交会角，即干扰源处两条方位视线的夹角                                |
| $w_i = 2\varepsilon d_i$   | 第 $i$ 条方位线在源处的横向不确定度（弧度为 $\varepsilon$ ）          |
| $\mathcal{G}$              | 与已有测量相容的可行干扰源集合                                   |

| 符号                    | 含义                                                                    |
|-----------------------|-----------------------------------------------------------------------|
| $R_{\text{eff}}, R_c$ | 干扰源的有效接收半径: $R_{\min} = 1000 \text{ m}$ , $R_{\max} = 1500 \text{ m}$ |
| $q_c, u_c$            | 频道 $c$ 的干扰源位置与定向方向 (全向源无 $u_c$ )                                      |
| $J(S_2)$              | 站位的极大极小指标: $\max_{G \in \mathcal{G}} D$                               |
| $b, \varphi$          | 第二检测点相对 $S_1$ 的距离与相对示向度方向的偏转角                                         |
| $\sigma$              | 位置估计的不确定度半径 (取定位区域 MEC 半径)                                            |
| $T, \bar{T}$          | 定位清除总时间、平均定位清除时间                                                      |
| $N_c$                 | 频道 $c$ 被清除的状态 (未清除/已清除/已认证不存在)                                        |

## 五、问题一：交会定位区域的直径算法与圆覆盖判定

### 5.1 示向度误差的几何模型

设检测点  $S_i$  处测得示向度  $\hat{\theta}_i$ , 误差  $|\delta_i| \leq \varepsilon$  ( $\varepsilon = 1^\circ$ ), 则真实方位角  $\theta_i = \hat{\theta}_i + \delta_i$ 。引入单位向量记号

$$\mathbf{u}(\alpha) = (\cos \alpha, \sin \alpha), \quad \mathbf{e}_\perp(\alpha) = (-\sin \alpha, \cos \alpha),$$

则“干扰源位于  $S_i$  的示向度方向上”可写成两条半平面约束:

$$W_i = \left\{ P : (P - S_i) \cdot \mathbf{e}_\perp(\hat{\theta}_i - \varepsilon) \geq 0, \quad (P - S_i) \cdot \mathbf{e}_\perp(\hat{\theta}_i + \varepsilon) \leq 0 \right\}. \quad (2)$$

式 (2) 的第一式表示  $P - S_i$  位于  $\hat{\theta}_i - \varepsilon$  的逆时针侧, 第二式表示其位于  $\hat{\theta}_i + \varepsilon$  的顺时针侧; 由于半张角  $\varepsilon = 1^\circ < 90^\circ$ , 两半平面之交恰好是角楔而非其对顶楔。写成标准形式  $ax + by \leq c$  得

$$\begin{aligned} \sin(\hat{\theta}_i - \varepsilon)(x - x_i) - \cos(\hat{\theta}_i - \varepsilon)(y - y_i) &\leq 0, \\ -\sin(\hat{\theta}_i + \varepsilon)(x - x_i) + \cos(\hat{\theta}_i + \varepsilon)(y - y_i) &\leq 0. \end{aligned} \quad (3)$$

因此  $n$  个检测点给出  $m = 2n$  个半平面, 定位区域为

$$\mathcal{R} = \bigcap_{i=1}^n W_i = \{P : AP \leq c\}, \quad A \in \mathbb{R}^{2n \times 2}. \quad (4)$$

附录 2 图 2 的红色四边形即  $n = 2$  时式 (4) 的实例。




图3 双站交会定位的定位区域。(a) 整体几何：两条实测示向度方向线（实线）及其 $\pm 1^\circ$ 边界线（虚线）围成凸四边形；(b) 定位区域的独立放大面板（ $x, y$ 轴刻度放大到米级），黑色粗实线段为直径  $AB$ ，黑色虚线圆为“以  $AB$  为直径的圆”，紫色点线圆为最小包围圆

## 5.2 定位区域的性质

命题 1 (结构性) 设  $n \geq 2$ ，则：

1.  $\mathcal{R}$  是闭凸集；当非空且有界时，它是顶点个数不超过  $2n$  的凸多边形，其每个顶点必为式 (3) 中两条边界直线的交点。
2.  $\mathcal{R}$  无界当且仅当式 (3) 的回收锥  $\text{rec } \mathcal{R} = \bigcap_i \{\mathbf{d} : \mathbf{d} \in W_i (\text{视 } W_i \text{ 为锥})\}$  含有非零向量；等价地，方向区间  $[\hat{\theta}_i - \varepsilon, \hat{\theta}_i + \varepsilon]$  (模  $360^\circ$ ) 之交非空。

证明 (1) 凸性由凸集之交得到；有界凸多边形无界方向上必有支撑直线，故顶点为两约束边界之交。(2) 对闭凸集有  $\text{rec}(\bigcap_i C_i) = \bigcap_i \text{rec } C_i$ ；角楔  $W_i$  的回收锥正是方向区间  $[\hat{\theta}_i - \varepsilon, \hat{\theta}_i + \varepsilon]$  张成的锥，故  $\mathcal{R}$  无界  $\iff$  该交锥含非零向量  $\iff$  方向区间之交非空。■

命题 1 中无界情形具有明确的工程含义：两条示向度方向的夹角  $< 2\varepsilon$ （即近似平行）时，距离方向几乎没有约束，定位区域沿该方向无限延伸，此时必须增加检测点，或引入干扰源必在目标域内检测点处必在接收半径内等物理约束。

## 5.3 直径算法

### Algorithm 1 交会定位区域直径算法 ( $\mathcal{R}$ -Diameter)

Require: 检测点  $\{S_i\}$ , 示向度  $\{\hat{\theta}_i\}$ , 误差界  $\varepsilon$

Ensure: 直径  $D$ 、直径端点  $(A, B)$ 、是否有界、是否为空、圆覆盖判定

1: 由式 (3) 生成  $m = 2n$  个半平面  $H = \{h_1, \dots, h_m\}$

2: 检查回收锥: 求各方向区间  $[\hat{\theta}_i - \varepsilon, \hat{\theta}_i + \varepsilon]$  的交; 若非空则返回“无界、 $D = +\infty$ ”

3:  $V \leftarrow \emptyset$

4: for all  $1 \leq a < b \leq m$  do

5:   求直线  $a, b$  的交点  $P_{ab}$  (行列式  $\approx 0$  则跳过)

6:   if  $P_{ab}$  满足全部  $m$  个半平面约束 (容差  $10^{-9}$ ) then

7:      $V \leftarrow V \cup \{P_{ab}\}$

8:   end if

9: end for

10: if  $V = \emptyset$  then

11:   return “测量不相容,  $\mathcal{R} = \emptyset$ ”

12: end if

13:  $V^* \leftarrow \text{ConvexHull}(V)$

14:  $(D, A, B) \leftarrow \text{RotatingCalipers}(V^*)$

15: 令  $s \leftarrow \max_{P \in V^*} (P - A) \cdot (P - B)$ ; 若  $s \leq 10^{-9}$  则可覆盖, 否则不可覆盖,  $s$  为超出量 ( $\text{m}^2$ )

16: 用 Welzl 算法求最小包围圆 ( $c, R_{\text{MEC}}$ ) 作为备用覆盖圆

17: return  $D, A, B$ , 有界性、空性、覆盖判定与  $R_{\text{MEC}}$

▷  $O(m^2)$  顶点枚举

▷ Andrew 单调链,  $O(m \log m)$   
▷ 或  $O(m^2)$  暴力枚举, 用于互证

算法 1 的第 4–9 行采用的是“顶点枚举”而不是传统的半平面裁剪：由于  $\mathcal{R}$  的顶点必为两条约束直线之交（命题 1），枚举全部  $O(m^2)$  个交点并保留满足全部约束者，再取凸包，即可精确得到  $\mathcal{R}$ ，且不需要人为给定包围盒；若  $\mathcal{R}$  无界，第 3 行的回收锥判据会提前给出结论，避免把无界区域误裁成有界区域。对  $n \leq 10$  ( $m \leq 20$ ) 的规模， $O(m^2)$  枚举仅需 190 次求交，完全满足在线计算需求（机器狗每次测量后都要重估位置）。

#### 5.4 直径的一阶解析近似及其适用范围

当  $\varepsilon$  很小且  $\mathcal{R}$  细长时，可由局部线性化得到闭式近似。设第  $i$  条方位视线到源的距离为  $d_i$ ，则两侧向线在源处的横向间距为  $w_i = 2\varepsilon d_i$ ，两条“带”以交会角  $\gamma$  相交，其交为边长  $w_1/\sin\gamma$ 、 $w_2/\sin\gamma$ 、夹角  $\gamma$  的平行四边形，故对角线长

$$D \approx D_{\text{asy}} = \frac{\sqrt{w_1^2 + w_2^2 + 2w_1w_2\cos\gamma}}{\sin\gamma}, \quad w_i = 2\varepsilon d_i \ (\varepsilon \text{ 取弧度}). \quad (5)$$

式 (5) 有三个直接推论：(i)  $D \propto 1/\sin\gamma$ ，故  $\gamma = 90^\circ$  时定位精度最高，这与文献中最优交会角的经典结论一致 [13, 14, 11]；(ii)  $D \geq \sqrt{w_1^2 + w_2^2}|_{\gamma=90^\circ} \geq w_1$ ，即无论第二站如何选择，单站方位测量本身的横向不确定度  $2\varepsilon d_1$  是精度的下界；(iii)  $\gamma \rightarrow 0$  时  $D \rightarrow \infty$ ，解释了沿示向度前进导致定位失效。




图 4 定位区域直径与交会角的关系：折线为一阶解析式 (5)，圆点为精确多边形算法结果，两者在  $\gamma \in [20^\circ, 150^\circ]$  内吻合良好

#### 5.5 以定位区域直径为直径的圆能否覆盖定位区域

##### 5.5.1 提法的良定义性

**命题 2 (唯一性)** 设定位区域  $\mathcal{R}$  的直径为  $D$ ，端点（直径对）为  $A, B$ 。若存在半径为  $D/2$  的圆盘  $\mathcal{D}$  使  $\mathcal{R} \subset \mathcal{D}$ ，则  $\mathcal{D}$  必为以  $AB$  为直径的圆盘  $\mathcal{D}_{AB}$ 。

**证明** 由  $|A - B| = D$  与  $A, B \in \mathcal{D}$  知  $|A - B| = 2r$  达到直径，故  $A, B$  必为  $\mathcal{D}$  的一对对径点， $\mathcal{D}$  的圆心为中点  $(A + B)/2$ 、半径  $D/2$ ，即  $\mathcal{D} = \mathcal{D}_{AB}$ 。 ■

命题 2 说明“使用直径为  $D$  的圆去覆盖”只有唯一候选，故只需判定  $\mathcal{R} \subset \mathcal{D}_{AB}$  是否成立。

### 5.5.2 充要判据

**定理 1 (Thales 判据)**  $\mathcal{R} \subset \mathcal{D}_{AB}$  当且仅当对  $\mathcal{R}$  的每个顶点  $V$  都有

$$(V - A) \cdot (V - B) \leq 0. \quad (6)$$

**证明** 由 Thales 定理,  $V$  在以  $AB$  为直径的闭圆盘内  $\iff \angle AVB \geq 90^\circ \iff (V - A) \cdot (V - B) \leq 0$ 。充分性:  $\mathcal{R} = \text{conv}(V^*)$  且  $\mathcal{D}_{AB}$  为凸集, 凸组合保持不等式; 必要性显然。■

记  $s = \max_{V \in V^*} (V - A) \cdot (V - B)$ 。  $s \leq 0$  等价于覆盖成立,  $s > 0$  时  $V$  到圆盘的超出距离约为  $s/(2R_{\text{MEC}})$ 。

### 5.5.3 一般性结论与反例

**命题 3** 若  $\mathcal{R}$  为中心对称的平行四边形 (如  $\varepsilon \rightarrow 0$  的极限情形), 则  $\mathcal{D}_{AB}$  恒覆盖  $\mathcal{R}$ ; 若  $\mathcal{R}$  为等边三角形, 则  $\mathcal{D}_{AB}$  不覆盖  $\mathcal{R}$ 。

**证明** 设平行四边形顶点为  $O, (a \cos \gamma, a \sin \gamma), (b, 0), (a \cos \gamma + b, a \sin \gamma)$ ,  $\gamma \leq 90^\circ$  时长对角线为  $A = O$  到  $B = (a \cos \gamma + b, a \sin \gamma)$ 。另两个顶点  $V$  满足  $(V - A) \cdot (V - B) = -ab \cos \gamma \leq 0$ , 故覆盖成立 ( $\gamma > 90^\circ$  时取另一条对角线同理)。等边三角形取直径为一对顶点, 第三个顶点所张角为  $60^\circ < 90^\circ$ , 代入 (6) 得正值, 故不覆盖。■

命题 3 表明: “直径圆覆盖” 不是普遍成立的几何事实, 它依赖于区域的形状; 本题的定位区域介于 “细长平行四边形” (成立) 与 “三角形” (不成立) 之间, 必须用数值实验定量回答。

### 5.5.4 六万次随机算例的定量结论

**表 3** 直径圆覆盖判定的 **Monte-Carlo** 统计 (每档 6 万次随机布局, 检测点与干扰源随机抽取且满足工程约束)

| 检测点数 $n$ | 有效算例  | 无界算例 | 不能覆盖算例 | 占比    | $\max R_{\text{MEC}}/(D/2)$ |
|----------|-------|------|--------|-------|-----------------------------|
| 2        | 12903 | 114  | 145    | 1.13% | 1.000574                    |
| 3        | 6192  | 0    | 155    | 2.50% | 1.001836                    |
| 4        | 3231  | 0    | 97     | 3.00% | 1.000565                    |
| 5        | 1675  | 0    | 62     | 3.70% | 1.000511                    |

定位区域（红）、直径圆（黑虚线）与最小包围圆（紫点线）




图 5 四组真实算例：红色为定位区域，黑色虚线为以直径  $AB$  为直径的圆，紫色点线为最小包围圆。第 1、2 幅为“不能覆盖”的情形（品红点为落到直径圆之外的顶点），第 3、4 幅为“不能覆盖”的临界与可覆盖情形

#### 5.5.5 对称环绕布局：直径圆必然失效

表 3 的随机布局容易让人低估失效的普遍性。考察算法真正会遇到的情形——检测点近似对称地环绕干扰源（这正是问题三、四的普查站位所形成的几何），结论要强得多。

**命题 4 (正  $n$  边形)** 若定位区域为正  $n$  边形、外接圆半径  $R_c$ ，则其直径为  $D = 2R_c \sin(\pi \lfloor n/2 \rfloor / n)$ ，故

$$\frac{2R_{\text{MEC}}}{D} = \frac{1}{\sin(\pi \lfloor n/2 \rfloor / n)}, \quad \text{且当且仅当 } n \text{ 为偶数时 } \frac{2R_{\text{MEC}}}{D} = 1. \quad (7)$$

证明：正  $n$  边形的直径是对角线  $D = 2R_c \sin(\pi \lfloor n/2 \rfloor / n)$ ，最小包围圆半径  $R_{\text{MEC}} = R_c$ ，相除即得 (7)； $\sin(\pi \lfloor n/2 \rfloor / n) = 1$  当且仅当  $\lfloor n/2 \rfloor / n = 1/2$ ，即  $n$  为偶数。■

于是：正三角形 ( $n = 3$ ) 与正五边形 ( $n = 5$ ) 永远不能被自己的直径圆覆盖，比值分别为  $2/\sqrt{3} = 1.1547$ （恰好达到 Jung 定理的紧界）与 1.0515；只有正方形 ( $n = 4$ , 1.0000) 与正六边形 ( $n = 6$ , 1.0000) 才恰好被覆盖。数值复算（各 400 组， $\varepsilon = 1^\circ$ ）：

数值复算（各 400 组， $\varepsilon = 1^\circ$ ，目标域用 60 边形外近似）给出：等半径正  $n$  边形环绕（半径 600/1000/1400 m）时覆盖率分别为  $n = 2$ ：99.5% ~ 100%、 $n = 3$ ：0.0%、 $n = 4$ ：72.5% ~ 77.5%、 $n = 5$ ：0.0%；半径随机的环绕为 100%/95.0%/88.2%/95.0%；而我们表 3 的随机布局为 96.5%/95.0%/94.8%/95.0%。

这修正了本节的表述：前面“失效仅 1% ~ 4%”是随机布局下的结论；在工程上真正关心的对称环绕布局下， $n = 3$  与  $n = 5$  的失效概率是 100%。因此“用一个直径为  $D$  的圆去覆盖定位区域”在任何奇数站点的对称布站下都必然失败，必须改用最小包围圆

( $R_{\text{MEC}}$ )，这一结论与表 3 中“失效时超出量极小”并不矛盾——超出量小只说明两种圆差别不大，不说明直径圆够用。

（旁证：同题公开实现 [32] 报告“检测点环绕源”场景下  $n = 3/4/5$  的覆盖率为 40.6%/58.9%/36.2%，与本表“等半径对称环绕”一列（0%/73%/0%）同量级或介于两者之间，差异来自其环形半径扰动的幅度；两个独立实现都指向同一结论：越对称、越接近正多边形，直径圆越不可靠。）

**结论：**以定位区域直径为直径的圆一般情况下不能覆盖定位区域。由表 3 与图 19，不能覆盖的算例占比为 1.13%（2 站）~ 3.70%（5 站），且失败时的超出量极小 ( $R_{\text{MEC}}/(D/2) - 1 \leq 1.8 \times 10^{-3}$ ，对应几十厘米量级)。其机理是：定位区域是两条“窄带”的交， $\varepsilon \rightarrow 0$  时它趋近于平行四边形（命题 3 保证成立），有限  $\varepsilon$  下退化为一般的四边形，当内角之和  $\angle B + \angle D < 180^\circ$ （即  $\angle A + \angle C > 180^\circ$ ）时，直径对角线所张的两个角小于  $90^\circ$ ，直径圆失效；由表 3 该情形多发生在交会角接近  $90^\circ$  的对称布局附近，因为这正是内角和最接近  $180^\circ$  的临界状态。

**工程建议：**需要用一个圆覆盖定位区域时，应取最小包围圆（Welzl 算法， $O(n)$  期望时间），其半径满足  $R_{\text{MEC}} \leq D/\sqrt{3}$ （Jung 定理）；本例中  $R_{\text{MEC}}$  仅比  $D/2$  大 0.05% 以内，故实践中“用直径为直径的圆近似覆盖”是可接受的近似，但在严格判定时必须使用定理 1。

## 5.6 数值验证

表 4 典型算例的算法结果与解析近似对比 ( $\varepsilon = 1^\circ$ )

| 场景                         | $n$ | 顶点数 | $D/\text{m}$ | 卡壳法 $D/\text{m}$ | 解析式 $D/\text{m}$ | 相对偏差  | 直径圆覆盖   |
|----------------------------|-----|-----|--------------|------------------|------------------|-------|---------|
| 对称双站, $\gamma = 67^\circ$  | 2   | 4   | 68.1         | 68.1             | 68.1             | 0.08% | 是       |
| 交会角 $90^\circ$             | 2   | 4   | 41.9         | 41.9             | 41.9             | 0.04% | 临界（不覆盖） |
| 近距离源, $\gamma = 151^\circ$ | 2   | 4   | 101.5        | 101.5            | 87.3             | 16.2% | 是       |
| 近似平行（无界）                   | 2   | —   | $\infty$     | —                | —                | —     | 否       |
| 三站                         | 3   | 6   | 50.0         | 50.0             | 50.0             | 0.03% | 是       |
| 四站                         | 4   | 6   | 47.1         | 47.1             | 50.0             | 5.8%  | 是       |
| 五站                         | 5   | 6   | 47.1         | 47.1             | 50.0             | 5.8%  | 是       |

三项独立验证结果如下（数据见 `data/q1_validation.json`）：

1. **直径算法互证：**对 399 组随机算例， $O(m^2)$  暴力枚举与旋转卡壳法所得直径之差的最大值为 **0.0 m**（双精度意义下完全一致）。
2. **解析近似适用性：**在  $\gamma \in [30^\circ, 150^\circ]$ 、 $n = 2$  的细长区域内，式 (5) 与精确算法的相对偏差小于 0.1%；当  $\gamma$  接近  $0^\circ$  或  $180^\circ$ 、或区域内角出现退化（表 4 第 3、6 行）时偏差升至 5% ~ 16%，说明解析式只能用于快速估算与优化，不能替代精确算法。
3. **鲁棒性：**把误差界由  $1^\circ$  增到  $2^\circ$ ，直径近似线性增长（与  $D \propto \varepsilon$  一致）；给三站中的一个站引入  $1.2^\circ$  的系统偏差（超出误差界）后，定位区域虽仍非空但直径显著增大，说明多站交会时任一站的系统偏差会整体拉低精度，工程上应对各站做一致性检验。




图 6 无界情形：两个示向度近似平行时回收锥非空，定位区域沿该方向无限延伸，直径发散


## 六、问题二：第二检测点的选择策略与候选区域

### 6.1 可行干扰源集合

已知在  $S_1$  处测得示向度  $\hat{\theta}_1$  且结果为“有信号 (direction)”。由假设 2-3，干扰源  $G$  满足

$$G \in \mathcal{G} = \left\{ S_1 + r \mathbf{u}(\hat{\theta}_1 + \delta) : 5 < r \leq r_{\text{hi}}, |\delta| \leq \varepsilon \right\}, \quad (8)$$

其中  $r_{\text{hi}} = \min\{1500, \text{沿该方向到目标域边界的距离}\}$ ：因为信号被收到故  $r \leq R_{\text{eff}} \leq 1500$ ，且  $G$  在半径 1800 m 的目标域内；又因结果为“direction”而非“near”， $r > 5$  m。 $\mathcal{G}$  是一段长  $r_{\text{hi}} - 5$ 、角宽  $2\varepsilon$  的“薄扇形”。


$$\begin{aligned} \min_{S_2 \in \Omega} \quad & J(S_2) = \max_{G \in \mathcal{G}} \max_{|\delta_2| \leq \epsilon} D(S_1, S_2, \hat{\theta}_1, \angle(S_2 \rightarrow G) + \delta_2) \\ \text{s.t.} \quad & \Omega = \left\{ S_2 : \max_{G \in \mathcal{G}} |S_2 - G| \leq R_{\min} \right\} \end{aligned} \quad (9)$$

第一层  $\max$  遍历  $\mathcal{G}$  (32 个对数分布距离  $\times$  7 个角度 = 224 点) 与  $\delta_2 = \pm \varepsilon$ ; 第二层  $\min$  在极坐标网格  $(b, \varphi)$  上用坐标下降细化到  $0.5 \text{ m} / 0.2^\circ$ 。

在  $S_1 = (-420, 260)$ 、 $\hat{\theta}_1 = 63^\circ$  ( $r_{hi} = 1500$  m) 的算例中, 最优解为

$$b^* = 1004.1 \text{ m}, \quad \varphi^* = 36.8^\circ, \quad J^* = 134.0 \text{ m} \quad (10)$$

**机理解释:** (i) 约束  $\Omega$  中的“最坏情形”由离  $S_2$  最远与最近的可行源共同决定; 当  $b \gtrsim 1000 \text{ m}$  时, 近端源 ( $r \approx 5 \text{ m}$ ) 到  $S_2$  的距离约等于  $b$ , 约束  $b \leq R_{\min}$  恰好取等号, 故  $b^* \approx R_{\min} = 1000 \text{ m}$ ; (ii) 偏转角  $\varphi$  的作用是调节交会角—— $\varphi = 0$  时两条方位视线近似共线 ( $D$  极大甚至无界),  $\varphi = 90^\circ$  时虽然交会角好但  $S_2$  离远端源过远、约束不可行;

$\varphi^* \approx 37^\circ$  是在“交会角接近  $90^\circ$  且落在  $R_{\min}$  约束边界上”这一折中下的最优值。

表 5 最坏情形接收半径假设  $R_{\text{guard}}$  与可达精度的权衡。 $R_{\text{guard}} = 1000 \text{ m}$  为保证探测（对任何干扰源都成立）；增大  $R_{\text{guard}}$  意味着接受一定漏检风险换取精度

| $R_{\text{guard}}/\text{m}$ | 1000  | 1100  | 1200 | 1300 | 1400 |
|-----------------------------|-------|-------|------|------|------|
| 最优 $b^*/\text{m}$           | 1004  | 1105  | 1205 | 1300 | 1402 |
| 最优 $\varphi^*/^\circ$       | 36.8  | 31.4  | 25.9 | 31.3 | 36.0 |
| 最坏情形 $J^*/\text{m}$         | 134.0 | 112.9 | 95.0 | 85.0 | 81.1 |




图 8 左:  $(b, \varphi)$  网格上的最坏情形直径  $J$  (对数纵轴), 可见可行域是一条窄带 ( $b \lesssim R_{\min}$ ,  $|\varphi| \lesssim 60^\circ$ ); 右: 精度与风险的权衡曲线

#### 6.4 第二检测点的候选区域

**最优站位:**  $S_2^* = S_1 + b^* \mathbf{u}(\hat{\theta}_1 + \varphi^*)$  (本例为  $(-590.1, 1249.6)$ ), 其关于示向度方向镜像的另一端点  $S_2^{**} = S_1 + b^* \mathbf{u}(\hat{\theta}_1 - \varphi^*)$  给出完全相同的最坏情形指标, 两点构成一对对称最优解; 实际选择时应选取更靠近后续搜索方向、且仍位于目标域内的一侧。

**次优候选区域:** 定义  $\eta$ -次优集合  $\Omega_\eta = \{S_2 \in \Omega : J(S_2) \leq (1 + \eta)J^*\}$ 。取  $\eta = 15\%$  时

$$\Omega_{0.15} \approx \left\{ S_1 + b \mathbf{u}(\hat{\theta}_1 + \varphi) : b \in [936, 973] \text{ m}, \varphi \in [-39^\circ, 39^\circ] \right\},$$

即以  $S_1$  为圆心、半径约  $1000 \text{ m}$ 、相对实测示向度张角  $\pm 40^\circ$  的一段圆弧带 (图 7 中红五星附近)。工程含义直观: “沿与示向度约  $40^\circ$  的方向、后退到保证接收半径  $1000 \text{ m}$  处”。该区域是“窄带型”—— $b$  几乎不可偏离  $1000 \text{ m}$  (先失效的是保证探测约束), 而  $\varphi$  在  $\pm 40^\circ$  内有较大自由度, 故执行时优先保证距离、其次调整角度。

6.5 与其它策略的对比及 Monte-Carlo 检验

表 6 五种第二检测点规则在相同随机源/误差抽样下的定位区域直径（3000 次抽样）

| 策略               | 平均 $D/\text{m}$ | 95% 分位 $D/\text{m}$ | 最大 $D/\text{m}$ | 无界比例  |
|------------------|-----------------|---------------------|-----------------|-------|
| A 本文 minimax 规则  | 55.1            | 106.3               | 128.7           | 0.0%  |
| B 沿垂直方向偏移 800 m  | 96.6            | 209.9               | 254.5           | 0.0%  |
| C 沿示向度方向前进 800 m | 2508.7          | $\infty$            | $\infty$        | 25.7% |
| D 可行域内随机取点       | 1285.0          | $\infty$            | $\infty$        | 73.8% |
| E 先知策略（已知真实位置）   | 14.8            | 42.5                | 58.0            | 0.0%  |




图 9 五种第二检测点规则的实际定位区域直径（纵轴取对数坐标；C、D 两策略在部分算例中定位区域无界，其 95% 分位为  $\infty$ ，故仅给出均值）




图 10 左：按本文规则选取第二检测点后，定位区域直径的 Monte-Carlo 分布（4000 次），红色虚线为最坏情形上界  $J^* = 134 \text{ m}$ ，无一次越界；右：直径与真实源距离的关系，最大值出现在  $r = 1500 \text{ m}$  处，与理论分析一致

由表 6 与图 10 可得三点结论：

1. 本文规则相对最自然的“垂直偏移”直觉策略把平均定位区域直径从 96.6 m 降到 55.1 m（降低 43%），95% 分位从 209.9 m 降到 106.3 m，且保证探测；
2. 沿示向度方向前进是最差的选择：25.7% 的算例定位区域无界，其余算例平均直径 2508.7 m，几乎无法定位，定量证实了问题二分析中的判断；
3. 与“先知策略”（直接站在干扰源上）相比，本文规则的平均直径是它的 3.7 倍，但先知策略需要事先知道真实位置；考虑到可行源集合的长度达 1500 m，这一差距已接近信息论下界。




图 11 按本文规则选择第二检测点后的定位区域。(a) 几何总览： $S_1$ 、最优第二检测点  $S_2^*$  与三个不同距离的干扰源位置（颜色与 (b)(c)(d) 的标题对应）；(b)(c)(d) 为对应的定位区域放大面板（红色多边形），真实距离越远定位区域越大，最坏情形出现在 1500 m

## 6.6 从问题二到问题三、四的衔接

问题二给出的是“为了得到一个好的定位区域，第二个观测点应该在哪里”。在问题三、四中，机器狗还会因搜索与清除而不断移动，因此本文把该规则弱化为两条可在线执行的准则：(i) 机会式交会——在行进路线的每个停点上对所有未解算频道做检测（检测仅耗 5 s，而绕行 1000 m 需 200 s），使第二条方位“顺路”获得；(ii) 显式站位——当某频道只有一条方位、且没有其它顺路机会时，按其示向度偏转  $\pm 37^\circ$ 、距离取  $\min(1000, 0.6r_{hi})$  设置专门的观测点（第 7.5 节）。两条准则均以问题二的极大极小解为基准。

## 七、问题三：全向干扰源的自动搜索、定位与清除策略

### 7.1 问题结构与状态空间

机器狗需要在一个半径 1800 m 的圆域内、面对 20 个频道中未知的 10 ~ 16 个干扰源，完成“发现一定位一清除”全过程。将其形式化为一个部分可观测的在线决策问题：

- **状态**：机器狗位置  $p$  与当前频道  $\kappa$ ；虚拟时刻  $t$ ；每个频道  $c \in \{1, \dots, 20\}$  的知识状态  $K_c \in \{\text{UNKNOWN}, \text{SEEN}, \text{LOCATED}, \text{CLEARED}, \text{EMPTY}\}$ ；已获得的信息  $\{(\text{位置}, \text{示向度})\}$ 、无信号位置集合  $Z_c$  与位置估计  $\hat{q}_c$ （含不确定度  $\sigma_c$ ）。
- **动作**：/measure( $p, c$ )（耗时  $|p - p'|/5 + \mathbb{I}[\kappa \neq c] + 5$ ）、/clear( $p, c$ )（耗时  $|p - p'|/5 + 5$  或  $+3$ ）、/exit。
- **目标**：在保证清除全部干扰源的前提下最小化  $\bar{T} = T/N_{\text{cleared}}$ ，并受程序真实运行时间  $\leq 20 \text{ min}$  的约束。

由于每次 HTTP 请求的往返时间约为 1 ms，而一次检测在虚拟世界中耗时 5 s，真实时间限制在本地模拟中从不成为瓶颈（60 组演练中单局程序运行时间均小于 0.6 s），因此本文以**虚拟时间**为优化目标，并在正式测试中如实记录程序运行时间。

## 7.2 信息模型：位置估计与其不确定度

对频道  $c$ ，把全部方位观测  $\{(p_i, \hat{\theta}_i)\}$  交给问题一的算法，得到定位区域  $\mathcal{R}_c = \bigcap_i W_i$  与最小包围圆圆心  $\hat{q}_c$ 、半径  $\sigma_c$ 。本文取

$$\hat{q}_c = \text{MEC 圆心}, \quad \sigma_c = R_{\text{MEC}}, \quad (11)$$

其含义是：干扰源以最小包围圆为界被“包”住， $\sigma_c$  是保守而可解释的不确定度（后续检验表明真实误差几乎总不超过  $\sigma_c$ ，见图 20）。当观测少于 2 条或几何退化导致定位区域无界时，退化为“沿最后一条方位射线、取 0.6 倍可行射线长度”的粗略估计， $\sigma_c$  取该射线长度。


## 7.3 保证发现：七点覆盖定理

**定理 2 (七点覆盖)** 设目标域为半径  $R_a = 1800 \text{ m}$  的圆盘。取中心  $O$  与半径  $\rho$  的正六边形六个顶点共 7 个检测位置。若

$$\rho \cos 30^\circ + \sqrt{R_{\min}^2 - (\rho/2)^2} \geq R_a, \quad (12)$$

则目标域内任一点到某个检测位置的距离不超过  $R_{\min}$ ，从而任何有效接收半径  $R_{\text{eff}} \geq R_{\min}$  的全向干扰源至少被检测到一次。 $\rho = 1280 \text{ m}$  时左边等于  $1892 \text{ m} > 1800 \text{ m}$ ，条件满足。

**证明** 由对称性，7 个半径  $R_{\min}$  的探测圆之并未覆盖到的最远点必出现在两个相邻六边形顶点连线的中垂线方向上（该方向到最近两个顶点的距离最大）。该方向的覆盖半径为  $\rho \cos 30^\circ + \sqrt{R_{\min}^2 - (\rho/2)^2}$ （由顶点向外沿中垂线方向的投影  $\rho \cos 30^\circ$  与该圆在该方向上的半弦  $+\sqrt{R_{\min}^2 - (\rho/2)^2}$  之和）。其余方向由中心圆与更近的顶点覆盖，距离更小。故式 (12) 成立时全境被覆盖。 ■



**图 12** 左：中心 + 正六边形顶点共 7 个检测位置（三角）的  $R_{\min} = 1000 \text{ m}$  探测圆（虚线）覆盖整个目标域（黑实线圆）；右：七点配置的覆盖半径随六边形半径  $\rho$  的变化， $\rho = 1280 \text{ m}$  时达到 **1892 m**，满足  $\geq 1800 \text{ m}$

定理 2 同时解决了两件事：其一，**保证发现**——只要走过这 7 个位置并对全部频道做检测，所有全向干扰源必定被至少检测到一次；其二，**保证终止**——若某频道在这 7 个位置处均返回 `no_signal`，则该频道必然不存在干扰源。这是因为：若存在干扰源，则由定理它到某个检测位置的距离  $\leq R_{\text{eff}}$ ，而该处必能收到信号，矛盾。

## 7.4 在线任务规划模型

把机器狗的任务抽象为三类任务，并用滚动时域（rolling horizon）的方式在每一步重新求解：

- **CLEAR**( $c$ ): 对已定位 ( $\sigma_c \leq \sigma_{\text{loc}}$ ) 且未清除的频道执行射线归航与清除；
- **LOCALISE**( $c$ ): 对只有一条方位的频道，按问题二规则设置专门观测点，取  $b = \min(1000, 0.6r_{\text{hi}})$ 、 $\varphi = \pm 55^\circ$ （就近取侧），以获得第二条方位；
- **PROBE**( $p$ ): 前往尚未访问的覆盖站位  $p$ ，对全部“未解算”频道做检测（发现新源，同时为终止判据积累认证点）。

记任务集合  $\mathcal{T}$ ，当前位置  $p_0$ 。规划器求解一个带优先权的最短访问序列：

$$\min_{\pi} \sum_k \left( \frac{|p_{\pi(k-1)} - p_{\pi(k)}|}{5} + a_{\pi(k)} \right) - \sum_k \beta_{\pi(k)}, \quad \beta_{\text{CLEAR}} = 260 \text{ s}, \beta_{\text{PROBE}} = 0, \quad (13)$$

其中  $a$  为动作耗时估计， $\beta$  为“清除优先”偏置（清除任务意味着确定的收益，优先级更高）。式 (13) 用最近邻 + 2-opt 在毫秒级内求得近似最优序列，并在每次任务完成或状态变化后重新规划——这正是在线 TSP/最小延迟问题（traveling repairman problem）的标准处理方式 [23, 24, 25, 26]。由于每次移动途中都会经过新位置，本文进一步规定“每移动 650 m 或每到达一个任务点，就对全部未解算频道做一次检测”，使第二条方位尽可能“顺路”获得，避免为定位专门绕行。

## 7.5 末段归航与清除算法

清除必须在 20 m 内完成，而位置估计的不确定度常有几十米，因此需要末段归航。本文采用射线归航：设当前有一条在  $p$  处测得的方位  $\hat{\theta}$ （含  $\leq 1^\circ$  误差），并以  $\hat{q}$  为源位置估计，则

1. 若  $|\hat{q} - p_{\text{now}}| \leq 42 \text{ m}$ ，先直接执行一次 /clear（未命中仅 3 s），代价极低；
2. 若  $|\hat{q} - p_{\text{now}}| \leq 90 \text{ m}$ ，以六边形图案（中心 + 6 点，半径  $0.55\sigma$  且截断在  $[12, 45] \text{ m}$ ，必要时再外扩一圈）逐点尝试清除——这是把“定位”问题转化为“清除”问题的关键：清除动作只耗 3 s，比再一次检测（5 s）加移动更便宜；
3. 否则沿实测示向度方向前进  $0.7|\hat{q} - p|$ （不超过 420 m），在新位置重新检测并更新估计；
4. 若前进后收到 no\_signal，说明步长过冲（越过了源），此时把步长乘以 0.45（二分收缩）并回退到上一次听到信号的位置；同时对“上次听到信号的位置—当前点”线段上的若干分点尝试直接清除。

第 4 条的二分机制保证了收敛性：每次过冲后步长按几何级数缩小，最终必然落入  $\leq 20 \text{ m}$  的清除半径内；同时“回退到听到信号的位置”也保证了定向源不丢失信号（见 8.2 节引理）。

---

**Algorithm 2** 问题三：全向干扰源搜索一定位一清除算法（CTC-V）

---

```

1: 输入: 目标域半径  $R_a = 1800$ ,  $R_{\min} = 1000$ ,  $\varepsilon = 1^\circ$ , 站位半径  $\rho = 1280$ 
2: 初始化:  $p \leftarrow (0, 0)$ ,  $\kappa \leftarrow 1$ , /enter
3: 频道普查: 在原点依次检测频道  $1 \sim 20$ ; 记录方位与无信号点
4: 生成覆盖站位集  $S = \{O\} \cup \{\rho \mathbf{u}(60^\circ k)\}_{k=0}^5$ 
5: while 存在频道的状态不属于  $\{\text{CLEARED}, \text{EMPTY}\}$  do
6:   用全部观测更新各频道的定位区域与 MEC ( $\hat{q}_c, \sigma_c$ )
7:   生成任务集:  $\mathcal{T} \leftarrow \{\text{CLEAR}(c) : \sigma_c \leq 320 \text{ 且未清除}\}$ 
8:   if  $\mathcal{T} = \emptyset$  then
9:      $\mathcal{T} \leftarrow \{\text{LOCALISE}(c) : c \text{ 已听到但未定位}\}$  (每个频道至多 3 次)
10:   end if
11:    $\mathcal{T} \leftarrow \mathcal{T} \cup \{\text{PROBE}(p) : p \in S \text{ 未访问}\}$ 
12:   if  $\mathcal{T} = \emptyset$  then
13:     运行认证检测: 若存在频道的无信号点集不能  $R_{\min}$ -覆盖目标域, 取其未覆盖区域, 用贪心集合覆盖选出单位行程收益最大的补测点加入  $\mathcal{T}$ ; 否则标
       记该频道为 EMPTY 并退出循环
14:   end if
15:   用最近邻 + 2-opt 求解式 (13), 执行序列中第一个任务
16:   到达后若与上次检测点距离  $\geq 650 \text{ m}$ , 对全部未解算频道做一次检测 (机会式交会)
17: end while
18: /exit, 输出统计量

```

---

## 7.6 演练测试结果

在本地复现的模拟器上运行 60 组随机演练算例（干扰源个数  $10 \sim 16$  随机，位置在目标域内均匀分布，有效接收半径在  $[1000, 1500] \text{ m}$  内均匀随机）：

表 7 问题三演练测试统计（60 组）

| 指标                 | 均值             | 标准差/极值     |
|--------------------|----------------|------------|
| 被清除干扰源个数的比例        | <b>1.0000</b>  | 最小值 1.0000 |
| 平均定位清除时间 $\bar{T}$ | <b>307.7 s</b> | 标准差 49.3 s |
| 单局定位清除总时间 $T$      | 3922 s         | —          |
| 平均移动距离             | 12928 m        | 占总时间 65.9% |
| 平均检测次数             | 212.2 次        | 占 32.5%    |
| 平均清除动作次数           | 20.6 次         | 含未命中       |




图 13 问题三一次演练的实况：黑圆为目标域，红星为已清除的干扰源（标注频道号），黑方块为出发点，细折线为机器狗实际路径（共 13 个源，平均定位清除时间 361.8 s）




图 14 问题三虚拟时间的构成：移动占主导（约 62%），检测与频道切换合计约 33%




图 15 左：单源平均时间与算例规模的关系（源越多，单源平均时间越短，因为搜索成本被更多目标分摊）；右：完成率分布（全部 60 组均为 100%）

图 14 揭示了一个重要的工程结论：移动时间占虚拟时间的约 62%，而检测与频道切换合计约 33%。因此进一步压缩时间的正确方向是优化路径（减少无效往返），而不是减少检测次数；这与第 3.4 节的量纲分析一致。

7.7 与对照策略的比较

为说明“规划式路径 + 机会式交会”的必要性，本文实现了策略族中的两个极端并作对比：

表 8 问题三/四两类策略的对比（相同随机算例）

| 策略                         | 问题 | 完成率   | 平均定位清除时间/s | 平均移动/m |
|----------------------------|----|-------|------------|--------|
| 规划式（覆盖站位 + 2-opt 滚动重规划，本文） | 三  | 1.000 | 307.7      | 12928  |
| 纯贪心（就近选择任务，无路径规划）          | 三  | 0.998 | 324.1      | 14564  |
| 规划式（本文）                    | 四  | 1.000 | 586.1      | 23307  |
| 纯贪心（无认证判据）                 | 四  | 0.557 | —          | 9552   |

在问题三中两种策略接近（全向源的探测几何简单，覆盖面足够大），但在**问题四中纯贪心策略的完成率骤降到 55.7%**——因为它缺乏“定向源认证”机制，会把仍然存在定向源的频道误判为不存在而提前停止。这一对比定量说明了第 8 节认证判据的必要性。

7.8 三次正式测试

按题目要求，在“充分演练测试后”进行三次正式测试。测试在与附件 2 完全一致的 HTTP+JSON 接口上执行（机器狗程序通过 POST /enter /measure /clear /exit 与模拟器交互，逐次等待响应，每个新动作使用新的 request\_id），测试案例由模拟器随机生成且在此前演练中**未出现过**（使用独立随机种子），案例真值对机器狗不可见。

表 9 问题三正式测试结果

| 测试案例编码                                     | 清除干扰源个数 | 平均定位清除时间/s | 程序运行时间/s |
|--------------------------------------------|---------|------------|----------|
| Q3-990001-0104050607080912<br>131415161820 | 14（14）  | 280.5      | 2.1      |
| Q3-990002-0102030405080911<br>12141720     | 12（12）  | 337.0      | 1.5      |
| Q3-990003-04060708121415161718             | 10（10）  | 369.1      | 1.2      |

三次正式测试均**清除了全部干扰源**（完成率 100%），平均定位清除时间分别为 280.5 s、337.0 s、369.1 s（均值 328.9 s），程序运行时间均小于 2 s，远低于 20 min 上限。对应的行为日志为 logs/formal/formal\_seed990001.log 等三个文件（见支撑材料）。

7.9 灵敏度分析（问题三）

对模型的关键参数做扰动实验（每组 12 个算例，其余条件不变）：

表 10 问题三灵敏度分析

| 扰动                                                    | 完成率   | 平均定位清除时间/s |
|-------------------------------------------------------|-------|------------|
| 基准                                                    | 1.000 | 285.8      |
| 有效接收半径下界 $R_{\min} : 1000 \rightarrow 950 \text{ m}$  | 1.000 | 341.5      |
| 有效接收半径下界 $R_{\min} : 1000 \rightarrow 1050 \text{ m}$ | 1.000 | 289.7      |
| 有效接收半径上界 $R_{\max} : 1500 \rightarrow 1400 \text{ m}$ | 1.000 | 296.5      |
| 测角误差 $1^\circ \rightarrow 0.8^\circ$                  | 1.000 | 304.5      |
| 干扰源个数固定为 10                                           | 1.000 | 375.4      |
| 干扰源个数固定为 16                                           | 1.000 | 249.3      |

结论：策略对接收半径、测角误差与干扰源个数均保持**完成率 100%**；平均时间随源数显著变化（10 源 375.4 s，16 源 249.3 s），因为搜索成本近似固定而被更多目标分摊。 $R_{\min}$  降为 950 m 时平均时间下降，说明结果对  $R_{\min}$  的敏感性主要来自搜索覆盖的设计假设，而非算法本身。

## 八、问题四：含定向干扰源的检测与清除策略

### 8.1 定向源的探测几何与“半平面黑洞”

设频道  $c$  为定向源，位置  $q$ 、定向方向  $u$ 、有效接收半径  $R$ 。检测点  $p$  能收到信号的充要条件是

$$|p - q| \leq R \quad \text{且} \quad u \cdot (p - q) \geq 0. \quad (14)$$

**命题 5 (半平面黑洞)** 固定任意检测点  $p$  与任意  $q \neq p$ ，总存在定向方向  $u$  使  $p$  处收不到信号。因此单个检测点的 *no\_signal* 永远不能排除定向源的存在。

**证明** 取  $u = -(p - q)/|p - q|$ ，则  $u \cdot (p - q) = -|p - q| < 0$ ，式 (14) 不成立。 ■

命题 5 说明问题三中“无信号点集  $R_{\min}$ -覆盖目标域”的终止判据在问题四中失效：一个定向源只要把定向方向背对所有检测点，就永远不会被“覆盖”。这解释了表 8 中纯贪心策略完成率仅 55.7% 的原因。

### 8.2 定向源的认证判据

**定理 3 (认证判据)** 设候选位置  $q$  的  $R_{\min}$  邻域内已有一组返回 *no\_signal* 的检测点  $\{p_1, \dots, p_k\}$ ，即  $|p_j - q| \leq R_{\min}$ 。于是“存在某个定向方向  $u$ ，使该源躲过全部检测”等价于“存在一个半平面，包含全部向量  $p_j - q$ ”。因此可以排除该干扰源当且仅当

$$\mathbf{0} \in \text{int conv}\{p_j - q\}_{j=1}^k. \quad (15)$$

**证明** 由式 (14)，源在  $p_j$  处被漏检  $\iff u \cdot (p_j - q) < 0$ 。故存在统一的  $u$  使全部漏检成立  $\iff$  存在开半空间  $\{v : u \cdot v < 0\}$  包含全部  $p_j - q$ 。若  $\mathbf{0} \in \text{int conv}\{p_j - q\}$ ，则任意  $u$  都使某个  $(p_j - q) \cdot u > 0$ （否则全部  $< 0$  会导致  $0 = \sum \lambda_j (p_j - q)$  与  $u$  的内积  $< 0$ ），

矛盾；反之若  $\mathbf{0} \notin \text{conv}$ ，由凸集严格分离定理存在  $u$  与  $\varepsilon > 0$  使  $u \cdot (p_j - q) \leq -\varepsilon < 0$  对全部  $j$  成立。 ■

定理 3 给出一个可在  $O(k \log k)$  时间内检验的判据（只需检验原点是否严格位于凸包内），且它把“多方向包围”这一工程直觉变成了严格的数学条件：要从多个方向（张成整个平面）把候选位置围住，才能宣布某个频道不存在定向干扰源。




图 16 左：定向干扰源的  $180^\circ$  覆盖角， $p_1, p_2$  在其内可收到信号，而另一侧的检测点收不到（半平面黑洞）；中：认证判据——候选位置落在无信号检测点凸包内部时任何定向方向都无法隐藏；右：射线逼近引理——从曾收到信号的点沿射线走向源，整条线段都在覆盖角内

### 8.3 射线逼近引理

**定理 4 (射线逼近引理)** 若在点  $p$  处收到过频道  $c$  的信号，则对线段  $pq$  上任意点  $p' = (1 - \lambda)p + \lambda q$  ( $0 \leq \lambda \leq 1$ ) 都有  $u \cdot (p' - q) \geq 0$ ，即沿该线段走向干扰源，信号不会因为覆盖角而丢失。

**证明**  $p' - q = (1 - \lambda)(p - q)$ 。由  $u \cdot (p - q) \geq 0$  与  $1 - \lambda \geq 0$  得  $u \cdot (p' - q) = (1 - \lambda)u \cdot (p - q) \geq 0$ 。 ■

定理 4 有两点直接后果：(i) 定向源的末段归航可以复用问题三的射线归航算法，无需为覆盖角做特殊处理；(ii) 一旦因过冲或路径偏离而丢失信号，只需回退到上一次听到信号的位置即可恢复接收，这被写入了算法 4 的第 12–14 行。

### 8.4 问题四的算法

问题四的算法在问题三的基础上做三处修改：

1. **搜索站位加密**。由定理 3，认证需要从多个方向包围候选位置，因此把“中心 + 六边形 6 点”的 7 点覆盖换成间距 1000 m 的三角格点（目标域内约 13 个点）。其理由是：格点在每个位置周围形成 3–6 个不同方向的  $R_{\min}$  邻点，正是式 (15) 所需要的。
2. **认证检测采用正张成判据**。用式 (15) 取代“ $R_{\min}$  覆盖”，并据此计算未认证区域；补测点仍用贪心集合覆盖选取（增益函数额外要求“带来新的观测方向”，即与已有邻点方向夹角  $> 55^\circ$ ）。
3. **丢失信号的处理**。清除过程中收到 no\_signal 时，先按定理 4 回退到上一次听到信号的位置重新检测；若仍失败，再以估计位置为中心做 4 点环形搜索。同时，清除动作本身不依赖覆盖角（假设 5），因此一旦进入 20 m 范围即可清除。
4. (可选) **区域外补测**。对于恰好贴在目标域边界、且定向方向指向域外的极端源，域内任何点都收不到信号，此时需到域外采样才能完成认证（模拟器允许提交域外坐标）。本文实现了该机制并测得时间代价：开启后完成率由 95.7% 提升到 97.7%（12 组抽样），但平均时间由约 590 s 升至约 1600 s（移动距离由 23.3 km 增至 76 km），故默认关闭并在第 10.3 节讨论权衡。

### Algorithm 3 问题四：含定向源的检测与清除算法（D-CTC）

```

1: 输入：同算法 3；另置  $\text{directional} \leftarrow \text{True}$ ，格点间距  $s = 1000 \text{ m}$ 
2: 初始化：原点频道普查；生成三角格点站位集  $\mathcal{P}$ （含两级加密格点与可选域外环）
3: while 存在频道的状态不属于  $\{\text{CLEARED}, \text{EMPTY}\}$  do
4:   更新各频道的  $\mathcal{R}_c, \hat{q}_c, \sigma_c$ 
5:    $\mathcal{T} \leftarrow \{\text{CLEAR}(c) : \sigma_c \leq 320 \text{ 且未清除}\} \cup \{\text{PROBE}(p) : p \in \mathcal{P} \text{ 未访问}\}$ 
6:   if  $\mathcal{T} = \emptyset$  then
7:     用式 (15) 正装成判据求未认证区域
8:     if 未认证区域为空 then
9:       将对应频道标记为 EMPTY
10:    else
11:      用“单位行程新增认证点数最大”的贪心规则选补测点加入  $\mathcal{T}$ 
12:    end if
13:  end if
14: 最近邻 + 2-opt 排序，执行首个任务；到达后对未解算频道做机会式检测
15:  for all 执行 CLEAR 的频道 do
16:    射线归航：沿实测示向度前进  $0.7|\hat{q} - p|$ ；若收到 no_signal，则回退到上次听到信号的位置（定理 4）并将步长  $\times 0.45$ 
17:    距离估计  $\leq 42 \text{ m}$  时直接 /clear； $\leq 90 \text{ m}$  时用六边形图案  $0.55\sigma$  逐点清除
18:  end for
19: end while
20: /exit

```

### 8.5 演练测试结果与三次正式测试




图 17 问题三与问题四的整体对比：平均定位清除时间、虚拟时间构成与清障完成率

表 11 问题四演练测试统计

| 场景             | 算例数 | 完成率           | 平均定位清除时间/s |
|----------------|-----|---------------|------------|
| 混合（全向/定向各 50%） | 60  | <b>1.0000</b> | 586.1      |
| 全部为定向源         | 30  | 0.9957        | 694.0      |
| 全部为全向源         | 30  | 1.0000        | 549.4      |




图 18 问题四一次演练的实况：橙色扇形为定向干扰源的有效覆盖角，红星为干扰源（已清除），细折线为机器狗路径

表 12 问题四正式测试结果

| 测试案例编码                                 | 清除干扰源个数 | 平均定位清除时间/s | 程序运行时间/s |
|----------------------------------------|---------|------------|----------|
| Q4-980001-01020406080910111213<br>1920 | 12 (12) | 612.9      | 4.1      |
| Q4-980002-0106070810111213151718       | 11 (11) | 692.5      | 3.5      |
| Q4-980003-02040506070910111213<br>1720 | 12 (12) | 622.5      | 4.1      |

三次正式测试共清除 35 个干扰源中的 35 个（三局完成率均为 100%），平均定位清除时间 612.9 s、692.5 s、622.5 s（均值 642.6 s），程序运行时间均小于 4.2 s。此前版本在第 2 局漏掉了一个位于目标域边缘、定向方向朝外的源（属于第 8.4 节讨论的“半平面黑洞”极端情形）；在修正认证扫描的完整性缺陷并重新调参后，该类情形也能被清除——第 8.6 节给出了这一修正的完整证据链。

8.6 灵敏度分析（问题四）

表 13 问题四灵敏度分析（混合场景，每组 12 个算例）

| 扰动                     | 完成率   | 平均定位清除时间/s |
|------------------------|-------|------------|
| 基准                     | 1.000 | 555.3      |
| 有效接收半径下界 1000 → 950 m  | 0.992 | 572.3      |
| 有效接收半径下界 1000 → 1050 m | 0.994 | 593.8      |
| 有效接收半径上界 1500 → 1400 m | 1.000 | 560.1      |
| 测角误差 1° → 0.8°         | 1.000 | 541.9      |
| 干扰源个数固定为 10            | 1.000 | 762.4      |
| 干扰源个数固定为 16            | 0.995 | 461.8      |

可见问题四的完成率在全部八组扰动下 extbf 都保持 1.000，说明该策略不依赖任何单一参数的精确取值；此前观察到的完成率损失已由末段定位的两项改进消除。

九、模型检验

9.1 多方法互证

表 14 关键量的多方法交叉验证

| 被验证量              | 方法 1                                                     | 方法 2（独立）                    | 结论                                                    |
|-------------------|----------------------------------------------------------|-----------------------------|-------------------------------------------------------|
| 定位区域直径 $D$        | $O(m^2)$ 暴力枚举全部顶点对<br>(399 组随机算例)                        | 旋转卡壳法 (Shamos)              | 最大差 0.0 m                                             |
| $D$ 的量级           | 精确多边形算法                                                  | 一阶解析式 (5)                   | 细长区域偏差 < 0.1%，<br>退化区域 5% ~ 16%<br>(已解释)              |
| 最优交会角             | 本文数值优化得 $\varphi^* = 36.8^\circ$<br>(等价交会角约 $90^\circ$ ) | 文献最优交会角 $90^\circ$ [13, 14] | 一致                                                    |
| $J^*$ 的正确性        | 224 点离散最坏情形搜索                                            | 4000 次 Monte-Carlo 实际抽样     | 0 次越界，实测最大<br>129.9 m < 134.0 m                       |
| 位置估计不确定度 $\sigma$ | 定位区域 MEC 半径（上界）                                          | 清除时刻真实误差（图 20）              | 真实误差中位数 5.0 m，<br>95% 分位 22.5 m，几乎<br>全部落在 $\sigma$ 内 |
| 终止判据              | 七点覆盖定理（问题三）                                              | 正张成判据（问题四）                  | 后者在前者失效时仍给出<br>正确结论（贪心对照<br>仅 55.7%）                  |

9.2 残差结构分析

把“估计误差”视为模型的残差  $\eta_c = |\hat{q}_c - q_c|$ 。检验其分布与  $\sigma_c$  的关系（317 个已清除样本）：中位数 5.0 m、均值 8.6 m、95% 分位 22.5 m、最大 47.8 m；误差没有随虚拟时间或位置系统性增大，说明不存在累积漂移；误差超出 20 m 的样本占 4.4%，但清除流程允许多次逼近，因此不影响完成率。图 20 右图显示误差与  $\sigma$  的散点几乎全部位

于对角线上方（即  $\sigma \geq \eta$ ），验证了“定位区域 MEC 半径作为不确定度上界”这一建模选择的保守性，也说明问题一到问题三的信息传递是自洽的。

### 9.3 蒙特卡洛与合成数据回归

- **问题二：**在可行源集合内均匀抽样源位置与两处读数误差（4000 次），实际定位区域直径的中位数 47.2 m、99% 分位 119.5 m、最大值 129.9 m，全部不超过理论上界  $J^* = 134.0$  m；同时验证了最坏情形出现在  $r = 1500$  m（图 10 右）。
- **问题三/四：**分别用 60 组与 30~60 组独立生成的随机算例（位置、频道、类型、接收半径全部随机）回归“完成率”与“平均时间”两个指标，结果见表 7、表 11；完成率 100%（问题三 60 例）与 100%（问题四混合 60 例）具有统计稳定性，扩池复核 120 例的最差完成率为 0.9978。
- **策略对照：**以“纯贪心”策略作为对照组，问题三为 307.7 s 对 324.1 s，问题四贪心完成率仅 55.7%，说明认证判据是问题四的关键增量。

### 9.4 模拟器验证与认证判据的修正

本节数字来自“本地协议一致模拟器”（原因见第 10 节），故先说明其可信度。本文实现了 **68 项检查** 的验证套件（协议 18、时间记账 8、物理 16、响应契约 8、与开源实现交叉对照 5、守恒律 4、增量认证等价性 5、策略级保证 4），**68/68 通过**，并抓出修复三个真实缺陷：`robot_id` 在服务未指定时形同虚设；示向度四舍五入到两位小数后可突破  $\pm 1^\circ$  上界（实测  $1.0024^\circ$ ）；以及认证扫描的“未认证位置”列表被一个早退优化截断（真实 1253 个点、返回 1 个，规划器长期在残缺区域上决策）。第三条由“增量实现必须等于暴力重算”这一检查逼出，修好后单局 CPU 由 41 s 降到 2.8 s。

交叉对照方面，调研发现一份专门针对本题的公开工程（官方模拟器驱动与离线 mock，MIT 许可）。以它为独立参照：12 个物理/时间常量完全一致；把其成本公式独立实现后，本文模拟器 300 步随机动作的虚拟时间增量逐步偏差小于  $10^{-9}$  s。唯一实质分歧是误差模型——该 mock 每次测量重新随机，而附件 1 要求同一地点重复测量结果相同，本文按附件 1 实现。

修正对结果的影响必须如实说明：此前报告的 0.9574 与 661.0 s 是在残缺认证下提前宣布完成得到的，代价是漏掉约 4% 的干扰源。修正后搜索必须真正走完，时间随之上升；此后再做四轮改进，在从未参与调参的独立算例池（40 例）上，平均时间由 1377.6 s 降至 **871.3 s**（-36.7%）、行程减少 38.2%，完成率由 0.9981 升到 1.0000（最差由 0.9231 升到 1.0000）。此外在把上述改动落地后，追踪最后一个失败算例时又发现一个更基础的缺陷：归航按“最后一条观测的方位角”从当前位置前进，而该方位只在测量它的那个点上有意义——偏差达  $58^\circ$ ，机器人已把源定位到 4.2 m（清除半径 20 m）却在 400 m 外来回振荡。改为朝估计点前进后，该算例由 0.909 变为 1.000、时间下降 35%。一并记录一个被否掉的结论：首轮寻优给出的“下降 44%”在独立池上只有 1.7%，根因是算例池被复用而 Arena 会就地清除 Source 对象；脚本已改为每次评估重新生成算例并加入可复现性守卫。修正后三次正式测试三局全部清除（11/11、12/12、11/11），平均时间 612.9 s、692.5 s、622.5 s。

## 9.5 灵敏度与稳健性

灵敏度分析结果见表 10、表 13 与图 22、图 23。要点：(i) 完成率对全部扰动均稳健（问题三、问题四在全部扰动下仍保持 0.988 以上）；(ii) 平均时间对“干扰源个数”最敏感（10 个源时单源时间比 16 个源高 50% 以上），因为搜索成本近似固定；(iii) 平均时间对测角误差、接收半径上界的敏感性较弱（ $\pm 5\%$  以内），说明算法不是靠“精确知道接收半径”取胜；(iv) 主导不确定性的参数是目标个数与目标的空间分布（后者体现为不同算例的标准差 57.1 s 与 170.3 s），而不是测量误差本身。

## 9.6 与外部参照的对照

- 交会角的最优性：文献 [13] 以圆概率误差（CEP）最小为准则推出最优交会角为  $90^\circ$ ；文献 [14] 进一步指出存在系统误差时最优交会角会偏离  $90^\circ$ 。本文问题二的最优解  $\varphi^* = 36.8^\circ$  对应的实际交会角为  $89.5^\circ \sim 91.2^\circ$ （随源距离变化），与之完全一致；其偏离正对应本文“两侧读数误差同号”的最坏情形设定。
- 覆盖数：Kershner[15] 给出用等半径圆覆盖圆盘的经典结果与渐近覆盖密度  $3\sqrt{3}/(2\pi) \approx 1.2092$ 。以面积比作下界估计，覆盖 1800 m 圆域大约需要 3.9 个  $R_{\min} = 1000$  m 的圆，而真正保证覆盖需要 7 个（定理 2）。这一差距正是“渐近密度”与“有限规模精确覆盖”的差别，本文采用后者以保证正确性。
- 可观测性：纯方位定位在观测平台不机动时不可观测 [28, 29]。本文的“射线归航”看似沿直线运动，但其读数误差随地点改变且每次检测都在新位置进行，等价于连续机动；这与 Le Cadre 等 [30] 的离散时间可观测性结论一致。
- 在线路径：本文的滚动重规划对应在线 TSP 的竞争比框架 [23] 与最小延迟问题 [24, 25]；由于探测半径（1000 m）远大于目标间距（平均约 440 m），信息获取的边际成本低，因此在线策略的表现接近离线最优（问题三对照实验证实）。

# 十、模型的评价、改进与推广

## 10.1 模型优点

1. 几何内核统一且严格。四个问题共用同一套“角度楔交会一定位区域—最小包围圆”内核，问题一的结论（有界性判据、Thales 覆盖判据）直接支撑问题二的最坏情形分析与问题三、四的不确定度定义，模型体系自洽。
2. 给出可证明的保证。七点覆盖定理保证“不漏源”，覆盖/正张成判据保证“敢停机”，射线逼近引理保证“逼近不丢信号”，三者把工程直觉提升为可检验的数学命题。
3. 在线算法与信息论下界对齐。问题二的极大极小解给出了单站观测条件下可达精度的理论界限（ $J^*$ ），Monte-Carlo 实测最大 129.9 m 与之相差 3%，接近下界。
4. 工程可用。算法只需要 4 条 HTTP 指令，单次决策计算量在毫秒级；在本地复现的协议环境中，60 组演练与 6 次正式测试均正常完成，程序运行时间小于 2.5 s（限制 1200 s）。

## 10.2 模型缺点与改进方向

针对上一版列出的四个方向，本轮把它们逐一做成可开关的实现并在同一算例池上实测（完整记录见支撑材料 docs/optional\_changes.pdf：11 项尝试中 3 项有效、6 项

为负优化、2 项无效)。结论如下。

**(1) 完成率损失——已解决。**该损失此前被归因于“贴边且朝外的定向源在域内不可认证”，但诊断显示真实原因在更上游：

(i) 末段三次观测点**近乎共线**（归航沿直线走），共线的方位测量无法约束距离，最小包围圆半径因此停在 77 m，而末段清除图案的半径取  $0.55\sigma \approx 42$  m，图案点没有一个落进 20 m 清除半径；

(ii) 图案扫完后机器人停在**最后一个外圈点**上，该点可能位于定向源的背光侧，随后的原地复测必然无声，循环空转直至预算耗尽。

两处修复分别是：**垂向截断测量**（图案失败时从垂直于视线的方向补一次观测， $\sigma$  由 77 m 降到 1 m）与**自适应沿射线站位**（第二站位偏移角随失败次数收缩，最终回到射线上——由射线逼近引理保证必定受光）。在**从未参与调参的独立算例池**（40 例）上，完成率由 0.9945 升到 **1.0000**（最差由 0.8462 升到 1.0000），平均时间同时下降 **38.2%**。真正的解不是域外采样，而是把定位做准、把站位放对。

**(2) 路径规划的耦合——部分有效。**把“清除顺序影响后续探测”具体化为两个可实现的耦合：顺路清除（巡访站位时清除近旁的已知源）与自适应补测间隔（未解算频道多时缩短补测间隔）。24 例对照：前者 881.3 → 882.2 s（无效，说明任务排序中的优先权偏置已隐含实现了该耦合），后者 881.3 → **852.1 s**（-3.3%，已默认启用）。因此本文的路径规划仍属启发式，但“耦合未被利用”这一自评偏保守。

**(3) 误差独立同界——经检验无需建模。**把示向度误差换成空间相关的平滑随机场（波长 1200 ~ 3000 m，相关比例取 0/50/80/100%）后，完成率与时间的差异落在运行波动范围内（ $a = 100\%$  时反而最好）。原因是结构性的：本文把每条读数当作**硬约束**（真实方位落在  $\hat{\theta} \pm 1^\circ$  内），定位区域取全部约束之交、不确定度取最小包围圆半径，该结论对任意满足逐条界的误差实现都成立，与是否相关无关。相关性只影响“重测取平均”的收益，而本文重测的价值来自**交会角改善**而非误差平均。（若改用卡尔曼滤波一类统计估计器，则必须先建模相关性。）

**(4) 真实时间耦合——本地环境判定无需建模，但在官方环境需复测。**实测一次正式测试（问题四，799 次 HTTP 请求）的真实耗时为 5.18 s，平均每请求 **6.48 ms**，相对 1200 s 上限有 **232 倍**余量；即使计入仿真环境内部开销 19.63 s，余量仍有 61 倍。但本结论只对本地模拟器成立：官方模拟器是 Windows 图形程序，其响应受界面刷新影响，可能慢得多。本队无法获取官方模拟器（见第 10.1 节），故**无法实测**，只能给出定量说法——官方每请求需比本地慢 230 倍以上才会触限。

## 10.3 推广

本文框架可直接推广到：(i) **多机器人协同**——按 Voronoi 划分站位并行搜索，终止判据变为“全体无信号点之并集覆盖目标域”；(ii) **移动干扰源**——估计改为带运动模型的滤波，覆盖判据改为时空覆盖；(iii) **TDOA/AOA 混合定位**——角度楔换成双曲线带，问题一算法推广为二次约束可行域枚举；(iv) **应急搜救**——替换“接收半径/频道”为“探测半径/目标类型”后三件套同样适用。

## 参考文献

- [1] 中华人民共和国国务院, 中华人民共和国中央军事委员会. 中华人民共和国无线电管理条例（国令第 672 号）[Z]. 2016-11-11 修订, 2016-12-01 施行. [https://www.gov.cn/zhengce/content/2016-11/25/content\\_5137687.htm](https://www.gov.cn/zhengce/content/2016-11/25/content_5137687.htm)
- [2] Recommendation ITU-R SM.854-3. Direction finding and location determination at monitoring stations[S]. ITU, 2011-09. <https://www.itu.int/rec/R-REC-SM.854/en>
- [3] Recommendation ITU-R SM.2060-0. Test procedure for measuring direction finder accuracy[S]. ITU, 2014-11. <https://www.itu.int/rec/R-REC-SM.2060/en>

- [4] ITU-R. Handbook on Spectrum Monitoring (R-HDB-23-2011)[M]. Geneva: ITU, 2011. <https://www.itu.int/pub/R-HDB-23-2011>
- [5] GB/T 34089-2017. VHF/UHF 无线电监测测向系统开测测试参数和测试方法 [S]. 北京: 中国标准出版社, 2017.
- [6] YD/T 3730-2020. VHF/UHF 无线电测向系统多径传播抗扰度测试程序 [S]. 北京: 人民邮电出版社, 2020.
- [7] GB/T 25003-2010. VHF/UHF 频段无线电监测站电磁环境保护要求和测试方法 [S]. 北京: 中国标准出版社, 2010.
- [8] 张洪顺, 王磊. 无线电监测与测向定位 [M]. 西安: 西安电子科技大学出版社, 2011. ISBN 978-7-5606-2654-3.
- [9] 周靖博, 黄艳. 做好无线电干扰源测向定位的几点经验 [J]. 中国无线电, 2009(2).
- [10] 黄裕文, 李怡恒, 程擎, 等. 机场终端区 GNSS 信号干扰源定位研究 [J]. 现代雷达, 2023(12): 87-93.
- [11] Torrieri D J. Statistical theory of passive location systems[J]. IEEE Transactions on Aerospace and Electronic Systems, 1984, AES-20(2): 183-198.
- [12] Stansfield R G. Statistical theory of d.f. fixing[J]. Journal of the Institution of Electrical Engineers - Part IIIA: Radiocommunication, 1947, 94(15): 762-770.
- [13] 修建娟, 何友, 王国宏, 等. 测向交叉定位系统中的交会角研究 [J]. 宇航学报, 2005, 26(3): 282-285.
- [14] 盛丹, 王国宏, 孙殿星. 存在系统误差下交叉定位系统最优交会角研究 [J]. 系统工程与电子技术, 2016, 38(7): 1516-1523.
- [15] Kershner R. The number of circles covering a set[J]. American Journal of Mathematics, 1939, 61(3): 665-671.
- [16] Gáspár Z, Tamai T, Hincz K. Partial covering of a circle by 6 and 7 congruent circles[J]. Symmetry, 2021, 13(11): 2133.
- [17] Koopman B O. Search and Screening[M]. New York: Pergamon Press, 1980 (first edition: Operations Evaluation Group, 1946). ISBN 0080231357.
- [18] Stone L D. Theory of Optimal Search[M]. New York: Academic Press, 1975. ISBN 0126724504.
- [19] Stone L D, Royset J O, Washburn A R. Optimal Search for Moving Targets[M]. Springer, 2016. DOI 10.1007/978-3-319-26899-6.
- [20] 陈建勇. 实用搜索理论 [M]. 北京: 国防工业出版社, 2021. ISBN 978-7-118-12327-2.
- [21] Choset H. Coverage for robotics - a survey of recent results[J]. Annals of Mathematics and Artificial Intelligence, 2001, 31(1-4): 113-126.
- [22] Galceran E, Carreras M. A survey on coverage path planning for robotics[J]. Robotics and Autonomous Systems, 2013, 61(12): 1258-1276.
- [23] Ausiello G, Feuerstein E, Leonardi S, et al. Algorithms for the on-line travelling salesman[J]. Algorithmica, 2001, 29(4): 560-581.
- [24] Afrati F, Cosmadakis S, Papadimitriou C H, et al. The complexity of the travelling repairman problem[J]. RAIRO - Theoretical Informatics and Applications, 1986, 20(1): 79-87.
- [25] Blum A, Chalasani P, Coppersmith D, et al. The minimum latency problem[C]//Proceedings of the 26th Annual ACM Symposium on Theory of Computing (STOC'94), 1994: 163-171.
- [26] Psarafitis H N. Dynamic vehicle routing: status and prospects[J]. Annals of Operations Research, 1995, 61(1): 143-164.
- [27] Bertsimas D J, van Ryzin G. A stochastic and dynamic vehicle routing problem in the Euclidean plane[J]. Operations Research, 1991, 39(4): 601-615.
- [28] Nardone S C, Aidala V J. Necessary and sufficient observability conditions for bearings-only target motion analysis[R]. NUSC Technical Memorandum TM 80-2059 / DTIC AD-A102073, 1980.
- [29] Nardone S C, Aidala V J. Observability criteria for bearings-only target motion analysis[J]. IEEE Transactions on Aerospace and Electronic Systems, 1981, AES-17(2): 162-166.
- [30] Le Cadre J E, Jauffret C. Discrete-time observability and estimability analysis for bearings-only target motion analysis[J]. IEEE Transactions on Aerospace and Electronic Systems, 1997, 33(1): 178-201.
- [31] Payne A N. Observability problem for bearings-only tracking[J]. International Journal of Control, 1989, 49(3): 761-768.
- [32] 同题公开实现: 2026 CUMCM B 题无线电干扰源定位与清除 (交会定位几何 + 覆盖侦察完备性 + 追踪逼近/清除扫描) [CP/OL]. <https://github.com/1i2396803/cumcm2026-b-radio-interference-localization>
- [33] LaTeX 工作室. CUMCMThesis: 全国大学生数学建模竞赛 LaTeX 论文模板 [CP/OL]. <https://github.com/latexstudio/CUMCMThesis>

## A 支撑材料清单

支撑材料压缩包内文件如下（所有文件均不含参赛者身份、学校与赛区信息）：

| 文件/目录                 | 说明                                                              |
|-----------------------|-----------------------------------------------------------------|
| code/geom_core.py     | 几何内核：角楔半平面、定位区域顶点枚举、回收锥有界性判据、卡壳直径、Thales 覆盖判据、Welzl 最小包围圆（问题一）  |
| code/q2_solver.py     | 问题二：可行源集合、极大极小站位优化、候选区域、风险-精度权衡、Monte-Carlo 检验与基线对比             |
| code/q2_strategy.py   | 问题二早期版本（网格搜索与垂直族研究）                                             |
| code/q1_scan.py,      | 问题一的随机算例扫描、直径圆失效反例搜索                                            |
| q1_counterexample.py, | 与冒烟测试                                                           |
| q1_smoke.py           |                                                                 |
| code/simulator.py     | 依照附件 1、附件 2 复现的本地模拟器（HTTP+JSON 四条指令、虚拟时间记账、方位误差地点固定、定向覆盖角、日志导出） |
| code/robot_core.py    | 机器狗策略内核：信息状态、定位区域估计、七点覆盖、任务规划（最近邻+2-opt）、射线归航与末段清除、认证判据（问题三、四）  |

| 文件/目录                                                  | 说明                                                                           |
|--------------------------------------------------------|------------------------------------------------------------------------------|
| code/run_http_tests.py                                 | 正式测试执行器：启动模拟器 HTTP 服务、机器狗通过 HTTP 交互、导出行为日志与统计                                |
| code/make_data.py                                      | 全部数值结果生成脚本（问题一—四的算例、统计、灵敏度分析）                                                |
| code/make_figures.py,<br>zh_labels.json, fix_labels.py | 全部论文插图生成脚本与中文标签数据                                                            |
| code/tune.py, tune_q4.py                               | 策略参数随机搜索与坐标细化（问题三、四）                                                         |
| data/*.csv, *.json                                     | 运行结果数据：q1_*.csv、q2_*.csv、q3_*.csv、q4_*.csv、formal_*.json、*_sensitivity.csv 等 |
| figures/*.png                                          | 论文全部插图（200 dpi）                                                              |
| logs/formal/*.log                                      | 六次正式测试的机器狗行为日志（JSON Lines，逐条记录虚拟时刻、位置、频道、指令、响应）                              |
| logs/drill/*.log                                       | 演练测试日志                                                                       |
| report/self_check.md                                   | 自检报告                                                                         |
| report/REFERENCE_SOURCES.md                            | 参考文献来源与核实记录                                                                  |

## B 补充图表

以下三张图为正文中的诊断性插图，为控制正文篇幅移至此处；正文中对应的引用编号保持不变。




图 19 左：直径圆不能覆盖定位区域的算例比例；右：超出半径的相对量级（最大仅 0.18%）




图 20 残差与一致性检验：左为清除时刻的定位误差分布（中位数 5.0 m，95% 分位 22.5 m，最大 47.8 m）；中为估计不确定度  $\sigma$  的累积分布；右为不确定度与实际误差的散点关系，绝大多数点位于  $y = x$  上方，说明  $\sigma$  是误差的可靠上界




图 21 一次完整测试中的检测行为：左为各次检测的位置到出发点距离随虚拟时刻的变化（可见“由内向外”的搜索波前与回访），右为检测结果统计

## C 完整源程序代码

以下给出全部建模与求解程序的完整源码（可直接运行；运行环境 Python 3.9 + numpy/matplotlib）。为满足“代码中不出现中文”的可移植性要求，程序中的标识符与字符串全部为 ASCII，说明性注释与图形标签分别使用中文注释与外部 UTF-8 标签文件（zh\_labels.json）。

### 3.1 几何内核 geom\_core.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  geom_core.py -- Core geometry engine for bearing-only (cross-fixing) localization.
5
6  Chinese comments are used for readability; all executable identifiers/strings are ASCII.
7
8  Model background
9  -----
10 A direction finder at station S_i measures the bearing (deg) of one interference
11 source. Because of the local electromagnetic environment the reading carries a
12 bounded systematic error, so the TRUE bearing of the source seen from S_i is
13 unknown but confined to
14
15     [ theta_i - eps , theta_i + eps ] (eps = 1 deg in this problem)
16
17 Hence every station defines an angular WEDGE (a convex cone with apex S_i). The
18 cross-fixing positioning region is the intersection of all wedges
19
20     R = { P : | angle(P - S_i) - theta_i | <= eps for every i }
21
22 which is a convex polygon (possibly empty, possibly unbounded). This module
23 builds that polygon exactly, computes its diameter, tests whether the disk whose
24 diameter equals the region diameter covers the region, and computes the minimum
25 enclosing circle (Welzl) for comparison.
26
27 Conventions
28 -----
29 * angle : degrees, measured counter-clockwise from +x axis (east), range [0,360)
30 * half-plane : (a, b, c) encodes a*x + b*y <= c
31 """
32
33 import math
34 import random
35
36
37 # -----
38 # basic angle helpers
39 # -----
40 def norm360(a):
41     """Normalize an angle (deg) into [0, 360)."""
42     return a % 360.0
43
44
45 def deg2rad(a):
46     return a * math.pi / 180.0

```

```

47
48
49 def bearing(px, py, qx, qy):
50     """Bearing (deg, [0,360)) of the vector from P to Q."""
51     return norm360(math.degrees(math.atan2(qy - py, qx - px)))
52
53
54 def ang_diff(a, b):
55     """Signed smallest difference a-b wrapped into (-180, 180]."""
56     d = (a - b + 180.0) % 360.0 - 180.0
57     return 180.0 if d == -180.0 else d
58
59
60 def unit(a_deg):
61     r = deg2rad(a_deg)
62     return math.cos(r), math.sin(r)
63
64
65 # -----
66 # wedge -> half planes
67 # -----
68 def wedge_halfplanes(sx, sy, theta_deg, eps_deg):
69     """
70     Two half planes whose intersection is the angular wedge
71     { P : bearing(P - S) in [theta-eps, theta+eps] (ccw) }.
72
73     Derivation: v = P - S must satisfy
74     cross(u(theta-eps), v) >= 0 and cross(u(theta+eps), v) <= 0
75     with cross(u, v) = ux*vy - uy*vx. Writing v = (x - sx, y - sy) this gives
76     sin(theta-eps)*(x-sx) - cos(theta-eps)*(y-sy) <= 0
77     -sin(theta+eps)*(x-sx) + cos(theta+eps)*(y-sy) <= 0
78     Both are of the form a*x + b*y <= c.
79     """
80     t1 = deg2rad(theta_deg - eps_deg)
81     t2 = deg2rad(theta_deg + eps_deg)
82     hp = []
83     a1, b1 = math.sin(t1), -math.cos(t1)
84     hp.append((a1, b1, a1 * sx + b1 * sy))
85     a2, b2 = -math.sin(t2), math.cos(t2)
86     hp.append((a2, b2, a2 * sx + b2 * sy))
87     return hp
88
89
90 def halfplanes_satisfied(hps, x, y, tol=1e-9):
91     """True when the point satisfies every half plane a*x+b*y <= c (within tol)."""
92     for (a, b, c) in hps:
93         if a * x + b * y > c + tol * max(1.0, abs(c)):
94             return False
95     return True
96
97
98 def intersect_lines(l1, l2):
99     """
100     Intersection of two lines a1 x + b1 y = c1 and a2 x + b2 y = c2.
101     Returns None when (nearly) parallel.
102     """
103     a1, b1, c1 = l1
104     a2, b2, c2 = l2
105     det = a1 * b2 - a2 * b1
106     scale = math.hypot(a1, b1) * math.hypot(a2, b2)
107     if abs(det) <= 1e-12 * max(scale, 1.0):
108         return None
109     x = (c1 * b2 - c2 * b1) / det
110     y = (a1 * c2 - a2 * c1) / det
111     return (x, y)
112
113
114 def convex_hull(points, tol=1e-9):
115     """
116     Andrew monotone chain. Returns hull vertices in counter-clockwise order,
117     without duplicated points. Collinear points on the boundary are dropped.
118     """
119     pts = sorted(set((round(p[0], 9), round(p[1], 9)) for p in points))
120     if len(pts) <= 2:
121         return [tuple(p) for p in pts]
122
123     def cross(o, a, b):
124         return (a[0] - o[0]) * (b[1] - o[1]) - (a[1] - o[1]) * (b[0] - o[0])
125

```

```

126 lower = []
127 for p in pts:
128     while len(lower) >= 2 and cross(lower[-2], lower[-1], p) <= tol:
129         lower.pop()
130     lower.append(p)
131 upper = []
132 for p in reversed(pts):
133     while len(upper) >= 2 and cross(upper[-2], upper[-1], p) <= tol:
134         upper.pop()
135     upper.append(p)
136 return tuple(p for p in lower[:-1] + upper[::-1])
137
138
139 def polygon_vertices(hps):
140     """
141     Exact vertex enumeration of the feasible polygon { P : A P <= c }.
142
143     Every vertex of a 2-D polyhedron is the intersection of two of its boundary
144     lines, so we enumerate all  $O(m^2)$  line pairs, keep the feasible ones and take
145     their convex hull. This is robust for the tiny systems appearing here
146     ( $m = 2n \leq 40$ ) and it needs no artificial bounding box, therefore an
147     unbounded region is not silently truncated: the caller is warned through
148     the 'bounded' flag (see region_from_bearings).
149     """
150     feasible = []
151     m = len(hps)
152     for i in range(m):
153         for j in range(i + 1, m):
154             p = intersect_lines(hps[i], hps[j])
155             if p is None:
156                 continue
157             if halfplanes_satisfied(hps, p[0], p[1]):
158                 feasible.append(p)
159     if not feasible:
160         return []
161     return convex_hull(feasible)
162
163
164 # -----
165 # boundedness: recession cone of the region
166 # -----
167 def _circular_arc_intersection(arcs):
168     """
169     Intersection of circular arcs [lo_i, hi_i] (degrees, ccw, length < 180).
170     Returns (nonempty, [representative angle]). Implemented by sampling the
171     boundary directions: an intersection of closed arcs is non-empty iff one of
172     the arc start points lies inside all arcs (or all arcs are the full circle).
173     """
174     starts = [a[0] % 360.0 for a in arcs]
175     for s in starts:
176         ok = True
177         for (lo, hi) in arcs:
178             if ang_diff(s, lo) < -1e-9 or ang_diff(s, hi) > 1e-9:
179                 ok = False
180                 break
181         if ok:
182             return True, s
183     # also test just-inside points to be safe against floating point edges
184     for s in starts:
185         for d in (1e-7, -1e-7):
186             t = (s + d) % 360.0
187             if all(ang_diff(t, lo) >= -1e-9 and ang_diff(t, hi) <= 1e-9 for (lo, hi) in arcs):
188                 return True, t
189     return False, None
190
191
192 def is_bounded(bearings_deg, eps_deg):
193     """
194     The region is unbounded iff the recession cone
195     { d : bearing(d) in [theta_i-eps, theta_i+eps] for all i }
196     contains a non-zero direction, i.e. iff the arcs have a common direction.
197     """
198     arcs = [(norm360(t - eps_deg), norm360(t + eps_deg)) for t in bearings_deg]
199     nonempty, _ = _circular_arc_intersection(arcs)
200     return not nonempty
201
202
203 # -----
204 # region built from a set of (station, bearing) measurements

```

```

205 # -----
206 def halfplanes_from_bearings(stations, bearings_deg, eps_deg):
207     hps = []
208     for (sx, sy), th in zip(stations, bearings_deg):
209         hps.extend(wedge_halfplanes(sx, sy, th, eps_deg))
210     return hps
211
212
213 def region_from_bearings(stations, bearings_deg, eps_deg=1.0):
214     """
215     Full description of the cross-fixing positioning region.
216
217     Returns a dict with
218     vertices : hull vertices (ccw). Meaningful only when not empty.
219     empty    : True when no point is consistent with all measurements.
220     bounded  : False when the region is an unbounded cone-like set.
221     diameter : max pairwise distance of the vertices (inf if unbounded),
222     d_pair   : the vertex pair realizing the diameter,
223     cover_ok : whether the disk having that pair as diameter contains the
224                 whole region (Thales test on every vertex),
225     cover_slack : max over vertices of (V-A).(V-B) (<=0 means covered)
226     mec      : (cx, cy, r) minimum enclosing circle
227     """
228     hps = halfplanes_from_bearings(stations, bearings_deg, eps_deg)
229     verts = polygon_vertices(hps)
230     bounded = is_bounded(bearings_deg, eps_deg)
231     out = {
232         "vertices": verts,
233         "empty": len(verts) == 0,
234         "bounded": bounded,
235         "diameter": float("inf"),
236         "d_pair": None,
237         "cover_ok": None,
238         "cover_slack": None,
239         "mec": None,
240     }
241     if out["empty"]:
242         return out
243     if not bounded:
244         # an unbounded region has no finite diameter: report the recession
245         # direction so that the caller can react (add stations / use the
246         # physically bounded region instead)
247         arcs = [(norm360(t - eps_deg), norm360(t + eps_deg)) for t in bearings_deg]
248         _, d = _circular_arc_intersection(arcs)
249         out["recession_dir"] = d
250         return out
251
252     d, pair = polygon_diameter(verts)
253     out["diameter"] = d
254     out["d_pair"] = pair
255     slack = diameter_disk_slack(verts, pair[0], pair[1])
256     out["cover_slack"] = slack
257     out["cover_ok"] = bool(slack <= 1e-9)
258     out["mec"] = min_enclosing_circle(verts)
259     return out
260
261
262 # -----
263 # diameter of a point set / convex polygon
264 # -----
265 def polygon_diameter(pts):
266     """
267     Diameter (largest pairwise distance) of a convex polygon given by its
268     vertices. Brute force  $O(m^2)$  is used because  $m \leq 40$  here; the result is
269     exact for a convex polygon (the diameter is realized by two vertices).
270     Returns (value, (P, Q)).
271     """
272     best = -1.0
273     bp = None
274     m = len(pts)
275     for i in range(m):
276         xi, yi = pts[i]
277         for j in range(i + 1, m):
278             xj, yj = pts[j]
279             d = math.hypot(xi - xj, yi - yj)
280             if d > best:
281                 best = d
282                 bp = (pts[i], pts[j])
283     if bp is None:

```

```

284         return 0.0, (pts[0], pts[0])
285     return best, bp
286
287
288 def rotating_calipers_diameter(pts):
289     """
290     Independent cross-check of polygon_diameter() using rotating calipers on the
291     convex hull (Shamos). Both methods must agree; the agreement is reported in
292     the self-check of Q1.
293     """
294     hull = convex_hull(pts)
295     n = len(hull)
296     if n < 2:
297         return 0.0, (hull[0], hull[0]) if n == 1 else (None, None)
298     if n == 2:
299         d = math.dist(hull[0], hull[1])
300         return d, (hull[0], hull[1])
301     best = -1.0
302     bp = None
303     j = 1
304     for i in range(n):
305         ni = (i + 1) % n
306         while True:
307             nj = (j + 1) % n
308             # advance j while the triangle area keeps growing
309             a1 = abs(_tri_area2(hull[i], hull[ni], hull[j]))
310             a2 = abs(_tri_area2(hull[i], hull[ni], hull[nj]))
311             if a2 > a1:
312                 j = nj
313             else:
314                 break
315         for k in (j, (j + 1) % n):
316             d = math.dist(hull[i], hull[k])
317             if d > best:
318                 best = d
319                 bp = (hull[i], hull[k])
320     return best, bp
321
322
323 def _tri_area2(a, b, c):
324     return (b[0] - a[0]) * (c[1] - a[1]) - (b[1] - a[1]) * (c[0] - a[0])
325
326
327 # -----
328 # Thales test : does the disk with AB as diameter contain every vertex?
329 # -----
330 def diameter_disk_slack(pts, A, B):
331     """
332     By Thales' theorem P lies in the closed disk with diameter AB iff
333     (P - A) . (P - B) <= 0.
334     Returns the maximum of that quantity over the point set: <= 0 means the
335     disk covers everything, > 0 gives the size of the violation (metres^2).
336     """
337     worst = -float("inf")
338     for (x, y) in pts:
339         v = (x - A[0]) * (x - B[0]) + (y - A[1]) * (y - B[1])
340         if v > worst:
341             worst = v
342     return worst
343
344
345 # -----
346 # minimum enclosing circle (Welzl, randomized incremental, exact arithmetic in
347 # double precision with a small tolerance)
348 # -----
349 def _circle_from2(a, b):
350     cx, cy = (a[0] + b[0]) / 2.0, (a[1] + b[1]) / 2.0
351     return (cx, cy, math.dist(a, b) / 2.0)
352
353
354 def _circle_from3(a, b, c):
355     ax, ay = a
356     bx, by = b
357     cx, cy = c
358     d = 2.0 * (ax * (by - cy) + bx * (cy - ay) + cx * (ay - by))
359     if abs(d) < 1e-12:
360         # collinear: fall back to the farthest pair
361         cand = [(_circle_from2(a, b), a, b), (_circle_from2(a, c), a, c),
362                (_circle_from2(b, c), b, c)]

```

```

363     return max(cand, key=lambda t: t[0][2])[0]
364     ux = ((ax * ax + ay * ay) * (by - cy) + (bx * bx + by * by) * (cy - ay)
365           + (cx * cx + cy * cy) * (ay - by)) / d
366     uy = ((ax * ax + ay * ay) * (cx - bx) + (bx * bx + by * by) * (ax - cx)
367           + (cx * cx + cy * cy) * (bx - ax)) / d
368     return (ux, uy, math.hypot(ux - ax, uy - ay))
369
370
371 def _inside(c, p, tol=1e-7):
372     return math.hypot(p[0] - c[0], p[1] - c[1]) <= c[2] + tol
373
374
375 def min_enclosing_circle(points, seed=20260913):
376     """
377     Smallest enclosing circle of a point set (Welzl's algorithm).
378     Returns (cx, cy, r).
379     """
380     pts = list(points)
381     if not pts:
382         return None
383     rnd = random.Random(seed)
384     rnd.shuffle(pts)
385     c = (pts[0][0], pts[0][1], 0.0)
386     for i in range(1, len(pts)):
387         if _inside(c, pts[i]):
388             continue
389         c = (pts[i][0], pts[i][1], 0.0)
390         for j in range(i):
391             if _inside(c, pts[j]):
392                 continue
393             c = _circle_from2(pts[i], pts[j])
394             for k in range(j):
395                 if _inside(c, pts[k]):
396                     continue
397             c = _circle_from3(pts[i], pts[j], pts[k])
398     return c
399
400
401 # -----
402 # analytic description of the 2-station region (used for closed-form checks)
403 # -----
404 def two_station_region(s1, s2, th1_deg, th2_deg, eps_deg=1.0):
405     """
406     Explicit four lines of the classical two-station cross-fixing figure and the
407     four corner points A = L1- ^ L2-, B = L1- ^ L2+ , C = L1+ ^ L2- ,
408     D = L1+ ^ L2+ (the feasible ones form the red quadrilateral of the problem
409     statement). Returns dict with the lines and the feasible corners.
410     """
411     hps = wedge_halfplanes(s1[0], s1[1], th1_deg, eps_deg) + \
412           wedge_halfplanes(s2[0], s2[1], th2_deg, eps_deg)
413     L1m, L1p, L2m, L2p = hps
414     corners = {}
415     for name, la, lb in (("A", L1m, L2m), ("B", L1m, L2p),
416                        ("C", L1p, L2m), ("D", L1p, L2p)):
417         p = intersect_lines(la, lb)
418         if p is not None:
419             corners[name] = p
420     feasible = {k: v for k, v in corners.items() if halfplanes_satisfied(hps, v[0], v[1])}
421     return {"lines": { "L1m": L1m, "L1p": L1p, "L2m": L2m, "L2p": L2p },
422           "corners": corners, "feasible": feasible}
423
424
425 def region_intersection_angle(s1, s2, g):
426     """
427     Intersection angle gamma (deg) at the source G between the two lines of
428     sight: the geometric quality factor of a two-station fix.
429     """
430     b1 = bearing(g[0], g[1], s1[0], s1[1])
431     b2 = bearing(g[0], g[1], s2[0], s2[1])
432     return abs(ang_diff(b1, b2))
433
434
435 def asymptotic_diameter(d1, d2, gamma_deg, eps_deg=1.0):
436     """
437     Closed-form first-order diameter of the positioning region for a slender
438     region: the two +-eps rays through the source form, after linearisation, a
439     parallelogram with side widths w_i = 2*eps*d_i cut at angle gamma, hence
440     D ~ sqrt(w1^2 + w2^2 + 2 w1 w2 cos(gamma)) / sin(gamma).
441     Used as an independent analytic check of the polygon-based diameter.

```

```

442     """
443     w1 = 2.0 * deg2rad(eps_deg) * d1
444     w2 = 2.0 * deg2rad(eps_deg) * d2
445     s = math.sin(deg2rad(gamma_deg))
446     if abs(s) < 1e-12:
447         return float("inf")
448     return math.sqrt(w1 * w1 + w2 * w2 + 2.0 * w1 * w2 * math.cos(deg2rad(gamma_deg))) / s

```

### 3.2 问题二求解 q2\_solver.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  q2_solver.py -- PROBLEM 2 (complete study)
5
6  Contents
7      1. solve_second_point() : the robust (minimax) design of the second station
8      2. study_guard_tradeoff(): how the optimum depends on the assumed worst-case
9         reception radius (the "risk" parameter)
10     3. candidate_region() : the eta-sub-level set, i.e. the answer to
11        "give the candidate region for the second point"
12     4. monte_carlo_check() : Monte-Carlo verification against the true errors
13     5. baseline comparison : the proposed rule vs naive rules and the oracle
14  Outputs: ../data/q2_*.csv, ../data/q2_summary.json
15  Run: python q2_solver.py
16  """
17  import csv
18  import json
19  import math
20  import os
21  import random
22
23  import geom_core as g
24
25  EPS = 1.0
26  R_MAX = 1500.0
27  R_MIN = 1000.0
28  R_NEAR = 5.0
29  ARENA_R = 1800.0
30  HERE = os.path.dirname(os.path.abspath(__file__))
31  OUT = os.path.normpath(os.path.join(HERE, "..", "data"))
32
33
34  # -----
35  # geometry helpers in the local frame of S1 (bearing direction = +x axis)
36  # -----
37  def local_to_world(p, s1, th1_hat):
38      a = math.radians(th1_hat)
39      return (s1[0] + p[0] * math.cos(a) - p[1] * math.sin(a),
40              s1[1] + p[0] * math.sin(a) + p[1] * math.cos(a))
41
42
43  def world_to_local(p, s1, th1_hat):
44      a = math.radians(-th1_hat)
45      dx, dy = p[0] - s1[0], p[1] - s1[1]
46      return (dx * math.cos(a) - dy * math.sin(a), dx * math.sin(a) + dy * math.cos(a))
47
48
49  def sector_points(s1, th1_hat, r_lo=R_NEAR + 1.0, r_hi=R_MAX, n_r=32, n_d=7, eps=EPS):
50      pts = []
51      for i in range(n_r):
52          f = i / float(n_r - 1)
53          r = r_lo * (r_hi / r_lo) ** f
54          for j in range(n_d):
55              d = -eps + 2.0 * eps * j / float(n_d - 1)
56              a = math.radians(th1_hat + d)
57              p = (s1[0] + r * math.cos(a), s1[1] + r * math.sin(a))
58              if math.hypot(p[0], p[1]) <= ARENA_R:
59                  pts.append((r, d, p))
60      return pts
61
62
63  def worst_diameter(s1, s2, th1_hat, gset, eps=EPS):
64      """Worst-case diameter of the two-station cross-fixing region."""
65      worst = 0.0

```

```

66     info = None
67     for (r, d, p) in gset:
68         th2 = g.bearing(s2[0], s2[1], p[0], p[1])
69         for sgn in (-1.0, 1.0):
70             res = g.region_from_bearings([s1, s2], [th1_hat, th2 + sgn * eps], eps)
71             if res["empty"] or not res["bounded"]:
72                 D = float("inf")
73             else:
74                 D = res["diameter"]
75             if D > worst:
76                 worst = D
77                 info = {"r": r, "delta": d, "G": p, "sign2": sgn, "D": D}
78     return worst, info
79
80
81 def guard_ok(s2, gset, r_guard):
82     return all(math.dist(s2, p) <= r_guard + 1e-9 for (_, _, p) in gset)
83
84
85 def guard_margin(s2, gset):
86     return max(math.dist(s2, p) for (_, _, p) in gset)
87
88
89 # -----
90 # 1. solve the design problem
91 # -----
92 def solve_second_point(s1, th1_hat, r_guard=R_MIN, r_hi=R_MAX,
93                       n_b=61, n_phi=121, phi_span=75.0, refine=True):
94     """
95     Grid + local refinement minimisation of J(S2) = worst-case region diameter
96     over the polar family (b, phi) centred on the measured bearing direction.
97     Returns a dict describing the optimum.
98     """
99     gset = sector_points(s1, th1_hat, r_hi=r_hi)
100     best = None
101     for ib in range(n_b):
102         b = 60.0 + (r_guard + 120.0 - 60.0) * ib / float(n_b - 1)
103         for ip in range(n_phi):
104             phi = -phi_span + 2.0 * phi_span * ip / float(n_phi - 1)
105             loc = (b * math.cos(math.radians(phi)), b * math.sin(math.radians(phi)))
106             s2 = local_to_world(loc, s1, th1_hat)
107             if not guard_ok(s2, gset, r_guard):
108                 continue
109             J, info = worst_diameter(s1, s2, th1_hat, gset)
110             if best is None or J < best["J"]:
111                 best = {"b": b, "phi": phi, "S2": s2, "J": J, "info": info,
112                        "guard_margin": guard_margin(s2, gset)}
113     if best is None:
114         return None
115     # local refinement (coordinate descent on (b, phi))
116     if refine:
117         step_b, step_p = 25.0, 4.0
118         for _ in range(40):
119             improved = False
120             for db, dp in ((step_b, 0), (-step_b, 0), (0, step_p), (0, -step_p)):
121                 b, phi = best["b"] + db, best["phi"] + dp
122                 if b <= 20.0 or abs(phi) > 88.0:
123                     continue
124                 loc = (b * math.cos(math.radians(phi)), b * math.sin(math.radians(phi)))
125                 s2 = local_to_world(loc, s1, th1_hat)
126                 if not guard_ok(s2, gset, r_guard):
127                     continue
128                 J, info = worst_diameter(s1, s2, th1_hat, gset)
129                 if J < best["J"] - 1e-9:
130                     best = {"b": b, "phi": phi, "S2": s2, "J": J, "info": info,
131                            "guard_margin": guard_margin(s2, gset)}
132             improved = True
133         if not improved:
134             step_b *= 0.5
135             step_p *= 0.5
136             if step_b < 0.5:
137                 break
138     best["gset"] = gset
139     best["r_guard"] = r_guard
140     return best
141
142
143 # -----
144 # 2. trade-off between the risk parameter and the attainable accuracy

```

```

145 # -----
146 def study_guard_tradeoff(s1=(-420.0, 260.0), th1_hat=63.0):
147     rows = []
148     for rg in (1000, 1050, 1100, 1150, 1200, 1300, 1400, 1500):
149         sol = solve_second_point(s1, th1_hat, r_guard=float(rg))
150         if sol is None:
151             rows.append({"r_guard": rg, "feasible": 0})
152             continue
153         rows.append({"r_guard": rg, "feasible": 1, "b": sol["b"], "phi": sol["phi"],
154                     "J": sol["J"], "worst_r": sol["info"]["r"],
155                     "S2_x": sol["S2"][0], "S2_y": sol["S2"][1]})
156         print(" r_guard=%4d b=%7.1f phi=%+6.2f J=%8.3f m (worst source r=%6.1f m)"
157               % (rg, sol["b"], sol["phi"], sol["J"], sol["info"]["r"]))
158     return rows
159
160 # -----
161 # 3. candidate region = eta sub-level set
162 # -----
163
164 def candidate_region(sol, eta=0.15, n_b=41, n_phi=81, phi_span=75.0):
165     gset = sol["gset"]
166     s1 = None
167     rows = []
168     for ib in range(n_b):
169         b = 200.0 + 1400.0 * ib / float(n_b - 1)
170         for ip in range(n_phi):
171             phi = -phi_span + 2.0 * phi_span * ip / float(n_phi - 1)
172             rows.append((b, phi))
173     return rows
174
175
176 def candidate_region_map(s1, th1_hat, r_guard, Jstar, eta=0.15,
177                        n_b=45, n_phi=91, phi_span=80.0):
178     """Return a list of (b, phi, J) with the feasibility flag, for plotting."""
179     gset = sector_points(s1, th1_hat)
180     out = []
181     for ib in range(n_b):
182         b = 100.0 + 1600.0 * ib / float(n_b - 1)
183         for ip in range(n_phi):
184             phi = -phi_span + 2.0 * phi_span * ip / float(n_phi - 1)
185             loc = (b * math.cos(math.radians(phi)), b * math.sin(math.radians(phi)))
186             s2 = local_to_world(loc, s1, th1_hat)
187             if not guard_ok(s2, gset, r_guard):
188                 out.append((b, phi, float("nan"), 0))
189                 continue
190             J, _ = worst_diameter(s1, s2, th1_hat, gset)
191             out.append((b, phi, J, 1 if J <= (1.0 + eta) * Jstar else 0))
192     return out
193
194 # -----
195 # 4. Monte-Carlo verification
196 # -----
197
198 def monte_carlo_check(sol, s1, th1_hat, n=4000, seed=2026):
199     """
200     Draw the true source uniformly in the feasible sector and the two reading
201     errors uniformly in [-eps, eps]; build the real two-station region and
202     record its diameter. The prescribed point must never exceed J*.
203     """
204     rnd = random.Random(seed)
205     r_hi = max(r for (r, _, _) in sol["gset"])
206     s2 = sol["S2"]
207     Ds = []
208     violations = 0
209     for _ in range(n):
210         r = R_NEAR + 1.0 + (r_hi - R_NEAR - 1.0) * rnd.random()
211         a_true = th1_hat + rnd.uniform(-EPS, EPS)
212         G = (s1[0] + r * math.cos(math.radians(a_true)), s1[1] + r * math.sin(math.radians(a_true)))
213         th2_hat = g.bearing(s2[0], s2[1], G[0], G[1]) + rnd.uniform(-EPS, EPS)
214         res = g.region_from_bearings([s1, s2], [th1_hat, th2_hat], EPS)
215         if res["empty"] or not res["bounded"]:
216             D = float("inf")
217         else:
218             D = res["diameter"]
219         if D > sol["J"] + 1e-6:
220             violations += 1
221         Ds.append(D)
222     Ds.sort()
223     return {"n": n, "max": Ds[-1], "p99": Ds[int(0.99 * n)], "median": Ds[n // 2],

```

```

224         "mean": sum(Ds) / n, "violations_of_Jstar": violations,
225         "Jstar": sol["J"]}]
226
227
228 # -----
229 # 5. baseline comparison
230 # -----
231 def baseline_compare(s1, th1_hat, r_guard=R_MIN, n=3000, seed=99):
232     """
233     Compare the proposed second point with four alternatives under the same
234     random source/error draws:
235     A proposed : the minimax point of this section
236     B perp_800 : 800 m perpendicular to the bearing (a common intuition)
237     C along    : 800 m further along the bearing
238     D random   : a uniformly random point of the guard-feasible set
239     E oracle   : the point at the true source position (upper bound)
240     Metric: mean and 95th percentile of the realised region diameter.
241     """
242     sol = solve_second_point(s1, th1_hat, r_guard=r_guard)
243     gset = sol["gset"]
244     rnd = random.Random(seed)
245     draws = []
246     r_hi = max(r for (r, _, _) in gset)
247     for _ in range(n):
248         r = R_NEAR + 1.0 + (r_hi - R_NEAR - 1.0) * rnd.random()
249         a_true = th1_hat + rnd.uniform(-EPS, EPS)
250         G = (s1[0] + r * math.cos(math.radians(a_true)),
251             s1[1] + r * math.sin(math.radians(a_true)))
252         e1 = rnd.uniform(-EPS, EPS)
253         e2 = rnd.uniform(-EPS, EPS)
254         draws.append((G, e1, e2))
255
256     def eval_point(get_s2):
257         vals = []
258         for (G, e1, e2) in draws:
259             s2 = get_s2(G)
260             if s2 is None:
261                 vals.append(float("inf"))
262                 continue
263             th1_hat_used = th1_hat
264             th2_hat = g.bearing(s2[0], s2[1], G[0], G[1]) + e2
265             res = g.region_from_bearings([s1, s2], [th1_hat_used, th2_hat], EPS)
266             if res["empty"] or not res["bounded"]:
267                 vals.append(float("inf"))
268             else:
269                 vals.append(res["diameter"])
270         vals.sort()
271         fin = [v for v in vals if math.isfinite(v)]
272         return {"mean": sum(fin) / max(len(fin), 1),
273             "p95": vals[int(0.95 * len(vals)) - 1] if vals else float("inf"),
274             "max": vals[-1], "inf_rate": 1.0 - len(fin) / float(len(vals))}
275
276     def pt(b, phi):
277         loc = (b * math.cos(math.radians(phi)), b * math.sin(math.radians(phi)))
278         return local_to_world(loc, s1, th1_hat)
279
280     out = {}
281     out["A_proposed"] = eval_point(lambda G: sol["S2"])
282     out["B_perp_800"] = eval_point(lambda G: pt(800.0, 90.0))
283     out["C_along_800"] = eval_point(lambda G: pt(800.0, 0.0))
284     out["D_random"] = eval_point(
285         lambda G: (random.Random(hash(G) & 0xffff).choice(
286             [p for (_, _, p) in gset]) if gset else None))
287     out["E_oracle"] = eval_point(lambda G: G)
288     out["_solution"] = {"b": sol["b"], "phi": sol["phi"], "J": sol["J"],
289         "S2": sol["S2"]}
290     return out
291
292
293 def main():
294     os.makedirs(OUT, exist_ok=True)
295     s1 = (-420.0, 260.0)
296     th1_hat = 63.0
297     summary = {"s1": s1, "th1_hat": th1_hat}
298
299     print("=== 1) optimal second point, guaranteed detection (r_guard=1000 m) ===")
300     sol = solve_second_point(s1, th1_hat, r_guard=R_MIN)
301     print(" b*=%8.2f m phi*=%+7.2f deg J*=%9.3f m" % (sol["b"], sol["phi"], sol["J"]))
302     print(" worst case uses source at r=%8.2f m, error sign %d"

```

```

303     % (sol["info"]["r"], int(sol["info"]["sign2"])))
304     summary["solution_guard1000"] = {"b": sol["b"], "phi": sol["phi"], "J": sol["J"],
305                                     "S2": sol["S2"],
306                                     "worst_r": sol["info"]["r"],
307                                     "guard_margin": sol["guard_margin"]}
308     mc = monte_carlo_check(sol, s1, th1_hat)
309     print(" Monte-Carlo: median %.2f m, p99 %.2f m, max %.2f m, violations of J*: %d/%d"
310           % (mc["median"], mc["p99"], mc["max"], mc["violations_of_Jstar"], mc["n"]))
311     summary["monte_carlo_guard1000"] = mc
312
313     print("\n=== 2) sensitivity of the optimum to the assumed worst-case radius ===")
314     rows = study_guard_tradeoff(s1, th1_hat)
315     with open(os.path.join(OUT, "q2_guard_tradeoff.csv"), "w", newline="", encoding="utf-8") as f:
316         w = csv.DictWriter(f, fieldnames=list(rows[0].keys()))
317         w.writeheader()
318         for r in rows:
319             w.writerow(r)
320     summary["guard_tradeoff"] = rows
321
322     print("\n=== 3) candidate region (eta sub-level set) ===")
323     cmap = candidate_region_map(s1, th1_hat, R_MIN, sol["J"], eta=0.15)
324     with open(os.path.join(OUT, "q2_candidate_region.csv"), "w", newline="", encoding="utf-8") as f:
325         w = csv.writer(f)
326         w.writerow(["b_m", "phi_deg", "J_m", "in_region_eta15"])
327         for (b, phi, J, ok) in cmap:
328             w.writerow(["%.3f" % b, "%.3f" % phi,
329                         "" if not math.isfinite(J) else "%.4f" % J, ok])
330     ok_pts = [(b, phi) for (b, phi, J, ok) in cmap if ok]
331     if ok_pts:
332         print(" candidate region spans b in [%.0f, %.0f] m, phi in [%.1f, %.1f] deg"
333               % (min(p[0] for p in ok_pts), max(p[0] for p in ok_pts),
334                 min(p[1] for p in ok_pts), max(p[1] for p in ok_pts)))
335         summary["candidate_region_bounds"] = {
336             "b_min": min(p[0] for p in ok_pts), "b_max": max(p[0] for p in ok_pts),
337             "phi_min": min(p[1] for p in ok_pts), "phi_max": max(p[1] for p in ok_pts)}
338
339     print("\n=== 4) baseline comparison ===")
340     bl = baseline_compare(s1, th1_hat)
341     for k, v in bl.items():
342         if k.startswith("_"):
343             continue
344         print(" %-12s mean=%.3f p95=%.3f max=%.3f inf_rate=%.3f"
345               % (k, v["mean"], v["p95"], v["max"], v["inf_rate"]))
346     summary["baselines"] = {k: v for k, v in bl.items() if not k.startswith("_")}
347     summary["baseline_solution"] = bl["_solution"]
348
349     with open(os.path.join(OUT, "q2_summary.json"), "w", encoding="utf-8") as f:
350         json.dump(summary, f, ensure_ascii=False, indent=1)
351     print("\nsaved:", os.path.join(OUT, "q2_summary.json"))
352
353
354 if __name__ == "__main__":
355     main()

```

### 3.3 本地模拟器 simulator.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  simulator.py -- local replica of the official "radio interference source"
5  environment simulator for 2026 CUMCM problem B.
6
7  The official simulator (downloadable only from the competition's Baidu-Netdisk
8  link, GUI + online registration required) could not be obtained in this
9  environment, therefore this module re-implements the documented behaviour
10 exactly as specified by 附件1 (simulator manual) and 附件2 (HTTP+JSON protocol):
11
12 * POST /enter /measure /clear /exit on http://127.0.0.1:<port>
13 * virtual clock: measure = move/5 + channel_switch(1 s if changed) + 5 s
14                   clear = move/5 + (5 s if cleared else 3 s)
15 * move is implied by the position of the previous accepted action
16 * /clear does NOT change the current channel
17 * measure results: no_signal | near (<=5 m and inside coverage) | direction
18 * bearing error: bounded by +1 deg, FIXED for a given location (the local
19   electromagnetic environment does not change), so repeating a measurement at

```

```

20     the same point returns the same reading
21 * effective reception radius per source: uniform in [1000, 1500] m
22 * omni sources radiate in 360 deg; directional sources radiate in the 180 deg
23   sector centred on their direction
24 * clear radius 20 m, independent of the radiation pattern
25 * request_id idempotency, strict field checking, HTTP status codes
26
27 Two entry points are provided:
28 * class Arena      -- pure python API (used for massive Monte-Carlo runs)
29 * serve(port, ...) -- HTTP server implementing the protocol of 附件2
30                   (used for the formal tests, identical to the
31                   official interface, producing log files)
32 """
33
34 import json
35 import math
36 import os
37 import random
38 import threading
39 import time
40 import zlib
41 from http.server import BaseHTTPRequestHandler, ThreadingHTTPServer
42
43 ARENA_RADIUS = 1800.0
44 SPEED = 5.0          # m/s
45 MEASURE_TIME = 5.0   # s
46 SWITCH_TIME = 1.0    # s
47 CLEAR_TIME_HIT = 5.0  # s (optical 3 s + laser 2 s)
48 CLEAR_TIME_MISS = 3.0 # s (optical only)
49 NEAR_RADIUS = 5.0     # m
50 CLEAR_RADIUS = 20.0   # m
51 R_EFF_LO, R_EFF_HI = 1000.0, 1500.0
52 MAX_VIRTUAL_DURATION = 360000.0
53 MAX_REAL_DURATION = 1200.0
54 BEARING_ERROR = 1.0   # deg, bounded and location dependent
55 ARENA_ID = "default"
56
57
58 # -----
59 # a single interference source
60 # -----
61 class Source(object):
62     def __init__(self, channel, x, y, r_eff, kind="omni", direction=None):
63         self.channel = channel
64         self.x = x
65         self.y = y
66         self.r_eff = r_eff
67         self.kind = kind          # "omni" or "directional"
68         self.direction = direction # deg, None for omni
69         self.cleared = False
70
71     def pos(self):
72         return (self.x, self.y)
73
74     def covers(self, px, py):
75         """Is the point inside the radiation sector (angular condition only)?"""
76         if self.kind == "omni":
77             return True
78         vx, vy = px - self.x, py - self.y
79         if vx * vx + vy * vy < 1e-18:
80             return True
81         a = math.radians(self.direction)
82         # sector = +-90 deg around the direction vector
83         return (vx * math.cos(a) + vy * math.sin(a)) >= 0.0
84
85
86 def make_case(rng, n_sources=None, n_channels=20, kind_mix=0.0, r_eff_lo=R_EFF_LO,
87              r_eff_hi=R_EFF_HI, radius=ARENA_RADIUS, min_sep=0.0):
88     """
89     Random test case. kind_mix = probability that a source is directional.
90     Returns the list of sources (channels are distinct by construction).
91     """
92     if n_sources is None:
93         n_sources = rng.randint(10, 16)
94     chans = rng.sample(range(1, n_channels + 1), n_sources)
95     sracs = []
96     guard = 0
97     while len(sracs) < n_sources and guard < 20000:
98         guard += 1

```

```

99     a = 2.0 * math.pi * rng.random()
100     r = radius * math.sqrt(rng.random())
101     x, y = r * math.cos(a), r * math.sin(a)
102     if min_sep > 0 and any(math.hypot(x - s.x, y - s.y) < min_sep for s in srcs):
103         continue
104     kind = "directional" if rng.random() < kind_mix else "omni"
105     direc = rng.uniform(0.0, 360.0) if kind == "directional" else None
106     srcs.append(Source(chans[len(srcs)], x, y, rng.uniform(r_eff_lo, r_eff_hi),
107                     kind, direc))
108     return srcs
109
110
111 def _round_within_error(value, truth, bound):
112     """
113     Round `value` to two decimals without letting the deviation from `truth`
114     exceed `bound`. Rounding alone can push a value that sits exactly on the
115     limit a few thousandths of a degree outside it, which would violate the
116     +-1 deg guarantee of attachment 1.
117     """
118     v = round(value, 2)
119     d = ((v - truth + 180.0) % 360.0) - 180.0
120     while abs(d) > bound and abs(round(d, 6)) > 0.0:
121         v = round(v - math.copysign(0.01, d), 2)
122         d = ((v - truth + 180.0) % 360.0) - 180.0
123     return v
124
125
126 def _loc_error(px, py, channel):
127     """
128     Bounded, location dependent bearing error in [-1, 1] deg.
129     Identical for repeated measurements at the same (rounded) location, which
130     reproduces the assumption of the problem statement.
131     """
132     key = "%.2f|%.2f|%.2f" % (round(px, 2), round(py, 2), channel)
133     h = zlib.crc32(key.encode("utf-8")) & 0xFFFFFFFF
134     return -BEARING_ERROR + 2.0 * BEARING_ERROR * (h / 4294967295.0)
135
136
137 # -----
138 # the arena (pure python API, mirrors the HTTP protocol one-to-one)
139 # -----
140 class Arena(object):
141     def __init__(self, sources, log_path=None, seed=0):
142         self.sources = list(sources)
143         self.by_channel = {}
144         for s in self.sources:
145             self.by_channel[s.channel] = s
146         self.virtual_time = 0.0
147         self.pos = (0.0, 0.0)
148         self.channel = 1
149         self.robot_id = None
150         self.started = False
151         self.finished = False
152         self.n_measure = 0
153         self.n_clear = 0
154         self.n_clear_hit = 0
155         self.n_switch = 0
156         self.n_no_signal = 0
157         self.travel = 0.0
158         self.log_path = log_path
159         self.seed = seed
160         self._rid_cache = {}
161         self.log_handle = None
162         if log_path:
163             self.log_handle = open(log_path, "w", encoding="utf-8")
164
165     # ---- logging -----
166     def _log(self, record):
167         if self.log_handle is not None:
168             self.log_handle.write(json.dumps(record, ensure_ascii=False) + "\n")
169             self.log_handle.flush()
170
171     def close(self):
172         if self.log_handle is not None:
173             self.log_handle.close()
174             self.log_handle = None
175
176     # ---- helpers -----
177     def _step(self, target):

```

```

178     """Advance the virtual clock for the movement towards `target`."""
179     d = math.hypot(target[0] - self.pos[0], target[1] - self.pos[1])
180     t = d / SPEED
181     self.travel += d
182     self.pos = (float(target[0]), float(target[1]))
183     self.virtual_time += t
184     return d, t
185
186 def cleared_count(self):
187     return sum(1 for s in self.sources if s.cleared)
188
189 def stats(self):
190     n_total = len(self.sources)
191     n_clr = self.cleared_count()
192     return {
193         "n_sources": n_total,
194         "n_cleared": n_clr,
195         "clear_ratio": (n_clr / float(n_total)) if n_total else 0.0,
196         "mean_time": (self.virtual_time / n_clr) if n_clr else float("inf"),
197         "virtual_time": self.virtual_time,
198         "travel_m": self.travel,
199         "n_measure": self.n_measure,
200         "n_clear": self.n_clear,
201         "n_switch": self.n_switch,
202         "n_no_signal": self.n_no_signal,
203     }
204
205 # ---- the four actions -----
206 def enter(self, robot_id, request_id):
207     if self.started:
208         return self._reject()
209     self.started = True
210     if self.robot_id is None:
211         # the official runtime knows the team; binding on the first enter
212         # reproduces that, so a later different id is rejected
213         self.robot_id = robot_id
214     rec = {"t": 0.0, "action": "enter", "pos": list(self.pos),
215           "channel": self.channel, "request_id": request_id}
216     self._log(rec)
217     return {"accepted": True, "virtual_time_s": self.virtual_time,
218           "max_virtual_duration_s": MAX_VIRTUAL_DURATION,
219           "max_real_duration_s": MAX_REAL_DURATION,
220           "remaining_real_duration_s": MAX_REAL_DURATION}
221
222 def exit(self, robot_id, request_id):
223     if not self.started:
224         return self._reject()
225     self.finished = True
226     self._log({"t": self.virtual_time, "action": "exit",
227             "pos": list(self.pos), "channel": self.channel,
228             "request_id": request_id})
229     return {"accepted": True, "virtual_time_s": self.virtual_time,
230           "exit_reason": "user_exit"}
231
232 def measure(self, robot_id, request_id, position, channel):
233     if not self.started or self.finished:
234         return self._reject()
235     channel = int(channel)
236     target = (float(position["x"]), float(position["y"]))
237     moved, move_t = self._step(target)
238     switch = 0.0
239     if channel != self.channel:
240         switch = SWITCH_TIME
241         self.n_switch += 1
242     self.channel = channel
243     self.virtual_time += switch + MEASURE_TIME
244     self.n_measure += 1
245
246     src = self.by_channel.get(channel)
247     result = "no_signal"
248     svd = None
249     dist = None
250     if src is not None and not src.cleared:
251         dist = math.hypot(target[0] - src.x, target[1] - src.y)
252         if dist <= src.r_eff and src.covers(target[0], target[1]):
253             if dist <= NEAR_RADIUS:
254                 result = "near"
255             else:
256                 result = "direction"

```

```

257         true_brg = math.degrees(math.atan2(src.y - target[1],
258                                             src.x - target[0])) % 360.0
259         svd = (true_brg + _loc_error(target[0], target[1], channel)) % 360.0
260         svd = _round_within_error(svd, true_brg, BEARING_ERROR)
261         if result == "no_signal":
262             self.n_no_signal += 1
263
264         out = {"accepted": True, "virtual_time_s": self.virtual_time,
265               "measure_result": result}
266         if svd is not None:
267             out["svd_deg"] = svd
268         self._log({"t": self.virtual_time, "action": "measure",
269                  "pos": list(target), "channel": channel,
270                  "move_m": moved, "move_s": move_t, "switch_s": switch,
271                  "result": result, "svd_deg": svd, "request_id": request_id,
272                  "n_cleared": self.cleared_count()})
273         return out
274
275     def clear(self, robot_id, request_id, position, channel):
276         if not self.started or self.finished:
277             return self._reject()
278         channel = int(channel)
279         target = (float(position["x"]), float(position["y"]))
280         moved, move_t = self._step(target)
281         self.n_clear += 1
282
283         src = self.by_channel.get(channel)
284         hit = False
285         if src is not None and not src.cleared:
286             if math.hypot(target[0] - src.x, target[1] - src.y) <= CLEAR_RADIUS:
287                 src.cleared = True
288                 hit = True
289         self.virtual_time += CLEAR_TIME_HIT if hit else CLEAR_TIME_MISS
290         if hit:
291             self.n_clear_hit += 1
292         out = {"accepted": True, "virtual_time_s": self.virtual_time,
293               "clear_result": "success" if hit else "no_target_in_range"}
294         self._log({"t": self.virtual_time, "action": "clear",
295                  "pos": list(target), "channel": channel,
296                  "move_m": moved, "move_s": move_t,
297                  "result": out["clear_result"], "request_id": request_id,
298                  "n_cleared": self.cleared_count()})
299         return out
300
301     def _reject(self):
302         return {"accepted": False, "virtual_time_s": 0.0}
303
304
305     # -----
306     # HTTP layer (mirrors 附件2 exactly)
307     # -----
308     class _State(object):
309         def __init__(self):
310             self.arena = None
311             self.robot_id = None
312
313     class _Handler(BaseHTTPRequestHandler):
314         protocol_version = "HTTP/1.1"
315         server_version = "LocalArenaSim/1.0"
316
317         def log_message(self, fmt, *args):
318             pass # keep the console clean
319
320         # ---- utilities -----
321         def _send(self, code, obj):
322             body = json.dumps(obj, ensure_ascii=False).encode("utf-8")
323             self.send_response(code)
324             self.send_header("Content-Type", "application/json; charset=utf-8")
325             self.send_header("Content-Length", str(len(body)))
326             self.end_headers()
327             self.wfile.write(body)
328
329         def _err(self, self, code, msg):
330             st = self.server.state
331             vt = st.arena.virtual_time if st.arena else 0.0
332             self._send(code, {"accepted": False,
333                               "real_timestamp_ms": int(time.time() * 1000),
334                               "virtual_time_s": vt, "error": msg})
335

```

```

336
337 def do_POST(self):
338     st = self.server.state
339     path = self.path
340     if path not in ("/enter", "/measure", "/clear", "/exit"):
341         return self._err(404, "unknown path")
342     ctype = self.headers.get("Content-Type", "")
343     if not ctype.lower().startswith("application/json"):
344         return self._err(415, "content type")
345     ce = self.headers.get("Content-Encoding", "identity")
346     if ce.lower() not in ("", "identity"):
347         return self._err(415, "content encoding")
348     try:
349         n = int(self.headers.get("Content-Length", "0"))
350     except ValueError:
351         return self._err(400, "bad length")
352     if n > 65536:
353         return self._err(413, "body too large")
354     raw = self.rfile.read(n)
355     try:
356         body = json.loads(raw.decode("utf-8"))
357     except Exception:
358         return self._err(400, "bad json")
359     if not isinstance(body, dict):
360         return self._err(400, "body must be an object")
361
362     allowed = {"enter": {"arena_id", "robot_id", "request_id"},
363               "measure": {"arena_id", "robot_id", "request_id", "position", "channel"},
364               "clear": {"arena_id", "robot_id", "request_id", "position", "channel"},
365               "exit": {"arena_id", "robot_id", "request_id"}}[path[1:]]
366     if set(body.keys()) - allowed:
367         return self._send(200, {"accepted": False,
368                                "real_timestamp_ms": int(time.time() * 1000),
369                                "virtual_time_s": 0.0})
370     for f in ("arena_id", "robot_id", "request_id"):
371         if f not in body:
372             return self._err(400, "missing " + f)
373     if body["arena_id"] != ARENA_ID:
374         return self._send(200, {"accepted": False,
375                                "real_timestamp_ms": int(time.time() * 1000),
376                                "virtual_time_s": 0.0})
377     # the id is either fixed at launch or bound by the first /enter
378     bound = st.robot_id
379     if bound is None and st.arena is not None:
380         bound = getattr(st.arena, "robot_id", None)
381     if bound is not None and body["robot_id"] != bound:
382         return self._send(200, {"accepted": False,
383                                "real_timestamp_ms": int(time.time() * 1000),
384                                "virtual_time_s": 0.0})
385     if path in ("/measure", "/clear"):
386         if "position" not in body or "channel" not in body:
387             return self._err(400, "missing position/channel")
388         p = body["position"]
389         if not isinstance(p, dict) or "x" not in p or "y" not in p:
390             return self._err(400, "bad position")
391         if set(p.keys()) - {"x", "y"}:
392             return self._send(200, {"accepted": False,
393                                    "real_timestamp_ms": int(time.time() * 1000),
394                                    "virtual_time_s": 0.0})
395         for k in ("x", "y"):
396             v = p[k]
397             if isinstance(v, bool) or not isinstance(v, (int, float)):
398                 return self._err(400, "bad coordinate")
399             if not math.isfinite(v) or abs(v) > 2000000:
400                 return self._err(400, "coordinate range")
401         c = body["channel"]
402         if isinstance(c, bool) or not isinstance(c, (int, float)):
403             return self._err(400, "bad channel")
404         if float(c) != int(c) or not (1 <= int(c) <= 20):
405             return self._err(400, "channel range")
406
407     # idempotency
408     rid = body["request_id"]
409     key = (path, rid)
410     if key in st.arena._rid_cache:
411         return self._send(200, st.arena._rid_cache[key])
412
413     if st.arena is None:
414         return self._err(400, "arena not ready")

```

```

415     try:
416         if path == "/enter":
417             resp = st.arena.enter(body["robot_id"], rid)
418         elif path == "/measure":
419             resp = st.arena.measure(body["robot_id"], rid, body["position"],
420                                     int(body["channel"]))
421         elif path == "/clear":
422             resp = st.arena.clear(body["robot_id"], rid, body["position"],
423                                   int(body["channel"]))
424         else:
425             resp = st.arena.exit(body["robot_id"], rid)
426     except Exception as exc:
427         # pragma: no cover
428         return self._err(500, str(exc))
429     resp = dict(resp)
430     resp["real_timestamp_ms"] = int(time.time() * 1000)
431     st.arena._rid_cache[key] = resp
432     return self._send(200, resp)
433
434 class ArenaHTTPServer(ThreadingHTTPServer):
435     daemon_threads = True
436     allow_reuse_address = True
437
438
439 def serve(port=2026, sources=None, log_path=None, robot_id=None, seed=0,
440          ready_file=None):
441     """Start the HTTP simulator (blocking). Returns nothing."""
442     arena = Arena(sources if sources is not None else make_case(random.Random(seed)),
443                  log_path=log_path, seed=seed)
444     st = _State()
445     st.arena = arena
446     st.robot_id = robot_id
447     srv = ArenaHTTPServer(("127.0.0.1", port), _Handler)
448     srv.state = st
449     if ready_file:
450         with open(ready_file, "w", encoding="utf-8") as f:
451             f.write(str(port))
452     try:
453         srv.serve_forever()
454     except KeyboardInterrupt:
455         pass
456     finally:
457         arena.close()
458
459
460 def run_server_thread(port=2026, sources=None, log_path=None, robot_id=None, seed=0):
461     arena = Arena(sources if sources is not None else make_case(random.Random(seed)),
462                  log_path=log_path, seed=seed)
463     st = _State()
464     st.arena = arena
465     st.robot_id = robot_id
466     srv = ArenaHTTPServer(("127.0.0.1", port), _Handler)
467     srv.state = st
468     th = threading.Thread(target=srv.serve_forever, daemon=True)
469     th.start()
470     return srv, arena
471
472
473 if __name__ == "__main__":
474     import argparse
475     ap = argparse.ArgumentParser()
476     ap.add_argument("--port", type=int, default=2026)
477     ap.add_argument("--seed", type=int, default=0)
478     ap.add_argument("--log", default=None)
479     ap.add_argument("--robot-id", default=None)
480     ap.add_argument("--dir-mix", type=float, default=0.0)
481     ap.add_argument("--n", type=int, default=0)
482     a = ap.parse_args()
483     rng = random.Random(a.seed)
484     srcs = make_case(rng, n_sources=(a.n or None), kind_mix=a.dir_mix)
485     print("case: %d sources (%d directional)"
486           % (len(srcs), sum(1 for s in srcs if s.kind == "directional")))
487     serve(port=a.port, sources=srcs, log_path=a.log, robot_id=a.robot_id, seed=a.seed)

```

### 3.4 机器狗策略内核 robot\_core.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  robot_core.py -- robot-dog client + search/localisation/clearance strategy for
5  problems 3 (all omni sources) and 4 (mixed omni + directional sources).
6
7  The client speaks the HTTP+JSON protocol of 附件2 (four actions /enter, /measure,
8  /clear, /exit, one new request_id per action, retry with the same request_id on
9  network failure). A local in-process adapter exposing the same three methods is
10 provided so that thousands of Monte-Carlo runs can be executed quickly.
11
12 Strategy ("census - opportunistic triangulation - homing - verification"):
13
14 phase A census : measure every channel at the entry point; each detected
15                 channel yields one bearing ray.
16 phase B task loop : repeatedly execute the cheapest useful task
17                     * CLEAR(c) : a located source, cleared by bearing
18                               homing with the Q2 geometry rule,
19                     * LOCALISE(c): obtain a second bearing for a channel
20                               that is detected but not yet located,
21                               from the Q2-optimal vantage point,
22                     * PROBE(p) : drive to a survey stop of a triangular
23                               lattice and measure the unresolved
24                               channels (this both discovers hidden
25                               sources and, together with the
26                               verification test, certifies channels
27                               that do not exist).
28 phase C verification: a channel is certified empty when the positions at which
29                       it returned "no_signal" prevent any source from hiding
30                       (omni: a 1000 m cover; directional: the "no direction
31                       can hide" test of section 4 of the paper).
32 """
33
34 import json
35 import math
36 import os
37 import random
38 import time
39
40 import geom_core as g
41 import simulator as sim
42
43 EPS = 1.0
44 ARENA_R = 1800.0
45 R_MIN = 1000.0
46 R_MAX = 1500.0
47 SPEED = 5.0
48 VANTAGE_B = 1000.0      # Q2 result: |S1S2| ~ R_min
49 VANTAGE_PHI = 37.0      # Q2 result: +-37 deg off the measured bearing
50
51
52 # =====
53 # clients
54 # =====
55 class HTTPClient(object):
56     """Thin HTTP client for the simulator interface (附件2)."""
57
58     def __init__(self, robot_id, port=2026, host="127.0.0.1", timeout=15.0):
59         self.robot_id = robot_id
60         self.base = "http://%s:%d" % (host, port)
61         self.timeout = timeout
62         self.n_requests = 0
63         self.t_wall = 0.0
64         self._session = None
65
66     def _post(self, path, payload, request_id):
67         import requests
68         body = dict(payload)
69         body["arena_id"] = "default"
70         body["robot_id"] = self.robot_id
71         body["request_id"] = request_id
72         t0 = time.time()
73         last = None
74         for attempt in range(4):
75             try:
76                 r = requests.post(self.base + path, json=body,
77                                 headers={"Content-Type": "application/json; charset=utf-8"},
78                                 timeout=self.timeout)
79                 self.n_requests += 1

```

```

80         self.t_wall += time.time() - t0
81         if r.status_code != 200:
82             raise RuntimeError("HTTP %d: %s" % (r.status_code, r.text[:200]))
83         js = r.json()
84         if not js.get("accepted", False):
85             raise RuntimeError("rejected: %s" % json.dumps(js)[:200])
86         return js
87     except Exception as exc:          # retry the SAME request
88         last = exc
89         time.sleep(0.05 * (attempt + 1))
90         raise RuntimeError("request failed: %s" % last)
91
92     def enter(self, rid="enter-1"):
93         return self._post("/enter", {}, rid)
94
95     def exit(self, rid="exit-1"):
96         return self._post("/exit", {}, rid)
97
98     def measure(self, request_id, x, y, channel):
99         return self._post("/measure", {"position": {"x": float(x), "y": float(y)},
100                                         "channel": int(channel)}, request_id)
101
102     def clear(self, request_id, x, y, channel):
103         return self._post("/clear", {"position": {"x": float(x), "y": float(y)},
104                                         "channel": int(channel)}, request_id)
105
106
107 class LocalClient(object):
108     """In-process adapter with the same call signature as HTTPClient."""
109
110     def __init__(self, arena, robot_id="local-team"):
111         self.arena = arena
112         self.robot_id = robot_id
113         self.n_requests = 0
114         self.t_wall = 0.0
115         self._k = 0
116         self.sources = arena.sources
117
118     def _rid(self, tag):
119         self._k += 1
120         return "%s-%d" % (tag, self._k)
121
122     def enter(self, rid=None):
123         return self.arena.enter(self.robot_id, rid or self._rid("enter"))
124
125     def exit(self, rid=None):
126         return self.arena.exit(self.robot_id, rid or self._rid("exit"))
127
128     def measure(self, request_id, x, y, channel):
129         self.n_requests += 1
130         return self.arena.measure(self.robot_id, request_id or self._rid("m"),
131                                   {"x": x, "y": y}, channel)
132
133     def clear(self, request_id, x, y, channel):
134         self.n_requests += 1
135         return self.arena.clear(self.robot_id, request_id or self._rid("c"),
136                                 {"x": x, "y": y}, channel)
137
138
139 # =====
140 # helpers used by the verification test
141 # =====
142 def _origin_inside_hull(points, tol=1e-9):
143     """
144     Strict positive-spanning test: is the origin in the INTERIOR of the convex
145     hull of `points`? Equivalently: no open half plane through the origin
146     contains all the points, i.e. no radiation sector can hide a source.
147     """
148     pts = [(round(p[0], 6), round(p[1], 6)) for p in points]
149     pts = list(set(pts))
150     if len(pts) < 3:
151         return False
152     hull = g.convex_hull(pts)
153     if len(hull) < 3:
154         return False
155     # the origin must be strictly left of every directed hull edge
156     n = len(hull)
157     for i in range(n):
158         a = hull[i]

```

```

159     b = hull[(i + 1) % n]
160     cr = (b[0] - a[0]) * (0.0 - a[1]) - (b[1] - a[1]) * (0.0 - a[0])
161     if cr <= tol:
162         return False
163     return True
164
165
166 # =====
167 # robot brain
168 # =====
169 DEFAULT_PARAMS = {
170     "policy": "planned", # "planned" (covering tour + TSP) or "greedy"
171     "census": True, # measure all 20 channels at the entry point
172     "probe_spacing": 650.0, # go at least this far before probing again
173     "probe_min_angle": 22.0, # min predicted intersection angle to re-measure
174     "locate_sigma": 320.0, # uncertainty radius accepted as "located"
175     "term_iters": 9, # iterations of the terminal homing loop
176     "term_cap": 420.0, # max length of one homing step
177     "clear_try_radius": 42.0, # try the clear action when the estimate is this close
178     "endgame_radius": 90.0, # switch to the local clear pattern below this
179     "endgame_step": 11.0, # spacing of the local clear pattern
180     "sweep_center_first": True, # try the estimate centre before the ring
181     "orient_belief": False, # 定向源朝向硬约束可行集 (自主设计的改进)
182     "orient_bins": 24, # 朝向分箱数 (24 = 每箱 15 度)
183     "orient_len": 350.0, # 前向侧取数点的距离
184     "survey_max_r": 1800.0, # truncate the certification lattice radius
185     "vantage_b": VANTAGE_B,
186     "vantage_phi": VANTAGE_PHI,
187     "vantage_b_local": 550.0, # short oblique offset used when no covering
188     "vantage_phi_local": 55.0, # stop is pending
189     "vantage_max_tries": 3,
190     "survey_spacing": 1000.0, # lattice spacing of the survey stops
191     "survey_mode": "ring", # "ring" (problem 3) or "lattice" (problem 4)
192     "search_cost_bias": 60.0, # seconds of "fixed cost" per search stop
193     "use_ring": True, # force the planned search stops
194     "ring_radius": 1280.0, # radius of the primary covering ring
195     "ring_n": 6, # number of stops on that ring (6 = hexagon)
196     "ring_rotation": 0.0, # rotation (deg) of the covering hexagon
197     "max_attempts": 6, # per-channel budget of clear attempts
198     "hard_attempt_cap": 24, # absolute cap of clear attempts per channel
199     # (raised: the exhaustive fallback now
200     # guarantees convergence on located sources)
201     "progress_ratio": 0.7, # a better localisation re-opens the budget
202     "clear_bonus": 260.0, # task priority bonus (seconds)
203     "localise_bonus": 120.0,
204     "probe_bonus": 150.0,
205     "max_channels_probe": 20,
206     "dir_search_r": 60.0, # re-acquisition radius around an estimate
207     "oracle_count": False, # debug only
208     # verification test
209     "verify_grid": 60.0, # spacing (m) of the certification lattice
210     "verify_margin": 90.0, # candidates closer to the rim than this
211     # are excluded: they can never be certified
212     # with in-domain readings (theorem 2)
213     "verify_r": R_MIN, # guaranteed reception radius used for the test
214     "rim_patrol": False, # visit points just outside the rim when a
215     # candidate location cannot be certified inside
216     "rim_step": 130.0, # radial offset (m) of those outside samples
217     "rim_max_pts": 9, # cap on outside samples per search step
218     "max_rim_patrols": 12, # total number of outside sampling trips
219     "oropt_limit": 12, # Or-opt prefix used when re-planning often
220     "oropt_limit_batch": 60, # ... and when re-planning rarely (batch mode)
221     "replan_mode": "each", # MEASURED NEGATIVE: re-plan after every task
222     # beats committing to a stale tour
223     "adaptive_batch": 4, # 自适应采样一次取几个候选站位交给巡回规划
224     "rim_ring_n": 0, # 贴边环: 在 r=rim_ring_r 上补 n 个站位,
225     # 专门发现"朝外辐射"的贴边定向源
226     "rim_ring_r": 1750.0,
227     "spread_stops": True, # order the survey stops by farthest-point
228     # sampling, so a cap keeps the arena covered
229     "max_survey_stops": 0, # cap on the number of primary survey stops
230     # (0 = no cap); an explicit time/ratio knob
231     "periodic_cert": True, # evaluate the certificate during the sweep so
232     # that certified channels stop being measured
233     "periodic_cert_every": 2, # ... after every N covering stops
234     "cert_heard_channels": False, # certification also covers channels that
235     # were already heard (wasteful: measured 18
236     # extra stops per case), kept as a switch
237     "phase_separate": False, # MEASURED NEGATIVE (see the report): clearing

```

```

238         # early removes channels from the certification
239         # burden, so the phases must stay interleaved
240         "perp_step": 80.0, # endgame perpendicular vantage offset (m)
241         "perp_sigma": 26.0, # only when sigma is still above this
242         "perp_max": 3, # cap on perpendicular cuts per channel
243         "enroute_clear": False, # C1 measured NEUTRAL (881.3 vs 882.2 s over
244         # 24 cases): the priority bonus already
245         # captures that coupling
246         "enroute_radius": 260.0, # detour budget (m)
247         "adaptive_probe": True, # C2: shrink the probe interval while many
248         "probe_spacing_busy": 320.0, # channels are still unresolved
249         "busy_channels": 5, # "many" = this many unresolved
250         "vantage_short_step": 35.0, # MEASURED NEGATIVE, see the report: unused
251         "skip_useless_stops": True, # 邻域已被完全认证的普查站位直接跳过
252         "leg_probe_step": 0.0, # 长距离移动的分段长度 (m); >0 时途中顺带测量
253         "leg_probe_max_channels": 8, # 每个中间测点最多测几个频道
254         "enroute_clear": False, # MEASURED NEGATIVE (24 cases): 1.0000 -> 0.9946
255         # and 540.3 -> 573.3 s; the opportunistic clear
256         # interrupts the sweep and its own homing costs
257         # more than the detour it saves
258         "enroute_radius": 520.0, # "附近"的半径 (m)
259         "skip_certified": True, # 站位附近已全部认证的频道不再测量
260         "exhaustive_clear": True, # 未段兜底: 圆盘上栅格穷举清除
261         "exhaustive_grid": 15.0, # 栅格间距 (m):  $15/\sqrt{2} = 10.6 < 20$  m 保证覆盖
262         "exhaustive_after": 2, # 常规未段连续失败几次后启用
263         "exhaustive_cap": 80, # 单次穷举的清除动作上限
264         "relocate": True, # 单条方位的频道: 横向偏移二分 + 沿射线爬行
265         "relocate_deltas": [400.0, 250.0, 150.0, 90.0, 55.0, 33.0, 20.0],
266         "relocate_crawls": 4, # 全部偏移失败后沿射线前进的次数
267         "relocate_crawl_step": 200.0,
268         "relocate_sigma": 900.0, # 估计 sigma 大于此值仍视为"未定位"
269         "vantage_step_onray": 200.0, # creep along the ray instead of jumping
270         "vantage_onray_bisect": True, # retreat and halve when the signal is lost
271         "vantage_onray_tries": 16, # hop budget while creeping
272         "vantage_onray": True, # shrink the 2nd-station offset and finally
273         # go on the bearing ray (rim sources)
274         "no_plain_fallback": True, # directional runs: do not travel for a stop
275         # that cannot complete a certificate
276         "outer_ring_gap": 0.0, # distance of the outside ring beyond the rim
277         # (0 disables it; it makes the verification of
278         # rim positions possible but costs a lot of
279         # travel, see the discussion in the paper)
280         "max_search_stops": 40, # safety cap on the additional search stops
281     }
282
283
284 class Brain(object):
285     def __init__(self, client, params=None, arena_radius=ARENA_R, verbose=False,
286                 seed=0):
287         self.cl = client
288         self.p = dict(DEFAULT_PARAMS)
289         if params:
290             self.p.update(params)
291         self.arena_r = arena_radius
292         self.verbose = verbose
293         self.rng = random.Random(seed)
294
295         self.channels = list(range(1, 21))
296         self.obs = dict((c, []) for c in self.channels) # [(x, y, bearing)]
297         self.nosig = dict((c, []) for c in self.channels) # [(x, y)] no_signal
298         self.status = dict((c, "unknown") for c in self.channels)
299         self.est = dict((c, None) for c in self.channels) # (x, y, sigma)
300         self.near_hits = dict((c, 0) for c in self.channels)
301         self.measure_points = dict((c, set()) for c in self.channels)
302         self.vantage_tries = dict((c, 0) for c in self.channels)
303         self.attempts = dict((c, 0) for c in self.channels)
304         self.last_attempt_sigma = dict((c, None) for c in self.channels)
305         self.total_attempts = dict((c, 0) for c in self.channels)
306         self.last_seen = dict((c, None) for c in self.channels)
307         self.meas_cache = {}
308         nb = int(self.p.get("orient_bins", 24) or 24)
309         # 朝向可行集: 每个频道一组仍可行的朝向分箱
310         self.orient_ok = dict((c, set(range(nb))) for c in self.channels)
311
312         self.pos = (0.0, 0.0)
313         self.vtime = 0.0
314         self.cur_channel = 1
315         self.rid = 0
316         self.last_probe_pos = None

```

```

317     self.visited_stops = set()
318     self.rim_patrols = 0
319     self.perp_tries = {}
320     self.last_attempt_obs = {}
321     self.onray_scale = {}
322     self.onray_tries = {}
323     self.reloc = {}
324     self.survey_stops = self._make_survey_stops()
325     self._stops_cache = None
326     self.trace = []
327     self.fail_log = []
328     self._task_travel = {"clear": 0.0, "localise": 0.0, "probe": 0.0, "census": 0.0}
329     self._task_count = {"clear": 0, "localise": 0, "probe": 0, "census": 0}
330     self._task_time = {"clear": 0.0, "localise": 0.0, "probe": 0.0, "census": 0.0}
331     self._cur_task = "census"
332
333     # ----- utils
334     def _rid_new(self, tag):
335         self.rid += 1
336         return "%s-%d" % (tag, self.rid)
337
338     def _dist(self, a, b):
339         return math.hypot(a[0] - b[0], a[1] - b[1])
340
341     def _inside(self, p, margin=0.0):
342         return math.hypot(p[0], p[1]) <= self.arena_r + margin
343
344     def _clip_to_arena(self, p):
345         r = math.hypot(p[0], p[1])
346         if r <= self.arena_r:
347             return p
348         k = self.arena_r / r
349         return (p[0] * k, p[1] * k)
350
351     def _make_survey_stops(self, spacing=None):
352         """Triangular lattice of survey stops covering the arena.
353
354         `survey_max_r` (default = arena radius) truncates the lattice: only the
355         region that actually has to be certified needs the multi-directional
356         coverage a lattice provides, so the outer shell can be dropped when a
357         separate mechanism (the rim ring) covers it.
358         """
359         s = self.p["survey_spacing"] if spacing is None else spacing
360         rmax = float(self.p.get("survey_max_r", self.arena_r))
361         stops = []
362         ny = int(self.arena_r / (s * math.sqrt(3.0) / 2.0)) + 2
363         nx = int(2 * self.arena_r / s) + 2
364         for iy in range(-ny, ny + 1):
365             y = iy * s * math.sqrt(3.0) / 2.0
366             for ix in range(-nx, nx + 1):
367                 x = ix * s + (s / 2.0 if iy % 2 else 0.0)
368                 rr = math.hypot(x, y)
369                 if rr <= self.arena_r + 1e-9 and rr <= rmax + 1e-9:
370                     stops.append((x, y))
371         stops.sort(key=lambda p: math.hypot(p[0], p[1]))
372         return stops
373
374     def _spread_order(self, pts):
375         """
376         Farthest-point ordering: start at the point nearest the origin, then
377         repeatedly append the point farthest from everything chosen so far.
378
379         Truncating this list to N stops therefore keeps the arena evenly covered,
380         whereas truncating the radius-sorted list would drop the outer ring -- the
381         only chance of finding a source near the rim.
382         """
383         rest = [tuple(q) for q in pts]
384         if not rest:
385             return []
386         first = min(rest, key=lambda q: q[0] * q[0] + q[1] * q[1])
387         order = [first]
388         rest.remove(first)
389         while rest:
390             nxt = max(rest, key=lambda q: min(
391                 (q[0] - a[0]) ** 2 + (q[1] - a[1]) ** 2 for a in order))
392             order.append(nxt)
393             rest.remove(nxt)
394         return order
395

```

```

396 def _all_search_stops(self):
397     """
398     Search lattice in several resolutions: if the coarse lattice cannot rule
399     out every position, a finer one around the remaining hole is used, which
400     keeps the search complete instead of giving up.
401     In addition a ring of positions OUTSIDE the target region is offered.
402     It is indispensable for the mixed problem: a directional source sitting on
403     the rim may radiate outwards, so no measurement taken inside the arena can
404     ever rule it out (all those points lie in one half plane through the
405     source). Measuring from outside the region closes that loophole, and the
406     simulator explicitly accepts positions outside the target area.
407     """
408     if getattr(self, "_stops_cache", None) is None:
409         s = self.p["survey_spacing"]
410         pts = []
411         for lvl in range(2):
412             for p in self._make_survey_stops(s / (2.0 ** lvl)):
413                 pts.append(p)
414             rr = self.arena_r + self.p["outer_ring_gap"]
415             n = int(2.0 * math.pi * rr / max(s, 400.0)) + 6
416             for k in range(n):
417                 a = 2.0 * math.pi * k / n
418                 pts.append((rr * math.cos(a), rr * math.sin(a)))
419             self._stops_cache = pts
420     return self._stops_cache
421
422 def _make_ring_stops(self):
423     """
424     Stops on a circle of radius `ring_radius` (plus the entry point) whose
425     detection disks (radius R_min = 1000 m) cover the whole arena. With
426     `ring_n` = 6 this is the minimal complete-search configuration of the
427     seven-point covering theorem (Kershner 1939); more points keep a larger
428     coverage margin and give better triangulation geometry at the cost of
429     extra legs.
430     """
431     r = self.p["ring_radius"]
432     n = int(self.p.get("ring_n", 6) or 6)
433     a0 = math.radians(self.p["ring_rotation"])
434     return [(r * math.cos(a0 + 2.0 * math.pi * k / n),
435             r * math.sin(a0 + 2.0 * math.pi * k / n)) for k in range(n)]
436
437 # ----- verification
438 def _verify_grid(self):
439     if getattr(self, "_vgrid", None) is None:
440         s = self.p["verify_grid"]
441         lim = self.arena_r - float(self.p.get("verify_margin", 90.0))
442         pts = []
443         ny = int(self.arena_r / s) + 1
444         for iy in range(-ny, ny + 1):
445             y = iy * s
446             for ix in range(-ny, ny + 1):
447                 x = ix * s
448                 if math.hypot(x, y) <= lim:
449                     pts.append((x, y))
450         self._vgrid = pts
451     return self._vgrid
452
453 def certification_scan(self, channels):
454     """
455     Decide, for every channel, whether the readings collected so far prove
456     that no source can be hiding, and collect the arena positions that are
457     not ruled out yet.
458
459     omni : q is ruled out when some reading position p obeys |p-q| <= R,
460           because the source would certainly have been received there.
461     directional (problem 4): a source at q radiates into a 180 deg sector,
462           so q is ruled out only when NO direction u can hide it, i.e.
463           when q lies in the interior of the convex hull of the reading
464           positions inside the R disk (theorem 2).
465
466     The status is maintained incrementally: "ruled out" is monotone (a new
467     reading only enlarges the hull, or turns an empty set into a non empty
468     one), so once a grid point is ruled out it never comes back, and every
469     new reading is only tested against the grid points that are still open.
470
471     Returns (all_certified, uncovered_points, per_channel_flags)
472     """
473     grid = self._verify_grid()
474     slack = self.p["verify_grid"] * 0.7072

```

```

475 R = self.p["verify_r"] - slack
476 R2 = R * R
477 directional = bool(self.p.get("directional", False))
478
479 if getattr(self, "_cert_ruled", None) is None:
480     self._cert_ruled = {}
481     self._cert_open = {}
482     self._cert_done = {}
483
484 for c in channels:
485     ruled = self._cert_ruled.setdefault(c, set())
486     open_ = self._cert_open.setdefault(c, set(range(len(grid))))
487     done = self._cert_done.get(c, 0)
488     fresh = self.nosig[c][done:]
489     if not fresh:
490         continue
491     readings = self.nosig[c]
492     for p in fresh:
493         px, py = p[0], p[1]
494         for gi in list(open_):
495             q = grid[gi]
496             dx, dy = px - q[0], py - q[1]
497             if dx * dx + dy * dy > R2:
498                 continue
499             near = [(r[0] - q[0], r[1] - q[1]) for r in readings
500                    if (r[0] - q[0]) ** 2 + (r[1] - q[1]) ** 2 <= R2]
501             if not near:
502                 continue
503             if not directional or _origin_inside_hull(near):
504                 ruled.add(gi)
505                 open_.discard(gi)
506             self._cert_done[c] = len(readings)
507
508 flags = {}
509 uncovered = []
510 seen = set()
511 for c in channels:
512     open_ = self._cert_open.get(c, set())
513     flags[c] = (len(open_) == 0)
514     if open_:
515         for gi in open_:
516             if gi not in seen:
517                 seen.add(gi)
518                 uncovered.append(grid[gi])
519 return (not uncovered), uncovered, flags
520
521 # ----- actions
522 def _enroute_survey(self, x, y):
523     """
524     On the way to (x, y), stop every `leg_probe_step` metres and measure the
525     channels that have never been heard.
526
527     Those intermediate points cost no extra travel -- the leg is walked
528     anyway -- so they are free sampling positions, and the certificate is
529     exactly what needs readings for the never-heard channels. This is what
530     lets the dedicated survey stops be dropped.
531     """
532     step = float(self.p.get("leg_probe_step", 0.0) or 0.0)
533     if step <= 0.0:
534         return 0
535     x0, y0 = self.pos
536     d = math.hypot(x - x0, y - y0)
537     if d <= 1.5 * step:
538         return 0
539     todo_all = [c for c in self.channels
540                 if not self.obs.get(c)
541                 and self.status.get(c) not in ("cleared", "empty")]
542     if not todo_all:
543         return 0
544     k_max = int(self.p.get("leg_probe_max_channels", 8))
545     n = int(d // step)
546     done = 0
547     for k in range(1, n + 1):
548         t = k * step / d
549         if t >= 0.92 or self.vtime > self.p.get("max_virtual_guard", 1e18):
550             break
551         px, py = x0 + (x - x0) * t, y0 + (y - y0) * t
552         todo = [c for c in self.channels
553                 if not self.obs.get(c)

```

```

554         and self.status.get(c) not in ("cleared", "empty")][:k_max]
555         todo.sort()
556         for c in todo:
557             self.move_measure(px, py, c) # d <= step: no recursion
558             done += 1
559         return done
560
561     def move_measure(self, x, y, channel):
562         """measure action (includes the implied move); returns the result dict"""
563         x = float(max(-2.0e6, min(2.0e6, x)))
564         y = float(max(-2.0e6, min(2.0e6, y)))
565         if self.p.get("leg_probe_step", 0.0):
566             self._enroute_survey(x, y)
567         d = self._dist(self.pos, (x, y))
568         sw = 1.0 if channel != self.cur_channel else 0.0
569         self.vtime += d / SPEED + sw + 5.0
570         self.pos = (x, y)
571         self.cur_channel = channel
572         r = self.cl.measure(self._rid_new("m"), x, y, channel)
573         r["virtual_time_s"] = self.vtime
574         self._task_travel[self._cur_task] += d
575         self._task_time[self._cur_task] += d / SPEED + sw + 5.0
576         self._handle_measure(channel, (x, y), r)
577         self.meas_cache[(channel, (round(x, 2), round(y, 2)))] = r
578         return r
579
580     def move_clear(self, x, y, channel):
581         x = float(max(-2.0e6, min(2.0e6, x)))
582         y = float(max(-2.0e6, min(2.0e6, y)))
583         d = self._dist(self.pos, (x, y))
584         self.vtime += d / SPEED
585         self.pos = (x, y)
586         r = self.cl.clear(self._rid_new("c"), x, y, channel)
587         # virtual cost of a clear action: 5 s on success, 3 s otherwise
588         ct = 5.0 if r["clear_result"] == "success" else 3.0
589         self.vtime += ct
590         self._task_travel[self._cur_task] += d
591         self._task_time[self._cur_task] += d / SPEED + ct
592         if r["clear_result"] == "success":
593             self.status[channel] = "cleared"
594         return r
595
596     def _handle_measure(self, c, pos, r):
597         res = r["measure_result"]
598         key = (round(pos[0], 2), round(pos[1], 2))
599         self.measure_points[c].add(key)
600         if res == "direction":
601             self.obs[c].append((pos[0], pos[1], r["svd_deg"]))
602             self.last_seen[c] = pos
603             if self.status[c] in ("unknown", "empty"):
604                 self.status[c] = "seen"
605         elif res == "near":
606             self.near_hits[c] += 1
607             self.last_seen[c] = pos
608             self.status[c] = "seen"
609         else:
610             self.nosig[c].append((pos[0], pos[1]))
611
612     # ----- estimation
613     def _best_pair(self, c):
614         obs = self.obs[c]
615         best = None
616         for i in range(len(obs)):
617             for j in range(i + 1, len(obs)):
618                 p1, p2 = obs[i], obs[j]
619                 if self._dist(p1, p2) < 25.0:
620                     continue
621                 pt = self._ray_intersect(p1, p2)
622                 if pt is None:
623                     continue
624                 gam = self._intersection_angle(p1, p2, pt)
625                 if best is None or gam > best[0]:
626                     best = (gam, i, j, pt)
627         return best
628
629     @staticmethod
630     def _ray_intersect(p1, p2):
631         """Intersection of the two measured rays (p, bearing)."""
632         x1, y1, b1 = p1

```

```

633     x2, y2, b2 = p2
634     a1 = math.radians(b1)
635     a2 = math.radians(b2)
636     d1x, d1y = math.cos(a1), math.sin(a1)
637     d2x, d2y = math.cos(a2), math.sin(a2)
638     den = d1x * d2y - d1y * d2x
639     if abs(den) < 1e-9:
640         return None
641     t = ((x2 - x1) * d2y - (y2 - y1) * d2x) / den
642     return (x1 + t * d1x, y1 + t * d1y)
643
644 @staticmethod
645 def _intersection_angle(p1, p2, pt):
646     b1 = math.degrees(math.atan2(pt[1] - p1[1], pt[0] - p1[0]))
647     b2 = math.degrees(math.atan2(pt[1] - p2[1], pt[0] - p2[0]))
648     return abs(g.ang_diff(b1, b2))
649
650 def update_estimate(self, c):
651     """Least-squares style estimate built from the cross-fixing region."""
652     if len(self.obs[c]) < 2:
653         return None
654     sts = [(o[0], o[1]) for o in self.obs[c]]
655     bs = [o[2] for o in self.obs[c]]
656     res = g.region_from_bearings(sts, bs, EPS)
657     if res["empty"] or not res["bounded"] or len(res["vertices"]) == 0:
658         bp = self._best_pair(c)
659         if bp is None:
660             return None
661         gam, i, j, pt = bp
662         sigma = R_MAX / max(math.sin(math.radians(gam)), 1e-3) * math.radians(EPS)
663         return (pt[0], pt[1], max(sigma, 5.0))
664     cx, cy, r = res["mec"]
665     # the source must lie in the arena and within 1500 m of every station
666     if not self._inside((cx, cy), 5.0):
667         cx, cy = self._clip_to_arena((cx, cy))
668     return (cx, cy, max(r, 1.0))
669
670 def _commit_estimates(self):
671     for c in self.channels:
672         if self.status[c] == "cleared":
673             continue
674         if len(self.obs[c]) >= 2:
675             e = self.update_estimate(c)
676             if e is None:
677                 continue
678             self.est[c] = e
679             if e[2] <= self.p["locate_sigma"]:
680                 self.status[c] = "located"
681         elif len(self.obs[c]) == 1 and self.est[c] is None:
682             # a single bearing: use the middle of the plausible ray
683             p = self.obs[c][0]
684             r_lim = self._ray_limit(p)
685             self.est[c] = (p[0] + 0.6 * r_lim * math.cos(math.radians(p[2])),
686                           p[1] + 0.6 * r_lim * math.sin(math.radians(p[2])),
687                           r_lim)
688             if self.status[c] == "unknown":
689                 self.status[c] = "seen"
690
691 def _ray_limit(self, obs, cap=R_MAX):
692     """Length of the plausible ray from `obs` before leaving the arena."""
693     x, y, b = obs
694     a = math.radians(b)
695     dx, dy = math.cos(a), math.sin(a)
696     # solve |p + t d| = arena_r
697     bq = 2.0 * (x * dx + y * dy)
698     cq = x * x + y * y - self.arena_r ** 2
699     disc = bq * bq - 4.0 * cq
700     t = cap
701     if disc > 0:
702         t1 = (-bq + math.sqrt(disc)) / 2.0
703         t2 = (-bq - math.sqrt(disc)) / 2.0
704         cand = [v for v in (t1, t2) if v > 0]
705         if cand:
706             t = min(t, min(cand))
707     return max(t, 30.0)
708
709 # ----- probing
710 def _worth_measuring(self, c, pos):
711     if self.status[c] in ("cleared", "empty"):

```

```

712         return False
713     key = (round(pos[0], 2), round(pos[1], 2))
714     if key in self.measure_points[c]:
715         return False
716     if self.status[c] == "unknown":
717         if (self.p.get("skip_certified", True)
718             and not self._cert_open_near(c, pos)):
719             # 该站附近已被完全认证: 此处不可能有源, 测了没有信息量
720             return False
721         return True
722     if self.status[c] == "located":
723         return False
724     if self.status[c] == "seen":
725         if not self.obs[c]:
726             return True
727         # predicted intersection angle with the best existing bearing
728         best = 0.0
729         for o in self.obs[c]:
730             r_lim = self._ray_limit(o)
731             pt = (o[0] + 0.6 * r_lim * math.cos(math.radians(o[2])),
732                  o[1] + 0.6 * r_lim * math.sin(math.radians(o[2])))
733             if self._dist(o, pos) < 25.0:
734                 continue
735             best = max(best, self._intersection_angle(o, (pos[0], pos[1], 0.0), pt))
736         if best >= self.p["probe_min_angle"]:
737             return True
738         if self.status[c] == "seen" and len(self.obs[c]) == 1:
739             # the source may be invisible from the existing ray estimate:
740             # probe anyway with a reduced priority
741             return self._dist(pos, self.est[c][:2]) < R_MAX if self.est[c] else True
742         return False
743     return False
744
745 def _enroute_clears(self, pos):
746     """
747     C1: located sources close to `pos`. Visiting a search stop already pays
748     for the travel, so neutralising a known source inside a small radius
749     costs almost nothing; doing it later means paying for the trip twice.
750     """
751     if not self.p.get("enroute_clear", True):
752         return 0
753     rad = float(self.p.get("enroute_radius", 260.0))
754     done = 0
755     for c in list(self.channels):
756         if self.status.get(c) in ("cleared", "empty"):
757             continue
758         e = self.est.get(c)
759         if e is None or e[2] > self.p["locate_sigma"] * 3.0:
760             continue
761         if self._dist(pos, (e[0], e[1])) > rad:
762             continue
763         if self.total_attempts.get(c, 0) >= self.p["hard_attempt_cap"]:
764             continue
765         self._cur_task = "clear"
766         self._task_count["clear"] += 1
767         self.attempts[c] = self.attempts.get(c, 0) + 1
768         self.total_attempts[c] = self.total_attempts.get(c, 0) + 1
769         self.last_attempt_sigma[c] = e[2]
770         self.last_attempt_obs[c] = len(self.obs.get(c, []))
771         if self.clear_channel(c):
772             done += 1
773         else:
774             self.est[c] = None
775     return done
776
777 def probe(self, pos, force=False):
778     """Measure the unresolved channels at the current position."""
779     spacing = self.p["probe_spacing"]
780     if self.p.get("adaptive_probe", True):
781         busy = sum(1 for c in self.channels
782                    if self.status.get(c) not in ("cleared", "empty"))
783         if busy >= self.p.get("busy_channels", 5):
784             spacing = min(spacing, self.p.get("probe_spacing_busy", 320.0))
785     if not force and self.last_probe_pos is not None:
786         if self._dist(pos, self.last_probe_pos) < spacing:
787             return 0
788     todo = [c for c in self.channels if self._worth_measuring(c, pos)]
789     # order by channel number: minimises the channel switching time
790     todo.sort()

```

```

791     n = 0
792     for c in todo[:self.p["max_channels_probe"]]:
793         self.move_measure(pos[0], pos[1], c)
794         n += 1
795     self.last_probe_pos = pos
796     return n
797
798 # ----- terminal homing
799 def hear(self, c, pos):
800     """
801     Move to `pos` and measure channel `c`. Repeating a measurement at the
802     same point is useless (the reading error is a property of the location),
803     so a cached reading is reused: only the travel time is paid.
804     """
805     key = (round(pos[0], 2), round(pos[1], 2))
806     hit = self.meas_cache.get((c, key))
807     if hit is not None:
808         d = self._dist(self.pos, pos)
809         self.vtime += d / SPEED
810         self.pos = (float(pos[0]), float(pos[1]))
811         self._task_travel[self._cur_task] += d
812         self._task_time[self._cur_task] += d / SPEED
813         return hit
814     r = self.move_measure(pos[0], pos[1], c)
815     self.meas_cache[(c, key)] = r
816     return r
817
818 # ----- orientation belief
819 def _orient_update(self, c, q):
820     """
821     把一次 no_signal 转成对朝向的半平面约束 (q-p).u < 0, 更新可行分箱。
822     仅当估计位置与检测点距离不超过 R_min 时该约束才成立（否则可能只是超距）。
823     """
824     if not self.p.get("orient_belief", False):
825         return
826     est = self.est.get(c)
827     if est is None:
828         return
829     dx, dy = q[0] - est[0], q[1] - est[1]
830     d = math.hypot(dx, dy)
831     if d < 1e-6 or d > float(self.p["verify_r"]):
832         return
833     nb = int(self.p.get("orient_bins", 24) or 24)
834     ok = self.orient_ok.get(c)
835     if not ok:
836         return
837     # 可行朝向必须指向背离 q 的一侧，即与 (q-p) 的夹角 > 90 度
838     keep = set()
839     for b in ok:
840         ang = 2.0 * math.pi * (b + 0.5) / nb
841         if math.cos(ang) * dx + math.sin(ang) * dy < 0.0:
842             keep.add(b)
843     self.orient_ok[c] = keep
844
845 def _orient_front(self, c):
846     """
847     返回"源的前向侧"取数点: p + L*u_hat. u_hat 取所有幸存分箱中最靠近当前
848     位置的方向（这样移动距离最短）。可行集为空时返回 None。
849     """
850     est = self.est.get(c)
851     ok = self.orient_ok.get(c)
852     if est is None or not ok:
853         return None
854     nb = int(self.p.get("orient_bins", 24) or 24)
855     L = float(self.p.get("orient_len", 350.0))
856     best = None
857     for b in ok:
858         ang = 2.0 * math.pi * (b + 0.5) / nb
859         pt = (est[0] + L * math.cos(ang), est[1] + L * math.sin(ang))
860         d = self._dist(self.pos, pt)
861         if best is None or d < best[0]:
862             best = (d, pt)
863     if best is None:
864         return None
865     return self._clip_to_arena(best[1])
866
867 def _retreat(self, c):
868     """
869     The channel is silent here. Go back to the last position where it was

```

```

870 heard and listen again. For a directional source this is the only safe
871 move: the segment joining a hearing point to the source lies inside the
872 radiation sector, therefore reception is guaranteed to come back.
873 """
874 seen = self.last_seen.get(c)
875 if self.p.get("orient_belief", False):
876     # 自主设计的改法: 背向丢失时主动绕到源的前向侧, 而不是退回去
877     front = self._orient_front(c)
878     if front is not None and self._dist(self.pos, front) > 2.0:
879         r = self.hear(c, front)
880         if r.get("measure_result") in ("direction", "near"):
881             return True
882 if seen is None:
883     return False
884 if self._dist(self.pos, seen) < 1.0:
885     return False
886 r = self.hear(c, seen)
887 return r["measure_result"] in ("direction", "near")
888
889 def _try_clear(self, c, pos=None):
890     """A clear attempt at `pos` (default: current position)."""
891     p = self.pos if pos is None else pos
892     return self.move_clear(p[0], p[1], c) ["clear_result"] == "success"
893
894 def _local_clear_sweep(self, c, center, radius=None, sigma=None):
895     """
896     Endgame: the estimate is a few tens of metres from the source, so try the
897     clear action on a small hexagonal pattern around it. A clear costs only
898     3 s when it misses, which makes this far cheaper than another homing
899     cycle. The pattern radius follows the uncertainty radius of the estimate
900     (a clear succeeds anywhere inside 20 m).
901     """
902     if radius is None:
903         s = 30.0 if sigma is None else sigma
904         radius = min(max(0.55 * s, 12.0), 45.0)
905     # The centre is the single best guess, so by default it is tried FIRST
906     # (a miss costs only 3 s) and repeated LAST, so that a failed sweep still
907     # leaves the robot standing on the estimate -- the position where an extra
908     # bearing is most useful.
909     if self.p.get("sweep_center_first", True):
910         if self._try_clear(c, center):
911             return True
912     for k in range(6):
913         a = math.radians(60.0 * k)
914         p = self._clip_to_arena((center[0] + radius * math.cos(a),
915                                center[1] + radius * math.sin(a)))
916         if self._try_clear(c, p):
917             return True
918     if radius > 24.0:
919         for k in range(6):
920             a = math.radians(30.0 + 60.0 * k)
921             p = self._clip_to_arena((center[0] + 2.0 * radius * math.cos(a),
922                                    center[1] + 2.0 * radius * math.sin(a)))
923             if self._try_clear(c, p):
924                 return True
925     # the centre last: see the note above
926     if self._try_clear(c, center):
927         return True
928     return False
929
930 def _perp_cut(self, c, est):
931     """
932     Take one bearing from a point perpendicular to the line of sight and
933     refresh the estimate. Returns True when a new bearing was obtained.
934     """
935     if not self.obs.get(c):
936         return False
937     o = self.obs[c][-1]
938     los = math.atan2(est[1] - o[1], est[0] - o[0])
939     step = float(self.p["perp_step"])
940     for sgn in (1.0, -1.0):
941         a = los + sgn * math.pi / 2.0
942         q = self._clip_to_arena((est[0] + step * math.cos(a),
943                                est[1] + step * math.sin(a)))
944         if self._dist(q, (est[0], est[1])) < step * 0.5:
945             continue
946         r = self.hear(c, q)
947         if r.get("measure_result") == "direction":
948             e2 = self.update_estimate(c)

```

```

949         if e2 is not None:
950             self.est[c] = e2
951         return True
952     return False
953
954 def _enroute_clear(self, radius):
955     """
956     顺路清除: 把"已定位且就在附近"的源当场清除。
957
958     必须走到离源 20 m 以内才能清除, 所以"接近行程"本身省不掉;
959     省掉的是"从扫描路线专门拐出去再拐回来"的往返。
960     radius 取得比典型站距小(默认 520 m), 保证只处理真正顺路的那些,
961     不会为了顺路而打乱远处源的最优顺序。
962     """
963     if not self.p.get("enroute_clear", True):
964         return 0
965     done = 0
966     thresh = float(self.p.get("locate_sigma", 320.0)) * 1.732
967     for c in list(self.channels):
968         if self.status.get(c) in ("cleared", "empty"):
969             continue
970         e = self.est.get(c)
971         if e is None or e[2] > thresh:
972             continue
973         if self._dist(self.pos, (e[0], e[1])) > radius:
974             continue
975         if self.clear_channel(c):
976             done += 1
977         # 刚清完一个, 状态可能变化, 重新读取位置
978     return done
979
980 def _cert_open_near(self, c, pos):
981     """
982     pos 的认证半径邻域内是否还有"尚未被排除"的候选点。
983
984     返回 False 表示该处对频道 c 已无信息量(测了也不会改变任何结论)。
985     """
986     ruled = self._cert_ruled.get(c) if getattr(self, "_cert_ruled", None) else None
987     if ruled is None:
988         return True # 认证结构尚未建立: 保守地测
989     R = self.p["verify_r"] - self.p["verify_grid"] * 0.7072
990     R2 = R * R
991     for gi, q in enumerate(self._verify_grid()):
992         dx, dy = q[0] - pos[0], q[1] - pos[1]
993         if dx * dx + dy * dy > R2:
994             continue
995         if gi not in ruled:
996             return True
997     return False
998
999 def _exhaustive_clear(self, c, center, sigma):
1000     """
1001     在 圆盘上按 <=15 m 间距穷举清除。
1002
1003     这是"有保证"的兜底: 间距 g 的方形栅格中, 圆盘内任一点到最近栅格点
1004     不超过 g/sqrt(2)。取 g=15 m 得 10.6 m < 20 m 的清除半径,
1005     因此只要真值落在 圆盘内(由问题一的定位区域保证), 必定命中。
1006     """
1007     g = float(self.p.get("exhaustive_grid", 15.0))
1008     cap = int(self.p.get("exhaustive_cap", 80))
1009     rad = max(sigma, 20.0)
1010     n = int(rad / g) + 1
1011     tried = 0
1012     pts = []
1013     for iy in range(-n, n + 1):
1014         for ix in range(-n, n + 1):
1015             dx, dy = ix * g, iy * g
1016             if dx * dx + dy * dy > rad * rad:
1017                 continue
1018             pts.append((dx * dx + dy * dy, center[0] + dx, center[1] + dy))
1019     pts.sort() # 从中心向外, 先试最可能的
1020     for item in pts:
1021         q = (item[1], item[2])
1022         if tried >= cap:
1023             break
1024         tried += 1
1025         if self._try_clear(c, q):
1026             return True
1027     return False

```

```

1028
1029 def _bracket_clear(self, c, p_from, p_to):
1030     """
1031     The channel went silent right after a step: the walk overran the source,
1032     so the source lies on the segment between the last hearing point and the
1033     current position. Try the cheap clear action (3 s when it misses) along
1034     that segment.
1035     """
1036     for f in (0.5, 0.25, 0.7, 0.85, 0.15):
1037         p = (p_from[0] + f * (p_to[0] - p_from[0]),
1038              p_from[1] + f * (p_to[1] - p_from[1]))
1039         if self._try_clear(c, p):
1040             return True
1041     return False
1042
1043 def clear_channel(self, c):
1044     """
1045     Bearing homing: walk along the measured bearing, shrinking the step as
1046     the estimate improves, and clear as soon as the source is inside the
1047     20 m clear radius. Returns True when the source has been cleared.
1048     """
1049     dbg = getattr(self, "debug_channel", None) == c
1050     step_scale = 1.0
1051     for it in range(self.p["term_iters"]):
1052         est = self.est[c]
1053         if est is None:
1054             est = self.update_estimate(c)
1055             if est is None:
1056                 return False
1057             self.est[c] = est
1058         d = self._dist(self.pos, est[:2])
1059         # 1) close enough according to the estimate: a miss only costs 3 s
1060         if d <= self.p["clear_try_radius"]:
1061             if self._try_clear(c):
1062                 return True
1063         # 2) endgame: small pattern around the estimate
1064         if d <= self.p["endgame_radius"]:
1065             if self._local_clear_sweep(c, est[:2], sigma=est[2]):
1066                 return True
1067             # 兜底: 常规图案连续失败后, 在圆盘上做有保证的栅格穷举
1068             if (self.p.get("exhaustive_clear", True)
1069                 and self.attempts.get(c, 0) >= int(
1070                     self.p.get("exhaustive_after", 2))
1071                 and self._exhaustive_clear(c, est[:2], est[2])):
1072                 return True
1073             # 2b) the estimate is coarse because the bearings were taken from
1074             # nearly collinear points along the homing path. One cut
1075             # perpendicular to the line of sight constrains the range and
1076             # collapses sigma, which is what makes the pattern work.
1077             if (est[2] > self.p["perp_sigma"]
1078                 and self.perp_tries.get(c, 0) < self.p["perp_max"]
1079                 and self._perp_cut(c, est)):
1080                 self.perp_tries[c] = self.perp_tries.get(c, 0) + 1
1081             if d <= self.p["endgame_radius"] * 0.5:
1082                 return False
1083         # 3) make sure we are standing on a point where the source is heard
1084         if self.last_seen[c] is None or self._dist(self.pos, self.last_seen[c]) > 2.0:
1085             res = self.hear(c, self.pos)
1086             if dbg:
1087                 print(" [home %s it%d] hear here %s pos=%s d_est=%.0f"
1088                       % (c, it, res.get("measure_result"),
1089                          tuple(round(v for v in self.pos), d))
1090                       if res.get("measure_result") == "near":
1091                           if self._try_clear(c):
1092                               return True
1093                           continue
1094                       if res.get("measure_result") == "no_signal":
1095                           self._orient_update(c, self.pos)
1096                           if not self._retreat(c):
1097                               return False
1098                           continue
1099             # 4) walk along the last measured bearing towards the source. The
1100             # step is scaled down every time the walk overruns the source
1101             # (bisection), so the source is approached from the side on which
1102             # it was heard -- which also keeps a directional source inside
1103             # its radiation sector.
1104             o = self.obs[c][-1]
1105             step = max(6.0, min(float(self.p.get("term_step_frac", 0.7)) * d,
1106                                self.p["term_cap"])) * step_scale

```

```

1107     # Walk towards the ESTIMATE, not along the raw last bearing: that
1108     # bearing was measured at o[:2] and is only valid there. Reusing its
1109     # angle from a position hundreds of metres away sent the robot the
1110     # wrong way (58 deg off, every step away from the target). When the
1111     # robot does stand on the observation point the two coincide.
1112     b = math.atan2(est[1] - self.pos[1], est[0] - self.pos[0])
1113     tgt = self._clip_to_arena((self.pos[0] + step * math.cos(b),
1114                               self.pos[1] + step * math.sin(b)))
1115     if self._dist(tgt, self.pos) < 5.0:
1116         a = self.rng.uniform(0.0, 2.0 * math.pi)
1117         tgt = (self.pos[0] + 8.0 * math.cos(a), self.pos[1] + 8.0 * math.sin(a))
1118     res = self.move_measure(tgt[0], tgt[1], c)
1119     self.meas_cache[(c, (round(tgt[0], 2), round(tgt[1], 2)))] = res
1120     if dbg:
1121         print(" [home %s it%d] walk %.0f m -> %s res=%s scale=%.2f" %
1122               (c, it, step, tuple(round(v) for v in tgt),
1123                res.get("measure_result"), step_scale))
1124     if res["measure_result"] == "near":
1125         if self._try_clear(c, tgt):
1126             return True
1127     elif res["measure_result"] == "direction":
1128         e2 = self.update_estimate(c)
1129         if e2 is not None:
1130             self.est[c] = e2
1131             step_scale = min(1.0, step_scale * 1.3)
1132             if dbg:
1133                 print("    new est %s" % (tuple(round(v) for v in self.est[c]),))
1134     else:
1135         self._orient_update(c, tgt)
1136         step_scale *= 0.45
1137         if self.p.get("bracket_clear", True) and self._bracket_clear(c, self.last_seen[c], tgt):
1138             return True
1139         if not self._retreat(c):
1140             return False
1141     return False
1142
1143 # ----- vantage
1144 def vantage_point(self, c, local=False):
1145     """
1146     Second-station rule of problem 2. `local=True` uses the short oblique
1147     offset (cheap, used when a covering stop is not available); otherwise the
1148     robust rule [S1S2] - R_min at +-37 deg off the measured bearing.
1149     """
1150     o = self.obs[c][-1]
1151     r_lim = self._ray_limit(o)
1152     tries = self.vantage_tries.get(c, 0)
1153     onray = False
1154     if local:
1155         b = min(self.p["vantage_b_local"], max(220.0, 0.6 * r_lim))
1156         phi0 = self.p["vantage_phi_local"]
1157     else:
1158         b = min(self.p["vantage_b"], max(260.0, 0.85 * r_lim))
1159         phi0 = self.p["vantage_phi"]
1160     # For a directional source on the rim the lit cap is thin, so a large
1161     # offset lands on the dark side. Shrink the offset as attempts fail and
1162     # finally go ON the bearing ray, which the ray lemma guarantees is lit.
1163     if self.p.get("vantage_onray", True):
1164         if tries <= 0:
1165             phi0 = min(phi0, 45.0)
1166         elif tries == 1:
1167             phi0 = min(phi0, 20.0)
1168         else:
1169             # On-ray: creep instead of jumping. A long hop can pass the
1170             # source and land on the dark side (the range is unknown), so the
1171             # step is short and is halved whenever the signal is lost.
1172             phi0 = 0.0
1173             onray = True
1174             b = min(float(self.p.get("vantage_step_onray", 200.0))
1175                     * self.onray_scale.get(c, 1.0), max(r_lim - 1.0, 12.0))
1176             b = max(b, 12.0)
1177     phis = (phi0, -phi0)
1178     best = None
1179     for sgn in (+1.0, -1.0):
1180         for phi in phis:
1181             ang = math.radians(o[2] + sgn * abs(phi))
1182             p = (o[0] + b * math.cos(ang), o[1] + b * math.sin(ang))
1183             if not self._inside(p, 60.0):
1184                 p = self._clip_to_arena(p)
1185             # prefer the side that keeps the robot inside the arena and

```

```

1186         # requires the least travel
1187         cost = self._dist(self.pos, p) / SPEED
1188         if not self._inside(p, 0.0):
1189             cost += 200.0
1190         if best is None or cost < best[0]:
1191             best = (cost, p)
1192     if best is None:
1193         return None
1194     return best[1] if not onray else (best[1], True)
1195
1196 # ----- main loop
1197 def run(self, max_actions=6000):
1198     self.cl.enter()
1199     n_act = 0
1200     if self.p["census"]:
1201         self._cur_task = "census"
1202         for c in self.channels:
1203             self.move_measure(0.0, 0.0, c)
1204             n_act += 1
1205         self._task_count["census"] += 1
1206         self.last_probe_pos = (0.0, 0.0)
1207     self._ring_stops = self._make_ring_stops()
1208     if self.p["policy"] == "planned":
1209         n_act = self._run_planned(n_act, max_actions)
1210     else:
1211         n_act = self._run_greedy(n_act, max_actions)
1212     try:
1213         self.cl.exit()
1214     except Exception:
1215         pass
1216     return self.stats()
1217
1218 # ----- planned policy
1219 def _rim_ring_stops(self):
1220     """
1221     贴边环: 在半径 rim_ring_r 上均匀放 n 个站位。
1222
1223     贴边且朝外辐射的定向源, 其域内受光区是一条贴着边界的薄月牙;
1224     任何方向的月牙都会与这圈站位相交, 因此在环上均匀取样就能发现它。
1225     这些站位只服务于**发现**, 与认证边距 (verify_margin) 无关。
1226     """
1227     n = int(self.p.get("rim_ring_n", 0) or 0)
1228     if n <= 0:
1229         return []
1230     r = float(self.p.get("rim_ring_r", 1750.0))
1231     rot = math.radians(float(self.p.get("ring_rotation", 0.0)))
1232     return [(r * math.cos(rot + 2.0 * math.pi * k / n),
1233             r * math.sin(rot + 2.0 * math.pi * k / n)) for k in range(n)]
1234
1235 def _primary_stops(self):
1236     """
1237     The planned search positions.
1238     'ring' : centre + six stops on a circle; the minimal configuration
1239             whose 1000 m reception disks cover the arena, sufficient
1240             for omnidirectional sources (problem 3).
1241     'lattice' : a triangular lattice of the whole arena; each position is
1242                 surrounded from several directions in less than 1000 m,
1243                 which is what a directional source requires before it can
1244                 be declared absent (problem 4).
1245     """
1246     cached = getattr(self, "_primary_cache", None)
1247     if cached is not None:
1248         return list(cached)
1249     if self.p.get("survey_mode") == "adaptive":
1250         # 自适应: 不预置任何站位, 全部由认证扫描按需给出
1251         base = []
1252     elif self.p.get("survey_mode", "ring") == "lattice":
1253         base = list(self.survey_stops)
1254     else:
1255         base = self._make_ring_stops()
1256     # 贴边环在**任何模式**下都生效: 它是"贴边朝外定向源"的唯一发现手段,
1257     # 与普查用什么形状无关。单独记下来, 好让站位上限只作用于格点部分。
1258     self._rim_only = list(self._rim_ring_stops())
1259     base = base + self._rim_only
1260     if self.p.get("spread_stops", True) and base:
1261         # 最近点采样排序: 截断时保留均匀覆盖, 而不是砍掉外圈
1262         base = self._spread_order(base)
1263     self._primary_cache = list(base)
1264     self.survey_stops = list(base)

```

```

1265     return list(base)
1266
1267 def _stop_is_useless(self, p):
1268     """
1269     True when p no longer needs a visit: every certification candidate within
1270     the certification radius of p is already ruled out for every channel that
1271     has not been certified yet.
1272
1273     Then no source can hide there (so the visit would discover nothing) and the
1274     certificate does not need p's readings either.
1275     """
1276     if not self.p.get("skip_useless_stops", True):
1277         return False
1278     ruled_map = getattr(self, "_cert_ruled", None)
1279     if not ruled_map:
1280         return False
1281     open_ch = [c for c in self.channels
1282                 if self.status.get(c) not in ("cleared", "empty")
1283                 and not self.obs.get(c)]
1284     if not open_ch:
1285         return True
1286     R = self.p["verify_r"] - self.p["verify_grid"] * 0.7072
1287     R2 = R * R
1288     grid = self._verify_grid()
1289     for gi, q in enumerate(grid):
1290         dx, dy = q[0] - p[0], q[1] - p[1]
1291         if dx * dx + dy * dy > R2:
1292             continue
1293         for c in open_ch:
1294             if gi not in ruled_map.get(c, ()):
1295                 return False
1296     return True
1297
1298 def _pending_stops(self):
1299     """
1300     Covering stops that still have to be visited.
1301
1302     `max_survey_stops` caps only the LATTICE part. The rim ring is always
1303     kept: it is the only way to discover sources that radiate outward from the
1304     rim, and capping the combined list silently dropped it entirely (which is
1305     why the earlier cap experiments looked so bad).
1306     """
1307     cap = int(self.p.get("max_survey_stops", 0) or 0)
1308     rim = set((round(q[0], 1), round(q[1], 1))
1309               for q in getattr(self, "_rim_only", ()))
1310     out = []
1311     n_base = 0
1312     visited_base = sum(1 for k in self.visited_stops if k not in rim)
1313     for p in self._primary_stops():
1314         key = (round(p[0], 1), round(p[1], 1))
1315         if key in self.visited_stops:
1316             continue
1317         if self._stop_is_useless(p):
1318             continue
1319         if key not in rim:
1320             if cap > 0 and visited_base + n_base >= cap:
1321                 continue
1322             n_base += 1
1323         out.append(p)
1324     return out
1325
1326 def _needs_stops(self):
1327     for c in self.channels:
1328         if self.status[c] == "cleared":
1329             continue
1330         if self.status[c] in ("unknown", "seen", "located"):
1331             return True
1332     return False
1333
1334 def _build_tasks(self):
1335     """
1336     Task list. Clearing targets always have priority; the covering stops are
1337     used for the second bearing whenever some of them are still pending, so
1338     that no extra detour is paid for the localisation.
1339     """
1340     tasks = []
1341     pending = self._pending_stops() if (self.p["use_ring"] and self._needs_stops()) else []
1342     clears = []
1343     for c in self.channels:

```

```

1344     if self.status[c] == "cleared":
1345         continue
1346     e = self.est[c]
1347     if e is None:
1348         continue
1349     good = (len(self.obs[c]) >= 2 and e[2] <= self.p["locate_sigma"]) or \
1350           (len(self.obs[c]) >= 3 and e[2] <= self.p["locate_sigma"] * 3.0)
1351     if not good:
1352         continue
1353     # the attempt budget only throttles repeated failures at the same
1354     # quality: a clearly better localisation re-opens it, but a hard cap
1355     # prevents an endless loop on a source that cannot be cleared
1356     if self.total_attempts.get(c, 0) >= self.p["hard_attempt_cap"]:
1357         continue
1358     if self.attempts.get(c, 0) >= self.p["max_attempts"]:
1359         prev = self.last_attempt_sigma.get(c)
1360         prev_obs = self.last_attempt_obs.get(c, 0)
1361         # reopen when the localisation improved, or when new bearings
1362         # have arrived since the last attempt (a fresh cut can turn a
1363         # hopeless estimate into a solvable one)
1364         if (prev is not None and e[2] > self.p["progress_ratio"] * prev
1365             and len(self.obs[c]) <= prev_obs):
1366             continue
1367         self.attempts[c] = 0
1368         clears.append(("clear", c, (e[0], e[1])))
1369     if self.p.get("phase_separate", True) and pending:
1370         # SURVEY PHASE: while any covering stop is still unvisited, the tour
1371         # contains stops only. Mixing a clearing detour into the sweep makes
1372         # the robot leave the survey area and come back, and the same detour is
1373         # then paid twice.
1374         return [("stop", None, q) for q in pending]
1375     tasks.extend(clears)
1376     # second bearings are preferably taken at positions the robot visits
1377     # anyway (probe after every action); a dedicated oblique offset is only
1378     # bought when no clearing target is left
1379     if not clears:
1380         for c in self.channels:
1381             if self.status[c] == "cleared":
1382                 continue
1383             if len(self.obs[c]) < 1:
1384                 continue
1385             if self._relocate_needed(c):
1386                 continue # 由 relocate 机制负责, 不用旧的斜向站位
1387             if (self.vantage_tries.get(c, 0) >= self.p["vantage_max_tries"]
1388                 and self.onray_tries.get(c, 0)
1389                 >= self.p.get("vantage_onray_tries", 16)):
1390                 continue
1391             p = self.vantage_point(c, local=True)
1392             if p is not None:
1393                 if isinstance(p, tuple) and len(p) == 2 and p[1] is True:
1394                     tasks.append(("vantage", c, p[0],
1395                                   {"onray": True,
1396                                    "origin": self.obs[c][-1][:2]}))
1397                 else:
1398                     tasks.append(("vantage", c, p))
1399             elif self.est[c] is not None:
1400                 tasks.append(("clear", c, (self.est[c][0], self.est[c][1])))
1401     cap = int(self.p.get("max_survey_stops", 0) or 0)
1402     if cap > 0:
1403         room = cap - len(self.visited_stops)
1404         pending = pending[:max(room, 0)]
1405     # 只有一条方位的频道: 给它安排一次"横向偏移二分"观测。
1406     # 放在清除任务之后、覆盖站位之前——它便宜(短距离往返),
1407     # 而且一旦成功就把一个"已听到"的频道变成可清除的目标。
1408     if self.p.get("relocate", True):
1409         for c in self.channels:
1410             if self.status.get(c) in ("cleared", "empty"):
1411                 continue
1412             if not self._relocate_needed(c):
1413                 continue
1414             r = self._relocate_point(c)
1415             if r is not None:
1416                 tasks.append(("relocate", c, r[0]))
1417     for p in pending:
1418         tasks.append(("stop", None, p))
1419     return tasks
1420
1421 # ----- targeted search stops
1422 def next_search_stop(self, unresolved):

```

```

1423 """
1424 Greedy set-cover step for the verification search: among the candidate
1425 survey stops pick the one that rules out the largest number of arena
1426 positions per second of travel.
1427 Returns (stop, certified_flags) or (None, flags) when nothing is left.
1428 """
1429 if not self.p.get("cert_heard_channels", False):
1430     # A channel that was heard exists: it needs locating and clearing, not
1431     # a proof of absence. Certifying it is logically pointless and, as
1432     # measured, costs about eighteen wasted stops per case.
1433     cert_set = [c for c in unresolved if not self.obs.get(c)]
1434 else:
1435     cert_set = list(unresolved)
1436 if not cert_set:
1437     return None, {}
1438 ok, uncov, flags = self.certification_scan(cert_set)
1439 for c, v in flags.items():
1440     if v:
1441         self.status[c] = "empty"
1442 if ok or not uncov:
1443     return None, flags
1444 slack = self.p["verify_grid"] * 0.7072
1445 R = self.p["verify_r"] - slack
1446 directional = bool(self.p.get("directional", False))
1447 best = None
1448 fallback = None
1449 for p in self._all_search_stops():
1450     if (round(p[0], 1), round(p[1], 1)) in self.visited_stops:
1451         continue
1452     gain = 0
1453     gain_plain = 0
1454     for q in uncov:
1455         dx, dy = p[0] - q[0], p[1] - q[1]
1456         if dx * dx + dy * dy > R * R:
1457             continue
1458         gain_plain += 1
1459         if not directional:
1460             gain += 1
1461             continue
1462         # directional sources also need a NEW direction of observation
1463         a = math.atan2(dy, dx)
1464         fresh = True
1465         for c in unresolved:
1466             for rp in self.nosig[c]:
1467                 ex, ey = rp[0] - q[0], rp[1] - q[1]
1468                 if ex * ex + ey * ey > R * R:
1469                     continue
1470                 if abs(g.ang_diff(math.degrees(a),
1471                                     math.degrees(math.atan2(ey, ex)))) < 55.0:
1472                     fresh = False
1473                     break
1474             if not fresh:
1475                 break
1476         if fresh:
1477             gain += 1
1478     cost = self._dist(self.pos, p) / SPEED + self.p["search_cost_bias"]
1479     if gain > 0:
1480         score = gain / cost
1481         if best is None or score > best[0]:
1482             best = (score, p)
1483     elif gain_plain > 0 and not (directional
1484                                and self.p.get("no_plain_fallback")):
1485         score = gain_plain / cost * 0.5
1486         if fallback is None or score > fallback[0]:
1487             fallback = (score, p)
1488 if best is not None:
1489     return best[1], flags
1490 if not self.p.get("rim_patrol", True):
1491     return (fallback[1] if fallback else None), flags
1492 if self.rim_patrols >= int(self.p.get("max_rim_patrols", 12)):
1493     return (fallback[1] if fallback else None), flags
1494 # nothing inside the arena can help any more: try the outside samples
1495 # aimed at the rim candidates before giving up
1496 for p in self._rim_patrol_stops(uncov):
1497     gain = 0
1498     for q in uncov:
1499         dx, dy = p[0] - q[0], p[1] - q[1]
1500         if dx * dx + dy * dy <= R * R:
1501             gain += 1

```

```

1502         if gain > 0:
1503             self.rim_patrols += 1
1504             return p, flags
1505         return (fallback[1] if fallback else None), flags
1506
1507     def _mark_certified(self):
1508         """
1509         Evaluate the certificate during the sweep and mark the channels it proves
1510         absent as "empty".
1511
1512         Nothing else would do it when the search stops are disabled, and a
1513         certified channel can never be heard again, so measuring it at every
1514         remaining stop is pure waste.
1515         """
1516         unresolved = [c for c in self.channels
1517                       if self.status[c] not in ("cleared", "empty")]
1518         if not self.p.get("cert_heard_channels", False):
1519             cert_set = [c for c in unresolved if not self.obs.get(c)]
1520         else:
1521             cert_set = list(unresolved)
1522         if not cert_set:
1523             return 0
1524         try:
1525             ok, uncov, flags = self.certification_scan(cert_set)
1526         except Exception:
1527             return 0
1528         n = 0
1529         for c, v in flags.items():
1530             if v and self.status.get(c) not in ("cleared", "empty"):
1531                 self.status[c] = "empty"
1532                 n += 1
1533         return n
1534
1535     def _relocate_point(self, c):
1536         """
1537         为"只有一条方位"的频道给出**当前**候选观测点（纯查询，不改变状态）。
1538
1539         状态机：按位于 self.reloc[c] 的 (d, side, crawl) 给出候选点；
1540         推进由 `self._relocate_advance()` 在任务执行之后完成。
1541         """
1542         if not self.obs.get(c):
1543             return None
1544         st = self.reloc.setdefault(c, {"d": 0, "side": 0, "crawl": 0})
1545         deltas = list(self.p.get("relocate_deltas",
1546                                  [400.0, 250.0, 150.0, 90.0, 55.0, 33.0, 20.0]))
1547         if st["d"] >= len(deltas):
1548             return None
1549         o = self.obs[c][-1]
1550         anchor = self.reloc.get((c, "anchor"), (o[0], o[1]))
1551         brg = math.radians(o[2])
1552         d = deltas[st["d"]]
1553         sgn = 1.0 if st["side"] == 0 else -1.0
1554         a = brg + sgn * math.pi / 2.0
1555         q = self._clip_to_arena((anchor[0] + d * math.cos(a),
1556                                anchor[1] + d * math.sin(a)))
1557         return q, "lateral %.0f m" % d
1558
1559     def _relocate_advance(self, c):
1560         """任务执行之后推进状态：先换边，再放大；都试完则沿射线爬行一步。"""
1561         st = self.reloc.setdefault(c, {"d": 0, "side": 0, "crawl": 0})
1562         deltas = list(self.p.get("relocate_deltas",
1563                                  [400.0, 250.0, 150.0, 90.0, 55.0, 33.0, 20.0]))
1564         if st["side"] == 0:
1565             st["side"] = 1
1566             return
1567         st["side"] = 0
1568         st["d"] += 1
1569         if st["d"] < len(deltas):
1570             return
1571         # 所有横向偏移都失败：沿射线前进，重新从最大偏移试起
1572         st["d"] = 0
1573         st["crawl"] += 1
1574         if st["crawl"] > int(self.p.get("relocate_crawls", 4)):
1575             return
1576         o = self.obs[c][-1]
1577         anchor = self.reloc.get((c, "anchor"), (o[0], o[1]))
1578         step = float(self.p.get("relocate_crawl_step", 200.0))
1579         brg = math.radians(o[2])
1580         nxt = self._clip_to_arena((anchor[0] + step * math.cos(brg),

```

```

1581         anchor[1] + step * math.sin(brg)))
1582     if self._dist(nxt, anchor) > 30.0:
1583         self.reloc([c, "anchor"]) = nxt
1584
1585 def _relocate_needed(self, c):
1586     """频道听过但还没有可用估计。"""
1587     if not self.p.get("relocate", True):
1588         return False
1589     if not self.obs.get(c):
1590         return False
1591     e = self.est.get(c)
1592     return e is None or e[2] > float(self.p.get("relocate_sigma", 900.0))
1593
1594 def next_search_batch(self, unresolved, k):
1595     """
1596     一次给出至多 k 个"认证最需要"的站位。
1597
1598     单个站位交给巡回规划没有意义（只有一个点时无所谓顺序）；
1599     一批站位才能让 2-opt 在它们之间排好路线。
1600     贪心地反复调用 next_search_stop，并把已选中的点临时视作已访问，
1601     以免一批里出现重复位置。
1602     """
1603     out = []
1604     for _ in range(max(int(k), 1)):
1605         stop, flags = self.next_search_stop(unresolved)
1606         if stop is None:
1607             break
1608         key = (round(stop[0], 1), round(stop[1], 1))
1609         if key in self.visited_stops:
1610             break
1611         self.visited_stops.add(key) # 临时占位，避免重复
1612         out.append(stop)
1613     return out
1614
1615 def _rim_patrol_stops(self, uncov):
1616     """
1617     Candidate positions just OUTSIDE the arena rim, aimed at the candidate
1618     locations that could not be certified from inside.
1619
1620     For a candidate q close to the rim, every in-domain reading position p
1621     satisfies (p - q) pointing inward, so the origin can never lie inside
1622     the convex hull of the (p - q): no in-domain search can ever certify q
1623     (theorem 2). Stepping a little outside, radially from the centre
1624     through q and slightly to both sides, produces directions that bracket
1625     q and makes the certificate reachable.
1626     """
1627     step = float(self.p.get("rim_step", 130.0))
1628     cap = int(self.p.get("rim_max_pts", 9))
1629     lim = self.arena_r - 2.0 * self.p["verify_grid"]
1630     out, seen = [], set()
1631     # nearest candidates first: the trip to the rim is the expensive part
1632     uncov = sorted(uncov, key=lambda q: self._dist(self.pos, q))
1633     for q in uncov:
1634         r = math.hypot(q[0], q[1])
1635         if r < lim:
1636             continue
1637         ux, uy = (q[0] / r, q[1] / r) if r > 1e-9 else (1.0, 0.0)
1638         for deg in (-38.0, 0.0, 38.0):
1639             a = math.radians(deg)
1640             dx = ux * math.cos(a) - uy * math.sin(a)
1641             dy = ux * math.sin(a) + uy * math.cos(a)
1642             k = step / max(0.35, math.cos(a))
1643             key = (round(q[0] + k * dx, 1), round(q[1] + k * dy, 1))
1644             if key in seen or key in self.visited_stops:
1645                 continue
1646             seen.add(key)
1647             out.append((q[0] + k * dx, q[1] + k * dy))
1648             if len(out) >= cap:
1649                 return out
1650     return out
1651
1652 def _plan_tour(self, tasks, start):
1653     """
1654     Nearest-neighbour ordering of the task positions followed by a 2-opt
1655     improvement; the clear tasks receive a priority bonus so that they are
1656     visited early when they are not far away.
1657     """
1658     nodes = list(range(len(tasks)))
1659     if not nodes:

```

```

1660         return []
1661     pos = [t[2] for t in tasks]
1662     bonus = [self.p["clear_bonus"] if t[0] == "clear" else 0.0 for t in tasks]
1663     order = []
1664     cur = start
1665     remaining = set(nodes)
1666     while remaining:
1667         best = None
1668         for i in remaining:
1669             d = self._dist(cur, pos[i]) - bonus[i]
1670             if best is None or d < best[0]:
1671                 best = (d, i)
1672         order.append(best[1])
1673         remaining.discard(best[1])
1674         cur = pos[best[1]]
1675     # 2-opt improvement (open tour starting at `start`)
1676     improved = True
1677     guard = 0
1678     while improved and guard < 40:
1679         improved = False
1680         guard += 1
1681         for i in range(len(order) - 1):
1682             for j in range(i + 1, len(order)):
1683                 a = start if i == 0 else pos[order[i - 1]]
1684                 b = pos[order[i]]
1685                 c = pos[order[j]]
1686                 d = pos[order[j + 1]] if j + 1 < len(order) else None
1687                 old = self._dist(a, b) + (self._dist(c, d) if d else 0.0)
1688                 new = self._dist(a, c) + (self._dist(b, d) if d else 0.0)
1689                 if new < old - 1e-9:
1690                     order[i:j + 1] = order[i:j + 1][::-1]
1691                     improved = True
1692
1693     # Or-opt over the WHOLE tour, with O(1) move evaluation.
1694     #
1695     # The plan is rebuilt after every executed task, so this has to stay
1696     # cheap; the constant-time delta below is what makes a full-tour Or-opt
1697     # affordable (the previous version only improved the first few tasks).
1698     def seg_delta(seq, i, j, k):
1699         """delta of moving seq[i:j+1] to just after position k"""
1700         n = len(seq)
1701         prev = start if i == 0 else pos[seq[i - 1]]
1702         first = pos[seq[i]]
1703         last = pos[seq[j]]
1704         nxt = pos[seq[j + 1]] if j + 1 < n else None
1705         gain = self._dist(prev, first)
1706         if nxt is not None:
1707             gain += self._dist(last, nxt) - self._dist(prev, nxt)
1708         else:
1709             gain += 0.0 # open tour: nothing after
1710         if k < 0:
1711             a = start
1712             b = pos[seq[0]]
1713         else:
1714             a = pos[seq[k]]
1715             b = pos[seq[k + 1]] if k + 1 < n else None
1716         cost = self._dist(a, first)
1717         if b is not None:
1718             cost += self._dist(last, b) - self._dist(a, b)
1719         return cost - gain
1720
1721     limit = int(self.p.get("oropt_limit_batch", 60))
1722     if self.p.get("replan_mode") == "each":
1723         limit = int(self.p.get("oropt_limit_full", 60))
1724     rounds = 0
1725     improved = True
1726     while improved and rounds < 12 and len(order) > 4:
1727         improved = False
1728         rounds += 1
1729         n = len(order)
1730         for L in (3, 2, 1):
1731             for i in range(n - L + 1):
1732                 if i >= limit:
1733                     break
1734                 j = i + L - 1
1735                 for k in range(-1, n - L):
1736                     if i <= k + 1 <= j:
1737                         continue
1738                     if seg_delta(order, i, j, k) < -1e-9:

```

```

1739         seg = order[i:j + 1]
1740         rest = order[:i] + order[j + 1:]
1741         at = k + 1 if k < i else k + 1 - L
1742         order = rest[:at] + seg + rest[at:]
1743         improved = True
1744         break
1745     if improved:
1746         break
1747     if improved:
1748         break
1749     return [tasks[i] for i in order]
1750
1751 def _run_planned(self, n_act, max_actions):
1752     replan = True
1753     tour = []
1754     extra_stops = []
1755     batch = self.p.get("replan_mode", "batch") == "batch"
1756
1757     def heard_count():
1758         return sum(1 for c in self.channels if self.obs.get(c))
1759
1760     def clear_count():
1761         return sum(1 for c in self.channels if self.status.get(c) == "cleared")
1762
1763     last_heard, last_cleared = heard_count(), clear_count()
1764     while n_act < max_actions:
1765         self._commit_estimates()
1766         if self._all_done():
1767             break
1768         if replan or not tour:
1769             tasks = self._build_tasks()
1770             for p in extra_stops:
1771                 tasks.append(("stop", None, p))
1772             tour = self._plan_tour(tasks, self.pos)
1773             replan = False
1774             if not tour:
1775                 # no task left: decide whether the search may stop
1776                 unresolved = [c for c in self.channels
1777                               if self.status[c] not in ("cleared", "empty")]
1778                 if not unresolved:
1779                     break
1780                 if self.p.get("survey_mode") == "adaptive":
1781                     # 自适应采样: 一次取一批"认证最需要"的站位,
1782                     # 交给巡回规划排序(单个站位无顺序可言)
1783                     stops = self.next_search_batch(
1784                         unresolved, int(self.p.get("adaptive_batch", 4)))
1785                     if not stops:
1786                         break
1787                     tour = [("stop", None, q) for q in stops]
1788                 else:
1789                     stop, flags = self.next_search_stop(unresolved)
1790                     if (stop is None
1791                         or len(extra_stops) >= self.p["max_search_stops"]):
1792                         break
1793                     extra_stops.append(stop)
1794                     tour = [("stop", None, extra_stops.pop(0))]
1795             last_heard, last_cleared = heard_count(), clear_count()
1796             task = tour.pop(0)
1797             kind = task[0]
1798             if kind == "stop":
1799                 # C1: the trip is already paid for, so take any located source
1800                 # that sits next to this stop
1801                 self._enroute_clears(task[2])
1802             if kind == "clear":
1803                 self._cur_task = "clear"
1804                 self._task_count["clear"] += 1
1805                 self.attempts[task[1]] = self.attempts.get(task[1], 0) + 1
1806                 self.total_attempts[task[1]] = self.total_attempts.get(task[1], 0) + 1
1807                 if self.est[task[1]] is not None:
1808                     self.last_attempt_sigma[task[1]] = self.est[task[1]][2]
1809                     self.last_attempt_obs[task[1]] = len(self.obs.get(task[1], []))
1810                     ok = self.clear_channel(task[1])
1811                     n_act += 1
1812                     if not ok:
1813                         self.fail_log.append({"channel": task[1], "reason": "clear_failed",
1814                                                "pos": self.pos, "vtime": self.vtime})
1815                         self.est[task[1]] = None
1816                     # a visited source position is a free vantage point: probe the
1817                     # still unresolved channels here (discovery + verification)

```

```

1818         self.probe(self.pos)
1819         replan = (not batch) or heard_count() > last_heard or clear_count() > last_cleared
1820     elif kind == "relocate":
1821         self._cur_task = "localise"
1822         self._task_count["localise"] += 1
1823         c = task[1]
1824         p = task[2]
1825         r = self.move_measure(p[0], p[1], c)
1826         n_act += 1
1827         if r.get("measure_result") in ("direction", "near"):
1828             # 拿到了第二条方位: 重新估计, 若可用则立刻转为可清除
1829             e = self.update_estimate(c)
1830             if e is not None:
1831                 self.est[c] = e
1832                 self.reloc.pop(c, None)
1833                 self.reloc.pop((c, "anchor"), None)
1834             else:
1835                 self._relocate_advance(c)
1836         self.probe(self.pos)
1837         replan = (not batch) or heard_count() > last_heard or clear_count() > last_cleared
1838     elif kind == "vantage":
1839         self._cur_task = "localise"
1840         self._task_count["localise"] += 1
1841         c = task[1]
1842         p = task[2]
1843         meta = task[3] if len(task) > 3 else {}
1844         self.vantage_tries[c] = self.vantage_tries.get(c, 0) + 1
1845         r = self.move_measure(p[0], p[1], c)
1846         n_act += 1
1847         if meta.get("onray") and self.p.get("vantage_onray_bisect", True):
1848             self.onray_tries[c] = self.onray_tries.get(c, 0) + 1
1849             if r.get("measure_result") in ("direction", "near"):
1850                 self.onray_scale[c] = 1.0
1851             else:
1852                 # overshoot: return to the hearing point and shorten the
1853                 # next hop so that it lands inside the lit part of the ray
1854                 self.onray_scale[c] = max(
1855                     0.08, self.onray_scale.get(c, 1.0) * 0.45)
1856                 o = meta.get("origin")
1857                 if o is not None:
1858                     self.hear(c, (o[0], o[1]))
1859         self.probe(self.pos)
1860         replan = (not batch) or heard_count() > last_heard or clear_count() > last_cleared
1861     else: # covering stop
1862         self._cur_task = "probe"
1863         self._task_count["probe"] += 1
1864         p = task[2]
1865         self.visited_stops.add((round(p[0], 1), round(p[1], 1)))
1866         self.probe(p, force=True)
1867         n_act += 1
1868         self._commit_estimates()
1869         self._enroute_clear(float(self.p.get("enroute_radius", 520.0)))
1870         if self.p.get("periodic_cert", True):
1871             self._since_cert = getattr(self, "_since_cert", 0) + 1
1872             if self._since_cert >= int(self.p.get("periodic_cert_every", 2)):
1873                 self._since_cert = 0
1874                 self._mark_certified()
1875         replan = (not batch) or heard_count() > last_heard or clear_count() > last_cleared
1876     return n_act
1877
1878 # ----- greedy policy
1879 def _run_greedy(self, n_act, max_actions):
1880     while n_act < max_actions:
1881         self._commit_estimates()
1882         if self._all_done():
1883             break
1884         task = self._choose_task()
1885         if task is None:
1886             break
1887         kind = task[0]
1888         if kind == "clear":
1889             self._cur_task = "clear"
1890             self._task_count["clear"] += 1
1891             c = task[1]
1892             ok = self.clear_channel(c)
1893             n_act += 1
1894             if not ok:
1895                 self.fail_log.append({"channel": c, "reason": "clear_failed",
1896                                     "pos": self.pos, "vtime": self.vtime})

```

```

1897         # give up on this channel for a while
1898         self.est[c] = None
1899         if len(self.obs[c]) == 0:
1900             self.status[c] = "seen"
1901     elif kind == "localise":
1902         self._cur_task = "localise"
1903         self._task_count["localise"] += 1
1904         c = task[1]
1905         p = task[2]
1906         self.move_measure(p[0], p[1], c)
1907         n_act += 1
1908         self._commit_estimates()
1909         self.probe(self.pos)
1910     elif kind == "probe":
1911         self._cur_task = "probe"
1912         self._task_count["probe"] += 1
1913         p = task[1]
1914         self.visited_stops.add((round(p[0], 1), round(p[1], 1)))
1915         # travel in two hops so that bearings are refreshed on the way
1916         mid = ((self.pos[0] + p[0]) / 2.0, (self.pos[1] + p[1]) / 2.0)
1917         if self._dist(self.pos, mid) > 300.0:
1918             self.probe(mid, force=False)
1919             self._commit_estimates()
1920             self.probe(p, force=True)
1921             n_act += 1
1922             self._commit_estimates()
1923             # opportunistic clearance: clear anything that became located
1924             self._clear_nearby(700.0)
1925     return n_act
1926
1927 def _clear_nearby(self, radius):
1928     """Clear located sources close to the current position."""
1929     cands = [c for c in self.channels
1930              if self.status[c] == "located" and self.est[c]
1931                 and self._dist(self.pos, self.est[c][:2]) <= radius]
1932     cands.sort(key=lambda c: self._dist(self.pos, self.est[c][:2]))
1933     for c in cands[:2]:
1934         self.clear_channel(c)
1935
1936 def _all_done(self):
1937     """Termination: every channel is either cleared or certified empty."""
1938     for c in self.channels:
1939         if self.status[c] in ("cleared", "empty"):
1940             continue
1941     return False
1942     return True
1943
1944 def _choose_task(self):
1945     cands = []
1946     for c in self.channels:
1947         if self.status[c] == "located" and self.est[c] is not None:
1948             t = self._dist(self.pos, self.est[c][:2]) / SPEED + 40.0
1949             cands.append((t - self.p["clear_bonus"], ("clear", c)))
1950         elif self.status[c] == "seen" and len(self.obs[c]) == 1:
1951             p = self.vantage_point(c)
1952             if p is not None:
1953                 t = self._dist(self.pos, p) / SPEED + 30.0
1954                 cands.append((t - self.p["localise_bonus"], ("localise", c, p)))
1955     # survey stops for unknown / unresolved channels
1956     if any(self.status[c] in ("unknown", "seen") for c in self.channels):
1957         best = None
1958         for p in self.survey_stops:
1959             key = (round(p[0], 1), round(p[1], 1))
1960             if key in self.visited_stops:
1961                 continue
1962             t = self._dist(self.pos, p) / SPEED
1963             if best is None or t < best[0]:
1964                 best = (t, p)
1965         if best is not None:
1966             cands.append((best[0] - self.p["probe_bonus"], ("probe", best[1])))
1967     if not cands:
1968         return None
1969     cands.sort(key=lambda x: x[0])
1970     return cands[0][1]
1971
1972 # ----- stats
1973 def stats(self):
1974     arena = getattr(self, "arena", None)
1975     if arena is not None:

```

```

1976         st = arena.stats()
1977     else:
1978         st = {}
1979     st["brain_vtime"] = self.vtime
1980     # task accounting: how much travel / time every task class consumed
1981     st["task_travel"] = dict((k, round(v, 1)) for k, v in self._task_travel.items())
1982     st["task_count"] = dict(self._task_count)
1983     st["task_time"] = dict((k, round(v, 1)) for k, v in self._task_time.items())
1984     return st
1985
1986
1987 def run_case(sources, params=None, seed=0, arena_radius=ARENA_R, verbose=False):
1988     """Run one complete test on an in-process arena and return the statistics."""
1989     arena = sim.Arena(sources, seed=seed)
1990     client = LocalClient(arena, robot_id="local-team")
1991     brain = Brain(client, params=params, arena_radius=arena_radius,
1992                  verbose=verbose, seed=seed)
1993     st = brain.run()
1994     st["n_requests"] = client.n_requests
1995     arena.close()
1996     return st, brain
1997
1998
1999 if __name__ == "__main__":
2000     rng = random.Random(1)
2001     srcs = sim.make_case(rng, n_sources=13)
2002     st, brain = run_case(srcs, seed=1)
2003     print(json.dumps(st, indent=1, ensure_ascii=False))

```

### 3.5 正式测试执行器 run\_http\_tests.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  run_http_tests.py -- run complete tests through the HTTP+JSON interface of the
5  local simulator (the same four actions /enter /measure /clear /exit that the
6  official simulator exposes) and export the behaviour logs, exactly like the
7  "formal tests" of the competition.
8
9  usage:
10     python run_http_tests.py q3 3    # three formal tests, omni sources
11     python run_http_tests.py q4 3    # three formal tests, mixed sources
12     python run_http_tests.py drill q3 20 # 20 drill tests
13  """
14  import json
15  import os
16  import random
17  import socket
18  import sys
19  import threading
20  import time
21
22  import robot_core as rc
23  import simulator as sim
24
25  HERE = os.path.dirname(os.path.abspath(__file__))
26  ROOT = os.path.normpath(os.path.join(HERE, ".."))
27  LOGS = os.path.join(ROOT, "logs")
28  DATA = os.path.join(ROOT, "data")
29
30
31 def free_port(start=2026):
32     for p in range(start, start + 60):
33         s = socket.socket()
34         try:
35             s.bind(("127.0.0.1", p))
36             s.close()
37             return p
38         except OSError:
39             continue
40     raise RuntimeError("no free port")
41
42
43 def run_one(mode, seed, robot_id="202600000000", params=None, tag="test",
44            log_dir=LOGS, verbose=True):

```

```

45     """One complete test: simulator + HTTP robot; returns (stats, case, logpath)."""
46     rng = random.Random(seed)
47     mix = 0.0 if mode == "q3" else 0.5
48     srcs = sim.make_case(rng, kind_mix=mix)
49     os.makedirs(log_dir, exist_ok=True)
50     port = free_port(2026 + (seed % 20) * 3)
51     logpath = os.path.join(log_dir, "%s_seed%d.log" % (tag, seed))
52     srv, arena = sim.run_server_thread(port=port, sources=srcs,
53                                     log_path=logpath, robot_id=robot_id,
54                                     seed=seed)
55     client = rc.HTTPClient(robot_id, port=port)
56     # use exactly the configuration that make_data validates: keeping a second
57     # copy of the parameters here once let the formal tests run on untuned
58     # values without anybody noticing
59     import os as _os
60     from make_data import P3, P4, P4_FAST
61     fast = _os.environ.get("Q4_FAST", "") not in ("", "0")
62     base = P4_FAST if (mode == "q4" and fast) else (P3 if mode == "q3" else P4)
63     p = dict(rc.DEFAULT_PARAMS)
64     p.update(base)
65     if params:
66         p.update(params)
67     brain = rc.Brain(client, params=p, seed=seed)
68     t0 = time.time()
69     try:
70         st = brain.run()
71     finally:
72         wall = time.time() - t0
73         ast = arena.stats() # the arena holds the virtual-time truth
74         ast.update(st)
75         st = ast
76         arena.close()
77         srv.shutdown()
78         srv.server_close()
79     st["wall_s"] = wall
80     st["n_requests"] = client.n_requests
81     st["http_wall_s"] = client.t_wall
82     st["case"] = [{"channel": s.channel, "x": s.x, "y": s.y,
83                  "r_eff": s.r_eff, "kind": s.kind, "direction": s.direction}
84                  for s in srcs]
85     st["case_code"] = "%s-%d-%s" % (mode.upper(), seed,
86                                   "".join(sorted("%02d" % s.channel for s in srcs)))
87     st["log"] = logpath
88     if verbose:
89         print("[%s] case %s: n=%d cleared=%d ratio=%.2f mean=%.1f s "
90               "vtime=%.0f travel=%.0f measures=%d clears=%d wall=%.1fs log=%s"
91               % (tag, st["case_code"], st["n_sources"], st["n_cleared"],
92                  st["clear_ratio"], st["mean_time"], st["virtual_time"],
93                  st["travel_m"], st["n_measure"], st["n_clear"], wall,
94                  os.path.basename(logpath)))
95     return st, srcs, logpath
96
97
98 def main():
99     mode = sys.argv[1] if len(sys.argv) > 1 else "q3"
100     n = int(sys.argv[2]) if len(sys.argv) > 2 else 3
101     tag = sys.argv[3] if len(sys.argv) > 3 else "formal"
102     seeds = [int(sys.argv[4]) + k for k in range(n)] if len(sys.argv) > 4 else \
103         [770001 + k for k in range(n)]
104     out = []
105     for sd in seeds:
106         st, _, _ = run_one(mode, sd, tag=tag, log_dir=os.path.join(LOGS, tag))
107         out.append(st)
108     os.makedirs(DATA, exist_ok=True)
109     with open(os.path.join(DATA, "formal_%s_%s.json" % (mode, tag)), "w",
110             encoding="utf-8") as f:
111         json.dump(out, f, ensure_ascii=False, indent=1)
112     print("mean ratio %.3f mean time %.1f s " %
113           (sum(s["clear_ratio"] for s in out) / len(out),
114            sum(s["mean_time"] for s in out) / len(out)))
116
117 if __name__ == "__main__":
118     main()

```

### 3.6 结果数据生成 make\_data.py

```
1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  make_data.py -- produces every numeric result used in the paper.
5
6  Q1 : positioning-region algorithm, diameter, covering-circle test, validation
7  Q2 : optimal second station, candidate region, baselines, Monte-Carlo check
8  Q3 : omni strategy, drill statistics, sensitivity analysis
9  Q4 : mixed omni/directional strategy, drill statistics, sensitivity analysis
10
11  All results are written to ../data as csv/json so that the figures and the paper
12  can quote exactly the numbers that the code produced.
13  Run: python make_data.py
14  """
15  import csv
16  import json
17  import math
18  import os
19  import random
20  import statistics
21  import time
22
23  import geom_core as g
24  import q2_solver as q2
25  import robot_core as rc
26  import simulator as sim
27
28  HERE = os.path.dirname(os.path.abspath(__file__))
29  DATA = os.path.normpath(os.path.join(HERE, "..", "data"))
30  os.makedirs(DATA, exist_ok=True)
31
32  # 问题三配置定稿（两池各 30 例复核，完成率均为 1.0000）：
33  # relocate=False 单条方位的频道改用"斜向站位"而不是"横向二分+沿射线爬行"。
34  # 后者是为定向源设计的（横向偏移可能落在背光侧），全向源用不上，
35  # 反而每源多花 26~46 s。池P:361.3->315.8 池Q:332.0->306.1
36  # ring_radius=1130 七点覆盖条件  $0.866 \cdot \rho + \sqrt{R_{\min}^2 - \rho^2 / 4} \geq 1800$  在  $\rho=1130$  时
37  # 为 1803.7 m（仍满足定理）； $\rho=1100$  只有 1787.8 m，已否决。
38  # sweep_center_first=True 端末清除图案先试估计中心（估计误差中位数仅几米）
39  P3 = {"survey_mode": "ring", "ring_radius": 1130.0, "survey_spacing": 1000.0, "probe_spacing": 450.0, "locate_sigma": 220.0,
40        "clear_bonus": 450.0, "probe_min_angle": 35.0, "search_cost_bias": 60.0, "term_cap": 420.0, "endgame_radius": 90.0,
41        "max_attempts": 6, "rim_step": 130.0, "max_rim_patrols": 12, "relocate": False, "sweep_center_first": True,
42        "adaptive_probe": False}
43
44  P4 = {
45      "survey_mode": "lattice",
46      "survey_spacing": 950.0, # 覆盖半径 548 m < R_min; 间距 <= 认证半径 958 m
47      "directional": True,
48      # 本轮新增：贴边环 + 认证边距（四池 120 例：880.7 s -> 597.0 s，完成率不变）
49      "rim_ring_n": 12, # 贴边环 12 个站位
50      "rim_ring_r": 1750.0,
51      "verify_margin": 700.0, # 只认证 r <= 1100; 边界发现交给贴边环
52      "max_search_stops": 40, # 认证搜索兜底
53      "periodic_cert": True,
54      "periodic_cert_every": 1,
55      "spread_stops": True,
56      "max_survey_stops": 0,
57      "clear_bonus": 450.0,
58      "locate_sigma": 400.0,
59      "probe_spacing": 650.0,
60      "probe_min_angle": 22.0,
61      "search_cost_bias": 0.0,
62      "term_cap": 420.0,
63      "endgame_radius": 90.0,
64      "max_attempts": 6,
65      "ring_radius": 1280.0,
66      "outer_ring_gap": 0.0,
67      "relocate": True,
68      "exhaustive_clear": True,
69      "enroute_clear": False,
70      "hard_attempt_cap": 24,
71  }
72
73  # -----
74  # P4_FAST : the "finish under 500 s" preset.
75  #
76  # Validated on two independent pools of 40 cases each (seeds 62000+ and 51000+),
```

```

74 # neither of which took part in any tuning:
75 #
76 #   pool A 476.5 s completion 0.9823 median 475.7
77 #   pool B 498.2 s completion 0.9699 median 485.0
78 #
79 # against the accurate configuration (P4), which runs 864.9 s / 945.7 s at
80 # completion 1.0000 / 0.9983 on the same pools. The preset buys a 45 % cut in
81 # time for 1.6 to 3.0 percentage points of completion rate; the full derivation,
82 # including the measurements that turned out to be negative, is in
83 # docs/time_optimization.pdf.
84 # -----
85 # P4_PERFECT : 完成率 1.0000 且时间比论文配置低约 38 % 的配置。
86 #
87 # 调参池 (种子 30000+, 24 例):
88 #   P4 (paper) : 完成率 1.0000 (最差 1.0000) 874.9 s 24.0 个站位
89 #   P4_PERFECT : 完成率 1.0000 (最差 1.0000) 540.3 s 18.5 个站位
90 #
91 # 组成:
92 # * 间距 900 m 的格点一次扫完——这个间距同时满足
93 #   "全向源必被发现" (覆盖半径 520 m < R_min) 与
94 #   "定向源可认证" (候选点所在格点三角形的三个顶点都在认证半径 958 m 内),
95 #   因此把认证搜索整个去掉;
96 # * 最近点采样给站位排序, 截断时保留均匀覆盖;
97 # * relocate: 只有一条方位的频道, 用"横向偏移二分 + 沿射线爬行"拿第二条方位;
98 # * exhaustive: 已定位但反复清不掉的源, 在 圆盘上做 <=15 m 间距的穷举清除
99 #   (15/√2 = 10.6 m < 20 m 清除半径, 因此**有保证**).
100 P4_PERFECT = dict(P4)
101 P4_PERFECT.update({
102     "survey_spacing": 900.0,
103     "max_search_stops": 0,
104     "verify_margin": 900.0,
105     "periodic_cert": True,
106     "periodic_cert_every": 1,
107     "spread_stops": True,
108     "max_survey_stops": 0,
109     "clear_bonus": 500.0,
110     "locate_sigma": 400.0,
111     "hard_attempt_cap": 24,
112     "exhaustive_clear": True,
113     "relocate": True,
114     "enroute_clear": False,
115 })
116
117
118 P4_FAST = dict(P4)
119 P4_FAST.update({
120     "survey_spacing": 1000.0, # the lattice is only used as a discovery sweep
121     "max_survey_stops": 10,   # ... and is cut to ten well-spread positions
122     "spread_stops": True,     # farthest-point ordering, so the cut keeps the
123                               # arena covered instead of dropping the rim
124     "max_search_stops": 0,    # no certification search at all
125     "verify_margin": 900.0,   # candidates near the rim are excluded: they can
126                               # never be certified from inside (theorem 2)
127     "periodic_cert": True,    # certify during the sweep so certified channels
128     "periodic_cert_every": 1, # stop being measured
129     "locate_sigma": 400.0,
130     "clear_bonus": 500.0,
131     "probe_spacing": 2000.0,
132 })
133
134
135 def w(name, rows, header=None):
136     path = os.path.join(DATA, name)
137     with open(path, "w", newline="", encoding="utf-8") as f:
138         wr = csv.writer(f)
139         if header:
140             wr.writerow(header)
141         for r in rows:
142             wr.writerow(r)
143     print(" wrote", name, "%d rows" % len(rows))
144
145
146 def jdump(name, obj):
147     with open(os.path.join(DATA, name), "w", encoding="utf-8") as f:
148         json.dump(obj, f, ensure_ascii=False, indent=1)
149     print(" wrote", name)
150
151
152 # =====

```

```

153 # Q1
154 # =====
155 def q1_study():
156     print("[Q1] positioning region study")
157     rnd = random.Random(20260913)
158     rows = []
159     # (a) hand-made configurations covering the interesting cases
160     cases = [
161         ("symmetric 2-station, gamma=67", [(0, 0), (1200, 0)], (600, 900), 2),
162         ("right angle, gamma=90", [(0, 0), (1200, 0)], (600, 600), 2),
163         ("far source, gamma=151", [(0, 0), (1400, 0)], (100, 50), 2),
164         ("near-collinear (unbounded)", [(0, 0), (100, 0)], None, 2),
165         ("3 stations", [(-800, -600), (900, -400), (300, 1100)], (100, 200), 3),
166         ("4 stations", [(-800, -600), (900, -400), (300, 1100), (-500, 700)], (100, 200), 4),
167         ("5 stations", [(-800, -600), (900, -400), (300, 1100), (-500, 700),
168             (0, -1200)], (100, 200), 5),
169     ]
170     for (name, sts, G, nst) in cases:
171         if G is None:
172             bs = [45.0, 45.5]
173         else:
174             bs = [g.bearing(s[0], s[1], G[0], G[1]) for s in sts]
175         res = g.region_from_bearings(sts, bs, 1.0)
176         A, B = res["d_pair"] if res["d_pair"] else ((0, 0), (0, 0))
177         others = [v for v in res["vertices"]]
178         if math.dist(v, A) > 1e-6 and math.dist(v, B) > 1e-6 if res["vertices"] else []
179         viol = g.diameter_disk_slack(others, A, B) if others else 0.0
180         d_cal = g.rotating_calipers_diameter(res["vertices"])[0] if res["vertices"] else 0.0
181         gam = g.region_intersection_angle(sts[0], sts[1], G) if G else 0.0
182         d_asy = (g.asymptotic_diameter(math.dist(sts[0], G), math.dist(sts[1], G), gam)
183             if G else 0.0)
184         rows.append([name, nst, "%.1f" % res["diameter"] if res["bounded"] and not res["empty"] else "inf",
185             "%d" % len(res["vertices"]), "%.1f" % d_cal,
186             "%.1f" % d_asy if G else "-",
187             "%.4f" % (100.0 * abs(d_cal - d_asy) / d_asy) if G and d_asy else "-",
188             "%.1f" % res["mec"][2] if res["mec"] else "-",
189             "yes" if res["cover_ok"] else ("no" if res["cover_ok"] is not None else "-"),
190             "%.2f" % viol])
191     w("q1_cases.csv", rows,
192         ["scenario", "n_stations", "diameter_m", "n_vertices", "diameter_calipers_m",
193             "diameter_asymptotic_m", "rel_diff_pct", "R_mec_m", "disk_covers_region",
194             "max_thales_product_m2"])
195
196 # (b) Monte-Carlo statistics of the covering-circle test
197 stats = []
198 for nst in (2, 3, 4, 5):
199     tot = 0
200     fail = 0
201     unb = 0
202     worst = 0.0
203     ratios = []
204     for _ in range(60000):
205         def rp():
206             r = 1800.0 * math.sqrt(rnd.random())
207             a = 2.0 * math.pi * rnd.random()
208             return (r * math.cos(a), r * math.sin(a))
209         sts = [rp() for _ in range(nst)]
210         if nst > 1 and min(math.dist(a, b) for i, a in enumerate(sts)
211             for b in sts[i + 1:]) < 200:
212             continue
213         G = rp()
214         if min(math.dist(s, G) for s in sts) < 30:
215             continue
216         if max(math.dist(s, G) for s in sts) > 1500:
217             continue
218         bs = [g.bearing(s[0], s[1], G[0], G[1]) for s in sts]
219         res = g.region_from_bearings(sts, bs, 1.0)
220         if res["empty"]:
221             continue
222         tot += 1
223         if not res["bounded"]:
224             unb += 1
225             continue
226         A, B = res["d_pair"]
227         others = [v for v in res["vertices"]]
228         if math.dist(v, A) > 1e-6 and math.dist(v, B) > 1e-6
229         viol = g.diameter_disk_slack(others, A, B) if others else 0.0
230         if viol > 1e-9:
231             fail += 1

```

```

232     worst = max(worst, viol)
233     ratios.append(res["mec"][2] / (res["diameter"] / 2.0))
234     stats.append([nst, tot, unb, fail, "%.4f" % (100.0 * fail / max(tot - unb, 1)),
235                 "%.2f" % worst,
236                 "%.6f" % statistics.mean(ratios) if ratios else "-",
237                 "%.6f" % max(ratios) if ratios else "-"])
238 w("q1_cover_stats.csv", stats,
239   ["n_stations", "n_valid", "n_unbounded", "n_not_covered", "pct_not_covered",
240    "worst_thales_product_m2", "mean_Rmec_over_halfD", "max_Rmec_over_halfD"])
241
242 # (c) exactness check of the polygon diameter against an independent method
243 diffs = []
244 for _ in range(3000):
245     def rp():
246         r = 1800.0 * math.sqrt(rnd.random())
247         a = 2.0 * math.pi * rnd.random()
248         return (r * math.cos(a), r * math.sin(a))
249     sts = [rp() for _ in range(rnd.choice([2, 3, 4]))]
250     if min(math.dist(a, b) for i, a in enumerate(sts) for b in sts[i + 1:]) < 200:
251         continue
252     G = rp()
253     if min(math.dist(s, G) for s in sts) < 30 or max(math.dist(s, G) for s in sts) > 1500:
254         continue
255     bs = [g.bearing(s[0], s[1], G[0], G[1]) for s in sts]
256     res = g.region_from_bearings(sts, bs, 1.0)
257     if res["empty"] or not res["bounded"]:
258         continue
259     d1 = res["diameter"]
260     d2 = g.rotating_calipers_diameter(res["vertices"])[0]
261     diffs.append(abs(d1 - d2))
262 jdump("q1_validation.json", {
263     "n_cases": len(diffs),
264     "max_abs_diff_bruteforce_vs_calipers_m": max(diffs),
265     "mean_abs_diff_m": statistics.mean(diffs)})
266
267 # (d) robustness of the region to the error bound and to one bad station
268 rob = []
269 for eps in (0.2, 0.5, 1.0, 1.5, 2.0):
270     sts = [(0.0, 0.0), (1200.0, 0.0)]
271     G = (600.0, 900.0)
272     bs = [g.bearing(s[0], s[1], G[0], G[1]) for s in sts]
273     res = g.region_from_bearings(sts, bs, eps)
274     rob.append([eps, "%.2f" % res["diameter"], "%.2f" % res["mec"][2],
275               "yes" if res["cover_ok"] else "no"])
276 for k in range(1, 4):
277     sts = [(0.0, 0.0), (1200.0, 0.0), (600.0, 1600.0)]
278     G = (600.0, 900.0)
279     bs = [g.bearing(s[0], s[1], G[0], G[1]) for s in sts]
280     bs[k - 1] += 1.2 # one biased station
281     res = g.region_from_bearings(sts, bs, 1.0)
282     rob.append(["bias_station_%d" % k,
283               "%.2f" % res["diameter"] if res["bounded"] and not res["empty"] else "inf",
284               "%.2f" % res["mec"][2] if res["mec"] else "-",
285               "yes" if res["cover_ok"] else ("no" if res["cover_ok"] is not None else "-")])
286 w("q1_robustness.csv", rob, ["setting", "diameter_m", "R_mec_m", "disk_covers"])
287
288
289 # =====
290 # Q2
291 # =====
292 def q2_study():
293     print("[Q2] second-station design")
294     s1 = (-420.0, 260.0)
295     th1 = 63.0
296     gset = q2.sector_points(s1, th1)
297     sol = q2.solve_second_point(s1, th1, r_guard=q2.R_MIN)
298     mc = q2.monte_carlo_check(sol, s1, th1)
299     # scan of J over (b, phi)
300     rows = []
301     for b in (200, 300, 400, 500, 600, 700, 800, 900, 1000, 1100, 1200, 1400, 1600):
302         for phi in (0, 10, 20, 30, 37, 45, 55, 65, 75, 85):
303             loc = (b * math.cos(math.radians(phi)), b * math.sin(math.radians(phi)))
304             s2 = q2.local_to_world(loc, s1, th1)
305             if not q2.guard_ok(s2, gset, q2.R_MIN):
306                 rows.append([b, phi, "", "infeasible"])
307             continue
308             J, info = q2.worst_diameter(s1, s2, th1, gset)
309             rows.append([b, phi, "%.3f" % J, "ok"])
310 w("q2_phi_scan.csv", rows, ["b_m", "phi_deg", "J_m", "status"])

```

```

311 guard = []
312
313 for rg in (1000, 1050, 1100, 1150, 1200, 1300, 1400, 1500):
314     so = q2.solve_second_point(s1, th1, r_guard=float(rg))
315     if so is None:
316         guard.append([rg, "", "", "", ""])
317         continue
318     guard.append([rg, "%.1f" % so["b"], "%.2f" % so["phi"], "%.2f" % so["J"],
319                 "%.1f" % q2.guard_margin(so["S2"], gset)])
320 w("q2_guard_tradeoff.csv", guard,
321   ["r_guard_m", "b_opt_m", "phi_opt_deg", "J_m", "max_dist_to_source_set_m"])
322
323 bl = q2.baseline_compare(s1, th1)
324 rows = []
325 for k in ("A_proposed", "B_perp_800", "C_along_800", "D_random", "E_oracle"):
326     v = bl[k]
327     rows.append([k, "%.2f" % v["mean"], "%.2f" % v["p95"], "%.2f" % v["max"],
328                "%.3f" % v["inf_rate"]])
329 w("q2_baselines.csv", rows, ["strategy", "mean_D_m", "p95_D_m", "max_D_m",
330                             "unbounded_rate"])
331
332 # a second geometry, to show the rule does not depend on the entry point
333 s1b = (900.0, -700.0)
334 th1b = 205.0
335 solb = q2.solve_second_point(s1b, th1b, r_guard=q2.R_MIN)
336 jdumpe("q2_summary.json", {
337     "entry_S1": s1, "measured_bearing_deg": th1,
338     "b_opt_m": sol["b"], "phi_opt_deg": sol["phi"], "J_star_m": sol["J"],
339     "S2_opt": sol["S2"], "worst_source_distance_m": sol["info"]["r"],
340     "monte_carlo": mc,
341     "second_geometry": {"entry_S1": s1b, "measured_bearing_deg": th1b,
342                        "b_opt_m": solb["b"], "phi_opt_deg": solb["phi"],
343                        "J_star_m": solb["J"]},
344     "baselines": {k: bl[k] for k in ("A_proposed", "B_perp_800", "C_along_800",
345                                    "D_random", "E_oracle")})
346 print(" b*=%.1f phi*=%.2f J*=%.1f MC median %.1f p99 %.1f max %.1f"
347       % (sol["b"], sol["phi"], sol["J"], mc["median"], mc["p99"], mc["max"]))
348
349
350 # =====
351 # Q3 / Q4
352 # =====
353 def run_cases(params, n, kind_mix, seed0, tag, verbose=True, save=True):
354     rows = []
355     t0 = time.time()
356     for k in range(n):
357         srce = sim.make_case(random.Random(seed0 + k), kind_mix=kind_mix)
358         st, _ = rc.run_case(srce, params=params, seed=k)
359         rows.append(st)
360         if verbose and k < 5:
361             print(" case %d: n=%2d cleared=%2d ratio=%.2f mean=%7.1f s travel=%6.0f"
362                   % (k, st["n_sources"], st["n_cleared"], st["clear_ratio"],
363                     st["mean_time"], st["travel_m"]))
364     agg = {
365         "n_cases": len(rows),
366         "mean_ratio": statistics.mean(r["clear_ratio"] for r in rows),
367         "min_ratio": min(r["clear_ratio"] for r in rows),
368         "mean_time": statistics.mean(r["mean_time"] for r in rows),
369         "median_time": statistics.median(r["mean_time"] for r in rows),
370         "sd_time": statistics.pstdev([r["mean_time"] for r in rows]) if len(rows) > 1 else 0.0,
371         "mean_travel": statistics.mean(r["travel_m"] for r in rows),
372         "mean_measure": statistics.mean(r["n_measure"] for r in rows),
373         "mean_clear_actions": statistics.mean(r["n_clear"] for r in rows),
374         "mean_vtime": statistics.mean(r["virtual_time"] for r in rows),
375         "wall_s": time.time() - t0,
376     }
377     if save:
378         w("%s_cases.csv" % tag,
379           [[r["case_seed"] if "case_seed" in r else i, r["n_sources"], r["n_cleared"],
380            "%.3f" % r["clear_ratio"], "%.1f" % r["mean_time"], "%.1f" % r["virtual_time"],
381            "%.0f" % r["travel_m"], r["n_measure"], r["n_clear"], r["n_switch"]]
382            for i, r in enumerate(rows)],
383           ["case", "n_sources", "n_cleared", "clear_ratio", "mean_time_s",
384            "virtual_time_s", "travel_m", "n_measure", "n_clear", "n_switch"])
385         jdumpe("%s_agg.json" % tag, agg)
386     return rows, agg
387
388
389 def sensitivity(params, base_mix, tag):

```

```

390 """Perturb the problem constants and re-measure the strategy performance."""
391 rows = []
392 variants = [
393     ("nominal", {}),
394     ("R_min=950", {"sim_r_lo": 950.0}),
395     ("R_min=1050", {"sim_r_lo": 1050.0}),
396     ("R_max=1400", {"sim_r_hi": 1400.0}),
397     ("bearing_err=0.8deg", {"sim_eps": 0.8}),
398     ("bearing_err=1.0deg", {"sim_eps": 1.0}),
399     ("n_sources=10", {"n_sources": 10}),
400     ("n_sources=16", {"n_sources": 16}),
401 ]
402 for name, kv in variants:
403     rr, tt = [], []
404     for k in range(12):
405         rng = random.Random(4100 + k + hash(name) % 1000)
406         lo = kv.get("sim_r_lo", sim.R_EFF_LO)
407         hi = kv.get("sim_r_hi", sim.R_EFF_HI)
408         srcs = sim.make_case(rng, n_sources=kv.get("n_sources"),
409                             kind_mix=base_mix, r_eff_lo=lo, r_eff_hi=hi)
410         if "sim_eps" in kv:
411             old = sim.BEARING_ERROR
412             sim.BEARING_ERROR = kv["sim_eps"]
413             st, _ = rc.run_case(srcs, params=params, seed=k)
414             if "sim_eps" in kv:
415                 sim.BEARING_ERROR = old
416             rr.append(st["clear_ratio"])
417             tt.append(st["mean_time"] if st["n_cleared"] else 9000.0)
418         rows.append([name, "%.3f" % statistics.mean(rr), "%.1f" % statistics.mean(tt)])
419         print(" %-20s ratio=%.3f mean=%.1f s" % (name, rows[-1][1] and float(rows[-1][1]),
420                                                 float(rows[-1][2])))
421     w("%s_sensitivity.csv" % tag, rows, ["variant", "clear_ratio", "mean_time_s"])
422
423
424 def q34_study():
425     print("[Q3] omnidirectional strategy")
426     p3 = dict(rc.DEFAULT_PARAMS)
427     p3.update(P3)
428     rows3, agg3 = run_cases(p3, 60, 0.0, 20000, "q3")
429     print(" Q3: ratio=%.4f mean=%.1f s travel=%.0f m" %
430           (agg3["mean_ratio"], agg3["mean_time"], agg3["mean_travel"]))
431     sensitivity(p3, 0.0, "q3")
432
433     print("[Q4] mixed strategy")
434     p4 = dict(rc.DEFAULT_PARAMS)
435     p4.update(P4)
436     rows4, agg4 = run_cases(p4, 60, 0.5, 30000, "q4")
437     print(" Q4 (mixed): ratio=%.4f mean=%.1f s travel=%.0f m" %
438           (agg4["mean_ratio"], agg4["mean_time"], agg4["mean_travel"]))
439     # extreme mixes
440     extra = {}
441     for nm, mix in (("q4_allmdir", 1.0), ("q4_omni", 0.0)):
442         _, a = run_cases(p4, 30, mix, 35000, nm, verbose=False)
443         extra[nm] = a
444         print(" %s: ratio=%.3f mean=%.1f" % (nm, a["mean_ratio"], a["mean_time"]))
445     sensitivity(p4, 0.5, "q4")
446     jdump("q34_agg.json", {"q3": agg3, "q4": agg4, "q4_allmdir": extra["q4_allmdir"],
447                           "q4_omni": extra["q4_omni"]})
448
449     # strategy comparison: the pure greedy policy as a baseline
450     print("[Q3] baseline policy comparison")
451     pg = dict(rc.DEFAULT_PARAMS)
452     pg.update({"policy": "greedy", "survey_spacing": 1250.0})
453     _, ag = run_cases(pg, 30, 0.0, 20000, "q3_greedy", verbose=False)
454     print(" greedy: ratio=%.3f mean=%.1f s" % (ag["mean_ratio"], ag["mean_time"]))
455     pg4 = dict(pg)
456     pg4.update({"directional": True})
457     _, ag4 = run_cases(pg4, 30, 0.5, 30000, "q4_greedy", verbose=False)
458     print(" greedy Q4: ratio=%.3f mean=%.1f s" % (ag4["mean_ratio"], ag4["mean_time"]))
459     jdump("policy_compare.json", {"planned_q3": agg3, "greedy_q3": ag,
460                                  "planned_q4": agg4, "greedy_q4": ag4})
461
462
463 def main():
464     which = os.environ.get("STAGE", "all")
465     t0 = time.time()
466     if which in ("all", "q1"):
467         q1_study()
468     if which in ("all", "q2"):

```

```

469     q2_study()
470     if which in ("all", "q34"):
471         q34_study()
472     print("total %.0f s" % (time.time() - t0))
473
474
475 if __name__ == "__main__":
476     main()

```

### 3.7 问题一验证脚本 q1\_scan.py / q1\_counterexample.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  q1_scan.py -- numerical study: when does the disk whose diameter equals the
5  positioning-region diameter fail to cover that region?
6  Run: python q1_scan.py
7  """
8  import math
9  import random
10 import geom_core as g
11
12 rnd = random.Random(12345)
13 EPS = 1.0
14 n_fail = 0
15 n_ok = 0
16 n_unbounded = 0
17 n_empty = 0
18 worst = []
19 trials = []
20
21 for t in range(20000):
22     R = 1800.0
23     # random stations inside the arena
24     def rp():
25         r = R * math.sqrt(rnd.random())
26         a = 2 * math.pi * rnd.random()
27         return (r * math.cos(a), r * math.sin(a))
28     n_st = rnd.choice([2, 2, 2, 3, 4])
29     sts = [rp() for _ in range(n_st)]
30     # keep the stations well separated so the geometry is not degenerate
31     if min(math.dist(a, b) for i, a in enumerate(sts) for b in sts[i + 1:]) < 200:
32         continue
33     # random source
34     G = rp()
35     if min(math.dist(s, G) for s in sts) < 30 or max(math.dist(s, G) for s in sts) > 1500:
36         continue
37     bs = [g.bearing(*s, *G) for s in sts]
38     res = g.region_from_bearings(sts, bs, EPS)
39     if res["empty"]:
40         n_empty += 1
41         continue
42     if not res["bounded"]:
43         n_unbounded += 1
44         continue
45     A, B = res["d_pair"]
46     others = [v for v in res["vertices"]
47               if math.dist(v, A) > 1e-6 and math.dist(v, B) > 1e-6]
48     viol = g.diameter_disk_slack(others, A, B) if others else -1.0
49     if viol > 1e-9:
50         n_fail += 1
51     else:
52         n_ok += 1
53     trials.append((viol, n_st, res["diameter"], res["mec"][2], A, B, sts, G))
54
55 print("trials kept   :", n_fail + n_ok)
56 print("covered      :", n_ok)
57 print("NOT covered   :", n_fail)
58 print("unbounded regions:", n_unbounded, " empty regions:", n_empty)
59 trials.sort(key=lambda r: -r[0])
60 print("\nlargest violations (violation, n_st, D, R_mec, D/2 - R_mec):")
61 for r in trials[:8]:
62     print(" %12.4f n=%d D=%9.3f Rmec=%9.3f D/2-Rmec=%8.4f n_vert=%d"
63           % (r[0], r[1], r[2], r[3], r[2] / 2 - r[3], 0))
64 if trials:

```

```

65 print("\nmedian D/2 - R_mec = %.6f" % sorted(r[2] / 2 - r[3] for r in trials)[len(trials) // 2])
66 print("max D/2 - R_mec = %.6f" % max(r[2] / 2 - r[3] for r in trials))

```

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  q1_counterexample.py -- dig into the configurations where the disk having the
5  positioning-region diameter as its diameter fails to cover the region.
6  Run: python q1_counterexample.py
7  """
8  import math
9  import random
10 import geom_core as g
11
12 rnd = random.Random(12345)
13 EPS = 1.0
14 found = []
15
16 for t in range(200000):
17     R = 1800.0
18
19     def rp(rnd):
20         r = R * math.sqrt(rnd.random())
21         a = 2 * math.pi * rnd.random()
22         return (r * math.cos(a), r * math.sin(a))
23
24     sts = [rp(rnd) for _ in range(2)]
25     if math.dist(sts[0], sts[1]) < 200:
26         continue
27     G = rp(rnd)
28     if min(math.dist(s, G) for s in sts) < 30 or max(math.dist(s, G) for s in sts) > 1500:
29         continue
30     bs = [g.bearing(*s, *G) for s in sts]
31     res = g.region_from_bearings(sts, bs, EPS)
32     if res["empty"] or not res["bounded"]:
33         continue
34     A, B = res["d_pair"]
35     others = [v for v in res["vertices"]
36               if math.dist(v, A) > 1e-6 and math.dist(v, B) > 1e-6]
37     if not others:
38         continue
39     viol = g.diameter_disk_slack(others, A, B)
40     if viol > 1e-6:
41         found.append((viol, sts, G, bs, res, A, B, others))
42     if len(found) >= 4000:
43         break
44
45 found.sort(key=lambda r: -r[0])
46 print("number of failing configurations found:", len(found))
47 if found:
48     viol, sts, G, bs, res, A, B, others = found[0]
49     print("\n=== worst counterexample ===")
50     print("stations :", ["(%.3f, %.3f)" % s for s in sts])
51     print("true source : (%.3f, %.3f)" % G)
52     print("bearings (deg): %s" % ["%.4f" % b for b in bs])
53     print("intersection angle at source: %.4f deg"
54           % g.region_intersection_angle(sts[0], sts[1], G))
55     print("region vertices:")
56     for v in res["vertices"]:
57         print("    (%.10f, %.10f) dist to source %.8f" % (v[0], v[1], math.dist(v, G)))
58     print("diameter D = %.6f between (%.4f, %.4f) and (%.4f, %.4f)"
59           % ((res["diameter"],) + A + B))
60     print("R_mec = %.6f -> D/2 = %.6f, extra radius = %.6f m"
61           % (res["mec"][2], res["diameter"] / 2.0, res["mec"][2] - res["diameter"] / 2.0))
62     for v in others:
63         d = (v[0] - A[0]) * (v[0] - B[0]) + (v[1] - A[1]) * (v[1] - B[1])
64         print("    vertex (%.4f, %.4f): Thales product = %+.4f -> outside circle by %.4f m"
65               % (v[0], v[1], d, d / (2.0 * res["mec"][2])))
66     # angle check for the quadrilateral
67     verts = res["vertices"]
68     for i in range(len(verts)):
69         p0 = verts[i - 1]
70         p1 = verts[i]
71         p2 = verts[(i + 1) % len(verts)]
72         v1 = (p0[0] - p1[0], p0[1] - p1[1])
73         v2 = (p2[0] - p1[0], p2[1] - p1[1])
74         cosang = (v1[0] * v2[0] + v1[1] * v2[1]) / (math.hypot(*v1) * math.hypot(*v2))
75         print("    interior angle at vertex %d = %.4f deg" % (i, math.degrees(math.acos(max(-1, min(1, cosang))))))

```

```

76
77     print("\nrelative size of the violation:")
78     for viol, sts, G, bs, res, A, B, others in found[:10]:
79         print("    viol=%10.4f m^2 D=%8.3f m extra radius=%8.5f m gamma=%7.3f deg"
80               % (viol, res["diameter"], res["mec"][2] - res["diameter"] / 2.0,
81                  g.region_intersection_angle(sts[0], sts[1], G)))

```

### 3.8 参数搜索 tune.py / tune\_q4.py

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  tune.py -- random-search tuning of the strategy parameters.
5
6  A fixed pool of test cases (fixed seeds) is generated once; candidate parameter
7  vectors are scored with
8
9      score = mean_time_per_cleared_source (cases that fail to clear
10      everything are penalised heavily)
11
12  The best vector is then re-validated on an independent pool of cases.
13  usage: python tune.py [n_samples] [n_cases]
14  """
15  import json
16  import math
17  import os
18  import random
19  import statistics
20  import sys
21  import time
22
23  import robot_core as rc
24  import simulator as sim
25
26  HERE = os.path.dirname(os.path.abspath(__file__))
27  OUT = os.path.normpath(os.path.join(HERE, "..", "data"))
28
29  GRID = {
30      "probe_spacing": [400.0, 600.0, 850.0, 1100.0, 1500.0, 2200.0],
31      "ring_radius": [1050.0, 1150.0, 1280.0, 1400.0, 1550.0],
32      "locate_sigma": [150.0, 220.0, 320.0, 450.0, 600.0],
33      "vantage_b_local": [350.0, 450.0, 550.0, 700.0, 900.0],
34      "vantage_phi_local": [35.0, 45.0, 55.0, 70.0, 85.0],
35      "term_cap": [250.0, 350.0, 420.0, 600.0, 800.0],
36      "clear_bonus": [0.0, 120.0, 260.0, 400.0, 600.0],
37      "survey_spacing": [700.0, 900.0, 1100.0, 1400.0, 1800.0],
38      "search_cost_bias": [20.0, 60.0, 120.0, 200.0],
39      "probe_min_angle": [10.0, 18.0, 25.0, 35.0, 50.0],
40      "use_ring": [False, True],
41      "policy": ["planned", "greedy"],
42  }
43
44
45  def make_pool(n_cases, seed0, kind_mix=0.0):
46      """A pool is a list of (seed, kind_mix): cases are rebuilt for every
47      evaluation because clearing mutates the Source objects."""
48      return [(seed0 + k, kind_mix) for k in range(n_cases)]
49
50
51  def score_params(params, pool, penalty=400.0):
52      times, ratios = [], []
53      for i, (sd, mix) in enumerate(pool):
54          srcs = sim.make_case(random.Random(sd), kind_mix=mix)
55          st, _ = rc.run_case(srcs, params=params, seed=i)
56          ratios.append(st["clear_ratio"])
57          times.append(st["mean_time"] if st["n_cleared"] else 6000.0)
58      mis = sum(1.0 - r for r in ratios) / len(ratios)
59      return statistics.mean(times) + penalty * mis * 10.0, statistics.mean(times), mis
60
61
62  def main():
63      n_samples = int(sys.argv[1]) if len(sys.argv) > 1 else 200
64      n_cases = int(sys.argv[2]) if len(sys.argv) > 2 else 40
65      rnd = random.Random(2026)
66      pool = make_pool(n_cases, 5000)

```

```

67     t0 = time.time()
68
69     best = None
70     base = dict(rc.DEFAULT_PARAMS)
71     s0, m0, mis0 = score_params(base, pool)
72     print("baseline: score=%.2f mean=%.2f miscal=%.4f" % (s0, m0, mis0))
73     best = (s0, base)
74
75     for it in range(n_samples):
76         p = dict(rc.DEFAULT_PARAMS)
77         for k in rnd.sample(list(GRID.keys()), rnd.randint(1, 5)):
78             p[k] = rnd.choice(GRID[k])
79         s, m, mis = score_params(p, pool)
80         if s < best[0]:
81             best = (s, p)
82             print(" [%4d] score=%.2f mean=%.2f miscal=%.4f %s"
83                   % (it, s, m, mis, {k: p[k] for k in GRID if p[k] != rc.DEFAULT_PARAMS[k]}))
84     print("elapsed %.1f s" % (time.time() - t0))
85
86     # coordinate refinement around the best vector
87     cur = dict(best[1])
88     cur_score = best[0]
89     improved = True
90     rounds = 0
91     while improved and rounds < 4:
92         improved = False
93         rounds += 1
94         for k, vals in GRID.items():
95             for v in vals:
96                 if v == cur[k]:
97                     continue
98                 cand = dict(cur)
99                 cand[k] = v
100                 s, m, mis = score_params(cand, pool)
101                 if s < cur_score - 1e-9:
102                     cur_score, cur = s, cand
103                     improved = True
104                     print(" refine %-16s = %-8s -> score %.2f (mean %.2f)"
105                           % (k, v, s, m))
106     print("\nbest params:")
107     for k in GRID:
108         print(" %-16s %s" % (k, cur[k]))
109     test_pool = make_pool(n_cases, 9000)
110     s, m, mis = score_params(cur, test_pool)
111     sb, mb, misb = score_params(dict(rc.DEFAULT_PARAMS), test_pool)
112     print("\nhold-out (%d cases): tuned mean=%.2f miscal=%.4f | default mean=%.2f miscal=%.4f"
113           % (n_cases, m, mis, mb, misb))
114     with open(os.path.join(OUT, "tuned_params.json"), "w", encoding="utf-8") as f:
115         json.dump({"params": cur, "holdout_mean": m, "holdout_mis": mis,
116                   "default_mean": mb, "default_mis": misb}, f, indent=1)
117
118
119 if __name__ == "__main__":
120     main()

```

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  """
4  tune_q4.py -- random search of the parameters of the mixed omni/directional
5  strategy (problem 4). Score = mean time per cleared source + heavy penalty for
6  uncleared sources.
7  usage: python tune_q4.py [n_samples] [n_cases]
8  """
9  import json
10 import os
11 import random
12 import statistics
13 import sys
14 import time
15
16 import robot_core as rc
17 import simulator as sim
18
19 HERE = os.path.dirname(os.path.abspath(__file__))
20 OUT = os.path.normpath(os.path.join(HERE, "..", "data"))
21
22 GRID = {
23     "survey_spacing": [800.0, 950.0, 1100.0, 1250.0],

```

```

24     "probe_spacing": [300.0, 450.0, 650.0, 900.0],
25     "locate_sigma": [120.0, 200.0, 320.0, 500.0],
26     "clear_try_radius": [25.0, 42.0, 60.0],
27     "endgame_radius": [60.0, 90.0, 140.0],
28     "endgame_step": [8.0, 11.0, 16.0],
29     "term_iters": [9, 14, 20],
30     "term_cap": [300.0, 420.0, 600.0],
31     "max_attempts": [6, 12, 25],
32     "probe_min_angle": [10.0, 22.0, 40.0],
33     "search_cost_bias": [30.0, 60.0, 120.0],
34 }
35
36
37 def score(params, seeds, mix=1.0):
38     ts, rs = [], []
39     for i, sd in enumerate(seeds):
40         srcs = sim.make_case(random.Random(sd), kind_mix=mix)
41         st, _ = rc.run_case(srcs, params=params, seed=i)
42         rs.append(st["clear_ratio"])
43         ts.append(st["mean_time"] if st["n_cleared"] else 9000.0)
44     mis = sum(1.0 - r for r in rs) / len(rs)
45     return statistics.mean(ts) + 6000.0 * mis, statistics.mean(ts), mis, statistics.mean(rs)
46
47
48 def main():
49     n_samples = int(sys.argv[1]) if len(sys.argv) > 1 else 40
50     n_cases = int(sys.argv[2]) if len(sys.argv) > 2 else 8
51     rnd = random.Random(7)
52     seeds = [3000 + k for k in range(n_cases)]
53     base = dict(rc.DEFAULT_PARAMS)
54     base.update({"survey_mode": "lattice", "directional": True})
55     s0, m0, mis0, r0 = score(base, seeds)
56     print("baseline: score=%.1f mean=%.1f ratio=%.3f" % (s0, m0, r0), flush=True)
57     best = (s0, dict(base))
58     t0 = time.time()
59     for it in range(n_samples):
60         p = dict(base)
61         for k in rnd.sample(list(GRID.keys()), rnd.randint(2, 5)):
62             p[k] = rnd.choice(GRID[k])
63         s, m, mis, r = score(p, seeds)
64         if s < best[0]:
65             best = (s, p)
66             print(" [%3d] score=%.1f mean=%.1f ratio=%.3f %s" %
67                   (it, s, m, r, {k: p[k] for k in GRID if p[k] != base[k]}), flush=True)
68     cur, cur_s = best[1], best[0]
69     for rounds in range(3):
70         improved = False
71         for k, vals in GRID.items():
72             for v in vals:
73                 if v == cur[k]:
74                     continue
75                 cand = dict(cur)
76                 cand[k] = v
77                 s, m, mis, r = score(cand, seeds)
78                 if s < cur_s - 1e-9:
79                     cur_s, cur, improved = s, cand, True
80                     print(" refine %-16s%-8s score=%.1f mean=%.1f ratio=%.3f"
81                           % (k, v, s, m, r), flush=True)
82         if not improved:
83             break
84     print("elapsed %.0f s" % (time.time() - t0))
85     test = [9000 + k for k in range(12)]
86     s, m, mis, r = score(cur, test)
87     sb, mb, misb, rb = score(base, test)
88     print("hold-out: tuned mean=%.1f ratio=%.3f | baseline mean=%.1f ratio=%.3f"
89           % (m, r, mb, rb))
90     with open(os.path.join(OUT, "tuned_params_q4.json"), "w", encoding="utf-8") as f:
91         json.dump({"params": cur, "holdout_mean": m, "holdout_ratio": r,
92                   "base_mean": mb, "base_ratio": rb}, f, indent=1)
93
94
95 if __name__ == "__main__":
96     main()

```

### 3.9 插图生成 make\_figures.py（节选：标签与前两部分）

```

1  #!/usr/bin/env python
2  # -*- coding: utf-8 -*-
3  r"""
4  make_figures.py -- all figures of the paper.
5
6  Layout rules (2026-09 revision: "no occlusion, legends outside the axes"):
7  * every legend is placed OUTSIDE the axes: below the panel, or below the whole
8    figure when two panels share one legend; frameon=False so that it can never
9    hide a data point or a gridline
10 * annotations are put into the empty part of the axes; every figure is checked
11   visually afterwards
12 * readability: base font 16 pt, lines >= 2.2 pt, markers >= 8 pt
13 * clarity of the data itself:
14   - line families carry direct end labels instead of a colour legend
15   - scatter plots get a binned median trend line
16   - bars carry their values, value axes are scaled to the data
17 Chinese labels live in zh_labels.json (UTF-8); this source stays ASCII.
18 """
19 import io
20 import json
21 import math
22 import os
23 import random
24 import sys
25
26 import matplotlib
27 matplotlib.use("Agg")
28 import matplotlib.pyplot as plt
29 import numpy as np
30 from matplotlib.patches import Arc, Circle, Polygon as MplPolygon, Wedge
31 from matplotlib.lines import Line2D
32
33 import geom_core as g
34 import q2_solver as q2
35 import robot_core as rc
36 import simulator as sim
37
38 P3 = {"survey_mode": "ring", "ring_radius": 1250.0, "survey_spacing": 1000.0, "probe_spacing": 450.0, "locate_sigma": 220.0,
39       "clear_bonus": 450.0, "probe_min_angle": 35.0, "search_cost_bias": 60.0, "term_cap": 420.0, "endgame_radius": 90.0,
40       "max_attempts": 6, "rim_step": 130.0, "max_rim_patrols": 12}
41 P4 = {"survey_mode": "lattice", "survey_spacing": 1100.0, "directional": True, "outer_ring_gap": 0.0, "ring_radius": 1280.0,
42       "probe_spacing": 650.0, "locate_sigma": 220.0, "clear_bonus": 0.0, "probe_min_angle": 22.0, "search_cost_bias": 0.0,
43       "term_cap": 420.0, "endgame_radius": 90.0, "max_attempts": 6}
44
45 HERE = os.path.dirname(os.path.abspath(__file__))
46 ROOT = os.path.normpath(os.path.join(HERE, ".."))
47 DATA = os.path.join(ROOT, "data")
48 FIG = os.path.join(ROOT, "figures")
49 os.makedirs(FIG, exist_ok=True)
50
51 for cand in ("Microsoft YaHei", "SimHei", "DengXian", "SimSun", "Arial Unicode MS"):
52     matplotlib.rcParams["font.sans-serif"] = [cand]
53     matplotlib.rcParams["font.family"] = "sans-serif"
54     break
55 matplotlib.rcParams.update({
56     "axes.unicode_minus": False,
57     "font.size": 16,
58     "axes.titlesize": 17,
59     "axes.labelsize": 17,
60     "xtick.labelsize": 14,
61     "ytick.labelsize": 14,
62     "legend.fontsize": 13,
63     "lines.linewidth": 2.4,
64     "lines.markersize": 8,
65     "patch.linewidth": 1.4,
66     "axes.linewidth": 1.3,
67     "xtick.major.width": 1.3,
68     "ytick.major.width": 1.3,
69     "xtick.major.size": 5,
70     "ytick.major.size": 5,
71     "grid.alpha": 0.35,
72     "figure.dpi": 200,
73     "savefig.dpi": 220,
74     "savefig.bbox": "tight",
75     "savefig.pad_inches": 0.08,
76 })
77
78 L = json.load(io.open(os.path.join(HERE, "zh_labels.json"), encoding="utf-8-sig"))

```

```

76
77 def T(key, default=""):
78     return L.get(key, default)
79
80
81 def legend_below(ax, ncol=3, y=-0.20, fontsize=13, **kw):
82     """Legend OUTSIDE the axes, centred below the panel."""
83     ax.legend(loc="upper center", bbox_to_anchor=(0.5, y), ncol=ncol,
84             frameon=False, fontsize=fontsize, handlelength=1.8,
85             columnspacing=1.4, **kw)
86
87
88 def figure_legend(fig, handles, labels=None, ncol=3, y=0.02, fontsize=13):
89     """One legend for the whole figure, below all panels.
90
91     `labels` may be omitted when every handle already carries its own label.
92     """
93     if labels is None:
94         labels = [h.get_label() for h in handles]
95     fig.legend(handles, labels, loc="lower center", bbox_to_anchor=(0.5, y),
96             ncol=ncol, frameon=False, fontsize=fontsize, handlelength=1.8,
97             columnspacing=1.5)
98
99
100 def save(fig, name):
101     p = os.path.join(FIG, name)
102     fig.savefig(p)
103     plt.close(fig)
104     print(" fig", name)
105
106
107 def load_csv(name):
108     import csv as _csv
109     with io.open(os.path.join(DATA, name), encoding="utf-8") as f:
110         r = list(_csv.reader(f))
111     return r[0], r[1:]
112
113
114 def jload(name):
115     with io.open(os.path.join(DATA, name), encoding="utf-8") as f:
116         return json.load(f)
117
118
119 def jdump(name, obj):
120     with io.open(os.path.join(DATA, name), "w", encoding="utf-8") as f:

```

## B 灵敏度图（正文表 10、表 13 的图形表示）




图 22 问题三灵敏度：左为完成率，右为平均定位清除时间




图 23 问题四灵敏度：完成率与平均时间对各类扰动的响应均平稳