## BeepBoop Blog

## 题目描述:

A few robots got together and started a blog! It's full of posts that make absolutely no sense, but a little birdie told me that one of them left a secret in their drafts. Can you find it?

翻译一波: 几个机器人聚在一起开了一个博客!里面全是些毫无意义的帖子, 但有只小鸟告诉我其中一人在草稿里留下了一个秘密。你能找到吗? 打开题目地址真的是上千篇无意义的帖子




遇事不决看源码

看到 css 文件和 js 文件, css 是定义了网页样式, 而 js 文件则是定义程序, 康康 js 文件

```
function loadPosts() {
    fetch "/posts"). then (data => {
        return data.json();
    \}). then(json => {
        document.getElementById("contents").innerHTML = "";
        let out = "":
        for (let i = 0; i < json.posts.length; <math>i++) {
            let post = json.posts[i].post;
            let preview = post.substring(0, 100) + "...";
            let post_url = json.posts[i]["post_url"].split("/");
            let post_id = post_url[post_url.length - 1];
            const postElement = document.createElement("div");
            postElement.classNames = "post";
            const headElement = document.createElement("h3");
            headElement.innerText = `Post from ${json.posts[i].user}`;
            postElement.appendChild(headElement);
            const textElement = document.createElement("p");
            textElement.innerText = preview;
            postElement.appendChild(textElement);
            const linkElement = document.createElement("a");
            linkElement.onclick = evt => { loadPost(post id) };
            linkElement.href = "#":
            linkElement.innerText = "View All...":
            postElement.appendChild(linkElement);
            document.getElementById("contents").appendChild(postElement);
    })
}
```

```
function loadPost(post_id) {
    document.getElementById("contents").innerHTML = "";
                               then(data => {
    }). then(json => {;
        const postElement = document.createElement("div");
        postElement.classNames = "post";
        const headElement = document.createElement("h3");
        headElement.innerText = Post from ${json.user};
        postElement.appendChild(headElement);
        const textElement = document.createElement("p");
        textElement.innerText = json.post;
        postElement.appendChild(textElement);
        const linkElement = document.createElement("a");
        linkElement.onclick = evt => { loadPosts() };
        linkElement.href = "#";
        linkElement.innerText = "Go Back";
        postElement.appendChild(linkElement);
        document.getElementById("contents").appendChild(postElement);
    })
}
window.onload = evt => {
    loadPosts();
```

可以看到代码有三部分,第一部分是将/posts 里的内容切割分成 id 和文章,第二部分将其放入/post/[id]中我们查看一手/posts




发现他的每条数据都与id对应但是到最后一条时却错

## 位了



可推测隐藏了一条 post, 经过翻找发现是 608 被隐藏了



## 那我们直接去看 608,得到 flag

