

介绍

基于以太坊 (Ethereum) 的募捐系统可以利用智能合约和区块链技术来创建透明、安全和可追溯的募捐平台。这样的系统允许捐款者直接向特定的慈善机构或项目捐款,并确保资金的流向和使用情况可以公开审查

功能

发起募捐

- id
- 项目名称
- 目标金额
- 截止时间

- 申请描述
- 凭证hash
- 发起人

查看所有募捐项目

可使用项目名称进行查询

- id
- 项目名称
- 目标金额
- 截止时间
- 申请描述
- 凭证hash
- 发起人
- 项目状态

查看我发起的募捐项目

可使用项目名称进行查询

查看我捐赠的募捐项目

可使用项目名称进行查询

查看募捐详情

- id
- 项目名称
- 目标金额
- 截止时间
- 申请描述
- 凭证hash
- 发起人
- 已募捐到的金额
- 已使用资金
- 捐赠人数

捐赠

金额

募捐纪录

- id
- 金额
- 捐赠时间

使用

• 申请使用原因

募捐使用纪录

- id
- 使用时间
- 申请使用原因

技术栈

前端调用小狐狸插件,进行快捷转账,后端保存支持的公链地址,和合约地址 abi

合约

solidity

前端

- vue3
- vite
- pinia
- vue-router
- element-plus
- axios
- unocss

后端

• golang+gin

详细设计

登陆

前端判断web3是否有注入,小狐狸插件启动会注入web3,相关api,使用对应api获取当前小狐狸激活的地址,区块链id。使用区块链id访问后端接口获取合约地址,然后初始化合约,保存激活地址。如果没用web3注入会跳到error页面提示用户

```
S permission.js : 
'H-FUNDRAISING-UI
                                     日間ひ回
                                                                          router.beforeEach(async (to, from, next) => {
  const metamaskStore = useMetamaskStore()
                                                                                if (metamaskStore.getStatus == 'unauthorized') {
  console.log(metamaskStore.getStatus)
                                                                                    console.log(weather try(
    const walletAddress = await window.ethereum.enable()
    metamaskStore.setStatus('connected')
    console.log("当前线包地址:" + walletAddress[0]);
    const provider = await detectEthereumProvider()
₩ Middle.vue
                                                                                     const frovider = await detections com
if (provider) {
  console.log("provider", provider)
  console.log("Ethereum successfully detected!")
  const account = await provider.request(( method: 'eth_accounts' ))
  console.log("account: ", account)
  metamaskStore.setAccount(account[0])
₩ index.vue
JS index.is
 s metamask.is
                                                                                           // get chain id
const chainId = await provider.request({ method: 'eth_chainId' })
console.log("chainId: ", chainId)
                                                                                           // chain id to 10 base
const chainIdDecimal = parseInt(chainId, 16)
const res = await api.contract.findByChainId({chainId: chainIdDecimal})
console.log("res: ", res)
if(res.data.data == null){
    next({path: '/error'})
    return
 √ fundrising
W add.vue
  ₩ list.vue
                                                                                           }
const contractAddress = res.data.data.contractAddress
const web3js = new Web3(provider);
const ethContract = new web3js.eth.Contract(abi,contractAddress)
metamaskStore.setFundrisingContract(ethContract)
next({path: '/'})
                                                                                 PROBLEMS OUTPUT DEBUG CONSOLE PORTS GITLENS GITLENS
   var contract contractModel
              if contract.ContractAddress != "" {
                           c.JSON(http.StatusOK, gin.H{"status": http.StatusOK, "data": contract})
```

首页

调用合约的方法获取统计信息

```
eth-fundraising.sgl C:\Users\snow\Desk.

kscript setup> You, 2
import { ref } from 'vue';
                          日の日日
TH-FUNDRAISING-UI
∠ api
                                                   const fundrisingContract = metamaskStore.fundrisingContract
                                                    fundrisingContract.methods.info().call().then((res) => {
 components
                                                      data.value = {
   allAmount: res['0'],
                                                         completeCount: res['2
♥ index.vue
                                                      donateCount: 0,
✓ utils
JS hash.js
                                                      completeCount: 0,
JS metamask is

√ fundrising

 ₩ add.vue
 ₩ detail.vue
                                                         <el-col :span="6">
     <div class="statistic-card">
 ₩ list.vue
                                                             <el-statistic :value="data.allAmount">
<template #title>
♥ error.vue
```

发起募捐

上传凭证

凭证通过后端接口上传到后端同级目录 files下,上传成功后前端进行计算得出凭证的hash,防止凭证在后端被修改

```
eth-fundraising.sql C:\Users\snow\Desk...
   JS vite.config.is
× JS hash.js src\utils
                                                             async function hashFileInternal(file, alog) {
    // 指定块的大小,这里设置为20MB,可以根据实际情况进行配置
    const chunkSize = 20 * 1024 * 1024
                                                                for (let index = 0; index < file.size; index += chunkSize) {
    promise = promise.then(() => hashBlob(file.slice(index, index + chunkSize)))
}

√ components

 ♥ Content.vue
                                                                function hashBlob(blob) {
 ₩ index.vue
∨ router
                                                                     const reader = new FileReader()
                                                                       const wordArray = CryptoJs.lib.WordArray.create(target.result)
// 增重更新计算结果
JS index.js

✓ store

                                                                        alog.update(wordArray)
                                                                        resolve()
 JS hash.is
                                                                     reader.readAsArrayBuffer(blob)
 JS metamask.js

✓ fundrising

   ₩ add.vue
                                                                await promise
   ₩ detail.vue
JS main.is
                                                            export const calculateSha256 = (file) => {
    return hashFileInternal(file, CryptoJs.algo.SHA256.create())
```

保存募捐纪录到区块链

调用区块链合约方法把数据保存到区块链中,保存成功则跳到我发起的募捐列表

```
const add = () => {
    console.log("add: form.value);
    // check form
    if (form.value.name == '') {
    ElMessage.error("現住名称不成方空")
    return
    }
    if (form.value.target == '') {
        ElMessage.error("現住名称不成方空")
        return
    }
    if (form.value.daddline == '') {
        ElMessage.error("再提在图方空")
        return
    }
    if (form.value.description == '') {
        ElMessage.error("再提在图方空")
        return
    }
    if (form.value.description == '') {
        ElMessage.error("中海協任不愿方空")
        return
    }
    if (form.value.fileHash == '' || form.value.fileUrl == '') {
        ElMessage.error("現在不服方空")
        return
    }
    const specificDate = new Date(form.value.deadline); // 注意日期格式要符合 ISO 8601 标准
    const timestamp = 's(specificDate.getTime() / 1800);
    console.log("timestamp: form.value.fileUrl).send((
        from: matmaskStore.getAccount,
        gas: 3000000
    )) them((res) => {
        console.log("res: ", res);
        ElMessage.error("再报及经表数")
        ).catch((rer) => {
        console.log("res: ", res);
        ElMessage.error("再报及经表数")
        ). Catch((rer) => {
        console.log("ren: ", err);
        ElMessage.error("再报及是表数")
        ). Catch((rer) => {
        console.log("ren: ", err);
        ElMessage.error("再报及是表数")
        ).
```

募捐结束时间要大于当前时间+1小时

```
| Solution | Solution
```

募捐列表

根据路由名称判断使用那个合约方法获取募捐列表

```
<script setup> You, 2 months ago • feat: comple
const activelype = ref(currentRoute.value.meta.type)
                                                      if (activeType.value == 'initiator') {
    fundrisingContract.methods.getMyInitiatedRecords().call({
                              日日日日
V ETH-FUNDRAISING-UI
                                                             from: metamaskStore.getAccount,
                                                           ).then((res) => {
    console.log("getMyInitiatedRecords: ", res);
  > assets

∨ components

                                                             tableData.value = res.map((item) => {
    ₩ Middle.vue
                                                                  name: item.projectName,
                                                                initiator: item.initiator,
target: item.targetAmount,
                                                                 donatedAmount: item.donatedAmount,
   JS token.js
   JS hash.is
   JS metamask.is

∨ views

                                                            tundrisingContract.methods.getMyDonation().call(

√ fundrising

     ▼ add.vue
                                                                from: metamaskStore.getAccount,
                                                           ).then((res) => {
  console.log("getMyDonatedRecords: ", res);
                                                             tableData.value = res.map((item) => {
                                                                 name: item.projectName,
                                                                  target: item.targetAmount,
  8 style.scss
 .env
                                                                  donatedAmount: item.donatedAmount,
 .gitignore
 TS components.d.ts
 {} package.json
! pnpm-lock.vaml > OUTLINE
                                                           findAll()
> LOCAL HISTORY
```

跳转到详情界面

募捐详情

初始化时调用合约获取当前募juju情

```
| Consideration | Consideratio
```

判断激活的标签页获取对应的 捐款纪录或者使用纪录

```
្រាប្រ
1-FUNDRAISING-UI
                                                                  const getDonationRecords = () => {
  fundrisingContract.methods.getDonationRecords(router.query.id).call({
                                                                    from: metamaskStore.getAccount,
}).then((res) => {
s config.js
                                                                      console.log("getDonationRecords: ", res);
donateList.value = res.map((item) => {
components
                                                                             id: item.id,
Content.vue
                                                                              donator: item.donor,
amount: item.amount,
                                                                              time: item.timestamp
♥ index.vue
router
JS metamask is
                                                                 const getUsageRequests = () => {
  fundrisingContract.methods.getUsageRequests(router.query.id).call({
    from: metamaskStore.getAccount,
  }).then((res) => {
IS token.is
                                                                      console.log("getUseRecords: ", res);
useList.value = res.map((item) => {
s metamask.js
views
                                                                             id: item.id, reason: item.reason,
                                                                              amount: item.amount,
time: moment(Number(item.timestamp) * 1000).format('YYYY-MM-DD HH:mm:ss'),
 ₩ list.vue
♥ error.vue
 main.is
 permission.js
                                                                 onMounted(() => {
    getDonationRecords()
                                                                  match(activeName, (newVal, oldVal) => {
    console.log("activeName: ", newVal, oldVal);
    if (newVal == "donate") {
                                                        160
.gitignore
components.d.ts
                                                                       getDonationRecords()
JTLINE
                                                                        getUsageRequests()
M SCRIPTS
CAL HISTORY
```


捐赠

调用合约的捐赠方法把捐赠金额转移到合约账号上

```
amount: 0,
JS urls.is
> assets
                                                                donateVisiable.value = true
 ₩ Middle.vue
∨ layout
₩ index.vue
                                                               console.log("donate: ", donateForm);
fundrisingContract.methods.donate(router.query.id).send({
∨ router
                                                                  from: metamaskStore.getAccount,
JS metamask.js
                                                                }).then((res) => {
  console.log("donate: ", res);
  ElMessage.success("捐款成功")
JS token.is
                                                                  activeName.value = "donate'
                                                                  getDetail()
                                                                   getDonationRecords()

√ fundrising

                                                                }).catch((err) => {
    console.log("err: ", err);
    ElMessage.error("捐款失败")
 ₩ add.vue
   ♥ detail.vue
  ♥ list.vue
```



使用

调用合约的使用方法,把金额从合约账号上转到发起募捐人的账号上

```
function requestUsage(
   uint _donationId,
   string memory _reason,
   uint amount
       msg.sender == donations[_donationId].initiator,
        "Only initiator can request usage"
       donations[_donationId].donatedAmount -
           donations[_donationId].usedAmount >=
            amount,
        "Donated amount must be greater than usage amount"
   usageCount++;
   donations[_donationId].usageRequestsArray.push(
       UsageRequest({
            id: usageCount,
           {\tt donationId: \_donationId,}
           recipient: msg.sender,
           amount: amount,
           reason: _reason,
            time: block.timestamp
   payable(msg.sender).transfer(amount);
   donations[_donationId].usedAmount += amount;
```

Powered by Gitea Version: 1.20.5 Page: **226ms** Template: **13ms**

⊕ English | Licenses | API