COMP2310/COMP6310
Systems, Networks, & Concurrency

Convener: Prof John Taylor

The development of C

- **Combined Programming Language (CPL)** was developed in the early 1960s at the University of Cambridge.
- CPL was a high-level language with a very complex and large structure Including data types.
- Its complexity made it difficult to learn and implement, which led to a simplified version called **Basic Combined Programming Language (BCPL)**, developed by Martin Richards in 1967.
- BCPL was designed for writing compilers and operating systems. A key innovation of BCPL was that it introduced the **concept of a "typeless" language** where all data was treated as a word, which was a machine-dependent unit of memory.

The development of C

- BCPL heavily influenced the creation of the **B language** by Ken Thompson in 1969. B was developed for the first version of the Unix operating system on the DEC PDP-7 computer.
- It was essentially a simplified version of BCPL, stripped of more features to make it easier to use on the smaller machines of the time.
- Like BCPL, **B was also a typeless language**, with everything being treated as a machine word. This made it concise but also required that the programmer keep track of the different data types making it error prone and hard to debug.
- B relied heavily on `goto` for control flow

The development of C

- **C developed in 1972 by Dennis Ritchie** at Bell Labs based on the B language
- Introduced data types, structures, and type checking, making it more powerful and flexible than B.
- Introduced **explicit pointer types** (**int *p**, **char *s**, etc.)
- **C Language** formalized control structures like **if**, **while**, and **for**, making them standard in procedural programming and influencing countless languages that followed.
- **C Language** also introduced structures and unions, which allowed for the creation of complex data types
- Used to rewrite the Unix operating system, which helped popularize it.

C and Rust

- two powerful system programming languages

- **C trusts the programmer** — full control but limited protection.
- Mature, vast legacy codebase.
- Extremely fast and low-level
- Use cases: OS kernels, embedded systems, compilers

- **Rust** has had a stable release since 2015
- **Rust protects the programmer** — enforcing memory and concurrency safety without sacrificing performance
- Community growing rapidly with modern libraries
- Use cases: WebAssembly, embedded systems, secure apps

Machine-Level Programming V: Advanced Topics

Acknowledgement of material: With changes suited to ANU needs, the slides are obtained from Carnegie Mellon University: https://www.cs.cmu.edu/~213/

Today

- **Memory Layout**
- **Buffer Overflow**
  - Vulnerability
  - Protection
- **Unions**

x86-64 Linux Memory Layout

not drawn to scale

- **Stack**
  - Runtime stack (8MB limit)
  - E. g., local variables
- **Heap**
  - Dynamically allocated as needed
  - When calling malloc(), calloc(), new()
- **Data**
  - Statically allocated data
  - E.g., global vars, `static` vars, string constants
- **Text / Shared Libraries**
  - Executable machine instructions
  - Read-only



Memory Allocation Example

not drawn to scale

```
char big_array[1L<<24];  /* 16 MB */
char huge_array[1L<<31]; /*  2 GB */

int global = 0;

int useless() { return 0; }

int main ()
{
    void *p1, *p2, *p3, *p4;
    int local = 0;
    p1 = malloc(1L << 28); /* 256 MB */
    p2 = malloc(1L << 8);  /* 256  B */
    p3 = malloc(1L << 32); /*   4 GB */
    p4 = malloc(1L << 8);  /* 256  B */
 /* Some print statements ... */
}
```



Where does everything go?

x86-64 Example Addresses

address range ~2^{47}

not drawn to scale

`local`	`0x00007ffe4d3be87c`
`p1`	`0x00007f7262a1e010`
`p3`	`0x00007f7162a1d010`
`p4`	`0x000000008359d120`
`p2`	`0x000000008359d010`
`big_array`	`0x0000000080601060`
`huge_array`	`0x0000000000601060`
`main()`	`0x000000000040060c`
`useless()`	`0x0000000000400590`



Today

- Memory Layout
- **Buffer Overflow**
  - Vulnerability
  - Protection
- Unions

Memory Referencing Bug Example

```
typedef struct {
  int a[2];
  double d;
} struct_t;

double fun(int i) {
  volatile struct_t s;
  s.d = 3.14;
  s.a[i] = 1073741824; /* Possibly out of bounds */
  return s.d;
}
```

```
fun(0)  →  3.14
fun(1)  →  3.14
fun(2)  →  3.1399998664856
fun(3)  →  2.00000061035156
fun(4)  →  3.14
fun(6)  →  Segmentation fault
```

- Result is system specific

Memory Referencing Bug Example

```
typedef struct {
  int a[2];
  double d;
} struct_t;
```

```
fun(0)  →  3.14
fun(1)  →  3.14
fun(2)  →  3.1399998664856
fun(3)  →  2.00000061035156
fun(4)  →  3.14
fun(6)  →  Segmentation fault
```

Explanation:



Such problems are a BIG deal

- **Generally called a "buffer overflow"**
  - when exceeding the memory size allocated for an array
- **Why a big deal?**
  - It's the #1 technical cause of security vulnerabilities
    - #1 overall cause is social engineering / user ignorance
- **Most common form**
  - Unchecked lengths on string inputs
  - Particularly for bounded character arrays on the stack
    - sometimes referred to as stack smashing

String Library Code

- **Implementation of Unix function `gets()`**

```
/* Get string from stdin */
char *gets(char *dest)
{
    int c = getchar();
    char *p = dest;
    while (c != EOF && c != '\n') {
        *p++ = c;
        c = getchar();
    }
    *p = '\0';
    return dest;
}
```

  - No way to specify limit on number of characters to read

- **Similar problems with other library functions**
  - **`strcpy`, `strcat`**: Copy strings of arbitrary length
  - **`scanf`, `fscanf`, `sscanf`,** when given `%s` conversion specification

Vulnerable Buffer Code

```
/* Echo Line */
void echo()
{
    char buf[4];  /* Way too small! */
    gets(buf);
    puts(buf);
}
```

← btw, how big
is big enough?

```
void call_echo() {
    echo();
}
```

```
unix>./bufdemo-nsp
Type a string:012345678901234567890123
012345678901234567890123
```

```
unix>./bufdemo-nsp
Type a string:0123456789012345678901234
Segmentation Fault
```

Buffer Overflow Disassembly

echo:

```
00000000004006cf <echo>:
 4006cf:  48 83 ec 18              sub    $0x18,%rsp
 4006d3:  48 89 e7                 mov    %rsp,%rdi
 4006d6:  e8 a5 ff ff ff           callq  400680 <gets>
 4006db:  48 89 e7                 mov    %rsp,%rdi
 4006de:  e8 3d fe ff ff           callq  400520 <puts@plt>
 4006e3:  48 83 c4 18              add    $0x18,%rsp
 4006e7:  c3                       retq
```

call_echo:

```
4006e8:   48 83 ec 08              sub    $0x8,%rsp
 4006ec:  b8 00 00 00 00           mov    $0x0,%eax
 4006f1:  e8 d9 ff ff ff           callq  4006cf <echo>
 4006f6:  48 83 c4 08              add    $0x8,%rsp
 4006fa:  c3                       retq
```

Buffer Overflow Stack

Before call to gets




```
/* Echo Line */
void echo()
{
    char buf[4];  /* Way too small! */
    gets(buf);
    puts(buf);
}
```

```
echo:
  subq   $24, %rsp
  movq   %rsp, %rdi
  call   gets
  . . .
```

Buffer Overflow Stack Example

Before call to gets




```
void echo()
{
    char buf[4];
    gets(buf);
    . . .
}
```

```
echo:
  subq   $24, %rsp
  movq   %rsp, %rdi
  call   gets
  . . .
```

call_echo:

```
 . . .
 4006f1:  callq  4006cf <echo>
 4006f6:  add    $0x8,%rsp
 . . .
```

Buffer Overflow Stack Example #1

After call to gets

Stack Frame for `call_echo`			
00	00	00	00
00	40	06	f6
00	32	31	30
39	38	37	36
35	34	33	32
31	30	39	38
37	36	35	34
33	32	31	30

buf ← %rsp

```
void echo()
{
    char buf[4];
    gets(buf);
    . . .
}
```

```
echo:
  subq   $24, %rsp
  movq   %rsp, %rdi
  call   gets
  . . .
```

call_echo:

```
  . . .
  4006f1:  callq   4006cf <echo>
  4006f6:  add     $0x8,%rsp
  . . .
```

```
unix>./bufdemo-nsp
Type a string:01234567890123456789012
01234567890123456789012
```

Overflowed buffer, but did not corrupt state

Buffer Overflow Stack Example #2

After call to gets

Stack Frame for `call_echo`			
00	00	00	00
00	40	00	34
33	32	31	30
39	38	37	36
35	34	33	32
31	30	39	38
37	36	35	34
33	32	31	30

`buf` ← `%rsp`

```
void echo()
{
    char buf[4];
    gets(buf);
    . . .
}
```

```
echo:
  subq   $24, %rsp
  movq   %rsp, %rdi
  call   gets
  . . .
```

call_echo:

```
  . . .
  4006f1:  callq  4006cf <echo>
  4006f6:  add    $0x8,%rsp
  . . .
```

```
unix>./bufdemo-nsp
Type a string:012345678901234567890123
Segmentation Fault
```

Overflowed buffer and corrupted return pointer

Buffer Overflow Stack Example #3

After call to gets

Stack Frame for `call_echo`			
00	00	00	00
00	40	06	00
33	32	31	30
39	38	37	36
35	34	33	32
31	30	39	38
37	36	35	34
33	32	31	30

buf ← %rsp

```
void echo()
{
    char buf[4];
    gets(buf);
    . . .
}
```

```
echo:
  subq   $24, %rsp
  movq   %rsp, %rdi
  call   gets
  . . .
```

call_echo:

```
  . . .
  4006f1:  callq   4006cf <echo>
  4006f6:  add     $0x8,%rsp
  . . .
```

```
unix>./bufdemo-nsp
Type a string:01234567890123456789012
01234567890123456789012
```

Overflowed buffer, corrupted return pointer, but program seems to work!

Buffer Overflow Stack Example #3 Explained

After call to gets



register_tm_clones:

```
  . . .
400600:  mov    %rsp,%rbp
400603:  mov    %rax,%rdx
400606:  shr    $0x3f,%rdx
40060a:  add    %rdx,%rax
40060d:  sar    %rax
400610:  jne    400614
400612:  pop    %rbp
400613:  retq
```

"Returns" to unrelated code…

Lots of things happen, without modifying critical state

Eventually executes `retq` back to `main`

Code Injection Attacks

```
void P(){
   Q();
   ...
}
```

return address A

```
int Q() {
   char buf[64];
   gets(buf);
   ...
   return ...;
}
```



- Input string contains byte representation of executable code
- Overwrite return address A with address of buffer B
- When Q executes `ret`, will jump to exploit code

Exploits Based on Buffer Overflows

- ***Buffer overflow bugs can allow remote machines to execute arbitrary code on victim machines***

- **Distressingly common in real programs**
  - Programmers keep making the same mistakes ☹
  - Recent measures make these attacks much more difficult

Aside: Worms and Viruses

- **Worm: A program that**
  - Can run by itself
  - Can propagate a fully working version of itself to other computers

- **Virus: Code that**
  - Adds itself to other programs
  - Does not run independently

- **Both are (usually) designed to spread among computers and to wreak havoc**

OK, what to do about buffer overflow attacks…

- Avoid overflow vulnerabilities
- Employ system-level protections
- Have compiler use "stack canaries"

➢ We will examine each of these cases…

1. Avoid Overflow Vulnerabilities in Code (!)

```
/* Echo Line */
void echo()
{
    char buf[4];  /* Way too small! */
    fgets(buf, 4, stdin);
    puts(buf);
}
```

- **For example, use library routines that limit string lengths**
  - `fgets` instead of `gets`
  - `strncpy` instead of `strcpy`
  - Don't use `scanf` with `%s` conversion specification
    - Use `fgets` to read the string
    - Or use `%ns` where `n` is a suitable integer

2. System-Level Protections can help

- **Randomized stack offsets**
  - At start of program, allocate random amount of space on stack
  - Shifts stack addresses for entire program
  - Makes it difficult for hacker to predict beginning of inserted code
  - E.g.: 5 executions of memory allocation code

local	0x7ffe4d3be87c	0x7fff75a4f9fc	0x7ffeadb7c80c	0x7ffeaea2fdac	0x7ffcd452017c

  - Stack repositioned each time program executes



2. System-Level Protections can help

- **Nonexecutable code segments**
  - In traditional x86, can mark region of memory as either "read-only" or "writeable"
    - Can execute anything readable
  - X86-64 added explicit "execute" permission
  - Stack marked as non-executable



Any attempt to execute this code will fail

3. Stack Canaries can help

- **Idea**
  - Place special value (“canary”) on stack just beyond buffer
  - Check for corruption before exiting function
- **GCC Implementation**
  - `-fstack-protector`
  - Now the default (disabled earlier)

```
unix>./bufdemo-sp
Type a string:0123456
0123456
```

```
unix>./bufdemo-sp
Type a string:01234567
*** stack smashing detected ***
```

Protected Buffer Disassembly

echo:

```
40072f:  sub    $0x18,%rsp
400733:  mov    %fs:0x28,%rax
40073c:  mov    %rax,0x8(%rsp)
400741:  xor    %eax,%eax
400743:  mov    %rsp,%rdi
400746:  callq  4006e0 <gets>
40074b:  mov    %rsp,%rdi
40074e:  callq  400570 <puts@plt>
400753:  mov    0x8(%rsp),%rax
400758:  xor    %fs:0x28,%rax
400761:  je     400768 <echo+0x39>
400763:  callq  400580 <__stack_chk_fail@plt>
400768:  add    $0x18,%rsp
40076c:  retq
```

Setting Up Canary

Before call to gets




```
/* Echo Line */
void echo()
{
    char buf[4];  /* Way too small! */
    gets(buf);
    puts(buf);
}
```

```
echo:
    . . .
    movq    %fs:40, %rax   # Get canary
    movq    %rax, 8(%rsp)  # Place on stack
    xorl    %eax, %eax     # Erase canary
    . . .
```

Checking the Canary

After call to gets




```
/* Echo Line */
void echo()
{
    char buf[4];   /* Way too small! */
    gets(buf);
    puts(buf);
}
```

Input: ***0123456***

```
echo:
    . . .
    movq    8(%rsp), %rax      # Retrieve from
stack
    xorq    %fs:40, %rax       # Compare to canary
    je      .L6                # If same, OK
    call    __stack_chk_fail   # FAIL
.L6:    . . .
```

Return-Oriented Programming Attacks

- **Challenge (for hackers)**
  - Stack randomization makes it hard to predict buffer location
  - Marking stack nonexecutable makes it hard to insert binary code
- **Alternative Strategy**
  - Use existing code
    - E.g., library code from stdlib
  - String together fragments to achieve overall desired outcome
  - *Does not overcome stack canaries*
- **Construct program from *gadgets***
  - Sequence of instructions ending in `ret`
    - Encoded by single byte `0xc3`
  - Code positions fixed from run to run
  - Code is executable

Gadget Example #1

```
long ab_plus_c
  (long a, long b, long c)
{
   return a*b + c;
}
```

```
00000000004004d0 <ab_plus_c>:
  4004d0:  48 0f af fe  imul %rsi,%rdi
  4004d4:  48 8d 04 17  lea (%rdi,%rdx,1),%rax
  4004d8:  c3           retq
```

rax ← rdi + rdx

Gadget address = `0x4004d4`

- **Use tail end of existing functions**

Gadget Example #2

```
void setval(unsigned *p) {
    *p = 3347663060u;
}
```

Encodes `movq %rax, %rdi`

```
<setval>:
  4004d9:  c7 07 d4 48 89 c7  movl   $0xc78948d4,(%rdi)
  4004df:  c3                 retq
```

rdi ← rax

Gadget address = `0x4004dc`

- **Repurpose byte codes**

ROP Execution



- **Trigger with `ret` instruction**
  - Will start executing Gadget 1
- **Final `ret` in each gadget will start next one**

Today

- **Memory Layout**
- **Buffer Overflow**
  - Vulnerability
  - Protection
- **Unions**

Union Allocation

- Allocate according to largest element
- Can only use one field at a time

```
union U1 {
  char c;
  int i[2];
  double v;
} *up;
```




```
struct S1 {
  char c;
  int i[2];
  double v;
} *sp;
```



Using Union to Access Bit Patterns

```
typedef union {
  float f;
  unsigned u;
} bit_float_t;
```




```
float bit2float(unsigned u)
{
  bit_float_t arg;
  arg.u = u;
  return arg.f;
}
```

Same as `(float) u` ?

```
unsigned float2bit(float f)
{
  bit_float_t arg;
  arg.f = f;
  return arg.u;
}
```

Same as `(unsigned) f` ?

Byte Ordering Revisited

- **Idea**
  - Short/long/quad words stored in memory as 2/4/8 consecutive bytes
  - Which byte is most (least) significant?
  - Can cause problems when exchanging binary data between machines
- **Big Endian**
  - Most significant byte has lowest address
  - Sparc
- **Little Endian**
  - Least significant byte has lowest address
  - Intel x86, ARM Android and IOS
- **Bi Endian**
  - Can be configured either way
  - ARM

Byte Ordering Example

```
union {
  unsigned char c[8];
  unsigned short s[4];
  unsigned int i[2];
  unsigned long l[1];
} dw;
```

32-bit

<table>
<tr><td>c[0]</td><td>c[1]</td><td>c[2]</td><td>c[3]</td><td>c[4]</td><td>c[5]</td><td>c[6]</td><td>c[7]</td></tr>
<tr><td colspan="2">s[0]</td><td colspan="2">s[1]</td><td colspan="2">s[2]</td><td colspan="2">s[3]</td></tr>
<tr><td colspan="4">i[0]</td><td colspan="4">i[1]</td></tr>
<tr><td colspan="4">l[0]</td><td colspan="4"></td></tr>
</table>

64-bit

<table>
<tr><td>c[0]</td><td>c[1]</td><td>c[2]</td><td>c[3]</td><td>c[4]</td><td>c[5]</td><td>c[6]</td><td>c[7]</td></tr>
<tr><td colspan="2">s[0]</td><td colspan="2">s[1]</td><td colspan="2">s[2]</td><td colspan="2">s[3]</td></tr>
<tr><td colspan="4">i[0]</td><td colspan="4">i[1]</td></tr>
<tr><td colspan="8">l[0]</td></tr>
</table>

Byte Ordering Example (Cont).

```
int j;
for (j = 0; j < 8; j++)
    dw.c[j] = 0xf0 + j;

printf("Characters 0-7 ==
[0x%x,0x%x,0x%x,0x%x,0x%x,0x%x,0x%x,0x%x]\n",
    dw.c[0], dw.c[1], dw.c[2], dw.c[3],
    dw.c[4], dw.c[5], dw.c[6], dw.c[7]);

printf("Shorts 0-3 == [0x%x,0x%x,0x%x,0x%x]\n",
    dw.s[0], dw.s[1], dw.s[2], dw.s[3]);

printf("Ints 0-1 == [0x%x,0x%x]\n",
    dw.i[0], dw.i[1]);

printf("Long 0 == [0x%lx]\n",
    dw.l[0]);
```

Byte Ordering on IA32

Little Endian

<table>
<tr><td>f0</td><td>f1</td><td>f2</td><td>f3</td><td>f4</td><td>f5</td><td>f6</td><td>f7</td></tr>
<tr><td>c[0]</td><td>c[1]</td><td>c[2]</td><td>c[3]</td><td>c[4]</td><td>c[5]</td><td>c[6]</td><td>c[7]</td></tr>
<tr><td colspan="2">s[0]</td><td colspan="2">s[1]</td><td colspan="2">s[2]</td><td colspan="2">s[3]</td></tr>
<tr><td colspan="4">i[0]</td><td colspan="4">i[1]</td></tr>
<tr><td colspan="4">l[0]</td><td colspan="4"></td></tr>
</table>

LSB MSB LSB MSB

Print

Output:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts     0-3 == [0xf1f0,0xf3f2,0xf5f4,0xf7f6]
Ints       0-1 == [0xf3f2f1f0,0xf7f6f5f4]
Long       0   == [0xf3f2f1f0]
```

Byte Ordering on Sun

Big Endian



Output on Sun:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts     0-3 == [0xf0f1,0xf2f3,0xf4f5,0xf6f7]
Ints       0-1 == [0xf0f1f2f3,0xf4f5f6f7]
Long       0   == [0xf0f1f2f3]
```

Byte Ordering on x86-64

Little Endian



Output on x86-64:

```
Characters 0-7 == [0xf0,0xf1,0xf2,0xf3,0xf4,0xf5,0xf6,0xf7]
Shorts     0-3 == [0xf1f0,0xf3f2,0xf5f4,0xf7f6]
Ints       0-1 == [0xf3f2f1f0,0xf7f6f5f4]
Long       0   == [0xf7f6f5f4f3f2f1f0]
```

Summary of Compound Types in C

- **Arrays**
  - Contiguous allocation of memory
  - Aligned to satisfy every element's alignment requirement
  - Pointer to first element
  - No bounds checking
- **Structures**
  - Allocate bytes in order declared
  - Pad in middle and at end to satisfy alignment
- **Unions**
  - Overlay declarations
  - Way to circumvent type system