## F.R.I.D.A.Y.

Generated by Doxygen 1.9.6

## **Chapter 1**

## F.R.I.D.A.Y.

NOTE: Run `` doxygen Doxyfile `` to generate full documentation.

## 1.1 F.R.I.D.A.Y. Programmer Manual R1

#### 1.1.0.1 Contents

- 1. Overview
- 2. OS Lifecycle
- 3. Extending Systems
  - (a) kmain() and Startup
  - (b) The Command Handler
  - (c) Registering a Command
    - · Command Function
    - · Adding Command to Help
- 4. Conclusion

#### 1.1.1 1. Overview

F.R.I.D.A.Y. is a light-weight OS built to run on QEMU. You can use this documentation to extend the existing systems and add more functionality.

#### 1.1.2 2. OS Lifecycle

When the OS kernel is booted, the first function kmain() is called. This function bootstraps most of the core functionality of the OS. Once bootstrapping is done, control is passed to comhand() for the command handler.

Once the command handler has finished, comhand() will return, thus giving control back to kmain() kmain() then begins the shutdown process and exits.

2 F.R.I.D.A.Y.

#### 1.1.3 3. Extending Systems

#### 1.1.3.1 3.i. kmain() and Startup

kmain() is the first function called after the bootloader for the OS. This function is located in kmain.c and is responsible for bootstrapping most of the OS' core functionality. After all core systems have been initialized, full control is passed to the comhand() function in comhand.c. If something needs to be initialized, put the method call for it before the call to comhand().

#### 1.1.3.2 3.ii. The Command Handler

comhand () is what defines the OS' command handling system. When kmain () calls this function, the command handler welcomes the user and begins listening for user input. The command handler requests user input via a  $sys\_req$  () call. The input gathered from this method is then used to run the command that matches the input, if any.

#### 1.1.3.3 3.iii. Registering a Command

All commands are 'registered' via the comm\_funcs array inside comhand.c. This array contains pointers to functions that follow the format:

```
bool cmd_((COMMAND_NAME))(const char *command);
```

Note that the name of the method is **not** required to be followed, but should to maintain convention. Any new command **should** be placed in user space, preferably in the <u>commands.c</u> file. The return value of the function should signify if the command matched the **label** of the command. i.e. the command help junk-option1 junk-option2 should still return true for the help command, even though the options are not valid.

**Command Function** The start of a command function should resemble:

```
bool cmd_name(const char *comm)
{
   const char *label = "name";
   if (!matches_cmd(comm, label))
      return false;
   //cmd logic
   return true;
}
```

Use the  $matches\_cmd$  (const char \*cmd, const char \*label) function to check if the command's label matches.

**Adding Command to Help** Once you've added a command, you should add a help message for it. Use the help\_messages array to add an instance of the help\_info struct. Doing so should resemble:

```
nelp_messages array to add an instance of the help_info struct. Doing so should resemble:
```

{.str\_label = "name", .help\_message = "The %s command does X and then does Y.\nYou should include Z arguments

After adding this, running help name command will then recognize the added struct and return the help $\leftarrow$ message formatted with the command's name.

#### 1.1.3.4 4. Conclusion

The information above covers most important information on how to extend F.R.I.D.A.Y. Please use the included Doxygen documentation for more information on how the internal systems work. If you'd like to learn how to use the system from a user's perspective, please refer to our <a href="User Manual">User Manual</a>

## **Chapter 2**

## **Preparing Windows for MPX Development**

Windows is not suited for native MPX development. Instead, you will need to set up a Linux distribution in a either virtual machine or using the Windows Subsystem for Linux (WSL).

#### 2.1 Virtual Machine

The recommended virtual machine is LOUD, the LCSEE Optimized Ubuntu Distribution. Follow the directions at <a href="https://lcseesystems.wvu.edu/services/loud">https://lcseesystems.wvu.edu/services/loud</a>. If you encounter issues where the virtual machine hangs at a black screen, or is unusably slow (indicated by a turtle icon in the bottom-right hand corner of the VirtualBox window), consider WSL instead.

#### 2.2 WSL

WSL is an optional component of Windows 10 and later. First, you will need to ensure that WSL itself is enabled, and that a distribution is installed. Open an elevated Command Prompt or PowerShell window by pressing the Windows Key + X, and choosing "Command Prompt (Admin)" or "PowerShell (Admin)". In this window, run:

```
wsl --install -d ubuntu
```

This will enable WSL if it isn't already, and install Ubuntu along with it. If WSL wasn't already installed, you may need to reboot before you can launch an Ubuntu window. The first time you open an Ubuntu window, you'll be prompted to create a username and password. This will become the local account within the Ubuntu environment, and the password will become the one you need later to run commands with sudo. Once the account is set up, follow the steps for Ubuntu below.

## 2.3 Preparing Ubuntu and Other Debian Derivatives for MPX Development

Ubuntu is the primary development environment for MPX and the basis for LOUD, so no extensive preparation is needed. Simply open a terminal window and run the following commands:

```
sudo apt update
sudo apt install -y clang make nasm git binutils-i686-linux-gnu qemu-system-x86 gdb
```

### 2.4 Preparing macOS for MPX Development

All commands need to be run from a Terminal. You should be able to find the Terminal application in the  $/\leftarrow$  Applications folder of your system's internal disk. Alternatively, pressing Command+Space and typing Terminal should bring it up.

#### 2.4.1 Install XCode Tools

First, you need to install the XCode development tools. This includes the compiler, clang, and GNU make. This command will open a pop-up window for confirmation. Once confirmed, this may take some time to complete.

xcode-select --install

#### 2.4.2 Install Homebrew

Next, install the Homebrew package manager from <a href="https://brew.sh">https://brew.sh</a>. There should be a command under the label "Install Homebrew" that you can copy and paste into your Terminal window. Note that this makes use of the XCode tools installed in the first step, so that **must** be complete prior to this step.

It is likely that installing Homebrew will prompt you for your password so that it can elevate privileges using sudo. This is the same password you use to unlock your account when you turn on your system.

Note also that once the command you paste from the web site completes, there are a few additional steps you need to take to finalize the installation of Homebrew. In your terminal window, there will be some output beginning with the bold words \*\*==> Next steps:\*\*. You must follow the instructions in your Terminal window to complete the Homebrew installation.

#### 2.4.3 Install Remaining Tools

Once Homebrew is installed, you can easily install NASM, QEMU, the cross-linker, and cross-debugger.

brew install nasm qemu i686-elf-binutils i386-elf-gdb

If you get an error here, make sure that you followed the \*\*=> Next steps:\*\* portion of the Homebrew installation process. You may need to open a new Terminal window for the changes to take effect.

## **Chapter 3**

## **Class Index**

## 3.1 Class List

Here are the classes, structs, unions and interfaces with brief descriptions:

gdt_descriptor	?? ??
help_info	
Used to store information on a specific label of the 'help' command	??
idt descriptor	
The metadata for the IDT	??
idt entry	
A single entry in the IDT	??
line_entry	
Used to store a specific line previously entered	??
linked_list_	
Contains the definition of our linked list	??
linked_list_node_	
Contains the structure of the nodes in our linked list	??
page_dir	
page_entry	??
page_table	??
pcb	
The definition of a process control block	22

6 Class Index

# **Chapter 4**

## File Index

## 4.1 File List

Here is a list of all documented files with brief descriptions:

include/bomb_catcher.h	??
include/cli.h	
Contains useful commands for interfacing with the CLI	??
include/color.h	??
include/commands.h	
This file contains headers for commands run by the command handler	??
include/ctype.h	
A subset of standard C library functions	??
include/linked_list.h	??
include/math.h	
A header full of useful math type functions	??
include/memory.h	
MPX-specific dynamic memory functions	??
include/print_format.h	??
include/processes.h	
Provided system process and user processes for testing	??
include/stdio.h	
Contains useful functions for standard IO	??
include/stdlib.h	
A subset of standard C library functions	??
include/string.h	
A subset of standard C library functions	??
include/sys_req.h	
System request function and constants	??
include/time_zone.h	??
include/mpx/clock.h	
Contains functions for interacting with the system clock	??
include/mpx/comhand.h	??
include/mpx/device.h	??
include/mpx/gdt.h	
Kernel functions to initialize the Global Descriptor Table	??
include/mpx/interrupts.h	
Kernel functions related to software and hardware interrupts	??
include/mpx/io.h	
Kernel macros to read and write I/O ports	??

8 File Index

include/mpx/panic.h	
Common system functions and definitions	??
include/mpx/pcb.h	??
include/mpx/serial.h	
Kernel functions and constants for handling serial I/O	??
include/mpx/vm.h	
Kernel functions for virtual memory and primitive allocation	??

## **Chapter 5**

## **Class Documentation**

## 5.1 gdt\_descriptor Struct Reference

#### **Public Attributes**

- uint16\_t size
- struct gdt\_entry \* base

The documentation for this struct was generated from the following file:

· kernel/core.c

## 5.2 gdt\_entry Struct Reference

#### **Public Attributes**

- uint16\_t limit\_low
- uint16\_t base\_low

first 16 bits of limit

uint8\_t base\_mid

first 16 bits of base

• uint8 t access

bits 16-23 of base

• uint8\_t flags

next 8 bits; access flags

uint8\_t base\_high

page granularity, size

The documentation for this struct was generated from the following file:

· kernel/core.c

10 Class Documentation

## 5.3 help\_info Struct Reference

Used to store information on a specific label of the 'help' command.

#### **Public Attributes**

• char \* **str\_label** [15]

The label of the command for the help message.

• char \* help\_message

The help message to send for this struct.

#### 5.3.1 Detailed Description

Used to store information on a specific label of the 'help' command.

The documentation for this struct was generated from the following file:

· user/commands.c

## 5.4 idt\_descriptor Struct Reference

The metadata for the IDT.

#### **Public Attributes**

- uint16\_t size
- struct idt\_entry \* base

#### 5.4.1 Detailed Description

The metadata for the IDT.

The documentation for this struct was generated from the following file:

· kernel/core.c

### 5.5 idt\_entry Struct Reference

A single entry in the IDT.

#### **Public Attributes**

- uint16\_t base\_low
- uint16\_t sselect

offset bits 0..15

• uint8\_t zero

stack selector in gdt or ldt

• uint8\_t flags

this stays zero; unused

uint16\_t base\_high

attributes

### 5.5.1 Detailed Description

A single entry in the IDT.

The documentation for this struct was generated from the following file:

· kernel/core.c

## 5.6 line\_entry Struct Reference

Used to store a specific line previously entered.

#### **Public Attributes**

• char \* line

The line that was entered.

• size\_t line\_length

The line's length, not including the null terminator.

#### 5.6.1 Detailed Description

Used to store a specific line previously entered.

### 5.6.2 Member Data Documentation

12 Class Documentation

#### 5.6.2.1 line

```
char* line_entry::line
```

The line that was entered.

Does not include null terminator.

The documentation for this struct was generated from the following file:

· kernel/serial.c

### 5.7 linked\_list\_ Struct Reference

Contains the definition of our linked list.

#### **Public Attributes**

· int \_size

The size of the linked list.

· int max size

The maximum size of the linked list, set to -1 for infinite.

int(\* sort\_func )(void \*, void \*)

A pointer to the sorting function.

Il\_node \* \_first

The first node in the linked list.

Il\_node \* \_last

The second node in the linked list.

#### 5.7.1 Detailed Description

Contains the definition of our linked list.

The documentation for this struct was generated from the following file:

· lib/struct/linked list.c

### 5.8 linked\_list\_node\_ Struct Reference

Contains the structure of the nodes in our linked list.

#### **Public Attributes**

void \* \_item

The pointer to the item we're storing.

Il\_node \* \_next

The next node in the list.

#### 5.8.1 Detailed Description

Contains the structure of the nodes in our linked list.

The documentation for this struct was generated from the following file:

· lib/struct/linked\_list.c

## 5.9 page\_dir Struct Reference

#### **Public Attributes**

```
page_table * tables [1024]uint32_t tables_phys [1024]
```

The documentation for this struct was generated from the following file:

· kernel/core.c

### 5.10 page\_entry Struct Reference

#### **Public Attributes**

- uint32\_t present:1
- uint32\_t writeable:1
- uint32 t usermode:1
- uint32\_t accessed:1
- uint32\_t dirty:1
- uint32\_t reserved:7
- uint32\_t frameaddr:20

The documentation for this struct was generated from the following file:

· kernel/core.c

### 5.11 page\_table Struct Reference

#### **Public Attributes**

page\_entry pages [1024]

The documentation for this struct was generated from the following file:

· kernel/core.c

14 Class Documentation

## 5.12 pcb Struct Reference

The definition of a process control block.

#include <pcb.h>

#### **Public Attributes**

· const char \* name

The name of the PCB, max length of 8.

• enum pcb\_class process\_class

The process class type.

int priority

Integer priority of PCB, 0-9, lower = higher priority;.

• enum pcb\_exec\_state exec\_state

The execution state of this PCB.

• enum pcb\_dispatch\_state dispatch\_state

The dispatch state of this PCB.

int stack\_ptr

A pointer to the next available byte in the stack.

• unsigned char stack [PCB\_STACK\_SIZE]

The stack itself.

#### 5.12.1 Detailed Description

The definition of a process control block.

The documentation for this struct was generated from the following file:

• include/mpx/pcb.h

## **Chapter 6**

## **File Documentation**

## 6.1 bomb\_catcher.h

```
00001 //
00002 // Created by Andrew Bowie on 1/27/23.
00003 //
00004
00005 #ifndef F_R_I_D_A_Y_BOMB_CATCHER_H
00006 #define F_R_I_D_A_Y_BOMB_CATCHER_H
00007
00011 void start_bombcatcher(void);
00012
00013 #endif //F_R_I_D_A_Y_BOMB_CATCHER_H
```

#### 6.2 include/cli.h File Reference

Contains useful commands for interfacing with the CLI.

#### **Functions**

• void set\_cli\_history (bool enabled)

Sets if the CLI is enabled.

void set\_command\_formatting (bool enabled)

If command color formatting should be enabled.

• void set\_invisible (bool enabled)

Sets if the input for the line should be invisible.

void set\_tab\_completions (bool enabled)

Sets if the input should use tab completions.

#### 6.2.1 Detailed Description

Contains useful commands for interfacing with the CLI.

#### 6.2.2 Function Documentation

## 6.2.2.1 set\_cli\_history()

```
void set_cli_history (
                bool enabled )
```

Sets if the CLI is enabled.

6.3 cli.h 17

#### **Parameters**

enabled if the CLI should be enabled.

#### 6.2.2.2 set\_command\_formatting()

```
void set_command_formatting (
            bool enabled )
```

If command color formatting should be enabled.

#### **Parameters**

enabled

if it should be enabled.

#### 6.2.2.3 set\_invisible()

```
void set_invisible (
            bool enabled )
```

Sets if the input for the line should be invisible.

#### **Parameters**

enabled if it's enabled or not.

#### 6.2.2.4 set\_tab\_completions()

```
void set_tab_completions (
           bool enabled )
```

Sets if the input should use tab completions.

#### **Parameters**

enabled if it's enabled or not.

#### 6.3 cli.h

Go to the documentation of this file.

```
00001 //
00002 // Created by Andrew Bowie on 1/27/23.
00003 //
00004
00005 #ifndef F_R_I_D_A_Y_CLI_H
00006 #define F_R_I_D_A_Y_CLI_H
00007
00017 void set_cli_history(bool enabled);
00018
00023 void set_command_formatting(bool enabled);
00024
00029 void set_invisible(bool enabled);
00030
00035 void set_tab_completions(bool enabled);
00036
00037 #endif //F_R_I_D_A_Y_CLI_H
```

#### 6.4 color.h

```
00001 //
00002 // Created by Andrew Bowie on 1/27/23.
00003 //
00004
00005 #ifndef F_R_I_D_A_Y_COLOR_H
00006 #define F_R_I_D_A_Y_COLOR_H
00007
00014 typedef struct {
          const char *color_label;
const int color_num;
00016
00018
00019 } color_t;
00020
00025 void set_output_color(const color_t *color);
00026
00031 const color_t *get_output_color(void);
00032
00038 const color_t *get_color(const char *label);
00044 const color_t **get_colors(void);
00045
00046 #endif //F_R_I_D_A_Y_COLOR_H
```

#### 6.5 include/commands.h File Reference

This file contains headers for commands run by the command handler.

```
#include "stdbool.h"
```

#### **Functions**

• bool command\_exists (const char \*cmd)

Checks if the given command exists.

• bool cmd\_version (const char \*comm)

The version command, used to handle when the user asks for a version number.

bool cmd\_shutdown (const char \*comm)

The shutdown command.

• bool cmd\_get\_time\_menu (const char \*comm)

The get time command, used to get the time on the system.

bool cmd\_help (const char \*comm)

The help command, used to help the user when they are struggling.

• bool cmd set time (const char \*comm)

The set time command, used to set time user wants.

bool cmd\_set\_date (const char \*comm)

The set date command, used to set time user wants.

bool cmd\_set\_tz (const char \*comm)

The set timezone command, used to set the system timezone.

• bool cmd\_clear (const char \*comm)

The clear command, used to clear the console.

• bool cmd\_color (const char \*comm)

The color command, used to change text color for the terminal.

• bool cmd\_block\_pcb (const char \*comm)

The pcb\_block command, used to block a pcb.

• bool cmd\_unblock\_pcb (const char \*comm)

The pcb\_unblock command, used to unblock a pcb.

bool cmd\_suspend\_pcb (const char \*comm)

The pcb suspend command, suspends non system pcbs.

• bool cmd pcb (const char \*comm)

The pcb command, used to interact with the pcb system.

#### 6.5.1 Detailed Description

This file contains headers for commands run by the command handler.

#### 6.5.2 Function Documentation

#### 6.5.2.1 cmd\_block\_pcb()

The pcb\_block command, used to block a pcb.

#### **Parameters**

```
comm the command string.
```

#### Returns

true if it was handled, false if not.

#### 6.5.2.2 cmd\_clear()

The clear command, used to clear the console.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.3 cmd\_color()

The color command, used to change text color for the terminal.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.4 cmd\_get\_time\_menu()

The get time command, used to get the time on the system.

#### **Parameters**

comm the command string.

#### Returns

true if the command was handled, false if not.

#### 6.5.2.5 cmd\_help()

The help command, used to help the user when they are struggling.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.6 cmd\_pcb()

The pcb command, used to interact with the pcb system.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.7 cmd\_set\_date()

The set date command, used to set time user wants.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.8 cmd\_set\_time()

The set time command, used to set time user wants.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.9 cmd\_set\_tz()

The set timezone command, used to set the system timezone.

#### **Parameters**

comm the command string.

#### Returns

true if it was handled, false if not.

#### 6.5.2.10 cmd\_shutdown()

The shutdown command.

If ran, will re-prompt the user for confirmation.

#### **Parameters**

comm the command string.

#### Returns

true if the command was handled, false if not.

#### 6.5.2.11 cmd\_suspend\_pcb()

```
bool cmd_suspend_pcb ( {\tt const\ char\ *\ comm\ )}
```

The pcb suspend command, suspends non system pcbs.

#### **Parameters**

```
comm the command string.
```

#### Returns

true if it was handled, false if not.

#### 6.5.2.12 cmd\_unblock\_pcb()

The pcb\_unblock command, used to unblock a pcb.

#### **Parameters**

```
comm the command string.
```

#### Returns

true if it was handled, false if not.

#### 6.5.2.13 cmd\_version()

The version command, used to handle when the user asks for a version number.

Must Include Compilation date

#### **Parameters**

comm the command string.

#### Returns

true if the command was handled, false if not.

#### 6.5.2.14 command\_exists()

```
bool command_exists ( {\tt const\ char\ *\ cmd\ )}
```

Checks if the given command exists.

#### **Parameters**

```
cmd the command to check for.
```

#### Returns

true if it does, false if not.

#### 6.6 commands.h

#### Go to the documentation of this file.

```
00001 //
00002 // Created by Andrew Bowie on 1/18/23.
00003 //
00004
00005 #ifndef F_R_I_D_A_Y_COMMANDS_H
00006 #define F_R_I_D_A_Y_COMMANDS_H
00007
00008 #include "stdbool.h"
00009
00021 bool command_exists(const char *cmd);
00022
00028 bool cmd_version(const char *comm);
00029
00035 bool cmd_shutdown(const char *comm);
00036
00042 bool cmd_get_time_menu(const char *comm);
00043
00049 bool cmd_help(const char *comm);
00056 bool cmd_set_time(const char* comm);
00057
00063 bool cmd_set_date(const char* comm);
00064
00070 bool cmd_set_tz(const char *comm);
00077 bool cmd_clear(const char *comm);
00078
00084 bool cmd_color(const char *comm);
00090 bool cmd_block_pcb(const char *comm);
00096 bool cmd_unblock_pcb(const char *comm);
00102 bool cmd_suspend_pcb(const char *comm);
00103
00104
00110 bool cmd_pcb(const char *comm);
00111
00112 #endif //F_R_I_D_A_Y_COMMANDS_H
```

## 6.7 include/ctype.h File Reference

A subset of standard C library functions.

#### **Functions**

• int isspace (int c)

Determine if a character is whitespace.

• int isdigit (int c)

Determine if a character is a digit.

• int todigit (int c)

Return int value of character if is digit.

• int isupper (int c)

Determine if a character is uppercase.

• int islower (int c)

Determine if a character is lowercase.

• int tolower (int c)

Converts the given character to lowercase.

• int toupper (int c)

Converts the given character to uppercase.

#### 6.7.1 Detailed Description

A subset of standard C library functions.

#### 6.7.2 Function Documentation

#### 6.7.2.1 isdigit()

```
int isdigit ( \quad \text{int } c \ )
```

Determine if a character is a digit.

#### **Parameters**

```
c Character to check
```

#### Returns

Non-zero if digit, 0 if not digit

#### 6.7.2.2 islower()

```
int islower ( \quad \text{int } c \ )
```

Determine if a character is lowercase.

If the character is not alphabetical, 0 is returned.

#### **Parameters**

c Character to check.

#### Returns

Non-zero if lower, 0 if not lower.

#### 6.7.2.3 isspace()

```
int isspace ( \quad \text{int } c \ )
```

Determine if a character is whitespace.

#### **Parameters**

c Character to check

#### Returns

Non-zero if space, 0 if not space

#### 6.7.2.4 isupper()

```
int isupper ( \quad \text{int } c \ )
```

Determine if a character is uppercase.

If the character is not alphabetical, 0 is returned.

#### **Parameters**

c Character to check.

#### Returns

Non-zero if upper, 0 if not upper.

#### 6.7.2.5 todigit()

```
int todigit ( \quad \text{ int } c \ )
```

Return int value of character if is digit.

**Parameters** 

c Character to check

Returns

Negative not digit, value of digit otherwise

#### 6.7.2.6 tolower()

```
int tolower ( \quad \text{int } c \ )
```

Converts the given character to lowercase.

**Parameters** 

c the character to convert.

Returns

the lowercase character.

#### 6.7.2.7 toupper()

Converts the given character to uppercase.

#### **Parameters**

c the character to convert.

#### Returns

the uppercase character.

### 6.8 ctype.h

#### Go to the documentation of this file.

```
00001 #ifndef MPX_CTYPE_H
00002 #define MPX_CTYPE_H
00003
00014 int isspace(int c);
00021 int isdigit(int c);
00027 int todigit(int c);
00028
00035 int isupper(int c);
00036
00043 int islower(int c);
00044
00050 int tolower(int c);
00051
00057 int toupper(int c);
00058
00059 #endif
```

### 6.9 linked\_list.h

```
00002 // Created by Andrew Bowie on 9/18/22.
00003 //
00004
00005 #ifndef LINKEDLIST_H
00006 #define LINKEDLIST_H
00018 typedef struct linked_list_node_ ll_node;
00022 typedef struct linked_list_ linked_list;
00023
00028 linked list
00029 *nl_unbounded(void);
00030
00035 linked_list
00036 *nl_maxsize(int max_size);
00037
00044 11_node
00045 *get_first_node(linked_list *list);
00046
00053 11_node
00054 *next_node(11_node *node);
00055
00062 void
00063 *get_item_node(ll_node *node);
00064
00069 int
00070 list_size(linked_list *list);
00071
00079 void *
00080 get_item(linked_list *list, int index);
00081
00088 destroy_list(linked_list *list, int destroy_values);
00089
00096 int
00097 add_item_i(linked_list *list, int item);
00098
00106 int
00107 add_item_index_i(linked_list *list, int index, int item);
00108
00115 int.
00116 add_item(linked_list *list, void *item);
00117
00125 int
00126 add_item_index(linked_list *list, int index, void *item);
00127
00135 void
00136 set_item_i(linked_list *list, int index, int new_item);
00137
00146 void
00147 *set_item_i_unsafe(linked_list *list, int index, int new_item);
00148
00155 void
00156 remove_item(linked_list *list, int index);
00157
00164 int
00165 remove_item_ptr(linked_list *list, void *item_ptr);
00166
```

```
00174 void
00175 *remove_item_unsafe(linked_list *list, int index);
00176
00182 void
00183 set_sort_func(linked_list *list, int sort_func(void *, void *));
00184
00190 void
00191 for_each_il(linked_list *list, void call(void *node));
00192
00193 #endif //LINKEDLIST_H
```

#### 6.10 include/math.h File Reference

A header full of useful math type functions.

#### **Functions**

• unsigned int ui\_realmod (int x, int mod)

Calculates the real modulo value of X modulo 'mod'.

• double pow (double a, double b)

Calculates the Answer from a variable and a exponent.

void s\_rand (unsigned long seed)

Seeds the random number generator.

unsigned int next\_random (void)

Returns the next random 30 bits from the LCRNG.

### 6.10.1 Detailed Description

A header full of useful math type functions.

#### 6.10.2 Function Documentation

#### 6.10.2.1 next\_random()

Returns the next random 30 bits from the LCRNG.

Returns

the next random number.

#### 6.10.2.2 pow()

```
double pow ( \label{eq:double a, double b} \mbox{double } b \mbox{ )}
```

Calculates the Answer from a variable and a exponent.

#### **Parameters**

а	is the variable
b	is the exponent

#### Returns

The new value from the a^b

#### 6.10.2.3 s\_rand()

```
void s_rand (
            unsigned long seed )
```

Seeds the random number generator.

#### **Parameters**

```
the seed.
seed
```

#### 6.10.2.4 ui\_realmod()

```
unsigned int ui_realmod (
            int x,
            int mod )
```

Calculates the real modulo value of X modulo 'mod'.

#### **Parameters**

Χ	the value.
mod	the modulo.

#### Returns

the modulo value of x modulo 'mod'

#### 6.11 math.h

```
Go to the documentation of this file.
00001 //
00002 // Created by Andrew Bowie on 1/19/23.
00003 //
00004
```

```
00005 #ifndef F_R_I_D_A_Y_MATH_H
00006 #define F_R_I_D_A_Y_MATH_H
00007
00019 unsigned int ui_realmod(int x, int mod);
00020
00027 double pow(double a, double b);
00028
00033 void s_rand(unsigned long seed);
00034
00039 unsigned int next_random(void);
00040 #endif //F_R_I_D_A_Y_MATH_H
```

## 6.12 include/memory.h File Reference

MPX-specific dynamic memory functions.

```
#include <stddef.h>
```

#### **Functions**

```
    void * sys_alloc_mem (size_t size)
    Allocate dynamic memory.
```

int sys\_free\_mem (void \*ptr)

Free dynamic memory.

void sys\_set\_heap\_functions (void \*(\*alloc\_fn)(size\_t), int(\*free\_fn)(void \*))

Installs user-supplied heap management functions.

#### 6.12.1 Detailed Description

MPX-specific dynamic memory functions.

#### 6.12.2 Function Documentation

#### 6.12.2.1 sys\_alloc\_mem()

Allocate dynamic memory.

#### Parameters

size The amount of memory, in bytes, to allocate

#### Returns

NULL on error, otherwise the address of the newly allocated memory

#### 6.12.2.2 sys\_free\_mem()

Free dynamic memory.

#### **Parameters**

```
ptr The address of dynamically allocated memory to free
```

#### Returns

0 on success, non-zero on error

#### 6.12.2.3 sys\_set\_heap\_functions()

Installs user-supplied heap management functions.

#### **Parameters**

alloc⊷ _fn	A function that dynamically allocates memory
free_fn	A function that frees dynamically allocated memory

## 6.13 memory.h

### Go to the documentation of this file.

```
00001 #ifndef MPX_MEMORY_H
00002 #define MPX_MEMORY_H
00003
00004 #include <stddef.h>
00005
00016 void *sys_alloc_mem(size_t size);
00017
00023 int sys_free_mem(void *ptr);
00024
00030 void sys_set_heap_functions(void * (*alloc_fn)(size_t), int (*free_fn)(void *));
00031
00032 #endif
```

# 6.14 include/mpx/clock.h File Reference

Contains functions for interacting with the system clock.

```
#include "time_zone.h"
```

#### **Functions**

const time\_zone\_t \* get\_clock\_timezone (void)

Gets the current timezone for the clock.

void set\_timezone (const time\_zone\_t \*offset)

Sets the timezone hour offset.

int print\_time (void)

Prints the time and date of the system.

int \* adj\_timezone (int time[6], int tz\_offset\_hr, int tz\_offset\_min)

Adjusts the given time array to the specified timezone.

int \* get\_time (int t\_buf[7])

Gets the time and stores it in the given array in the form: {year, month, date, week\_day, hours, mins, seconds}.

bool set\_time\_clock (unsigned int hr, unsigned int min, unsigned int sec)

Sets the time of the system clock to the provided values.

bool set\_date\_clock (unsigned int month, unsigned int day, unsigned int year)

Sets the date of the system clock to the provided values.

• unsigned char decimal\_to\_bcd (unsigned int decimal)

Converts the given decimal number to BCD.

int bcd\_to\_decimal (unsigned char bcd)

Converts the given BCD number to decimal.

• bool is\_valid\_date\_or\_time (int word\_len, char buf[][word\_len], int buff\_len)

Checks if the given array of time values is validly defined.

unsigned int get\_days\_in\_month (int month, int year)

Gets the amount of days in the provided month and returns it in BCD.

### 6.14.1 Detailed Description

Contains functions for interacting with the system clock.

### 6.14.2 Function Documentation

#### 6.14.2.1 adj\_timezone()

Adjusts the given time array to the specified timezone.

### **Parameters**

time	the time array, should be passed in with the format {year, month, date, week_day, hours, mins}.
tz_offset_hr	the hour offset.
tz_offset_min	the minute offset.

# Returns

a pointer to the adjusted array.

# 6.14.2.2 bcd\_to\_decimal()

Converts the given BCD number to decimal.

#### **Parameters**

## Returns

the converted number.

# 6.14.2.3 decimal\_to\_bcd()

```
unsigned char decimal_to_bcd (
          unsigned int decimal )
```

Converts the given decimal number to BCD.

#### **Parameters**

ĺ	decimal	the number to convert.
	accimai	the number to convert.

#### Returns

the converted number.

## 6.14.2.4 get\_clock\_timezone()

```
\begin{tabular}{ll} \begin{tabular}{ll} const time\_zone\_t * get\_clock\_timezone ( \\ & void \ ) \end{tabular}
```

Gets the current timezone for the clock.

Returns

the timezone.

# 6.14.2.5 get\_days\_in\_month()

Gets the amount of days in the provided month and returns it in BCD.

#### **Parameters**

month	the month of the year, in BCD.
year	the year, in BCD. (Used for leap years)

### Returns

the amount of days in the month, in BCD.

### 6.14.2.6 get\_time()

```
int * get_time ( int \ t\_buf[7] \ )
```

Gets the time and stores it in the given array in the form: {year, month, date, week\_day, hours, mins, seconds}.

## **Parameters**

t\_buf the buffer to store the time in. Can be NULL.

#### Returns

the time array.

# 6.14.2.7 is\_valid\_date\_or\_time()

Checks if the given array of time values is validly defined.

All strings in the array must be valid, positive, 2 digit numbers.

### **Parameters**

word_len	the length of 2nd dimension of the array.
buf	the array.
buff_len	the length of the 1st dimension of the array.

### Returns

if the provided array is valid.

### 6.14.2.8 print\_time()

```
int print_time (
     void )
```

Prints the time and date of the system.

# Returns

0 if successful, negative if not.

### 6.14.2.9 set\_date\_clock()

Sets the date of the system clock to the provided values.

#### **Parameters**

month	the month, in BCD.
day	the day, in BCD.
year	the year, in BCD.

6.15 clock.h 39

#### Returns

true if the time was changed, false if the values were invalid.

### 6.14.2.10 set\_time\_clock()

```
bool set_time_clock (
          unsigned int hr,
          unsigned int min,
          unsigned int sec )
```

Sets the time of the system clock to the provided values.

#### **Parameters**

hr	the hours, in BCD.
min	the minutes, in BCD.
sec	the seconds, in BCD.

#### Returns

true if the time was changed, false if the values were invalid.

#### 6.14.2.11 set\_timezone()

Sets the timezone hour offset.

### **Parameters**

```
offset the hour offset.
```

# 6.15 clock.h

#### Go to the documentation of this file.

```
00001 #ifndef F_R_I_D_A_Y_SET_TIME_H
00002 #define F_R_I_D_A_Y_SET_TIME_H
00003
00004 #include "time_zone.h"
00005
00015 const time_zone_t *get_clock_timezone(void);
00016
00021 void set_timezone(const time_zone_t *offset);
00022
00027 int print_time(void);
```

```
00028
00037 int *adj_timezone(int time[6], int tz_offset_hr, int tz_offset_min);
00038
00045 int *get_time(int t_buf[7]);
00046
00054 bool set_time_clock(unsigned int hr, unsigned int min, unsigned int sec);
00055
00063 bool set_date_clock(unsigned int month, unsigned int day, unsigned int year);
00064
00070 unsigned char decimal_to_bcd(unsigned int decimal);
00071
00071
00077 int bcd_to_decimal(unsigned char bcd);
00078
00087 bool is_valid_date_or_time(int word_len, char buf[][word_len], int buff_len);
00088
00095 unsigned int get_days_in_month(int month, int year);
00096 #endif
```

# 6.16 comhand.h

```
00001
00002 #ifndef F_R_I_D_A_Y_COMHAND_H
00003 #define F_R_I_D_A_Y_COMHAND_H
00004
00005 #define CMD_PROMPT "» "
00006
00017 void signal_shutdown(void);
00018
00022 void comhand(void);
00023
00024 #endif //F_R_I_D_A_Y_COMHAND_H
```

# 6.17 device.h

# 6.18 include/mpx/gdt.h File Reference

Kernel functions to initialize the Global Descriptor Table.

# **Functions**

void gdt\_init (void)

Creates and installs the Global Descriptor Table.

# 6.18.1 Detailed Description

Kernel functions to initialize the Global Descriptor Table.

6.19 gdt.h 41

# 6.19 gdt.h

#### Go to the documentation of this file.

```
00001 #ifndef MPX_GDT_H

00002 #define MPX_GDT_H

00003

00010 void gdt_init(void);

00011

00012 #endif
```

# 6.20 include/mpx/interrupts.h File Reference

Kernel functions related to software and hardware interrupts.

### **Macros**

```
    #define sti() __asm__ volatile ("sti")
        Disable interrupts.
    #define cli() __asm__ volatile ("cli")
        Enable interrupts.
```

#### **Functions**

void irq\_init (void)

Installs the initial interrupt handlers for the first 32 IRQ lines.

void pic\_init (void)

Initializes the programmable interrupt controllers and performs the necessary remapping of IRQs.

void idt\_init (void)

Creates and installs the Interrupt Descriptor Table.

void idt\_install (int vector, void(\*handler)(void \*))

Installs an interrupt handler.

# 6.20.1 Detailed Description

Kernel functions related to software and hardware interrupts.

### 6.20.2 Function Documentation

# 6.20.2.1 irq\_init()

```
void irq_init (
     void )
```

Installs the initial interrupt handlers for the first 32 IRQ lines.

Most do a panic for now.

### 6.20.2.2 pic\_init()

```
void pic_init (
     void
```

Initializes the programmable interrupt controllers and performs the necessary remapping of IRQs.

Leaves interrupts turned off.

# 6.21 interrupts.h

#### Go to the documentation of this file.

```
00001 #ifndef MPX_INTERRUPTS_H
00002 #define MPX_INTERRUPTS_H
00003
00010 #define sti() __asm__ volatile ("sti")
00011
00011 #define cli() __asm__ volatile ("cli")
00014
00019 void irq_init(void);
00020
00025 void pic_init(void);
00026
00028 void idt_init(void);
00029
00031 void idt_install(int vector, void (*handler)(void *));
00032
00033 #endif
```

# 6.22 include/mpx/io.h File Reference

Kernel macros to read and write I/O ports.

### **Macros**

```
• #define outb(port, data) __asm__ volatile ("outb %%al, %%dx" :: "a" (data), "d" (port))

Write one byte to an I/O port.
```

• #define inb(port)

Read one byte from an I/O port.

### 6.22.1 Detailed Description

Kernel macros to read and write I/O ports.

# 6.22.2 Macro Definition Documentation

#### 6.22.2.1 inb

Read one byte from an I/O port.

6.23 io.h 43

#### **Parameters**

port	The port to read from
------	-----------------------

#### Returns

A byte of data read from the port

#### 6.22.2.2 outb

Write one byte to an I/O port.

#### **Parameters**

port	The port to write to
data	The byte to write to the port

# 6.23 io.h

#### Go to the documentation of this file.

# 6.24 include/mpx/panic.h File Reference

Common system functions and definitions.

```
#include <stdnoreturn.h>
```

### **Functions**

• noreturn <u>\_\_attribute\_\_</u> ((no\_caller\_saved\_registers)) void kpanic(const char \*msg) Kernel panic.

# 6.24.1 Detailed Description

Common system functions and definitions.

# 6.24.2 Function Documentation

```
6.24.2.1 __attribute__()
```

Kernel panic.

Prints an error message and halts.

#### **Parameters**

```
msg A message to display before halting
```

# 6.25 panic.h

### Go to the documentation of this file.

```
00001 #ifndef MPX_PANIC_H
00002 #define MPX_PANIC_H
00003
00004 #include <stdnoreturn.h>
00005
00015 /*
00016 non-standard attribute is required for clang < 15
00017 */
00018 noreturn __attribute__((no_caller_saved_registers)) void kpanic(const char *msg);
0019
0020 #endif
```

# 6.26 pcb.h

```
00001 #ifndef MPX_PCB_H
00002 #define MPX_PCB_H
00003
00005 #define PCB_MAX_NAME_LEN 8
00007 #define PCB_STACK_SIZE 4096
00008
00012
         SYSTEM = 1,
00013 };
00014
RUNNING = 1,
BLOCKED = 2,
00018
00019
00020 };
00021
00023 enum pcb_dispatch_state {
00024 NOT_SUSPENDED = 0,
00025
         SUSPENDED = 1,
```

```
00026 };
00029 struct pcb {
00031 const char *name;
00033
         enum pcb_class process_class;
00035
         int priority;
        enum pcb_exec_state exec_state;
00039
         enum pcb_dispatch_state dispatch_state;
00041
         int stack_ptr;
00043
         unsigned char stack[PCB_STACK_SIZE];
00044 };
00049 void setup_queue(void);
00050
00057 struct pcb *pcb_alloc(void);
00058
00066 int pcb_free(struct pcb* pcb_ptr);
00067
00077 struct pcb *pcb_setup(const char *name, int class, int priority);
00084 void pcb_insert(struct pcb* pcb_ptr);
00085
00092 struct pcb *pcb_find(const char *name);
00093
00101 bool pcb_remove(struct pcb *pcb_ptr);
00102
00108 void exec_pcb_cmd(const char *comm);
00109
00110
00111 #endif
```

# 6.27 include/mpx/serial.h File Reference

Kernel functions and constants for handling serial I/O.

```
#include <stddef.h>
#include <mpx/device.h>
```

#### **Functions**

• int serial\_init (device dev)

Initializes devices for user input and output.

• int serial\_out (device dev, const char \*buffer, size\_t len)

Writes a buffer to a serial port.

• int serial\_poll (device dev, char \*buffer, size\_t len)

Reads a string from a serial port.

## 6.27.1 Detailed Description

Kernel functions and constants for handling serial I/O.

## 6.27.2 Function Documentation

#### 6.27.2.1 serial init()

```
int serial_init ( \label{eq:dev} \mbox{device } \mbox{\it dev} \ )
```

Initializes devices for user input and output.

### **Parameters**

device A serial port to initialize (COM1, COM2, COM3, or COM4)
--

### Returns

0 on success, non-zero on failure

# 6.27.2.2 serial\_out()

Writes a buffer to a serial port.

### **Parameters**

device	The serial port to output to
buffer	A pointer to an array of characters to output
len	The number of bytes to write

## Returns

The number of bytes written

# 6.27.2.3 serial\_poll()

Reads a string from a serial port.

#### **Parameters**

device	The serial port to read data from
buffer	A buffer to write data into as it is read from the serial port
count	The maximum number of bytes to read

6.28 serial.h 47

#### Returns

The number of bytes read on success, a negative number on failure

### 6.28 serial.h

### Go to the documentation of this file.

```
00001 #ifndef MPX_SERIAL_H
00002 #define MPX_SERIAL_H
00003
00004 #include <stddef.h>
00005 #include <mpx/device.h>
00006
00017 int serial_init(device dev);
00018
00026 int serial_out(device dev, const char *buffer, size_t len);
00027
00036 int serial_poll(device dev, char *buffer, size_t len);
00037
00038 #endif
```

# 6.29 include/mpx/vm.h File Reference

Kernel functions for virtual memory and primitive allocation.

```
#include <stddef.h>
```

# **Functions**

```
    void * kmalloc (size_t size, int align, void **phys_addr)
        Allocates memory from a primitive heap.

    void vm_init (void)
        Initializes the kernel page directory and initial kernel heap area.
```

# 6.29.1 Detailed Description

Kernel functions for virtual memory and primitive allocation.

## 6.29.2 Function Documentation

## 6.29.2.1 kmalloc()

Allocates memory from a primitive heap.

#### **Parameters**

size	The size of memory to allocate
align If non-zero, align the allocation to a page boundary	
phys_addr	If non-NULL, a pointer to a pointer that will hold the physical address of the new memory

#### Returns

The newly allocated memory

# 6.29.2.2 vm\_init()

```
void vm_init (
     void )
```

Initializes the kernel page directory and initial kernel heap area.

Performs identity mapping of the kernel frames such that the virtual addresses are equivalent to the physical addresses.

# 6.30 vm.h

#### Go to the documentation of this file.

```
00001 #ifndef MPX_VM_H
00002 #define MPX_VM_H
00003
00009 #include <stddef.h>
00010
00019 void *kmalloc(size_t size, int align, void **phys_addr);
00020
00026 void vm_init(void);
00027
00028 #endif
```

# 6.31 print format.h

```
00002 // Created by Andrew Bowie on 2/1/23.
00003 //
00004
00005 #ifndef F_R_I_D_A_Y_PRINT_FORMAT_H
00006 #define F_R_I_D_A_Y_PRINT_FORMAT_H
00007
00008 #include "color.h"
00009 #include "stdbool.h"
00010
00012 typedef enum { 00013 BOLD = 0,
            UNDERLINE = 1,
00014
            ITALIC = 2,
INVISIBLE = 3,
00015
00016
00017
           INVERSE = 4,
BLINKING = 5,
00018
           STRIKETHROUGH = 6,
00019
00020 } format_code_t;
00028 bool is_format_code(format_code_t format_code);
00029
00036 void set_format_code(format_code_t format_code, bool active);
00037
00041 void clear_formats();
00043 #endif //F_R_I_D_A_Y_PRINT_FORMAT_H
```

# 6.32 include/processes.h File Reference

Provided system process and user processes for testing.

#### **Functions**

void proc1 (void)

A test process that prints a message then yields, exiting after 1 iteration.

void proc2 (void)

A test process that prints a message then yields, exiting after 2 iterations.

· void proc3 (void)

A test process that prints a message then yields, exiting after 3 iterations.

· void proc4 (void)

A test process that prints a message then yields, exiting after 4 iterations.

void proc5 (void)

A test process that prints a message then yields, exiting after 5 iterations.

void sys\_idle\_process (void)

System idle process.

void comwrite (void)

This process attempts to write a message to the serial device.

· void comread (void)

This process writes a prompt to the serial device, and then reads user input which is then printed back to the device.

void iocom25 (void)

This process attempts to write a message to the serial device 25 times and then exits.

· void iocom (void)

This process attempts to write a message to the serial device until suspended and terminated.

### 6.32.1 Detailed Description

Provided system process and user processes for testing.

### 6.32.2 Function Documentation

### 6.32.2.1 comwrite()

```
void comwrite (
     void )
```

This process attempts to write a message to the serial device.

This should be the first test process executed when testing R6.

#### 6.32.2.2 sys\_idle\_process()

System idle process.

Used in dispatching. It will be dispatched if NO other processes are available to execute. Must be a system process.

# 6.33 processes.h

#### Go to the documentation of this file.

```
00001 #ifndef MPX_PROCESSES_H
00002 #define MPX_PROCESSES_H
00003
00010 The following functions are needed for Module R3.
00016 void proc1(void);
00017
00021 void proc2(void);
00022
00026 void proc3(void);
00031 void proc4(void);
00032
00036 void proc5(void);
00037
00039 The following function is needed for Module R4.
00041
00046 void sys_idle_process(void);
00047
00049 The following functions are needed for Module R6.
00051
00056 void comwrite(void);
00057
00062 void comread(void):
00063
00067 void iocom25(void);
00068
00072 void iocom(void);
00073
00074 #endif
```

# 6.34 include/stdio.h File Reference

Contains useful functions for standard IO.

```
#include "stddef.h"
#include "stdbool.h"
```

### **Functions**

• char getc (void)

Reads a single ASCII character from standard input.

• char pollc (void)

Polls a single ASCII character from standard input.

• char \* gets (char \*str\_buf, size\_t buf\_len)

Reads a string of input from the standard input source.

void print (const char \*str)

Prints a null-terminated string to standard output.

• int printf (const char \*str,...)

Prints the string with formatting to standard outpu.

void println (const char \*str)

Prints a null-terminated string, then a new line, to standard output.

void clearscr (void)

Clears the screen.

# 6.34.1 Detailed Description

Contains useful functions for standard IO.

### 6.34.2 Function Documentation

## 6.34.2.1 getc()

```
char getc (
          void )
```

Reads a single ASCII character from standard input.

Returns

The character read

# 6.34.2.2 gets()

Reads a string of input from the standard input source.

### **Parameters**

str_	buf	the buffer to store the string in.	
buf	_len	the amount of bytes to read. (The buffer should be at least one byte longer)	

### Returns

a pointer to the read array.

# 6.34.2.3 pollc()

```
char pollc (
     void )
```

Polls a single ASCII character from standard input.

If no characters are available, 0 is returned.

# Returns

The character polled.

### 6.34.2.4 print()

```
void print ( {\rm const\ char\ *\ str\ )}
```

Prints a null-terminated string to standard output.

## **Parameters**

```
str the string.
```

# 6.34.2.5 printf()

```
int printf ( \label{eq:const_char} \mbox{const_char} \ * \ str, \\ \hdots \hdo
```

Prints the string with formatting to standard outpu.

6.35 stdio.h 53

#### **Parameters**

str	the string to print.
	the formatting objects.

#### Returns

0 if successful, -1 if there was a formatting error.

### 6.34.2.6 println()

```
void println ( {\tt const\ char\ *\ str\ )}
```

Prints a null-terminated string, then a new line, to standard output.

### **Parameters**

str the string.

# 6.35 stdio.h

### Go to the documentation of this file.

```
00002 // Created by Andrew Bowie on 1/13/23.
00003 //
00004
00005 #ifndef F_R_I_D_A_Y_STDIO_H
00006 #define F_R_I_D_A_Y_STDIO_H
00007
00008 #include "stddef.h"
00009 #include "stdbool.h"
00010
00020 char getc(void);
00021
00027 char pollc(void);
00035 char *gets(char *str_buf, size_t buf_len);
00036
00041 void print(const char *str);
00042
00049 int printf(const char *str, ...);
00055 void println(const char *str);
00056
00060 void clearscr(void);
00061
00062 #endif //F_R_I_D_A_Y_STDIO_H
```

# 6.36 include/stdlib.h File Reference

A subset of standard C library functions.

# **Functions**

```
• int atoi (const char *s)
```

Convert an ASCII string to an integer.

• char \* itoa (int i, char \*str\_buf, int buf\_len)

Convert a signed integer to a string.

• char \* itoa\_base (int i, int base, char \*str\_buf, int buf\_len)

Convert a signed integer to a string.

# 6.36.1 Detailed Description

A subset of standard C library functions.

### 6.36.2 Function Documentation

### 6.36.2.1 atoi()

```
int atoi ( \label{eq:const_char} \mbox{const_char} \ *\ s\ )
```

Convert an ASCII string to an integer.

# **Parameters**

```
s A NUL-terminated string
```

### Returns

The value of the string converted to an integer

## 6.36.2.2 itoa()

```
\begin{array}{c} \text{char * itoa (} \\ & \text{int $i$,} \\ & \text{char * $str\_buf,} \\ & \text{int $buf\_len )} \end{array}
```

Convert a signed integer to a string.

### Parameters

i	the integer to convert
str_buf	the buffer to store the integer in
buf len	the string buffer length

6.37 stdlib.h 55

#### Returns

the created string from the integer

# 6.36.2.3 itoa\_base()

Convert a signed integer to a string.

#### **Parameters**

i	the integer to convert
base	the base of the number
str_buf	the buffer to store the integer in
buf_len	the string buffer length

### Returns

the created string from the integer

# 6.37 stdlib.h

### Go to the documentation of this file.

```
00001 #ifndef MPX_STDLIB_H
00002 #define MPX_STDLIB_H
00003
00014 int atoi(const char *s);
00015
00023 char *itoa(int i, char *str_buf, int buf_len);
00024
00033 char *itoa_base(int i, int base, char *str_buf, int buf_len);
00034
00035 #endif
```

# 6.38 include/string.h File Reference

A subset of standard C library functions.

```
#include <stddef.h>
#include "stdarg.h"
#include "stdbool.h"
```

#### **Functions**

• bool first\_label\_matches (const char \*str1, const char \*label)

Checks if the given string's first part matches the label.

void \* memcpy (void \*restrict dst, const void \*restrict src, size\_t n)

Copy a region of memory.

void \* memset (void \*address, int c, size\_t n)

Fill a region of memory.

char \* strcpy (char \*str\_dest, const char \*str\_src, size\_t maxlen)

Copies the data from the string source into the string destination.

• int strcmp (const char \*s1, const char \*s2)

Compares two strings.

int strcicmp (const char \*s1, const char \*s2)

Compares two strings, ignoring case.

char \* str\_strip\_whitespace (char \*str, char \*buffer, size\_t buf\_len)

Strips leading and trailing whitespace from the given string.

• size t strlen (const char \*s)

Returns the length of a string.

• char \* str to upper (char \*str, char \*buffer, int buf len)

Converts the given string to upper case.

char \* str\_to\_lower (char \*str, char \*buffer, int buf\_len)

Converts the given string to lower case.

char \* strtok (char \*restrict s1, const char \*restrict s2)

Split string into tokens TODO.

char \* sprintf (const char \*format, char \*str, size\_t buf\_len,...)

Formats the string with normal C formatting options.

char \* vsprintf (const char \*format, char \*str, size t buf len, va list varargs)

Formats the string with normal C formatting options.

• char split\_once\_after (const char \*string, const char \*split\_after, char buff[], int buff\_len)

Returns string located after where to split, orginal string returned if not split.

bool starts\_with (const char \*string, const char \*starts\_with)

Returns true if string starts with given string.

• bool ci\_starts\_with (const char \*string, const char \*prefix)

Returns true if the string starts with the given prefix.

int split (const char \*string, char split\_at, int word\_length, char buff[][word\_length], int words)

Splits the given string at character saving into a 2D buffer.

• int substring (const char \*string, int start, int end, char buff[], int buff size)

Splits the given string at character saving into a 2D buffer.

# 6.38.1 Detailed Description

A subset of standard C library functions.

### 6.38.2 Function Documentation

## 6.38.2.1 ci\_starts\_with()

Returns true if the string starts with the given prefix.

Case is ignored.

### **Parameters**

string	the string to be tested.
prefix	the prefix of the string.

#### Returns

true if the string starts with the prefix.

# 6.38.2.2 first\_label\_matches()

Checks if the given string's first part matches the label.

#### **Parameters**

str1	the string.
label	the label.

# Returns

if the string matches the label.

# 6.38.2.3 memcpy()

Copy a region of memory.

### **Parameters**

dst	The destination memory region
src	The source memory region
n	The number of bytes to copy

#### Returns

A pointer to the destination memory region

# 6.38.2.4 memset()

Fill a region of memory.

#### **Parameters**

address	The start of the memory region
С	The byte to fill memory with
n	The number of bytes to fill

# Returns

A pointer to the filled memory region

# 6.38.2.5 split()

Splits the given string at character saving into a 2D buffer.

# **Parameters**

string	string to be split
split_at	character to split at
wordlength	length of the column dimension of buffer must match buff dimension
words	number of rows (words) available in buff

#### Returns

error codes 0 is successful, negative if not

# 6.38.2.6 split\_once\_after()

Returns string located after where to split, orginal string returned if not split.

#### **Parameters**

string	string to be split
split← At	string that chooses where to split

#### Returns

the string split or not

# 6.38.2.7 sprintf()

Formats the string with normal C formatting options.

# **Parameters**

format	the string format.
str	the buffer to store the resulting string in.
buf_len	the length of the provided string buffer.
	the formatting values.

## Returns

the formatted string.

# 6.38.2.8 starts\_with()

Returns true if string starts with given string.

### **Parameters**

string	string to be tested
starts_with	given string to start with

#### Returns

if string starts with starts\_with string

# 6.38.2.9 str\_strip\_whitespace()

Strips leading and trailing whitespace from the given string.

### **Parameters**

str	the string to strip from.
buffer the buffer to store the resulting string in, or NULL if the strip should be done	
buf_len	the length of the buffer.

## Returns

a pointer to the resulting string, or NULL if it failed.

# 6.38.2.10 str\_to\_lower()

Converts the given string to lower case.

If the provided buffer is null, overwrites the original string.

#### **Parameters**

str the original string.	
buffer	the buffer to store the string in, or NULL if the original string should be overwritten.
buf_len	the length of the buffer. If buffer is NULL, can be any number.

#### Returns

a pointer to the lower case string, or NULL if the buffer was too small to store the resulting string.

# 6.38.2.11 str\_to\_upper()

Converts the given string to upper case.

If the provided buffer is null, overwrites the original string.

### **Parameters**

str	the original string.	
buffer	the buffer to store the string in, or NULL if the original string should be overwritten.	
buf_len	the length of the buffer. If buffer is NULL, can be any number.	

#### Returns

a pointer to the upper case string, or NULL if the buffer was too small to store the resulting string.

# 6.38.2.12 strcicmp()

```
int strcicmp (  {\rm const~char} \ * \ s1, \\ {\rm const~char} \ * \ s2 \ )
```

Compares two strings, ignoring case.

#### **Parameters**

s1	The first string to compare
s2	The second string to compare

#### Returns

0 if strings are equal, <0 if s1 is lexicographically before s2, >0 otherwise

# 6.38.2.13 strcmp()

```
int strcmp ( \label{eq:const_char} \mbox{const char} \ * \ s1, \\ \mbox{const char} \ * \ s2 \ )
```

Compares two strings.

#### **Parameters**

s1	The first string to compare
s2	The second string to compare

#### Returns

0 if strings are equal, <0 if s1 is lexicographically before s2, >0 otherwise

# 6.38.2.14 strcpy()

Copies the data from the string source into the string destination.

If maxlen is exceeded, it only copies that amount of chars over.

#### **Parameters**

str_dest	the string destination.	
str_src	the string source.	
maxlen	the maximum amount of bytes to copy. Note that maxlen does not include the null terminator.	

# Returns

a pointer to the string, or NULL if there was an error.

## 6.38.2.15 strlen()

```
size_t strlen ( {\tt const\ char\ *\ s\ )}
```

Returns the length of a string.

### **Parameters**

```
s A NUL-terminated string
```

### Returns

The number of bytes in the string (not counting NUL terminator)

# 6.38.2.16 substring()

Splits the given string at character saving into a 2D buffer.

### **Parameters**

string	string to be spliced
start	index to start at
end	index to end at
buff	buffer to save result to
buff_size	length of buff

#### Returns

error codes 0 is successful, negative if not

### 6.38.2.17 vsprintf()

Formats the string with normal C formatting options.

#### **Parameters**

format	the string format.
str	the buffer to store the resulting string in.
buf_len	the length of the provided string buffer.
	the formatting values.

#### Returns

the formatted string.

# 6.39 string.h

#### Go to the documentation of this file.

```
00001 #ifndef MPX_STRING_H
00002 #define MPX_STRING_H
00003
00004 #include <stddef.h>
00005 #include "stdarg.h"
00006 #include "stdbool.h"
00007
00019 bool first_label_matches(const char *str1, const char *label);
00020
00028 void* memcpy(void * restrict dst, const void * restrict src, size_t n);
00037 void* memset(void *address, int c, size_t n);
00038
00047 char *strcpy(char *str_dest, const char *str_src, size_t maxlen);
00048
00055 int strcmp(const char *s1, const char *s2);
00063 int strcicmp(const char *s1, const char *s2);
00064
00073 char *str_strip_whitespace(char *str, char *buffer, size_t buf_len);
00074
00080 size_t strlen(const char *s);
00081
00093 char *str_to_upper(char *str, char *buffer, int buf_len);
00094
00106 char *str_to_lower(char *str, char *buffer, int buf_len);
00107
00112 char* strtok(char * restrict s1, const char * restrict s2);
00113
00122 char *sprintf(const char *format, char *str, size_t buf_len, ...);
00123
00132 char *vsprintf(const char *format, char *str, size_t buf_len, va_list varargs);
00133
00140 char split_once_after(const char* string, const char* split_after, char buff[], int buff_len);
00141
00148 bool starts_with(const char* string, const char* starts_with);
00157 bool ci_starts_with(const char *string, const char *prefix);
00158
00167 int split(const char *string, char split_at, int word_length, char buff[][word_length], int words);
00168
00178 int substring(const char* string, int start, int end, char buff[], int buff_size);
00179 #endif
```

# 6.40 include/sys\_req.h File Reference

System request function and constants.

```
#include <mpx/device.h>
```

6.41 sys\_req.h 65

# **Macros**

- #define INVALID\_OPERATION (-1)
- #define INVALID\_BUFFER (-2)
- #define INVALID\_COUNT (-3)

# **Enumerations**

• enum op\_code { EXIT , IDLE , READ , WRITE }

# **Functions**

```
    int sys_req (op_code op,...)
    Request an MPX kernel operation.
```

# 6.40.1 Detailed Description

System request function and constants.

# 6.40.2 Function Documentation

## 6.40.2.1 sys\_req()

Request an MPX kernel operation.

### **Parameters**

op_code	One of READ, WRITE, IDLE, or EXIT
	As required for READ or WRITE

#### Returns

Varies by operation

# 6.41 sys\_req.h

### Go to the documentation of this file.

```
00001 #ifndef MPX_SYS_REQ_H
00002 #define MPX_SYS_REQ_H
```

```
00004 #include <mpx/device.h>
00005
00011 typedef enum {
           EXIT,
IDLE,
00012
00013
            READ,
00015
            WRITE,
00016 } op_code;
00017
00018 // error codes
00019 #define INVALID_OPERATION (-1)
00020 #define INVALID_BUFFER (-2)
00021 #define INVALID_COUNT
00022
00029 int sys_req(op_code op, ...);
00030
00031 #endif
```

# 6.42 time\_zone.h

```
00001
00002 #ifndef F_R_I_D_A_Y_TIME_ZONE_H
00003 #define F_R_I_D_A_Y_TIME_ZONE_H
00004
00011 typedef struct {
        const char *tz_label;
const char *tz_longformat;
00013
00015
00017
           const int tz_hour_offset;
         const int tz_minute_offset;
00019
00021
          const char* tz_city;
00022 } time_zone_t;
00029 const time_zone_t **get_all_timezones(void);
00030
00036 const time_zone_t *get_timezone(const char *tz_label);
00037
00038 #endif //F_R_I_D_A_Y_TIME_ZONE_H
```