Active Directory & Help Desk Home Lab

A self-built company IT environment: **Windows Server 2025 Active Directory**, a domain-joined **Windows 11** client, and an **Ubuntu Linux** server running the **osTicket** help desk. Documented step by step, including the reasoning behind each decision and every problem I hit.

Full write-up as PDF: docs/AD-Home-Lab-Build-Log.pdf · **PowerShell scripts:** scripts/

Overview

I built a small company IT environment from scratch in VirtualBox: an Active Directory domain, `lab.local`, a domain-joined Windows 11 workstation, and an Ubuntu Linux server running the osTicket help desk. On top of it I worked ten realistic help desk tickets end to end, from password resets and onboarding to Group Policy, DNS and PowerShell automation.


The goal is hands-on practice with the work an IT support or junior sysadmin role handles daily, documented with the reasoning behind each decision and the problems I hit along the way. The roadmap at the end shows what comes next.

Skills demonstrated

- Windows Server 2025: AD DS, DNS (forward and reverse zones), Group Policy
- User lifecycle: onboarding, offboarding, password resets, account lockouts
- Access control: OUs, security groups, AGDLP, NTFS and share permissions
- PowerShell: bulk user creation from CSV, auditing and fixing account data
- Security practice: least privilege, named admin accounts, UAC, lockout policy
- Identity and PKI: LDAP over StartTLS, an Enterprise Root CA (AD CS), certificate trust on Linux, a read-only service account
- Linux: Ubuntu Server administration over SSH, packages, services, permissions
- Web stack: Apache, MariaDB and PHP (LAMP) hosting the osTicket help desk, built from source where needed
- Help desk practice: ticket ownership, internal notes, data-owner approval, follow-up tasks, the full access lifecycle
- Troubleshooting: documented problems, causes and fixes throughout

Lab environment

Three VMs share an isolated VirtualBox internal network, `labnet`, with no router. DC01 provides AD and DNS; CLIENT01 and HELPDESK01 use it as their DNS server. HELPDESK01 also has an outbound-only NAT adapter for software downloads.



Every DNS lookup and login from CLIENT01 goes to DC01, which is why the client can't join or log in while DC01 is off.

Item	Value
Host	Laptop, 16 GB RAM
Hypervisor	Oracle VirtualBox
Network	Internal Network `labnet`, 192.168.10.0/24, no gateway
Domain	`lab.local` (NetBIOS name `LAB`), single forest, single domain

VM	OS	Role	vCPU	RAM	Disk	IP address	DNS server
DC01	Windows Server 2025 Standard Evaluation (Desktop Experience)	Domain controller, DNS, Global Catalog, file server, certificate authority (AD CS)	2	4 GB	60 GB	192.168.10.10 (static)	127.0.0.1
CLIENT01	Windows 11 Enterprise Evaluation	Domain-joined workstation	2	4 GB	64 GB	192.168.10.20 (static)	192.168.10.10
HELPDESK01	Ubuntu Server 26.04 LTS	osTicket help desk (Apache, MariaDB, PHP 8.4) with AD sign-in over LDAP/TLS	2	2 GB	25 GB	192.168.10.30 (static)	192.168.10.10

Directory structure

OU path	Contents
Company\Users\IT	Alex Lee (`alee`)
Company\Users\HR	Jane Smith (`jsmith`)
Company\Users\Sales	John Brown (`jbrown`)
Company\Groups	`IT-Staff`, `HR-Staff`, `Sales-Staff` (Global, Security)
Company\Computers	CLIENT01


Users and computers sit in separate OUs so Group Policy can target each independently. Each user is a member of their department's group.

Build steps


The build took 12 steps, from an empty VirtualBox install to a domain user logged in on CLIENT01. Usernames in file paths are blurred.

Domain controller (DC01)


1. **Prepared the host.** Confirmed virtualization was enabled, installed VirtualBox, and downloaded the Windows Server 2025 and Windows 11 Enterprise evaluation ISOs from the Microsoft Evaluation Center.
2. **Created the DC01 VM.** 2 vCPU, 4 GB RAM, 60 GB disk, unattended installation skipped. Attached Adapter 1 to Internal Network `labnet`.




3. **Installed Windows Server 2025.** Chose *Standard Evaluation (Desktop Experience)* for the full GUI, and set the Administrator password.




4. **Configured the base server.** Installed VirtualBox Guest Additions, set a static IP (192.168.10.10/24, DNS 127.0.0.1), set the time zone to UTC-04:00, and renamed the server to DC01 before promotion.



Server Manager
Server Manager ‣ Local Server
Manage
Tools
View
Help
Dashboard
Local Server
All Servers
File and Storage
PROPERTIES
For WIN-RRG729SAKNS
TASKS
System Properties
Computer Name/Domain Changes
You can change the name and the membership of this computer. Changes might affect access to network resources.
Computer name:
DC01
Full computer name:
DC01
More...
Member of
Domain:
Workgroup:
WORKGROUP
OK
Cancel
Apply
Last installed updates
Never
Windows Update
Last checked for updates
Today at
Microsoft Defender Antivirus
Feedback & Diagnostics
Settings
IE Enhanced Security Configuration
On
Time zone
Product ID
Processors
Server Name
ID
Severity
Source
Log
Date and Time
WIN-RRG729SAKNS 8198 Error Microsoft-Windows-Security-SPP Application 9/27/2026 6:43:14 PM
WIN-RRG729SAKNS 1014 Error Microsoft-Windows-Security-SPP Application 9/27/2026 6:43:14 PM
WIN-RRG729SAKNS 8200 Error Microsoft-Windows-Security-SPP Application 9/27/2026 6:43:14 PM
Search
10:41 PM
9/27/2026



5. **Snapshot:** `Clean install - before AD`.


6. **Installed AD DS and promoted DC01.** Added the Active Directory Domain Services role, then promoted DC01 to a domain controller in a new forest, `lab.local`, with DNS and Global Catalog. NetBIOS name `LAB`. The server rebooted automatically.






7. **Snapshot:** `AD installed - lab.local`.


8. **Built the OU structure, users and groups** in Active Directory Users and Computers, as listed under Lab environment. Added each user to their department group.




Client (CLIENT01)

9. **Created the CLIENT01 VM.** 2 vCPU, 4 GB RAM, 64 GB disk, OS version Windows 11 (64-bit), which enables the virtual TPM 2.0, EFI and Secure Boot. Attached to `labnet`.







10. **Installed Windows 11 Enterprise** with a local account, `localadmin`. Installed Guest Additions.





11. **Pointed the client at the domain.** Set a static IP (192.168.10.20/24, DNS 192.168.10.10) and confirmed with `nslookup lab.local`, which returned 192.168.10.10.





12. **Renamed and joined the domain.** Renamed to CLIENT01 and joined `lab.local` using domain Administrator credentials, then restarted. Logged in as `LAB\jsmith`, and moved the CLIENT01 computer object from the default Computers container to `Company\Computers`.





Troubleshooting log


Eight issues came up during the build; seven were fixed and one is known and non-blocking. Each has an error screenshot where one was captured.

#	Symptom	Cause	Fix
1	DC01 would not boot: "No bootable medium found". VM showed OS type Other/Unknown (32-bit).	Downloaded the wrong ISO: `SERVER_LOF_PACKAGES_OEM.iso` is the Languages and Optional Features disc, not an installer.	Downloaded the 64-bit `SERVER_EVAL` ISO, set the VM type to Microsoft Windows, 64-bit, and remounted it. *Screenshot below.*
2	Ctrl+Alt+Del opened the host's security screen instead of the VM's.	Windows on the host always intercepts Ctrl+Alt+Del.	Sent it with Input > Keyboard > Insert Ctrl-Alt-Del, or Host key (Right Ctrl) + Delete.
3	DC01 clock ran 3 hours ahead of real time.	VM clock not yet synced with the host.	Resolved after installing Guest Additions and rebooting. Matters because Kerberos logins fail when clocks differ by more than 5 minutes.
4	Promotion prerequisites check failed: "Role change is in progress or this computer needs to be restarted."	Started promotion before the AD DS role install had fully finished.	Restarted the server and reran promotion from the Server Manager flag. After the restart, Server Manager briefly showed Roles: 0 until it finished loading. *Screenshot below.*
5	CLIENT01 boot failed: "No bootable option or device was found."	Missed the 5-second "Press any key to boot from CD or DVD" prompt, so the VM tried the empty disk.	Remounted the ISO, restarted, and pressed a key at the prompt. *Screenshot below.*
6	`nslookup lab.local` on CLIENT01 timed out.	DC01 was powered off, so no DNS server answered.	Started DC01 and waited for DNS to load; the lookup then returned 192.168.10.10. The remaining "Server: UnKnown" line is expected with no reverse lookup zone. *Screenshot below.*


#	Symptom	Cause	Fix
7	After "Welcome to the lab.local domain", an error said changing the Primary Domain DNS name failed.	Known Windows quirk when renaming and joining in one step.	No action needed: the join succeeded. Verified CLIENT01 in ADUC and `whoami` as `lab\jsmith`. *Screenshot below.*
8	CLIENT01 desktop shows "Windows License is expired".	The evaluation cannot activate without internet access.	Open, non-blocking. To revisit if it starts affecting the VM.

Error screenshots


Issue 1: the LOF ISO attached as the boot disc, so DC01 had nothing to boot from.




Issue 4: promotion blocked because the role install hadn't finished.




Issue 5: the boot prompt was missed, so CLIENT01 tried the empty disk.



Issue 6: DNS timed out while DC01 was powered off.




Issue 7: the harmless DNS name error shown after a successful join.



Verification

Four checks confirm the domain works end to end, from the server side and the client side.

Check	Where	Result
Server is a domain controller	DC01, Server Manager > Local Server	Domain: `lab.local` ; AD DS and DNS roles listed; firewall profile Domain: On
Client can find the domain	CLIENT01, `nslookup lab.local`	Resolves to 192.168.10.10
Computer joined the domain	DC01, ADUC	CLIENT01 computer object present, now in `Company\Computers`
Domain user can log in	CLIENT01, `whoami`	`lab\jsmith`



Help desk tickets


With the domain running, I worked simulated help desk tickets end to end: verify the request, fix it, then prove the fix from the user's side.


Ticket	Request	Resolution	Skill
#1001	John Brown (Sales) forgot his password	Temporary password, must change at next logon	Password reset
#1002	New Sales Rep, Maria Garcia, starts Monday	Account in the Sales OU with Sales-Staff access, title, department and manager set	Onboarding
#1003	Jane Smith (HR) locked out	Added a domain lockout policy, then unlocked her account	Lockout policy and unlock
#1004	Alex Lee (IT) leaving today	Account disabled, groups removed, moved to Disabled Users, reason recorded	Offboarding

Ticket	Request	Resolution	Skill
#1005	Sales needs a private shared folder	`\\DC01\Sales` share, access granted through FS-Sales-Modify (AGDLP)	File shares and NTFS permissions
#1006	Sales keeps forgetting the share's address	GPO linked to the Sales OU maps it as S: at login	Group Policy drive mapping
#1007	nslookup shows "Server: UnKnown"	AD-integrated reverse lookup zone with PTR records	DNS reverse lookups
#1008	Four new starters across Sales and HR	PowerShell script creates accounts from HR's CSV	PowerShell bulk onboarding
#1009	Accounts missing title and department	Found with a `Where-Object` audit, fixed with `Set-ADUser`, re-verified	PowerShell auditing and bulk edits
#1010	Security audit: all admin work done as built-in Administrator	Named `adm-` admin account in its own OU; built-in account kept as break-glass	Privileged account management, UAC


#1001: Password reset


John had forgotten his password after vacation. I reset it in ADUC to a temporary password and ticked **User must change password at next logon**, so IT never knows his real password. In a real environment the caller's identity is verified first, so nobody can reset someone else's password by impersonating them.






At his next sign-in, Windows forced John to choose a new password before letting him in.







#1002: New hire onboarding

Sales manager Karen Mills asked for a new Sales Rep, Maria Garcia, with the same access as the rest of Sales. Karen didn't exist in AD yet, so I created her first, then created Maria (`mgarcia`) in the Sales OU. I added Maria to **Sales-Staff** and set her job title, department (Sales) and manager (Karen Mills). These profile fields feed org charts and address books, and AD fills in Karen's Direct reports automatically.










#1003: Account lockout

Jane reported being locked out, but the domain had no lockout policy, so unlimited wrong guesses were possible. I set one in the **Default Domain Policy**: lock after **5** invalid attempts, for **15 minutes**, with the counter resetting after **15 minutes**. I left Allow Administrator account lockout enabled, since the built-in Administrator is the most-guessed account. After applying it with `gpupdate /force`, I unlocked Jane and confirmed she could sign in. Before unlocking anyone, it's worth asking why the lockout happened: repeat lockouts usually mean an old saved password is retrying somewhere.



DC01 (Client joined) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Server Manager
Server Manager • Dashboard
Manage Tools View Help
Dashboard
Local Server
All Servers
AD DS
DNS
File and Storage Services
WELCOME TO SERVER MANAGER
Group Policy Management
Group Policy Management Editor
File Action View Help
Default Domain Policy [DC0
Computer Configuration
Policies
Software Settings
Windows Settings
Name Resolut
Scripts (Startu
Security Settir
Account P
Passwo
Accou
Kerber
Local Polic
Event Log
Restricted
System Se
Registry
File Systen
Wired Net
Windows I
Network L
Wireless N
Public Key
Software F
Policy
Policy Setting
Account lockout duration
15 minutes
Account lockout threshold
5 invalid logon attempts
Allow Administrator account lockout
Enabled
Reset account lockout counter after
15 minutes
Hide
Server 1
eability
nance
sults
10/1/2026 12:05 AM
All Servers 1
Manageability
Events
Services
Performance
BPA results
10/1/2026 12:05 AM
Search
12:14 AM
10/1/2026
Right Ctr



DC01 (Client joined) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Server Manager
Server Manager • Dashboard
Manage Tools View Help
Dashboard
Local Server
All Servers
AD DS
DNS
File and Storage Services
WELCOME TO SERVER MANAGER
Group Policy Management
File Action View
Group Policy Managema
Forest: lab.local
Domains
lab.local
Default Do
Company
Domain C
Group Pol
WMI Filter
Starter GP
Sites
Group Policy Mod
Group Policy Res
Administrator: Command Pro
Microsoft Windows [Version 10.0.26100.32230]
(c) Microsoft Corporation. All rights reserved.
C:\Users\Administrator>gpudate /force
'gpudate' is not recognized as an internal or external command,
operable program or batch file.
C:\Users\Administrator>gpupdate /force
Updating policy...
Computer Policy update has completed successfully.
User Policy update has completed successfully.
C:\Users\Administrator>
Hide
BPA results
1
1/2026 12:05 AM
Search
12:13 AM
10/1/2026
Right Ctr




#1004: Leaver offboarding

HR asked for Alex Lee's access to be removed on his last day, without deleting anything his manager might need. I **disabled** the account rather than deleting it: deletion is permanent and breaks the links to his files and permissions, so companies delete only after a retention period. I removed him from IT-Staff, leaving only Domain Users (his primary group), so the account would grant nothing even if re-enabled by mistake. I then created a **Company\Disabled Users** OU and moved him into it, keeping leavers in one place for auditing.









Alex's account Description was later set to `Disabled 2026-10-01 - Ticket #1004 - left company` (in #1009), so anyone who finds the account knows why it exists and when it was disabled.

#1005: Department file share


Sales manager Karen Mills asked for a shared folder only her team could use. I built it with the **AGDLP** model: **A**ccount → **G**lobal group → **D**omain **L**ocal group → **P**ermission. Maria sits in Sales-Staff (a global group of people), Sales-Staff sits in **FS-Sales-Modify** (a domain local group representing access to the folder), and only FS-Sales-Modify appears on the folder. This separates "who works in Sales" from "who can edit this folder", so future access changes are group-membership edits rather than folder-permission edits, and auditing access means reading one group's members.

The folder `C:\Shares\Sales` is shared as `\\DC01\Sales`. Windows enforces two permission layers and applies the stricter one, so I opened the **share** layer to Authenticated Users (Full Control) and did the real restriction in **NTFS**. Leaving the default share permission (Everyone: Read) would have silently blocked writes. On the folder, I disabled inheritance (converting the inherited entries so Administrators and SYSTEM stayed), removed the inherited **Users** entries that would have let every domain user in, and granted FS-Sales-Modify **Modify** rather than Full Control, so users can't change permissions (least privilege).






Testing covered both directions. Maria could create a file, which proves write access over the network, through both layers.



The negative test: Jane (HR) was refused by the NTFS layer, since no entry on the folder matches her groups.





#1006: Mapped drive with Group Policy

Sales staff kept forgetting the `\\DC01\Sales` address, so I pushed the share to them as drive **S:** with a Group Policy Object (GPO), a named bundle of settings the domain controller applies to everything in the OU it's linked to.


I created `Sales - Map S Drive` and linked it to the **Company\Users\Sales** OU, so only Sales users receive it; the name states who it targets and what it does. The drive map sits under **User Configuration**, so it follows the person to any PC, and under **Preferences**, the only place drive maps exist (they replaced older `net use`


logon scripts). I chose the **Update** action, which creates the drive if missing and corrects it if it exists, unlike Replace, which tears it down at every refresh.





The drive appeared for Maria at her next sign-in without running `gpupdate /force`, because Group Policy applies at every login as well as in a background refresh roughly every 90 minutes. Jane, in the HR OU, received no drive, confirming the GPO's scope.





A drive map is a convenience, not a security control: if it reached Jane by mistake, the NTFS permissions from #1005 would still deny her.


#1007: DNS reverse lookup zone

`nslookup` on the clients reported **Server: UnKnown** and timed out before answering. Forward lookups (name to IP, via A records) worked, but there was no **reverse lookup zone** to turn an IP back into a name (via PTR records), so nslookup couldn't name the DNS server it was talking to. Reverse lookups also matter for logs and security tools that record only IP addresses.


I created a primary, **AD-integrated** reverse zone, so its records replicate to future domain controllers automatically. I set replication to all DNS servers in the domain and allowed **secure dynamic updates only**,

so only authenticated domain computers can register or change their own records, and a rogue device can't claim a server's name.


My first attempt failed: I typed the network ID as `192.68.10` instead of `192.168.10`, creating the zone `10.68.192.in-addr.arpa`. Creating DC01's PTR record then failed with "the referenced reverse lookup zone cannot be found", because DNS looked for `10.168.192.in-addr.arpa`. Zones can't be renamed, so I deleted the zone and recreated it, this time checking the zone name on the wizard's summary page before finishing.



With the zone correct, I created PTR records for DC01 and CLIENT01 from their existing A records, which guarantees the name and IP match.



`nslookup lab.local` now names the server as dc01.lab.local, and a direct reverse lookup of 192.168.10.20 returns CLIENT01.lab.local.



#1008: Bulk onboarding with PowerShell

HR sent four new starters across Sales and HR. Rather than creating them by hand, I scripted it, so the same steps scale to any number of people, every field is filled identically, and the script itself records what was done.

I saved HR's list as `C:\Scripts\newhires.csv`, adding a Username column following the first-initial-plus-surname convention, and checked it with `Import-Csv` before changing anything. The script below loops over each row, builds the target OU's distinguished name from the Department column, creates the account with splatted parameters, and adds it to the matching `<Department>-Staff` group, which only works because


group names follow a consistent convention. The temporary password is prompted for at run time and never stored in the file. `New-ADUser` creates accounts disabled by default, so the script sets `Enabled` explicitly.

```
$password = Read-Host "Temporary password for new starters" -AsSecureString
$users = Import-Csv "C:\Scripts\newhires.csv"


foreach ($u in $users) {
    $ou = "OU=$($u.Department),OU=Users,OU=Company,DC=lab,DC=local"

    $params = @{
        Name                = "$($u.FirstName) $($u.LastName)"
        GivenName           = $u.FirstName
        Surname             = $u.LastName
        DisplayName         = "$($u.FirstName) $($u.LastName)"
        SamAccountName      = $u.Username
        UserPrincipalName   = "$($u.Username)@lab.local"
        Title               = $u.Title
        Department          = $u.Department
        Path                = $ou
        AccountPassword     = $password
        ChangePasswordAtLogon = $true
        Enabled             = $true
    }


    New-ADUser @params
    Add-ADGroupMember -Identity "$($u.Department)-Staff" -Members $u.Username
    Write-Host "Created $($u.Username) in $($u.Department)"
}
```



A `Get-ADUser` audit confirmed each account's title and department, and `Get-ADGroupMember` confirmed the group memberships. The audit also exposed that the two earliest hand-made accounts, Jane Smith and John Brown, had no title or department, which is the kind of inconsistency PowerShell audits catch and manual clicking misses.



The real test was Priya Patel's first login. Without any per-user setup, she received the S: drive (from the Sales OU's GPO, #1006) and could open it (through Sales-Staff → FS-Sales-Modify, #1005). Once the structure is right, onboarding is just creating the account in the right OU and group.




#1009: Auditing and fixing account data

The #1008 audit showed accounts with no title or department, which makes people vanish from HR reports and the address book. Rather than fixing the two names I already knew, I searched for the condition itself, so any other incomplete account would surface too:

```
        Get-ADUser -Filter * -SearchBase "OU=Users,OU=Company,DC=lab,DC=local" -Properties T
itle,Department |
            Where-Object { -not $_.Title -or -not $_.Department } |
            Select-Object Name,SamAccountName,Title,Department
```

It returned Jane Smith and John Brown. My first fix contained a mistake: the second `Set-ADUser` targeted `jsmith` instead of `jbrown`, overwriting Jane's new values and leaving John blank. Rerunning the same search is the step that catches this kind of error. I corrected both accounts, and the rerun search returned nothing. The mistake changed only a descriptive field; access was never affected, because it comes from group membership and OU placement, not profile attributes. In the same session I recorded why Alex Lee's account is disabled (#1004).




Lesson: a check only finds what it's designed to look for. The blank-field search proves nothing is missing, but not that values are correct; reading changed accounts back covers that.

#1010: Named admin accounts


A simulated security audit found all admin work being done as the built-in **Administrator**. That account is shared (so logs can't say which person acted), is the first account attackers target, and by default bypasses UAC, so everything it runs has full rights.

I created a **Company\Admin Accounts** OU, kept beside Company\Users rather than inside it so user-targeted GPOs never reach admin accounts, and a named admin account, `adm-zramkissoon`, added to Domain Admins. The `adm-` prefix makes privileged accounts obvious in logs and easy to find with a script. The built-in Administrator stays enabled as a **break-glass** account for emergencies only.


My first `New-ADUser` attempt failed. Pasting lost the line breaks, so the line-continuation backticks landed mid-line, where a backtick instead escapes the next character, turning `-SamAccountName` into plain text ("A positional parameter cannot be found"). The OU path also had `OU-` instead of `OU=`. I reran it as a single line with no backticks.



Signed in as the new account, `whoami /groups` showed UAC at work. In a normal window, Domain Admins is present but marked **Group used for deny only**, so its rights are inactive.



In an elevated window, the same group is **Enabled**. Admin rights apply only where I deliberately elevate.





The group's SID ends in **512**, the fixed identifier for Domain Admins in every domain; the built-in Administrator is always **500**, which is part of why it's such a predictable target.

Linux server build: HELPDESK01


HELPDESK01 is an Ubuntu Server 26.04 LTS VM at 192.168.10.30 that will host the osTicket help desk, managed over SSH from CLIENT01. I chose an LTS release for five years of security updates, and the Server edition without a desktop, which runs in 2 GB of RAM and is managed the way real Linux servers are.

Setting	Value	Why
vCPU / RAM / disk	2 / 2 GB / 25 GB	Enough for a web server and database without a GUI
Adapter 1	NAT, DHCP (10.0.2.15)	Outbound-only internet for package downloads; nothing can reach in
Adapter 2	labnet, static 192.168.10.30/24, no gateway	Fixed address on the lab network; one default route, via NAT
DNS	192.168.10.10, search domain `lab.local`	Split DNS: lab names resolve via DC01, everything else via NAT
Storage	LVM, whole disk	Volumes can be grown later without reinstalling
Remote access	OpenSSH server	Encrypted remote administration
Admin account	Local user with sudo	Elevate per command instead of logging in as root





The first install attempt hung for nearly an hour at "Loading essential drivers." The Ubuntu installer runs entirely from RAM, so I raised the VM to 4 GB for the install only, and disabled 3D acceleration, a common cause of Linux boot hangs in VirtualBox. The second attempt booted normally. During installation the kernel logged a "soft lockup" warning, meaning a virtual CPU was starved of host CPU time for 39 seconds; it was non-fatal and pointed to a busy host rather than a fault. After installing, I patched the system and returned the RAM to 2 GB.




The SSH session from CLIENT01 confirms the static lab address works, the host key was verified and recorded on first connection, and no updates are outstanding.

osTicket help desk on a LAMP stack

osTicket 1.18.4 now runs on HELPDESK01 at `http://helpdesk01.lab.local`, with the staff panel at `/scp/`. It sits on a LAMP stack: Linux, Apache, MariaDB and PHP.

Compatibility check first. osTicket 1.18.4 supports PHP 8.2 to 8.4, but Ubuntu 26.04 ships PHP 8.5. Rather than install an unsupported version, I added the signed packages.sury.org repository, with its key scoped to that repository only via `Signed-By`, and installed PHP 8.4 explicitly, naming `php8.4-*` packages so Ubuntu's default 8.5 was never pulled in.





Database, least privilege. I ran `mariadb-secure-installation` (removing anonymous users, remote root login and the test database; root stays on Unix-socket authentication, so it has no password to steal) and created a dedicated `osticket` user that can connect only from localhost and only reach the `osticket` database. Logged in as that user, only `osticket` is visible.



Web server. osTicket's files live in `/var/www/osticket`, served by its own Apache virtual host with separate error and access logs. The config was validated with `apache2ctl configtest` before reloading. I added a DNS A record and PTR on DC01, so users reach the site by name.

```
zach@helpdesk01:/tmp$ sudo mkdir -p /var/www/osticket
sudo cp -r osticket/upload/. /var/www/osticket/
sudo cp /var/www/osticket/include/ost-sampleconfig.php /var/www/osticket/include/ost-config.php


zach@helpdesk01:/tmp$ sudo a2ensite osticket.conf
sudo a2dissite 000-default.conf
sudo a2enmod rewrite
sudo apache2ctl configtest
sudo systemctl reload apache2
[sudo: authenticate] Password:
Enabling site osticket.
To activate the new configuration, you need to run:
  systemctl reload apache2
Site 000-default disabled.
To activate the new configuration, you need to run:
  systemctl reload apache2
Enabling module rewrite.
To activate the new configuration, you need to run:
  systemctl restart apache2
AH00558: apache2: Could not reliably determine the server's fully qualified domain name, using 127.0.1.
1. Set the 'ServerName' directive globally to suppress this message
Syntax OK
zach@helpdesk01:/tmp$
```

```
Command Prompt


Microsoft Windows [Version 10.0.26200.6584]
(c) Microsoft Corporation. All rights reserved.


C:\Users\ppatel>nslookup helpdesk01.lab.local
Server:  DC01.lab.local
Address:  192.168.10.10


Name:    helpdesk01.lab.local
Address:  192.168.10.30


C:\Users\ppatel>
```

Install and lockdown. The installer's prerequisite check passed every required item; only IMAP (email fetching, unused here) was missing. During install, Apache's account (`www-data`) owned the files so it could write the config. Afterwards I deleted the `setup` folder, so nobody can rerun the installer, and made `ost-config.php`, which holds the database password, owned by root and read-only to Apache (`0644`).


osTicket Installer
Support Ticket System
Installing osTicket v1.18.4
Installation Guide — Get Professional Help — Contact Us
Thank You for Choosing osTicket!
We are delighted you have chosen osTicket for your customer support ticketing system!
The installer will guide you every step of the way in the installation process. You're minutes away from your awesome customer support system!
Prerequisites
Before we begin, we'll check your server configuration to make sure you meet the minimum requirements to run the latest version of osTicket.
Required:
These items are necessary in order to install and use osTicket.
PHP v8.2 or greater — (8.4.26)
MySQLi extension for PHP — module loaded
Recommended:
You can use osTicket without these, but you may not be able to use all features.
Gdlib Extension
PHP ICONV Extension — Useful for email processing
PHP IMAP Extension — Useful for email processing
PHP CTYPE Extension — Required for email fetching
PHP XML Extension — Required for XML API
PHP XML-DOM Extension — Useful for HTML email processing
PHP JSON Extension — Recommended for faster performance
Mbstring Extension — Recommended for all installations
Phar Extension — Recommended for plugins and language packs
Intl Extension — Recommended for improved localization
APCu Extension — Recommended for faster performance
Zend OPcache Extension — Recommended for faster performance
Continue »
Need Help?
If you are looking for a greater level of support, we provide professional installation services and commercial support with guaranteed response times, and access to the core development team. We can also help customize osTicket or even add new features to the system to meet your unique needs. Learn More!
Copyright © 2026 osTicket.com


osTicket Installer
Support Ticket System
Installing osTicket v1.18.4
Installation Guide — Get Professional Help — Contact Us
Congratulations!
Your osTicket installation has been completed successfully. Your next step is to fully configure your new support ticket system for use, but before you get to it please take a minute to cleanup.
Config file permission:
Change permission of ost-config.php to remove write access as shown below.
CLI:
chmod 0644 include/ost-config.php
Windows PowerShell:
icacls include\ost-config.php /reset
FTP:
Using WS_FTP this would be right hand clicking on the file, selecting chmod, and then remove write access
Cpanel:
Click on the file, select change permission, and then remove write access.
Below, you'll find some useful links regarding your installation.
Your osTicket URL:
http://helpdesk01.lab.local/
Your Staff Control Panel:
http://helpdesk01.lab.local/scp
osTicket Forums:
https://forum.osticket.com/
osTicket Documentation:
https://docs.osticket.com/
PS: Don't just make customers happy, make happy customers!
What's Next?
Post-Install Setup: You can now log in to Admin Panel with the username and password you created during the install process. After a successful log in, you can proceed with post-install setup.For complete and upto date guide see osTicket wiki!
Commercial Support Available: Don't let technical problems impact your osTicket implementation. Get guidance and hands-on expertise to address unique challenges and make sure your osTicket runs smoothly, efficiently, and securely.
Learn More!
Copyright © 2026 osTicket.com



Connecting osTicket to Active Directory

Employees and IT staff now sign in to osTicket with their domain accounts. osTicket checks every login against DC01 over LDAP, encrypted with StartTLS, using a read-only service account. I tested it end to end on 23 Oct 2026 with ticket #239263, below.

What happens when Jane signs in to the portal:

1. She types `jsmith` and her domain password.
2. osTicket connects to `dc01.lab.local` on port 389 and upgrades the connection to TLS. It trusts DC01's certificate because the lab's own certificate authority signed it.
3. It logs in (binds) as `svc-osticket` and searches `OU=Users,OU=Company,DC=lab,DC=local` for `jsmith`.
4. It binds again as Jane, with the password she typed. DC01 accepts or refuses it.
5. On her first login, osTicket creates its own record for her from her AD name and email address.

There is one account and one password per person, managed in AD. Disabling someone in AD also locks them out of the help desk.

Finishing the install: lockdown

The installer's `setup` folder has no password, so anyone who could reach it could reinstall over the help desk. I deleted it, gave `ost-config.php` to root with mode `0644` (only root can change it; the web server can still read it), and restarted Apache. The staff panel's warning banner disappeared, and I took the snapshot "osTicket Installed and lockdown".

```
Ubuntu 26.04.1 LTS helpdesk01 tty1

helpdesk01 login: zach
Password:
Welcome to Ubuntu 26.04.1 LTS (GNU/Linux 7.0.0-38-generic x86_64)

 * Documentation:  https://docs.ubuntu.com
 * Management:     https://landscape.canonical.com
 * Support:        https://ubuntu.com/pro

 System information as of Sat Oct 17 05:50:22 AM UTC 2026

  System load:             0.79
  Usage of /:              49.2% of 11.21GB
  Memory usage:            22%
  Swap usage:              0%
  Processes:               125
  Users logged in:         0
  IPv4 address for enp0s3: 10.0.2.15
  IPv6 address for enp0s3: fd17:625c:f037:2:a00:27ff:feb4:ee7b

 * Canonical Workshop gives developers fast, composable, reproducible, and
   secure developer environments that are perfect for agentic workflows.

   https://ubuntu.com/workshop


Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status


The list of available updates is more than a week old.
To check for new updates run: sudo apt update

zach@helpdesk01:~$ sudo systemctl restart apache2
[sudo: authenticate] Password:
zach@helpdesk01:~$ sudo rm -rf /var/www/osticket/setup
zach@helpdesk01:~$ sudo chown root:root /var/www/osticket/include/ost-config.php
zach@helpdesk01:~$ sudo chmod 0644 /var/www/osticket/include/ost-config.php
zach@helpdesk01:~$
```




Read-only service account

osTicket needs an account of its own to log in to AD and look people up. I created `svc-osticket` in a new **Company\Service Accounts** OU, kept apart from people so it's easy to find and audit. The `svc-` prefix marks it as a service account at a glance.

- **Password never expires:** no person rotates it, and an expiry would silently break every login one day. I compensated with a long password and no extra rights.
- **User cannot change password:** only an admin can.
- **No group memberships beyond Domain Users:** ordinary users can already read the directory, which is all osTicket needs. If the password leaked, it could read user details but change nothing.


Larger environments solve the expiry problem with a group Managed Service Account (gMSA), whose password AD rotates automatically.



Building the LDAP plugin


osTicket's "LDAP and Active Directory Authentication and Lookup" plugin has no pre-built download, so I compiled it from the official osTicket-plugins repository on HELPDESK01.


PHP first needs its LDAP extension. `php8.4-ldap` was already installed with the other PHP 8.4 packages, and `php -m | grep ldap` confirmed it was loaded. I named the 8.4 package explicitly so apt couldn't pull in a module for a different PHP version.




The build has two stages. `php make.php hydrate` downloads the plugin's third-party libraries, then `php -dphar.readonly=0 make.php build auth-ldap` packs the plugin into a single `.phar` archive. The `-dphar.readonly=0` flag lifts PHP's default refusal to write `.phar` files, for that one command.

Hydrate first failed with `Call to undefined function curl_init()`. The script downloads with PHP's cURL extension, which osTicket itself never needed, so it wasn't installed. Installing `php8.4-curl` fixed it, and hydrate pulled in **Net_LDAP2**, the library that does the LDAP work.


HELPDESK01 (osTicket Installed and lockdown) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Swap usage: 0%
Processes: 118
Users logged in: 0
IPv4 address for enp0s3: 10.0.2.15
IPv6 address for enp0s3: fd17:625c:f037:2:a00:27ff:feb4:ee7b
* Canonical Workshop gives developers fast, composable, reproducible, and
secure developer environments that are perfect for agentic workflows.
https://ubuntu.com/workshop
Expanded Security Maintenance for Applications is not enabled.
26 updates can be applied immediately.
19 of these updates are standard security updates.
To see these additional updates run: apt list --upgradable
Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status
zach@helpdesk01:~$ sudo apt install git
[sudo: authenticate] Password:
git is already the newest version (1:2.53.0-1ubuntu1).
git set to manually installed.
Summary:
Upgrading: 0, Installing: 0, Removing: 0, Not Upgrading: 26
zach@helpdesk01:~$ cd ~
zach@helpdesk01:~$ git clone https://github.com/osTicket/osTicket-plugins.git
Cloning into 'osTicket-plugins'...
remote: Enumerating objects: 971, done.
remote: Counting objects: 100% (343/343), done.
remote: Compressing objects: 100% (141/141), done.
remote: Total 971 (delta 239), reused 202 (delta 202), pack-reused 628 (from 3)
Receiving objects: 100% (971/971), 538.03 KiB | 1.72 MiB/s, done.
Resolving deltas: 100% (520/520), done.
zach@helpdesk01:~$ cd osTicket-plugins
zach@helpdesk01:~/osTicket-plugins$ php make.php hydrate
PHP Fatal error: Uncaught Error: Call to undefined function curl_init() in /home/zach/osTicket-plugins/make.php:538
Stack trace:
#0 /home/zach/osTicket-plugins/make.php(669): PluginBuilder->_http_get()
#1 /home/zach/osTicket-plugins/make.php(665): PluginBuilder->getComposer()
#2 /home/zach/osTicket-plugins/make.php(714): PluginBuilder->ensureComposer()
#3 /home/zach/osTicket-plugins/make.php(459): PluginBuilder->resolveDependencies()
#4 /home/zach/osTicket-plugins/make.php(340): PluginBuilder->_hydrate()
#5 /home/zach/osTicket-plugins/make.php(240): PluginBuilder->run()
#6 /home/zach/osTicket-plugins/make.php(732): Module->_run()
#7 {main}
thrown in /home/zach/osTicket-plugins/make.php on line 538
zach@helpdesk01:~/osTicket-plugins$
Right Ctrl




I copied `auth-ldap.phar` into `/var/www/osticket/include/plugins/` and made `www-data`, the web server's user, its owner so osTicket can load it.



Encrypted LDAP: a certificate authority on DC01


Windows Server 2025 refuses plain LDAP logins out of the box. Testing the service account with `ldapsearch` from HELPDESK01 returned `Strong(er) authentication required (8)`: DC01 requires every login to be signed or to travel inside TLS. Unsigned LDAP sends passwords readably and has been used in relay attacks, which is why Microsoft now enforces this by default.



I had two options: weaken DC01 with a Group Policy that stops requiring signing, or give DC01 a certificate so LDAP runs over TLS. I chose TLS, which keeps Microsoft's protection on.


After a DC01 snapshot ("Before AD CS"), I installed **Active Directory Certificate Services** and configured it as an **Enterprise Root CA** named `lab-DC01-CA`:

- **Enterprise** rather than Standalone: it publishes itself in AD, so domain-joined machines trust it automatically, and it issues certificates from templates with auto-enrollment.
- **Root**: it's the lab's first and only CA, so it sits at the top of the chain of trust.
- RSA 2048-bit key, SHA256 signatures, 5-year validity.




The CA is on the domain controller as a lab shortcut, to save RAM. In production it would run on its own server, ideally as a two-tier design with an offline root CA, so one break-in can't hand an attacker both the directory and the ability to issue trusted certificates.


`gpupdate /force` and `certutil -pulse` triggered auto-enrollment. DC01 received a **Domain Controller** certificate for `DC01.lab.local`, valid for Server Authentication, which is what turns on TLS for LDAP.




HELPDESK01 isn't domain-joined, so it had to be told to trust the CA. On CLIENT01, I fetched the CA certificate with `certutil -ca.cert`, converted it to text (PEM) with `certutil -encode`, and copied it across with `scp`.

Before trusting it, I compared fingerprints. `openssl` on HELPDESK01 and the Thumbprint on DC01 both read `EE:57:0F:…:9E:19`, proving the file was the genuine CA certificate and hadn't been altered on the way.



CLIENT01 (Tickets 1001-1010 complete) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
zach@helpdesk01: ~
Windows IP Configuration
Successfully flushed the DNS Resolver Cache.
PS C:\Users\ppatel> scp lab-root-ca.crt zach@helpdesk01.lab.local:~/
zach@helpdesk01.lab.local's password:
lab-root-ca.crt 100% 1250 203.5KB/s 00:00
PS C:\Users\ppatel> ssh zach@helpdesk01.lab.local
zach@helpdesk01.lab.local's password:
Welcome to Ubuntu 26.04.1 LTS (GNU/Linux 7.0.0-38-generic x86_64)
* Documentation: https://docs.ubuntu.com
* Management: https://landscape.canonical.com
* Support: https://ubuntu.com/pro
System information as of Fri Oct 23 01:40:28 PM UTC 2026
System load: 0.1
Usage of /: 50.2% of 11.21GB
Memory usage: 23%
Swap usage: 0%
Processes: 124
Users logged in: 1
IPv4 address for enp0s3: 10.0.2.15
IPv6 address for enp0s3: fd17:625c:f037:2:a00:27ff:feb4:ee7b
* Canonical Workshop gives developers fast, composable, reproducible, and
secure developer environments that are perfect for agentic workflows.
https://ubuntu.com/workshop
Expanded Security Maintenance for Applications is not enabled.
7 updates can be applied immediately.
To see these additional updates run: apt list --upgradable
Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status
Last login: Wed Oct 21 11:44:47 2026 from 192.168.10.20
zach@helpdesk01:~$ openssl x509 -in ~/lab-root-ca.crt -noout -subject -fingerprint -sha1
subject=DC=local, DC=lab, CN=lab-DC01-CA
sha1 Fingerprint=EE:57:0F:E8:10:2C:31:D6:BB:D4:14:E5:8E:F2:5F:19:84:AF:9E:19
zach@helpdesk01:~$
ENG US
9:41 am 23/10/2026
Right Ctrl



Copying it into `/usr/local/share/ca-certificates/` and running `update-ca-certificates` added it to Ubuntu's trusted list (`1 added`).




The same `ldapsearch` with `-ZZ` (StartTLS, required) then logged in as svc-osticket and found Jane Smith: `result: 0 Success`.




Plugin settings, and the freeze on save

Every attempt to save the plugin's settings froze HELPDESK01 for minutes at a time. The console showed both virtual CPUs stalled, one of them inside Apache. Because the whole VM froze, nothing reached Apache's error log.



I tested each link in the chain separately. `nslookup -type=SRV _ldap._tcp.lab.local` found DC01, and `nc -zv dc01.lab.local 389` reached its LDAP port, so DNS and the network were fine.




That left osTicket's side, which hid two separate problems:

1. DC01 refused plain LDAP logins. That was fixed by the CA and TLS above.
2. The save still froze with TLS working. With **LDAP servers** left blank, the plugin finds the domain controller itself through an old bundled DNS library, rather than Ubuntu's normal lookup. On PHP 8.4 that code spun the CPU. Naming `dc01.lab.local` in **LDAP servers** skips it, and the save then succeeded instantly.

Neither fix alone would have worked. Testing with `nc`, `ldapsearch` and one changed setting at a time is what separated them.

osTicket identifies portal users by email, and my users had none. Setting one for every employee was a job for PowerShell (eight users, one pattern):


```
        Get-ADUser -Filter * -SearchBase "OU=Users,OU=Company,DC=lab,DC=local" | ForEach-Obj
ect { Set-ADUser $_ -EmailAddress "$($_.SamAccountName)@lab.local" }
```




Alex Lee isn't in the list: his disabled account sits in Company\Disabled Users, outside the search, which is correct for a former employee. I also added the email address to the onboarding script, so new starters get one automatically.


The final settings:

Setting	Value	Why
Default Domain	`lab.local`	Lets people sign in as `jsmith` rather than `jsmith@lab.local`
LDAP servers	`dc01.lab.local`	Named directly; auto-discovery froze the VM
Use TLS	On	StartTLS on port 389; DC01 refuses unencrypted, unsigned logins
Search User	`svc-osticket@lab.local`	The read-only service account
Search Base	`OU=Users,OU=Company,DC=lab,DC=local`	Only employees can sign in. Admin and service accounts sit outside it, and searching below the domain root avoids AD's referrals to its other partitions
LDAP Schema	Microsoft Active Directory	AD's layout for names and email
Staff / Client authentication	Both on	IT staff and employees both use domain logins; local osTicket accounts still work as a fallback






osTicket has two switches, one per plugin and one per instance. The plugin itself also had to be set to **Enabled**.




Ticket #239263: Jane needs the Sales folder


The first real ticket went through the whole access lifecycle in 50 minutes: request, approval, read-only grant, verification, revocation, verification again, then resolved. Every decision is recorded in the ticket.

Request. Jane (HR) signed in to the portal as `jsmith` with her domain password. osTicket filled in her name and `jsmith@lab.local` from AD; nobody created an osTicket account for her. She asked for access to the Sales shared folder for a payroll report.




Triage. I claimed the ticket so it had a named owner, then recorded my reasoning in an **internal note**, which staff can see and Jane can't. Sales data belongs to its **data owner**, the Sales Manager Kevin Mills. Access isn't granted just because someone asks, and `FS-Sales-Modify` would let her edit and delete files when she likely only needs to read. I replied asking her to confirm the scope. The Default SLA set a due date of 27 Oct.



CLIENT01 (Tickets 1001-1010 complete) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Ticket #239263
Not secure helpdesk01.lab.local/scp/tickets.php?id=2#note
Open My Tickets Closed Search New Ticket
Ticket #239263: Internal note posted successfully
Ticket #239263
Need access to the Sales shared folder
Status: Open
Priority: Normal
Department: Maintenance
Create Date: 10/23/26 10:12 AM
User: Jane Smith (1) (Manage Collaborators)
Email: jsmith@lab.local
Source: Web (192.168.10.20)
Assigned To: Zachry Ramkissoon
SLA Plan: Default SLA
Due Date: 10/27/26 10:12 AM
Help Topic: Report a Problem
Last Message: 10/23/26 10:12 AM
Last Response:
Ticket Thread (2)
Tasks
Jane Smith posted 10/23/26 10:12 AM
Hi, I'm working on a payroll report with the Sales team and need to open files in the Sales shared folder (S: drive). Can I get access? Thanks, Jane.
Created by Jane Smith 10/23/26 10:12 AM
Zachry Ramkissoon claimed this 10/23/26 10:13 AM
Zachry Ramkissoon posted 10/23/26 10:15 AM
Access to \\DC01\Sales requires data-owner approval. Requested approval from Kevin Mills (Sales Manager). Jane only needs read access for a payroll report - will confirm scope before granting.
Post Reply
Post Internal Note
ENG US
10:15 am 23/10/2026
Right Ctrl




Approval. Jane confirmed view-only. Kevin's approval (simulated) went into an internal note with its scope and end condition, so the ticket proves why HR could see Sales files.





Grant. I created **FS-Sales-Read**, a domain local security group with only Read & execute, List folder contents and Read on `C:\Shares\Sales`, and added Jane to it. Strict AGDLP would nest a global group in between. For one approved, temporary exception, adding the user directly is an accepted shortcut; a second HR reader would justify the global group.


DC01 (Before AD CS) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Server Manager
Server Manager ▸ Dashboard
Manage Tools View Help
Dashboard
Local Server
WELCOME TO SERVER MANAGER
Sales
Local Disk (C:) › Shares › Sales
Search Sales
New
Downloads
Documents
Pictures
Music
Videos
Screenshots
Local Disk (
Scripts
This PC
Local Disk
CD Drive (
CD Drive (D
1 item State: Shared
Sales Properties
General Sharing Security Previous Versions Customize
Object name: C:\Shares\Sales
Group or user names:
CREATOR OWNER
SYSTEM
FS-Sales-Modify (LAB\FS-Sales-Modify)
FS-Sales-Read (LAB\FS-Sales-Read)
Administrators (LAB\Administrators)
To change permissions, click Edit.
Edit...
Permissions for FS-Sales-Read Allow Deny
Full control
Modify
Read & execute ✓
List folder contents ✓
Read ✓
Write
For special permissions or advanced settings, click Advanced.
Advanced
OK Cancel Apply
View
Details
Type
Size
Text Document
0 KB
DNS 1
Manageability
Events
Services
File and Storage Services 1
Manageability
Events
Services
Search
10:23 AM
10/23/2026
Right Ctrl





Verify. Group membership is fixed into the access token at sign-in, so Jane signed in fresh. She could open `\\DC01\Sales` and read `proposal.txt`, and creating a file failed with "Destination Folder Access Denied". She has no S: drive, because the mapping GPO applies only to the Sales OU.


CLIENT01 (Tickets 1001-1010 complete) [Running] - Oracle VirtualBox
File
Machine
View
Input
Devices
Help
Recycle Bin
Learn about this picture
Microsoft Edge
Sales
Network
DC01
Sales
Search Sales
New
Sort
View
Details
Home
Gallery
OneDrive
Desktop
Downloads
Documents
Pictures
Music
Videos
This PC
CD Drive (D:) Vir
Name
Date modified
Type
Size
proposal
02/10/2026 7:01 pm
Text Document
0 KB
1 item
Windows 11 Enterprise Evaluation
Windows License is expired
Build 26100.ge_release.240331-1435
ENG
US
10:38 am
23/10/2026
Right Ctrl




Follow-up task. The removal went into an osTicket **task** on the ticket, assigned to me with a one-week due date. osTicket then refused to resolve the ticket while the task was open: the job isn't done until access is removed.



CLIENT01 (Tickets 1001-1010 complete) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Ticket #239263
Not secure helpdesk01.lab.local/scp/tickets.php?id=2
osTicket
Welcome, Zachry. | Admin Panel | Profile | Log Out
Dashboard Users Tasks Tickets Knowledgebase
Open My Tickets Closed Search New Ticket
Ticket #239263
Need access to the Sales shared folder
Status: Open
Priority: Normal
Department: Maintenance
Create Date: 10/23/26 10:12 AM
User: Jane Smith (1) (Manage Collaborators)
Email: jsmith@lab.local
Source: Web (192.168.10.20)
Assigned To: Zachry Ramkissoon
SLA Plan: Default SLA
Due Date: 10/27/26 10:12 AM
Help Topic: Report a Problem
Last Message: 10/23/26 10:17 AM
Last Response: 10/23/26 10:15 AM
Ticket Thread (5) Tasks (1)
Showing 1 - 1 of 1 task
Add New Task Options
Number Date Status Title Department Assignee
1 10/23/26 10:44 AM Open Remove jsmith from FS-Sales-Read Support Zachry Ramkissoon
Copyright © 2006-2026 Lab Help Desk All Rights Reserved.
ENG US 10:44 am 23/10/2026
Right Ctrl




Revoke and verify. When Jane said the report was finished, I removed her from FS-Sales-Read. Her already-open session could have kept access until sign-out, because her old token still listed the group. For an urgent removal, such as a dismissal, I'd also force a sign-off. After a fresh sign-in, Windows refused `\\DC01\Sales`.



Close. I closed the task with the evidence, replied to Jane and set the ticket to **Resolved**. Resolved means fixed; it reopens automatically if she replies. One snag along the way: a reply left unsent for 12 minutes lost osTicket's **ticket lock**, which stops two technicians answering at once. Refreshing the page took a new lock, and the auto-saved draft survived.


CLIENT01 (Tickets 1001-1010 complete) [Running] - Oracle VirtualBox
File Machine View Input Devices Help
Ticket #239263
Not secure helpdesk01.lab.local/scp/tickets.php?id=2#reply
Ticket #239263
Need access to the Sales shared folder
Status: Open
Priority: Normal
Department: Maintenance
Create Date: 10/23/26 10:12 AM
User: Jane Smith (1) (Manage Collaborators)
Email: jsmith@lab.local
Source: Web (192.168.10.20)
Assigned To: Zachry Ramkissoon
SLA Plan: Default SLA
Due Date: 10/27/26 10:12 AM
Help Topic: Report a Problem
Last Message: 10/23/26 10:58 AM
Last Response: 10/23/26 10:57 AM
Ticket Thread (7)
Tasks (1)
All Tasks (1) / Task #1
View Task
Actions
Remove jsmith from FS-Sales-Read
Zachry Ramkissoon posted 10/23/26 10:44 AM
Temporary read access approved by K, Mills for the payroll report. Remove once the report is complete.
Created by Zachry Ramkissoon 10/23/26 10:44 AM
Zachry Ramkissoon claimed this 10/23/26 10:44 AM
Zachry Ramkissoon posted 10/23/26 11:01 AM
Removed jsmith from FS-Sales-Read. Verified access denied.
Closed by Zachry Ramkissoon 10/23/26 11:01 AM
Update posted successfully
Search
ENG US
11:01 am 23/10/2026
Right Ctrl



All three VMs were then snapshotted as "Phase 4 complete - AD login + CA".

Key concepts and next steps

The biggest lesson from Part 1: AD depends on DNS, so most join and login problems start there.

Concepts put into practice

- **Domain controller:** stores the directory and authenticates logins. It also runs DNS, so clients must use its IP as their DNS server.
- **OUs vs groups:** an account lives in exactly one OU, used for organizing, Group Policy and delegation. It can belong to many groups, used for granting access.
- **Rename before promoting:** renaming a domain controller after promotion is disruptive, so DC01 was named first.
- **Default containers:** new computers land in the built-in Computers container, where GPOs cannot be linked, so they're moved into a managed OU.
- **Snapshots:** taken at each milestone so the lab can be rolled back in seconds.
- **LDAP:** the protocol applications use to query a directory. AD is the directory; LDAP is how osTicket asks it who someone is and whether their password is right.

- **LDAP signing and StartTLS:** Windows Server 2025 refuses unsigned, unencrypted LDAP logins. StartTLS starts on port 389 and upgrades to TLS before any password is sent; LDAPS on port 636 is encrypted from the first byte.
- **Certificate authority and trust:** a CA signs certificates; a machine accepts a server's certificate only if it trusts the CA that signed it. Domain members trust an Enterprise CA automatically; a non-domain Linux server has to be told, after checking the fingerprint.
- **Service accounts:** a dedicated, least-privilege account for an application to log in with, never a person's or an admin's account.
- **Access lifecycle:** access to another team's data needs the data owner's approval, the smallest permission that does the job, a recorded end date, and verification both when it's granted and when it's removed.

Roadmap

The lab grows from on-prem Active Directory into a small, connected IT environment: a Linux server running a real ticketing system, hybrid cloud identity, and an AI help desk assistant. Each phase builds on the AD foundation rather than standing alone.

Phase	Focus	How it ties into the lab	Status
1	Core AD build	Domain controller, `lab.local`, OUs, users, groups, domain-joined client	Done
2	Help desk tickets #1001–#1009	Password resets, onboarding and offboarding, lockout policy, file shares, Group Policy, DNS, PowerShell	Done
3	Admin account separation (#1010)	Named `adm-` admin accounts; built-in Administrator kept for emergencies	Done
4	Linux server and osTicket	Ubuntu Server VM hosting osTicket; staff and employees sign in with AD accounts over LDAP/TLS; first ticket worked end to end	Done
4b	Hardening and clean-up	HTTPS for osTicket with a certificate from lab-DC01-CA; an IT Support department replacing the sample ones; CLIENT01's expired evaluation licence	Planned
5	Remaining AD work, ticketed in osTicket	Delegation, DHCP, Group Policy troubleshooting, security filtering, AD Recycle Bin, second DC and replication, FSMO roles, backup and restore	Planned
6	Hybrid identity with Microsoft Entra ID	Lab users synced to the cloud for on-prem and cloud sign-in	Planned
7	AI help desk assistant	Agent triages osTicket tickets and proposes fixes; least-privilege delegated account, human approval, full logging	Planned

The AI assistant comes last on purpose: it depends on the ticketing system's API, delegated permissions from phase 5, and PowerShell automation.