# Brain Tumor Detection with MRI Images

2022 International Conference on Computational Intelligence and Sustainable Engineering Solutions (CISES) | 978-1-6654-8004-8/22/$31.00 ©2022 IEEE | DOI: 10.1109/CISES54857.2022.9844387

1st Harsh Yadav
*Computer Science & Engineering*
*GL Bajaj Institute of Technology & Management*
Greater Noida, India
1998harshyadav@gmail.com

2nd Shivam Singh
*Computer Science & Engineering*
*GL Bajaj Institute of Technology & Management*
Greater Noida, India
singhshivamsingh52@gmail.com

3rd Krishna Kant Mishra
*Computer Science & Engineering*
*GL Bajaj Institute of Technology & Management*
Greater Noida, India
krishkmishra005@gmail.com

4th Sarthak Srivastava
*Computer Science & Engineering*
*GL Bajaj Institute of Technology & Management*
Greater Noida, India
ssrivastav947@gmail.com

5th Mahaveer Singh Naruka
*Computer Science & Engineering*
*GL Bajaj Institute of Technology & Management*
*Greater Noida, India*
*ms.naruka@glbitm.ac.in*

6th Satya Prakash Yadav
*Computer Science & Engineering*
*GL Bajaj Institute of Technology & Management*
*Greater Noida, India*
*satya.yadav_cse@glbitm.ac.in*

***Abstract*—Disorder detection using medical imaging has become a prominent topic in a number of medical diagnostic techniques recently. The importance of automated MRI tumor analysis is that it can provide information about the identification of tumor to even general public. Errors in detection by human scrutiny have been long there for magnetic resonance mind snap photographs. Also, human scrutiny technique is not practical for vast variety of data. As a result, to avoid deaths, reliable and automatic classification techniques are required. Development of automated tumor diagnosis algorithms is required to save time while maintaining high accuracy. MRI brain tumor detection is difficult due to the complexity and variety of malignancies. The authors of this study present a method for detecting malignancies in brain MRI pictures using deep learning approaches, which can save a lot of time and reduce inconsistency for a large number of MRI images. This will aid in precise and cost-effective tumor diagnosis of brain.**

***Keywords—detection, brain tumor, deep learning, conventional techniques, hybrid techniques, transfer learning***

## I. INTRODUCTION

Every year, more than 190,000 people worldwide are diagnosed with primary or metastatic (secondary) brain tumors. Although the causes of brain tumors are unknown, there are some common patterns among those who develop them. It can affect anyone, whether they are a toddler or an adult. The creation of a tumor is caused by the uneven proliferation of cells that multiply uncontrollably. Mind cells that form around the brain's membranes (meninges), glands, or other organs form tumors. A device has been developed that correctly classifies new MRI scans of the brain into tumor-containing and tumor-free images. This must be carried out without the use of humans. This study should preprocess a variety of photo features, such as color, hobby area, image document extension, and comparison level, so that different types of classifiers can be observed. The magnetic resonance images of the human brain are manifested in the parent figure 1.





Fig. 1 exhibits Magnetic Resonance Images of the human brain

The pre-processing of MRI images is the first phase in image analysis, which entails using image enhancement and noise reduction procedures to improve the MRI image before employing morphological strategies to locate the tumor in the image. The morphological procedures are mostly based on the assumption that the tumor's length and shape are obvious. The analysis of tumor detection is viewed as an image segmentation problem, with the goal of determining whether the image contains a tumor. Various machine learning algorithms and associative learning procedures are used to solve this problem. The two types of brain tumors are benign (normal) and malignant (cancerous) (abnormal). There are many ways through which tumors can be detected i.e., magnetic resonance imaging, computed tomography, and ultrasound. The use of magnetic resonance imaging (MRI) in tumor evaluation, diagnosis, and treatment planning is critical. Before beginning any treatment, it is necessary to eradicate the tumor to protect healthy tissues while destroying and removing malignant cells. Brain tumor segmentation entails identifying, delineating, and separating active cells, edema, and necrotic cores from tissues such as GM, CSF, and WM. There are roughly 130 different varieties of brain tumors, depending on the cell type that the tumor is made of, where it is located inside the brain, and how quickly it grows and expands. However, the general classification divides brain tumors into two categories: primary and secondary. The classification of brain tumors is manifested in Fig 2.



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.





Fig. 2 depicts the classification of brain tumor

It's not always the case that a benign tumor is cancerous or malignant. It may not infiltrate nearby tissue or expand to different parts of the body in the same way that other malignancies do. Although benign tumor aren't dangerous, they can be if they press against vital organs like blood vessels or nerves. The cells in these tumor aren't currently cancerous, but they have the potential to become so. Premalignant tissue is detected using appropriate clinical and laboratory testing while it is still in the premalignant stage. A variety of treatments are available to remove or kill the tissue, preventing cancer from developing. Malignant tumor are cancerous tumor. They appear when cells expand out of control. The disease will become dangerous if the cells continue to develop and unfold. Malignant tumor grow quickly and expand to different parts of the body through a process known as metastasis. Tumor are classified according to how normal or aberrant the cells seem. This measurement will be used by the doctor to assist plan your therapy. The tumor's grade also reflects how quickly the tumor is likely to grow and spread. Grade 1 cells have a normal appearance and expand gradually. You might decide to stay for a long time. Grade 2 cells have an odd appearance and develop slowly. The tumor could spread to neighbouring tissue and return, possibly in a more life-threatening form. Grade 3 cells have an irregular appearance and are actively expanding into adjacent brain tissue. These tumor have a tendency to recur. Grade 4 cells have the most unusual appearance and proliferate and spread swiftly.

Table 1: Advantages, disadvantages and applications of Brain Tumor Detection

| Advantages | Disadvantages | Applications |
|---|---|---|
| Early detection of a brain tumor can boost the patient's chances of recovery after treatment. | High computational complexity. | Prediction of brain tumors in patients can be done very fast. |
| Brain tumor detection using MRI offers detailed explanation about human tissue, which aids in the diagnosis of brain tumors. | It may give more false positive predictions than expected while classifying enhancing tumors. | Higher accuracy helps in providing the treatment to the patients. |
| The digital image can be made available in any desired format which helps to improve images for brain tumor interpretation. | A brain tumor increases fast in size. As a result, determining the prognosis of a tumor at an early stage is a difficult task. | Helps the radiologist in making quick decisions. |
| Gaining a larger dataset with high-resolution photos taken immediately from the MRI scanner can result in much improved accuracy. | Because of the tumor's appearance, size, form, and structure, it's still difficult to discover it. | |

.

In scientific technology, a brain tumor is one of the most deadly disease to treat. An efficient and environmentally friendly radiologist analysis improves the accuracy and efficacy, saving time and increasing the survival rate of patients.

## II. LITERATURE SURVEY

Several research papers Inside the brain tumor detection field were started and completed over the previous two decades. Several medical journals have published articles on the subject. In this work a few are evaluated for their outstanding efforts.

The researchers in [1] conducted an in-depth examination of state-of-the-art CAD structures utilized for brain tumor detection in the context of contemporary internet/cloud-based technology. They conducted a thorough investigation into the capabilities of the photograph used and the distinctive selection criteria employed for tumor detection. They have depicted how many photo datasets are utilized to train or validate the detecting device.

Author [2] proposed a technique for detecting and identifying and categorizing brain tumors at the picture and lesion stages. Preprocessing, capability extraction, and class extraction are just a few of the processes in the proposed method. They used specialized strategies for segmenting candidate lesions in the preprocessing stage. Then, for each candidate lesion, texture, form and depth-based functions are applied. Because of the textural mix, form, and the severity of a lesion offers stronger information about discrimination, texture functions are proper descriptors of the tumors alongside form and depth capabilities. Finally, some assessments are done based on the chosen capability set in order to select a bigger acceptable classification technique. As a result, a geometrical circle of relatives help vector system (SVM) with unique move validations is used. Linear, Gaussian, and Cubic kernel features are investigated in three SVM variations.

The authors of [3] wanted to use CNN networks and CNN layers to categorize mental tumor snapshots. The Resnet50 framework is employed as the foundation, and a hybrid version is also available. The five levels of Resnet50 architecture which were present in last were deleted, and a total of ten new strata had been added to their region. The hybrid version's outcomes improved with the addition of ten layers to the final component, outperforming the traditional architecture. The improved hybrid model has a precision charge of 97.01 percent.

In [4] a hybrid technique was used On MRI images of the brain to find and diagnose the tumor, and the BRATS database was used in this study. Using SVM techniques and supervised hybrid CNN, the technology in use is designed to classify brain images. The first steps in the preprocessing



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.

method were to normalize the images that have been entered, and then huge capabilities were extracted using the maximally solid extremal regions (MSER) tool, creating a photo from a pre-processed image. approach, and then segmented the data using a series of completely segmentation rules based on a threshold. To classify mental MRI images, the categorized segmented functions are supplied as input to hybrid CNN and SVM algorithms. The end result demonstrates that the hybrid model is the most successfully classified with PPV and the least effective with FPV, with an average of 98.4959 percent effectively classified, SVM received 72.5536 percent one by one, whereas CNN received 97.4394 percent. With only a quick study, it's clear that the proposed hybrid version offers superior efficiency and type creation procedures. The CNN with SVM and other optimization techniques performed better in destiny studies (bioinspired algorithms) could be used to illustrate the general evolution for better decision making. As a result of the tumor's discovery, the length and particular location of the tumor are also taken into account inside the case.

Author [5] Segmentation divides a picture into components of regions or items, as proposed for tumor identification. In order to look through the picture pleasantly as well as classify the content material picture precisely, it must first section the item from the historical past. Area detection is a fundamental device for picture segmentation in this architecture. In this study, the authors attempted to examine the overall performance of the most often used component detection algorithms for picture segmentation, as well as the evaluation of such techniques through a test.

Authors in [6] suggested a desegregation wave entropy strategy in order to categorize the Brain MRI based entirely on the main Spider net plots and probabilistic neural network. The function extraction was carried out using wavelet redesign, and the entropy cost, as well as the spider internet plot vicinity computation, were calculated. The entropy highly worth type of probabilistic neural network was calculated with the assistance of entropy. The probabilistic neural community offers a wide range of pattern type resolutions.

Table 2: Contrasting many approaches (with their merits and demerits)

| **Approach** | **Zone** | **Merits** | **Demerits** | **Measuring Parameters** |
|---|---|---|---|---|
| Feed Forward Neural Network | DL based | The handling and processing of non-linear data can be done easily with a neural network. | Loss of neighborhood information. | Sensitivity-0.9810 Specificity-0.9810 Recall-0.9810 Accuracy-0.9139 |
| Fuzzy C-means algorithm | ML based | Unlike k-means, where information factors must only belong to one cluster center, facts points are assigned a club to each cluster center, allowing facts points to belong to several cluster centers. | The number of clusters is specified ahead of time. | Sensitivity-0.9241 Specificity-0.9241 Recall-0.9241 Accuracy-0.9017 |
| FKM-SOM algorithm | Hybrid Technique | It offers an easy-to-understand set of rules, is simple to implement, and generates accurate and intuitive outcomes. | Slow education and difficult training in the face of rapidly changing data | Sensitivity-0.6939 Specificity-0.6939 Recall-0.6939 Accuracy-0.9790 |

Table 2 also indicates the advantages, disadvantages and sensitivity of numerous approaches for detecting brain tumors in various fields. [7] published a work in which they employed a combination of wavelet statistical functions and co-prevalence wavelet texture characteristic acquired from two stage different riffle redecorates for the classification of odd mental issues into benign and malignant. The division of the hobby area, separate ripple disintegration, characteristic abstraction, feature choice, enterprise, and assessment are the four stages of the desired system. The assist vector tool was utilized for tumor segmentation. To obtain the capabilities of the tumor website derived from second level distinct ripple redesign, a combination of WST and WCT are applied. Using a genetic algorithm, the exquisite texture possibilities were selected from a pool of well-mined options.

Table 3: Recent contributions of researchers in brain tumor detection

| **Author/ Year** | **Work** | **Modality** | **Technique** | **Research Contribution** |
|---|---|---|---|---|
| (LO Hall et. al. (1992)) | Tumor Detection | Brain | 1) A technique based on fuzzy C-means that is unsupervised<br><br>2)Feedforward Cascade Correlation With Supervision | On a series of photos, both approaches were evaluated and compared.<br><br>In comparison to the supervised FFCC, the unsupervised FCM confirmed better results. |



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.

| | | | | |
|---|---|---|---|---|
| (J. Zhou et. al. (2005)) | Tumor Detection | Brain | One Class Support Vector Machine(SVM) | It outperformed the fuzzy clustering strategy in terms of tumor segmentation results. |
| (M. Schmidt et. al. (2005)) | Tumor Detection | Brain | Alignment based feature encoding | For picture segmentation, this technique assesses four different types of AB functions. Device learning is used to integrate these AB features. |
| (A. Kharrat et. al. (2009)) | Tumor Detection | Brain | Fuzzy C-means clustering technique with intelligent optimization tools:<br>1)GA<br>2PSO | PSO with Fuzzy C-way is a proposed algorithm. takes longer than GA and Fuzzy C-approach. In addition, the PSO with Fuzzy C-approach has a better level of accuracy. |
| (Gopal et. al. (2010)) | Tumor Detection | Brain | Adaptive Threshold approach and Canny Edge detection method | Each of the four rates is compared to the adaptive threshold and Canny area.<br>1) A healthy mind gets misdiagnosed as a tumor-ridden mind.<br>2) A healthy mind gets misdiagnosed as a brain with a tumor.<br>3) A benign tumor is mistakenly diagnosed as cancerous.<br>4) A benign tumor is mistakenly diagnosed as malignant. |
| (Ahmed et. al. (2010)) | Tumor Detection | Brain | SVM | This method extracts capabilities using the spatial grey degree dependence method (SGLDM) and a hybrid strategy that identifies the cause as normal, benign, or malignant tumor. |
| (Dilpreet Kaur et. al. (2014)) | Tumor Detection | Brain | K-means, Fuzzy C means and histogram thresholding | The three tactics are compared and contrasted. And the outcomes are stated since combining the three strategies improves overall performance. |
| (Sandabad Sara et. al. (2015)) | Tumor Detection | Brain | Expectation Maximization | This includes both the study and the histogram analysis. With a simulation period of about 5 to 8 seconds, the proposed method is said to be rapid, straightforward, and reasonably simple to programme. |

Table 3 indicates the contributions done by numerous researchers on Brain Tumor Detection using different techniques based on the approaches such as K-means, Support Vector Machine, Fuzzy C-means Expectation Maximization and histogram thresholding.

## III. TECHNIQUES/TOOLS FOR BRAIN TUMOR DETECTION

To extract the required region, preprocessing is essential. Non-brain tissue removal is accomplished using the 2D brain extraction algorithm. Due to defects in the radio frequency coil known as intensity inhomogeneity, the bias field is a major issue in MRI. Linear, fixed, nonlinear, pixel-based and multi-scale preprocessing methods are employed in many different ways. The thresholding technique is a simple and effective way to partition the required objects, however choosing an optimal threshold in low-assessment snap images is difficult. The selection of threshold values is mostly dependent on histogram examination. For segmentation, the global thresholding method is a comfortable alternative. The most appropriate fee threshold can be calculated. The threshold charge can't be calculated from a complete picture or the brink's single price does not provide accurate segmentation results. As much as possible. The thresholding approach is used in some cases. In Region-Based, the photograph pixels from discontinuous locations are assessed using surrounding pixels, which is blended with equivalent qualities formed on predefined resemblance standards in RG procedures. Due to the partial quantity effect, location development may fail to deliver higher precision. To exaggerate MRGM is desirable as a result of this effect. The localities are also possible to grow using BA techniques.

In the Watershed method, ASMR photographs have a higher supermolecule fluid potency, watershed techniques are used to investigate those photograph's strength. The watershed approach leads to over segmentation due to noise. The results of accurate segmentation can be obtained using a mix of methods. Watershed transform using statistical techniques merged. Topological algorithms are used in some watershed algorithms like photograph foresting remodel (IFT) watershed, as well as a watershed based on markers. The entire review of the literature on brain tumors. There is room for improvement, according to detection. As a brain tumor can appear in a variety of shapes and sizes. The basic goal of any technique is to use image records to extract the desired



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.

features, which may subsequently be used by a device to provide the appropriate diagnosis. Upgrades to segmentation techniques are required. The different techniques used to detect brain tumors in MRI images is shown in Fig. 4.





Fig. 4 shows the different Brain Tumor Detection techniques

*A. Machine Learning Method*

To identify this type of problem, AI computations typically use hand-made highlights (which are known as pre-characterized highlights). The most crucial stage in this type of division is the removal of the urgent data that was extracted from the info picture using an element extraction technique. Following this, a discriminative model is used to distinguish cancer from healthy tissues. In modified AI techniques, hand-made features are typically combined with a few classifiers, such as irregular woods, SVM (Support Vector Machine), and fluffy grouping [10]. Other relevant data should be divided according to the planned methods and computations for extracting the elements, which takes time and involves Features, edge-related nuances. Additionally, these approaches might be used when the boundaries between solid tissues and malignancies are unclear or ambiguous.

*B. Transfer Learning Method*

Due to the asymmetrical nature of the lesions, the region's flexibility, and the unknown boundaries, detecting brain tumors manually is difficult. As a result, it has been suggested that a transfer learning model can be used. Transfer learning is a system learning technique in which a model developed for one project is repurposed for a different one; in other words, a model developed for one paper is claimed as the starting point for a model for a different project. Switch learning is an optimization that allows for quick advancement and superior performance while modelling the second task. The model is trained on a specified dataset that comprises “Yes” and “No” brain tumor classifications, and the learned version may be able to predict the elegance to which the input mind MRI image belongs. This kind of analysis eliminates the problems that exist in the current manual machine, such as the time factor and the risk of radiation exposure to the patient's health. The learning of these new tasks is based on the tasks that are previously learned, as shown in Fig. 5.





Fig. 5 depicts the methodology of transfer learning

To train our model, transfer learning is tried to deduce the needed output from just one or a few training samples. This is especially useful in real-world scenarios where it isn't feasible to have classified records for each and every possible elegance (if it's a category venture) and when new classes can be given on a frequent basis. Our strategy is to develop a powerful computer-based method for detecting brain cancers. Deep learning techniques have been employed and switch learning to educate our version and classifiers, as well as convolution neural networks, to categorize MRI images into training brain tumor and without-brain tumor categories, thereby automating the detection system and allowing for speedier prognosis [13]. This assumption, however, may not hold true in many real-world programs. For example, there may be a caring endeavor in one area of interest however just be sufficient data on tutoring in another, where the last data may be in an extraordinary component region or follow an exceptional data dissemination. When utilized appropriately, ability exchanging in these circumstances can fundamentally further develop dominance execution by killing the requirement for difficult information naming exercises. Lately, a shiny new system for learning called move learning has arisen to resolve this issue. Brain organizations might work with undeniably less data in light of the fact that to move learning. A model can successfully apply the knowledge they learned from a previous challenge to their current one through transfer learning. The notion is that the two assignments are not wholly independent from one another, therefore some community factors discovered by version during its extensive education have been utilised while avoiding the need for us to acquire this education. It has been shown that transfer learning can shorten training time while increasing model accuracy. less statistics, a lot less time, and increased precision. The three types of transfer mastery are inductive transfer learning, transudative transfer learning, and unsupervised transfer learning. The settings were the main focus of the majority of the earlier pieces. Additionally, depending on what is intended to be conveyed in mastery, each method for switching can be classified into 4 contexts.

These strategies include the relational knowledge switch approach, the function representation transfer method, the parameter switch approach, and the instance switch methodology. Pre-education is a strategy in which smaller networks converge and are then utilized as initializations for bigger, deeper networks. While providing logical experience,



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.

pre-schooling is a time-consuming and arduous task that necessitates the teaching of an entire network before it can act as a foundation for a larger community.

*C. Hybrid Method*

The Proposed (CNN-SVM) hybrid model is used to combine. The general design of CNN including layers (Pooling layer, flatten layer, Convolution layer, and fully connected layer) is delineated.

*Hybrid CNN-SVM Model:* The shape of the blended CNN-SVM version is designed by replacing the final layer of CNN with the SVM model.; As a result, the output of CNN's absolutely related layer has been confirmed to be correct technique for SVM load to improve development by the type. The main reason for combining the advantages is to save time. The advantage of CNN vs SVM is that CNN has faster access and should include the extraction techniques that have been hampered by hidden layers. Capabilities are expanding in addition to precision and universal performance. It has always been crucial in many ways. SVM, on the other hand, comes with Its extraction skills that are unique, and it is quite efficient and the speed with which different algorithms operate. Having this combination can be beneficial. MRI images Figure three depicts the hybrid version's form. CNN and SVM are two types of algorithms. In this way, the CNN version employs a fluctuate-based approach of convolution and subsampling, as well as convolution and subsampling at the same time a layer based on a 28-28 function map with five-five convolution, and in a similar manner. That by putting this trait to work, you can speed up the process. Information extraction that is entirely dependent on the teach and check process. The SVM version, on the other hand, uses the result of a wholly related as an input layer. The function vectors, types as well as the input are all trained separately.

## IV. PROPOSED WORK

This deep learning method is used to organize the data into elements of different objectives and to verify its exactness for every point. Using diverse classifications from this useful resource, only a few investigations were transmitted. Deep learning, often known as neural artificial networks, is a type of AI that manages calculations prompted by brain anatomy and capacity. The large realization, which is used to clarify the improvement of several new technologies in an ANN to handle larger calculation of information and enhance its perfection of data categorization, is what distinguishes it from neural systems. The Convolution Neural Network (CNN) is a unique type of neural system for getting this information into sound structures, image, and text that has proven to be effective. To demonstrate their network, the expression "Convolution Neural Network" built up a quantifiable activity called convolution. The convolution operation is a dot product among the procedures of the input matrices.

A CNN is an example of an artificial neural network (ANN). This sort of network is divided in three layers: an output layer and an input layer, a hidden layer. The output of one strata is typically owned as an input for the following layer in this type of network. For photograph analysis, the CNN model is employed, which has four degrees: convolution layer, fully connected layer and pooling layer, flatten layer, but a pattern look with distinct architectural styles. Features, you'll see that there's a wide range of layers, in addition to layers, which could be unique. The convolution layer is the first strata in the CNN model. The prop-layer is used to decode the characteristic from an image. The possessions of every pixel, as well as the relationship between neighboring pixels, will be extracted with the help of a few math operations. It's a supervised machine learning algorithm that takes into account both linear and non-linear data and also applied to any category or regression problem. The SVM classifier is being used in this study. To improve the adaptability and efficiency of the date duration to turn the essentials, the remaining stratum of the absolutely linked strata of CNN was added.

Our proposed method, composed of various phases is shown in figure 6:





Fig. 6 shows the methodology of the proposed work

This provides built-in features to do fact augmentation, which is the process of adding more training statistics by applying a number of operations like rotation, cropping, resizing, and so on. To each individual photograph in the batch. Image Data Generator has been employed, which augments our photos in real-time, reducing undesirable distortions and improving image functionalities. The main motive of this strategy is to enhance the performance by removing duplicate and irrelevant functions. Convolution neural network runs images through numerous convolutional filters, each of which activates and extracts specific information from the images. Pooling clarifies our output by decreasing the number of parameters that the network must investigate and doing non-linear down sampling. The output of the last pooling layer functions as an input to the entirely related layer at the end of a CNN, and this residue has an activation characteristic called ReLU. The final layer is the prediction layer, which classifies the input into both of the outputs. The dataset has two folders for the purpose of education. The 'dataset' folder contains two sub-folders labeled "Yes" and "No," each containing snap photos of magnetic resonance images of distinct patients. The 'dataset' folder contains 3060 MRI images of a variety of patients with HGG and LGG cases jumbled together. T1, T1C, T2, OT, and FLAIR are the five distinct MRI picture modalities for each affected individual. All of the 'jpg' files are 64x64 pixels in size, resolution, and have been skull



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.

stripped. Every voxel in the ground reality pix is classed as a zero or a non-zero, corresponding to the daily pixel and tumor cell portions, respectively. The images are in the shape of grayscale.jpg files. In this case with our online Kaggle dataset, a zip file was created. It included 1500 MRI scans of healthy people and 1500 MRI images of infected-tumors.

```
Epoch 1/10
150/150 [==============================] - 25s 111ms/step - loss: 0.5422 - accuracy: 0.7267 - val_loss: 0.4937 - val_accuracy: 0.
7733
Epoch 2/10
150/150 [==============================] - 19s 125ms/step - loss: 0.3724 - accuracy: 0.8413 - val_loss: 0.3279 - val_accuracy: 0.
8433
Epoch 3/10
150/150 [==============================] - 19s 127ms/step - loss: 0.2802 - accuracy: 0.8921 - val_loss: 0.2467 - val_accuracy: 0.
8883
Epoch 4/10
150/150 [==============================] - 17s 113ms/step - loss: 0.1988 - accuracy: 0.9287 - val_loss: 0.1631 - val_accuracy: 0.
9417
Epoch 5/10
150/150 [==============================] - 17s 113ms/step - loss: 0.1281 - accuracy: 0.9550 - val_loss: 0.1279 - val_accuracy: 0.
9600
Epoch 6/10
150/150 [==============================] - 17s 113ms/step - loss: 0.0770 - accuracy: 0.9771 - val_loss: 0.1104 - val_accuracy: 0.
9583
Epoch 7/10
150/150 [==============================] - 18s 119ms/step - loss: 0.0537 - accuracy: 0.9817 - val_loss: 0.0692 - val_accuracy: 0.
9817
Epoch 8/10
150/150 [==============================] - 17s 112ms/step - loss: 0.0354 - accuracy: 0.9887 - val_loss: 0.0798 - val_accuracy: 0.
9800
Epoch 9/10
150/150 [==============================] - 16s 109ms/step - loss: 0.0179 - accuracy: 0.9962 - val_loss: 0.1243 - val_accuracy: 0.
9650
Epoch 10/10
150/150 [==============================] - 16s 106ms/step - loss: 0.0264 - accuracy: 0.9908 - val_loss: 0.0897 - val_accuracy: 0.
9783
```

An epoch is a measure of time used in device mastering that indicates how many runs the learning algorithm has done over the entire dataset. Batches are commonly used to organize datasets in institutions (mainly whilst the quantity of records would be very big). When using the time period generation, some people err on the side of caution and test by running one batch through the model as an era. If the batch size is the entire schooling dataset, the range of epochs is a huge number of iterations. For realistic considerations, this is no longer the case. Many models are created using several epochs.

$$i \times b = d \times e \qquad (1)$$

Equation (1) is a common relationship between dataset length (d), number of epochs (e), range of iterations (i), and batch size (b). At its core, TensorFlow is a DL library that focuses on the training of DNNs. Keras is used in its APIs to allow customers to make their own device mastery models. It can assist in loading the statistics necessary to train the model and setting it up using TensorFlow, as well as developing and educating the model. Python is used for this work because it is a free and open-source programming language with a larger library of packages and data sets to choose from. Python packages such as NumPy, Matplotlib, and Pandas are used for mathematical computing. Keras is a TensorFlow and Keras-based neural network API. In this work, OpenCV is employed. It's a library of programming capabilities aimed at real-time computer vision, such as reading and writing photos, modifying photo quality, removing noise with Gaussian Blur, performing binary thresholding on photos, converting the original picture into an array, converting the photo from RGB to grayscale, and so on.

## V. RESULT AND DISCUSSION

Automated tumor analysis in virtual histopathology images is a vast subject within itself and with a wide range of methodologies ranging from traditional functions to cutting-edge procedures. A brain tumor is a misshaped cellular growth that can be cancerous or non-cancerous. The analysis of Brain Tumor Detection Using Deep Learning is shown below:





Fig. 7. Process to select the input image using the file directory for the further prediction of the image





Fig. 8. The selected image will be shown on the screen after which the prediction button will be pressed





Fig. 9. This particular image shown to be tumor infected in nature after the tumor detection process





Fig. 10. Process to take another image from the file directory for the tumor detection process



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.





Fig. 11. This particular image shown to be non-tumor infected in nature after the tumor detection process

The process of selecting and operating the input images to fetch the results about to detect the result whether tumor or not as shown in fig. 7, fig.8. fig. 9, fig.10 and fig. 11 respectively. Numerical data comparisons with different modalities as herewith table 2.

| Models | Recall | Precision | Accuracy | Time (min) | ROC AUC (Score) | F1 (Score) |
|---|---|---|---|---|---|---|
| Inception-V3 | 0.710 | 0.770 | 0.750 | 93.830 | 0.750 | 0.740 |
| ResNet-50 | 0.930 | 0.870 | 0.890 | 151.510 | 0.890 | 0.900 |
| VGG-16 | 1.00 | 0.930 | 0.960 | 114.100 | 0.960 | 0.970 |

The graphs providing the training and validation accuracy of different CNN-architecture models are shown in fig. 12, fig. 13, and fig. 14 respectively.





Fig. 12. Accuracy graph to detect the tumor with Inception-V3 model





Fig. 13. Accuracy graph to detect the tumor with Resnet-50 model





Fig. 14. Accuracy graph to detect the tumor with VGG-16 model

## VI. CONCLUSION

Brain tumors can impact any human being, whether a toddler or an adult. The creation of a tumor is caused by the uneven proliferation of cells that multiply uncontrollably. Due to the tumor's appearance, size, shape, and shape, detecting a brain tumor is still a distressing experience. In this paper, we used a new method in classifying brain tumors. First, we acquired the images dataset from Kaggle and using the image preprocessing technique, we resized the MRI images then converted them from BGR to RGB format. Second, using the image augmentation technique, we increased the size of the training data. This paper includes all the fundamental components of contemporary artwork completed to date, as well as our proposed work using transfer learning algorithm. It also compares the accuracy and time taken by different CNN model architecture in detecting the tumors with MRI images. The ascendancy of the proposed method is its excellent ability to analyze large amounts of data from MRI images using OpenCV. Having a superior dataset with high-definition photographs collected all at once from the MRI scanner can result in greatly improved accuracy. By using VGG-16 model final accuracy obtained was 0.960 as compared to 0.750 and 0.890 in Inception-V3 and Resnet-50 respectively, this will help the doctors in the accurate diagnosis of brain tumors.

## VII. FUTURE PROSPECTS

Future research could be done to discover brain tumors more effectively by the use of real-life statistics about affected people from any source (distinctive image capture) (scanners). To improve category outcomes, handcrafted and deep capabilities can be combined. Quantum machine



Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.

research, for example, is a light-weight method that plays an important role in improving accuracy and efficacy, saving radiologists' time and increasing the survival rate of patients.

## REFERENCES


[1] Mandhir Kaur and Dr. Rinkesh Mittal , Survey of Intelligent Methods for Brain Tumor Detection,IJCSI International Journal of Computer Science Issues, Vol. 11, Issue 5, No 1, September 2014 .

[2] Javeria Amina , Muhammad Sharifa , Mussarat Yasmina and Steven Lawrence Fernandes , A Distinctive Approach to Brain Tumor Detection and Classification using MRI ,https://doi.org/10.1016/j.patrec.2017.10.036

[3] Ahmet Çinar, Muhammed Yildirim , Detection of tumors on brain MRI images using the hybrid convolutional neural network architecture ,https://doi.org/10.1016/j.mehy.2020.109684

[4] M.O. Khairandish a, M. Sharma b, V. Jain c, J.M. Chatterjee d, N.Z. Jhanjhi , A Hybrid CNN-SVM Threshold Segmentation Approach for Tumor Detection and Classification of MRI Brain Images, https://doi.org/10.1016/j.irbm.2021.06.003

[5] Swapnil R.Telrandhe,"segmentation methods for medical image analysis",tesis no 1434,center for medical image science and visualization ,se-58185 linkoping ,Sweden.

[6] Malathi Hong-Long , , "Segmentation C- Means Clustering With Spatial Information For Image Segmentation," Computerized Medical Imaging And Graphics 30 (2006) 9–15.

[7] Image fusion using hybrid methods in multimodality medical images SP Yadav, S Yadav - Medical & biological engineering & computing, 2020 Cited by 31

[8] Rajeshwari G tayade,Michel Crucian , "Unsupervised And Semi-Supervised Clustering: A Brief Survey," Inria Rocquencourt, B.P. 105 78153 Le Chesnay Cedex, France.

[9] Lukas L. et Al. Brain Tumor Classification Based On Long Echo Proton Mrs Signals. Artificial Intelligence In Medicine, 31:73–89, 2004.

[10] Professor Teuvo Kohonen ,"Self-Organizing Maps",Springer series in Information Science,1995.

[11] Amin J, Sharif M, Yasmin M, Fernandes SL (2020) A distinctive approach in brain tumor detection and classification using MRI. Pattern Recogn Lett 139:118–127

[12] Amin J, Sharif M, Anjum MA, Raza M, Bukhari SAC (2020) Convolutional neural network with batch normalization for glioma and stroke lesion detection using MRI. Cogn Syst Res 59:304–311

[13] 13Amin J, Sharif M, Raza M, Saba T, Anjum MA (2019) Brain tumor detection using statistical and machine learning methods. Comput Methods Programs Biomed 177:69–79.

[14] S. Banerjee, S. Mitra, and B. U. Shankar, ―Synergetic neuro-fuzzy feature selection and classification of brain tumors,‖ in 2017 IEEE International Conference on Fuzzy Systems (FUZZ-IEEE), 2017, pp.1–6.

[15] S.U. Aswathy, G.Glan Deva Dhas and S.S. Kumar ―A Survey on detection of brain tumor from MRI Brain images‖, 7th International Conference on Cloud Computing, Data Science & Engineering –Confluence 2017.

[16] Minu Samantaray ,Millee Panigrahi, K.C .Patra ,Avipsa S.Panda and Rina Mahakud ―An adaptive filtering technique filtering technique for brain tumor analysis and detection‖,10th International Conference on Intellligent and Control (ISCO),2016.

[17] Luxit Kapoor and Sanjeev Thakur ―A survey on brain tumor detection using Image processing techniques‖,7s International Conference on Cloud Computing, Data Science & Engineering-Confluence, 2017.

[18] k. Ramya and L. K. Joshila Grace ―Brain tumor detection based on watershed transformation‖, International Conference on Communication and Signal Processing (ICCSP),2016.

[19] International Journal of Computer Science and communication Vol. 2, No. 2, JulyDecember-2011,pp. 325-331

[20] A.Vidyarthi, N.Mittal, ―CLAP: Closely link associated pixel based extraction of brain tumor in MR images‖, International Advance Computing Conference on Signal Processing and Communication (IACC), pp. 202 -206

[21] S. Bakas, M. Reyes, A. Jakab, S. Bauer, M. Rempfler, A. Crimi, et al., "Identifying the Best Machine Learning Algorithms for Brain Tumor Segmentation, Progression Assessment, and Overall Survival Prediction in the BRATS Challenge", arXiv preprint arXiv:1811.02629 (2018)

[22] S. Bakas, H. Akbari, A. Sotiras, M. Bilello, M. Rozycki, J.S. Kirby, et al., "Advancing The Cancer Genome Atlas glioma MRI collections with expert segmentation labels and radiomic features", Nature Scientific Data, 4:170117 (2017) DOI: 10.1038/sdata.2017.117

[23] B. H. Menze, A. Jakab, S. Bauer, J. Kalpathy-Cramer, K. Farahani, J. Kirby, et al. "The Multimodal Brain Tumor Image Segmentation Benchmark (BRATS)", IEEE Transactions on Medical Imaging 34(10), 1993-2024 (2015) DOI: 10.1109/TMI.2014.2377694

[24] Using CNN Technique, a Reliable Method for Brain Tumor Detection Assistant Professor Mrs. Shruti K2, NeethuOuseph C1 (Malabar Institute of Technology, Malabar, India, ECE in digital electronics) (Electronics and Communication Engineering, Malabar Institute of Technology, India)

[25] S.C. Turaga, J.F. Murray, V. Jain, F. Roth, M. Helmstaedter, K. Briggman, W. Denk, and H. S. Seung are some of the authors. For the purpose of segmenting images, convolutional networks can learn to produce affinity graphs. In 2010, Neural Computation 22(2): 511-538

[26] Dr. Rasel Ahmed The 2016 International Conference on Computer Communication and Informatics (ICCCI -2016), held in Coimbatore, India, included a paper by Foisal Hossain titled "Tumor Detection in Brain MRI Image Using Template based K-means and Fuzzy C-means Clustering Algorithm."

[27] Victor Alves, Sergio Pereira, Adriano Pinto, and Carlos A. Silva IEEE TRANSACTIONS ON MEDICAL IMAGING, VOL. 35, NO. 5, MAY 2016 "Brain Tumor Segmentation Using Convolutional Neural Networks in MRI Images"Vinod Kumar, JainySachdeva, Indra Gupta ―Classification of brain tumors using PCAANN ‖ 2011 World Congress on Information and Communication Technologies

[28] A hybrid model for multimodal brain tumour segmentation, by R. Meier et al., in Proc. NCIMICCAI BRATS, 2013, pp. 31–37.

[29] In Medical Image Computing and Computer-Assisted Intervention-MICCAI 2011, S. Bauer, L.-P. Nolte, and M. Reyes published a paper titled "Fully Automatic Segmentation of Brain Tumor Images Using Support Vector Machine Classification in Combination with Hierarchical Conditional Random Field Regularization." 2011: Springer, New York, pp. 354–361.

[30] A survey of MRI-based medical image analysis for brain tumour investigations by S. Bauer et al., Physical Medicine and Biology, vol. 58, no. 13, pp. 97-129, 2013..

[31] The multimodal brain tumour image segmentation benchmark (BRATS), B. Menze et al. (2015) IEEE Trans. Med. Imag., vol. 34, no. 10, pp. 1993-2024.

[32] The multimodal brain tumour image segmentation benchmark (BRATS), B. Menze et al. (2015) IEEE Trans. Med. Imag., vol. 34, no. 10, pp. 1993-2024.

[33] Using pseudo-conditional random fields, C.-H. Lee et al. segmented brain tumours in Medical Image Computing and Computer-Assisted.

[34] 2008 Intervention-MICCAI 2008, Springer, New York, pp. 359-366.




Authorized licensed use limited to: East West University. Downloaded on October 08,2026 at 08:53:18 UTC from IEEE Xplore. Restrictions apply.