



MAWLANA BHASHANI SCIENCE AND TECHNOLOGY UNIVERSITY

Santosh, Tangail-1902

LAB REPORT

Department of : Information & Communication Technology

Lab Report No : 09

Lab Report On : **Implementation of Priority Scheduling
Algorithm**

Course Title : Operating Systems Lab

Course Code : ICT - 3110

Submitted by,

Name : Zahid Hasan Chowdhury

Student ID : IT-18017

Session : 2017-18

Year: 3rd Semester : 1st

Dept. of ICT
MBSTU

Submitted to,

Nazrul Islam

Assistant Professor

Dept. of ICT,
MBSTU

Experiment no : 09**Experiment Name** : Implementation of Priority Scheduling Algorithm.**Theory** :

Priority scheduling is one of the most common scheduling algorithms in batch systems. Each process is assigned a priority. Process with the highest priority is to be executed first and so on. Processes with the same priority are executed on first come first served basis. Priority can be decided based on memory requirements, time requirements or any other resource requirement.

Implementation :

1. First input the processes with their burst time and priority.
2. Sort the processes, burst time and priority according to the priority.
3. Now simply apply FCFS algorithm.

Process	Burst Time	Priority
P1	10	2
P2	5	0
P3	8	1

Gantt Chart :

P1				P3				P2							
0				10				18				23			

Working Process :

Code for Priority Scheduling Algorithm –

```
#include<stdio.h>
#include<conio.h>
int main()
{
    int x,n,p[10],pp[10],pt[10],w[10],t[10],awt,atat,i;
    printf("Enter the number of process : ");
    scanf("%d",&n);
    printf("\nEnter process : time priorities \n");
    for(i=0;i<n;i++)
    {
        printf("\nProcess no %d : ",i+1);
        scanf("%d %d",&pt[i],&pp[i]);
        p[i]=i+1;
    }
    for(i=0;i<n-1;i++)
    {
        for(int j=i+1;j<n;j++)
        {
            if(pp[i]<pp[j])
            {
                x=pp[i];
                pp[i]=pp[j];
                pp[j]=x;
                x=pt[i];
                pt[i]=pt[j];
                pt[j]=x;
                x=p[i];
                p[i]=p[j];
                p[j]=x;
            }
        }
    }
    w[0]=0;
    awt=0;
    t[0]=pt[0];
    atat=t[0];
    for(i=1;i<n;i++)
    {
        w[i]=t[i-1];
        awt+=w[i];
    }
```

```

    t[i]=w[i]+pt[i];
    atat+=t[i];
}
printf("\n\n Job \t Burst Time \t Wait Time \t Turn Around Time Priority \n");
for(i=0;i<n;i++)
    printf("\n %d \t %d \t %d \t %d \t %d \n",p[i],pt[i],w[i],t[i],pp[i]);
awt/=n;
atat/=n;
printf("\n Average Wait Time : %d \n",awt);
printf("\n Average Turn Around Time : %d \n",atat);
getch();
}

```

Output :

```

Enter process : time priorities
Process no 1 : 3
1
Process no 2 : 4
2
Process no 3 : 5
3
Process no 4 : 6
4

Job      Burst Time      Wait Time      Turn Around Time      Priority
4         6             0             6             4
3         5             6             11            3
2         4             11            15            2
1         3             15            18            1

Average Wait Time : 8
Average Turn Around Time : 12

```

Discussion :

This lab helps to learn Priority scheduling algorithm. We have implemented this algorithm using C language. The program worked perfectly.