

# Rajalakshmi Engineering College

Name: Zaina Raheen A.P

Email: 241801328@rajalakshmi.edu.in

Roll no: 241801328

Phone: 9384899474

Branch: REC

Department: I AI & DS AF

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_COD\_Question 1

Attempt : 1

Total Mark : 10

Marks Obtained : 10

### Section 1 : Coding

#### 1. Problem Statement

John is learning about Binary Search Trees (BST) in his computer science class. He wants to create a program that allows users to delete a node with a given value from a BST and print the remaining nodes using an in-order traversal.

Implement a function to help him delete a node with a given value from a BST.

#### *Input Format*

The first line of input consists of an integer N, representing the number of nodes in the BST.

The second line consists of N space-separated integers, representing the values of the BST nodes.

The third line consists of an integer V, which is the value to delete from the BST.

### **Output Format**

The output prints the space-separated values in the BST in an in-order traversal, after the deletion of the specified value.

If the specified value is not available in the tree, print the given input values in-order traversal.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5  
10 5 15 2 7  
15

Output: 2 5 7 10

### **Answer**

```
#include <stdio.h>
#include <stdlib.h>
```

```
struct TreeNode {
    int data;
    struct TreeNode* left;
    struct TreeNode* right;
};
```

```
struct TreeNode* createNode(int key) {
    struct TreeNode* newNode = (struct TreeNode*)malloc(sizeof(struct
TreeNode));
    newNode->data = key;
    newNode->left = newNode->right = NULL;
    return newNode;
}
```

```
// You are using GCC
```

```
struct TreeNode* insert(struct TreeNode* root, int key) {
    //Type your code here
```

```

    if (root == NULL) {
        return createNode(key);
    }
    if (key < root->data) {
        root->left = insert(root->left, key);
    } else if (key > root->data) {
        root->right = insert(root->right, key);
    }
    return root;
}

```

```

struct TreeNode* findMin(struct TreeNode* root) {
    //Type your code here
    while (root && root->left != NULL) {
        root = root->left;
    }
    return root;
}

```

```

struct TreeNode* deleteNode(struct TreeNode* root, int key) {
    if (root == NULL) return NULL;

    if (key < root->data) {
        root->left = deleteNode(root->left, key);
    } else if (key > root->data) {
        root->right = deleteNode(root->right, key);
    } else {
        if (root->left == NULL) {
            struct TreeNode* temp = root->right;
            free(root);
            return temp;
        } else if (root->right == NULL) {
            struct TreeNode* temp = root->left;
            free(root);
            return temp;
        }

        struct TreeNode* temp = findMin(root->right);
        root->data = temp->data;
        root->right = deleteNode(root->right, temp->data);
    }
}

```

```

    return root;
}

void inorderTraversal(struct TreeNode* root) {
    //Type your code here
    if (root != NULL) {
        inorderTraversal(root->left);
        printf("%d ", root->data);
        inorderTraversal(root->right);
    }
}

int main()
{
    int N, rootValue, V;
    scanf("%d", &N);
    struct TreeNode* root = NULL;
    for (int i = 0; i < N; i++) {
        int key;
        scanf("%d", &key);
        if (i == 0) rootValue = key;
        root = insert(root, key);
    }
    scanf("%d", &V);
    root = deleteNode(root, V);
    inorderTraversal(root);
    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

# Rajalakshmi Engineering College

Name: Zaina Raheen A.P

Email: 241801328@rajalakshmi.edu.in

Roll no: 241801328

Phone: 9384899474

Branch: REC

Department: I AI & DS AF

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_PAH\_Updated

Attempt : 1

Total Mark : 50

Marks Obtained : 47.5

### Section 1 : Coding

#### 1. Problem Statement

Viha, a software developer, is working on a project to automate searching for a target value in a Binary Search Tree (BST). She needs to create a program that takes an integer target value as input and determines if that value is present in the BST or not.

Write a program to assist Viha.

#### ***Input Format***

The first line of input consists of integers separated by spaces, which represent the elements to be inserted into the BST. The input is terminated by entering -1.

The second line consists of an integer target, which represents the target value to be searched in the BST.

### **Output Format**

If the target value is found in the BST, print "[target] is found in the BST".

Else, print "[target] is not found in the BST"

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5 3 7 1 4 6 8 -1

4

Output: 4 is found in the BST

### **Answer**

```
// You are using GCC
```

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int data;  
    struct Node *left, *right;  
};
```

```
struct Node* createNode(int value) {  
    struct Node* newNode = (struct Node*)malloc(sizeof(struct Node));  
    newNode->data = value;  
    newNode->left = newNode->right = NULL;  
    return newNode;  
}
```

```
struct Node* insert(struct Node* root, int value) {  
    if (root == NULL) return createNode(value);  
    if (value < root->data)  
        root->left = insert(root->left, value);  
    else if (value > root->data)  
        root->right = insert(root->right, value);  
    return root;  
}
```

```

int search(struct Node* root, int target) {
    if (root == NULL) return 0;
    if (root->data == target) return 1;
    if (target < root->data)
        return search(root->left, target);
    else
        return search(root->right, target);
}

int main() {
    struct Node* root = NULL;
    int value;

    while (1) {
        scanf("%d", &value);
        if (value == -1) break;
        root = insert(root, value);
    }

    int target;
    scanf("%d", &target);

    if (search(root, target))
        printf("%d is found in the BST", target);
    else
        printf("%d is not found in the BST", target);

    return 0;
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Joseph, a computer science student, is interested in understanding binary search trees (BST) and their node arrangements. He wants to create a program to explore BSTs by inserting elements into a tree and displaying the nodes using post-order traversal of the tree.

Write a program to help Joseph implement the program.

# Rajalakshmi Engineering College

Name: Zaina Raheen A.P

Email: 241801328@rajalakshmi.edu.in

Roll no: 241801328

Phone: 9384899474

Branch: REC

Department: I AI & DS AF

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_CY\_Updated

Attempt : 1

Total Mark : 30

Marks Obtained : 30

### Section 1 : Coding

#### 1. Problem Statement

You are given a series of magic levels (integers) and need to construct a Binary Search Tree (BST) from them. After constructing the BST, your task is to perform a range search, which involves finding and printing all the magic levels within a specified range [L, R].

#### ***Input Format***

The first line of input consists of an integer N, the number of magic levels to insert into the BST.

The second line consists of N space-separated integers, representing the magic levels to insert.

The third line consists of two integers, L and R, which define the range for the search.



### **Output Format**

The output prints all the magic levels within the range [L, R] in ascending order, separated by spaces.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

10 5 15 3 7

2 20

Output: 3 5 7 10 15

### **Answer**

// You are using GCC

#include <stdio.h>

#include <stdlib.h>

```
struct Node {  
    int data;  
    struct Node* left;  
    struct Node* right;  
};
```

```
struct Node* newNode(int data) {  
    struct Node* node = (struct Node*)malloc(sizeof(struct Node));  
    node->data = data;  
    node->left = node->right = NULL;  
    return node;  
}
```

```
struct Node* insert(struct Node* root, int data) {  
    if (root == NULL) {  
        return newNode(data);  
    }
```

```
    if (data < root->data) {  
        root->left = insert(root->left, data);  
    } else if (data > root->data) {
```

```

        root->right = insert(root->right, data);
    }

    return root;
}

void inOrderRange(struct Node* root, int L, int R) {
    if (root == NULL) {
        return;
    }

    if (root->data >= L && root->data <= R) {
        inOrderRange(root->left, L, R);
        printf("%d ", root->data);
        inOrderRange(root->right, L, R);
    }
    else if (root->data > R) {
        inOrderRange(root->left, L, R);
    }
    else {
        inOrderRange(root->right, L, R);
    }
}

int main() {
    int N;
    scanf("%d", &N);

    struct Node* root = NULL;
    int magicLevel;

    for (int i = 0; i < N; i++) {
        scanf("%d", &magicLevel);
        root = insert(root, magicLevel);
    }

    int L, R;
    scanf("%d %d", &L, &R);

    inOrderRange(root, L, R);

    return 0;
}

```

}

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Arun is working on a Binary Search Tree (BST) data structure. His goal is to implement a program that reads a series of integers and inserts them into a BST. Once the integers are inserted, he needs to add a given integer value to each node in the tree and find the maximum value in the BST.

Your task is to help Arun implement this program.

### **Input Format**

The first line of input consists of an integer N, representing the number of elements to be inserted into the BST.

The second line consists of N space-separated integers, each representing an element to be inserted into the BST.

The third line consists of an integer add, representing the value to be added to each node in the BST.

### **Output Format**

The output prints the maximum value in the BST after adding the add value.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5  
10 5 15 20 25  
5

Output: 30

### **Answer**

// You are using GCC

# Rajalakshmi Engineering College

Name: Zaina Raheen A.P

Email: 241801328@rajalakshmi.edu.in

Roll no: 241801328

Phone: 9384899474

Branch: REC

Department: I AI & DS AF

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 5\_MCQ

Attempt : 1

Total Mark : 15

Marks Obtained : 14

### Section 1 : MCQ

1. Which of the following is the correct in-order traversal of a binary search tree with nodes: 9, 3, 5, 11, 8, 4, 2?

**Answer**

2, 3, 4, 5, 8, 9, 11

**Status : Correct**

**Marks : 1/1**

2. While inserting the elements 71, 65, 84, 69, 67, 83 in an empty binary search tree (BST) in the sequence shown, the element in the lowest level is \_\_\_\_\_.

**Answer**

67

**Status :** Correct

**Marks :** 1/1

3. Which of the following operations can be used to traverse a Binary Search Tree (BST) in ascending order?

**Answer**

Inorder traversal

**Status :** Correct

**Marks :** 1/1

4. Which of the following is a valid preorder traversal of the binary search tree with nodes: 18, 28, 12, 11, 16, 14, 17?

**Answer**

18, 12, 11, 16, 14, 17, 28

**Status :** Correct

**Marks :** 1/1

5. How many distinct binary search trees can be created out of 4 distinct keys?

**Answer**

14

**Status :** Correct

**Marks :** 1/1

6. The preorder traversal of a binary search tree is 15, 10, 12, 11, 20, 18, 16, 19. Which one of the following is the postorder traversal of the tree?

**Answer**

11, 12, 10, 16, 19, 18, 20, 15

**Status :** Correct

**Marks :** 1/1

7. Which of the following is the correct post-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

**Answer**

20, 30, 32, 52, 57, 55, 50

**Status :** Wrong

**Marks :** 0/1

8. Which of the following is the correct pre-order traversal of a binary search tree with nodes: 50, 30, 20, 55, 32, 52, 57?

**Answer**

50, 30, 20, 32, 55, 52, 57

**Status :** Correct

**Marks :** 1/1

9. Find the preorder traversal of the given binary search tree.

**Answer**

9, 2, 1, 6, 4, 7, 10, 14

**Status :** Correct

**Marks :** 1/1

10. Find the in-order traversal of the given binary search tree.

**Answer**

1, 2, 4, 13, 14, 18

**Status :** Correct

**Marks :** 1/1

11. In a binary search tree with nodes 18, 28, 12, 11, 16, 14, 17, what is the value of the left child of the node 16?

**Answer**

14

**Status :** Correct

**Marks :** 1/1

12. Find the pre-order traversal of the given binary search tree.

**Answer**

13, 2, 1, 4, 14, 18

**Status :** Correct

**Marks :** 1/1

13. Find the postorder traversal of the given binary search tree.

**Answer**

1, 4, 2, 18, 14, 13

**Status :** Correct

**Marks :** 1/1

14. While inserting the elements 5, 4, 2, 8, 7, 10, 12 in a binary search tree, the element at the lowest level is \_\_\_\_\_.

**Answer**

12

**Status :** Correct

**Marks :** 1/1

15. Find the post-order traversal of the given binary search tree.

**Answer**

10, 17, 20, 18, 15, 32, 21

**Status :** Correct

**Marks :** 1/1