

# Rajalakshmi Engineering College

Name: Zaina Raheen A.P

Email: 241801328@rajalakshmi.edu.in

Roll no: 241801328

Phone: 9384899474

Branch: REC

Department: AI & DS - Section 4

Batch: 2028

Degree: B.E - AI & DS

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 11

Attempt : 1

Total Mark : 20

Marks Obtained : 20

### Section 1 : Project

#### 1. Problem Statement

In ABC Corporation, employee records are stored in a database.

To efficiently manage employee details using Java and JDBC, you are tasked with building an Employee Management System that supports the following functionalities:

Adding a new employee

Updating an employee's salary

Viewing an employee's details

Displaying all employees

You are given two files:

File 1: Employee.java (POJO Class)

This class represents the Employee entity.

An Employee contains the following details:

Field Description

employeeId Unique Employee ID (Integer)

name Employee Name (String)

department Employee Department (String)

salary Employee Salary (Double)

Students must write code in the marked area:

```
class Employee {  
    private int employeeId;  
    private String name;  
    private String department;  
    private double salary;  
  
    public Employee() {}  
    public Employee(int employeeId, String name, String department, double salary) {  
        // write your code here  
    }  
  
    // Include getters and setters  
}
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: EmployeeDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class EmployeeDAO {

    public void addEmployee(Connection conn, Employee employee) throws
SQLException {

        // write your code here

    }

    public void updateSalary(Connection conn, int employeeId, double
newSalary) throws SQLException {

        // write your code here

    }

    public void deleteEmployee(Connection conn, int employeeId) throws
SQLException {

        // write your code here

    }

    public Employee viewEmployeeRecord(Connection conn, int employeeId)
throws SQLException {

        // write your code here

    }

    public List<Employee> displayAllEmployees(Connection conn) throws
SQLException {

        // write your code here

    }

}
```

```
private Employee mapToEmployee(ResultSet rs) throws SQLException {  
    return new Employee(  
        // write your code here  
    );  
}  
}
```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to Employee objects using mapToEmployee().

Return a List<Employee> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri\_dbUsername: testPassword: test123

The employees table has already been created with the following structure:

### ***Input Format***

The first line of input consists of an integer choice, representing the operation to be performed:

(1 for Add Employee, 2 for Update Salary, 3 for View Employee Record, 4 for Display All Employees, 5 for Exit)

For choice 1 (Add Employee):

1. The second line consists of an integer employee\_id.
2. The third line consists of a string name.
3. The fourth line consists of a string department.
4. The fifth line consists of a double salary (must be at least 30000).

For choice 2 (Update Salary):

1. The second line consists of an integer `employee_id`.
2. The third line consists of a double `new_salary` (must be at least 30000).

For choice 3 (View Employee Record):

1. The second line consists of an integer `employee_id`.

For choice 4 (Display All Employees).

For choice 5 (Exit).

### ***Output Format***

For choice 1 (Add Employee),

1. Print "Employee added successfully" if the employee was added.

For choice 2 (Update Salary),

1. Print "Salary updated successfully" if the salary update was successful.
2. Print "Employee not found." if the specified employee ID does not exist.
3. Print "Salary must be at least 30000." if the provided salary is below the minimum.

For choice 3 (View Employee Record),

1. Display the employee details in the format:
2. ID: `[employee_id]` | Name: `[name]` | Department: `[department]` | Salary: `[salary]`
3. Print "Employee not found." if the specified employee ID does not exist.

For choice 4 (Display All Employees),

1. Display each employee on a new line in the format:
2. ID | Name | Department | Salary

For choice 5 (Exit),

1. Print "Exiting Employee Management System."

For invalid input:

1. Print "Invalid choice. Please try again."

### **Sample Test Case**

Input: 1

101

Alice Johnson

Engineering

31000.75

4

6

5

Output: Employee added successfully

ID | Name | Department | Salary

101 | Alice Johnson | Engineering | 31000.75

Invalid choice. Please try again.

Exiting Employee Management System.

### **Answer**

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
// You are using Java
```

```
class Employee {
```

```
    private int employeeId;
```

```
    private String name;
```

```
    private String department;
```

```
    private double salary;
```

```

// Constructor
public Employee(int employeeId, String name, String department, double salary) {
    this.employeeId = employeeId;
    this.name = name;
    this.department = department;
    this.salary = salary;
}

// Include Getters and Setters
public int getEmployeeId() { return employeeId; }
public String getName() { return name; }
public String getDepartment() { return department; }
public double getSalary() { return salary; }
}

```

```

class EmployeeManagementSystem {

```

```

    public static void addEmployee(Connection conn, Scanner scanner) {
        // Write your code here
        try {
            int id = scanner.nextInt();
            scanner.nextLine(); // consume newline
            String name = scanner.nextLine();
            String department = scanner.nextLine();
            double salary = scanner.nextDouble();

            if (salary < 30000) {
                System.out.println("Salary must be at least 30000.");
                return;
            }

            String sql = "INSERT INTO employees (employee_id, name, department, salary) VALUES (?, ?, ?, ?)";
            PreparedStatement stmt = conn.prepareStatement(sql);
            stmt.setInt(1, id);
            stmt.setString(2, name);
            stmt.setString(3, department);
            stmt.setDouble(4, salary);

```

```

        stmt.executeUpdate();

        System.out.println("Employee added successfully");

    } catch (SQLIntegrityConstraintViolationException e) {
        System.out.println("Employee with this ID already exists.");
    } catch (SQLException e) {
        System.out.println("Database Error: " + e.getMessage());
    }
}

```

```

public static void updateSalary(Connection conn, Scanner scanner) {
    // Write your code here
    try {
        int id = scanner.nextInt();
        double newSalary = scanner.nextDouble();

        String sql = "UPDATE employees SET salary = ? WHERE employee_id = ?";
        PreparedStatement stmt = conn.prepareStatement(sql);
        stmt.setDouble(1, newSalary);
        stmt.setInt(2, id);

        int rows = stmt.executeUpdate();
        if (rows > 0) {
            System.out.println("Salary updated successfully");
        } else {
            System.out.println("Employee not found.");
        }
    } catch (SQLException e) {
        System.out.println("Database Error: " + e.getMessage());
    }
}

```

```

public static void viewEmployeeRecord(Connection conn, Scanner scanner) {
    // Write your code here
    try {
        int id = scanner.nextInt();
        String sql = "SELECT * FROM employees WHERE employee_id = ?";
        PreparedStatement stmt = conn.prepareStatement(sql);
        stmt.setInt(1, id);
        ResultSet rs = stmt.executeQuery();
    }
}

```



```

        if (rs.next()) {
            System.out.println("ID: " + rs.getInt("employee_id") +
                " | Name: " + rs.getString("name") +
                " | Department: " + rs.getString("department") +
                " | Salary: " + String.format("%.2f", rs.getDouble("salary")));
        } else {
            System.out.println("Employee not found.");
        }
    }
}

```

```

    } catch (SQLException e) {
        System.out.println("Database Error: " + e.getMessage());
    }
}

```

```

public static void displayAllEmployees(Connection conn) {
    // Write your code here
    try {
        String sql = "SELECT * FROM employees";
        Statement stmt = conn.createStatement();
        ResultSet rs = stmt.executeQuery(sql);
    }
}

```

```

        System.out.println("ID | Name | Department | Salary");
        while (rs.next()) {
            System.out.println(rs.getInt("employee_id") + " | " +
                rs.getString("name") + " | " +
                rs.getString("department") + " | " +
                String.format("%.2f", rs.getDouble("salary")));
        }
    }
}

```

```

    } catch (SQLException e) {
        System.out.println("Database Error: " + e.getMessage());
    }
}

```

```

public static void main(String[] args) {
    String url = "jdbc:mysql://localhost/ri_db";
    String username = "test";
    String password = "test123";
}

```

```

    try (Connection conn = DriverManager.getConnection(url, username,
        password);
        Scanner scanner = new Scanner(System.in)) {
    }
}

```

```

int choice;
do {
    choice = scanner.nextInt();

    switch (choice) {
        case 1 -> addEmployee(conn, scanner);
        case 2 -> updateSalary(conn, scanner);
        case 3 -> viewEmployeeRecord(conn, scanner);
        case 4 -> displayAllEmployees(conn);
        case 5 -> System.out.println("Exiting Employee Management
System.");
        default -> System.out.println("Invalid choice. Please try again.");
    }

    } while (choice != 5);

    } catch (SQLException e) {
        System.out.println("Database Error: " + e.getMessage());
    }
}
}

```

**Status :** Correct

**Marks :** 10/10

## 2. Problem Statement

Create a JDBC-based Hospital Management System that handles runtime input to manage patient records. The system should allow users to:

Add a new patient (patient ID, name, age, status).

Update a patient's status.

View a specific patient's record by patient ID.

Display all patient records in the database.

Exit the application.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri\_db

USER: test

PWD: test123

The patients table has already been created with the following structure:

Table Name: patients

### ***Input Format***

The first line of input consists of an integer choice, representing the operation to be performed:

(1 for Add Patient, 2 for Update Patient Status, 3 for View Patient Record, 4 for Display All Patients, 5 for Exit)

For choice 1 (Add Patient):

- The second line consists of an integer patient\_id.
- The third line consists of a string name.
- The fourth line consists of an integer age.
- The fifth line consists of a string status.

For choice 2 (Update Patient Status):

- The second line consists of an integer patient\_id.
- The third line consists of a string new\_status.

For choice 3 (View Patient Record):

- The second line consists of an integer patient\_id.

For choice 4 (Display All Patients):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

### **Output Format**

For choice 1 (Add Patient):

- Print "Patient added successfully" if the patient was added.
- Print "Failed to add patient." if the insertion failed.

For choice 2 (Update Patient Status):

- Print "Patient status updated successfully" if the update was successful.
- Print "Patient not found." if the specified patient ID does not exist.

For choice 3 (View Patient Record):

- Display the patient details in the format:
- ID: [patient\_id] | Name: [name] | Age: [age] | Status: [status]
- Print "Patient not found." if the specified patient ID does not exist.

For choice 4 (Display All Patients):

- Display each patient on a new line in the format:
- ID | Name | Age | Status
- If no records are available, print nothing (or handle it with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Hospital Management System."

For invalid input:

- Print "Invalid choice. Please try again."

### **Sample Test Case**

Input: 1

101

John Doe

45

Admitted

4

5

Output: Patient added successfully  
ID | Name | Age | Status  
101 | John Doe | 45 | Admitted  
Exiting Hospital Management System.

**Answer**

```
import java.sql.*;
import java.util.Scanner;

class HospitalManagementSystem {
    public static void main(String[] args) {
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://
localhost/ri_db", "test", "test123");
            Scanner scanner = new Scanner(System.in)) {

            boolean running = true;

            while (running) {

                int choice = scanner.nextInt();

                switch (choice) {
                    case 1:
                        addPatient(conn, scanner);
                        break;
                    case 2:
                        updatePatientStatus(conn, scanner);
                        break;
                    case 3:
                        viewPatientRecord(conn, scanner);
                        break;
                    case 4:
                        displayAllPatients(conn);
                        break;
                    case 5:
                        System.out.println("Exiting Hospital Management System.");
                        running = false;
                        break;
                    default:
                        System.out.println("Invalid choice. Please try again.");
                }
            }
        }
    }
}
```

```

    }
    } catch (SQLException e) {
        e.printStackTrace();
    }
}

// You are using Java
public static void addPatient(Connection conn, Scanner scanner) {
    // Write your code here
    int patientId = scanner.nextInt();
    scanner.nextLine(); // Consume newline

    String name = scanner.nextLine();

    int age = scanner.nextInt();

    scanner.nextLine(); // Consume newline
    String status = scanner.nextLine();

    String insertQuery = "INSERT INTO patients (patient_id, name, age, status)
VALUES (?, ?, ?, ?)";
    try (PreparedStatement stmt = conn.prepareStatement(insertQuery)) {
        stmt.setInt(1, patientId);
        stmt.setString(2, name);
        stmt.setInt(3, age);
        stmt.setString(4, status);

        int rowsInserted = stmt.executeUpdate();
        System.out.println(rowsInserted > 0 ? "Patient added successfully" :
"Failed to add patient.");
    } catch (SQLException e) {
        System.out.println("Error adding patient: " + e.getMessage());
    }
}

public static void updatePatientStatus(Connection conn, Scanner scanner) {
    // Write your code here
    int patientId = scanner.nextInt();
    scanner.nextLine(); // Consume newline

    String newStatus = scanner.nextLine();

    String updateQuery = "UPDATE patients SET status = ? WHERE patient_id
= ?";

```

```

try (PreparedStatement stmt = conn.prepareStatement(updateQuery)) {
    stmt.setString(1, newStatus);
    stmt.setInt(2, patientId);

    int rowsUpdated = stmt.executeUpdate();
    System.out.println(rowsUpdated > 0 ? "Patient status updated
successfully" : "Patient not found.");
} catch (SQLException e) {
    System.out.println("Error updating patient status: " + e.getMessage());
}

}

```

```

public static void viewPatientRecord(Connection conn, Scanner scanner) {
    // Write your code here
    int patientId = scanner.nextInt();

    String selectQuery = "SELECT * FROM patients WHERE patient_id = ?";
    try (PreparedStatement stmt = conn.prepareStatement(selectQuery)) {
        stmt.setInt(1, patientId);

        ResultSet rs = stmt.executeQuery();
        if (rs.next()) {
            System.out.printf("ID: %d | Name: %s | Age: %d | Status: %s\n",
                rs.getInt("patient_id"),
                rs.getString("name"),
                rs.getInt("age"),
                rs.getString("status"));
        } else {
            System.out.println("Patient not found.");
        }
    } catch (SQLException e) {
        System.out.println("Error retrieving patient record: " + e.getMessage());
    }

}

```

```

public static void displayAllPatients(Connection conn) {
    // Write your code here
    String displayQuery = "SELECT * FROM patients ORDER BY patient_id";
    try (Statement stmt = conn.createStatement();
        ResultSet rs = stmt.executeQuery(displayQuery)) {

```

```
System.out.println("ID | Name | Age | Status");
while (rs.next()) {
    System.out.printf("%d | %s | %d | %s%n",
        rs.getInt("patient_id"),
        rs.getString("name"),
        rs.getInt("age"),
        rs.getString("status"));
}
} catch (SQLException e) {
    System.out.println("Error displaying patients: " + e.getMessage());
}
}
}
```

**Status :** Correct

**Marks :** 10/10