

General Information

Customer

:

Address

:

Calibration Date

:

Received Date :

Location of Calibration

:

Equipment Name

:

T awal

:

°C

Manufacturer

:

T akhir

:

°C

Type

:

RH awal

:

%RH

SN

:

RH akhir

:

%RH

Range

:

()

Thermohygro Used

:

Insitu:

☐ TH-2

☐ TH-6

☐ H-7

Resolution

:

()

Inlab :

☐ TH-4

Methode

:

SIDIK-IK-CAL-0516

Data Result

Before Adjustment

Standard ()		UUT Reading ()				
		1	2	3	4	5
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					

After Adjustment

Standard ()		UUT Reading ()				
		1	2	3	4	5
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					
	°Brix / nD ₂₀					
	°C					

Standard Used:

Larutan Std Refracto 2.5 °Brix (1.33659 nD20)

☐

Larutan Std Refracto 40 °Brix (1.39986 nD20)

☐

Calibrated by:

Name:

Sign:

Corrected by:

Name:

Sign:

Catatan: