

PT. SIDIK		Calibration Worksheet – Turbidimeter					LK-285-IDN				
Received Date : Calibration Date :											
EQUIPMENT IDENTITY AND CUSTOMER DATA				CALIBRATION RESULT							
1. Name : 2. Range/Resolution : NTU *Tuliskan resolusi UUT di masing-masing titik kalibrasi 3. Type/Model : 4. Serial Number/LPI : 5. Merk/Manufacture : OWNER 1. Name : 2. Address : STANDARD Standard Used : Turbidity Std. Solutions 0.04 NTU ☐ Turbidity Std. Solutions 15 NTU ☐ Turbidity Std. Solutions 100 NTU ☐ Turbidity Std. Solutions 750 NTU ☐ Turbidity Std. Solutions 2000 NTU ☐ RTD Sensor/SH1/20 ☐ Victor 14+/992613877 ☐ CALIBRATION DATA 1. Location : 2. Calibration Methode : SIDIK-IK-CAL-0523				Env. Condition :		First (°C) End (°C)		First (%RH) End (%RH)			
				Solution Standard		Before Adjustment Reading of UUT (NTU)				TH used:	
						0.04	15	100	750	2000	Insitu: ☐ TH-2 ☐ TH-6 ☐ TH-7 Inlab: ☐ TH-4
Repeat		Resolusi:	Resolusi:	Resolusi:	Resolusi:	Resolusi:					
1	NTU										
	°C										
2	NTU										
	°C										
3	NTU										
	°C										
4	NTU										
	°C										
5	NTU										
	°C										
Solution Standard		After Adjustment Reading of UUT (NTU)									
		0.04	15	100	750	2000					
Repeat		Resolusi:	Resolusi:	Resolusi:	Resolusi:	Resolusi:					
1	NTU										
	°C										
2	NTU										
	°C										
3	NTU										
	°C										
4	NTU										
	°C										
5	NTU										
	°C										
Catatan:											
Calibrated by :		Checked by :									
Sign Name		Sign Name									