



Creating filesystems and mount points

Let's start by taking a look at the hard disks (sdc, sdd) that we are going to be using:

```
sudo fdisk -l /dev/sdc /dev/sdd
```

```
Disk /dev/sdc: 10 Gib, 1073741824 bytes
```

```
255 heads, 63 sectors/track, 130 cylinders
```

```
Units = cylinders of 16065 * 512 = 8225280 bytes
```

```
Sector size (logical/physical): 512 bytes / 512 bytes
```

```
I/O size (minimum/optimal): 512 bytes / 512 bytes
```

```
Disk identifier: 0x000d5df1
```

Device	Boot	Start	End	Blocks	Id	System
--------	------	-------	-----	--------	----	--------

```
Disk /dev/sdd: 10 Gib, 1073741824 bytes
```

```
255 heads, 63 sectors/track, 130 cylinders
```

```
Units = cylinders of 16065 * 512 = 8225280 bytes
```

```
Sector size (logical/physical): 512 bytes / 512 bytes
```

```
I/O size (minimum/optimal): 512 bytes / 512 bytes
```

```
Disk identifier: 0x0000523e
```

Device	Boot	Start	End	Blocks	Id	System
--------	------	-------	-----	--------	----	--------

We can see from the information above that each drive is 1 Gb in size.

fdisk -l will list all drives and their partitions. These drives have not been partitioned yet.



Creating filesystems and mount points

Partition /dev/sdc

We use fdisk to partition disks:

```
fdisk /dev/sdc
```

Device contains neither a valid DOS partition table, nor Sun, SGI or OSF disklabel

Building a new DOS disklabel with disk identifier 0x05adea0a.

Changes will remain in memory only, until you decide to write them.

After that, of course, the previous content won't be recoverable.

Warning: invalid flag 0x0000 of partition table 4 will be corrected by w(rite)

WARNING: DOS-compatible mode is deprecated. It's strongly recommended to

switch off the mode (command 'c') and change display units to

sectors (command 'u').

Command (m for help): **n** <--

Command action

e extended

p primary partition (1-4)

p <--

Partition number (1-4): **1** <--

First cylinder (1-10, default 1): **1** <--

Last cylinder, +cylinders or +size{K,M,G} (1-130, default 130): **+500M**

<--

Command (m for help): **n** <--

Command action

e extended

p primary partition (1-4)

p <--

Partition number (1-4): **2** <--

First cylinder (66-130, default 66): **[enter]** <--

Using default value 66

Last cylinder, +cylinders or +size{K,M,G} (66-130, default 130):



Creating filesystems and mount points

[enter]

Using default value 10

n

Command (m for help): w <--

The partition table has been altered!

Calling ioctl() to re-read partition table.

Syncing disks.

```
[root@centos-in ~]# fdisk -l /dev/sdc
```

255 heads, 63 sectors/track, 130 cylinders
Units = cylinders of 16065 * 512 = 8225280 bytes
Sector size (logical/physical): 512 bytes / 512 bytes
I/O size (minimum/optimal): 512 bytes / 512 bytes
Disk identifier: 0x000d5df1

Device	Boot	Start	End	Blocks	Id	System
/dev/sdc1		1	65	522081	83	Linux
/dev/sdc2		66	130	522112+	83	Linux

If you see the partition table highlighted above, you have successfully partitioned /dev/sdc into two partitions, /dev/sdc1 and /dev/sdc2.

The first partition we specified a size of 500 MB (+500M)

The second partition we defaulted to the rest of the disk

Formatting

We want to use the ext4 filesystem on both partitions:

```
mkfs -t ext4 /dev/sdc1  
mkfs -t ext4 /dev/sdc2
```

You should get output from the mkfs command with inode counts and that the format completed successfully.



Creating filesystems and mount points

Mount Point

Create directories named sdc1 and sdc2 in the /media directory:

```
mkdir /media/sdc1  
mkdir /media/sdc2
```

Mount the partitions to the appropriate directory:

```
mount -o rw /dev/sdc1 /media/sdc1  
mount -o rw /dev/sdc2 /media/sdc2
```

Use the **mount** command to verify that you have mounted the filesystems correctly. You should see the following lines:

```
/dev/sdc1 on /media/sdc1 type ext4 (rw)  
/dev/sdc2 on /media/sdc2 type ext4 (rw)
```

Add to /etc/fstab (example only - do not modify!)

Using nano, add the following lines to your /etc/fstab so that the filesystems will automount on reboot:

```
/dev/sdc1 /media/sdc1 ext4 defaults 0 0  
/dev/sdc2 /media/sdc2 ext4 defaults 0 0
```