

Lab1: Implementing RBAC

```
create role cashier_role;
```

Data Output Messages Notifications

```
CREATE ROLE
```

Query returned successfully in 117 msec.

```
create user mike with password 'mike123';
```

```
create user jon with password 'jon123';
```

Data Output Messages Notifications

```
CREATE ROLE
```

Query returned successfully in 341 msec.

```
grant cashier_role to mike;
```

```
grant cashier_role to jon;
```

Data Output Messages Notifications

```
GRANT ROLE
```

Query returned successfully in 66 msec.

```
grant select on film, staff to cashier_role;
```

```
grant select, insert on payment to cashier_role;
```

Data Output Messages Notifications

```
GRANT
```

Query returned successfully in 582 msec.

Lab 2: Implementing RLS

```
alter table payment enable row level security;
```

Data Output Messages Notifications

ALTER TABLE

Query returned successfully in 65 msec.

```
create policy isolate_cashier_payments on payment
for select
to cashier_role
using (
    staff_id = (select staff_id from staff where username = current_user)
);
```

Data Output Messages Notifications

CREATE POLICY

Query returned successfully in 154 msec.

```
set role mike;  
select count(*) from payment;
```

Data Output Messages Notifications

	count bigint 
1	7292

```
set role jon;  
select count(*) from payment;
```

Data Output Messages Notifications

	count bigint 
1	7304