Table 1: Accuracy and cost on AR-Bench, selection split, 100 episodes per cell, with a frozen Qwen2.5-7B-Instruct. Cost is mean input plus output tokens per episode. Guess Number is reported for completeness but is saturated by the harness search and is not evidence about reasoning (the text).

	Guess Number		Detective Cases		Situation Puzzles	
Method	Acc.	Tok/ep	Acc.	Tok/ep	Acc.	Tok/ep
Zero-shot	0.0	31,094	–	–	4.5	37,413
Few-shot with instruction	–	–	34.0	286,863	3.5	54,746
Tree of Thoughts[†]	6.0	21,176	31.0	95,518	12.5	8,624
Proactive CoT	2.0	46,161	35.0	114,648	–	–
Ask nothing (anchor)	0.0	226	37.0	863	12.0	216
Ours, cost-efficient	**100.0**	**12**	57.0	20,854	36.5	8,448
Ours, best	**100.0**	**7**	**80.0**	25,344	**41.0**	12,368

[†] Repaired. AR-Bench's `gn/tot` scores each candidate guess against the hidden answer and its `sp/dc` ToT never assigns the state evaluator Yao et al. specify; both are corrected here. Uncertainty-of-Thoughts is held out of the seed set and is not reported. A dash marks a method AR-Bench does not provide for that task.

Held-out split. Our systems were finalised once on the sealed test split: Guess Number 100.0, Detective Cases 63.0 (cost-efficient variant 57.0), Situation Puzzles 32.5; the anchor moves by at most 1.5 points. The published arms have not yet been re-measured there, so the table above keeps every method on the split they share.