

ONECORE MYTHOS

KEYpanel - Full Configuration, Security & Production Setup Guide

Hinglish • JavaLoader / OneCore.Vip • Encrypted API v2

Final production identity

Item	Final value
Android package	OneCore.Vip
App name	OneCore MyThos
Signing alias	onecore-mythos-prod
Production certificate SHA-256	B343111BBFA30ED565F9B61A52CF5B34CB2EAF0485EB8B396AB373B2ECCA53D4
Encrypted licensing route	/api/v2/connect
Default game ID	PUBG

Important: JKS password, database password, Telegram bot token, real .env, RSA private key aur production .jks ko GitHub source/PDF/screenshots me kabhi store mat karo.

1. Final architecture - kaun kya karta hai

KEYpanel ek standalone PHP control panel hai jo JavaLoader ke encrypted key-login flow ka server-side source of truth banega. Android app package aur release signing identity dono server par bind hote hain.

Layer	Role
Android app	OneCore.Vip request banata hai, package/cert identity bhejta hai, HTTPS + TLS pin use karta hai.
Transport	Fresh AES-256-GCM session key; session key RSA-OAEP se panel public key par wrap hoti hai.
KEYpanel API	/api/v2/connect encrypted envelope decrypt karta hai, nonce/canary/time/package/cert/version/key/dev
MySQL	keys_code, users, rate limits, nonces, audit log, generation options store karta hai.
RSA private key	Sirf hosting runtime/ me rehti hai; GitHub ko sirf public key milti hai.
GitHub Actions	Production JKS + transport config se manually signed production APK banata hai.

Request fail hone par server plaintext secret expose nahi karta; production authorization server-side final authority rehni chahiye.

2. KEYpanel folder me kya kya hai

```
KEYpanel/  
.env.example  
.gitignore  
.htaccess  
index.php  
README.md  
CONFIGURATION-HINGLISH.md  
SECURITY.md  
assets/app.css  
database/schema.sql  
runtime/.htaccess  
src/*.php  
tests/*.php  
tools/generate-secrets.php  
tools/configure-telegram.php  
tools/telegram-user-id.php  
tools/tls-pin.php  
tools/deploy-check.php
```

- .env.example: safe template; production me copy karke .env banao.
- runtime/: RSA private/public transport key pair aur PHP error log; web access blocked.
- src/: login, security, DB, crypto, Telegram, routing aur UI.
- tests/: PHP security/config tests + MySQL encrypted transport integration.
- tools/deploy-check.php: go-live se pehle production configuration sanity-check.

3. Hosting requirements

Requirement	Minimum
PHP	8.1+ (8.2/8.3 recommended)
Database	MySQL 8.0+ or MariaDB 10.5+
PHP extensions	PDO, pdo_mysql, session, json, openssl, curl

Requirement	Minimum
Web server	Apache/LiteSpeed with .htaccess + rewrite
TLS	Public HTTPS domain/subdomain
Filesystem	runtime/ writable by PHP; private files not world-readable

Example: <https://key.example.com>. Shared hosting par dedicated subdomain easiest setup hota hai.

4. Panel upload + MySQL database

JavaLoader repo ke KEYpanel/ ke andar ke contents ko panel domain ke document-root me upload karo. KEYpanel folder ko extra nesting me mat chhodo agar URL root par chahiye.

```
public_html/
.env
.htaccess
index.php
assets/
database/
runtime/
src/
tests/
tools/
```

cPanel -> MySQL Databases me empty database aur dedicated user banao, strong random password do, aur us user ko database par ALL PRIVILEGES do.

```
DB_HOST=localhost
DB_PORT=3306
DB_NAME=YOUR_DB_NAME
DB_USER=YOUR_DB_USER
DB_PASSWORD=YOUR_PRIVATE_DB_PASSWORD
```

5. Production .env - exact skeleton

```
APP_ENV=production
APP_URL=https://YOUR-PANEL-DOMAIN
APP_BASE_PATH=
APP_TIMEZONE=UTC
PANEL_NAME=OneCore MyThos
SESSION_NAME=onecore_mythos_panel
SETUP_TOKEN=YOUR_GENERATED_RANDOM_SETUP_TOKEN
TRUSTED_PROXY_IPS=

DB_HOST=localhost
DB_PORT=3306
DB_NAME=YOUR_DB_NAME
DB_USER=YOUR_DB_USER
DB_PASSWORD=YOUR_DB_PASSWORD

TELEGRAM_BOT_TOKEN=
TELEGRAM_BOT_USERNAME=
TELEGRAM_WEBHOOK_SECRET=YOUR_GENERATED_WEBHOOK_SECRET
TELEGRAM_ALLOWED_USER_IDS=

API_PRIVATE_KEY_PATH=runtime/api-private.pem
API_PUBLIC_KEY_PATH=runtime/api-public.b64

EXPECTED_ANDROID_PACKAGE=OneCore.Vip
EXPECTED_ANDROID_CERT_SHA256=B343111BBFA30ED565F9B61A52CF5B34CB2EAF0485EB8B396AB373B2ECCA53D4
MIN_ANDROID_VERSION_CODE=1
```

APP_BASE_PATH: direct subdomain/root deployment me blank. Agar URL <https://example.com/panel> hai to APP_URL=<https://example.com> aur APP_BASE_PATH=/panel.

TRUSTED_PROXY_IPS: normal shared hosting me blank. Sirf controlled reverse proxy use karte waqt exact proxy IPs daalo; wildcard trust mat karo.

6. First-run secrets generate karo

```
cd /path/to/panel
cp .env.example .env
php tools/generate-secrets.php
```

Generated SETUP_TOKEN aur Telegram webhook secret ko .env me paste karo. Real .env ko Git me add mat karo.

Recommended filesystem permissions hosting ke hisaab se: .env 0600/0640, RSA private key 0600, runtime directory PHP-writable but public web se denied.

7. Browser first setup

<https://YOUR-PANEL-DOMAIN/setup>

- SETUP_TOKEN enter karo.
- Owner username choose karo.
- Owner password minimum 12 characters; unique strong password use karo.
- Numeric Telegram user ID enter karo (panel setup flow me required).

Setup MySQL schema install karta hai, first owner create karta hai aur 3072-bit RSA transport key pair generate karta hai:

```
runtime/api-private.pem
runtime/api-public.b64
```

api-private.pem sirf hosting par. Isko GitHub, Telegram, email, source ZIP ya public backup me mat bhejo.

8. Deployment self-check

```
cd /path/to/panel
php tools/deploy-check.php
```

Tool PHP/extensions, .env, HTTPS APP_URL, DB fields, SETUP_TOKEN, OneCore.Vip package, production cert allowlist, runtime permissions, RSA files aur proxy trust validate karta hai.

Output me READY aane ke baad hi production connect karo. FAIL ko ignore mat karo.

9. Panel login, users, keys aur durations

Setup ke baad /login open karo. Owner dashboard se keys, settings, panel users aur account security manage kar sakta hai.

Role	Access
Owner	Full settings, users, keys, generation lists, account.
Admin	Operational keys/settings access; owner-only user controls restricted.
Reseller	Own generated key inventory + credit limits.

Settings -> Key generation lists me current loader ke liye PUBG rehna chahiye:

PUBG|PUBG Mobile
BGMI|Battlegrounds Mobile India

2|2 Hours
5|5 Hours
24|1 Day
72|3 Days
168|7 Days
336|14 Days

Issued key ka duration first successful use par expiry me convert hota hai. Device list max_devices enforce karti hai; panel reset/block/enable/delete actions audit log me record hote hain.

10. KEYpanel security controls

- Argon2id available ho to password hashing usse; otherwise secure PHP default.
- Strict cookie-only sessions, HttpOnly + SameSite=Strict + HTTPS Secure cookies.
- Session ID regeneration, idle timeout aur absolute timeout.
- CSRF token + same-origin browser validation.
- Login per-account/IP throttling + one-time arithmetic CAPTCHA.
- HSTS, CSP, frame deny, nosniff, no-referrer, browser isolation headers.
- Private directories/.env/PEM/SQL/log/backup files .htaccess se deny.
- Encrypted API envelope: RSA-OAEP + AES-256-GCM.
- Fresh nonce, timestamp window, random canary, replay table and request-size bounds.
- Server-side package, signing certificate, minimum app version, key, device and expiry checks.
- Telegram webhook secret header + Telegram ID allowlist + owner/admin account linkage.
- Audit log for sensitive panel actions.

11. GitHub Actions - 4 production Secrets

Repo -> Settings -> Secrets and variables -> Actions -> Secrets. Ye values private hain:

Secret	Kahan se milega
ANDROID_KEYSTORE_BASE64	Production OneCore_MyThos_Production.jks ka Base64.
ANDROID_KEYSTORE_PASSWORD	Production JKS store password.
ANDROID_KEY_ALIAS	onecore-mythos-prod
ANDROID_KEY_PASSWORD	Production private-key password.

```
base64 -w0 OneCore_MyThos_Production.jks | gh secret set ANDROID_KEYSTORE_BASE64 --repo ZayYadav/JavaLoader
```

```
gh secret set ANDROID_KEYSTORE_PASSWORD --repo ZayYadav/JavaLoader  
gh secret set ANDROID_KEY_ALIAS --body "oncore-mythos-prod" --repo ZayYadav/JavaLoader  
gh secret set ANDROID_KEY_PASSWORD --repo ZayYadav/JavaLoader
```

Password ko --body ke saath shell history me type mat karo; gh secret set ka interactive prompt use karo.

12. GitHub Actions - 4 repository Variables

Same page -> Variables. Ye public build configuration values hain, secrets nahi:

Variable	Value / source
JAVA_LOADER_LICENSE_URL	https://YOUR-PANEL-DOMAIN/api/v2/connect
JAVA_LOADER_API_PUBLIC_KEY_B64	Panel setup ke baad runtime/api-public.b64
JAVA_LOADER_TLS_PINS	tools/tls-pin.php se live domain ka sha256/... SPKI pin
JAVA_LOADER_GAME_ID	PUBG

```
cat runtime/api-public.b64
php tools/tls-pin.php YOUR-PANEL-DOMAIN
```

TLS certificate rotate hone wala ho to old+new planned pins temporarily comma-separated rakh sakte ho. Random CA/intermediate ko broad trust ke liye pin mat karo.

13. Optional Telegram control bot

- @BotFather me /newbot -> token + username lo.
- Bot ko /start bhejo.
- Hosting: php tools/telegram-user-id.php se numeric Telegram ID find karo.
- .env me token, username, webhook secret, allowed IDs set karo.
- php tools/configure-telegram.php run karke HTTPS webhook register karo.

```
TELEGRAM_BOT_TOKEN=...
TELEGRAM_BOT_USERNAME=...
TELEGRAM_WEBHOOK_SECRET=...
TELEGRAM_ALLOWED_USER_IDS=123456789
```

Bot token ko public source me kabhi mat commit karo. Telegram control sirf private-chat updates aur allowlisted owner/admin IDs accept kare.

14. Production Release APK build

Normal PR/main push compile-validation hai. Real distributable production APK manual workflow_dispatch se banta hai, jahan production JKS aur transport variables mandatory hain.

```
gh workflow run android-build.yml --repo ZayYadav/JavaLoader --ref main
```

GitHub UI: Actions -> OneCore MyThos Release -> Run workflow -> main.

Production signer certificate SHA-256 exact hona chahiye:

```
B343111BBFA30ED565F9B61A52CF5B34CB2EAF0485EB8B396AB373B2ECCA53D4
```

Compile-only/temporary signer wala APK production me install mat karo.

15. Downloaded APK ko install se pehle verify karo

```
apksigner verify --verbose --print-certs OneCore-MyThos-release.apk
```

Expected certificate digest (colon/case ignore kar sakte ho):

```
B343111BBFA30ED565F9B61A52CF5B34CB2EAF0485EB8B396AB373B2ECCA53D4
```

APK file SHA-256 aur certificate SHA-256 alag cheezein hain. App identity binding ke liye certificate SHA-256 use hota hai.

16. Common errors - quick troubleshooting

Error / symptom	Check
APP IDENTITY FAILED	Panel EXPECTED_ANDROID_PACKAGE=OneCore.Vip aur cert B343...53D4; APK signer verify karo
INVALID ENCRYPTED REQUEST	Loader RSA public key panel ke current runtime key pair se match karta hai?
TLS pin failure	Live certificate changed; tools/tls-pin.php se current pin nikalo aur loader rebuild karo.
USER OR GAME NOT REGISTERED	Key exists? game field JAVA_LOADER_GAME_ID/PUBG se match?
MAX DEVICE REACHED	Panel Keys -> Reset devices ya max_devices review karo.
EXPIRED KEY	New key issue karo; DB clock UTC/time sync check karo.
TOO MANY REQUESTS	Client retry loop check karo; temporary rate limit expire hone do.
Setup page locked	Owner already exists - intentional. DB reset bina backup ke mat karo.
500 panel error	runtime/php-error.log + deploy-check.php run karo; production me errors browser me hidden ha

17. Backup & recovery

Ye 4 items ek saath private backup me rakho:

- MySQL database dump
- production .env
- runtime/api-private.pem
- Android production signing .jks

RSA private key lost hua to new transport key pair + loader rebuild chahiye. Android signing key lost hua to app update identity break ho sakti hai. Backup encrypt karke offline copy rakho.

18. Final go-live checklist

- ☐ HTTPS panel URL live.
- ☐ PHP/MySQL/extensions ready.
- ☐ .env private aur correct.
- ☐ DB dedicated user configured.
- ☐ /setup complete; owner login works.
- ☐ deploy-check.php READY.
- ☐ OneCore.Vip package binding correct.
- ☐ B343...53D4 production certificate allowlisted.
- ☐ RSA private key only hosting par.
- ☐ RSA public key GitHub variable me.
- ☐ Live TLS pin GitHub variable me.
- ☐ PUBG generation option enabled.
- ☐ 4 GitHub signing Secrets set.
- ☐ 4 JavaLoader Variables set.
- ☐ Manual production workflow successful.
- ☐ Final APK signer apksigner se B343...53D4 verified.
- ☐ MySQL/.env/RSA private/JKS backups created.

Security reality: client-side protections compromised/rooted device par absolute secrecy guarantee nahi kar sakti. Server authorization, expiry, device policy aur signing identity ko final authority rakho. Private secrets client APK me embed mat karo.