TUGAS BASIS DATA MEMBUAT TABLE PENJUALAN BARANG

NAMA : Teguh Tegar Aulia

NIM : 20230801124

```
Microsoft Windows [Version 10.0.22631.4169]
(c) Microsoft Corporation. All rights reserved.

C:\Users\HP>cd\xampp\mysql\bin

C:\xampp\mysql\bin>mysql -u root -p
Enter password:
Welcome to the MariaDB monitor.  Commands end with ; or \g.
Your MariaDB connection id is 11
Server version: 10.4.32-MariaDB mariadb.org binary distribution

Copyright (c) 2000, 2018, Oracle, MariaDB Corporation Ab and others.

Type 'help;' or '\h' for help. Type '\c' to clear the current input statement.

MariaDB [(none)]> show databases;
+--------------------+
| Database           |
+--------------------+
| information_schema |
| mysql              |
```

```
| orderentry         |
| performance_schema |
| phpmyadmin         |
| praktikum          |
| test               |
+--------------------+
7 rows in set (0.001 sec)

MariaDB [(none)]> create database penjualan_barang;
Query OK, 1 row affected (0.001 sec)

MariaDB [(none)]> use penjualan_barang;
Database changed
MariaDB [penjualan_barang]> create table pelanggan(
    -> id_pelanggan varchar(20) primary key,
    -> nama varchar(30),
    -> alamat varchar(50),
    -> pekerjaan varchar(50),
    -> no_ktp varchar(20),
    -> no_telp varchar(15));
Query OK, 0 rows affected (0.016 sec)

MariaDB [penjualan_barang]> create table nota_penjualan(
    -> id_nota varchar(20) primary key,
    -> tgl_nota date,
    -> total int,
    -> id_pelanggan varchar(20),
    -> foreign key (id_pelanggan) references pelanggan(id_pelanggan));
Query OK, 0 rows affected (0.024 sec)
```

```
MariaDB [penjualan_barang]> create table barang(
    -> id_barang varchar(20) primary key,
    -> nama_barang varchar(30),
    -> harga int,
    -> stok int);
Query OK, 0 rows affected (0.007 sec)

MariaDB [penjualan_barang]> create table detail_jual(
    -> id_nota varchar(20),
    -> id_barang varchar(20),
    -> jumlah int,
    -> harga int,
    -> primary key(id_nota, id_barang),
    -> foreign key(id_nota) references nota_penjualan(id_nota),
    -> foreign key(id_barang) references barang(id_barang));
Query OK, 0 rows affected (0.027 sec)

MariaDB [penjualan_barang]> show tables;
+---------------------------+
| Tables_in_penjualan_barang |
+---------------------------+
| barang                    |
| detail_jual               |
| nota_penjualan            |
| pelanggan                 |
+---------------------------+
4 rows in set (0.001 sec)
```

```
MariaDB [penjualan_barang]> desc barang;
+------------+------------+------+-----+---------+-------+
| Field      | Type       | Null | Key | Default | Extra |
+------------+------------+------+-----+---------+-------+
| id_barang  | varchar(20) | NO   | PRI | NULL    |       |
| nama_barang | varchar(30) | YES  |     | NULL    |       |
| harga      | int(11)    | YES  |     | NULL    |       |
| stok       | int(11)    | YES  |     | NULL    |       |
+------------+------------+------+-----+---------+-------+
4 rows in set (0.011 sec)

MariaDB [penjualan_barang]> desc detail_jual;
+-----------+------------+------+-----+---------+-------+
| Field     | Type       | Null | Key | Default | Extra |
+-----------+------------+------+-----+---------+-------+
| id_nota   | varchar(20) | NO   | PRI | NULL    |       |
| id_barang | varchar(20) | NO   | PRI | NULL    |       |
| jumlah    | int(11)    | YES  |     | NULL    |       |
| harga     | int(11)    | YES  |     | NULL    |       |
+-----------+------------+------+-----+---------+-------+
4 rows in set (0.018 sec)

MariaDB [penjualan_barang]> desc nota_penjualan;
+-------------+------------+------+-----+---------+-------+
| Field       | Type       | Null | Key | Default | Extra |
+-------------+------------+------+-----+---------+-------+
| id_nota     | varchar(20) | NO   | PRI | NULL    |       |
| tgl_nota    | date       | YES  |     | NULL    |       |
| total       | int(11)    | YES  |     | NULL    |       |
```

```
| id_pelanggan | varchar(20) | YES  | MUL | NULL    |       |
+--------------+-------------+------+-----+---------+-------+
4 rows in set (0.009 sec)

MariaDB [penjualan_barang]> desc pelanggan;
+--------------+-------------+------+-----+---------+-------+
| Field        | Type        | Null | Key | Default | Extra |
+--------------+-------------+------+-----+---------+-------+
| id_pelanggan | varchar(20) | NO   | PRI | NULL    |       |
| nama         | varchar(30) | YES  |     | NULL    |       |
| alamat       | varchar(50) | YES  |     | NULL    |       |
| pekerjaan    | varchar(50) | YES  |     | NULL    |       |
| no_ktp       | varchar(20) | YES  |     | NULL    |       |
| no_telp      | varchar(15) | YES  |     | NULL    |       |
+--------------+-------------+------+-----+---------+-------+
6 rows in set (0.018 sec)

MariaDB [penjualan_barang]>
```