

Week 8 Notes

Note | w.r.t = with respect to

Normal Forms

- 1st normal form | 1NF
- 2nd normal form | 2NF
- 3rd normal form | 3NF
- Boyce-Codd normal form | BCNF The higher the normal form the less redundancies

1st Normal Form

A relation is in normal form if all attributes are atomic Usually every table will be in 1st normal form 1NF

Every relation generated from ERD will be in first normal form

Non-Key Attributes

- Any attributes of relation R which are not part of **any** candidate key of R

Partial Dependency

- $X \twoheadrightarrow Y$ is a partial dependency if X is a subset of some candidate key

We can then say that Y is partially dependent on the candidate key

2NF

A relation is in 2NF if there is no non-key attribute in R which is partially dependant on a candidate key of R

Transitive Dependency

Let $X \rightarrow Y$ be an FD that holds for relation R. We say that $X \twoheadrightarrow Y$ if $X \rightarrow Y$ is not a partial dependency and X is not a super key

3NF

A relation is in 3NF if the relation is in 2NF and there iff for every non-trivial FD $\rightarrow X \rightarrow Y$ either X is a superkey of R or Y is a set of key attributes

Normalising to 2NF

B \twoheadrightarrow D Partial Dependency

- Create a new relation (B,D)
- Create a new relation with B and all remaining attributes R1.B is a foreign key to R2.B
- Reinstate FD's on the new relations

Normalising to 3NF

Normalise the tables to 2NF If there is a non trivial FD $X \rightarrow Y$ that violates the definition of the normal form, then decompose the table into two One contains X,Y , the other contains X and all other attributes

Step by Step Approach to Table Normalisation

1NF \rightarrow 2NF | Remove Partial Dependencies 2NF \rightarrow 3NF | Remove transitive Dependencies 3NF \rightarrow BCNF |
Remove functional dependencies where LHS is not a SK