

1.0 MATERIALS OF CONSTRUCTION

Body Material (Primary):	PVC Schedule 80 (Rigid Type 1, Grade 1)
Seat Material:	PTFE (Polytetrafluoroethylene Virgin)
O-Ring Seals:	EPDM Fluoroelastomer Dual Stem Seals
End Connection:	ANSI Class 150# Flanged Pattern

2.0 PRESSURE & TEMPERATURE OPERATING ENVELOPE

Max Operating Temperature:	450 °F (Continuous Service Rating)
Max Working Pressure:	235 PSI @ 73°F (1.62 MPa Non-Shock Water)
Hydrostatic Shell Test:	350 PSI Shell Test
Applicable Standard:	ASTM D1785, ASTM F441, ASME B31.3

3.0 PHYSICAL DIMENSIONS & PIPING SPECIFICATIONS

PARAMETER	SYM	DATASHEET DIMENSION	METRIC EQ.
Outer Diameter (O.D.)	D_o	2.375 in	60.33 mm
Inner Diameter (I.D.)	D_i	2.000 in	50.80 mm
Overall Length (F-to-F)	L	5.50 in	139.70 mm
Flange Diameter	D_f	4.75 in	120.65 mm
Nominal Port Size	d_n	1.50 in	38.10 mm