

Programming assignment 5: Optimization: Logistic regression ¶

```
In [12]: import numpy as np
import matplotlib.pyplot as plt
%matplotlib inline

from sklearn.datasets import load_breast_cancer
from sklearn.model_selection import train_test_split
from sklearn.metrics import accuracy_score, f1_score
```

Your task

In this notebook code skeleton for performing logistic regression with gradient descent is given. Your task is to complete the functions where required. You are only allowed to use built-in Python functions, as well as any `numpy` functions. No other libraries / imports are allowed.

For numerical reasons, we actually minimize the following loss function

$$\mathcal{L}(\mathbf{w}) = \frac{1}{N} NLL(\mathbf{w}) + \frac{1}{2} \lambda \|\mathbf{w}\|_2^2$$

where $NLL(\mathbf{w})$ is the negative log-likelihood function, as defined in the lecture (Eq. 33)

Exporting the results to PDF

Once you complete the assignments, export the entire notebook as PDF and attach it to your homework solutions. The best way of doing that is

1. Run all the cells of the notebook.
2. Download the notebook in HTML (click File > Download as > .html)
3. Convert the HTML to PDF using e.g. <https://www.sejda.com/html-to-pdf> (<https://www.sejda.com/html-to-pdf>) or `wkhtmltopdf` for Linux ([tutorial](https://www.cyberciti.biz/open-source/html-to-pdf-free-linux-osx-windows-software/) (<https://www.cyberciti.biz/open-source/html-to-pdf-free-linux-osx-windows-software/>))
4. Concatenate your solutions for other tasks with the output of Step 3. On a Linux machine you can simply use `pdfunite`, there are similar tools for other platforms too. You can only upload a single PDF file to Moodle.

This way is preferred to using `nbconvert`, since `nbconvert` clips lines that exceed page width and makes your code harder to grade.

Load and preprocess the data

In this assignment we will work with the UCI ML Breast Cancer Wisconsin (Diagnostic) dataset

<https://goo.gl/U2Uwz2> (<https://goo.gl/U2Uwz2>).

Features are computed from a digitized image of a fine needle aspirate (FNA) of a breast mass. They describe characteristics of the cell nuclei present in the image. There are 212 malignant examples and 357 benign examples.

```
In [13]: X, y = load_breast_cancer(return_X_y=True)

# Add a vector of ones to the data matrix to absorb the bias term
X = np.hstack([np.ones([X.shape[0], 1]), X])

# Set the random seed so that we have reproducible experiments
np.random.seed(123)

# Split into train and test
test_size = 0.3
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=test_size)
```

Task 1: Implement the sigmoid function

```
In [14]: def sigmoid(t):
        """
        Applies the sigmoid function elementwise to the input data.

        Parameters
        -----
        t : array, arbitrary shape
            Input data.

        Returns
        -----
        t_sigmoid : array, arbitrary shape.
            Data after applying the sigmoid function.
        """
        # TODO
        t_sigmoid = 1/(1+np.exp(-t))
        return t_sigmoid
```

Task 2: Implement the negative log likelihood

As defined in Eq. 33

```
In [15]: def negative_log_likelihood(X, y, w):
        """
        Negative Log Likelihood of the Logistic Regression.

        Parameters
        -----
        X : array, shape [N, D]
            (Augmented) feature matrix.
        y : array, shape [N]
            Classification targets.
        w : array, shape [D]
            Regression coefficients (w[0] is the bias term).

        Returns
        -----
        nll : float
            The negative log likelihood.
        """
        # TODO
        nll = 0
        for i in range(len(y)):
            nll = nll + (y[i]*np.log(sigmoid(np.dot(X[i],w))) + (1-y[i])*np
        nll = -nll
        return nll
```

Computing the loss function $\mathcal{L}(w)$ (nothing to do here)

```
In [16]: def compute_loss(X, y, w, lambda):
        """
        Negative Log Likelihood of the Logistic Regression.

        Parameters
        -----
        X : array, shape [N, D]
            (Augmented) feature matrix.
        y : array, shape [N]
            Classification targets.
        w : array, shape [D]
            Regression coefficients (w[0] is the bias term).
        lambda : float
            L2 regularization strength.

        Returns
        -----
        loss : float
            Loss of the regularized logistic regression model.
        """
        # The bias term w[0] is not regularized by convention
        return negative_log_likelihood(X, y, w) / len(y) + lambda * np.linalg
```

Task 3: Implement the gradient $\nabla_w \mathcal{L}(w)$

Make sure that you compute the gradient of the loss function $\mathcal{L}(\mathbf{w})$ (not simply the NLL!)

```
In [84]: def get_gradient(X, y, w, mini_batch_indices, lambda):
    """
    Calculates the gradient (full or mini-batch) of the negative log likelihood.

    Parameters
    -----
    X : array, shape [N, D]
        (Augmented) feature matrix.
    y : array, shape [N]
        Classification targets.
    w : array, shape [D]
        Regression coefficients (w[0] is the bias term).
    mini_batch_indices: array, shape [mini_batch_size]
        The indices of the data points to be included in the (stochastic) gradient.
        This includes the full batch gradient as well, if mini_batch_indices is None.
    lambda: float
        Regularization strength. lambda = 0 means having no regularization.

    Returns
    -----
    dw : array, shape [D]
        Gradient w.r.t. w.
    """
    # TODO
    N = len(mini_batch_indices)
    dw = np.dot(X[mini_batch_indices].T, (y[mini_batch_indices] - sigmoid(w.T * X[mini_batch_indices])))

    dw = dw / (-N)

    np.insert(w, 0, 0)
    dw = dw + lambda * w
    return dw
```

Train the logistic regression model (nothing to do here)

```

In [85]: def logistic_regression(X, y, num_steps, learning_rate, mini_batch_size)
        """
        Performs logistic regression with (stochastic) gradient descent.

        Parameters
        -----
        X : array, shape [N, D]
            (Augmented) feature matrix.
        y : array, shape [N]
            Classification targets.
        num_steps : int
            Number of steps of gradient descent to perform.
        learning_rate: float
            The learning rate to use when updating the parameters w.
        mini_batch_size: int
            The number of examples in each mini-batch.
            If mini_batch_size=n_train we perform full batch gradient descent.
        lambda: float
            Regularization strength. lambda = 0 means having no regularization.
        verbose : bool
            Whether to print the loss during optimization.

        Returns
        -----
        w : array, shape [D]
            Optimal regression coefficients (w[0] is the bias term).
        trace: list
            Trace of the loss function after each step of gradient descent.
        """

        trace = [] # saves the value of loss every 50 iterations to be able to plot it
        n_train = X.shape[0] # number of training instances

        w = np.zeros(X.shape[1]) # initialize the parameters to zeros

        # run gradient descent for a given number of steps
        for step in range(num_steps):
            permuted_idx = np.random.permutation(n_train) # shuffle the data

            # go over each mini-batch and update the parameters
            # if mini_batch_size = n_train we perform full batch GD and this is not needed
            for idx in range(0, n_train, mini_batch_size):
                # get the random indices to be included in the mini batch
                mini_batch_indices = permuted_idx[idx:idx+mini_batch_size]
                gradient = get_gradient(X, y, w, mini_batch_indices, lambda)

                # update the parameters
                w = w - learning_rate * gradient

            # calculate and save the current loss value every 50 iterations
            if step % 50 == 0:
                loss = compute_loss(X, y, w, lambda)
                trace.append(loss)
                # print loss to monitor the progress
                if verbose:
                    print('Step {0}, loss = {1:.4f}'.format(step, loss))

```

```
return w, trace
```

Task 4: Implement the function to obtain the predictions

```
In [86]: def predict(X, w):
        """
        Parameters
        -----
        X : array, shape [N_test, D]
            (Augmented) feature matrix.
        w : array, shape [D]
            Regression coefficients (w[0] is the bias term).

        Returns
        -----
        y_pred : array, shape [N_test]
            A binary array of predictions.
        """
        # TODO
        y_pred = []
        for i in range(len(X)):
            y_pred.append((sigmoid(np.dot(w.T, X[i])) >= 0.5).astype(np.int))
        return y_pred
```

Full batch gradient descent

```
In [87]: # Change this to True if you want to see loss values over iterations.
        verbose = False
```

```
In [88]: n_train = X_train.shape[0]
        w_full, trace_full = logistic_regression(X_train,
                                                y_train,
                                                num_steps=8000,
                                                learning_rate=1e-5,
                                                mini_batch_size=n_train,
                                                lambda=0.1,
                                                verbose=verbose)
```

```
In [89]: n_train = X_train.shape[0]
        w_minibatch, trace_minibatch = logistic_regression(X_train,
                                                         y_train,
                                                         num_steps=8000,
                                                         learning_rate=1e-5,
                                                         mini_batch_size=50,
                                                         lambda=0.1,
                                                         verbose=verbose)
```

Our reference solution produces, but don't worry if yours is not exactly the same.

Full batch: accuracy: 0.9240, f1_score: 0.9384

Mini-batch: accuracy: 0.9415, f1_score: 0.9533


```
In [90]: y_pred_full = predict(X_test, w_full)
y_pred_minibatch = predict(X_test, w_minibatch)

print('Full batch: accuracy: {:.4f}, f1_score: {:.4f}'
      .format(accuracy_score(y_test, y_pred_full), f1_score(y_test, y_p
print('Mini-batch: accuracy: {:.4f}, f1_score: {:.4f}'
      .format(accuracy_score(y_test, y_pred_minibatch), f1_score(y_test
```

Full batch: accuracy: 0.9240, f1_score: 0.9384

Mini-batch: accuracy: 0.9357, f1_score: 0.9488

```
In [63]: plt.figure(figsize=[15, 10])
plt.plot(trace_full, label='Full batch')
plt.plot(trace_minibatch, label='Mini-batch')
plt.xlabel('Iterations * 50')
plt.ylabel('Loss  $\mathcal{L}(\mathbf{w})$ ')
plt.legend()
plt.show()
```



In []: