

Special member functions

Zdenko Pavlik

Scheidt&Bachmann Slovakia s.r.o.

Special member functions

... done with support of



Figure 1: scheidt&bachmann

Agenda

- ▶ Lessons learned from previous lesson (Rule of 5)
- ▶ Intro into containers
- ▶ Establishing containers for demonstration

Lessons learned from previous lesson (Rule of 5)

Class has several function, that are used when we alter lifecycle of class (either by new creation, assigning of copying from already existing classes). Each of them can be default, user defined or deleted.

Lessons learned from previous lesson (Rule of 5)

constructor

`NamedClass()`

Called when class is created. Can be default or parametrized.

`NamedClass newClass;`

copy constructor

`NamedClass(const NamedClass& other) // copy constructor`

Called when class is constructed from instance of another class (of the same type).

Member data are **copied**.

`NamedClass newClass = std::copy(otherClass);`

move constructor

`NamedClass(NamedClass&& other) noexcept // move constructor`

Called when class is constructed from instance of another class (of the same type).

Member data are **moved** and instance being moved from is not safe to use anymore!

Benefit is reuse of resources and in general it is faster than copying.

`NamedClass newClass = std::move(otherClass);`

Lessons learned from previous lesson (Rule of 5)

copy assignment operator

`NamedClass& operator=(const NamedClass& other) // copy assignment`

Called when content of the class is overridden by other class using **copy**.

```
newClass = std::copy(otherClass);
```

move assignment operator

`NamedClass& operator=(NamedClass&& other) noexcept // move assignment`

Called when content of the class is overridden by other class using **move**.

```
newClass = std::move(otherClass);
```

Lessons learned from previous lesson (Rule of 5)

Examples

Intro into containers

what are containers, why they exists

Benefits of using std containers

`for (auto i : items){}`

`find_if`

safety bounds checking (`std::vector[10]` on 5 vector of 5 elements -> not accessing random memory) `.at(10)`

`algorithms (std::sort)`

Choosing containers for demonstration

map, list, vector, array

Common characteristics

push, pop, ...

Organization in memory

Organization of map, vector, list, array




Figure 2: List - organization in memory

Algorithm complexity (BigO notation)

	Access by index	Search	Insertion	Deletion
<code>std::array</code>	$O(1)$	$O(N)$	N/A(fixed size)	N/A(fixed size)
<code>std::vector</code>	$O(1)$	$O(N)$	$O(N)$ or $O(1)$	$O(N)$ or $O(1)$
<code>std::list</code>	$O(N)$	$O(N)$	$O(1)$	$O(1)$
<code>std::map</code>	$O(\log N)$	$O(\log N)$	$O(\log N)$	$O(\log N)$

Demonstration of adding/accessing/removing element

On `std::array`

On `std::list`

On `std::vector`

On `std::map`

Disclaimer binary tree (balanced)

Applied BigO notation on container

Explaining logarithm complexity on `std::map`

Lessons learned

Think before you choose a container, because it can have tremendous impact on performance. As well you can cause unintended memory deallocation/allocation.

links

<https://www.geeksforgeeks.org/cpp/where-to-use-a-particular-stl-container-cpp/>