

Zad.1

```
MariaDB [konta]> SELECT COUNT(gid) FROM tabela;  
+-----+  
| COUNT(gid) |  
+-----+  
|          278 |  
+-----+  
1 row in set (0.001 sec)
```

Zad.2

```
MariaDB [konta]> SELECT COUNT(gid) FROM tabela WHERE uid > 1000;  
+-----+  
| COUNT(gid) |  
+-----+  
|          251 |  
+-----+  
1 row in set (0.001 sec)
```

Zad.3

```
MariaDB [konta]> SELECT id FROM tabela WHERE user = "root";  
+-----+  
| id |  
+-----+  
|   1 |  
+-----+  
1 row in set (0.001 sec)
```

Zad.4

```
MariaDB [konta]> SELECT user FROM tabela WHERE uid = (SELECT MAX(uid) FROM tabela);  
+-----+  
| user |  
+-----+  
| iczyz |  
+-----+  
1 row in set (0.001 sec)
```

Zad.5

```
MariaDB [konta]> SELECT id FROM tabela WHERE user IS NULL || uid IS NULL || gid IS NULL;
+-----+
| id |
+-----+
| 25 |
| 278 |
| 279 |
+-----+
3 rows in set (0.001 sec)
```

Zad.6

```
MariaDB [konta]> SELECT * FROM tabela WHERE id > 10 LIMIT 10;
+-----+-----+-----+-----+
| id | user      | uid  | gid  |
+-----+-----+-----+-----+
| 11 | uuff      | 10   | 10   |
| 12 | miłek     | 13   | 13   |
| 13 | prymiarka | 33   | 33   |
| 14 | zawilec   | 34   | 34   |
| 15 | manszard  | 38   | 38   |
| 16 | iro       | 39   | 39   |
| 17 | serduszko | 41   | 41   |
| 18 | golas     | 65534 | 65534 |
| 19 | matek     | 100  | 101  |
| 20 | Debil     | 101  | 103  |
+-----+-----+-----+-----+
10 rows in set (0.000 sec)
```

Zad.7

```
MariaDB [konta]> SELECT gid, COUNT(gid) AS wystapienia FROM tabela GROUP BY gid;
+-----+-----+
| gid | wystapienia |
+-----+-----+
| NULL | 0 |
| 0 | 1 |
| 1 | 1 |
| 2 | 1 |
| 3 | 1 |
| 7 | 1 |
| 8 | 1 |
| 9 | 1 |
| 10 | 1 |
| 12 | 1 |
| 13 | 1 |
| 33 | 1 |
| 34 | 1 |
| 38 | 1 |
| 39 | 1 |
| 41 | 1 |
| 60 | 1 |
| 101 | 1 |
| 103 | 1 |
| 106 | 1 |
| 108 | 1 |
| 110 | 1 |
| 1001 | 1 |
| 1002 | 1 |
| 1003 | 1 |
| 5656 | 1 |
| 45676 | 1 |
| 50000 | 247 |
| 65534 | 5 |
+-----+-----+
29 rows in set (0.001 sec)
```

Zad.8

```
MariaDB [konta]> SELECT user FROM tabela WHERE user BETWEEN "M" AND "T" ORDER BY user;
```

user
mailto
manszard
matek
mbart
mbudy
mcies
mdubi
mdudz
message
mgarn
mgawl
mgnie
mhebd
mhuda
michk
michz
miłek

...

pwier
pwojc
pwojn
pwrob
rchac
rchmi
root
rpopl
rprze
rwala
rwios
serduszko
sgilx
shnat
skocm
slabe
standard
starzec
stroj
styra
suoxx
synek
system
sztat

Zad.9

```
MariaDB [konta]> SELECT (SUBSTR(user,1,1)) as Litera, count(user) as Wystapienia FROM tabela WHERE user BETWEEN "M" AND "T" GROUP BY (SUBSTR(user,1,1));
```

Litera	Wystapienia
m	60
n	5
o	2
p	27
r	7
s	13

```
6 rows in set (0.001 sec)
```

Zad.10

```
MariaDB [konta]> SELECT CONCAT(id, " ", user) AS uzytkownik FROM tabela LIMIT 10;
```

uzytkownik
1 root
2 diabeł
3 kawaler
4 system
5 synek
6 gracz
7 facet
8 starzec
9 mailto
10 news

```
10 rows in set (0.000 sec)
```

WSZYSTKIE ZAPYTANIA

```
MariaDB [konta]> SELECT * FROM zapytania;
```

nr_pyt	pytanie_sql
1	SELECT COUNT(gid) FROM tabela;
2	SELECT COUNT(uid) FROM tabela WHERE uid > 1000;
3	SELECT id FROM tabela WHERE user = "root";
4	SELECT user FROM tabela WHERE uid = (SELECT MAX(uid) FROM tabela);
5	SELECT id FROM tabela WHERE user IS NULL uid IS NULL gid IS NULL;
6	SELECT * FROM tabela WHERE id > 10 LIMIT 10;
7	SELECT gid, COUNT(gid) AS wystapienia FROM tabela GROUP BY gid;
8	SELECT user FROM tabela WHERE user BETWEEN "M" AND "T" ORDER BY user;
9	SELECT (SUBSTR(user,1,1)) as Litera, count(user) as Wystapienia FROM tabela WHERE user BETWEEN "M" AND "T" GROUP BY (SUBSTR(user,1,1));
10	SELECT CONCAT(id, " ", user) AS uzytkownik FROM tabela LIMIT 10;