

10.05.2022

Wykonawcy: Ksawery Zelek , Adrian Starostka

T: Konfiguracja VLANów i separacja portów.

VLANY i PVID

TL-SG105E

192.168.0.10

TL-SG105E

192.168.0.30

192.168.0.20

tp-link

TL-SG105E

System

Switching

Monitoring

VLAN

MTU VLAN

Port Based VLAN

802.1Q VLAN

802.1Q PVID Setting

QoS

Save Config

Logout

802.1Q VLAN Configuration

802.1Q VLAN Configuration: ☒ Enable ☐ Disable

Apply

VLAN ID	Port	Untagged	Tagged	Not Member
Select All				
Port 1	☐	☐	☐	☒
Port 2	☐	☐	☐	☒
Port 3	☐	☐	☐	☒
Port 4	☐	☐	☐	☒
Port 5	☐	☐	☐	☒

Add/Modify

Help

VLAN ID	VLAN Name	Member Ports	Tagged Ports	Untagged Ports	Delete
1	Default_VLAN	1-5		1-5	☐
10	VLAN10	1,4-5	5	1,4	☐

Select All

Delete

Copyright © 2016
TP-LINK Technologies Co., Ltd.
All rights reserved.

1000

10.05.2022

192.168.0.10

TL-SG105E

192.168.0.30

192.168.0.20

tp-link

TL-SG105E

System

Switching

Monitoring

VLAN

MTU VLAN

Port Based VLAN

802.1Q VLAN

802.1Q PVID Setting

QoS

Save Config

Logout

802.1Q VLAN PVID Setting

Select	Port	PVID
☐	Port 1	10
☐	Port 2	1
☐	Port 3	1
☐	Port 4	10
☐	Port 5	1

Apply

Help

Note:

1. By default, the PVID of all ports is 1.

2. 802.1Q VLAN PVID will be restored to 1 when 802.1Q VLAN is disabled.

Copyright © 2016
TP-LINK Technologies Co., Ltd.
All rights reserved.

1000

10.05.2022

T1600G-28TS

Udostępniono G dokument: „D:\...” x PSiUS_10.05.2022_Konfiguracja... x Zadania z zajęć 27i-4/4-PSiUS 2i... x T1600G-28TS x +

Niezabezpieczona | 192.168.0.30

tp-link

T1600G-28TS

VLAN Config Port Config

System
Switching
VLAN
+ 802.1Q VLAN
+ MAC VLAN
+ Protocol VLAN
Spanning Tree
Multicast
Routing
QoS
ACL
Network Security
SNMP
LLDP
Maintenance
Save Config
Index
Logout

VLAN Info

VLAN ID: 20 (1 - 4094)
Name: VLAN20 (16 characters maximum)

Untagged port

UNIT: 1 LAGS

2	4	6	8	10	12	14	16	18	20	22	24	26	28
3	5	7	9	11	13	15	17	19	21	23	25	27	

All Clear

Tagged port

UNIT: 1 LAGS

2	4	6	8	10	12	14	16	18	20	22	24	26	28
3	5	7	9	11	13	15	17	19	21	23	25	27	

All Clear Apply Help

☐ Unselected Port(s) ☒ Selected Port(s) ☐ Not Available for Selection

Copyright © 2016
TP-LINK Technologies Co.,
Ltd. All rights reserved.

09:59
10.05.2022

Udostępniono G dokument: „D:\...” x PSiUS_10.05.2022_Konfiguracja... x Zadania z zajęć 27i-4/4-PSiUS 2i... x T1600G-28TS x +

Niezabezpieczona | 192.168.0.30

tp-link

T1600G-28TS

VLAN Config Port Config

System
Switching
VLAN
+ 802.1Q VLAN
+ MAC VLAN
+ Protocol VLAN
Spanning Tree
Multicast
Routing
QoS
ACL
Network Security
SNMP
LLDP
Maintenance
Save Config
Index
Logout

VLAN Port Config

UNIT: 1 LAGS

Select	Port	PVID	LAG	VLAN
☐	1/0/1	20	---	Detail
☐	1/0/2	1	---	Detail
☐	1/0/3	1	---	Detail
☐	1/0/4	20	---	Detail
☐	1/0/5	1	---	Detail
☐	1/0/6	1	---	Detail
☐	1/0/7	1	---	Detail
☐	1/0/8	1	---	Detail
☐	1/0/9	1	---	Detail
☐	1/0/10	1	---	Detail
☐	1/0/11	1	---	Detail
☐	1/0/12	1	---	Detail
☐	1/0/13	1	---	Detail
☐	1/0/14	1	---	Detail
☐	1/0/15	1	---	Detail

All Apply Help

Copyright © 2016
TP-LINK Technologies Co.,
Ltd. All rights reserved.

09:59
10.05.2022

SPRAWDZENIE DZIAŁANIA VLANÓW

ST"LAN1" -> S"LAN1" VLAN10

```
C:\WINDOWS\system32\cmd.exe
C:\Users\user>ping 192.168.0.40

Pinging 192.168.0.40 with 32 bytes of data:
Reply from 192.168.0.40: bytes=32 time=1ms TTL=128
Reply from 192.168.0.40: bytes=32 time=1ms TTL=128
Reply from 192.168.0.40: bytes=32 time=1ms TTL=128
Reply from 192.168.0.40: bytes=32 time=1ms TTL=128

Ping statistics for 192.168.0.40:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Users\user>
```

ST"LAN1" -> S"WAN" VLAN10

```
C:\WINDOWS\system32\cmd.exe
C:\Users\user>ping 192.168.0.170

Pinging 192.168.0.170 with 32 bytes of data:
Request timed out.

Ping statistics for 192.168.0.170:
    Packets: Sent = 1, Received = 0, Lost = 1 (100% loss),
    Control-C
    ^C

C:\Users\user>
```

ST"LAN2" -> S"WAN"

```
C:\WINDOWS\system32\cmd.exe
C:\Users\user>ping 192.168.0.170
Pinging 192.168.0.170 with 32 bytes of data:
Reply from 192.168.0.170: bytes=32 time=1ms TTL=128
Reply from 192.168.0.170: bytes=32 time=1ms TTL=128
Reply from 192.168.0.170: bytes=32 time=1ms TTL=128
Reply from 192.168.0.170: bytes=32 time=1ms TTL=128
Ping statistics for 192.168.0.170:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
C:\Users\user>
```

ST"LAN2" -> S"LAN1"

```
C:\WINDOWS\system32\cmd.exe
C:\Users\user>ping 192.168.0.40
Pinging 192.168.0.40 with 32 bytes of data:
Reply from 192.168.0.120: Destination host unreachable.
Reply from 192.168.0.120: Destination host unreachable.
Ping statistics for 192.168.0.40:
    Packets: Sent = 2, Received = 2, Lost = 0 (0% loss),
    Control-C
C:\Users\user>
```

IZOLACJA PORTÓW

TL-SG105E widzą się porty 1,4,5

nie da się

T1600G-28TS widzą się porty 1,4,6

The screenshot shows the TP-Link web management interface for a T1600G-28TS switch. The browser tabs indicate the IP address 192.168.0.10 and the device model TL-SG105E. The interface is in Polish, with the URL 'Niezabezpieczona | 192.168.0.30' visible. The left sidebar contains a navigation menu with options like System, Switching, Port, LAG, Traffic Monitor, MAC Address, VLAN, Spanning Tree, Multicast, Routing, QoS, ACL, Network Security, SNMP, LLDP, Maintenance, Save Config, Index, and Logout. The main content area is titled 'T1600G-28TS' and has tabs for Port Config, Port Mirror, Port Security, Port Isolation, and Loopback Detection. The 'Port Isolation' tab is active, displaying a 'Port Isolation List' table. The table has columns for UNIT, Port, LAG, and Forward Portlist. The data shows that for UNIT 1 (LAGS), ports 1/0/1 through 1/0/11 are configured with various forward portlists, including 1/0/4, 1/0/6, and 1/0/1-28 LAG1-14. At the bottom of the table are 'Edit' and 'Help' buttons. The footer of the interface includes copyright information: 'Copyright © 2016 TP-LINK Technologies Co., Ltd. All rights reserved.'

UNIT	Port	LAG	Forward Portlist
1	1/0/1	---	1/0/4, 1/0/6
1	1/0/2	---	1/0/1-28 LAG1-14
1	1/0/3	---	1/0/1-28 LAG1-14
1	1/0/4	---	1/0/1, 1/0/6
1	1/0/5	---	1/0/6
1	1/0/6	---	1/0/1-28 LAG1-14
1	1/0/7	---	1/0/1-28 LAG1-14
1	1/0/8	---	1/0/1-28 LAG1-14
1	1/0/9	---	1/0/1-28 LAG1-14
1	1/0/10	---	1/0/1-28 LAG1-14
1	1/0/11	---	1/0/1-28 LAG1-14