Zebra RFID SDK for iOS Gen2X v1.2.46 — Software Release Notes

Software Release Version	v1.2.46 (iOS SDK Version) / v1.0.9 (iOS App Version)
Release Date	Oct 30, 2026

Contents

Contents 1
Overview 2
Device & Operating System Compatibility 2
Supported Hardware Portfolio 2
Supported Operating Systems Matrix 2
Development Environment & Installation Requirements 3
System & Tooling Requirements 3
Build Configuration 3
Version History & Major Changes 3
v1.0.9 Major Changes Since v1.0.6 3
New Features & Enhancements: 3
v1.0.6 Major Changes 3
New Features & Enhancements: 3
Known Issues / Limitations (optional) 4
Resources & Technical Support 4

Overview

The Zebra RFID SDK for iOS provides a comprehensive, enterprise-grade API suite engineered to unlock the full performance, intelligence, and versatility of Zebra's fixed, integrated, and handheld RFID portfolio. Designed to standardize and accelerate application development, this unified framework delivers consistent tag reading, device management, and multi-transport connectivity across all deployment environments.

Developers can leverage the Zebra RFID Mobile API Reference Applications (available with full source code) to develop new applications or port existing implementations to take complete advantage of advanced reader features.

Device & Operating System Compatibility

Supported Hardware Portfolio

- **Handheld RFID Sleds:** RFD40, RFD40 Premium, RFD40 Premium Plus, RFD4051, and RFD90 (Standard & Long Range)
- **Legacy Handheld Sled:** RFD8500

Supported Operating Systems Matrix

Zebra Device / Reader Family	Supported Host OS Versions
▪ RFD40 / RFD40 Premium / RFD40 Premium Plus ▪ RFD90 (Standard & Long Range)	iOS 17.x, 18.x ,26.x and 27.x
Legacy Handheld Sled ▪ RFD8500	iOS 17.x, 18.x ,26.x and 27.x

Development Environment & Installation Requirements

System & Tooling Requirements

- **Developer Workstation:** A Mac with at least 8 GB of memory is recommended
- **Integrated Development Environment (IDE):** Xcode 16 or later
- **iOS Target Platform:** iOS 17.x, 18.x and 26.x

Build Configuration

Add the SDK Framework to your application

```
#import <ZebraRfidSdkFramework/"Header File Name">
```

Version History & Major Changes

v1.0.9 Major Changes Since v1.0.6

New Features & Enhancements:

1. General: Bug fixes and stability improvements

v1.0.6 Major Changes

New Features & Enhancements:

1. Tag Protect/Unprotect
2. Enable/Disable Visibility
3. Quiet/Unquiet
4. Inventory Protocol
5. Fast ID
6. Custom Tag Quiet
7. Prefilter Support
8. Singulation Support

Known Issues / Limitations (optional)

Quiet timer inconsistencies and intermittent tag quieting failures may occur in high-density tag environments. The default quiet cycle timer has been optimized to 4 seconds per batch (configurable via the 'Quiet Time' text field) to ensure maximum hardware reliability.

Resources & Technical Support

🌐 Zebra RFID Developer Portal: Zebra RFID Developer Portal

⚙️ 123RFID Desktop & Mobile Utilities: Zebra 123RFID Configuration Tools

👥 Zebra RFID Support Community: Zebra Support Community and Downloads

🛠️ Zebra Technical Support: Contact Technical Support