

# 02180: INTRODUCTION TO ARTIFICIAL INTELLIGENCE

## LECTURE 4: NON-DETERMINISM AND PARTIAL OBSERVABILITY

Nina Gierasimczuk



# IDEALISATIONS

So far we have only considered search problems in environments that are:


- ▶ **Single-agent**. There is a single agent acting, the one we control.
- ▶ **Static**. When the agent is not acting, the world doesn't change.
- ▶ **Deterministic**. Every action has a unique outcome.
- ▶ **Fully observable**. The full state description is accessible to the agent.

Problem solving in the real world rarely satisfies these assumptions.

Today, we will drop the assumption of **determinism** and **full observability**.

## RECAP: VACUUM WORLD

**Vacuum World** consists of two locations, each of which may or may not contain dirt and the vacuum is in one of the locations.









## RECAP: VACUUM WORLD

States space consists of each possible configuration ( $2 \times 2^2$  possible states).

- ▶  $s_0$ : Initial state
- ▶  $\text{ACTIONS}(s)$ : for each state three possible actions: L, R, S.
- ▶  $\text{RESULTS}(s, a)$ : applying  $a$  in  $s$  leads to a state  $s'$ .
- ▶  $\text{GOAL-TEST}(s)$ : *are all squares clean?*
- ▶  $\text{STEP-COST}(s, a)$ : each step costs 1.

# RECAP: VACUUM WORLD


POSSIBLE STATES



# RECAP: VACUUM WORLD

## TRANSITION MODEL AND SIMPLE SOLUTION

The transitions in the Vacuum World can be represented as a graph.



# OUTLINE

NON-DETERMINISM

PARTIAL OBSERVABILITY

# THE ERRATIC VACUUM WORLD

Let us consider an erratic vacuum:

- ▶ When applied to a dirty square it cleans the square and sometimes cleans up dirt in an adjacent square, too.
- ▶ When applied to a clean square it sometimes deposits dirt in that square.



# ERRATIC VACUUM WORLD

## PROBLEM DESCRIPTION

- ▶  $s_0$ : Initial state
- ▶  $ACTIONS(s)$ : for each state three possible actions: L, R, S.
- ▶  $RESULTS(s, a)$ : applying  $a$  in  $s$  leads to **a set of states**  $S'$ .
- ▶  $GOAL-TEST(s)$ : *are all squares clean?*
- ▶  $STEP-COST(s, a)$ : each step costs 1.

# ERRATIC VACUUM WORLD

## PROBLEM DESCRIPTION

- ▶  $s_0$ : Initial state
- ▶  $ACTIONS(s)$ : for each state three possible actions: L, R, S.
- ▶  $RESULTS(s, a)$ : applying  $a$  in  $s$  leads to **a set of states**  $S'$ .
- ▶  $GOAL-TEST(s)$ : *are all squares clean?*
- ▶  $STEP-COST(s, a)$ : each step costs 1.

Q: What is a solution to the erratic vacuum problem starting in the state 1?

# REPRESENTING NONDETERMINISM

Search problems with nondeterminism:  $\text{RESULTS}(s, a)$  returns a *set* of states.

**Example.**  $\text{RESULTS}(1, \textit{Suck}) = \{5, 7\}$ .

## REPRESENTING NONDETERMINISM

Search problems with nondeterminism:  $\text{RESULTS}(s, a)$  returns a *set* of states.

**Example.**  $\text{RESULTS}((d, d, 1), \text{Suck}) = \{(c, d, 1), (c, c, 1)\}$ .

# REPRESENTING NONDETERMINISM


Search problems with nondeterminism:  $\text{RESULTS}(s, a)$  returns a *set* of states.

**Example.**  $\text{RESULTS}(1, \textit{Suck}) = \{5, 7\}$ .

# REPRESENTING NONDETERMINISM

Search problems with nondeterminism:  $\text{RESULTS}(s, a)$  returns a *set* of states.


**Example.**  $\text{RESULTS}(1, \textit{Suck}) = \{5, 7\}$ .



# REPRESENTING NONDETERMINISM

Search problems with nondeterminism:  $\text{RESULTS}(s, a)$  returns a *set* of states.

**Example.**  $\text{RESULTS}(1, \text{Suck}) = \{5, 7\}$ .




Non-deterministic action is represented with an **AND node**:  
outgoing edges representing all outcomes **linked by an arc**.

# REPRESENTING NONDETERMINISM

Search problems with nondeterminism:  $\text{RESULTS}(s, a)$  returns a *set* of states.

**Example.**  $\text{RESULTS}(1, \text{Suck}) = \{5, 7\}$ .



Non-deterministic action is represented with an **AND node**: outgoing edges representing all outcomes **linked by an arc**.

**OR** nodes are as usual, with deterministic ACTIONS.



# AND-OR SEARCH TREES


**AND-OR tree** is a tree with levels of AND and OR nodes.

- ▶ Root is OR node (agent choice).
- ▶ OR nodes have outgoing edges for all applicable actions.
- ▶ AND nodes have outgoing edges for all outcomes of action.

# AND-OR SEARCH TREES

**AND-OR tree** is a tree with levels of AND and OR nodes.

- ▶ Root is OR node (agent choice).
- ▶ OR nodes have outgoing edges for all applicable actions.
- ▶ AND nodes have outgoing edges for all outcomes of action.



# SOLUTION TO A NON-DETERMINISTIC SEARCH PROBLEM


A **solution** to a nondeterministic search problem is a subtree  $T'$  of  $T$  s.t.:

1. The root node of  $T$  is in  $T'$ .
2. Every leaf of  $T'$  is a goal state.
3. Every OR node of  $T'$  has exactly one outgoing edge (agent choice).
4. Every AND node of  $T'$  has the same outgoing edges as in  $T$  (nature choice).

# SOLUTION TO A NON-DETERMINISTIC SEARCH PROBLEM

A **solution** to a nondeterministic search problem is a subtree  $T'$  of  $T$  s.t.:

1. The root node of  $T$  is in  $T'$ .
2. Every leaf of  $T'$  is a goal state.
3. Every OR node of  $T'$  has exactly one outgoing edge (agent choice).
4. Every AND node of  $T'$  has the same outgoing edges as in  $T$  (nature choice).



# SOLUTIONS AS CONDITIONAL PLANS AND POLICIES

**Deterministic search problems:** Solution is a path in state space  
it can be turned into a sequence of *ACTIONS* (sequential plan).

# SOLUTIONS AS CONDITIONAL PLANS AND POLICIES

**Deterministic search problems:** Solution is a path in state space  
it can be turned into a sequence of `ACTIONS` (sequential plan).

**Non-deterministic search problems:** Solution is a subtree of state space,  
it can be turned into a conditional plan (contingency plan).

# SOLUTIONS AS CONDITIONAL PLANS AND POLICIES

**Deterministic search problems:** Solution is a path in state space  
it can be turned into a sequence of `ACTIONS` (sequential plan).

**Non-deterministic search problems:** Solution is a subtree of state space,  
it can be turned into a conditional plan (contingency plan).


Language of **conditional plans**:

$$\pi ::= \varepsilon \mid a \mid \text{if } s \text{ then } \pi_1 \text{ else } \pi_2 \mid \pi_1; \pi_2$$

where  $\varepsilon$  is the empty plan,  $a \in \text{ACTIONS}$  and  $s$  is a state.

The construct  $\pi_1; \pi_2$  denotes sequential composition: first execute  $\pi_1$ , then  $\pi_2$ .


# SOLUTIONS AS CONDITIONAL PLANS AND POLICIES



$T'$  as a **conditional plan**:  $\pi = \text{Suck}; \text{if } s_5 \text{ then } (\text{Right}; \text{Suck}).$



# SOLUTIONS AS CONDITIONAL PLANS AND POLICIES



$T'$  as a **conditional plan**:  $\pi = \text{Suck}; \text{if } s_5 \text{ then } (\text{Right}; \text{Suck})$ .

$T'$  as a **policy** (a mapping from states to ACTIONS):

Policy  $\Pi$ :  $\Pi(s_1) = \text{Suck}$ ,  $\Pi(s_5) = \text{Right}$ ,  $\Pi(s_6) = \text{Suck}$ .

# AND-OR GRAPH SEARCH

**function** AND-OR-GRAPH-SEARCH(*problem*) returns a conditional plan, or failure  
OR-SEARCH(*init state of problem*, []) // *problem* is implicit parameter

**function** OR-SEARCH(*state*, *path*)  
  **if** *state* is a goal **then return**  $\varepsilon$  // if in goal state, empty plan suffices  
  **if** *state* is on *path* **then return** failure // fail if looping  
  **for each** *action* applicable in *state* **do** // recursively search for plan  
    *plan*  $\leftarrow$  AND-SEARCH(RESULTS(*state*, *action*), [*state* | *path*])  
    **if** *plan*  $\neq$  failure **then return** *action*; *plan* // append plan to action  
  **return** failure // if all recursive searches for a plan fails

**function** AND-SEARCH(*states*, *path*)  
  **for each**  $s_i$  in *states* **do** // recursively find plans for each outcome state  
    *plan*<sub>*i*</sub>  $\leftarrow$  OR-SEARCH( $s_i$ , *path*)  
    **if** *plan*<sub>*i*</sub> = failure **then return** failure  
  **return** **if**  $s_1$  **then** *plan*<sub>1</sub> **else if**  $s_2$  **then** *plan*<sub>2</sub> **else**  $\dots$  **if**  $s_{n-1}$  **then** *plan* <sub>$n-1$</sub>  **else**  
    *plan*<sub>*n*</sub> // if  $n = 1$  then the returned plan is just *plan*<sub>1</sub>

# AND-OR GRAPH SEARCH

**function** AND-OR-GRAPH-SEARCH(*problem*) returns a conditional plan, or failure  
OR-SEARCH(*init state of problem*, [])      // *problem* is implicit parameter

**function** OR-SEARCH(*state*, *path*)  
  **if** *state* is a goal **then return**  $\varepsilon$       // if in goal state, empty plan suffices  
  **if** *state* is on *path* **then return failure**      // fail if looping  
  **for each** *action* applicable in *state* **do**      // recursively search for plan  
    *plan*  $\leftarrow$  AND-SEARCH(RESULTS(*state*, *action*), [*state* | *path*])  
    **if** *plan*  $\neq$  failure **then return** *action*; *plan*      // append plan to action  
  **return failure**      // if all recursive searches for a plan fails

**function** AND-SEARCH(*states*, *path*)  
  **for each**  $s_i$  in *states* **do**      // recursively find plans for each outcome state  
    *plan<sub>i</sub>*  $\leftarrow$  OR-SEARCH( $s_i$ , *path*)  
    **if** *plan<sub>i</sub>* = failure **then return failure**  
  **return** **if**  $s_1$  **then** *plan<sub>1</sub>* **else if**  $s_2$  **then** *plan<sub>2</sub>* **else**  $\dots$  **if**  $s_{n-1}$  **then** *plan<sub>n-1</sub>* **else**  
    *plan<sub>n</sub>*      // if  $n = 1$  then the returned plan is just *plan<sub>1</sub>*

Q: Which algorithm do we get when all ACTIONS are deterministic?

# THE SLIPPERY VACUUM WORLD


Let us consider a slipping vacuum:

- ▶ everything normal, except that
- ▶ movement action sometimes fails.

# THE SLIPPERY VACUUM WORLD

Let us consider a slipping vacuum:

- ▶ everything normal, except that
- ▶ movement action sometimes fails.



# ACYCLIC AND CYCLIC SOLUTIONS

**Acyclic solutions** are not always possible.

# ACYCLIC AND CYCLIC SOLUTIONS

**Acyclic solutions** are not always possible.

**Cyclic solutions:** Subtrees  $T'$  where every leaf is either a goal or a loop node.

Cyclic solutions guarantee reaching the goal, but only when assuming **fairness**:  
Every possible outcome of an action will eventually happen.

# ACYCLIC AND CYCLIC SOLUTIONS

**Acyclic solutions** are not always possible.

**Cyclic solutions:** Subtrees  $T'$  where every leaf is either a goal or a loop node.

Cyclic solutions guarantee reaching the goal, but only when assuming **fairness**:  
Every possible outcome of an action will eventually happen.

We need a language of conditional plans with loops.

$$\pi ::= \varepsilon \mid a \mid \text{if } s \text{ then } \pi_1 \text{ else } \pi_2 \mid \pi_1; \pi_2 \mid \text{while } cond \text{ do } \pi_1$$

where *cond* is some logical condition.



# ACYCLIC AND CYCLIC SOLUTIONS

**Acyclic solutions** are not always possible.

**Cyclic solutions:** Subtrees  $T'$  where every leaf is either a goal or a loop node.

Cyclic solutions guarantee reaching the goal, but only when assuming **fairness**:  
Every possible outcome of an action will eventually happen.

We need a language of conditional plans with loops.

$$\pi ::= \varepsilon \mid a \mid \text{if } s \text{ then } \pi_1 \text{ else } \pi_2 \mid \pi_1; \pi_2 \mid \text{while } cond \text{ do } \pi_1$$

where *cond* is some logical condition.

The slipping vacuum: *Suck ; Right; while not in 6 do Right; Suck*

# OUTLINE

NON-DETERMINISM

PARTIAL OBSERVABILITY

# LIMITING OBSERVABILITY

We are now back to deterministic domains.

# LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:  
the full state description is observable by the agent.

# LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:  
the full state description is observable by the agent.

Under **partial observability** the full state might not be observable:  
e.g. vacuum cleaning robot not knowing which squares are clean.

# LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:  
the full state description is observable by the agent.

Under **partial observability** the full state might not be observable:  
e.g. vacuum cleaning robot not knowing which squares are clean.

**Null observability**: is the case when *nothing* can be observed about the states.  
Search problems under null observability are called  
**conformant problems** or **sensorless problems**.

# LIMITING OBSERVABILITY

We are now back to deterministic domains.

We considered searching under **full observability**:  
the full state description is observable by the agent.

Under **partial observability** the full state might not be observable:  
e.g. vacuum cleaning robot not knowing which squares are clean.

**Null observability**: is the case when *nothing* can be observed about the states.  
Search problems under null observability are called  
**conformant problems** or **sensorless problems**.

**Example.** Consider the vacuum where it is not known which squares are clean,  
and the robot doesn't have any sensors.

Q: Can the problem still be solved, and if so, what is the solution?

# BELIEF STATES

**Belief state:** A set of (physical) states.

Contains the states considered possible by an agent in a given state.



# BELIEF STATES

**Belief state:** A set of (physical) states.

Contains the states considered possible by an agent in a given state.

We generally use  $s$  for (physical) states and  $b$  for belief states.

# BELIEF STATES

**Belief state:** A set of (physical) states.

Contains the states considered possible by an agent in a given state.

We generally use  $s$  for (physical) states and  $b$  for belief states.

If a problem has  $n$  states, there can be up to  $2^n$  belief states:  
an exponential blow-up in the worst case.

# BELIEF STATES

**Belief state:** A set of (physical) states.

Contains the states considered possible by an agent in a given state.

We generally use  $s$  for (physical) states and  $b$  for belief states.

If a problem has  $n$  states, there can be up to  $2^n$  belief states:  
an exponential blow-up in the worst case.

Conformant problems can be solved by  
any of the standard graph and tree search algorithms (e.g.  $A^*$ ),  
just using belief states instead of physical states.


# BELIEF STATES

Formally, given a fully observable problem  
( $s_0$ , ACTIONS, RESULTS, GOAL-TEST),  
we can define a corresponding conformant problem  
( $b_0$ , ACTIONS', RESULTS', GOAL-TEST')  
with initial belief state  $b_0$  by:


$$\begin{aligned}\text{ACTIONS}'(b) &= \bigcup_{s \in b} \text{ACTIONS}(s) \\ \text{RESULTS}'(b, a) &= \bigcup_{s \in b} \text{RESULTS}(s, a) \\ \text{GOAL-TEST}(b) &= \bigwedge_{s \in b} \text{GOAL-TEST}(s)\end{aligned}$$

# CONFORMANT SEARCH

## DETERMINISTIC SENSORLESS VACUUM




# SEARCHING WITH OBSERVATIONS (SENSING)



Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

## SEARCHING WITH OBSERVATIONS (SENSING)




Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

Q1: What would then be a solution to the cleaning problem?

# SEARCHING WITH OBSERVATIONS (SENSING)



Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.


Suppose the number of *Suck* actions have to be minimised.

Q1: What would then be a solution to the cleaning problem?

Q2: Can we use the GRAPH-SEARCH to solve problems with partial observability and sensing?



# SEARCHING WITH OBSERVATIONS (SENSING)



Assume the robot doesn't initially know which squares are dirty, but it has a *Sense* action to check whether the current square is clean or dirty.

Suppose the number of *Suck* actions have to be minimised.

Q1: What would then be a solution to the cleaning problem?

Q2: Can we use the GRAPH-SEARCH to solve problems with partial observability and sensing?

Q3: And what about AND-OR-GRAPH-SEARCH?

# PERCEPTS AS A MODEL FOR SENSING

A general treatment of observations/sensing under partial observability:  
including a new function in the problem description:  $\text{PERCEPT}(s)$   
which codes the observation made by the agent in state  $s$ .

# PERCEPTS AS A MODEL FOR SENSING

A general treatment of observations/sensing under partial observability:  
including a new function in the problem description:  $\text{PERCEPT}(s)$   
which codes the observation made by the agent in state  $s$ .

**Example:**  $\text{PERCEPT}(s) = \textit{dirty/clean}$ .


# PERCEPTS AS A MODEL FOR SENSING

A general treatment of observations/sensing under partial observability:  
including a new function in the problem description:  $\text{PERCEPT}(s)$   
which codes the observation made by the agent in state  $s$ .

**Example:**  $\text{PERCEPT}(s) = \text{dirty/clean}$ .

Full observability corresponds to  $\text{PERCEPT}(s) = \{s\}$ .

Null observability corresponds to  $\text{PERCEPT}(s) = \emptyset$ .



# THE NEW RESULTS FUNCTION

We define the following new functions:

1. POSSIBLE-PERCEPTS takes a belief state  $b$  and returns all the observations that are possible to receive in that belief state:

$$\text{POSSIBLE-PERCEPTS}(b) = \{\text{PERCEPT}(s) \mid s \in b\}.$$

2. UPDATE takes a belief state  $b$  and an observation  $o$  and filters away the states that are not consistent with the observation:

$$\text{UPDATE}(b, o) = \{s \in b \mid o = \text{PERCEPT}(s)\}.$$


So  $\text{UPDATE}(b, o)$  is the updated belief an agent has after having received observation  $o$  in belief state  $b$ .

New RESULTS function on belief states that takes observations into account:


$$\text{RESULTS}'(b, a) = \left\{ \text{UPDATE}\left(\bigcup_{s \in b} \text{RESULTS}(s, a), o\right) \mid o \in \text{POSSIBLE-PERCEPTS}\left(\bigcup_{s \in b} \text{RESULTS}(s, a)\right) \right\}$$

Note that  $\text{RESULTS}(b, a)$  is a set of belief states, that is, a set of sets of states.

# FROM FULL TO PARTIAL OBSERVABILITY TO MULTIPLE AGENTS



# FROM FULL TO PARTIAL OBSERVABILITY TO MULTIPLE AGENTS



Such models are one of the main topics of the course 02287.

THE END OF LECTURE 4