

# 02180: INTRODUCTION TO ARTIFICIAL INTELLIGENCE

## LECTURE 10: LOGICAL INFERENCE

Nina Gierasimczuk



# OUTLINE

PROPOSITIONAL THEOREM PROVING

RESOLUTION

HORN CLAUSES AND DEFINITE CLAUSES

EFFECTIVE PROPOSITIONAL MODEL CHECKING

# OUTLINE

PROPOSITIONAL THEOREM PROVING

RESOLUTION

HORN CLAUSES AND DEFINITE CLAUSES

EFFECTIVE PROPOSITIONAL MODEL CHECKING

# TRUTH-TABLE METHOD FOR INFERENCE

The most intuitive way to check validity of inference by brut-force truth-tables.

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well in the exam.
- ▶  $\varphi$ : Robert is not prepared.
- ▶ Question:  $KB \models \varphi$ ?

# TRUTH-TABLE METHOD FOR INFERENCE

The most intuitive way to check validity of inference by brut-force truth-tables.

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well in the exam.
- ▶  $\varphi$ : Robert is not prepared.
- ▶ Question:  $KB \models \varphi$ ?

$r$	$p$	$\ell$	$p \vee \ell$	$r \leftrightarrow p \vee \ell$	$\neg r$	$\neg p$
0	0	0	0	1	1	1
0	0	1	1	0	1	1
0	1	0	1	0	1	0
0	1	1	1	0	1	0
1	0	0	0	0	0	1
1	0	1	1	1	0	1
1	1	0	1	1	0	0
1	1	1	1	1	0	0

# TRUTH-TABLE METHOD FOR INFERENCE

The most intuitive way to check validity of inference by brut-force truth-tables.

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well in the exam.
- ▶  $\varphi$ : Robert is not prepared.
- ▶ Question:  $KB \models \varphi$ ?

$r$	$p$	$\ell$	$p \vee \ell$	$r \leftrightarrow p \vee \ell$	$\neg r$	$\neg p$
0	0	0	0	1	1	1
0	0	1	1	0	1	1
0	1	0	1	0	1	0
0	1	1	1	0	1	0
1	0	0	0	0	0	1
1	0	1	1	1	0	1
1	1	0	1	1	0	0
1	1	1	1	1	0	0

# SEMANTIC VS SYNTACTIC APPROACH

- ▶ (Semantic) model checking:  
enumerating models and showing it holds in all models.
- ▶ (Syntactic) theorem proving:  
applying rules of inference directly to the sentences in our knowledge base to construct a proof of the desired sentence without consulting models.

# SEMANTIC VS SYNTACTIC APPROACH

- ▶ (Semantic) model checking:  
enumerating models and showing it holds in all models.
- ▶ (Syntactic) theorem proving:  
applying rules of inference directly to the sentences in our knowledge base to construct a proof of the desired sentence without consulting models.

**Reason:** If the number of models is large but the length of the proof is short, then theorem proving can be more efficient than model checking.



# SOME CRUCIAL CONCEPTS

- **Logical equivalence**

two formulas  $\varphi$  and  $\psi$  are logically equivalent:

if they are true in the same set of models, or

if each of them entails the other:  $\varphi \equiv \psi$  if and only if  $\varphi \models \psi$  and  $\psi \models \varphi$ .

# SOME CRUCIAL CONCEPTS

- **Logical equivalence**

two formulas  $\varphi$  and  $\psi$  are logically equivalent:

if they are true in the same set of models, or

if each of them entails the other:  $\varphi \equiv \psi$  if and only if  $\varphi \models \psi$  and  $\psi \models \varphi$ .

- **Validity (tautology)**

$\varphi$  is valid if it is true in all models.

Every valid sentence is logically equivalent to  $\top$ .

# SOME CRUCIAL CONCEPTS

- **Logical equivalence**

two formulas  $\varphi$  and  $\psi$  are logically equivalent:

if they are true in the same set of models, or

if each of them entails the other:  $\varphi \equiv \psi$  if and only if  $\varphi \models \psi$  and  $\psi \models \varphi$ .

- **Validity (tautology)**

$\varphi$  is valid if it is true in all models.

Every valid sentence is logically equivalent to  $\top$ .

- **Satisfiability**

$\varphi$  is satisfiable if it is true in some model.

**The SAT problem**, determining the satisfiability of sentences, was the first problem shown to be NP-complete.

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

THEOREM (SEMANTIC DEDUCTION THEOREM)

*For any sentences  $\varphi$  and  $\psi$  of propositional logic*

*$\varphi \models \psi$  if and only if  $\varphi \rightarrow \psi$  is valid.*



# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

THEOREM (SEMANTIC DEDUCTION THEOREM)

*For any sentences  $\varphi$  and  $\psi$  of propositional logic*

*$\varphi \models \psi$  if and only if  $\varphi \rightarrow \psi$  is valid.*

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

THEOREM (SEMANTIC DEDUCTION THEOREM)

*For any sentences  $\varphi$  and  $\psi$  of propositional logic*

*$\varphi \models \psi$  if and only if  $\varphi \rightarrow \psi$  is valid.*

$\varphi \models \psi$  if and only if the sentence  $(\varphi \wedge \neg\psi)$  is ?

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

## THEOREM (SEMANTIC DEDUCTION THEOREM)

*For any sentences  $\varphi$  and  $\psi$  of propositional logic*

*$\varphi \models \psi$  if and only if  $\varphi \rightarrow \psi$  is valid.*

$\varphi \models \psi$  if and only if the sentence  $(\varphi \wedge \neg\psi)$  is ?  
go to [www.menti.com](https://www.menti.com), enter digit code: 66 60 28 6

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

THEOREM (SEMANTIC DEDUCTION THEOREM)

*For any sentences  $\varphi$  and  $\psi$  of propositional logic*

*$\varphi \models \psi$  if and only if  $\varphi \rightarrow \psi$  is valid.*

$\varphi \models \psi$  if and only if the sentence  $(\varphi \wedge \neg\psi)$  is

...

# VALIDITY AND SATISFIABILITY

$\varphi$  is valid iff  $\neg\varphi$  is unsatisfiable

$\varphi$  is satisfiable iff  $\neg\varphi$  is not valid

## THEOREM (SEMANTIC DEDUCTION THEOREM)

*For any sentences  $\varphi$  and  $\psi$  of propositional logic*

*$\varphi \models \psi$  if and only if  $\varphi \rightarrow \psi$  is valid.*

$\varphi \models \psi$  if and only if the sentence  $(\varphi \wedge \neg\psi)$  is

...

**(reductio ad absurdum, proof by refutation, proof by contradiction)**

# INFERENCE AND PROOFS

Inference rules are applied to derive a **proof of a formula**:  
a chain of conclusions that leads to the formula.

# INFERENCE AND PROOFS

Inference rules are applied to derive a **proof of a formula**:  
a chain of conclusions that leads to the formula.

## Examples of inference rules

$$\frac{\varphi \rightarrow \psi, \varphi}{\psi}$$

(Modus Ponens)

$$\frac{\varphi \wedge \psi}{\varphi}$$

(And-Elimination)

# USING SEARCH ALGORITHMS TO FIND PROOFS

A friendly statement of the theorem proving problem as a search problem:

- ▶ **Initial state:** the initial knowledge base.
- ▶ **Actions:** the inference rules.
- ▶ **Result:** the result of an action is to add the conclusion to  $KB$ .
- ▶ **Goal:** the sentence we are trying to prove.



# MONOTONICITY

In **monotonic logics** the set of entailed sentences can only increase as information is added to the knowledge base.

For any sentences  $\varphi$  and  $\psi$ , if  $KB \models \varphi$  then  $KB \cup \psi \models \varphi$ .

Note: **non-monotonic logics**, which violate the monotonicity property, capture a common property of human reasoning: changing one's mind.

# OUTLINE

PROPOSITIONAL THEOREM PROVING

RESOLUTION

HORN CLAUSES AND DEFINITE CLAUSES

EFFECTIVE PROPOSITIONAL MODEL CHECKING

## RESOLUTION: ONE RULE TO RULE THEM ALL

$$\frac{\ell_1 \vee \dots \vee \ell_k, m}{\ell_1 \vee \dots \vee \ell_{i-1} \vee \ell_{i+1} \vee \dots \vee \ell_k} \quad \text{(Unit Resolution)}$$

where literals  $\ell_i$  and  $m$  are complementary (i.e., one is negation of the other).

## RESOLUTION: ONE RULE TO RULE THEM ALL

$$\frac{\ell_1 \vee \dots \vee \ell_k, m}{\ell_1 \vee \dots \vee \ell_{i-1} \vee \ell_{i+1} \vee \dots \vee \ell_k} \quad \text{(Unit Resolution)}$$

where literals  $\ell_i$  and  $m$  are complementary (i.e., one is negation of the other).

$$\frac{\ell_1 \vee \dots \vee \ell_k, m_1 \vee \dots \vee m_n}{\ell_1 \vee \dots \vee \ell_{i-1} \vee \ell_{i+1} \vee \dots \vee \ell_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n} \quad \text{(Full Resolution)}$$

where literals  $\ell_i$  and  $m_j$  are complementary (i.e., one is negation of the other).

## RESOLUTION: ONE RULE TO RULE THEM ALL

$$\frac{\ell_1 \vee \dots \vee \ell_k, m}{\ell_1 \vee \dots \vee \ell_{i-1} \vee \ell_{i+1} \vee \dots \vee \ell_k} \quad \text{(Unit Resolution)}$$

where literals  $\ell_i$  and  $m$  are complementary (i.e., one is negation of the other).

$$\frac{\ell_1 \vee \dots \vee \ell_k, m_1 \vee \dots \vee m_n}{\ell_1 \vee \dots \vee \ell_{i-1} \vee \ell_{i+1} \vee \dots \vee \ell_k \vee m_1 \vee \dots \vee m_{j-1} \vee m_{j+1} \vee \dots \vee m_n} \quad \text{(Full Resolution)}$$

where literals  $\ell_i$  and  $m_j$  are complementary (i.e., one is negation of the other).

Practical comment: mind the **Factoring** (removing duplicates)!

E.g., if we resolve  $(A \vee B)$  with  $(A \vee \neg B)$ , we obtain  $(A \vee A)$ .

Single  $A$  is enough!

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF?

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

## EXAMPLE

Robert will pass the exam if and only if he will be prepared or lucky.



# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

## EXAMPLE

Robert will pass the exam if and only if he will be prepared or lucky.

$$r \leftrightarrow p \vee s$$

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

## EXAMPLE

Robert will pass the exam if and only if he will be prepared or lucky.

$$r \leftrightarrow p \vee s$$

1. Eliminate  $\leftrightarrow$ :  $(r \rightarrow p \vee s) \wedge (p \vee s \rightarrow r)$ .

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

## EXAMPLE

Robert will pass the exam if and only if he will be prepared or lucky.

$$r \leftrightarrow p \vee s$$

1. Eliminate  $\leftrightarrow$ :  $(r \rightarrow p \vee s) \wedge (p \vee s \rightarrow r)$ .
2. Eliminate  $\rightarrow$ :  $(\neg r \vee p \vee s) \wedge (\neg(p \vee s) \vee r)$ .

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

## EXAMPLE

Robert will pass the exam if and only if he will be prepared or lucky.

$$r \leftrightarrow p \vee s$$

1. Eliminate  $\leftrightarrow$ :  $(r \rightarrow p \vee s) \wedge (p \vee s \rightarrow r)$ .
2. Eliminate  $\rightarrow$ :  $(\neg r \vee p \vee s) \wedge (\neg(p \vee s) \vee r)$ .
3. Move  $\neg$  inwards (De Morgan):  $(\neg r \vee p \vee s) \wedge ((\neg p \wedge \neg s) \vee r)$ .

# CONJUNCTIVE NORMAL FORM (CNF)

- ▶ Resolution applies to clauses (disjunctions of literals).
- ▶ So, KBs should then be coded as conjunctions of clauses (CNFs).
- ▶ Can any sentence of propositional logic be translated into CNF? **YES!**

## EXAMPLE

Robert will pass the exam if and only if he will be prepared or lucky.

$$r \leftrightarrow p \vee s$$

1. Eliminate  $\leftrightarrow$ :  $(r \rightarrow p \vee s) \wedge (p \vee s \rightarrow r)$ .
2. Eliminate  $\rightarrow$ :  $(\neg r \vee p \vee s) \wedge (\neg(p \vee s) \vee r)$ .
3. Move  $\neg$  inwards (De Morgan):  $(\neg r \vee p \vee s) \wedge ((\neg p \wedge \neg s) \vee r)$ .
4. Distribute  $\wedge$  over  $\vee$ :  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r)$ .

# A RESOLUTION ALGORITHM

To show that  $KB \models \varphi$ , we show that  $KB \wedge \neg\varphi$  is unsatisfiable.  
We do this by proving a contradiction.

1. First,  $KB \wedge \neg\varphi$  is converted into CNF.

# A RESOLUTION ALGORITHM

To show that  $KB \models \varphi$ , we show that  $KB \wedge \neg\varphi$  is unsatisfiable.  
We do this by proving a contradiction.

1. First,  $KB \wedge \neg\varphi$  is converted into CNF.
2. Then, the resolution rule is applied to the resulting clauses.

# A RESOLUTION ALGORITHM

To show that  $KB \models \varphi$ , we show that  $KB \wedge \neg\varphi$  is unsatisfiable.

We do this by proving a contradiction.

1. First,  $KB \wedge \neg\varphi$  is converted into CNF.
2. Then, the resolution rule is applied to the resulting clauses.
3. Each pair that contains complementary literals is resolved to produce a new clause, which is added to the set if it is not already present.



# A RESOLUTION ALGORITHM

To show that  $KB \models \varphi$ , we show that  $KB \wedge \neg\varphi$  is unsatisfiable.  
We do this by proving a contradiction.

1. First,  $KB \wedge \neg\varphi$  is converted into CNF.
2. Then, the resolution rule is applied to the resulting clauses.
3. Each pair that contains complementary literals is resolved to produce a new clause, which is added to the set if it is not already present.
4. The process continues until one of two things happens:
  - A there are no new clauses that can be added, in which case  $KB$  does not entail  $\varphi$ ; or,
  - B two clauses resolve to yield the empty clause, in which case  $KB$  entails  $\varphi$ .

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
- ▶  $\varphi$ : Robert is not prepared.
- ▶ Question:  $KB \models \varphi$ ?

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.
  2.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r \wedge p$ , CNF for contradiction.

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.
  2.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r \wedge p$ , CNF for contradiction.
  3.  $clauses := (\neg r \vee p \vee s), (\neg p \vee r), (\neg s \vee r), \neg r, p$ .

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.
  2.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r \wedge p$ , CNF for contradiction.
  3.  $clauses := (\neg r \vee p \vee s), (\neg p \vee r), (\neg s \vee r), \neg r, p$ .
  4.  $clauses := clauses \cup \{r\}$  from resolving  $(\neg p \vee r)$  with  $p$ .

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.
  2.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r \wedge p$ , CNF for contradiction.
  3.  $clauses := (\neg r \vee p \vee s), (\neg p \vee r), (\neg s \vee r), \neg r, p$ .
  4.  $clauses := clauses \cup \{r\}$  from resolving  $(\neg p \vee r)$  with  $p$ .
  5.  $clauses := clauses \cup \{\perp\}$  from resolving  $r$  with  $\neg r$ .

## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.
  2.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r \wedge p$ , CNF for contradiction.
  3.  $clauses := (\neg r \vee p \vee s), (\neg p \vee r), (\neg s \vee r), \neg r, p$ .
  4.  $clauses := clauses \cup \{r\}$  from resolving  $(\neg p \vee r)$  with  $p$ .
  5.  $clauses := clauses \cup \{\perp\}$  from resolving  $r$  with  $\neg r$ .
  6. Result: empty clause, so



## EXAMPLE

- ▶  $KB$ : Robert does well in the exam if and only if he is prepared or lucky.  
Robert does not do well the exam.
  - ▶  $\varphi$ : Robert is not prepared.
  - ▶ Question:  $KB \models \varphi$ ?
1.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r$ , formalisation of  $KB$  as CNF.
  2.  $(\neg r \vee p \vee s) \wedge (\neg p \vee r) \wedge (\neg s \vee r) \wedge \neg r \wedge p$ , CNF for contradiction.
  3.  $clauses := (\neg r \vee p \vee s), (\neg p \vee r), (\neg s \vee r), \neg r, p$ .
  4.  $clauses := clauses \cup \{r\}$  from resolving  $(\neg p \vee r)$  with  $p$ .
  5.  $clauses := clauses \cup \{\perp\}$  from resolving  $r$  with  $\neg r$ .
  6. Result: empty clause, so  $KB \models \varphi$ .

# RESOLUTION ALGORITHM IS GOOD

1. Always terminates.
2. Is complete, by the **ground resolution theorem**: If a set of clauses is unsatisfiable, then the resolution closure of those clauses contains the empty clause.

# OUTLINE

PROPOSITIONAL THEOREM PROVING

RESOLUTION

HORN CLAUSES AND DEFINITE CLAUSES

EFFECTIVE PROPOSITIONAL MODEL CHECKING

# SPECIAL KINDS OF CLAUSES

Sometimes it's enough if we restrict the language to special types of clauses:

## DEFINITION

A **definite clause** is a clause of literals of which exactly one is positive.

For example:  $(\neg p \vee \neg s \vee r)$  is a definite clause, while  $(p \vee s \vee \neg r)$  is not.

# SPECIAL KINDS OF CLAUSES

Sometimes it's enough if we restrict the language to special types of clauses:

## DEFINITION

A **definite clause** is a clause of literals of which exactly one is positive.

For example:  $(\neg p \vee \neg s \vee r)$  is a definite clause, while  $(p \vee s \vee \neg r)$  is not.

## DEFINITION

A **Horn clause** is a disjunction of literals of which at most one is positive.

# SPECIAL KINDS OF CLAUSES

Sometimes it's enough if we restrict the language to special types of clauses:

## DEFINITION

A **definite clause** is a clause of literals of which exactly one is positive.

For example:  $(\neg p \vee \neg s \vee r)$  is a definite clause, while  $(p \vee s \vee \neg r)$  is not.

## DEFINITION

A **Horn clause** is a disjunction of literals of which at most one is positive.

All definite clauses are Horn clauses, as are clauses with no positive literals (**goal clauses**).

# SPECIAL KINDS OF CLAUSES

Sometimes it's enough if we restrict the language to special types of clauses:

## DEFINITION

A **definite clause** is a clause of literals of which exactly one is positive.

For example:  $(\neg p \vee \neg s \vee r)$  is a definite clause, while  $(p \vee s \vee \neg r)$  is not.

## DEFINITION

A **Horn clause** is a disjunction of literals of which at most one is positive.

All definite clauses are Horn clauses, as are clauses with no positive literals (**goal clauses**).

Horn clauses are closed under resolution:

if you resolve two Horn clauses, you get back a Horn clause.

# THE IMPORTANCE OF HORN CLAUSES

Why are Horn clauses interesting?



# THE IMPORTANCE OF HORN CLAUSES

Why are Horn clauses interesting?

- ▶ Definite clause can be written as an implication whose premise is a conjunction of positive literals and whose conclusion is a single positive literal. E.g.,  $(\neg p \vee \neg s \vee r)$  is equivalent to  $(p \wedge s) \rightarrow r$ . The premise is called the **body** and the conclusion is called the **head**. A sentence consisting of a single positive literal, such as  $r$ , is called a **fact** ( $\top \rightarrow r$ ).

# THE IMPORTANCE OF HORN CLAUSES

Why are Horn clauses interesting?

- ▶ Definite clause can be written as an implication whose premise is a conjunction of positive literals and whose conclusion is a single positive literal. E.g.,  $(\neg p \vee \neg s \vee r)$  is equivalent to  $(p \wedge s) \rightarrow r$ . The premise is called the **body** and the conclusion is called the **head**. A sentence consisting of a single positive literal, such as  $r$ , is called a **fact** ( $\top \rightarrow r$ ).
- ▶ Inference with Horn clauses can be done by **forward-** and **backward-chaining**.

# THE IMPORTANCE OF HORN CLAUSES

Why are Horn clauses interesting?

- ▶ Definite clause can be written as an implication whose premise is a conjunction of positive literals and whose conclusion is a single positive literal. E.g.,  $(\neg p \vee \neg s \vee r)$  is equivalent to  $(p \wedge s) \rightarrow r$ . The premise is called the **body** and the conclusion is called the **head**. A sentence consisting of a single positive literal, such as  $r$ , is called a **fact** ( $\top \rightarrow r$ ).
- ▶ Inference with Horn clauses can be done by **forward-** and **backward-chaining**.
- ▶ Deciding entailment with Horn clauses is **linear** in the size of the knowledge base.

# FORWARD- AND BACKWARD-CHAINING ON AND-OR GRAPHS

$$P \Rightarrow Q$$

$$L \wedge M \Rightarrow P$$


$$B \wedge L \Rightarrow M$$

$$A \wedge P \Rightarrow L$$

$$A \wedge B \Rightarrow L$$

$A$

$B$



# OUTLINE

PROPOSITIONAL THEOREM PROVING

RESOLUTION

HORN CLAUSES AND DEFINITE CLAUSES

EFFECTIVE PROPOSITIONAL MODEL CHECKING

# GENERAL MODEL-CHECKING ALGORITHMS FOR PROPOSITIONAL INFERENCE

- ▶ the algorithms checking satisfiability: the SAT problem
- ▶ testing entailment  $\varphi \models \psi$ , is done by testing unsatisfiability of  $\varphi \wedge \neg\psi$

# DAVIS-PUTNAM ALGORITHM (DPLL ALGORITHM)

DPLL is an improvement on the truth-table method that works on CNFs.

# DAVIS-PUTNAM ALGORITHM (DPLL ALGORITHM)

DPLL is an improvement on the truth-table method that works on CNFs.

Improvements over TT:

1. **Early termination**, e.g., if  $(A \vee B) \wedge (A \vee C)$  is true if  $A$  is true, regardless of  $B$  and  $C$ .



# DAVIS-PUTNAM ALGORITHM (DPLL ALGORITHM)

DPLL is an improvement on the truth-table method that works on CNFs.

Improvements over TT:

1. **Early termination**, e.g., if  $(A \vee B) \wedge (A \vee C)$  is true if  $A$  is true, regardless of  $B$  and  $C$ .
2. **Pure symbol heuristic**, e.g., in  $(A \vee \neg B)$ ,  $(\neg B \vee \neg C)$ ,  $(C \vee A)$ , the symbol  $A$  is pure. If a sentence has a model, then it has a model with the pure symbols assigned so as to make their literals true, because doing so can never make a clause false.

# DAVIS-PUTNAM ALGORITHM (DPLL ALGORITHM)

DPLL is an improvement on the truth-table method that works on CNFs.

Improvements over TT:

1. **Early termination**, e.g., if  $(A \vee B) \wedge (A \vee C)$  is true if  $A$  is true, regardless of  $B$  and  $C$ .
2. **Pure symbol heuristic**, e.g., in  $(A \vee \neg B)$ ,  $(\neg B \vee \neg C)$ ,  $(C \vee A)$ , the symbol  $A$  is pure. If a sentence has a model, then it has a model with the pure symbols assigned so as to make their literals true, because doing so can never make a clause false.
3. **Unit clause heuristic**, e.g., if the model contains  $B = \top$ , then  $(\neg B \vee \neg C)$  simplifies to  $\neg C$ , which is a unit clause. Assigning one unit clause can create another unit clause, such 'cascade' of forced assignments is called **unit propagation**.

# DAVIS-PUTNAM ALGORITHM (DPLL ALGORITHM)

**function** DPLL-SATISFIABLE?(*s*) **returns** *true* or *false*

**inputs:** *s*, a sentence in propositional logic

*clauses*  $\leftarrow$  the set of clauses in the CNF representation of *s*

*symbols*  $\leftarrow$  a list of the proposition symbols in *s*

**return** DPLL(*clauses*, *symbols*, { })

---

**function** DPLL(*clauses*, *symbols*, *model*) **returns** *true* or *false*

**if** every clause in *clauses* is true in *model* **then return** *true*

**if** some clause in *clauses* is false in *model* **then return** *false*

*P*, *value*  $\leftarrow$  FIND-PURE-SYMBOL(*symbols*, *clauses*, *model*)

**if** *P* is non-null **then return** DPLL(*clauses*, *symbols* - *P*, *model*  $\cup$  { *P*=*value* })

*P*, *value*  $\leftarrow$  FIND-UNIT-CLAUSE(*clauses*, *model*)

**if** *P* is non-null **then return** DPLL(*clauses*, *symbols* - *P*, *model*  $\cup$  { *P*=*value* })

*P*  $\leftarrow$  FIRST(*symbols*); *rest*  $\leftarrow$  REST(*symbols*)

**return** DPLL(*clauses*, *rest*, *model*  $\cup$  { *P*=*true* }) **or**

DPLL(*clauses*, *rest*, *model*  $\cup$  { *P*=*false* })

# WALKSAT ALGORITHM

- ▶ Local search algorithms can be applied to SAT problem given the right evaluation function.

# WALKSAT ALGORITHM

- ▶ Local search algorithms can be applied to SAT problem given the right evaluation function.
- ▶ The goal is to find an assignment that satisfies every clause, so
- ▶ evaluation function counts the number of unsatisfied clauses.

# WALKSAT ALGORITHM

- ▶ Local search algorithms can be applied to SAT problem given the right evaluation function.
- ▶ The goal is to find an assignment that satisfies every clause, so
- ▶ evaluation function counts the number of unsatisfied clauses.
- ▶ We flip the truth value of one symbol at a time and escape local minima with randomness.

# WALKSAT ALGORITHM

- ▶ Local search algorithms can be applied to SAT problem given the right evaluation function.
- ▶ The goal is to find an assignment that satisfies every clause, so
- ▶ evaluation function counts the number of unsatisfied clauses.
- ▶ We flip the truth value of one symbol at a time and escape local minima with randomness.

**WalkSat:** On every iteration, the algorithm picks an unsatisfied clause and picks a symbol in the clause to flip. It chooses randomly between two ways to pick which symbol to flip:

1. a **min-conflicts** step that minimises the number of unsatisfied clauses in the new state, and
2. a **random walk** step that picks the symbol randomly.

# WALKSAT ALGORITHM

**function** WALKSAT(*clauses*, *p*, *max\_flips*) **returns** a satisfying model or *failure*

**inputs:** *clauses*, a set of clauses in propositional logic

*p*, the probability of choosing to do a “random walk” move, typically around 0.5

*max\_flips*, number of flips allowed before giving up

*model*  $\leftarrow$  a random assignment of *true/false* to the symbols in *clauses*

**for** *i* = 1 **to** *max\_flips* **do**

**if** *model* satisfies *clauses* **then return** *model*

*clause*  $\leftarrow$  a randomly selected clause from *clauses* that is false in *model*

**with probability** *p* flip the value in *model* of a randomly selected symbol from *clause*

**else** flip whichever symbol in *clause* maximizes the number of satisfied clauses

**return** *failure*



End of Lecture 10