cat - concatenate files and print on the standard output

YNOPSIS

cat [<u>OPTION</u>]... [FILE]...

DESCRIPTION

Concatenate FILE(s), or standard input, to standard output.

-A, --show-all equivalent to -vET

--number-nonblank P,

number nonempty output lines, overrides -n

equivalent to -vE φ

--show-ends É

display \$ at end of each line

−n, −−number

number all output lines

--squeeze-blank ŝ

suppress repeated empty output lines

equivalent to -vI ۲

-T,

--show-tabs display TAB characters as ^I

(ignored) ₽

--show-nonprinting use ^ and M- notation, except for LFD and TAB

--help display this help and exit

output version information and exit

With no FILE, or when FILE is -, read standard input.

cat f = g . Output $f^{\,\prime}\, s$ contents, then standard input, then $g^{\,\prime}\, s$ contents.

Copy standard input to standard output. cat GNU coreutils online help: http://www.gnu.org/software/coreutils/> Report cat translation bugs to http://translationproject.org/team/>

PUTHOR

Written by Torbjorn Granlund and Richard M. Stallman.

OPYRIGHT

Copyright 8 2013 Free Software Foundation, Inc. License GPLv3+; GNU GPL version 3 or later Khttp://gnu.org/licenses/gpl.html>. This is free software; you are free to change and redistribute it. There is NO WARRANTY, to the extent permitted by law.

SEE ALSO

tac(1)

The full documentation for cat is maintained as a Texinfo manual. If the info and cat programs are properly installed at your site, the command

info coreutils 'cat invocation' Manual page cat(1) byte 2455 (press h for help or q to quit)