Socket:DIP_Socket-40_W11.9mm_W12.7mm_W15.24mm_W17.78mm_W18.5mm_3M_240-1280-00-0602J
www.zilog.com/manage_directlink.php?filepath=docs/z80/um0080

You can use 62256 (DIP) instead of 628128 (SMD). Not both at the same time!
To do this, the MEM_EN and MREQ_ signals must be logically summed.

J9 ZK
J3 ZK
J6 ZW
J1 ZW
RN1 8x4k7
J5 CA80/MSID
U7 82C55A
U8 Z80 CPU
U12 628128
U9 62256
U16 74HC138
R5 22R
R1 1K
D1 ON
J2 POWER +5V
SW1 ON/OFF
RN2 4X10k
J10 C H B A
J11 F E D
J7 CA80_ZS
J8 CA80_ZSa
A-BUS
D-BUS

H1 MountingHole
H2 MountingHole
H3 MountingHole
H4 MountingHole

C1 100n
C2 100n
C3 100n
C4 100n
C5 100n
C14 100uF
C6 100n
C7 100n
C8 100n

CloneFactory
Zegar.
Sheet: /
File: Tester-Z80-mini12.kicad_sch
Title: CA80 tester mini.
Size: A3 | Date: 2026-05-04 | **Rev: 1.2**
KiCad E.D.A. 9.0.6 | Id: 1/1