Hierarchical IPTC Topic Classification of French Press Articles with EuroBERT and Hierarchy-Guided Contrastive Learning

Zehua Huang

Internship report
Abstrakt, July to October 2026

Acknowledgements

Abstract

Contents

Acknowledgements i

Abstract ii

Notation and glossary viii

1 Introduction 1
- 1.1 Abstrakt and AI-assisted press monitoring . . . 1
- 1.2 The mission: a topic tag on each article . . . 1
- 1.3 Objectives and constraints . . . 2
- 1.4 Contributions of the internship . . . 2
- 1.5 Outline of the report . . . 3

2 Background 4
- 2.1 The IPTC Media Topics tree . . . 4
- 2.2 Hierarchical multi-label classification . . . 4
- 2.3 Encoders for French press . . . 5
- 2.4 Coherent predictions: C-HMCNN and the max rule . . . 5
- 2.5 Losses for imbalanced multi-label data . . . 5
- 2.6 Evaluation . . . 6

3 Data: three data sets 8
- 3.1 Starting point . . . 8
- 3.2 The easy data set . . . 8
- 3.3 The gold training set . . . 9
- 3.4 The real test set . . . 9
- 3.5 Purpose and limits . . . 9

4 Method 10
- 4.1 Model overview . . . 10
- 4.2 Baselines . . . 10
  - 4.2.1 Frozen encoder and an MLP head: choosing the encoder . . . 12
  - 4.2.2 Training the encoder: warm-up, learning rates, top layers, LoRA . . . 13
  - 4.2.3 Graphormer label attention . . . 14
  - 4.2.4 Several seeds: the spread and the ensemble . . . 14
- 4.3 The model block by block . . . 15
  - 4.3.1 Topic features and the graph encoder . . . 15
  - 4.3.2 Positive-sample generator and the two views . . . 16
  - 4.3.3 Article-to-topic attention and token FFN . . . 16
  - 4.3.4 Attention pooling . . . 17
  - 4.3.5 Head . . . 17
  - 4.3.6 Classification loss . . . 17

4.3.7 Contrastive loss and the total loss . . . 18
4.4 Coherence rules . . . 18
4.4.1 Rules at inference . . . 18
4.4.2 Rules in training . . . 19
4.4.3 The avg-max rule and its implementation . . . 20
4.5 Training settings . . . 20

5 Experimental setup **22**
5.1 Environment . . . 22
5.2 Metrics and protocol . . . 22

6 Results **24**
6.1 Baselines on the easy data set: encoders, frozen and fine-tuned . . . 24
6.2 Losses and coherence rules on the easy data set . . . 25
6.3 HGCLR and our changes on the easy data set . . . 25
6.4 Summary on the easy data set . . . 26
6.5 Runs on the gold training set . . . 26
6.6 Choice of the coherence rule . . . 27
6.7 Results on the real test set against the targets . . . 27
6.8 Ablations, seeds and learning curves . . . 27

7 Error analysis **29**
7.1 The errors by level . . . 29
7.2 Errors on the validation data: the model or the LLM topics? . . . 29
7.3 Errors on the real test set: a different mix of topics . . . 30
7.4 Lessons for the next model . . . 31

8 Discussion **32**
8.1 What worked and what did not . . . 32
8.2 Limits . . . 32
8.3 Deployment . . . 32
8.4 Next steps . . . 32

9 Side work: relevance rerankers for thematic search **33**
9.1 Problem and data . . . 33
9.2 zerank cross-encoders run locally . . . 33
9.3 GLiNER2 as a zero-shot classifier . . . 33
9.4 Findings . . . 33

10 Conclusion **34**
10.1 Summary of results . . . 34
10.2 Personal review . . . 34

A Full architecture graph **36**

B Configuration file and flag semantics **37**

C Run index **38**

D LLM labelling prompts **39**

E Experiment journal excerpts **40**

List of Figures

2.1 The idea of ASL, two figures from Ridnik et al. [5]. Top: the loss on a negative against its score, for cross-entropy, focal loss, and focal loss with the margin m. Bottom: the mean confidence in the right answer, p_t, of the positives and of the negatives during training on MS-COCO, with cross-entropy, focal loss and ASL. 6

4.1 The model: the data flow from the inputs on the top row to the topic tags. White: inputs. Blue: HGCLR blocks. Green: our changes. Green with an orange border: avg-max, our variant of the C-HMCNN rule. Solid: the inference path, one pass per article. Dashed: training only. The letters on the arrows are the symbols of the equations in Section 4.3; the positive view $\hat{e}$ follows the same chain as the article and gives $\hat{z}$ and $\hat{s}$. The losses are in Section 4.3; the full graph with tensor shapes is in Appendix A. 11

4.2 The frozen and the fine-tuned baselines share one chain. Frozen: the encoder runs once and its token vectors are stored. Fine-tune: the encoder trains with the head. White: input. Yellow: the blocks of the baselines. 13

4.3 The Graphormer label-attention baseline. The topic side on the left and the article on the right meet in the label attention, where each topic reads the article for itself. White: inputs. Yellow: the blocks of this baseline. 14

List of Tables

1.1 Targets and constraints set for the model at the start of the internship. Quality is measured against the LLM topics, so the LLM topics set a ceiling for the model. 2

2.1 The two encoders compared in this report. Sizes in parameters; input length in tokens. 5

3.1 The three data sets. The easy data set is mine; the gold training set and the real test set are the team's. 8

4.1 The blocks of the model in the order of Figure 4.1, where each one comes from, and what it does. 12
4.2 The baselines, in the order they were tried on the easy data set. All share the split, the topic set, the loss family and the metrics of the HGCLR runs. 12
4.3 Settings of the blocks in the run configuration. The HGCLR rows follow the paper and its reference code; the other rows are our blocks. 15
4.4 The five coherence settings. The rule in training sits inside the classification loss; the rule at inference runs on $p = \sigma(s)$ before the threshold. 19
4.5 The two rules on one chain root $\rightarrow$ A $\rightarrow$ a. The avg-max rule averages (A, a), then (root, a), then (root, A). 19
4.6 Training settings of the final model. 21

5.1 The training environment. 22

6.1 Baselines on the easy data set, validation split. One seed, or the ensemble of several seeds. Weighted BCE and no coherence rule unless stated. 24
6.2 The ASL sweep on the frozen baseline, easy data set, one seed. The weighted BCE row comes from a later run of the same baseline. Macro AP is the sort key of Chapter 6. 25
6.3 Coherence rules on the easy data set. Each block differs in the rule alone. The last three columns give macro F1 with no rule, with the max rule and with the avg-max rule applied to the saved scores; a run trained with a rule in the loss has the same value in all three. 25
6.4 HGCLR on the easy data set, one seed each, weighted BCE unless stated. Frozen rows: the positive view comes from a mask that keeps the stated share of tokens; a guided mask keeps the tokens closest to the names of the article's topics. Fine-tune rows: the positive view comes from the graph-guided generator of Section 4.3.2. The positive views of a frozen run are encoded once and cached; the two rows with no mask differ only in how often the cache is rebuilt, which with no mask changes the random stream alone. The plain fine-tune row repeats Table 6.1. . . 26
6.5 First runs on the gold training set, old platform, validation split of the gold set. The first four rows score about 251 topics; the last row scores all 329 and is not comparable. 27

6.6 The evidence for the avg-max rule. A: each rule applied after training to the saved scores of the 58 runs of the old platform trained without a rule. B: the rule inside the loss, macro AP on the validation data; a dash marks a pair that was not run. 28

7.1 The final model by level. Macro AP, and precision and recall over all article-topic pairs at the threshold of one half. 29
7.2 A validation article where the model and the LLM topics disagree. *Une retraitée d'Ajaccio tricote une écharpe de 21 kilomètres, chantier textile inédit en Corse*: a 72-year-old retired woman finishes a scarf 21 km long; the body stops at a paywall after two sentences. Votes: LLMs out of three that gave the topic; 0 means no LLM did. 30
7.3 Blind LLM judge on validation disagreements, earlier run of the same design. One judge, no human check. 30
7.4 Share of articles that carry a level 1 topic, in the generated validation data and in the real test set, and the model's results on the real test set at the threshold of one half. Topics with the largest change. 30
7.5 A real test page with many errors. *Service Photo : ses derniers articles publiés*, an author page of *Libération* that lists headlines: the war in the Middle East, the PSG victory, a heat wave. Missed: a topic the LLMs gave and the model scored below one half. Added: the reverse. 31

Notation and glossary

Chapter 1

Introduction

1.1 Abstrakt and AI-assisted press monitoring

Abstrakt is a French start-up. It sells a press monitoring service helped by AI. A customer wants to know what the press writes about a company or a public issue. Each day the service picks the articles that matter for that customer and sends them. The press publishes more articles than a person can read, so the AI reads first and a person reads what the AI kept. Abstrakt states the rule in one line: AI narrows the reading, people decide. Each automatic decision gets one of three answers, yes, no, or not sure, and a person handles the not sure cases. For a model this means two things. Recall comes first, because a customer does not see a missed article. Precision has a floor, because a person pays for each wrong article with reading time.

I did this internship from the end of July to October 2026 as a machine-learning intern in the engineering team. I worked on the step that gives each article its topics.

1.2 The mission: a topic tag on each article

Each article in the service carries topic tags. The tags come from the IPTC Media Topics list, the standard of the news industry. The topics form a tree. Level 1 has 17 broad topics, for example *politics and government* or *sport*. Level 2 has 120 topics and level 3 has 515. The project stops at level 3. Many articles have several topics. A topic implies its parent topics up to the root.

The product uses the tags in two places. With a level 3 tag on each article, a customer can filter the articles on one precise topic, as in a traditional press review. The level 2 tags serve as filters in the search bar.

A large language model (LLM) can read an article and classify its topics from the list. The team started this way, and the cost was the problem: **classifying each article with an LLM costs too much** at the scale of the service. My mission was to find a better way. A small model is trained once, then runs on one GPU and tags each article at a very low cost. A small model learns from examples, and the examples were missing. The team had **[number of titles]** titles, each with a level 1 and a level 2 topic, and no article text. So the LLMs keep one job, writing the training data. Several LLMs vote on the topics of each training article, and the model learns from the vote. A vote of several LLMs is more reliable than one LLM, so the model can tag better than the single LLM the team started with.

Three more facts guided the design. Copyright forbids training the model on real articles. The LLM therefore writes training articles for each topic, and the team keeps real articles for the test data. The tree has 652 topics down to level 3. The team cut the niche topics and the topics with no business use, and of the topics that remain, many appear in a few articles. These rare topics drive the macro scores. The model runs on one small GPU in production. One encoder

with a small head on top fits this GPU, so I kept that design and did not try one model per node of the tree.

The team chose the design at the start: a pre-trained text encoder, EuroBERT, and a head on top that outputs one score per topic. My work during the internship was to train the best model I could within this design. **[one or two sentences on what this meant, to write after the Method chapter is done]** Chapter 4 presents these choices and Chapter 6 compares them.

1.3 Objectives and constraints

Table 1.1 lists the targets the team agreed on at the start. The quality targets apply per level and put recall first: the model may miss a level 1 topic in at most one article out of twenty, with a precision of at least 0.70. Deeper levels get looser targets, because the LLM topics are less reliable there. The daily volume grows ten times over the year. Inference must fit one NVIDIA T4 GPU with 16 GB of memory. The team spends the LLM budget on training data.

Table 1.1: Targets and constraints set for the model at the start of the internship. Quality is measured against the LLM topics, so the LLM topics set a ceiling for the model.

Item	Scope	Target	Note
Recall, precision	Level 1 (17 topics)	$R \geq 0.95$, $P \geq 0.70$	recall first
Recall, precision	Level 2 (120 topics)	$R \geq 0.90$, $P \geq 0.70$	
Recall, precision	Level 3 and deeper	to be set	looser as the topic count grows
Throughput	production	20k articles/day by September	200k/day by January
Hardware	production	one NVIDIA T4 (16 GB), 32 GB RAM	inference only
Languages	input	French first, multilingual later	
Topics per article	Level 1	1 to 4, plus their child topics	several topics per article

Two constraints stay out of the table. The team is small and shares the code, so a colleague must be able to repeat each run from a commit hash. **[the training data changed during the internship: easy data set first, then the gold data set; write once the gold data set is final]**

1.4 Contributions of the internship

The work has four parts.

1. **Training data. The easy data set** (v2, Chapter 3): a random sample of the titles, the rare topics folded into their parent topic, and **one article per title written and tagged by a small LLM**. It carried the model work for two months. **The gold data set and its real test set** (Chapter 3), built with the team in September: several LLM runs vote on each topic, and rules clean the data and drop the rarest topics.

2. **A model that knows the tree. HGCLR is a training method that teaches the encoder the tree**. For each article it keeps the words that its topics point to, and it trains the encoder to give the same output for the full article and for the kept words. **I rebuilt HGCLR with EuroBERT in place of BERT and with four changes**: attention pooling in place of a single token or a simple pooling, a deeper head, the ASL loss, and an

attention block from the article to the topics before the pooling. **I compared three ways to make the output scores coherent**, which means a parent score at least as high as each child score. One of them is **a new averaging rule that moves a parent and its child toward each other**; it costs about as much as the maximum rule of C-HMCNN and scores higher (Chapter 4).

3. **Experiments on the easy data set. I built one platform to compare each choice of the project on the same footing**: encoders, model structures, losses, optimizer settings and coherence rules, each with several seeds, and **every run stored with its commit hash and its metrics** (Chapter 6).

4. **Analysis tools. A dashboard that shows the scores of a run per level and per topic, and lists the topics and the articles the model gets wrong**, so that an error can be traced to a topic, an article or a label (Chapter 7).

A short side study (Chapter 9) compares open rerankers for a nearby need of the product, thematic search.

1.5 Outline of the report

Chapter 2 gives the background: the topic tree, the task and the methods it borrows from, the encoders, the losses and the metrics. Chapter 3 describes the three data sets. Chapter 4 presents the model, from the baselines to HGCLR, my changes and the coherence rules. Chapter 5 states the environment and the protocol of the runs. Chapter 6 reports the results, first on the easy data set and then on the gold training set and the real test set. Chapter 7 analyses the errors. Chapter 8 covers limits, deployment and next steps. Chapter 9 reports the reranker study, and Chapter 10 ends with a personal review.

Chapter 2

Background

2.1 The IPTC Media Topics tree

IPTC Media Topics [4] **is the topic list of the news industry**, kept by the International Press Telecommunications Council. Each topic has a code, a name and a one-line definition in many languages. **The topics form a tree**: each topic has one parent, and the tree goes six levels deep. **The project uses the first three levels**: 17 topics on level 1, 120 on level 2 and 515 on level 3. The level 1 topics have no common root, so the tree is a forest of 17 trees. A press article gets a set of topics, and **a topic implies its parent topics up to level 1**: an article about a football match is about *football*, *competition* and *sport* at once.

2.2 Hierarchical multi-label classification

The task is multi-label: an article can have several topics, so the model gives one score per topic and a threshold turns each score into a yes or a no. **The task is hierarchical too**: the set of topics of an article contains the parents of each of its topics, so a child topic never comes without its parent. **A set of predictions is coherent when each parent scores at least as high as each of its children**; a threshold on coherent scores then keeps the tree intact.

A flat model gives one score per topic and knows nothing of the tree. It can say *football* and deny *sport*. **Hierarchy-aware models bring the tree in at one of two places**. Some put it into the model, so that the vectors of the topics or of the article carry the tree. Others put it at the output, with a rule that makes the scores coherent. **This report tries both places and compares them, alone and together**: HGCLR puts the tree into the encoder, and a coherence rule makes the scores coherent, at inference and, in one variant, in training as well.

HiAGM [9] is an earlier model that puts the tree into the model: a graph network turns the tree into one vector per topic, and each topic vector attends over the text to get its own view of it. The Graphormer label-attention baseline of Chapter 4 follows this design. **HGCLR [7] uses the topic vectors in training alone**, to build the positive view, and its paper reports higher scores than HiAGM on the three usual benchmarks.

HGCLR works as follows. **A graph encoder turns the topic tree into one vector per topic**. For each training article, **a generator uses these vectors and the article's topics to keep the tokens that speak for the topics and to mask the rest**; this masked copy is the positive view of the article. The encoder reads the article and its positive view, and **a contrastive loss pulls their two vectors together while pushing the other articles of the batch away**. The encoder thus learns which tokens carry the topics and keeps this knowledge at inference, where the model is a plain encoder with a head. Chapter 4 gives the blocks and the losses.

2.3 Encoders for French press

An encoder is a transformer that reads a whole text and gives one vector per token, where each vector carries the context of the token. Encoders of the BERT family are pre-trained on large text with masked tokens to fill in, then fine-tuned on the task at hand. Most of the articles here are French press articles of some length, and the product must handle other languages too, so **the encoder must read French well, handle several languages and accept long inputs**. Table 2.1 lists the two encoders I compared.

Table 2.1: The two encoders compared in this report. Sizes in parameters; input length in tokens.

Encoder	Languages	Sizes	Trained for	Input length
EuroBERT	European languages	210m, 610m, 2.1B	masked tokens	8,192
multilingual-e5-base	about 100 languages	280m	retrieval	512

EuroBERT [1] is a recent encoder for European languages, in three sizes, with the recipe of recent decoder models: rotary positions, no bias, and a long input window. Its tokenizer adds an end token and no start token, a detail that matters for the pooling in Chapter 4. **multilingual-e5 is an older multilingual encoder trained for retrieval**, so its vectors are made for comparing texts, and it reads short inputs.

2.4 Coherent predictions: C-HMCNN and the max rule

C-HMCNN [3] makes the output of any multi-label model coherent with one rule, the max rule. Let p_j be the score of topic j and D_j the set made of j and all its descendants. The output score of j is

$$\mathrm{MCM}_j = \max_{k \in D_j} p_k. \tag{2.1}$$

A parent then scores at least as high as each child, and a threshold on these scores respects the tree.

The rule alone has a flaw in training: a child with a wrong high score lifts its parent, and the loss then pushes the parent down instead of the child. C-HMCNN therefore trains with a loss where, **for a topic the article has, the maximum runs over the descendants it has too**:

$$L_j = -y_j \ln\Big(\max_{k \in D_j} y_k\, p_k\Big) - (1 - y_j) \ln\big(1 - \mathrm{MCM}_j\big). \tag{2.2}$$

The gradient then reaches the topic that caused the error. Chapter 4 uses this rule and derives from it the avg-max rule of the final model.

2.5 Losses for imbalanced multi-label data

The usual loss for multi-label classification is binary cross-entropy, one yes-or-no loss per topic. With hundreds of topics and a few topics per article, almost all the terms are negatives, and **the model learns to say no**. **The first fix weights the positive term of each topic by how rare the topic is**, with a cap on the weight. **The second is the asymmetric loss, ASL [5]**, and Figure 2.1 shows its idea. The top plot draws the loss on one negative against the score the model gives it. Cross-entropy keeps a loss on each negative down to a score of zero, so the many easy negatives add up and drive the training. Focal loss scales this loss down for a negative with a low score. **ASL goes one step further and shifts the curve to the right by a margin** m, so a negative with a score below m costs nothing. The positives keep the full

loss. The bottom plots show the result on MS-COCO, where p_t is the model's confidence in the right answer. With cross-entropy the negatives reach a high confidence within the first steps while the positives stay below. **With ASL the two curves meet**. ASL has three settings, one exponent per side and the margin, and with all three at zero it is binary cross-entropy again. Chapter 4 states the values used.




Figure 2.1: The idea of ASL, two figures from Ridnik et al. [5]. Top: the loss on a negative against its score, for cross-entropy, focal loss, and focal loss with the margin m. Bottom: the mean confidence in the right answer, p_t, of the positives and of the negatives during training on MS-COCO, with cross-entropy, focal loss and ASL.

2.6 Evaluation

The model gives one score per topic, and I read the scores in two ways. With a threshold, each score becomes a yes or a no, and the usual counts follow: **recall, the share of the article's topics the model found, and precision, the share of the model's topics that are right**. F1 is their harmonic mean. With TP the topics found, FP the topics predicted but wrong and FN the topics missed,

$$P = \frac{TP}{TP + FP}, \qquad R = \frac{TP}{TP + FN}, \qquad F_1 = \frac{2PR}{P + R}. \tag{2.3}$$

Without a threshold, **average precision (AP) ranks the scores and rewards a model that puts the right topics first**, whatever the threshold. It walks down the ranked list and sums the precision at each point where a right topic appears, weighted by the recall gained there:

$$AP = \sum_k \left(R_k - R_{k-1}\right) P_k, \tag{2.4}$$

where P_k and R_k are the precision and the recall of the first k scores.

Each of these comes in two flavours. **Micro pools all decisions of all articles into one count**, so the frequent topics dominate. **Macro computes the score per topic and**

takes the mean, so a rare topic counts as much as a frequent one. For precision, with L topics and TP_j, FP_j the counts of topic j,

$$P_{\text{micro}} = \frac{\sum_{j=1}^{L} TP_j}{\sum_{j=1}^{L} (TP_j + FP_j)}, \qquad P_{\text{macro}} = \frac{1}{L} \sum_{j=1}^{L} P_j, \tag{2.5}$$

and the same for recall, F1 and AP.

The targets of Table 1.1 are recall and precision per level, so the tables report them per level. For a target recall R^*, **the threshold τ goes to the point where the recall reaches the target, and the precision there says whether the target holds**:

$$P@R^* = P(\tau^*), \qquad \tau^* = \max\{\tau : R(\tau) \geq R^*\}. \tag{2.6}$$

Two more numbers serve the tree. **Recall at k is the share of an article's topics y_i among its k highest scores**, averaged over the N articles:

$$R@k = \frac{1}{N} \sum_{i=1}^{N} \frac{|\, y_i \cap \text{top}_k(i) \,|}{|\, y_i \,|}. \tag{2.7}$$

The violation rate V is the share of predicted child topics whose parent is not predicted. With $\hat{y}_{ij} \in \{0, 1\}$ the prediction for article i and topic j, and C the set of topics that have a parent,

$$V = \frac{\sum_i \sum_{j \in C} \hat{y}_{ij} \left(1 - \hat{y}_{i,\text{parent}(j)}\right)}{\sum_i \sum_{j \in C} \hat{y}_{ij}}. \tag{2.8}$$

The numerator counts the predicted child topics whose parent is off, the denominator all predicted child topics. A coherent model has $V = 0$.

Chapter 3

Data: three data sets

3.1 Starting point

At the start of the internship no training data existed for the task: no article with its three levels of topics. The team had two things. The first was a set of titles from its thematic search work, each title with a level 1 and a level 2 topic and no article text. The second was a scrape of real French press articles, which an LLM had tagged with topics in a first attempt, without the tree at first and with three levels later. Copyright keeps real articles out of training, so this scrape could serve as test data alone. Three data sets followed, in the order of Table 3.1: an easy data set that I built in August to try the methods, a gold training set that the team generated in September, and a real test set that the team drew from a new scrape and tagged the same way.

Table 3.1: The three data sets. The easy data set is mine; the gold training set and the real test set are the team's.

	Easy data set	Gold training set	Real test set
Built by	me, August	the team, September; pruned 21 September	the team, September; trimmed 5 October
Text	LLM-written from a title	LLM-written from an LLM-written seed title	real French press, scraped in 2026
Writer LLM	gpt-5.4-nano	gpt-5-mini	none
Topics given by	the same LLM, one vote	three LLMs, all votes kept	the same three LLMs
Languages	French	two thirds French, one third English	French
Articles	10,798	58,527 (59,495 before pruning)	9,701 (10,000 before trimming)
Topic list	294 distinct; 186 kept by the model	17 level 1, 120 level 2, 192 kept level 3	the same list
Use	compare methods, Sections 6.1 to 6.4	train the model, Section 6.5	measure the model, never train

3.2 The easy data set

My first design, in the first week of August, started from real articles: take about a hundred real articles of one topic, have an LLM extract a profile of them, turn the profile into a writing prompt, and generate many articles and hard negatives from it with a quality check. I wrote the profile step and stopped there: the method needs real seed articles per topic, and the tree has hundreds of topics. The second design, which produced the data set within the same week, starts from the titles instead and runs in four steps. First I picked a sample of the titles, spread

over the level 1 and level 2 topics, with a cap per pair of topics so that no topic floods the sample. Second, a small LLM wrote one press article from each title. Third, the same LLM read the article and tagged it with a tree of topics down to level 3; a tag outside the tree, or under the wrong parent, went back to the LLM, and after a few tries the invalid part was cut. I dropped the articles whose level 1 topic did not match the title's. Fourth, I folded the long tail: a topic with too few articles went into its parent topic, so that the data set holds topics the model can learn. One seed fixes the split into training and validation data, and the model's topic list drops the topics that appear in less than one percent of the training articles.

3.3 The gold training set

The gold training set is the team's work, built in September while I trained models on the easy data set; I took part in the discussions on its design. It keeps the idea of the easy data set, LLM-written articles, and fixes its two weaknesses: one LLM as both writer and judge, and topics with no articles. The team first cut the topic tree to the topics the product needs. For each kept topic an LLM wrote seed titles, and a stronger LLM wrote one article per seed, two thirds in French and one third in English, in a spread of press formats and lengths; a share of the bodies was cut at a paywall preview, the way scraped news arrives. Three LLMs then tagged each article from its body, and the set keeps each vote, so that a topic can count as present at one, two or three votes. The training of Section 6.5 uses the topics with at least two votes and keeps the one-vote topics as soft values.

A later pass pruned the set. The three voters share a bias toward too many topics, so the team added a judge of a different kind, which answers one yes-or-no question per level 1 topic with a probability. The pass drops a level 1 topic that the judge rejects, with its children, and removes an article whose own brief the judge rejects. A hand read of two hundred dropped topics found most of them wrong. The set before pruning stays on the Hub for provenance.

3.4 The real test set

The real test set measures the model and never trains it. The team scraped French press in 2026 and drew a sample balanced over the level 1 topics, so that each level 1 topic has about the same number of articles; religion, the rarest, has fewer. The same three LLMs tagged the articles from their body, with the same votes. A later pass trimmed the set: pages with no article body behind a paywall or a cookie wall, which the voters had tagged from the wall text, and duplicate copies of one article. A lede cut by a paywall stays, since this is how scraped news arrives. The topics of this set are votes, not ground truth: no human-tagged set exists yet, which Chapter 7 returns to.

3.5 Purpose and limits

Each data set has one job. The easy data set compares methods fast, and it is easy in two ways: the LLM that wrote an article tagged it as well, so the tags fit the text well, and the topics with few articles are gone. A score on it says how methods compare and says little about real press; all of Chapter 6 rests on it. The gold training set trains the model for the product, with the full topic list and three votes per topic. The real test set gives the number that matters, on real articles. Two limits run through all three. The topics come from LLMs and are votes, not ground truth, so they set a ceiling on what any score can show. And the generated articles differ from real press in which topics appear together and how often, a gap that Chapter 7 measures.

Chapter 4

Method

4.1 Model overview

The model takes two inputs, shown on the top row of Figure 4.1: **the IPTC topic tree**, and **an article with its title and text**. In training the article also brings its topics y. The topic side of the figure works on the tree. Each topic gets a vector: the EuroBERT embedding of its name plus a learned vector of its own. The IPTC topics form a forest: one tree per level 1 topic. A Graphormer then mixes the vectors within each tree, so that each topic vector carries the whole tree it belongs to. The result is G, one vector per topic. G **is learned during training and does not change at inference**.

The article side is the solid chain in the middle. The tokenizer cuts the title and the text into tokens, and the embedding table turns them into vectors e. The encoder g_θ, a pre-trained EuroBERT, reads e and outputs **one vector per token**. The article-to-topic attention scores each token vector against all the topics in G and **masks the unimportant tokens**. A small feed-forward layer then transforms each token vector on its own. Attention pooling merges the token vectors into **one vector z for the article**. The head maps z to **one score per topic**. The avg-max rule makes the scores coherent: **a parent topic scores at least as high as each of its children**. **Each topic whose score passes the threshold becomes a tag of the article**. **This chain is the whole model at inference**.

Training adds the positive view. The positive-sample generator compares each token embedding with G and masks the tokens that are unimportant for the article's topics y. This masked copy $\hat{e}$ goes through the same chain as the article and gives **a second vector $\hat{z}$ and a second set of scores**. The training loss then asks two things: **the scores of the article and of the positive view must match y, and z and $\hat{z}$ must be close**. Section 4.3 gives the losses.

Table 4.1 sums up the blocks. **HGCLR [7] gives the frame**: the topic side, the generator and the contrastive loss, on top of a BERT encoder, here EuroBERT. Inside this frame **I replaced four blocks with my own**: the article-to-topic attention with its feed-forward layer, the pooling, the head and the classification loss. On the output side **I added avg-max, a coherence rule derived from C-HMCNN [3]**. The rest of this chapter presents these parts one by one, starting with the baselines I compared the model against.

4.2 Baselines

The work started on the easy data set with the simplest model: a frozen encoder and a head on top. This model is cheap enough to run many times, so I used it first to compare encoders, different BERT models and different sizes. The models that followed add one thing each: training the encoder, a cheaper way to train it, and a head that knows the tree. All of them share the




Figure 4.1: The model: the data flow from the inputs on the top row to the topic tags. White: inputs. Blue: HGCLR blocks. Green: our changes. Green with an orange border: avg-max, our variant of the C-HMCNN rule. Solid: the inference path, one pass per article. Dashed: training only. The letters on the arrows are the symbols of the equations in Section 4.3; the positive view $\hat{e}$ follows the same chain as the article and gives $\hat{z}$ and $\hat{s}$. The losses are in Section 4.3; the full graph with tensor shapes is in Appendix A.

Table 4.1: The blocks of the model in the order of Figure 4.1, where each one comes from, and what it does.

Block	Origin	What it does
Topic features F	HGCLR	one vector per topic: the EuroBERT embedding of the topic name plus a learned vector
Graph encoder G	HGCLR	a Graphormer mixes the topic vectors within each tree of the forest
Encoder g_θ	EuroBERT	a pretrained BERT; reads the article tokens and, in training, the positive view
Positive-sample generator	HGCLR	in training, keeps the tokens that match the article's topics y and masks the unimportant tokens
Article-to-topic attention + token FFN	ours	scores each token against all the topics in G and masks the unimportant tokens, then a small feed-forward layer on each token
Attention pooling	ours	merges the token vectors into one vector z per article
Head	ours	three linear layers from z to one score per topic
Classification loss	ours	asymmetric loss (ASL) on the scores
Contrastive loss	HGCLR	pulls z and $\hat{z}$ together
Coherence rule	C-HMCNN, ours	avg-max: a parent topic scores at least as high as each child; our variant of the C-HMCNN rule

split, the topic set, the loss family and the metrics. Table 4.2 lists them; the results are in Chapter 6.

Table 4.2: The baselines, in the order they were tried on the easy data set. All share the split, the topic set, the loss family and the metrics of the HGCLR runs.

Step	Model	Encoder	What trains	Question it answers
1	Frozen + MLP head	EuroBERT 210m, 2.1B; multilingual-e5. Frozen, one pass, vectors stored	the head	which encoder, and how far a frozen encoder goes
2	Fine-tune	EuroBERT, all layers or the top layers trained	encoder and head	what training the encoder adds, and how much of it
3	LoRA	EuroBERT, weights fixed, low-rank adapters	adapters and head	fine-tune quality at a fraction of the memory
4	Graphormer label attention	EuroBERT, frozen or trained	Graphormer, topic attention, (encoder)	whether a head that knows the tree helps

4.2.1 Frozen encoder and an MLP head: choosing the encoder

The first model keeps the encoder as it is. It runs each article through the encoder once and pools the token vectors into one vector per article. **The pooling is a fixed rule: the mean and the maximum over the tokens**, side by side. Figure 4.2 shows the chain. **I store these vectors on disk**, so the encoder never runs again. **The head is a standard classifier**, a small MLP trained on the stored vectors with binary cross-entropy. **It is the baseline for everything that follows**: the choice of encoder, the architectures, the learning rates and the schedules. Training the head takes minutes, so I can run many settings and repeat each one with several seeds.

Because the encoder runs once, **this model is the right place to compare encoders**. I

compared **two models, EuroBERT and multilingual-e5, and two sizes of EuroBERT, 210m and 2.1B**. The encoders differ in the length they accept, the prefix their input needs and the pooling their weights were trained for, so I wrote these facts into one table in the code, and one training loop reads it. EuroBERT-2.1B scored higher, but a full fine-tune of it costs far more time and memory, so **EuroBERT-210m became the encoder for the main runs**. If a change made no clear difference on 210m, I tried it again on the bigger model. Chapter 6 gives the numbers.




Figure 4.2: The frozen and the fine-tuned baselines share one chain. Frozen: the encoder runs once and its token vectors are stored. Fine-tune: the encoder trains with the head. White: input. Yellow: the blocks of the baselines.

4.2.2 Training the encoder: warm-up, learning rates, top layers, LoRA

The second model trains the encoder as well as the head, and it beats the frozen model. The head starts random, so its first gradients are noise, and noise pushed into a pretrained encoder erases what it learned, a failure known as **catastrophic forgetting**. Two standard settings prevent it: **the encoder stays frozen for the first epochs while the head trains**, which I call the warm-up, and then **trains with a lower learning rate than the head**. **This full fine-tune model costs more than the frozen one in two ways**. The optimizer, AdamW, keeps two running averages for each weight of the encoder, so **the training state takes three times the memory of the encoder itself**. And **each run saves the whole encoder to disk**, where the frozen model saves a small head.

Two cheaper options sit between the frozen encoder and the full fine-tune. The first **trains the top layers of the encoder and freezes the lower ones**. The frozen layers keep their pretrained features, and AdamW holds no state for them, so the run is lighter. Early in the exploration I trained two or three top layers, without a record, and saw little change from the frozen model. Later, with HGCLR, **training the top six layers cut the training time and scored above the frozen model**. I have no clean comparison with the full fine-tune: the two runs used different settings for the positive samples, so the gap between them has two causes. I kept the option for cheap test runs; **the final model trains the whole encoder**.

The second option is LoRA. The pretrained weights stay fixed. Each attention projection gets a pair of small low-rank matrices, and **the gradient reaches these matrices and the head**, under one percent of the parameters. I tried it in the early exploration, without a record: **LoRA brought no clear gain over the frozen model**, and I dropped it.

Chapter 6 compares the options.

4.2.3 Graphormer label attention

The third model is the first one that sees the tree. Figure 4.3 shows its two sides. The topic side starts from the tree. **Each topic gets a vector from the frozen EuroBERT embedding of its name and definition**, plus a learned vector for its number of neighbours. **A Graphormer then runs attention between the topics**, and the attention score of two topics carries a learned bias set by their distance in the tree. The article side runs the article through EuroBERT. **The two sides meet in the label attention of HiAGM-LA [9]**: each topic attends over the tokens of the article and gathers its own view of it, and **a scorer per topic turns that view into the topic's score**. The encoder can stay frozen or train with the rest.




Figure 4.3: The Graphormer label-attention baseline. The topic side on the left and the article on the right meet in the label attention, where each topic reads the article for itself. White: inputs. Yellow: the blocks of this baseline.

A first version scored all topics with one shared scorer and gave each topic the same score; **the scorer per topic fixes this**.

4.2.4 Several seeds: the spread and the ensemble

A small gain may be noise. The seed sets the random start of the head, the dropout and the batch order, and two seeds of the same setting can differ by more than the gain. So **I ran each setting with several seeds**: more for the cheap models, fewer for the models where each seed is a full fine-tune. **A change counts as real when it beats the spread of the seeds**. The seeds give an ensemble too: **the mean of their probabilities, which scores much higher**

than any single seed. For the frozen model this is free, since each seed is one more head on the same stored vectors. Chapter 6 reports both.

4.3 The model block by block

At inference the model sees the article alone. The topic tree can help it then in one way: **the encoder must have learned the tree during training**. Hierarchy-guided contrastive learning (HGCLR) [7] does this by **making a positive view of each training article: a copy that keeps the tokens about the article's topics and masks the rest**. A generator reads the article's topics y and chooses these tokens. **The encoder reads the article and this positive view with the same weights**, and **a contrastive loss pulls together the two output vectors, one for the article and one for its positive view**. **The encoder learns to find the topic-bearing tokens on its own**, and at inference it does so without y. This section walks through the blocks of Figure 4.1 in the order of the data flow. **The topic side, the generator and the contrastive loss come from HGCLR; the article-to-topic attention, the pooling, the head and the classification loss are mine**. Table 4.3 lists the settings of the blocks.

Table 4.3: Settings of the blocks in the run configuration. The HGCLR rows follow the paper and its reference code; the other rows are our blocks.

Block	Origin	Setting	Value
Graph encoder	HGCLR	Graphormer layers	1
		attention heads	12
Generator	HGCLR	attention heads	8
		keep threshold γ	0.02
		Gumbel temperature τ	1
Article-to-topic attention	ours	attention heads	8
		token FFN hidden width	768
Attention pooling	ours	heads	12
		MLP hidden width	128
Head	ours	hidden width	1024
		layers	3
		dropout	0.2
Classification loss (ASL)	ours	γ_+	0
		γ_-	1
		margin m	0.05
Contrastive loss	HGCLR	temperature τ_{con}	1
		weight λ	0.1

4.3.1 Topic features and the graph encoder

Each topic i starts as a vector f_i with two parts. **The first part is the mean of the EuroBERT token embeddings of the topic name**, so the graph encoder starts with basic information on each topic. **The second part is a learned vector E_i of the topic's own**, which training moves as it needs to tell topics apart:

$$f_i = E_i + \text{name}_i, \qquad \text{name}_i = \frac{1}{|n_i|} \sum_{w \in n_i} \text{embed}(w), \tag{4.1}$$

where n_i is the set of tokens in the name of topic i, w runs over these tokens, embed(w) is the EuroBERT embedding of token w, and f_i is row i of F. I set the start scale of E to the scale of the token embeddings.

The graph encoder is one Graphormer layer [8], as in HGCLR: attention among the topics, where **the attention score of a pair of topics gets a learned bias from their distance in the tree** and from the edges on the path between them:

$$a_{ij} = \frac{(W_Q f_i) \cdot (W_K f_j)}{\sqrt{d}} + b_{\mathrm{dist}(i,j)} + c_{ij}, \tag{4.2}$$

with b one learned value per distance and c_{ij} the mean of a learned value per edge on the path from i to j. A softmax over j and a weighted sum of the f_j follow, as in any attention layer. **The output is G, one vector per topic that mixes in all the other topics of its tree**, weighted by distance; the tree knowledge itself sits in the learned biases and topic vectors, and G is recomputed from them at each step. In HGCLR, G serves the generator alone. **In our model the article-to-topic attention of Section 4.3.3 reads G too, at inference as well**.

4.3.2 Positive-sample generator and the two views

The generator decides which tokens of a training article survive into the positive view, as in HGCLR. **It works on the token embeddings e_i, before the encoder**. The equations follow the paper. Each token x_i is a query and each topic j, with its row G_j, is a key:

$$q_i = e_i W_Q, \qquad k_j = G_j W_K, \qquad A_{ij} = \frac{q_i k_j^\top}{\sqrt{d_h}}. \tag{4.3}$$

A softmax over the topics would give the probability that token x_i belongs to topic j. **HGCLR replaces it with a Gumbel-softmax, which adds noise and keeps the sampling differentiable**:

$$P_{ij} = \mathrm{gumbel_softmax}(A_{i1}, A_{i2}, \ldots, A_{ik})_j. \tag{4.4}$$

The sum over the article's topics y gives the probability of the token under its topic set, and a threshold γ builds the positive view:

$$P_i = \sum_{j \in y} P_{ij}, \qquad \hat{e}_i = \begin{cases} e_i & \text{if } P_i > \gamma \\ 0 & \text{else} \end{cases}. \tag{4.5}$$

The threshold has no gradient, so **the generator passes the hard choice forward and the gradient of P_i backward**. **In HGCLR this is the one path that trains the topic side**. The noise makes the choice random, so **the same article gets a different positive view at each epoch**.

In the positive view $\hat{e}$, **a kept token keeps its embedding and a dropped token becomes a zero vector at its position**. **I run the encoder once: the article and its positive view go into one batch of $2B$ rows**, which works because EuroBERT accepts embeddings as its input. From the encoder on, **the two views go through the same blocks with the same weights**, and come out as the vectors z and $\hat{z}$ and the scores s and $\hat{s}$.

4.3.3 Article-to-topic attention and token FFN

The generator highlights the tokens that carry the article's topics, but it reads y to do so, and y exists in training alone. **I added a block that does the same at inference, where there is no y: the article-to-topic attention**. It sits after the encoder and **scores each token state H_t**, the encoder's output for token t, **against the graph-aware topic features G** of the graph encoder, with the same attention as the generator:

$$q_t = H_t W_Q, \qquad k_j = G_j W_K, \qquad S_{tj} = \sigma\Big(\frac{q_t k_j^\top}{\sqrt{d_h}}\Big), \tag{4.6}$$

averaged over the heads. **A sigmoid replaces the softmax, and the maximum over all topics replaces the sum over** y, so the block runs without y:

$$r_t = \max_j S_{tj}, \qquad H'_t = H_t + \alpha\, r_t\, H_t. \tag{4.7}$$

The block drops no token; **it scales up a token that matches a topic**, with one learned scalar α that starts at zero. **A feed-forward layer on each token follows**, with the same zero start:

$$H''_t = H'_t + W_2\,\mathrm{GELU}\big(W_1\,\mathrm{RMSNorm}(H'_t)\big), \qquad W_2 = 0 \text{ at the start.} \tag{4.8}$$

Both blocks begin as the identity, so the model starts as the one without them.

4.3.4 Attention pooling

HGCLR takes the vector of the first token as the article vector, the usual BERT choice. **EuroBERT has no such token**: its tokenizer adds an end token and nothing in front. The frozen baseline of Section 4.2.1 pooled with a fixed rule, the mean and the maximum over the tokens. **The final model pools with attention**, the gated attention pooling of the torchmil library [6]: **a small MLP gives each token an attention value, a softmax over the tokens normalises the values, and the article vector is the weighted sum of the token states**:

$$\mathbf{f} = \big(\tanh(H''\mathbf{W}_1) \odot \mathrm{sigm}(H''\mathbf{W}_2)\big)\,\mathbf{w}, \qquad z = H''^{\top}\,\mathrm{Softmax}(\mathbf{f}) = \sum_{t=1}^{T} s_t\, H''_t, \tag{4.9}$$

where H'' holds one token state H''_t per row, $\mathbf{f} \in \mathbb{R}^T$ are the attention values, s_t is the normalised score of token t, and $\mathbf{W}_1$, $\mathbf{W}_2$ and $\mathbf{w}$ are the weights of the MLP. With several heads, $\mathbf{w}$ has one column per head, and **each head pools its own slice of** H'' **with its own scores**. The softmax skips the padding tokens. **The article vector is a weighted mean of the token states, where the model chooses the weights** and each head can look at different tokens. This block gave the largest single gain of my four changes on the easy data set, on the frozen baseline and inside HGCLR alike. A dropout on z follows, and z feeds both the head and the contrastive loss.

4.3.5 Head

HGCLR maps z to the scores with one linear layer. **Our head is a small MLP of three linear layers**, with a ReLU and a dropout after the first two:

$$s = W_3\,\mathrm{ReLU}\big(W_2\,\mathrm{ReLU}(W_1 z)\big), \tag{4.10}$$

biases and dropouts left out. The last layer has no activation: s **is one raw score per topic**, and the sigmoid and the coherence rule come after. **One head scores the article and the positive view**. The frozen baseline used a head of the same shape, and I kept it in the final model.

4.3.6 Classification loss

The classification loss compares $p = \sigma(s)$ **with the article's topics** y, one term per topic. The baselines used binary cross-entropy with a capped positive weight per topic, against the imbalance of Section 2.5. **The final model uses the asymmetric loss (ASL) [5]**:

$$p^- = \max(p - m, 0), \qquad L^+ = (1-p)^{\gamma_+}\log p, \qquad L^- = (p^-)^{\gamma_-}\log(1-p^-), \tag{4.11}$$

$$L^C = -\frac{1}{B} \sum_{\text{articles}} \sum_{j=1}^{L} \left[y_j L_j^+ + (1 - y_j) L_j^- \right]. \tag{4.12}$$

The margin m shifts the probability of a negative down and drops the easy negatives from the loss; the exponent γ_- dampens the ones that remain; γ_+ does the same on the positives. Figure 2.1 in Section 2.5 shows the effect. With all three settings at zero the loss is binary cross-entropy. I swept them on the frozen baseline, without a detailed study. **ASL scored higher than binary cross-entropy, and the setting with a light focusing on the negatives, a small margin and no focusing on the positives scored best**; Table 4.3 gives the values, and Table 6.2 in Section 6.2 lists the sweep. The same loss runs on s and on $\hat{s}$.

4.3.7 Contrastive loss and the total loss

The contrastive loss pulls z and $\hat{z}$ together and pushes the other articles of the batch away. It is the NT-Xent loss of SimCLR [2], as in HGCLR. A small projection, two linear layers with a ReLU between them, maps each of the $2B$ vectors to a vector c and scales it to unit length, so that a dot product is a cosine. **For each vector m the loss is a softmax over the other $2B - 1$ vectors, where the partner $\mu(m)$, the other view of the same article, must win**:

$$L^{con} = -\frac{1}{2B} \sum_{m=1}^{2B} \log \frac{\exp\left(\text{sim}(c_m, c_{\mu(m)})/\tau_{con}\right)}{\sum_{i \neq m} \exp\left(\text{sim}(c_m, c_i)/\tau_{con}\right)}. \tag{4.13}$$

Each article has one positive pair and $2B - 2$ negatives in the batch. **The gradient of this loss flows back through both views into the encoder**. The positive view holds the tokens that speak for the topics and masks the rest, so to bring z close to $\hat{z}$ **the encoder learns to build z from these tokens**. The projection exists for this loss alone, and inference drops it.

The total training loss adds the classification loss on both views, with the same y, and the contrastive loss weighted by λ:

$$L = L^C(s, y) + L^C(\hat{s}, y) + \lambda L^{con}. \tag{4.14}$$

HGCLR uses binary cross-entropy for L^C; our model uses the asymmetric loss of Section 4.3.6. I kept λ at the value the paper reports for its two data sets, 0.1, and did not re-tune it after the change of loss. **At inference the generator, the positive view and the contrastive loss disappear**; the model is the solid chain of Figure 4.1.

4.4 Coherence rules

Section 2.2 defined a coherent prediction: each parent scores at least as high as each of its children. The head of Section 4.3.5 has no sense of the tree, so **a rule has to make the scores coherent**. **One setting picks the rule, and with it where the rule runs**: at inference alone, as a step after the sigmoid, or in training as well, inside the loss. Table 4.4 lists the five settings I compared; Chapter 6 gives their scores.

4.4.1 Rules at inference

A rule at inference takes the scores p of one article and returns coherent scores, and the threshold then runs on these. **The max rule is the one of C-HMCNN**, Equation 2.1: the score of a topic becomes the maximum over its subtree. It raises scores and lowers none, so it adds predictions and removes none; **recall goes up and precision goes down, by construction**.

Table 4.4: The five coherence settings. The rule in training sits inside the classification loss; the rule at inference runs on $p = \sigma(s)$ before the threshold.

Setting	Rule in training	Rule at inference	Origin
none	none	none	flat baseline
hard_max	none	max	C-HMCNN, as a step after the sigmoid
hard_avg_max	none	avg-max	ours, as a step after the sigmoid
chmcnn	max	max	C-HMCNN
chmcnn_avg_max	avg-max	avg-max	ours; the final model

The avg-max rule is my variant. Instead of lifting the parent to the child, **it moves both to their mean**: the parent goes up as much as the child goes down. It walks the tree from the deepest level up; inside a level it visits the topics in rising order of score; for each topic it climbs its ancestors, nearest first, and **when an ancestor scores below the topic, both take their mean**:

$$p_k \leftarrow \frac{p_k + p_j}{2}, \qquad p_j \leftarrow \frac{p_k + p_j}{2} \qquad \text{when } k \text{ is an ancestor of } j \text{ and } p_k < p_j. \tag{4.15}$$

In code, for one article:

```
for each level, from the deepest to the top:
    for each topic j of the level, in rising order of p[j]:
        for each ancestor k of j, nearest first:
            if p[k] < p[j]:
                p[k] = p[j] = (p[k] + p[j]) / 2
```

An ancestor rises and a topic falls, and no step does the reverse, so **after the pass each parent scores at least as high as each child, and the violation rate is zero at any threshold**. Table 4.5 runs the rule on one chain. **The max rule lifts the parents up to a wrong high child; the avg-max rule brings that child down as much as it lifts the parents**, so the sum of the scores stays the same. The reason to trust the parent is the data: **a parent has the articles of all its children, so it has more training data than any one child and scores with more reliability**. The max rule hands the parent the child's score; the avg-max rule weighs the two. **The rule sorts the topics of a level by score so that the highest child meets its parent last**; the parent arrives at that meeting lifted by the lower children, and so within one subtree the order of the topics holds.

Table 4.5: The two rules on one chain root → A → a. The avg-max rule averages (A, a), then (root, a), then (root, A).

	root	A	a
scores p	0.30	0.20	0.90
max rule	0.90	0.90	0.90
avg-max rule	0.4875	0.4875	0.425

4.4.2 Rules in training

A rule at inference repairs the scores and teaches the model no part of the tree. **C-HMCNN puts the rule inside the loss**. The loss of Section 4.3.6 then reads a corrected score p_j in place of the raw score $h_j = \sigma(s_j)$:

$$p_j = y_j \max_{k \in D_j} y_k \, h_k \; + \; (1 - y_j) \max_{k \in D_j} h_k, \tag{4.16}$$

with D_j the subtree of topic j, as in Equation 2.1. **For a topic the article has, the maximum runs over the article's own topics. For a topic it has not, the maximum runs over the whole subtree.** A wrong high child thus raises the loss of its parent, and the gradient reaches the child. This is the setting chmcnn, Equation 2.2 with ASL in place of the cross-entropy. **The setting chmcnn_avg_max puts the avg-max rule of Section 4.4.1 in place of each maximum.** A soft value between zero and one counts as a negative here.

A model trained with a rule in the loss predicts with the same rule at inference; its raw scores are not coherent on their own. Such a run converges slower than a flat run and needs more epochs. On the first version of the gold training set, Table 6.5, **the max rule in training lowered the scores**. At inference the max rule lowered the scores as well, and **the avg-max rule lowered none**. **The final model therefore trains with the avg-max rule**. Section 6.6 gathers the evidence.

4.4.3 The avg-max rule and its implementation

The max rule is cheap. The sigmoid keeps the order of the scores, so **the maximum can run on the logits**, as one masked maximum over the whole batch on the GPU.

The avg-max rule cannot run on the logits: the mean of two scores is not the sigmoid of the mean of their logits. So it runs on the scores, as the loop of Section 4.4.1, per article and per tree. **Each step of the loop is a mean, which is linear, and the choice of which pairs to average carries no gradient**: a comparison of two scores is a yes-or-no decision, and its derivative is zero, so autograd on the tensor version gives the same gradient as the tape, through the means alone. **The forward pass therefore records the pairs it averaged, as a tape, and the backward pass replays the same means in reverse order on the gradient**. **The implementation went through three versions**. The first ran the loop on tensors, with a `torch.where` and two index writes per step, so autograd tracked each step, fired or not, and the backward pass walked them all; it was far too slow. The second ran the loop in plain code and recorded the means as a matrix M per article, then computed $P = Mw$ under autograd, one linear operation per batch. **The third, in the final model, is the tape**: it records the pairs alone and replays them, with no matrix. The loop runs in float64 on the CPU, compiled with numba, and **takes about as long as the max rule on the GPU**.

The loss needs $\log p$ and $\log(1-p)$. **The loop therefore takes two inputs, the score of a topic being present, $\sigma(s)$, and the score of it being absent, $\sigma(-s)$, and applies each mean to both**, so that $\log(1-p)$ needs no subtraction in floating point.

4.5 Training settings

The final model trains the whole encoder with the settings of Table 4.6. **The optimizer is AdamW with three learning rates**: a low one for the encoder, which has to keep its language skill, a middle one for the graph encoder, and a high one for the blocks that start from scratch, the attention, the pool, the head and the projection. **The learning rate warms up over the first steps and then follows a cosine down to a floor**. **The batch is 16 articles, whatever the GPU**. A large GPU holds all 16 in one step. **A small one holds the same batch through gradient accumulation**: it runs the 16 articles in several smaller steps, sums their gradients, and updates the weights once. A small script picks the split from the GPU's memory and an estimate of the memory one step needs. **A topic with one vote out of three enters the loss as a soft value**, Section 3.3. **A run stops when the validation loss has not improved for a few evaluations, and the checkpoint with the best macro average precision is the one kept**.

Table 4.6: Training settings of the final model.

Setting	Value	Note
Trained parameters	all layers of the encoder, all blocks	
Optimizer	AdamW, weight decay 0.01	
Learning rate, encoder	3×10^{-5}	
Learning rate, graph encoder	1×10^{-4}	
Learning rate, other blocks	1×10^{-3}	attention, pool, head, projection
Schedule	warm-up 6 %, then cosine to 10 % of the peak	
Gradient clipping	1.0	
Effective batch	16 articles	micro-batch × accumulation, from the GPU's memory
Precision	bf16 autocast	fp32 master weights
Input length	4,096 tokens	
Soft value	0.5 for a topic with one vote	two votes or more count as 1
Early stop	validation loss, patience 3 evaluations	2 on the full corpus, two evaluations per epoch
Checkpoint kept	best macro average precision	

Chapter 5

Experimental setup

5.1 Environment

All training ran on rented cloud GPUs, one GPU per run, with a laptop for the code and the small tests. The frozen baselines fit the small GPUs; the fine-tunes and the HGCLR runs needed the large ones, because the encoder sees two views per step and the activations grow with the square of the input length. A small script turns the GPU's memory into a batch plan, so that each run keeps the same effective batch whatever the card. Table 5.1 lists the hardware and the software.

Table 5.1: The training environment.

Item	Value
Cloud GPUs	NVIDIA T4 and L4 for the frozen baselines; A100, L40S, H100 and H200 for the fine-tunes and HGCLR
Production GPU	NVIDIA T4, 16 GB, inference only
Precision	bf16 autocast, fp32 master weights
Attention kernel	flash attention 2 on Ampere and newer, SDPA otherwise
Optimizer	AdamW, one learning rate per parameter group
Effective batch	16 articles, split into micro-batches by the GPU's memory
Input length	up to 4,096 tokens in the final pipeline; 2,048 on the easy data set
Software	Python, PyTorch 2.4 or later, transformers 5, numba for the avg-max rule
Run store	Hugging Face Hub, one folder per run with configuration, commit hash and metrics

Each run writes its configuration, the commit hash of the code and its metrics into a run store on the Hugging Face Hub, and an index page sorts the runs by their scores. A colleague can repeat a run from its commit and its configuration file. The code has tests for the shapes of all tensors, for which loss reaches which parameters, and for the coherence rules; they run on the laptop before I rent a GPU.

5.2 Metrics and protocol

Section 2.6 defined the metrics; this section says which ones the tables report and how. All numbers come from the validation data unless a table is marked as test. The threshold is one half for all topics, so the threshold metrics are comparable across runs; a threshold tuned per topic appears in the error analysis alone. Macro average precision is the headline number and the sort key of the run store: it needs no threshold and it weights the rare topics as much as the

frequent ones. Next to it the tables give micro average precision, macro F1, recall and precision per level against the targets, and the violation rate. Recall at twenty appears where the ranking of the topics matters.

Three details of the protocol matter. The team set aside a list of topics that the product does not use; they stay in the model and in training, and the metrics skip their columns, so that the scores count the topics the product uses. For a setting that ran with several seeds, the table gives the mean over the seeds and, where the spread matters, the ensemble of the seeds as well, as Section 4.2.4 describes. And a run stops on the validation loss and keeps the checkpoint with the best macro average precision, so the number in the table is the best ranking seen before the model began to overfit.

Chapter 6

Results

Sections 6.1 to 6.4 report the runs on the easy data set, from the run index of the old platform; Sections 6.5 to 6.8 report the runs on the gold training set and the real test set. All numbers of the easy data set come from its validation split, with the threshold and the metrics of Chapter 5; a row with one seed uses the same seed throughout, and a row marked as an ensemble averages the scores of its seeds before the metrics.

6.1 Baselines on the easy data set: encoders, frozen and fine-tuned

Table 6.1 gathers the baselines of Section 4.2 on the easy data set, from the run index of Appendix C. **The rows are not all on the same footing**: some have one seed and some an ensemble of seeds, and the frozen head changed its learning rate in September. The source comment of the table names the run behind each row.

Three results stand. **EuroBERT beats multilingual-e5** with a frozen encoder; the high recall of the e5 row comes from over-prediction. **The large EuroBERT scores higher than the small one, at several times the time and memory**; so **the 210m is the base of the work**, and the choice between the two sizes, trained or frozen, follows the requirements and the production budget. **Training the encoder helps**: the fine-tuned 210m beats the frozen 210m with one seed and with the ensemble. The attention pool on the frozen encoder recovers part of that gap, which is why Section 4.3.4 keeps it. The Graphormer label attention of Section 4.2.3 reaches the fine-tuned baseline and does not pass it. LoRA has no row in the index, as Section 4.2.2 says.

Table 6.1: Baselines on the easy data set, validation split. One seed, or the ensemble of several seeds. Weighted BCE and no coherence rule unless stated.

Model	Encoder	Seeds	Macro AP	Micro AP	Macro F1	Macro recall
Frozen + head	EuroBERT 210m	1	0.563	0.710	0.530	0.672
Frozen + head	EuroBERT 210m	ens.	0.579	0.727	0.547	0.671
Frozen + head	EuroBERT 2.1B	1	0.581	0.722	0.548	0.633
Frozen + head	multilingual-e5	1	0.547	0.697	0.435	0.848
Frozen + attention pool	EuroBERT 210m	ens.	0.598	0.737	0.546	0.747
Fine-tune	EuroBERT 210m	1	0.606	0.753	0.560	0.683
Fine-tune	EuroBERT 210m	ens.	0.627	0.773	0.584	0.689
Fine-tune	EuroBERT 2.1B	1	0.612	0.752	0.504	0.835
Graphormer LA, fine-tune	EuroBERT 210m	ens.	0.627	0.760	0.601	0.636
Graphormer LA, frozen, max rule + ASL	EuroBERT 210m	ens.	0.632	0.775	0.588	0.646
Graphormer LA, frozen, max rule + ASL	EuroBERT 2.1B	ens.	0.624	0.767	0.581	0.634

6.2 Losses and coherence rules on the easy data set

Table 6.2 lists the ASL sweep of Section 4.3.6 on the frozen baseline, one seed per run. **A light focusing on the negatives scores the highest macro AP**. **A higher γ_- raises recall and lowers both F1 and macro AP**. Focusing on the positives alone lowers recall. The adaptive runs, where γ_- changes during training, score no better. The weighted BCE row comes from a later run, so it is a rough reference.

Table 6.2: The ASL sweep on the frozen baseline, easy data set, one seed. The weighted BCE row comes from a later run of the same baseline. Macro AP is the sort key of Chapter 6.

Loss	γ_-	γ_+	m	Macro AP	Macro F1	Macro recall	Micro AP
BCE, no weight	0	0	0	0.571	0.507	0.449	0.726
BCE, capped positive weight	0	0	0	0.563	0.530	0.672	0.710
ASL	0	0	0.05	0.575	0.502	0.450	0.724
ASL	1	0	0.05	**0.581**	0.540	0.571	0.740
ASL	2	0	0.025	0.575	0.542	0.653	0.725
ASL	2	0	0.05	0.575	0.538	0.673	0.726
ASL	2	0	0.1	0.570	0.529	0.682	0.721
ASL	3	0	0.05	0.559	0.528	0.655	0.710
ASL	4	0	0.05	0.550	0.522	0.649	0.706
ASL	6	0	0.05	0.553	0.504	0.695	0.705
ASL	6	0	0.1	0.554	0.492	0.721	0.705
ASL	0	1	0	0.567	0.463	0.377	0.722
ASL, adaptive γ_-, gap 0.1	–	0	0.05	0.554	0.514	0.695	0.707
ASL, adaptive γ_-, gap 0.05	–	0	0.05	0.553	0.519	0.664	0.706
ASL, adaptive γ_-, gap 0.01	–	0	0.05	0.553	0.521	0.657	0.706
ASL, adaptive γ_-, gap 0.005	–	0	0.05	0.552	0.521	0.661	0.706

Table 6.3 compares the coherence rules of Section 4.4 in pairs that differ in the rule alone. **On the easy data set neither rule hurts the model**: with the max rule or the avg-max rule, in the loss or at inference, the scores stay within the noise of one seed, and **a rule in the loss keeps the predictions coherent during training**. **The gold training set tells the two rules apart**, Section 6.6.

Table 6.3: Coherence rules on the easy data set. Each block differs in the rule alone. The last three columns give macro F1 with no rule, with the max rule and with the avg-max rule applied to the saved scores; a run trained with a rule in the loss has the same value in all three.

Model	Rule in training	Seeds	Macro AP	Macro recall	F1 flat	F1 max	F1 avg-max
Frozen, ASL	none	ens.	0.592	0.582	0.552	0.552	0.550
Frozen, ASL	max (C-HMCNN)	ens.	0.593	0.580	0.557	0.557	0.557
Frozen, ASL	none	1	0.581	0.571	0.540	0.540	0.540
Frozen, ASL	avg-max	1	0.581	0.591	0.546	0.546	0.546
Fine-tune, BCE	none	ens.	0.627	0.689	0.584	0.583	0.586
Fine-tune, BCE	max (C-HMCNN)	ens.	0.630	0.689	0.584	0.584	0.584

6.3 HGCLR and our changes on the easy data set

Table 6.4 gives the HGCLR runs of Section 4.3 on the easy data set, one seed each. Two findings shaped the final model.

HGCLR needs a trained encoder. With a frozen encoder the contrastive loss cannot change the vectors it compares, and **the runs reached the frozen baseline and no further**. **A mask guided by the topic names, a random mask and no mask all score the same**. All later work trains the encoder.

With a trained encoder HGCLR gains a little at a high cost. With the paper's schedule, a positive view at each step and all layers trained, **HGCLR scored below the plain fine-tune and trained much slower**. Two changes **brought it above the plain fine-tune**. The first trains the top layers of the encoder alone. The second builds the positive view on one batch out of several instead of on each batch: the other batches train like a plain fine-tune, with the classification loss alone, and skip the second pass through the encoder that the positive view costs.

The two blocks of Sections 4.3.3 and 4.3.4 came in with the final model on the gold training set, so they have no HGCLR row here.

Table 6.4: HGCLR on the easy data set, one seed each, weighted BCE unless stated. Frozen rows: the positive view comes from a mask that keeps the stated share of tokens; a guided mask keeps the tokens closest to the names of the article's topics. Fine-tune rows: the positive view comes from the graph-guided generator of Section 4.3.2. The positive views of a frozen run are encoded once and cached; the two rows with no mask differ only in how often the cache is rebuilt, which with no mask changes the random stream alone. The plain fine-tune row repeats Table 6.1.

Encoder	Positive view	Contrastive loss	Macro AP	Micro AP	Macro F1	Macro recall
frozen	none, the article itself; cache built once	yes	0.567	0.714	0.536	0.670
frozen	none, the article itself; cache rebuilt every 8 epochs	yes	0.565	0.713	0.537	0.653
frozen	guided mask, 90 %	yes	0.564	0.709	0.506	0.761
frozen	guided mask, 90 %, re-scored by the head	yes	0.564	0.708	0.500	0.768
frozen	random mask, 90 %	yes	0.563	0.707	0.503	0.756
frozen	none, the article itself	no	0.560	0.708	0.534	0.663
frozen	random mask, 80 %	no	0.548	0.694	0.509	0.709
frozen baseline, no HGCLR	–	–	0.563	0.710	0.530	0.672
fine-tune, all layers	generator, every step	yes	0.595	0.742	0.556	0.675
fine-tune, top 2 layers	generator, one batch in ten	yes	0.597	0.737	0.550	0.697
fine-tune, top 2, adaptive ASL	generator, one batch in ten	yes	0.604	0.755	0.455	0.858
fine-tune, top 6 layers	generator, one batch in four	yes	0.613	0.756	0.571	0.677
fine-tune, top 6 layers	generator, one batch in six	yes	0.616	0.757	0.574	0.680
plain fine-tune, no HGCLR	–	–	0.606	0.753	0.560	0.683

6.4 Summary on the easy data set

The easy data set settled the design before the gold training set arrived. EuroBERT 210m is the encoder; it trains, with the lower learning rate and the warm-up of Section 4.2.2; the loss is ASL with a light focusing on the negatives; a coherence rule leaves the ranking as it is and removes the violations; HGCLR adds a small gain with the top layers trained and a sparse schedule of positive views; and the attention pool is worth its cost. The best rows of the index on this data set, all ensembles of seeds, sit within one point of macro AP of each other: the fine-tune with ASL, the Graphormer label attention with the C-HMCNN rule and ASL, and the fine-tune with the C-HMCNN rule. One seed cannot separate them, which is the reason for Section 4.2.4.

One fact holds across all rows: at the threshold of one half, each model predicts far more topics per article than the data has. The frozen family predicts about three times the true count, the fine-tuned models somewhat more than the true count. The ranking is fine, the threshold is not: a threshold tuned per topic on the validation data lifts macro F1 without moving the average precision. Chapter 7 returns to this on the real test set.

6.5 Runs on the gold training set

The first runs on the gold training set ran on the old platform in mid-September, through a bridge that converted the new data to the old format, before the pipeline of Chapter 4 was rebuilt. Table 6.5 lists them. The index files most of them under the easy data set's name, because the bridge kept the old data stamp; they trained and validated on the gold set. The rows show the jump that the gold data brings to the frozen baseline, and the first run of the final design, HGCLR with the attention pool, the top layers trained, ASL and the C-HMCNN rule in the loss, which scores the highest macro AP of the index. The same design without a rule in the loss stopped early at a much lower score. The last row, with the avg-max rule, keeps all topics in the metrics and is not comparable to the rows above it.

Table 6.5: First runs on the gold training set, old platform, validation split of the gold set. The first four rows score about 251 topics; the last row scores all 329 and is not comparable.

Model	Rule in training	Seeds	Macro AP	Micro AP	Macro F1	Macro recall
Frozen + head, BCE	none	ens.	0.717	0.800	0.601	0.834
Frozen + head, BCE	max	ens.	0.702	0.805	0.584	0.830
HGCLR, attention pool, top 6 layers, ASL	max	1	0.758	0.879	0.693	0.754
HGCLR, attention pool, top 6 layers, ASL	none	1	0.606	0.843	0.542	0.566
HGCLR, attention pool, top 6 layers, ASL	avg-max	1	0.673	0.850	0.611	0.649

The other runs of the rebuilt pipeline on the gold training set follow in this section.

6.6 Choice of the coherence rule

Table 6.6 gathers the evidence behind the coherence rule of the final model, from both run indexes. Two findings decided the choice.

At inference the max rule lowers the scores and the avg-max rule raises them. The run index of the old platform scores each run trained without a rule a second time, after it applies each rule to the saved scores. On most of these runs the max rule lowers macro F1 and the avg-max rule raises it. The change is a few thousandths, but its sign holds across encoders, losses and both data sets. The max rule lifts each parent to its highest child and so adds predictions and loses precision; the avg-max rule brings the wrong high child down as it lifts the parent.

In the loss the max rule hurts on the full gold corpus and the avg-max rule does not. On the easy data set neither rule in the loss moves macro AP. On the gold data the max rule in the loss lowers macro AP for the frozen head of the old platform and for the 610m encoder on the full corpus; on the gold subset both rules score a little above no rule. In the record the avg-max rule in the loss scores at or above no rule.

The final model therefore trains and predicts with the avg-max rule: it keeps the predictions coherent and costs no score in the record. Each pair in the loss has one seed or one ensemble, and the two runs of a pair come from different commits; Section 8.2 names the pair that is missing.

6.7 Results on the real test set against the targets

6.8 Ablations, seeds and learning curves

Table 6.6: The evidence for the avg-max rule. A: each rule applied after training to the saved scores of the 58 runs of the old platform trained without a rule. B: the rule inside the loss, macro AP on the validation data; a dash marks a pair that was not run.

Data	Runs	No rule	Max	Avg-max
A. Rule at inference, macro F1				
easy and gold, old platform	58 runs, mean	0.494	0.492	0.496
	runs above no rule	–	4 of 58	52 of 58
B. Rule in the loss, macro AP				
easy	frozen + head, ASL, ensemble	0.592	0.593	–
easy	frozen + head, ASL, one seed	0.581	–	0.581
gold, old platform	frozen + head, BCE, ensemble	0.717	0.702	–
gold, subset	HGCLR, 210m, one seed	0.738	0.744	0.743
gold, full corpus	HGCLR, 610m, one seed	0.824	0.799	–

Chapter 7

Error analysis

7.1 The errors by level

Table 7.1 splits the scores of the final model by level, on the validation data and on the real test set. Two patterns hold. The deeper the level, the lower the score: level 1 is almost solved, level 3 is where the model errs. And each level scores lower on real articles than on generated ones, with the largest drop at levels 2 and 3. On the validation data the model predicts more topics per article than the LLMs gave, so precision is the weak side there; on the real test set the two counts are close.

Table 7.1: The final model by level. Macro AP, and precision and recall over all article-topic pairs at the threshold of one half.

		Validation, generated			Test, real		
Level	Topics	Macro AP	Precision	Recall	Macro AP	Precision	Recall
1	17	0.965	0.859	0.943	0.907	0.821	0.803
2	106	0.848	0.731	0.889	0.711	0.689	0.742
3	168	0.792	0.615	0.821	0.642	0.599	0.667
all	291	0.823	0.725	0.884	0.683	0.705	0.743
Topics per article, LLM / model		12.8 / 15.6			11.3 / 11.9		

7.2 Errors on the validation data: the model or the LLM topics?

On the validation data a disagreement between the model and the LLM topics can be an error of either side: the LLM topics are votes, not truth. A script ranks the validation articles where the model's scores point away from the LLM topics, and Table 7.2 shows one of them. The model gives the article topics the LLMs did not, *senior citizens* for a story about a retired woman, and these look right. It misses *fashion*, which two LLMs gave for a knitted scarf, and that one is open to debate. The body is cut at a paywall after two sentences, as a share of the training articles is.

To measure this, I let an LLM judge a random sample of such disagreements, blind to which side proposed each topic. Table 7.3 gives the verdicts. For a topic the model adds, the model is wrong in most cases, so its precision is a real weakness. For a topic the model misses, the LLM topic is wrong in more than half of the cases, so a large part of the measured recall gap is noise in the topics, not in the model. The audit ran on an earlier run of the same design, with a single LLM judge and no human check.

Table 7.2: A validation article where the model and the LLM topics disagree. *Une retraitée d'Ajaccio tricote une écharpe de 21 kilomètres, chantier textile inédit en Corse*: a 72-year-old retired woman finishes a scarf 21 km long; the body stops at a paywall after two sentences. Votes: LLMs out of three that gave the topic; 0 means no LLM did.

Topic	Votes	Score
human interest	3	1.00
human interest > record and achievement	3	0.66
lifestyle and leisure	3	0.49
lifestyle and leisure > leisure	2	0.31
arts, culture, entertainment and media > arts and entertainment > fashion	2	0.05
society > demographic group > senior citizens	0	0.94
society > communities	0	0.71

Table 7.3: Blind LLM judge on validation disagreements, earlier run of the same design. One judge, no human check.

Disagreement	Model wrong	LLM topics wrong
model adds a topic the LLMs did not give	88 %	6 %
model misses a topic the LLMs gave	26 %	56 %

7.3 Errors on the real test set: a different mix of topics

An LLM wrote the training and validation articles; the test articles are real French press. The two differ less in style than in their mix of topics. Table 7.4 gives the share of articles that carry each level 1 topic. Politics and economy fill the generated articles; lifestyle, weather, environment and the arts are far more common in real press. The model scores lower on the topics that grew: it misses part of lifestyle and weather, and it gives *human interest* to half of the real articles while the LLMs give it to a third. Selecting the checkpoint on generated validation data hides this shift.

Table 7.4: Share of articles that carry a level 1 topic, in the generated validation data and in the real test set, and the model's results on the real test set at the threshold of one half. Topics with the largest change.

	LLM topics		Model, real test set		
Level 1 topic	Generated	Real	Predicted	Precision	Recall
politics and government	60 %	38 %	35 %	0.92	0.84
economy, business and finance	46 %	36 %	34 %	0.86	0.82
crime, law and justice	27 %	17 %	15 %	0.88	0.78
lifestyle and leisure	6 %	28 %	22 %	0.89	0.69
environment	9 %	22 %	19 %	0.92	0.79
weather	2 %	13 %	9 %	0.97	0.65
arts, culture, entertainment and media	16 %	24 %	25 %	0.78	0.82
human interest	29 %	33 %	52 %	0.59	0.92

The worst real articles, ranked by a script on the number of level 1 errors, are in many cases not articles at all. Table 7.5 shows the third worst: an author page of *Libération* that lists the latest headlines of its photo service. The LLMs tagged it with the topics of the listed stories; the model reads a page about the Middle East and predicts diplomacy. Index pages, daily digests, video pages and copies of the same text fill the top of this ranking. On an earlier run, removing

them all raised F1 by less than half a point, so they explain a small part of the gap.

Table 7.5: A real test page with many errors. *Service Photo : ses derniers articles publiés*, an author page of *Libération* that lists headlines: the war in the Middle East, the PSG victory, a heat wave. Missed: a topic the LLMs gave and the model scored below one half. Added: the reverse.

Topic	Error	Score
human interest	missed	0.42
health	missed	0.41
environment	missed	0.35
sport	missed	0.27
weather	missed	0.19
science and technology	added	0.75
politics and government > international relations > diplomacy	added	0.94

7.4 Lessons for the next model

Three lessons follow. **Work on precision, not recall**: most topics the model adds are wrong, while many of the topics it misses are noise in the LLM votes, so a lower threshold would chase the noise. **Select and calibrate on real articles**: the generated validation data has another topic mix, so a checkpoint or a threshold chosen on it does not carry over to real press. On an earlier run, a threshold per topic tuned on real articles raised F1 by about a point. **Clean the real input**: a filter should remove index pages and digests before the model sees them; the gain in the scores is small, but the product should not tag such pages at all.

Chapter 8

Discussion

8.1 What worked and what did not

8.2 Limits

The head is a three-layer MLP from the first frozen baseline on. I did not test it against the single linear layer of HGCLR, nor against other depths, so the depth of the head is an untested choice.

The avg-max rule went into the loss of the final model on two results: the max rule in the loss lowered the scores against no rule, and the avg-max rule at inference lowered none. The pair that closes the argument, the avg-max rule in the loss against no rule, exists on a subset of the gold corpus alone, with one seed, Table 6.6; on the full corpus it is missing.

The avg-max rule in the loss has one open case. A logit below about -744 gives a score of zero in float64; a zero takes part in no mean, so its $\log p$ is minus infinity and the loss of that batch is not a number. A guard in the training loop skips such a batch, which happened once in the final runs; a clamp on the logits would remove the case.

8.3 Deployment

8.4 Next steps

Chapter 9

Side work: relevance rerankers for thematic search

9.1 Problem and data

9.2 zerank cross-encoders run locally

9.3 GLiNER2 as a zero-shot classifier

9.4 Findings

Chapter 10

Conclusion

10.1 Summary of results

10.2 Personal review

Bibliography

[1] Nicolas Boizard et al. Eurobert: Scaling multilingual encoders for european languages, 2025. arXiv preprint; TODO confirm authors and id.

[2] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International Conference on Machine Learning (ICML)*, 2020. TODO confirm; NT-Xent as cited by HGCLR.

[3] Eleonora Giunchiglia and Thomas Lukasiewicz. Coherent hierarchical multi-label classification networks. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

[4] International Press Telecommunications Council. Iptc media topics newscodes. `https://iptc.org/standards/media-topics/`, 2026.

[5] Tal Ridnik, Emanuel Ben-Baruch, Nadav Zamir, Asaf Noy, Itamar Friedman, Matan Protter, and Lihi Zelnik-Manor. Asymmetric loss for multi-label classification. In *IEEE/CVF International Conference on Computer Vision (ICCV)*, 2021.

[6] torchmil developers. torchmil: Attentionpool. `https://torchmil.readthedocs.io/en/latest/api/nn/attention/attention_pool/`, 2025. TODO confirm authors and year.

[7] Zihan Wang, Peiyi Wang, Lianzhe Huang, Xin Sun, and Houfeng Wang. Incorporating hierarchy into text encoder: a contrastive learning approach for hierarchical text classification. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2022. exploration/docs/2022.acl-long.491.pdf.

[8] Chengxuan Ying, Tianle Cai, Shengjie Luo, Shuxin Zheng, Guolin Ke, Di He, Yanming Shen, and Tie-Yan Liu. Do transformers really perform bad for graph representation? In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[9] Jie Zhou, Chunping Ma, Dingkun Long, Guangwei Xu, Ning Ding, Haoyu Zhang, Pengjun Xie, and Gongshen Liu. Hierarchy-aware global model for hierarchical text classification. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics (ACL)*, 2020. exploration/docs/2020.acl-main.104.pdf.

Appendix A

Full architecture graph

Appendix B

Configuration file and flag semantics

Appendix C

Run index

Appendix D

LLM labelling prompts

Appendix E

Experiment journal excerpts