



Лабораторная работа №5

Молчанов Сергей ИС223

1. Создали среду 2 ПК для отдела программистов и 2 ноутбуков для отдела бухгалтеров и прописали им айди и маску и соединили их коммутатором switch



2. С помощью команд мы создали vlan 2 для отдела программистов и vlan 3 для отдела бухгалтеров и проверили



```
Switch>en
Switch#conf t
Enter configuration commands, one per line. End with CNTL/Z.
Switch(config)#vlan 2
Switch(config-vlan)#name programmer
Switch(config-vlan)#exit
Switch(config)#vlan 3
Switch(config-vlan)#name bugal
Switch(config-vlan)#exit
Switch(config)#exit
Switch#
SYS-5-CONFIG_I: Configured from console by console

Switch#show vlan

VLAN Name                Status    Ports
-----
1    default                active    Fa0/1, Fa0/2, Fa0/3, Fa0/4,
                                           Fa0/5, Fa0/6, Fa0/7, Fa0/8,
                                           Fa0/9, Fa0/10, Fa0/11, Fa0/12,
                                           Fa0/13, Fa0/14, Fa0/15, Fa0/16,
                                           Fa0/17, Fa0/18, Fa0/19, Fa0/20,
                                           Fa0/21, Fa0/22, Fa0/23, Fa0/24
                                           Gig0/1, Gig0/2
2    programmer              active
3    bugal                   active
1002 fddi-default            active
1003 token-ring-default    active
1004 fddinet-default       active
1005 tnnnet-default        active

VLAN Type  SAID      MTU    Parent RingNo BridgeNo Stp    BrgdMode Trans1 Trans2
-----
1    enet    100001    1500   -      -      -      -      -      0      0
2    enet    100002    1500   -      -      -      -      -      0      0
3    enet    100003    1500   -      -      -      -      -      0      0

Switch#
```

3. Внутри vlan 2 мы добавили для первого ПК порт 0/1 для второго ПК порт 0/2

```
Switch(config)#int fa0/1
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 2
Switch(config-if)#exit
Switch(config)#int fa0/2
Switch(config-if)#switchport mode access
Switch(config-if)#switchport access vlan 2
Switch(config-if)#exit
Switch(config)#
```

4. Проделали тоже для отдела бухгалтеров, внутри vlan 3

Switch#show vlan


VLAN Name	Status	Ports
1 default	active	Fa0/5, Fa0/6, Fa0/7, Fa0/8 Fa0/9, Fa0/10, Fa0/11, Fa0/12 Fa0/13, Fa0/14, Fa0/15, Fa0/16 Fa0/17, Fa0/18, Fa0/19, Fa0/20 Fa0/21, Fa0/22, Fa0/23, Fa0/24 Gig0/1, Gig0/2
2 programmer	active	Fa0/1, Fa0/2
3 bugal	active	Fa0/3, Fa0/4
1002 fddi-default	active	
1003 token-ring-default	active	
1004 fddinet-default	active	
1005 trnet-default	active	

VLAN Type	SAID	MTU	Parent	RingNo	BridgeNo	Stp	BrdgMode	Trans1	Trans2
1 enet	100001	1500	-	-	-	-	-	0	0
2 enet	100002	1500	-	-	-	-	-	0	0
3 enet	100003	1500	-	-	-	-	-	0	0
1002 fddi	101002	1500	-	-	-	-	-	0	0
--More--									


5. Мы передали пакеты данных внутри vlan

The screenshot displays the Cisco Packet Tracer interface. The main workspace shows a network topology with a central 2960-24TT Switch connected to four devices: PC-PT PC0, Laptop-PT Laptop0, PC-PT PC1, and Laptop-PT Laptop1. The interface includes a top menu bar, a toolbar, and a bottom status bar. On the right side, the 'Simulation Panel' is open, showing an 'Event List' with a table of events. The table has columns for 'Vis', 'Time(sec)', and 'Last Device'. The events list shows a series of ICMP Echo (ping) events between the switch and the laptops, with timestamps ranging from 0.310 to 1.000 seconds. The 'Play Controls' section at the bottom right includes buttons for 'Reset Simulation', 'Constant Delay', and 'Captured to: 1.000 s'. The bottom status bar shows the time as 80:17:01.548 and the simulation mode as 'Realtime'.

6. Мы передали пакеты вне vlan и выдало failed



7. Так же пинганули наш комп



#я больше ничего делать не буду