

# Functional API for Deep Learning

# Sequential API

```
# defining the architecture of the model
model = Sequential()
model.add(InputLayer(input_shape=(input_neurons,)))
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))
model.add(Dense(units=output_neurons, activation='sigmoid'))
```

```
# summary of the model
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6

Total params: 181  
Trainable params: 181  
Non-trainable params: 0

analytics  
vidhya

# Sequential API

```
# defining the architecture of the model  
model = Sequential()  
model.add(InputLayer(input_shape=(input_neurons,)))  
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))  
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))  
model.add(Dense(units=output_neurons, activation='sigmoid'))
```

```
# summary of the model  
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6

Total params: 181  
Trainable params: 181  
Non-trainable params: 0

analytics  
vidhya

# Sequential API

```
# defining the architecture of the model
model = Sequential()
model.add(InputLayer(input_shape=(input_neurons,)))
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))
model.add(Dense(units=output_neurons, activation='sigmoid'))
```

```
# summary of the model
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6

Total params: 181  
Trainable params: 181  
Non-trainable params: 0

Input Layer


analytics  
vidhya

# Sequential API

```
# defining the architecture of the model
model = Sequential()
model.add(InputLayer(input_shape=(input_neurons,)))
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))
model.add(Dense(units=output_neurons, activation='sigmoid'))
```

```
# summary of the model
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6
Total params: 181		
Trainable params: 181		
Non-trainable params: 0		




# Sequential API

```
# defining the architecture of the model
model = Sequential()
model.add(InputLayer(input_shape=(input_neurons,)))
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))
model.add(Dense(units=output_neurons, activation='sigmoid'))
```

```
# summary of the model
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6

Total params: 181  
Trainable params: 181  
Non-trainable params: 0




# Sequential API

```
# defining the architecture of the model
model = Sequential()
model.add(InputLayer(input_shape=(input_neurons,)))
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))
model.add(Dense(units=output_neurons, activation='sigmoid'))
```

```
# summary of the model
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6

Total params: 181  
Trainable params: 181  
Non-trainable params: 0




# Sequential API

```
# defining the architecture of the model
model = Sequential()
model.add(InputLayer(input_shape=(input_neurons,)))
model.add(Dense(units=neuron_hidden_layer_1, activation='relu'))
model.add(Dense(units=neuron_hidden_layer_2, activation='relu'))
model.add(Dense(units=output_neurons, activation='sigmoid'))
```


```
# summary of the model
model.summary()
```

Layer (type)	Output Shape	Param #
dense_1 (Dense)	(None, 10)	120
dense_2 (Dense)	(None, 5)	55
dense_3 (Dense)	(None, 1)	6
Total params: 181		
Trainable params: 181		
Non-trainable params: 0		







# Sequential API




Analytics Vidhya



# Sequential API



Analytics Vidhya




# Functional API

1. Provides more flexibility to define models
2. Can define multiple inputs, outputs models
3. Split and share the intermediate layers
4. Build State-of-the-Art model architectures or Custom architecture

# Build Simple NN model using Functional API

Create Layers and Connect



 Analytics Vidhya

# Build Simple NN model using Functional API

```
[ ] # defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1 = Dense(units=neuron_hidden_layer_1, activation='relu')(x)
hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(hidden1)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)


model_functional = Model(x, output)

[ ] # summary of the model
model_functional.summary()
```



Layer (type)	Output Shape	Param #
input_2 (InputLayer)	(None, 11)	0
dense_4 (Dense)	(None, 10)	120
dense_5 (Dense)	(None, 5)	55
dense_6 (Dense)	(None, 1)	6

=====  
Total params: 181  
Trainable params: 181  
Non-trainable params: 0  
=====



# Build Simple NN model using Functional API


```
[ ] # defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1 = Dense(units=neuron_hidden_layer_1, activation='relu')(x)
hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(hidden1)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)

model_functional = Model(x, output)

[ ] # summary of the model
model_functional.summary()
```



Layer (type)	Output Shape	Param #
input_2 (InputLayer)	(None, 11)	0
dense_4 (Dense)	(None, 10)	120
dense_5 (Dense)	(None, 5)	55
dense_6 (Dense)	(None, 1)	6
Total params: 181		
Trainable params: 181		
Non-trainable params: 0		



# Build Simple NN model using Functional API

```
[ ] # defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1 = Dense(units=neuron_hidden_layer_1, activation='relu')(x)
hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(hidden1)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)


model_functional = Model(x, output)

[ ] # summary of the model
model_functional.summary()
```



Layer (type)	Output Shape	Param #
input_2 (InputLayer)	(None, 11)	0
dense_4 (Dense)	(None, 10)	120
dense_5 (Dense)	(None, 5)	55
dense_6 (Dense)	(None, 1)	6

=====  
Total params: 181  
Trainable params: 181  
Non-trainable params: 0  
=====



# Build Simple NN model using Functional API

```
[ ] # defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1 = Dense(units=neuron_hidden_layer_1, activation='relu')(x)
hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(hidden1)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)
```


```
model_functional = Model(x, output)
```

```
[ ] # summary of the model
model_functional.summary()
```



Layer (type)	Output Shape	Param #
input_2 (InputLayer)	(None, 11)	0
dense_4 (Dense)	(None, 10)	120
dense_5 (Dense)	(None, 5)	55
dense_6 (Dense)	(None, 1)	6

=====  
Total params: 181  
Trainable params: 181  
Non-trainable params: 0  
=====





# Build Simple NN model using Functional API

```
[ ] # defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1 = Dense(units=neuron_hidden_layer_1, activation='relu')(x)
hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(hidden1)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)
```


```
model_functional = Model(x, output)
```

```
[ ] # summary of the model
model_functional.summary()
```




Layer (type)	Output Shape	Param #
input_2 (InputLayer)	(None, 11)	0
dense_4 (Dense)	(None, 10)	120
dense_5 (Dense)	(None, 5)	55
dense_6 (Dense)	(None, 1)	6

=====  
Total params: 181  
Trainable params: 181  
Non-trainable params: 0  
=====



# Build a Ad-hoc architecture using Functional API



# Build a Ad-hoc architecture using Functional API

```
# defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1_1 = Dense(units=neuron_hidden_layer_1_1, activation='relu')(x)
hidden1_2 = Dense(units=neuron_hidden_layer_1_2, activation='relu')(x)

combined = concatenate([hidden1_1, hidden1_2])

hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(combined)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)

model_functional = Model(x, output)
```

```
# summary of the model
model_functional.summary()
```

Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 11)	0	
dense_1 (Dense)	(None, 10)	120	input_1[0][0]
dense_2 (Dense)	(None, 20)	240	input_1[0][0]
concatenate_1 (Concatenate)	(None, 30)	0	dense_1[0][0] dense_2[0][0]
dense_3 (Dense)	(None, 5)	155	concatenate_1[0][0]
dense_4 (Dense)	(None, 1)	6	dense_3[0][0]
Total params: 521			
Trainable params: 521			
Non-trainable params: 0			

Input Layer

# Build a Ad-hoc architecture using Functional API

```
# defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1_1 = Dense(units=neuron_hidden_layer_1_1, activation='relu')(x)
hidden1_2 = Dense(units=neuron_hidden_layer_1_2, activation='relu')(x)


combined = concatenate([hidden1_1, hidden1_2])

hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(combined)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)

model_functional = Model(x, output)
```

```
# summary of the model
model_functional.summary()
```

Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 11)	0	
dense_1 (Dense)	(None, 10)	120	input_1[0][0]
dense_2 (Dense)	(None, 20)	240	input_1[0][0]
concatenate_1 (Concatenate)	(None, 30)	0	dense_1[0][0] dense_2[0][0]
dense_3 (Dense)	(None, 5)	155	concatenate_1[0][0]
dense_4 (Dense)	(None, 1)	6	dense_3[0][0]
Total params: 521			
Trainable params: 521			
Non-trainable params: 0			



# Build a Ad-hoc architecture using Functional API

```
# defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1_1 = Dense(units=neuron_hidden_layer_1_1, activation='relu')(x)
hidden1_2 = Dense(units=neuron_hidden_layer_1_2, activation='relu')(x)


combined = concatenate([hidden1_1, hidden1_2])

hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(combined)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)

model_functional = Model(x, output)
```

```
# summary of the model
model_functional.summary()
```

Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 11)	0	
dense_1 (Dense)	(None, 10)	120	input_1[0][0]
dense_2 (Dense)	(None, 20)	240	input_1[0][0]
concatenate_1 (Concatenate)	(None, 30)	0	dense_1[0][0] dense_2[0][0]
dense_3 (Dense)	(None, 5)	155	concatenate_1[0][0]
dense_4 (Dense)	(None, 1)	6	dense_3[0][0]
Total params: 521			
Trainable params: 521			
Non-trainable params: 0			



# Build a Ad-hoc architecture using Functional API

```
# defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1_1 = Dense(units=neuron_hidden_layer_1_1, activation='relu')(x)
hidden1_2 = Dense(units=neuron_hidden_layer_1_2, activation='relu')(x)


combined = concatenate([hidden1_1, hidden1_2])

hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(combined)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)

model_functional = Model(x, output)
```

```
# summary of the model
model_functional.summary()
```

Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 11)	0	
dense_1 (Dense)	(None, 10)	120	input_1[0][0]
dense_2 (Dense)	(None, 20)	240	input_1[0][0]
concatenate_1 (Concatenate)	(None, 30)	0	dense_1[0][0] dense_2[0][0]
dense_3 (Dense)	(None, 5)	155	concatenate_1[0][0]
dense_4 (Dense)	(None, 1)	6	dense_3[0][0]
Total params: 521			
Trainable params: 521			
Non-trainable params: 0			



# Build a Ad-hoc architecture using Functional API

```
# defining the architecture of the model using Functional API
x = Input(shape = (input_neurons,))
hidden1_1 = Dense(units=neuron_hidden_layer_1_1, activation='relu')(x)
hidden1_2 = Dense(units=neuron_hidden_layer_1_2, activation='relu')(x)


combined = concatenate([hidden1_1, hidden1_2])

hidden2 = Dense(units=neuron_hidden_layer_2, activation='relu')(combined)
output = Dense(units=output_neurons, activation='sigmoid')(hidden2)

model_functional = Model(x, output)
```

```
# summary of the model
model_functional.summary()
```

Layer (type)	Output Shape	Param #	Connected to
input_1 (InputLayer)	(None, 11)	0	
dense_1 (Dense)	(None, 10)	120	input_1[0][0]
dense_2 (Dense)	(None, 20)	240	input_1[0][0]
concatenate_1 (Concatenate)	(None, 30)	0	dense_1[0][0] dense_2[0][0]
dense_3 (Dense)	(None, 5)	155	concatenate_1[0][0]
dense_4 (Dense)	(None, 1)	6	dense_3[0][0]
Total params: 521			
Trainable params: 521			
Non-trainable params: 0			





Thank You