




I. SUPPLEMENTARY MATERIAL: DERIVATION OF THE TIME INDEPENDENT INDUCED ELECTRIC POTENTIAL FOR A FREE-SURFACE SYSTEM IN A RECTANGULAR DOMAIN

In this section, we derive the induced electric potential for a rectangular domain with four different electrical boundary conditions. The first case has the trivial solution i.e. $\Psi|_{\Omega} = 0$. The remaining cases and their boundary conditions are summarized in Table I. Insulating boundaries generally require a nontrivial potential correction. We first derive the potential correction Ψ in a domain with all insulating walls (B.C 4). Cases B.C 2 and 3 are modifications of B.C 4.

TABLE I. The electrical boundary and free-surface conditions of the three cases considered.

Case No.	Case name	Boundary conditions
2	B.C 2	 $\Psi _{x=\pm 0.5L_x} = 0,$ $\partial_y \Psi _{y=\pm 0.5L_y} = -\partial_x \phi B_z,$ $\partial_z \Psi _{z=0} = 0, \partial_z \Psi _{z=-h} = 0.$
3	B.C 3	 $\partial_x \Psi _{x=\pm 0.5L_x} = \partial_y \phi B_z,$ $\partial_y \Psi _{y=\pm 0.5L_y} = -\partial_x \phi B_z,$ $\partial_z \Psi _{z=0} = 0, \Psi _{z=-h} = 0.$
4	B.C 4	 $\partial_x \Psi _{x=\pm 0.5L_x} = \partial_y \phi B_z,$ $\partial_y \Psi _{y=\pm 0.5L_y} = -\partial_x \phi B_z,$ $\partial_z \Psi _{z=0} = 0, \partial_z \Psi _{z=-h} = 0.$

A. Electric potential of B.C 4:

From Eq. (6) in the main article, the Laplace equation for the induced electric potential can be expanded to

$$\frac{\partial^2 \Psi}{\partial x^2} + \frac{\partial^2 \Psi}{\partial y^2} + \frac{\partial^2 \Psi}{\partial z^2} = 0. \quad (\text{I.1})$$

We write $\Psi(m, n) = A(x) B(y) C(z)$, where A , B and C are functions of x , y and z accordingly

$$\frac{1}{A} \frac{\partial^2 A}{\partial x^2} + \frac{1}{B} \frac{\partial^2 B}{\partial y^2} + \frac{1}{C} \frac{\partial^2 C}{\partial z^2} = 0. \quad (\text{I.2})$$

Introducing constants ξ_x , ξ_y and ξ_z such that

$$\xi_x^2 + \xi_y^2 + (-\xi_z^2) = 0. \quad (\text{I.3})$$

From the given boundary conditions for B.C 4 in Table I, there is no straightforward way to solve the above Laplace equation using separation of variables, mainly due to the presence of non-zero boundary conditions in the x - and y -normal walls. This causes two of the constants to show exponential behavior in the solution, instead of separated modes with one hyperbolic and two trigonometric factors. Because the total sum of the balance must be zero, two of

the constants need to have the opposite sign of the third. As a solution to this problem, we split the residual problem into two harmonic components:

$$\text{I} : \xi_x^2 + (-\xi_y^2) + (-\xi_z^2) = 0, \quad (\text{I.4a})$$

$$\text{II} : (-\xi_x^2) + \xi_y^2 + (-\xi_z^2) = 0, \quad (\text{I.4b})$$

with Eqs. (I.4a and I.4b) solve the Laplace equation (I.2) in a system with the following boundary conditions:

$$\text{I} : \partial_x \Psi \big|_{x=\pm 0.5L_x} = \partial_y \phi B_z, \quad \partial_y \Psi \big|_{y=\pm 0.5L_y} = 0, \quad \partial_z \Psi \big|_{z=-h} = 0 \quad (\text{I.5a})$$

$$\text{II} : \partial_x \widehat{\Psi} \big|_{x=\pm 0.5L_x} = 0, \quad \partial_y \Psi \big|_{y=\pm 0.5L_y} = -\partial_x \phi B_z, \quad \partial_z \Psi \big|_{z=-h} = 0 \quad (\text{I.5b})$$

We first solve for system I considering the boundary conditions at $x = -0.5L_x$ and $x = 0.5L_x$:

$$\frac{\partial \Psi}{\partial x} \bigg|_{x=-0.5L_x, 0.5L_x} = \frac{\partial A}{\partial x}(-0.5L_x, 0.5L_x) B(y) C(z) = \frac{\partial \phi}{\partial y} B_z \bigg|_{x=-0.5L_x, 0.5L_x}. \quad (\text{I.6})$$

The term $A(x)$ can be written as a sum of hyperbolic functions

$$A(x) = A_{1x} \cosh [\xi_x x] + A_{2x} \sinh [\xi_x x], \quad (\text{I.7})$$

and at $x = -0.5L_x$:

$$\frac{\partial A}{\partial x} \bigg|_{x=-0.5L_x} = A_{1x} \xi_x \sinh [-\xi_x L_x/2] + A_{2x} \xi_x \cosh [-\xi_x L_x/2], \quad (\text{I.8})$$

$$= -\frac{n\pi}{L_y} \sin \left[\frac{n\pi}{L_y} (y + 0.5L_y) \right] \cos [0], \quad (\text{I.9})$$

whereas at $x = 0.5L_x$:

$$\frac{\partial A}{\partial x} \bigg|_{x=0.5L_x} = A_{1x} \xi_x \sinh [\xi_x L_x/2] + A_{2x} \xi_x \cosh [\xi_x L_x/2], \quad (\text{I.10})$$

$$= -\frac{n\pi}{L_y} \sin \left[\frac{n\pi}{L_y} (y + 0.5L_y) \right] \cos [m\pi]. \quad (\text{I.11})$$

When m is odd,

$$2A_{2x} \xi_x \cosh [\xi_x L_x/2] = 0, \quad \therefore A_{2x} = 0 \implies A(x) = A_{1x} \cosh [\xi_x x], \quad (\text{I.12})$$

and when m is even,

$$-2A_{1x} \xi_x \sinh [\xi_x L_x/2] = 0, \quad \therefore A_{1x} = 0 \implies A(x) = A_{2x} \sinh [\xi_x x]. \quad (\text{I.13})$$

Therefore,

$$A(x) = A_{1x} \frac{1 - (-1)^m}{2 \operatorname{sech} [\xi_x x]} + A_{2x} \frac{1 + (-1)^m}{2 \operatorname{csch} [\xi_x x]}. \quad (\text{I.14})$$

At the y -normal walls,

$$\frac{\partial B}{\partial y} (-0.5L_y, 0.5L_y) = 0, \quad (\text{I.15})$$

and therefore,

$$B(y) = \sum_{a=0}^{\infty} B_y \cos \left[\frac{a\pi}{L_y} \left(y + \frac{L_y}{2} \right) \right]. \quad (\text{I.16})$$

The boundary conditions at the bottom wall ($z = -h$), are

$$\frac{\partial C}{\partial z} (z = -h) = 0, \quad (\text{I.17})$$

and at the free-surface ($z \approx 0$) is

$$\frac{\partial C}{\partial z}(z \approx 0) = 0. \quad (\text{I.18})$$

This gives the vertical cosine basis

$$C(z) = \sum_{b=0}^{\infty} C_z \cos \left[\frac{b\pi}{h} (z + h) \right]. \quad (\text{I.19})$$

Combining the coefficients such that

$$\left(A_{1x} \frac{1 - (-1)^m}{2} + A_{2x} \frac{1 + (-1)^m}{2} \right) B_y C_z = \ddot{\mathcal{A}}_{ab}, \quad (\text{I.20})$$

the solution for system I is

$$\Rightarrow \sum_{a=0}^{\infty} \sum_{b=0}^{\infty} \ddot{\mathcal{A}}_{ab} \left(\frac{1 - (-1)^m}{2 \operatorname{sech}[\xi_x x]} + \frac{1 + (-1)^m}{2 \operatorname{csch}[\xi_x x]} \right) \cos \left[\frac{a\pi}{L_y} \left(y + \frac{L_y}{2} \right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right]. \quad (\text{I.21})$$

Similarly, the solution for system II is

$$\Rightarrow \sum_{a=0}^{\infty} \sum_{b=0}^{\infty} \ddot{\mathcal{B}}_{ab} \left(\frac{1 - (-1)^n}{2 \operatorname{sech}[\xi_y y]} + \frac{1 + (-1)^n}{2 \operatorname{csch}[\xi_y y]} \right) \cos \left[\frac{a\pi}{L_x} \left(x + \frac{L_x}{2} \right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right], \quad (\text{I.22})$$

where

$$\xi_x = \pi \sqrt{\left(\frac{a}{L_y} \right)^2 + \left(\frac{b}{h} \right)^2}, \quad \xi_y = \pi \sqrt{\left(\frac{a}{L_x} \right)^2 + \left(\frac{b}{h} \right)^2}. \quad (\text{I.23})$$

Combining the solutions of system I and II, we get

$$\begin{aligned} \Psi = & \sum_{a=0}^{\infty} \sum_{b=0}^{\infty} \ddot{\mathcal{A}}_{ab} \left(\frac{1 - (-1)^m}{2 \operatorname{sech}[\xi_x x]} + \frac{1 + (-1)^m}{2 \operatorname{csch}[\xi_x x]} \right) \cos \left[\frac{a\pi}{L_y} \left(y + \frac{L_y}{2} \right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right] \\ & + \sum_{a=0}^{\infty} \sum_{b=0}^{\infty} \ddot{\mathcal{B}}_{ab} \left(\frac{1 - (-1)^n}{2 \operatorname{sech}[\xi_y y]} + \frac{1 + (-1)^n}{2 \operatorname{csch}[\xi_y y]} \right) \cos \left[\frac{a\pi}{L_x} \left(x + \frac{L_x}{2} \right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right]. \end{aligned} \quad (\text{I.24})$$

We now need to determine the coefficients $\ddot{\mathcal{A}}_{ab}$ and $\ddot{\mathcal{B}}_{ab}$. This is achieved by projecting the boundary conditions in Table I (B.C 4) onto the oscillatory functions of Eq. (I.24) using the orthogonality relation

$$\int_{-0.5L}^{0.5L} \cos \left[\frac{a\pi}{L} \left(x + \frac{L}{2} \right) \right] \cos \left[\frac{a'\pi}{L} \left(x + \frac{L}{2} \right) \right] = \begin{cases} L, & a = 0, \\ 0.5L, & a \neq 0 \end{cases}, \quad (\text{I.25})$$

which yields a non-zero solution only for the condition $a = a'$ and thus, removing the double summations from the coefficients. The resulting coefficients as given in Eqs. (33 and 34) in the main article. The double sum in Eq. (I.24) consists of real elements for all elements of the series except when $a = 0$ and $b = 0$ which raises an undefined value, both in the expression, and in the coefficients $\ddot{\mathcal{A}}_{ab}$ and $\ddot{\mathcal{B}}_{ab}$. This non-zero mode representation requires separate treatment, giving rise to coupled polynomial contributions that are unique to case B.C 4. These originate from the boundary conditions in the x - and y -normal walls

$$\ddot{\mathcal{A}}_0 = \int \partial_y \phi_y B_z, \quad \& \quad \ddot{\mathcal{B}}_0 = \int -\partial_x \phi_x B_z. \quad (\text{I.26})$$

The expressions of $\ddot{\mathcal{A}}_0$ and $\ddot{\mathcal{B}}_0$ are elaborated in Eq. (32). This results in the final expression of the induced electric potential

$$\begin{aligned} \Psi(\text{B.C 4}) = & \ddot{\mathcal{A}}_0 x - \frac{\ddot{\mathcal{A}}_0(-1^n + (-1)^{m+n+1})}{2L_x} \left(x - \frac{L_x}{2}\right)^2 + \ddot{\mathcal{B}}_0 y - \frac{\ddot{\mathcal{B}}_0(-1^m + (-1)^{m+n+1})}{2L_y} \left(y - \frac{L_y}{2}\right)^2 \\ & + \sum_{\substack{a,b \geq 0 \\ (a,b) \neq (0,0) \\ a \neq n}}^{\infty} \ddot{\mathcal{A}}_{ab} \left(\frac{1 - (-1)^m}{2 \operatorname{sech}[\ddot{\xi}_x x]} + \frac{1 + (-1)^m}{2 \operatorname{csch}[\ddot{\xi}_x x]} \right) \cos \left[\frac{a\pi}{L_y} \left(y + \frac{L_y}{2}\right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right] \\ & + \sum_{\substack{a,b \geq 0 \\ (a,b) \neq (0,0) \\ a \neq m}}^{\infty} \ddot{\mathcal{B}}_{ab} \left(\frac{1 - (-1)^n}{2 \operatorname{sech}[\ddot{\xi}_y y]} + \frac{1 + (-1)^n}{2 \operatorname{csch}[\ddot{\xi}_y y]} \right) \cos \left[\frac{a\pi}{L_x} \left(x + \frac{L_x}{2}\right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right]. \end{aligned} \quad (\text{I.27})$$

B. Electric potential of B.C 2:

In case B.C 2, all the boundary conditions are the same as in B.C 4 except for the x -normal walls. This results in the solution of system I in Eq. (I.21) being equal to zero. The resultant expression for the electric potential is therefore:

$$\Psi(\text{B.C 2}) = \sum_{a,b=0}^{\infty} \ddot{\mathcal{B}}_{ab} \left(\frac{1 - (-1)^n}{2 \operatorname{sech}[\ddot{\xi}_y y]} + \frac{1 + (-1)^n}{2 \operatorname{csch}[\ddot{\xi}_y y]} \right) \sin \left[\frac{a\pi}{L_x} \left(x + \frac{L_x}{2}\right) \right] \cos \left[\frac{b\pi}{h} (z + h) \right], \quad (\text{I.28})$$

where $\ddot{\mathcal{B}}_{ab}$ is obtained using the orthogonality condition, which yields the expression presented in Eq. (23) in the main article.

C. Electric potential of B.C 3:

Case B.C 3 is also a modification of B.C 4, with the exception of the conducting bottom wall, which creates an asymmetric boundary condition along the z -axis. This is due to the free-surface acting as an insulating wall and the bottom wall being a perfect conductor,

$$\frac{\partial C}{\partial z}(z \approx 0) = 0, \quad C(z = -h) = 0, \quad (\text{I.29})$$

which results in

$$C(z) = \sum_{b=0}^{\infty} C_z \sin \left[(2b+1)p_h(z+h) \right], \quad \text{with } p_h = \frac{\pi}{2h}. \quad (\text{I.30})$$

Using the approach outlined in Sec. I A for case B.C 4, we obtain the following expression for the electric potential:

$$\begin{aligned} \Psi(\text{B.C 3}) = & \sum_{\substack{a,b \geq 0 \\ (a,b) \neq (0,0) \\ a \neq n}}^{\infty} \tilde{\mathcal{A}}_{ab} \left(\frac{1 - (-1)^m}{2 \operatorname{sech}[\tilde{\xi}_x x]} + \frac{1 + (-1)^m}{2 \operatorname{csch}[\tilde{\xi}_x x]} \right) \cos \left[\frac{a\pi}{L_y} \left(y + \frac{L_y}{2}\right) \right] \sin \left[(2b+1)p_h(z+h) \right] \\ & + \sum_{\substack{a,b \geq 0 \\ (a,b) \neq (0,0) \\ a \neq m}}^{\infty} \tilde{\mathcal{B}}_{ab} \left(\frac{1 - (-1)^n}{2 \operatorname{sech}[\tilde{\xi}_y y]} + \frac{1 + (-1)^n}{2 \operatorname{csch}[\tilde{\xi}_y y]} \right) \cos \left[\frac{a\pi}{L_x} \left(x + \frac{L_x}{2}\right) \right] \sin \left[(2b+1)p_h(z+h) \right], \end{aligned} \quad (\text{I.31})$$

where the coefficients $\tilde{\mathcal{A}}_{ab}$ and $\tilde{\mathcal{B}}_{ab}$ are obtained from the orthogonality condition. This gives expressions presented in Eqs. (28 and 29) in the main article. Similar to B.C 4, we need to incorporate additional constants to satisfy the

boundary conditions when the summation indices $a, b = 0$. This results in the terms $\tilde{\mathcal{A}}_0$ and $\tilde{\mathcal{B}}_0$, which are presented in Eqs. (26 and 27) in the main article. The final expression of the electrical potential is given by

$$\begin{aligned} \Psi(\text{B.C } 3) = & \sin[(z+h)p_h] \left(\frac{\tilde{\mathcal{A}}_0((-1)^m - (-1)^n) \sinh[p_h x]}{2p_h \cosh[0.5p_h L_x]} - \frac{\tilde{\mathcal{A}}_0((-1)^m + (-1)^n) \cosh[p_h x]}{2p_h \sinh[0.5p_h L_x]} \right. \\ & + \frac{\tilde{\mathcal{B}}_0((-1)^n - (-1)^m) \sinh[p_h y]}{2p_h \cosh[0.5p_h L_y]} - \frac{\tilde{\mathcal{B}}_0((-1)^n + (-1)^m) \cosh[p_h y]}{2p_h \sinh[0.5p_h L_y]} \Bigg) \\ & + \sum_{\substack{a,b \geq 0 \\ (a,b) \neq (0,0) \\ a \neq n}}^{\infty} \tilde{\mathcal{A}}_{ab} \left(\frac{1 - (-1)^m}{2 \operatorname{sech}[\tilde{\xi}_x x]} + \frac{1 + (-1)^m}{2 \operatorname{csch}[\tilde{\xi}_x x]} \right) \cos \left[\frac{a\pi}{L_y} \left(y + \frac{L_y}{2} \right) \right] \sin \left[(2b+1)p_h(z+h) \right] \\ & + \sum_{\substack{a,b \geq 0 \\ (a,b) \neq (0,0) \\ a \neq m}}^{\infty} \tilde{\mathcal{B}}_{ab} \left(\frac{1 - (-1)^n}{2 \operatorname{sech}[\tilde{\xi}_y y]} + \frac{1 + (-1)^n}{2 \operatorname{csch}[\tilde{\xi}_y y]} \right) \cos \left[\frac{a\pi}{L_x} \left(x + \frac{L_x}{2} \right) \right] \sin \left[(2b+1)p_h(z+h) \right]. \end{aligned} \quad (\text{I.32})$$

II. SUPPLEMENTARY MATERIAL: THE MECHANICAL ENERGY BALANCE IN THE BULK

In this section, we provide the detailed methodology of deriving the Ohmic damping rate λ_o using the mechanical energy balance, written once again in its complete form here:

$$\underbrace{\frac{d}{dt} \left(\frac{1}{2} \int_V \rho |\mathbf{u}|^2 dV \right)}_{E_{\text{kin}}} + \underbrace{\frac{d}{dt} \left(\int_S \frac{1}{2} \rho g \eta^2 dS \right)}_{E_{\text{pot}}} = \underbrace{\int_V \mathbf{u} \cdot (\mathcal{J} \times B_z \mathbf{e}_z) dV}_{D_{\text{bulk}}}, \quad (\text{II.1})$$

where each integral term E_{kin} is the time rate of change kinetic energy of the bulk, E_{pot} is the time rate of change potential energy of the free-surface and D_{bulk} , is the energy per unit volume transferred between the electromagnetic field and the moving fluid. On expanding $\mathcal{J}$ in the scalar triple product

$$\begin{aligned} \mathbf{u} \cdot (\mathcal{J} \times B_z \mathbf{e}_z) &= -\mathcal{J} \cdot (\mathbf{u} \times B_z \mathbf{e}_z), \\ &= - \left[-\sigma \nabla \Psi (\mathbf{u} \times B_z \mathbf{e}_z) + \sigma \|\mathbf{u} \times B_z \mathbf{e}_z\|^2 \right], \\ &= -\mathcal{J} \cdot \nabla \Psi - \frac{\mathcal{J}^2}{\sigma}. \end{aligned} \quad (\text{II.2})$$

Substituting Eq. (II.2) in (II.1), the term $\mathcal{J} \cdot \nabla \Psi$ on the integral on the right-hand side expands to

$$\int_V \mathcal{J} \cdot \nabla \Psi = \int_{\partial V} \Psi \mathcal{J} \cdot \mathbf{n} dS - \int_V \Psi \nabla \cdot \mathcal{J} dV, \quad (\text{II.3})$$

where,

$$\int_{\partial V} \Psi \mathcal{J} \cdot \mathbf{n} dS = \int_{\Sigma} \Psi \mathcal{J} \cdot \mathbf{n} dS + \int_S \Psi \mathcal{J} \cdot \mathbf{n} dS. \quad (\text{II.4})$$

In Eq. (II.3), $\nabla \cdot \mathcal{J} = 0$, by virtue of conservation of charge. In the following Eq. (II.4), the normal currents $\mathcal{J} \cdot \mathbf{n} = 0$ at insulating walls, whereas $\Psi = 0$ at conducting walls. These transformations reduce the complete balance equation to the one presented in Eq. (37), in the main article. Therefore, D_{bulk} is expanded as follows:

$$\begin{aligned} D_{\text{bulk}} &= \int_V \nabla \phi \cdot (\sigma [-\nabla \Psi + \nabla \phi \times B_z \mathbf{e}_z] \times B_z \mathbf{e}_z) dV, \\ &= \int_V \nabla \phi \cdot (-\sigma \nabla \Psi \times B_z \mathbf{e}_z) dV - \sigma \int_V \|\nabla \phi \times B_z \mathbf{e}_z\|^2 dV, \\ &= \mathcal{Q}_{\text{corr}} - \mathcal{Q}_{\text{ind}}. \quad \{\text{see Eqs. (39 and 40)}\} \end{aligned} \quad (\text{II.5})$$

The total dissipation averaged over a single oscillation cycle is

$$D_{\text{bulk}} = \frac{1}{2}(\mathcal{Q}_{\text{corr}} - \mathcal{Q}_{\text{ind}}). \quad (\text{II.6})$$

The flow velocity $\mathbf{u}$ and free-surface elevation η decay in proportion to $e^{-\lambda_o t}$ with respect to time t . For a standing wave, the total energy considering wave decay is the sum of the kinetic and potential energy with a phase difference, given by:

$$E_{\text{kin}} + E_{\text{pot}} = -\lambda_o \frac{1}{2} \int_V \rho |\mathbf{u}|^2 dV \cos[\omega t]^2 - \lambda_o \frac{1}{2} \int_S \rho g \eta^2 dS \cos[\omega t + 0.5\pi]^2. \quad (\text{II.7})$$

In the above equation, the integral

$$\int_S \rho g \eta^2 dS = p|_{z=0} \eta dS = K, \quad (\text{II.8})$$

which is hydrostatic pressure condition that is obtained from the kinematic-dynamic coupling of an inviscid, irrotational flow of a lightly deformed free-surface. On expanding η using Eq. (13), we obtain the expression for K as per Eq. (41) in the article. Similarly, using the vector identity $\nabla \phi \cdot \nabla \phi = \nabla \cdot (\phi \nabla \phi) - \phi \nabla \cdot \nabla \phi$, we write

$$\begin{aligned} \int_V \rho |\nabla \phi|^2 dV &= \int_V (\nabla \cdot \phi \nabla \phi - \phi \nabla^2 \phi) dV, \\ &= \int_{\partial V} \rho \phi \nabla \phi \cdot \mathbf{n} dS. \end{aligned} \quad (\text{II.9})$$

The above integral vanishes at the rigid walls Σ due to the impermeability condition $\mathbf{u} \cdot \mathbf{n} = 0$. At the free-surface, $\nabla \phi \cdot \mathbf{n}|_{z=0} = \partial_z \phi$, and from Eqs. (13 and 14) in the main article, the vertical component of the velocity potential is expressed as $\partial_z \phi = i\omega \phi$. Therefore, Eq. (II.9) is

$$\begin{aligned} \int_V \rho |\nabla \phi|^2 dV &= \int_S (-\rho(i\omega)\phi)|_{z=0} \eta dS, \\ &= \int_S p|_{z=0} \eta dS = K, \quad \{\cdot \cdot p = -\rho(i\omega)\phi\}. \end{aligned} \quad (\text{II.10})$$

From Eqs. (II.6, II.7, II.8 and II.10), we obtain the following relation for λ_o :

$$-\lambda_o K \cos[\omega t]^2 - \lambda_o K \sin[\omega t]^2 = \frac{1}{2}(\mathcal{Q}_{\text{corr}} - \mathcal{Q}_{\text{ind}}) \quad (\text{II.11})$$

$$\therefore \lambda_o = \frac{\mathcal{Q}_{\text{ind}} - \mathcal{Q}_{\text{corr}}}{2K} \quad (\text{II.12})$$

III. SUPPLEMENTARY MATERIAL: THE MECHANICAL ENERGY BALANCE AT THE BOUNDARY

As in Sec. II, we apply the mechanical energy balance but for the dissipation at the boundary due to viscous and magnetic effects. We calculate the damping rate due to boundary effects λ_b , which comprises of the damping rate due to the Hartmann layer at the bottom, and the Shercliff layer at the sidewalls. To summarize, the mechanical energy balance of a standing wave, considering dissipation at the boundaries is given by

$$\underbrace{\frac{d}{dt} \left(\frac{1}{2} \int_V \rho |\mathbf{u}|^2 dV \right)}_{E_{\text{kin}}} + \underbrace{\frac{d}{dt} \left(\int_S \frac{1}{2} \rho g \eta^2 dS \right)}_{E_{\text{pot}}} = \underbrace{-2\rho\nu \int_V \boldsymbol{\varepsilon} : \boldsymbol{\varepsilon} dV}_{D_b}, \quad (\text{III.1})$$

The terms E_{kin} and E_{pot} in Eq. (III.1) only consist of bulk quantities like $\mathbf{u}$ without the corrections, which in this particular case, decay proportional to $e^{-\lambda_b t}$. The boundary damping rate consists of $\lambda_b = \lambda_{\text{Ha}}(\text{wall}) + \lambda_{\text{Sh}}(\text{sidewall})$, each of which we calculate separately. Following the steps outlined in Sec. II, the total energy during the cycle is

$$E_{\text{kin}} + E_{\text{pot}} = -\lambda_* K, \quad (\text{III.2})$$

with

$$K = 0.25 A_{mn}^2 \epsilon_{mn} \rho g L_x L_y e^{-2\lambda_* t}, \quad \lambda_* = \lambda_{Ha}, \lambda_{Sh}, \quad \epsilon_r = \begin{cases} 2, & r = 0 \\ 1, & r \neq 0 \end{cases}. \quad (\text{III.3})$$

On the right hand side of Eq. (III.1), expanding the strain rate tensor $\boldsymbol{\varepsilon} = 0.5(\nabla \mathbf{u} + \nabla \mathbf{u}^T)$ in the double dot product gives

$$2 \boldsymbol{\varepsilon} : \boldsymbol{\varepsilon} = \|\nabla \times \mathbf{u}\|^2 + 2 \nabla \cdot ((\mathbf{u} \cdot \nabla) \mathbf{u}) \quad (\text{III.4})$$

The dissipation term D_b now takes the form of the Lamb's dissipation integral

$$D_b = -\rho \nu \int_V \|\nabla \times \mathbf{u}\|^2 dV - 2\rho \nu \int_{\partial V} (\mathbf{u} \cdot \nabla) \mathbf{u} \cdot \mathbf{n} dS, \quad (\text{III.5})$$

which consists of the dissipation due to rotational stresses at the boundary and the higher order irrotational stresses in the bulk. We calculate only the rotational stresses at the boundary, where only the corrections contribute. The boundary dissipation is therefore:

$$D_b = -\rho \nu \int_V \|\nabla \times \bar{\mathbf{u}}_\perp\|^2 dV, \quad (\text{III.6})$$

where tangential velocity corrections in the Hartmann and Shercliff layers are

$$\text{Re}[\bar{\mathbf{u}}_\perp](\text{Ha}) = -\nabla \phi e^{-\frac{\sqrt{1+\sqrt{1+\tau^2\omega^2}}}{\sqrt{2\tau\nu}}\zeta}, \quad \text{Re}[\bar{\mathbf{u}}_\perp](\text{Sh}) = -\nabla \phi e^{-\frac{\sqrt{1+\sqrt{1+\tau h^2\omega^2/\nu}}}{\sqrt{2}\sqrt{\tau\nu}}\zeta}. \quad (\text{III.7})$$

Here, the wall-normal coordinate ζ is the spatial coordinate normal to the wall that reduces the boundary layer corrections to zero away from the wall. It is given by

$$\zeta = \begin{cases} z+h, & \text{near } z=-h, \\ \frac{L_x}{2} - x, & \text{near } x=L_x/2, \\ \frac{L_y}{2} - y, & \text{near } y=L_y/2, \end{cases} \quad \begin{cases} x + \frac{L_x}{2}, & \text{near } x=-L_x/2, \\ y + \frac{L_y}{2}, & \text{near } y=-L_y/2, \end{cases}. \quad (\text{III.8})$$

Substituting the velocity corrections at the walls given in Eq. (III.7) into Eq. (III.6), we get

$$D_{Ha} = A_{mn}^2 \frac{\rho \nu \omega^2}{4\sqrt{2}} \sqrt{\frac{1}{\tau\nu} + \sqrt{\frac{1}{\tau^2\nu^2} + \frac{\omega^2}{\nu^2}}} \left(\frac{\epsilon_{mn} L_x L_y}{2 \sinh^2[kh]} \right) e^{-2\lambda_{Ha} t}, \quad (\text{III.9})$$

which is the dissipation due to the Hartmann layer at the top and bottom wall, and

$$D_{Sh} = A_{mn}^2 \frac{\rho \nu \omega^2}{\sqrt{2} k^2} \sqrt{\frac{1}{h\sqrt{\tau\nu}} + \sqrt{\frac{1}{h^2\tau\nu} + \frac{\omega^2}{\nu^2}}} \left(\epsilon_n \left[\frac{h(n^2\pi^2 - k^2 L_y^2)}{4L_y \sinh^2[kh]} + \frac{(n^2\pi^2 + k^2 L_y^2)}{4L_y k \tanh[kh]} \right] \right. \\ \left. + \epsilon_m \left[\frac{h(m^2\pi^2 - k^2 L_x^2)}{4L_x \sinh^2[kh]} + \frac{(m^2\pi^2 + k^2 L_x^2)}{4L_x k \tanh[kh]} \right] \right) e^{-2\lambda_{Sh} t}, \quad (\text{III.10})$$

which is the dissipation due to the Shercliff layer at all four sidewalls. For most industrial application where $B_z < ST3$, the dissipation term from Eq. (III.10) simplifies to

$$D_{Sh} \approx A_{mn}^2 \frac{\rho \nu \omega^2}{\sqrt{2} k^2} \sqrt{\frac{\omega}{\nu}} \left(\epsilon_n \left[\frac{h(n^2\pi^2 - k^2 L_y^2)}{4L_y \sinh^2[kh]} + \frac{(n^2\pi^2 + k^2 L_y^2)}{4L_y k \tanh[kh]} \right] \right. \\ \left. + \epsilon_m \left[\frac{h(m^2\pi^2 - k^2 L_x^2)}{4L_x \sinh^2[kh]} + \frac{(m^2\pi^2 + k^2 L_x^2)}{4L_x k \tanh[kh]} \right] \right) e^{-2\lambda_{Sh} t}, \quad (\text{III.11})$$

which is the dissipation due rotational stresses solely due to the viscous boundary layer.

From Eqs. (III.2 and III.6), we get the expression for λ_b , in its complete form is as follows:

$$\lambda_b = \lambda_{Ha} + \lambda_{Sh} = \frac{D_{Ha} + D_{Sh}}{K} \quad (\text{III.12})$$