

5. Write a MPI Program to demonstration of MPI_Send and MPI_Recv.

```
#include <mpi.h>
#include <stdio.h>

int main(int argc, char** argv) {
    MPI_Init(&argc, &argv); // Initialize MPI

    int rank, size, data;

    MPI_Comm_rank(MPI_COMM_WORLD, &rank); // Get current process ID
    MPI_Comm_size(MPI_COMM_WORLD, &size); // Get total number of processes

    if (size < 2) {
        if (rank == 0)
            printf("This program requires at least 2 processes.\n");
        MPI_Finalize();
        return 0;
    }

    if (rank == 0) {
        data = 42;

        MPI_Send(&data, 1, MPI_INT, 1, 0, MPI_COMM_WORLD);

        printf("Process 0 sent data: %d to Process 1\n", data);
    }

    if (rank == 1) {
        MPI_Recv(&data, 1, MPI_INT, 0, 0, MPI_COMM_WORLD, MPI_STATUS_IGNORE);

        printf("Process 1 received data: %d from Process 0\n", data);
    }

    MPI_Finalize(); // Finalize MPI

    return 0;
}
```

Output:

```
mpicc send_recv_simple.c -o send_recv_simple
```

```
mpi_programs$ mpirun ./send_recv_simple
```

```
Process 1 received data: 42 from Process 0
```

```
Process 0 sent data: 42 to Process 1
```