

RIGEL · SPEC EDITOR

Game Modes Guide

Build team games: teams, rounds, scores, traps, balls, scoreboards and your own Luau.

Contents

- | | | | |
|-------------------|---|--------------------|--|
| 1 | What a game mode is | 7 | Text on signs |
| 2 | Opening the Game Modes window | 8 | Your own code |
| 3 | Making one | 9 | The examples |
| 4 | Teams and team changers | 10 | Troubleshooting |
| 5 | Rules | 11 | Building game modes with an AI agent |
| 6 | Pieces and roles | | |

1 What a game mode is


A **game mode** is an area of the station with its own **teams, rounds and scores**. You build one in the Spec Editor, fill it with pieces -- team changers, start and score buttons, traps, force fields, timers, ball spawners, scoreboards, text signs -- and the server runs it for everyone, Quest players included, with no mods on their side.

- Players pick a team by walking into one of the mode's **team changers**.
- A round goes **idle** -> **countdown** -> **running** -> **ended** -> **idle**. The server counts the countdown and the round time, keeps the scores, decides the winner and tells every machine.
- Pieces get **roles** ("start button", "trap on during rounds", "ball spawner" ...). The editor turns the roles into the mode's **controller script** and wires everything for you.
- Your own Luau adds the rules only you can think of, through a handful of hooks and the **Rigel** library.
- Game modes are saved in your levels and come back exactly when a level loads.


2 Opening the Game Modes window

Click **Game Modes** in the toolbar (next to **+ Add**), or open **Details > Game Modes** and click **Open the Game Modes window**. The window can be moved and resized; your game modes are on the left, the one you picked on the right. Every game mode also shows in the viewport as an orange box (green while a round runs) with its name and state.

A level must be open to make a game mode (**Levels** tab, or Ctrl+S to save one).




1 the **Game Modes** button in the toolbar. **2** a game mode's area: the orange box, with its name and state on top. **3** its team changers (outlined).



The Game Modes window. **1** your game modes (click one to edit it). **2** its state, round, and each team's players and points. **3** round controls: Start round, End round, Reset, Go to (flies the camera there), Delete. **4** each team's name and max players. **5** Place team changer, one per team.

3 Making one

1. Fly to where the arena should be: a game mode is made around the point in front of the camera.
2. Click **+ New game mode**. Type a **name**, choose **1 to 4 teams**, name each team and set its **max players**.
3. Click **Create**. The orange box shows the area (about 78 x 95 x 19 m). Everything placed inside it belongs to the mode.



1 + New game mode. **2** the mode's name. **3** how many teams. **4** each team's name and max players. **5** Create.

Two modes can't overlap. **Delete...** removes a mode and everything in it.

4 Teams and team changers


For each team, **Place team changer** puts a team changer in front of the camera (the spot must be inside the box). Walking into it puts a player on that team; the team's size and the max show in the window and on scoreboards.

- A team changer is a **door**: its middle is 1.5 m up, so the server stands it on the floor under the spot you pick, facing the way the camera looks (players walk through it in that direction).
- Mark the doors so players can find them. The examples frame each door in its team's colour (two cube posts just outside the 3.5 m opening and a beam over the top; nothing crosses the doorway) with a sign above it: `{<mode>.team1.name} team`.

- Rename a team or change its max right in the window (press Enter / click away to apply).
- Team changers only work inside a game mode. Placed anywhere else the server refuses them.
- If a player is standing exactly where you place (or move) a team changer, it appears next to them and moves into place as soon as they step off. A changer created on top of a player would crash their game.

5 Rules

Rule	Meaning
Start	<i>Manual</i> (the window's Start round, or a script), <i>Start button</i> (a button with the Start role), <i>Automatic</i> (when every team has enough players)
Players per team to start	for Automatic
Countdown (s)	seconds between "start" and the round beginning; 0 = straight away
Round length (s)	0 = no time limit (the round ends by score or by a script)
Score to win	a team reaching it wins at once; 0 = no limit
Result shown (s)	how long the result stays before the lobby
Restart automatically	start the next round after the result
End a round when every team is empty	so an abandoned round doesn't run forever: once a round has had players on a team and they all leave. A round started with empty teams keeps running
Ball back to its spawner after a goal	a Goal / Score box point resets every ball (a kick-off)



The rules. **1** how a round starts (Manual / Start button / Automatic). **2** players per team to start, countdown, round length, score to win, how long the result shows. **3** restart automatically, and end a round when every team is empty.


Start round, **End round** and **Reset** in the window control the mode by hand. **Go to** flies the camera there.

6 Pieces and roles

Place pieces shows every useful piece with its icon; clicking one places it inside the mode (in front of the camera) and gives it its role straight away. **Objects and roles** lists everything in the mode with its icon; change any object's role from its drop-down.



Place pieces: each tile places that piece inside the mode with its role already set. **1** buttons: start, score, trap. **2** traps (the whole orange group). **3** moving platforms. **4** force field, for walls that open and close. **5** the round timer. **6** timer display, scoreboards and the score table.



Objects and roles. **1** the controller: the object that runs the mode's script (made with the mode, keep it). **2** each object's role. **3** the slot name your own code uses for that object (Start1, ScoreBoard1 ...). Score buttons also say which team they score for. **4** Apply script, Edit my code, Start from example..., and Auto-apply on save.

Role	For	What it does
Start button	buttons	starts a round (when none is on)
Score button (team N)	buttons	+1 point for team N while a round runs
Trap - on during rounds	traps, sliding platforms	switched on when a round starts, off when it ends
Trap - pulses during rounds (seconds)	traps	flips on/off every N seconds while a round runs
Trap - fired by trap buttons	traps	switched on for a while when a trap button is pressed
Trap button (seconds)	buttons	fires every "fired by trap buttons" trap for N seconds
Wall - between rounds only	force fields, walls	solid between rounds, gone while a round runs
Wall - during rounds only	force fields, walls	only there while a round runs


Force fields are switched on and off for the wall roles; any other piece is shown and hidden (and its collision switched) instead -- the editor picks the right one for the object.

Round timer	Timer	counts the countdown, then the round (or up, with no limit)
Ball spawner	Jake ball / ball spawners	the server spawns or resets its ball when a round starts
Goal (team N)	Driftball goal, Goal	the ball going in during a round gives team N the goal's points (1, more for long shots)
Score box (team N, 0 = by side)	Score box (a disc trigger)	the ball flies <i>through</i> it; each pass during a round gives team N a point. 0 = by side: along the box's forward arrow scores for team 1, the other way for team 2
Ball start ring	Ball start ring	between rounds, carry the ball into it to start a round; hidden while a round is on
Scoreboard (score + clock)	the classic Score board	shows team 1 / team 2 points
Score table	the Score table	one row per team: name, score, players, rounds won

After changing roles click **Apply script** (or keep **Auto-apply on save** on and just save your code).

Scoreboards

- **Scoreboard monitors** (and the side / half-court versions) need no role: the mode keeps its team scores and rounds won on them, and drives their clock and the arena state. During the **countdown** the monitor shows the seconds counting down while the round clock waits at the full round length; when the round starts it switches to the clock and the scores.
- A monitor shows its game page only once someone is on a team; with every team empty it shows the empty-arena page.
- The classic **Score board** shows team 1 and team 2 points (role *Scoreboard*).
- The **Score table** shows a row per team (role *Score table*).
- A **Text sign** can show anything the mode knows through templates (below).



In the arena: **1** a scoreboard monitor (its clock and the teams' scores), **2** the classic Score board (team 1 : team 2, rounds).

Balls, goals and the start ring (driftball)

Jake ball spawners (and the other ball spawners) spawn a real, networked ball on the server that every player sees. Give the spawner the **Ball spawner** role: the server spawns or resets the ball when each round starts, and `Rigel.resetBalls()` does it whenever your code asks (after a goal, say). Don't spawn balls from Luau: the script runs on every machine and each would make its own ball that only it can see.

Moving and sizing a ball. A ball is made at run time, so what you really place is its spawner. The editor lists the balls of your spawners (*Ball (edits its spawner)*) and you can pick and drag them like anything else: the spawner

moves by as much as you moved the ball, and the ball follows. Moving the spawner itself does the same. Balls the station owns (training balls, death balls) are not listed.

- **Resize a ball** by scaling the ball (not the spawner): the game sizes a spawner's ball at $1 / \text{the spawner's scale}$ on every machine, so a ball scaled to 2 sets its spawner to 0.5. Sizes 0.25 to 4 work; the ball keeps its size through rounds and moves, rests on the floor at its new size, and plays normally.
- **Rotating a ball** changes nothing: a ball's rotation is its physics (it rolls).
- Any edit to a spawner (move, scale, turn) rebuilds it, and it makes a fresh ball -- the old one is replaced, not lost. Scaling the *spawner* resizes its ball the other way round (a big spawner makes a small ball).
- **Goals.** Place a *Driftball goal* from the pieces (or give any goal the **Goal** role) and set the team that scores there. The game's own goal detection fires, the mode adds the goal's points to that team, and -- with *Ball back to its spawner after a goal* on (the default) -- every ball goes back to its spawner for a kick-off. The goal takes the colour of the team defending it.
- **Score boxes.** A *Score box* is a trigger the ball passes through (it doesn't bounce off). Give it a team, or **0 = by side**: the direction the ball crosses decides the team (along the box's forward arrow = team 1, the other way = team 2) -- rotate the box so its arrow points at team 2's end. Scale it to the gap you want to guard.
- **Start ring.** With a *Ball start ring* the mode keeps its ball out between rounds; a player carries it into the ring to start the round, like the station's arenas. The first 3 seconds after a round ends don't count (the ball is being put back), so a ring next to the spawner is fine. The ring hides while a round runs.
- A goal or box counts once even though every machine sees it (the server ignores repeats of the same goal within 2.5 s), and only while a round is running. In your own code, `Rigel.goal(team, points, key)` does the same.

7 Text on signs

Put a Text object in the mode and give it a text with `{templates}`. They update live for everyone. For a mode called **Arena**:


```
{Arena.state} {Arena.time} {Arena.round} {Arena.winner} {Arena.players} {Arena.team1.name}  
{Arena.team1.score} {Arena.team1.size} {Arena.team1.max} {Arena.team1.wins} (and team2, ...)
```

The window's **Text on signs** section lists them with a copy button. Your code can add its own:

```
Rigel.setText("Leader", "Blue lead!") fills {Leader}.
```

8 Your own code

Click **Edit my code** to open `Documents\RigelScripts\GameModes\<mode name>.luau` in VS Code (a template is made the first time), or **Start from example...** to begin from one of the examples. The editor puts your code into the mode's controller script together with the roles; **Show generated** shows the whole thing.



2 Start from example... opens 1 the list of example codes. Picking one replaces your code for this mode and applies it.

Don't write `BeginPlay` -- write any of these hooks:

```
function OnLobby() end -- no round on
function OnCountdown(seconds: number) end -- a round is about to start
function OnRoundStart(round: number) end -- round = 1, 2, ...
function OnRoundEnd(winner: number) end -- winner = team number, 0 = draw
function OnTeamChanged(team: number, size: number, old: number) end
function OnScore(team: number, score: number, old: number) end
function OnTime(secondsLeft: number) end -- every second of a countdown or round
```

Objects with roles are available by their slot names (shown next to each object in the window): `Start1`, `Score1`, `TrapRound1`, `TrapFired2`, `Timer1`, `Ball1`, `ScoreBoard1`, ...

The Rigel library


Read	
<code>Rigel.state()</code>	<code>"idle"</code> , <code>"countdown"</code> , <code>"running"</code> , <code>"ended"</code>
<code>Rigel.isRunning()</code> , <code>Rigel.round()</code> , <code>Rigel.timeLeft()</code>	round state; seconds left
<code>Rigel.teams()</code> , <code>Rigel.teamName(t)</code> , <code>Rigel.teamSize(t)</code> , <code>Rigel.teamMax(t)</code>	teams are numbered from 1
<code>Rigel.score(t)</code> , <code>Rigel.roundsWon(t)</code> , <code>Rigel.players()</code> , <code>Rigel.winner()</code>	
<code>Rigel.setting("round_time")</code> , <code>Rigel.settingNumber(k)</code>	the rules, and your Custom settings

Do	
<code>Rigel.startRound()</code> , <code>Rigel.startNow()</code>	with / without the countdown
<code>Rigel.endRound(winner?)</code>	a team number, or nothing to decide by score
<code>Rigel.resetGame()</code>	scores and rounds back to zero
<code>Rigel.addScore(team, n?)</code> , <code>Rigel.setScore(team, n)</code>	points count only during a round
<code>Rigel.goal(team, n?, key?)</code>	a goal: counted once per <code>key</code> per 2.5 s, then balls reset (rule <i>Ball back to its spawner</i>)
<code>Rigel.setCustom(key, value)</code> , <code>Rigel.setText(name, value)</code> , <code>Rigel.resetBalls()</code>	

Scripts run on every machine; the Rigel actions only take effect on the server, so it's safe that every machine calls them. `Rigel.onStateChanged(f)`, `onTeamChanged(f)`, `onScoreChanged(f)`, `onTimeChanged(f)` are the callbacks behind the hooks -- use them from any other script in the mode too.

9 The examples

Each example comes as a **level** (Levels tab, *Local projects*) with the arena built -- team changers, buttons, traps, scoreboards, signs -- and as code (**Start from example...**):



Levels tab: **1** the example levels are under *Local projects*. Click **Load here** to open one on the server you're on.

Level	What it shows
FirstToTen	a score race with a live "who leads" sign, start + score buttons, a scoreboard monitor and a Score board
AutoStartLobby	a lobby that counts players in and starts by itself, a force field that opens for the round, a timer
SuddenDeath	a timed round; a draw goes into a 30-second sudden death; a Score table
TrapGauntlet	traps fired by a trap button, a pulsing laser, a spinner on during rounds, all fired for the last 20 s
BallBattle	a Jake ball match: first to 5, the ball resets after every point
ScoreboardRace	every kind of scoreboard and a catch-up rule for the last 15 seconds

10 Troubleshooting

- **"Team changers only work inside a game mode"**: place them inside the orange box.
- **The round ends by itself**: *End a round when every team is empty* is on and everyone who was on a team left.
- **A button does nothing**: check its role in *Objects and roles*, then **Apply script**. Score buttons only count during a round.

- **My code doesn't run:** the Problems popup shows script errors; the game log shows `[GM_<mode>.lua]` lines. Use the checker in VS Code (the kit's *Rigel checks*), and never write `BeginPlay` in mode code.
- **The ball doesn't come back:** give the spawner the *Ball spawner* role and call `Rigel.resetBalls()`.
- **The monitor shows no countdown:** set *Countdown (s)* above 0 and put someone on a team (an empty arena shows its empty page). Levels saved before 2026-09-24 need **Apply script** once to pick up the countdown fix.
- **The ball is the wrong size:** its size is 1 / its spawner's scale. Scale the ball itself (not the spawner) to the size you want, or set the spawner back to 1.

11 Building game modes with an AI agent

The editor has an MCP server (`RigelScripts\mcp\rigel_mcp.py`) that lets an AI agent such as Claude or Codex build game modes, place objects and write, check and fix Luau for you. See **Rigel-MCP-Guide.pdf**.