



Natural Language Processing (CS-472)

Spring-2023

Muhammad Naseer Bajwa

Assistant Professor,
Department of Computing, SEecs
Co-Principal Investigator,
Deep Learning Lab, NCAI
NUST, Islamabad
naseer.bajwa@seecs.edu.pk



Overview of this week's lecture



Transformers

- Rationale
- Positional Encoding
- Self Attention
- Encoder-Decoder Architecture



What architectures have we studied so far?



- RNNs are great at handling temporal dependencies but they have some disadvantages.



What architectures have we studied so far?




- RNNs are great at handling temporal dependencies but they have some disadvantages.
 - Slower to train. We need truncated backprop to train them practically.
 - Can't handle very long sequences. Gradient vanishes very steeply.



What architectures have we studied so far?




- RNNs are great at handling temporal dependencies but they have some disadvantages.
 - Slower to train. We need truncated backprop to train them practically.
 - Can't handle very long sequences. Gradient vanishes very steeply.
- LSTMs can handle longer sequences better.



What architectures have we studied so far?




- RNNs are great at handling temporal dependencies but they have some disadvantages.
 - Slower to train. We need truncated backprop to train them practically.
 - Can't handle very long sequences. Gradient vanishes very steeply.
- LSTMs can handle longer sequences better.
 - Past information can pass through the cell unhindered via a special branch.
 - But they are even slower and more complex.



What architectures have we studied so far?




- RNNs are great at handling temporal dependencies but they have some disadvantages.
 - Slower to train. We need truncated backprop to train them practically.
 - Can't handle very long sequences. Gradient vanishes very steeply.
- LSTMs can handle longer sequences better.
 - Past information can pass through the cell unhindered via a special branch.
 - But they are even slower and more complex.
- GRUs are faster and can handle longer sequences.
 - Still not enough.



What architectures have we studied so far?



- RNNs are great at handling temporal dependencies but they have some disadvantages.
 - Slower to train. We need truncated backprop to train them practically.
 - Can't handle very long sequences. Gradient vanishes very steeply.
- LSTMs can handle longer sequences better.
 - Past information can pass through the cell unhindered via a special branch.
 - But they are even slower and more complex.
- GRUs are faster and can handle longer sequences.
 - Still not enough. **Need parallelisation.**



How can we achieve parallelisation for sequential data?



How can we achieve parallelisation for sequential data?



How can we achieve parallelisation for sequential data?




Figure 1: The Transformer - model architecture.

Transformers use encoder-decoder architecture without RNNs




Figure 1: The Transformer - model architecture.

Transformers use encoder-decoder architecture without RNNs



- The Encoder

- Accepts input as text.
- Gives output as word embeddings.
- Uses Self-Attention.
- Is bidirectional.




Figure 1: The Transformer - model architecture.

Transformers use encoder-decoder architecture without RNNs



- The Encoder

- Accepts input as text.
- Gives output as word embeddings.
- Uses Self-Attention.
- Is bidirectional.

- The Decoder

- Accepts input as word.
- Gives output as sequence of words.
- Uses Masked Self-Attention.
- Is unidirectional.





Figure 1: The Transformer - model architecture.

Transformers use positional encoders to get position-aware embeddings




- **Positional Encoder** uses a vector that gives context based on position of words in a sentence.



Transformers use positional encoders to get position-aware embeddings



- **Positional Encoder** uses a vector that gives context based on position of words in a sentence.
- The vector has the same length as the embeddings to allow summation.



Transformers use positional encoders to get position-aware embeddings




- **Positional Encoder** uses a vector that gives context based on position of words in a sentence.
- The vector has the same length as the embeddings to allow summation.
- Positional encodings can be fixed or learned. In the original transformer paper, they used *sine* and *cosine* functions of different frequencies.

$$PE_{(pos,2i)} = \sin\left(\frac{pos}{10000^{\left(\frac{2i}{d_{model}}\right)}}\right)$$

$$PE_{(pos,2i+1)} = \cos\left(\frac{pos}{10000^{\left(\frac{2i}{d_{model}}\right)}}\right)$$


- Here *pos* is position, *i* represents dimension and d_{model} corresponds to the total length of input.



How Positional Encodings are calculated?



The	p0	Large	p1	Red	p2	Dog	p3
0.2	?	-0.9	?	0.5	?	0.6	?
-0.8	?	0.3	?	0.6	?	0.0	?
-0.6	?	0.4	?	-0.8	?	0.8	?
0.9	?	0.6	?	0.7	?	0.9	?
0.1	?	-0.1	?	0.7	?	0.4	?



https://kazemnejad.com/blog/transformer_architecture_positional_encoding/
<https://www.youtube.com/watch?v=dichIcUZfOw>

How Positional Encodings are calculated?



The	p0	Large	p1	Red	p2	Dog	p3
0.2	?	-0.9	?	0.5	?	0.6	?
-0.8	?	0.3	?	0.6	?	0.0	?
-0.6	?	0.4	?	-0.8	?	0.8	?
0.9	?	0.6	?	0.7	?	0.9	?
0.1	?	-0.1	?	0.7	?	0.4	?

The-p

0.2+?
-0.8+?
-0.6+?
0.9+?
0.1+?

Large-p


-0.9+?
0.3+?
0.4+?
0.6+?
-0.1+?

Red-p

0.5+?
0.6+?
-0.8+?
0.7+?
0.7+?

Dog-p

0.6+?
0.0+?
0.8+?
0.9+?
0.4+?



https://kazemnejad.com/blog/transformer_architecture_positional_encoding/
<https://www.youtube.com/watch?v=dichIcUZfOw>

How Positional Encodings are calculated?



The	p0	Large	p1	Red	p2	Dog	p3
0.2	?	-0.9	?	0.5	?	0.6	?
-0.8	?	0.3	?	0.6	?	0.0	?
-0.6	?	0.4	?	-0.8	?	0.8	?
0.9	?	0.6	?	0.7	?	0.9	?
0.1	?	-0.1	?	0.7	?	0.4	?

$$PE_{(pos,2i)} = \sin\left(\frac{pos}{10000^{\left(\frac{2i}{d_{model}}\right)}}\right)$$


$$PE_{(pos,2i+1)} = \cos\left(\frac{pos}{10000^{\left(\frac{2i}{d_{model}}\right)}}\right)$$

p0

$PE_{(0,0)}$
$PE_{(0,1)}$
$PE_{(0,2)}$
$PE_{(0,3)}$
$PE_{(0,4)}$

$\sin\left(\frac{0}{10000^{\left(\frac{2 \times 0}{5}\right)}}\right)$
$\cos\left(\frac{0}{10000^{\left(\frac{2 \times 0}{5}\right)}}\right)$
$\sin\left(\frac{0}{10000^{\left(\frac{2 \times 1}{5}\right)}}\right)$
$\cos\left(\frac{0}{10000^{\left(\frac{2 \times 1}{5}\right)}}\right)$
$\cos\left(\frac{0}{10000^{\left(\frac{2 \times 1}{5}\right)}}\right)$
$\cos\left(\frac{0}{10000^{\left(\frac{2 \times 1}{5}\right)}}\right)$

0
1
0
1
0



<https://www.youtube.com/watch?v=dichIcUZfOw>

How Positional Encodings are calculated?



The	p0	Large	p1	Red	p2	Dog	p3
0.2	?	-0.9	?	0.5	?	0.6	?
-0.8	?	0.3	?	0.6	?	0.0	?
-0.6	?	0.4	?	-0.8	?	0.8	?
0.9	?	0.6	?	0.7	?	0.9	?
0.1	?	-0.1	?	0.7	?	0.4	?

$$PE_{(pos,2i)} = \sin\left(\frac{pos}{10000^{\left(\frac{2i}{d_{model}}\right)}}\right)$$


$$PE_{(pos,2i+1)} = \cos\left(\frac{pos}{10000^{\left(\frac{2i}{d_{model}}\right)}}\right)$$

p1

$PE_{(1,0)}$
$PE_{(1,1)}$
$PE_{(1,2)}$
$PE_{(1,3)}$
$PE_{(1,4)}$


$$\begin{matrix} \sin\left(\frac{1}{10000^{\left(\frac{2 \times 0}{5}\right)}}\right) \\ \cos\left(\frac{1}{10000^{\left(\frac{2 \times 0}{5}\right)}}\right) \\ \sin\left(\frac{1}{10000^{\left(\frac{2 \times 1}{5}\right)}}\right) \\ \cos\left(\frac{1}{10000^{\left(\frac{2 \times 1}{5}\right)}}\right) \\ \sin\left(\frac{1}{10000^{\left(\frac{2 \times 2}{5}\right)}}\right) \end{matrix}$$

0.174000
0.999800
0.000174
0.999900
0.000631



<https://www.youtube.com/watch?v=dichIcUZfOw>



How Self Attention is calculated?



<https://www.youtube.com/watch?v=mMa2PmYJlCo>

How Self Attention is calculated?



- A Linear layer is a fully connected layer without activation function.
 - Used to map input to the output.
 - Change dimensionality.



How Self Attention is calculated?




- A Linear layer is a fully connected layer without activation function.
 - Used to map input to the output.
 - Change dimensionality.
- Query, Key, Value Formulation is used to calculate Attention.




How Self Attention is calculated?



- A Linear layer is a fully connected layer without activation function.
 - Used to map input to the output.
 - Change dimensionality.
- Query, Key, Value Formulation is used to calculate Attention.
- Similarity between Query and Key can be considered as proxy to attention.
 - The similarity can be found using Cosine Similarity. (-1 to +1)





$$\cos(\mathbf{a}, \mathbf{b}) = \frac{\mathbf{a} \cdot \mathbf{b}}{|\mathbf{a}| |\mathbf{b}|}$$



How Self Attention is calculated?





- A Linear layer is a fully connected layer without activation function.
 - Used to map input to the output.
 - Change dimensionality.
- Query, Key, Value Formulation is used to calculate Attention.
- Similarity between Query and Key can be considered as proxy to attention.
 - The similarity can be found using Cosine Similarity. (-1 to +1)
- What do Query, Key and Values consist of?



How Self Attention is calculated?



- A Linear layer is a fully connected layer without activation function.
 - Used to map input to the output.
 - Change dimensionality.
- Query, Key, Value Formulation is used to calculate Attention.
- Similarity between Query and Key can be considered as proxy to attention.
 - The similarity can be found using Cosine Similarity. (-1 to +1)
- What do Query, Key and Values consist of?
 - Position-aware embeddings processed by relevant linear layers.



<https://www.youtube.com/watch?v=mMa2PmYJlCo>

Values of Query, Key and Value matrices are learnt




4x5 positional embeddings $W \in \mathbb{R}^{5 \times 3}$

The	0.2	-0.8	-0.6	0.9	0.1
Large	-0.9	0.3	0.4	0.6	-0.1
Red	0.5	0.6	-0.8	0.7	0.7
Dog	0.6	0.0	0.8	0.9	0.4

4x3 Query

0.7	0.5	0.2
-0.3	0.6	-0.1
0.1	0.2	-0.9
0.4	0.8	0.1



Values of Query, Kay and Value matrices are learnt




4x5 positional embeddings $W \in \mathbb{R}^{5 \times 3}$ 4x3 Query

The	0.2	-0.8	-0.6	0.9	0.1		0.7	0.5	0.2
Large	-0.9	0.3	0.4	0.6	-0.1		-0.3	0.6	-0.1
Red	0.5	0.6	-0.8	0.7	0.7		0.1	0.2	-0.9
Dog	0.6	0.0	0.8	0.9	0.4		0.4	0.8	0.1

4x5 positional embeddings $W \in \mathbb{R}^{5 \times 3}$ 4x3 Key

The	0.2	-0.8	-0.6	0.9	0.1		0.7	0.5	0.2
Large	-0.9	0.3	0.4	0.6	-0.1		-0.3	0.6	-0.1
Red	0.5	0.6	-0.8	0.7	0.7		0.1	0.2	-0.9
Dog	0.6	0.0	0.8	0.9	0.4		0.4	0.8	0.1



Values of Query, Kay and Value matrices are learnt



4x5 positional embeddings $W \in \mathbb{R}^{5 \times 3}$ 4x3 Query


The	0.2	-0.8	-0.6	0.9	0.1		0.7	0.5	0.2
Large	-0.9	0.3	0.4	0.6	-0.1		-0.3	0.6	-0.1
Red	0.5	0.6	-0.8	0.7	0.7		0.1	0.2	-0.9
Dog	0.6	0.0	0.8	0.9	0.4		0.4	0.8	0.1

4x5 positional embeddings $W \in \mathbb{R}^{5 \times 3}$ 4x3 Key

The	0.2	-0.8	-0.6	0.9	0.1		0.7	0.5	0.2
Large	-0.9	0.3	0.4	0.6	-0.1		-0.3	0.6	-0.1
Red	0.5	0.6	-0.8	0.7	0.7		0.1	0.2	-0.9
Dog	0.6	0.0	0.8	0.9	0.4		0.4	0.8	0.1

4x5 positional embeddings $W \in \mathbb{R}^{5 \times 3}$ 4x3 Value

The	0.2	-0.8	-0.6	0.9	0.1		0.7	0.5	0.2
Large	-0.9	0.3	0.4	0.6	-0.1		-0.3	0.6	-0.1
Red	0.5	0.6	-0.8	0.7	0.7		0.1	0.2	-0.9
Dog	0.6	0.0	0.8	0.9	0.4		0.4	0.8	0.1




Self Attention takes query and key from the same sequence



- Dot product of Query and Key gives attention scores.

$$\begin{array}{|c|c|c|} \hline 4 \times 3 \text{ Query} \\ \hline 0.7 & 0.5 & 0.2 \\ -0.3 & 0.6 & -0.1 \\ 0.1 & 0.2 & -0.9 \\ 0.4 & 0.8 & 0.1 \\ \hline \end{array} \times \begin{array}{|c|c|c|c|} \hline 3 \times 4 \text{ Key}^T \\ \hline -0.1 & 0.8 & 0.3 & -0.3 \\ 0.2 & -0.4 & 0.5 & 0.9 \\ 0.1 & -0.8 & -0.7 & -0.6 \\ \hline \end{array} = \begin{array}{|c|c|c|c|} \hline 4 \times 4 \text{ Attention Filter} \\ \hline 0.5 & 0.2 & 0.3 & 0.1 \\ 0.1 & -0.4 & 0.3 & 0.7 \\ -0.1 & 0.7 & 0.8 & 0.7 \\ 0.1 & -0.1 & 0.4 & 0.5 \\ \hline \end{array}$$



Self Attention takes query and key from the same sequence




- Dot product of Query and Key gives attention scores.

$$\begin{array}{|c|c|c|} \hline 4 \times 3 \text{ Query} \\ \hline 0.7 & 0.5 & 0.2 \\ -0.3 & 0.6 & -0.1 \\ 0.1 & 0.2 & -0.9 \\ 0.4 & 0.8 & 0.1 \\ \hline \end{array} \times \begin{array}{|c|c|c|c|} \hline 3 \times 4 \text{ Key}^T \\ \hline -0.1 & 0.8 & 0.3 & -0.3 \\ 0.2 & -0.4 & 0.5 & 0.9 \\ 0.1 & -0.8 & -0.7 & -0.6 \\ \hline \end{array} = \begin{array}{|c|c|c|c|} \hline 4 \times 4 \text{ Attention Filter} \\ \hline 0.5 & 0.2 & 0.3 & 0.1 \\ 0.1 & -0.4 & 0.3 & 0.7 \\ -0.1 & 0.7 & 0.8 & 0.7 \\ 0.1 & -0.1 & 0.4 & 0.5 \\ \hline \end{array}$$

- Scale the attention scores by $\frac{1}{\sqrt{5}}$ and apply *softmax*.

$$\begin{array}{|c|c|c|c|} \hline 4 \times 4 \text{ Attention Filter} \\ \hline 0.5 & 0.2 & 0.3 & 0.1 \\ 0.1 & -0.4 & 0.3 & 0.7 \\ -0.1 & 0.7 & 0.8 & 0.7 \\ 0.1 & -0.1 & 0.4 & 0.5 \\ \hline \end{array} \times \begin{array}{|c|c|c|} \hline 4 \times 3 \text{ Value} \\ \hline -0.1 & 0.4 & 0.5 \\ 0.6 & 0.7 & 0.8 \\ -0.2 & 0.3 & 0.9 \\ 0.3 & 0.9 & -0.1 \\ \hline \end{array} = \begin{array}{|c|c|c|} \hline 4 \times 3 \text{ Filtered Value} \\ \hline -0.1 & 0.4 & 0.5 \\ 0.6 & 0.7 & 0.8 \\ -0.2 & 0.3 & 0.9 \\ 0.3 & 0.9 & -0.1 \\ \hline \end{array}$$



Self Attention takes query and key from the same sequence




- Dot product of Query and Key gives attention scores.

$$\begin{array}{c} 4 \times 3 \text{ Query} \\ \begin{bmatrix} 0.7 & 0.5 & 0.2 \\ -0.3 & 0.6 & -0.1 \\ 0.1 & 0.2 & -0.9 \\ 0.4 & 0.8 & 0.1 \end{bmatrix} \end{array} \times \begin{array}{c} 3 \times 4 \text{ Key}^T \\ \begin{bmatrix} -0.1 & 0.8 & 0.3 & -0.3 \\ 0.2 & -0.4 & 0.5 & 0.9 \\ 0.1 & -0.8 & -0.7 & -0.6 \end{bmatrix} \end{array} = \begin{array}{c} 4 \times 4 \text{ Attention Filter} \\ \begin{bmatrix} 0.5 & 0.2 & 0.3 & 0.1 \\ 0.1 & -0.4 & 0.3 & 0.7 \\ -0.1 & 0.7 & 0.8 & 0.7 \\ 0.1 & -0.1 & 0.4 & 0.5 \end{bmatrix} \end{array}$$

- Scale the attention scores by $\frac{1}{\sqrt{5}}$ and apply *softmax*.

$$\begin{array}{c} 4 \times 4 \text{ Attention Filter} \\ \begin{bmatrix} 0.5 & 0.2 & 0.3 & 0.1 \\ 0.1 & -0.4 & 0.3 & 0.7 \\ -0.1 & 0.7 & 0.8 & 0.7 \\ 0.1 & -0.1 & 0.4 & 0.5 \end{bmatrix} \end{array} \times \begin{array}{c} 4 \times 3 \text{ Value} \\ \begin{bmatrix} -0.1 & 0.4 & 0.5 \\ 0.6 & 0.7 & 0.8 \\ -0.2 & 0.3 & 0.9 \\ 0.3 & 0.9 & -0.1 \end{bmatrix} \end{array} = \begin{array}{c} 4 \times 3 \text{ Filtered Value} \\ \begin{bmatrix} -0.1 & 0.4 & 0.5 \\ 0.6 & 0.7 & 0.8 \\ -0.2 & 0.3 & 0.9 \\ 0.3 & 0.9 & -0.1 \end{bmatrix} \end{array}$$


$$\text{Attention}(Q, K, V) = \text{softmax} \left(\frac{Q \cdot K^T}{\sqrt{d_k}} \right) \cdot V$$



Transformers encoder uses a Multi-Headed Attention block



- Multiple attention filters are learnt each focusing on a particular linguistic aspect.



Transformers encoder uses a Multi-Headed Attention block




- Multiple attention filters are learnt each focusing on a particular linguistic aspect.
- Value matrices filtered by these multiple filters are then concatenated and passed through another linear layer.

$$MultiHead(Q, K, V) = Concat(head_1, head_2, \dots, head_h)W^o$$

The original Transformer paper uses $h = 8$ attention heads and

$$d_k = d_v = \frac{d_{model}}{8} = 64$$



Transformers encoder uses a Multi-Headed Attention block



- Multiple attention filters are learnt each focusing on a particular linguistic aspect.
- Value matrices filtered by these multiple filters are then concatenated and passed through another linear layer.

$$MultiHead(Q, K, V) = Concat(head_1, head_2, \dots, head_h)W^o$$


The original Transformer paper uses $h = 8$ attention heads and

$$d_k = d_v = \frac{d_{model}}{8} = 64$$

-0.1	0.4	0.5
0.6	0.7	0.8
-0.2	0.3	0.9
0.3	0.9	-0.1
-0.1	0.4	0.5
0.6	0.7	0.8
-0.2	0.3	0.9
0.3	0.9	-0.1
-0.1	0.4	0.5
0.6	0.7	0.8
-0.2	0.3	0.9
0.3	0.9	-0.1



0.2	-0.6	0.9	0.1
-0.9	0.3	0.4	-0.1
0.5	0.6	-0.8	0.7
0.6	0.8	0.9	0.4
-0.8	0.6	0.1	-0.4



Add position-aware embedding to attention output and normalise



- Add Position-aware Embeddings and the output of Multi-head Attention Layer.


Skip Connection

0.1	-0.1	-0.3	0.8
0.8	-0.2	0.7	-0.9
-0.5	0.5	-0.6	0.3
0.7	-0.3	0.5	0.2
0.0	-0.3	0.4	0.1

+

MultiHead Attention Output

0.2	-0.6	0.9	0.1
-0.9	0.3	0.4	-0.1
0.5	0.6	-0.8	0.7
0.6	0.8	0.9	0.4
-0.8	0.6	0.1	-0.4




Add position-aware embedding to attention output and normalise



- Add Position-aware Embeddings and the output of Multi-head Attention Layer.

Skip Connection				MultiHead Attention Output			
0.1	-0.1	-0.3	0.8	0.2	-0.6	0.9	0.1
0.8	-0.2	0.7	-0.9	-0.9	0.3	0.4	-0.1
-0.5	0.5	-0.6	0.3	0.5	0.6	-0.8	0.7
0.7	-0.3	0.5	0.2	0.6	0.8	0.9	0.4
0.0	-0.3	0.4	0.1	-0.8	0.6	0.1	-0.4

- Perform z-score standardisation across features.




Add position-aware embedding to attention output and normalise



- Add Position-aware Embeddings and the output of Multi-head Attention Layer.


Skip Connection				MultiHead Attention Output			
0.1	-0.1	-0.3	0.8	0.2	-0.6	0.9	0.1
0.8	-0.2	0.7	-0.9	-0.9	0.3	0.4	-0.1
-0.5	0.5	-0.6	0.3	0.5	0.6	-0.8	0.7
0.7	-0.3	0.5	0.2	0.6	0.8	0.9	0.4
0.0	-0.3	0.4	0.1	-0.8	0.6	0.1	-0.4

- Perform z-score standardisation across features.
- Pass through feedforward network and that's it.



Decoder uses masked self attention


- The output of encoder is given to the decoder as Q and K matrices.



<https://www.youtube.com/watch?v=gJ9kaJsE78k>

Decoder uses masked self attention

- The output of encoder is given to the decoder as Q and K matrices.
- The V Matrix is generated by the decoder.



<https://www.youtube.com/watch?v=gJ9kaJsE78k>

Decoder uses masked self attention



- The output of encoder is given to the decoder as Q and K matrices.
- The V Matrix is generated by the decoder.

Attention Filter


0.5	0.2	0.3	0.1
0.1	-0.4	0.3	0.7
-0.1	0.7	0.8	0.7
0.1	-0.1	0.4	0.5

Masked Attention Filter

0.5	-inf	-inf	-inf
0.1	-0.4	-inf	-inf
-0.1	0.7	0.8	-inf
0.1	-0.1	0.4	0.5

*Softmax of
Masked Attention Filter*

0.5	0	0	0
0.1	-0.4	0	0
-0.1	0.7	0.8	0
0.1	-0.1	0.4	0.5




<https://www.youtube.com/watch?v=gJ9kaJsE78k>

Encoder converts words into embeddings




- Dimension of word embeddings is defined by the model.
 - Base BERT used 768 dimensional embeddings.



Encoder converts words into embeddings




- Dimension of word embeddings is defined by the model.
 - Base BERT used 768 dimensional embeddings.
- Transformer Encoder allows to process the whole input sequence in parallel.



Encoder converts words into embeddings




- Dimension of word embeddings is defined by the model.
 - Base BERT used 768 dimensional embeddings.
- Transformer Encoder allows to process the whole input sequence in parallel.
- Transformer's Encoder module learns positional embeddings.
 - Meaning of a word considering its position in the text.



Encoder converts words into embeddings



- Dimension of word embeddings is defined by the model.
 - Base BERT used 768 dimensional embeddings.
- Transformer Encoder allows to process the whole input sequence in parallel.
- Transformer's Encoder module learns positional embeddings.
 - Meaning of a word considering its position in the text.
- Uses Self-Attention mechanism, which consults other words in the sequence to learn the meaning of a given word.



Applications of Encoders



- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.



Applications of Encoders



- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.
- May also be used for sequence classification, question answering, masked language modelling etc.



Applications of Encoders




- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.
- May also be used for sequence classification, question answering, masked language modelling etc.
 - Masked Language Modelling. Makes use of bi-directional context.

You Know Nothing Snow

Applications of Encoders




- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.
- May also be used for sequence classification, question answering, masked language modelling etc.
 - Masked Language Modelling. Makes use of bi-directional context.



Applications of Encoders



- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.
- May also be used for sequence classification, question answering, masked language modelling etc.
 - Masked Language Modelling. Makes use of bi-directional context.



Applications of Encoders



- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.
- May also be used for sequence classification, question answering, masked language modelling etc.
 - Masked Language Modelling. Makes use of bi-directional context.
 - Sentiment Analysis

Even though she did **not** win the award, she was satisfied

Positive

Even though she did win the award, she was **not** satisfied

Negative



Applications of Encoders



- Encoders can be used as stand alone models.
 - Very good at learning meaningful representations.
- May also be used for sequence classification, question answering, masked language modelling etc.
 - Masked Language Modelling. Makes use of bi-directional context.
 - Sentiment Analysis

Even though she did **not** win the award, she was satisfied

Positive

Even though she did win the award, she was **not** satisfied

Negative


- Common examples are BERT (SOTA of its time) and its variants RoERTa and ALBERT.



Decoders are very similar in architecture to encoders




- Can be used to perform the same tasks as encoders (with reduced performance)



Decoders are very similar in architecture to encoders




- Can be used to perform the same tasks as encoders (with reduced performance)
- Transformer's Decoder module also learns positional embeddings.



Decoders are very similar in architecture to encoders



- Can be used to perform the same tasks as encoders (with reduced performance)
- Transformer's Decoder module also learns positional embeddings.
- Uses **Masked Self-Attention** mechanism, which **consults only the previous or the following words** in the sequence to learn the meaning of a given word.



Applications of Decoders



- Can be used as stand alone models



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.
 - Input an initial word, <You>.



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.
 - Input an initial word, <You>.
 - Decoder determines contextual embedding based on unidirectional context (so far).



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.
 - Input an initial word, <You>.
 - Decoder determines contextual embedding based on unidirectional context (so far).
 - A transformation maps the embedding to all known words.



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.
 - Input an initial word, <You>.
 - Decoder determines contextual embedding based on unidirectional context (so far).
 - A transformation maps the embedding to all known words.
 - The most probable next word is given as output.



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.
 - Input an initial word, <You>.
 - Decoder determines contextual embedding based on unidirectional context (so far).
 - A transformation maps the embedding to all known words.
 - The most probable next word is given as output.
 - Current output is used as next input.



Applications of Decoders




- Can be used as stand alone models
- Great at Natural Language Generation due to unidirectional context.
 - Input an initial word, <You>.
 - Decoder determines contextual embedding based on unidirectional context (so far).
 - A transformation maps the embedding to all known words.
 - The most probable next word is given as output.
 - Current output is used as next input.
- Examples include GPT and GPT-2.
- GPT-2 has a context of size 1024.



Encoder-Decoder architecture addresses *seq2seq* tasks




- Useful for translation and summarisation.



Encoder-Decoder architecture addresses *seq2seq* tasks




- Useful for translation and summarisation.



Encoder-Decoder architecture addresses *seq2seq* tasks



- Useful for translation and summarisation.
- Encoder and Decoder models do not necessarily share weights.




https://www.youtube.com/watch?v=0_4KEb08xrE

Encoder-Decoder architecture addresses *seq2seq* tasks




- Useful for translation and summarisation.
- Encoder and Decoder models do not necessarily share weights.
- Input distribution differs from output distribution.



Encoder-Decoder architecture addresses *seq2seq* tasks



- Useful for translation and summarisation.
- Encoder and Decoder models do not necessarily share weights.
- Input distribution differs from output distribution.
- Popular Enc-Dec models are T5, BART, M2M100, and Pegasus etc.




https://www.youtube.com/watch?v=0_4KEb08xrE

Encoder-Decoder architecture addresses *seq2seq* tasks



- Useful for translation and summarisation.
- Encoder and Decoder models do not necessarily share weights.
- Input distribution differs from output distribution.
- Popular Enc-Dec models are T5, BART, M2M100, and Pegasus etc.
- Can mix-and-match different stand-alone encoders and decoders.



https://www.youtube.com/watch?v=0_4KEb08xrE

Do you have any problem?



Some material (images, tables, text etc.) in this presentation has been borrowed from different books, lecture notes, and the web. The original contents solely belong to their owners, and are used in this presentation only for clarifying various educational concepts. Any copyright infringement is ***not at all*** intended.

