



GSA 130 - Motorized Guillotine Vertical Sliding System

SERIES: LOGAN SERIES | SYSTEM CODE: GSA130 | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX

MANUFACTURING STANDARD

Base Aluminum Alloy	EN AW-6063 T6 (Extrusion to EN 12020-2)
Frame Architectural Depth	130 mm Vertical Guide Jamb Channel
Sash / Vent Profile Depth	3-Panel Cascading Motorized Telescopic Sashes
Glazing Thickness Capacity	8 mm - 10 mm Tempered / 20 mm IGU Double Glass
Thermal Barrier Insulation	High-Density Brush & Acoustic Felt Seals
Air Permeability (EN 12207)	Automated Retractable Weather Gaskets
Water Tightness (EN 12208)	Class 7A (EN 12208 / 300 Pa)
Wind Load Resistance (EN 12210)	Class C3 (EN 12210 / 1200 Pa)
Acoustic Sound Reduction	Rw = 32 - 37 dB
Maximum Sash Weight Capacity	220 kg Automated Belt Drive Motor System

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

ENGINEERING DESK: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly