



CWA 50 SG - Full Structural Glazing Curtain Wall System

SERIES: BROMO SERIES | SYSTEM CODE: CWA50SG | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



| MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX |                                              | MANUFACTURING STANDARD |
|-------------------------------------------------|----------------------------------------------|------------------------|
| Base Aluminum Alloy                             | EN AW-6063 T6 (Extrusion to EN 12020-2)      |                        |
| Frame Architectural Depth                       | 80 mm - 220 mm Structural Mullion Depths     |                        |
| Sash / Vent Profile Depth                       | 50 mm Exterior Sightline (Flush Glass)       |                        |
| Glazing Thickness Capacity                      | 24 mm - 44 mm Structural Silicone Bonded IGU |                        |
| Thermal Barrier Insulation                      | Continuous EPDM Multi-Fin Thermal Isolators  |                        |
| Air Permeability (EN 12207)                     | Class AE 1200 (EN 12152 / 1200 Pa)           |                        |
| Water Tightness (EN 12208)                      | Class RE 1500 (EN 12154 / 1500 Pa)           |                        |
| Wind Load Resistance (EN 12210)                 | Design 2000 Pa / Safety 3000 Pa (EN 13116)   |                        |
| Acoustic Sound Reduction                        | Rw = 42 - 48 dB                              |                        |
| Maximum Sash Weight Capacity                    | 350 kg per Glazing Module                    |                        |

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

ENGINEERING DESK: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly