



IPA 45 - Acoustic Double-Glass Office Partition System

SERIES: IDA SERIES | SYSTEM CODE: IPA45 | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX		MANUFACTURING STANDARD
Base Aluminum Alloy	EN AW-6063 T6 (Extrusion to EN 12020-2)	
Frame Architectural Depth	45 mm Perimeter Profiles / 100 mm Total Wall	
Sash / Vent Profile Depth	Flush Internal Glazing with Integrated Blinds	
Glazing Thickness Capacity	6 mm - 12 mm Double Acoustic Laminated Glass	
Thermal Barrier Insulation	Acoustic Cavity Isolation (Rw = 42 - 46 dB)	
Air Permeability (EN 12207)	Interior Commercial Specification	
Water Tightness (EN 12208)	Interior Commercial Specification	
Wind Load Resistance (EN 12210)	Interior Impact Safety Standard (BS 5234)	
Acoustic Sound Reduction	Rw = 42 - 46 dB Certified	
Maximum Sash Weight Capacity	80 kg Hinged Architectural Glass Door	

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

ENGINEERING DESK: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly