



WA 45 - Economic Casement & Fixed Window System

SERIES: HEKLA SERIES | SYSTEM CODE: WA45 | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX

MANUFACTURING STANDARD

|                                 |                                         |
|---------------------------------|-----------------------------------------|
| Base Aluminum Alloy             | EN AW-6063 T6 (Extrusion to EN 12020-2) |
| Frame Architectural Depth       | 45 mm Compact Profile Depth             |
| Sash / Vent Profile Depth       | 52 mm Casement Sash                     |
| Glazing Thickness Capacity      | 4 mm Monolithic - 24 mm Double Glazing  |
| Thermal Barrier Insulation      | Single Hollow Chamber Non-Thermal       |
| Air Permeability (EN 12207)     | Class 2 (EN 12207 / 300 Pa)             |
| Water Tightness (EN 12208)      | Class 6A (EN 12208 / 250 Pa)            |
| Wind Load Resistance (EN 12210) | Class C2 (EN 12210 / 800 Pa)            |
| Acoustic Sound Reduction        | Rw = 30 - 34 dB                         |
| Maximum Sash Weight Capacity    | 90 kg (Window) / 120 kg (Door)          |

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

ENGINEERING DESK: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly