



WA 55 - Standard Casement Door & Window System

SERIES: HEKLA SERIES | SYSTEM CODE: WA55 | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX

MANUFACTURING STANDARD

|                                 |                                           |
|---------------------------------|-------------------------------------------|
| Base Aluminum Alloy             | EN AW-6063 T6 (Extrusion to EN 12020-2)   |
| Frame Architectural Depth       | 55 mm Architectural Frame                 |
| Sash / Vent Profile Depth       | 63 mm Overlap Sash with Drip Deflector    |
| Glazing Thickness Capacity      | 6 mm Monolithic - 32 mm Double IGU        |
| Thermal Barrier Insulation      | Standard Hollow Non-Thermal Multi-Chamber |
| Air Permeability (EN 12207)     | Class 3 (EN 12207 / 450 Pa)               |
| Water Tightness (EN 12208)      | Class 8A (EN 12208 / 450 Pa)              |
| Wind Load Resistance (EN 12210) | Class C3 (EN 12210 / 1200 Pa)             |
| Acoustic Sound Reduction        | Rw = 32 - 37 dB                           |
| Maximum Sash Weight Capacity    | 130 kg (Window) / 160 kg (Entrance Door)  |

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

ENGINEERING DESK: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly