




CWA 50 SG - Full Structural Glazing Curtain Wall System

SERIES: BROMO SERIES | SYSTEM CODE: CWA50SG | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX

MANUFACTURING STANDARD

Base Aluminum Alloy	EN AW-6063 T6 (Extrusion to EN 12020-2)
Frame Architectural Depth	80 mm - 220 mm Structural Mullion Depths
Sash / Vent Profile Depth	50 mm Exterior Sightline (Flush Glass)
Glazing Thickness Capacity	24 mm - 44 mm Structural Silicone Bonded IGU
Thermal Barrier Insulation	Continuous EPDM Multi-Fin Thermal Isolators
Air Permeability (EN 12207)	Class AE 1200 (EN 12152 / 1200 Pa)
Water Tightness (EN 12208)	Class RE 1500 (EN 12154 / 1500 Pa)
Wind Load Resistance (EN 12210)	Design 2000 Pa / Safety 3000 Pa (EN 13116)
Acoustic Sound Reduction	Rw = 42 - 48 dB
Maximum Sash Weight Capacity	350 kg per Glazing Module

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

DIRECT CONTACT: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly