



## GSA 130 - Motorized Guillotine Vertical Sliding System

SERIES: LOGAN SERIES | SYSTEM CODE: GSA130 | EXTRUSION: EN AW-6063 T6

## ENGINEERING 2D CAD PROFILE SCHEMATIC



## MECHANICAL &amp; ARCHITECTURAL SPECIFICATION MATRIX

## MANUFACTURING STANDARD

|                                 |                                                |
|---------------------------------|------------------------------------------------|
| Base Aluminum Alloy             | EN AW-6063 T6 (Extrusion to EN 12020-2)        |
| Frame Architectural Depth       | 130 mm Vertical Guide Jamb Channel             |
| Sash / Vent Profile Depth       | 3-Panel Cascading Motorized Telescopic Sashes  |
| Glazing Thickness Capacity      | 8 mm - 10 mm Tempered / 20 mm IGU Double Glass |
| Thermal Barrier Insulation      | High-Density Brush & Acoustic Felt Seals       |
| Air Permeability (EN 12207)     | Automated Retractable Weather Gaskets          |
| Water Tightness (EN 12208)      | Class 7A (EN 12208 / 300 Pa)                   |
| Wind Load Resistance (EN 12210) | Class C3 (EN 12210 / 1200 Pa)                  |
| Acoustic Sound Reduction        | Rw = 32 - 37 dB                                |
| Maximum Sash Weight Capacity    | 220 kg Automated Belt Drive Motor System       |

## FABRICATION STANDARDS &amp; QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

DIRECT CONTACT: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly