



WAT 63 - High-Performance Thermal Break Casement System

SERIES: HEKLA SERIES | SYSTEM CODE: WAT63 | EXTRUSION: EN AW-6063 T6

ENGINEERING 2D CAD PROFILE SCHEMATIC



MECHANICAL & ARCHITECTURAL SPECIFICATION MATRIX

MANUFACTURING STANDARD

Base Aluminum Alloy	EN AW-6063 T6 (Extrusion to EN 12020-2)
Frame Architectural Depth	63 mm Architectural Depth
Sash / Vent Profile Depth	71 mm Inward / Outward Rebate Sash
Glazing Thickness Capacity	20 mm - 42 mm High Acoustic IGU
Thermal Barrier Insulation	24 mm Polyamide PA66 GF25 Thermal Barrier
Air Permeability (EN 12207)	Class 4 (EN 12207 / 600 Pa)
Water Tightness (EN 12208)	Class 9A (EN 12208 / 600 Pa)
Wind Load Resistance (EN 12210)	Class C5 (EN 12210 / 2000 Pa)
Acoustic Sound Reduction	Rw = 38 - 44 dB
Maximum Sash Weight Capacity	180 kg (Tilt & Turn) / 220 kg (Door)

FABRICATION STANDARDS & QUALITY COMPLIANCE

- Extrusion Tolerances: Conforms strictly to EN 12020-2 / DIN 17615 high precision architectural standard.
- Surface Coating: Qualicoat Certified Electrostatic Powder Coating (60-80 microns) / Qualanod Anodizing (15-20 microns).
- Gaskets: EPDM weatherseals according to DIN 7863. Hardware groove: Standard European groove compatibility.
- Quality Management: Extruded and assembled under certified ISO 9001:2015 industrial manufacturing systems.

FACTORY DIRECTIVE: Official technical specifications verified for tender submissions, fabrication, and structural installation.

DIRECT CONTACT: +218 92 429 5050 | +218 91 614 1616 | Tripoli Industrial Complex, Libya | www.ainzara.ly