Measure, Don't Predict: Accuracy-Guarded Latency Optimization of Object Detectors on a Client NPU

Julien Beloin
Independent researcher
https://github.com/Zeta-12/OptiNPU

***Abstract*—Laptops now ship with neural processing units (NPUs) that promise low-power inference, yet modern object detectors run poorly on them. On an Intel Core Ultra NPU, none of seven state-of-the-art real-time detectors runs fastest on the NPU alone, FLOPs do not predict latency, the vendor's per-operation counters overlap, and the compiler can silently cost up to 4.6 AP or hang the device. We present OptiNPU, an open-source tool that profiles, validates and optimizes a model for the NPU using on-device measurements only. It rests on an observation that we verify: latency does not depend on the values of dense weights, so any variant of a model, such as a bypassed region, a rewritten operation, or an architecture not yet retrained, can be timed exactly before it is trained or calibrated. OptiNPU (i) attributes latency by bypassing module regions in paired, randomized rounds, repeated until a 95 % confidence interval is narrow; (ii) guards accuracy at the task level, with detection agreement and a paired non-inferiority test on COCO AP; and (iii) greedily applies exact and approximate rewrites, including a latency-guided mixed-precision search, and reports retraining rewrites with their measured latency. On five models, measured profiling picks the best intervention (regret at most 0.01), while acting on vendor counters or on an additive cost model loses on average 31 % and 32 % of the best saving. The optimizer makes YOLO26-N 2.86× and YOLO26-S 2.04× faster on the NPU, repairing a silent 4.6-AP loss and a device hang, with AP within 0.1 points of CPU FP32. On DETR-family detectors, the gains are at most 1.17×, and one repair costs latency. Mixed precision makes the ResNet-50 and MobileNetV2 classifiers 1.60× and 1.22× faster.**

***Index Terms*—neural processing unit, object detection, latency profiling, quantization, mixed precision, compiler validation**

I. Introduction

Client processors now integrate a neural processing unit (NPU) next to the CPU and the integrated GPU (iGPU): Intel Core Ultra, AMD Ryzen AI, Qualcomm Snapdragon X. Their purpose is to run sustained inference at low power and to leave the CPU and GPU free for the user. Real-time object detection is a natural workload for them, and the detectors of the last two years, mostly descendants of DETR [1] (RT-DETR [2], [3], D-FINE [4], DEIM [5], [6], RF-DETR [7], YOLO26 [8]) reach 40 to 53 COCO AP [9] at a few GFLOPs.

Deploying these detectors on an NPU is nevertheless a trial-and-error exercise. Our measurements on an Intel NPU 3720 (Section II) show that:

- none of seven detectors is fastest on the NPU alone: they run 1.4 to 3.6× slower than on the iGPU or in a hybrid NPU+iGPU placement;
- FLOPs do not predict latency: YOLO26-N (5.4 GFLOPs) takes 26 ms, ResNet-50 at 224 px takes 4 ms;
- the vendor's per-operation counters overlap, so their sum is several times the real latency;
- the compiler fails silently: in its default two-tile mode, YOLO26-N loses 4.6 AP, RT-DETRv2 3.8 AP, and YOLO26-S hangs the device after a few images.

Existing tools predict rather than measure. Latency predictors learn per-kernel costs and add them up [10]–[12]. Hardware-aware search and compression use such predictors or lookup tables [13]–[16]. Mixed-precision methods model the latency of a configuration as the sum of per-layer costs [17]. On this NPU, none of these assumptions holds: costs are not additive, and the compiled graph may be wrong.

We take the opposite approach: *measure, don't predict*. One property of the NPU makes this affordable: **latency does not depend on the values of dense weights**. A variant of a model can therefore be timed exactly with any weights, before it is trained, calibrated or even designed in PyTorch. We build OptiNPU on this property. Our contributions are:

1) a characterization of a client NPU that explains why prediction fails there: non-additive costs, overlapping counters, value-dependent operations, exploited weight sparsity, and silent compiler errors (Sections II and IV-A);
2) a measured profiler, based on region bypassing and paired, randomized, adaptive rounds, which picks better interventions than vendor counters and an additive cost model on 150 interventions over five models (Section V-B);
3) a task-level accuracy guard that combines detection agreement and a paired non-inferiority test on AP, calibrated on real compiler failures (Section IV-C);
4) a three-tier optimizer (exact, approximate, retraining), with a latency-guided mixed-precision search that does not assume additive costs, evaluated on seven detectors and three image classifiers (Sections IV-D, V-C and V-D);
5) an open-source implementation (Apache-2.0) at https://github.com/Zeta-12/OptiNPU, which runs every compilation and inference in a watched child process.

II. Background and Motivation

A. The Intel NPU 3720

The NPU of the Intel Core Ultra 5 235U has two neural compute tiles. Each tile has DPU arrays, which run convolutions and matrix products, SHAVE DSP cores, which run the

TABLE I
DETECTORS ON THE INTEL NPU 3720 (COCO VAL2017, BATCH 1). THE NPU-ONLY COLUMN GIVES THE FASTEST EXACT SETTING (ONE OR TWO TILES).

Model	AP	Fastest placement	NPU only (ms, AP)	Ratio
YOLO26-N	40.3	iGPU 10.9 ms	29.3 (1 tile, 40.2)	2.7×
DEIMv2-N	42.9	iGPU 15.1 ms	23.9 (2 tiles, 42.0)	1.6×
D-FINE-N	42.8	NPU+iGPU 15.5 ms	25.9 (2 tiles, 42.6)	1.7×
YOLO26-S	47.7	iGPU 23.8 ms	41.1 (1 tile, 47.7)	1.7×
RF-DETR-N	48.4	iGPU 23.0 ms	83.4 (2 tiles, 48.4)	3.6×
D-FINE-S	48.5	NPU+iGPU 34.0 ms	47.0 (2 tiles, 48.4)	1.4×
RT-DETRv2-R18	48.1	NPU+iGPU 34.9 ms	80.7 (1 tile, 48.0)	2.3×

other operations, and DMA engines. OpenVINO [18] compiles a whole graph for it, given in its intermediate representation (IR: an XML graph and a binary file of weights), in FP16 or INT8, and the `NPU_TILES` option selects one or two tiles (two by default). On dense 3×3 convolutions we measure 4 to 6 effective TOPS per layer, for a nominal peak of 6.1 (FP16) and 12.3 (INT8). The NPU only runs inference.

B. Today's detectors on this NPU

We exported seven detectors to OpenVINO and evaluated them on the full COCO val2017 on the CPU, the iGPU and the NPU (one and two tiles), in FP16 and INT8. Table I summarizes the results; our harness reproduces the published AP within 0.2 points for all of them. Six observations motivate this work.

O1: the NPU alone is never the fastest placement. The NPU-only latency is 1.4 to 3.6× that of the best placement (Table I).

O2: FLOPs do not predict latency. YOLO26-N (5.4 GFLOPs) takes 26 to 29 ms, while ResNet-50 at 224 px takes 4 ms. Micro-benchmarks of 396 blocks show where the time goes:

- depthwise convolutions reach only 0.1 to 0.3 TOPS;
- SiLU and HardSwish add 30 to 55 % to a layer;
- a LayerNorm over 6 400 tokens costs almost as much as an MLP;
- a `TopK` inside the graph costs 1.2 to 2.5 ms, against 0.13 ms on the host CPU.

The latency of a detector depends on which operations it uses, not on how many FLOPs it has.

O3: vendor counters overlap. The NPU reports per-task durations. For YOLO26-N (25.9 ms), the SHAVE tasks add up to 45.9 ms and the DPU tasks to 18.9 ms. On four models, the counters sum to 126 to 349 ms for inferences of 18 to 31 ms. The same model gave a sum of 66 ms in one run and 126 ms in the next.

O4: costs are not additive. Timing truncated prefixes of a graph gives some segments negative costs, down to -3.7 ms, because the compiler makes different decisions on each truncated graph.

O5: the compiler fails silently. In two-tile mode, YOLO26-N loses 4.6 AP, RT-DETRv2 3.8 and DEIMv2-N 0.9, without any error. YOLO26-S loses the device (`ZE_RESULT_ERROR_DEVICE_LOST`) after 4 to 7 different images; one repeated input passes. Every operation is correct when compiled alone, attention and `TopK` included. The faults come from decisions the compiler makes on the whole graph, so correctness must be checked on the deployed network with real inputs.

O6: INT8 is not a universal lever. INT8 makes ResNet-50 at 640 px 2.4× faster. It makes D-FINE-N slower (61.6 ms against 43.1 on one tile) and gives YOLO26-S only 13 %, for a loss of 0.3 to 2.6 AP.

O1–O6 rule out a static cost model: a tool for this NPU must measure latency and must check correctness.

III. RELATED WORK

Latency prediction. nn-Meter [10] detects kernel fusions and sums kernel-level predictions; on an Intel VPU, only 83 % of its predictions fall within 10 % of the measured latency. HW-NAS-Bench [11] and BRP-NAS [12] learn latency predictors for architecture search. O3 and O4 show that kernel costs do not add up on our NPU. We use an nn-Meter-style additive model as a baseline in Section V-B.

Hardware-aware design and compression. NetAdapt [13] adapts networks with empirical latency measurements; ProxylessNAS [14] and MnasNet [15] put latency into the search objective; AMC [16] prunes under a resource budget. MobileDets [19] and accelerator-aware NAS [20] show that edge accelerators favor regular, full convolutions over depthwise ones, which O2 confirms. These works produce new architectures and require training. OptiNPU starts from a given model and first applies the changes that need no training.

Mixed-precision quantization. HAQ [21] learns per-layer bit widths with reinforcement learning and hardware feedback. HAWQ [22] ranks layers by Hessian sensitivity, and HAWQ-V3 [17] picks bit widths under a latency budget expressed as a sum of per-layer latencies. On the NPU we find this sum misleading (Section V-F2). OptiNPU builds on NNCF post-training quantization [23] and measures every candidate mix as a whole.

Compilers and graph rewriting. TVM [24] and Ansor [25] tune kernels; TASO [26] and PET [27] search graph substitutions, the latter including partially equivalent ones with corrections. Vendor NPU compilers are closed, so OptiNPU works at the level of the model graph and the compile options. NNSmith [28] finds compiler bugs with generated graphs. We instead check the accuracy of the user's own deployed model on its task.

Heterogeneous execution and on-device studies. CoDL [29] and Band [30] split inference across mobile processors. We keep the network on the NPU, and use other devices only as a reference point. AI Benchmark [31], Almeida et al. [32] and MLPerf [33] characterize on-device inference. For measurement methodology we follow Hoefler and Belli [34] and randomize the execution order to avoid the biases described by Mytkowicz et al. [35].

TABLE II
LATENCY CHANGE OF A VARIANT, RELATIVE TO THE TRAINED MODEL (NPU, TWO TILES; CNNS AT 640 PX): RANDOM DENSE WEIGHTS, ALL-ZERO INPUTS, 50 % AND 90 % OF THE WEIGHTS SET TO ZERO.

Model	Random	Zero input	50 % zero	90 % zero
ResNet-50	−0.3 %	−0.4 %	**−25.5 %**	**−35.3 %**
MobileNetV2	+1.5 %	+0.6 %	−2.6 %	−3.8 %
YOLO26-N FP16	−5.2 %	+0.1 %	−5.9 %	−8.6 %
YOLO26-N INT8	−3.7 %	0.0 %	−6.3 %	−6.5 %
D-FINE-N FP16	+0.1 %	**+11.0 %**	−2.8 %	−2.8 %

TABLE III
AGREEMENT WITH CPU FP32 ON 30 IMAGES, AGAINST THE REAL AP LOSS OF THE TWO-TILE MODE (FULL VAL2017).

	AP loss	Agreement	
Model	(2 tiles)	2 tiles	1 tile
RF-DETR-N	0.0	0.990	0.990
D-FINE-N	−0.2	0.919	0.994
DEIMv2-N	−0.9	0.862	0.975
RT-DETRv2-R18	−3.8	0.729	0.990
YOLO26-N	−4.6	0.842	0.989

IV. OPTINPU

OptiNPU takes a model (OpenVINO IR, ONNX or PyTorch with an example input), a *task* that turns images into inputs and outputs into predictions, a few guard images, and optionally an annotated evaluation set. It returns a measured profile, an optimized deployment (one or two IR parts with their devices and compile options), and a report (Fig. 1).

A. Premise: latency does not depend on dense weight values

We time each model with its trained weights and with four variants, in 7 rounds of 40 inferences (Table II). Replacing the trained weights by random dense ones changes latency within the noise, except where the graph contains data-dependent operations. Two exceptions matter:

- **Data-dependent operations.** YOLO26 selects boxes with an in-graph `TopK`, and D-FINE selects queries and samples deformable attention [36] at data-dependent locations. D-FINE-N is 11 % slower on all-zero inputs.
- **Weight sparsity.** The NPU exploits unstructured zeros in the weights: ResNet-50 is 25.5 % faster with 50 % zero weights and 35.3 % faster with 90 %.

This premise has three consequences:

- OptiNPU can time any rewrite exactly before training it, for example SiLU replaced by ReLU in a model whose weights are not yet retrained;
- it profiles models on real images, which keeps data-dependent operations realistic;
- unstructured pruning becomes a rewrite whose speedup can be measured in advance.

B. Measured profiler

Regions. The profiler attributes latency to *regions*, sets of runtime operations that come from the same source module (PyTorch module paths, or ONNX node scopes), truncated at a depth chosen to give a target number of regions. It also attributes latency to operation types.

Bypassing a region. To bypass a region, OptiNPU removes its operations and reconnects every tensor the region hands to the rest of the graph to the one tensor it receives with the same shape and type. The rewrite is refused when this mapping is ambiguous, or when it would create a cycle, which happens for a region that is not contiguous. Outputs that are no longer real are converted so that the graph stays valid. The saving of the bypassed graph is the latency of that region in context, fusions with its neighbors included.

Paired, randomized, adaptive rounds. All variants and the reference are compiled in a single child process. Each round times every variant (30 to 40 inferences each) in a freshly shuffled order. A variant's saving is the mean of its per-round differences with the reference, with a t-based 95 % confidence interval. Pairing cancels the drift of the machine. Rounds continue until every half-width is at most $\max(0.02\,\text{ms}, 0.5\,\%)$ of the latency, up to 40 rounds. A saving is *significant* when its lower bound is positive.

C. Task-level accuracy guard

The reference is always the original model on the CPU in FP32. The guard has two levels.

Agreement. Both deployments run on 30 guard images. The agreement is the F1 score of matching their detections: same class, IoU ≥ 0.7, confidence ≥ 0.3. Without annotations, a state is exact when its agreement is at least $\tau = 0.95$. For a classifier, the agreement is the share of images with the same top-1 class; for any other model, it is $1-$ the relative L2 error of the worst output. Table III calibrates the threshold on the two-tile faults of O5. The previous criterion, the maximal output error, flagged RF-DETR (exact) and missed YOLO26-N (-4.6 AP); agreement separates them.

AP non-inferiority. Agreement is only a proxy, and it errs both ways. The two-tile YOLO26-N reached 0.966 on one set of 30 images while losing more than 4 AP; D-FINE-N reaches only 0.923 while losing 0.2 AP. When annotations are given, the AP therefore decides: OptiNPU evaluates it on $K = 20$ interleaved folds of 50 images, for the candidate and for the CPU FP32 reference. With the per-fold differences d_k, it accepts the candidate when a one-sided paired t test rejects a loss larger than the budget B [37]:

$$\bar{d} - t_{0.95,\,K-1}\,\frac{s_d}{\sqrt{K}} \;\geq\; -B. \tag{1}$$

We use $B = 0.5$ AP. For a classifier, the same test applies to top-1 accuracy on a labeled set, with the same budget in accuracy points. This test decides whether the original deployment, a repair or an approximation counts as exact; agreement only decides when there are no annotations.

Test power. The number of images matters in both directions. A point estimate on 200 images accepted a mixed-precision YOLO26-N within 0.3 points of the reference, which




Fig. 1. The OptiNPU optimization loop. Every candidate is timed against the current state in the same sandboxed process, and checked against the CPU FP32 original before it is accepted. The loop stops when no candidate is accepted.

TABLE IV
REWRITE CATALOG.

Tier	Rewrites
Exact	final selection on the host CPU; one or two tiles; DETR decoder compiled apart on one tile; depthwise as dense block-diagonal convolution
Approximate	INT8 post-training quantization (NNCF CNN and transformer schemes); latency-guided mixed precision
Retraining	SiLU/HardSwish/GELU $\rightarrow$ ReLU; LayerNorm $\rightarrow$ BatchNorm; 50 % and 75 % unstructured pruning

then lost 0.9 points on the report images; with the test, the same mix (-0.37 points, lower bound -1.2) is rejected. Conversely, 10 folds of 50 images left a margin of about 0.4 points: D-FINE-N's 0.25-point loss had a lower bound of -0.64, so the optimizer paid 15 ms to repair a loss within the budget. With 20 folds, the margins of approximate candidates close to the budget are 0.16 to 0.45 points on the seven detectors, and D-FINE-N's original deployment (-0.18, lower bound -0.44) is now exact. Top-1 on 2 000 ImageNetV2 images is noisier, with margins of 0.37 to 0.92 points: a classifier mix passes only when it shows almost no loss.

D. Optimizer

State. The optimizer searches over deployment states $s = (\text{graph}, \text{compile options}, \text{placement})$. The placement either runs the whole graph on the NPU, or cuts it into two IR parts, each with its own device and options.

Target. The network stays on the NPU: the point of an NPU is to leave the CPU and the iGPU free, at low power. Only a *light selection tail* may move to the CPU. This tail is the first `TopK` or NMS and everything that depends on it, provided it has no convolution or matrix product; this is the host post-processing every deployment performs. Moving heavier parts, such as a DETR decoder, to the iGPU or the CPU is an explicit option that we use only as a reference point (Section V-E).

Candidates. Table IV lists the rewrites, in three tiers:

- *exact* rewrites do not change the function;
- *approximate* rewrites change it on purpose and must keep AP within the budget;
- *retraining* rewrites are only timed on the final state, and reported with their measured latency.

Greedy loop (Algorithm 1). At each step, all candidates are timed against the current state in one paired session. They are then checked in decreasing order of saving. The first candidate that is significantly faster (lower bound above zero and saving above 1 %) and passes the guard is applied. Approximate candidates are always judged against the CPU FP32 original, never against the current state, so their errors do not accumulate.

Algorithm 1 Measured greedy optimization

Require: model M, task, guard images, annotated set, AP budget B

$s \leftarrow (M,$ default options, whole graph on the NPU$)$
$x \leftarrow \textsc{Exact}(s)$ ▷ Eq. (1), else agreement $\geq \tau$
loop
  $C \leftarrow \textsc{Candidates}(s)$
  time s and C in paired rounds: savings $\Delta_c \pm h_c$
  $s' \leftarrow \perp$
  for $c \in C$ in decreasing order of Δ_c **do**
    if x **and not** ($\Delta_c - h_c > 0$ **and** $\Delta_c > 1\,\%$) **then**
      continue ▷ an exact state only accepts gains
    end if
    if c is approximate **then**
      $ok \leftarrow$ Eq. (1) holds for c
      if not ok **and** x **then**
        $(ok, c) \leftarrow \textsc{MixedPrecision}(s, c)$
      end if
    else
      $ok \leftarrow \textsc{Exact}(c)$
    end if
    if ok **then**
      $s' \leftarrow c$; **break**
    end if
  end for
  if $s' = \perp$ **then**
    break
  end if
  $s \leftarrow s'$; $x \leftarrow \textsc{Exact}(s)$
end loop
return s and the measured latency of the retraining rewrites on s

Repairs. An inexact state (O5) accepts any candidate that repairs it, even a slower one: correctness comes first. A candidate that is faster and agrees better without being exact is also accepted. Approximate candidates can repair too; for instance, INT8 removes the two-tile fault of RT-DETRv2.

Latency-guided mixed precision. The search starts when full INT8 is significantly faster but outside the AP budget. It

forms *groups* of operations to keep in float:

- one group per module region that contains a convolution or a matrix product, with about ten groups in total;
- one group, *rest*, for every other quantized operation. Without it, quantizers on a DETR decoder's box arithmetic can never return to float (Section V-F2).

Each group is kept alone in float on top of full INT8, quantized with 64 calibration images. Its AP gain is measured on the annotated set, and its latency cost in a paired session against full INT8. Among the groups that cost more than a quarter of the INT8 saving, the most useful one that can be split is split into its sub-modules and measured again, up to three times. Groups are then ranked by AP gained per millisecond. Growing mixes are quantized with all 300 calibration images and *verified as a whole*, for latency and with Eq. (1). The search stops at the first mix that passes, or when adding float groups removes the significant gain. We never assume that the latency of a mix is the sum of its groups' costs.

E. Implementation

OptiNPU is a Python library and command-line tool (`optinpu profile`, `optinpu optimize`) built on OpenVINO and NNCF. Every compilation and inference runs in a child process watched for memory and time, whose whole process tree is killed on failure. On this NPU, the compiler reached 53 to 55 GB of virtual memory on some graphs, and a lost device must become a rejected candidate rather than a crash of the tool. The optimized deployment is saved as IR parts with a JSON description (devices, compile options, applied changes) and a report. It can also be rebuilt from its list of changes: the seven rebuilt detector deployments reproduce their recorded AP exactly.

V. Evaluation

A. Setup

Hardware and software. We use an Intel Core Ultra 5 235U laptop (NPU 3720, driver 32.0.100.4778, 15.5 GB of RAM) on mains power, with Windows 11, OpenVINO 2026.4.1 and NNCF 3.4. All latencies are for batch 1.

Models. We use seven detectors, chosen to cover the architectural families that behave differently on the NPU:

- YOLO26-N and -S [8]: CNNs with an in-graph `TopK`, no NMS;
- D-FINE-N and -S [4], and DEIMv2-N [6]: HGNetv2 backbones and deformable decoders;
- RT-DETRv2-R18 [3]: a ResNet backbone and a standard attention decoder;
- RF-DETR-N [7]: a DINOv2 ViT backbone [38].

They are exported as FP16 IRs. To show that the approach is not specific to detection, we also optimize three ImageNet classifiers [39] at 224 px, with their torchvision weights: ResNet-50 [40], MobileNetV2 [41] and EfficientNet-B0 [42]. The profiler validation uses the same three CNNs at 640 px.

Protocol. All detectors were trained on COCO train2017, so every decision is taken on val2017 images disjoint from the reported ones: guard [4970, 5000), INT8 calibration [4500, 4800), and AP budget [2500, 3500) in 20 folds of 50 images. We report AP on val2017 [0, 2500), on which nothing is decided. The classifiers are judged on ImageNetV2 [43] (matched frequency, 10 000 images), which none of them was trained on. We split one fixed shuffle of it into disjoint slices: guard [7300, 7600) (top-1 agreement), calibration [7000, 7300), top-1 budget [5000, 7000) in 10 folds of 200, and report [0, 5000).

TABLE V
Predicting the saving of an intervention: mean over five models (73 significant interventions out of 150).

Predictor	ρ	Error (% lat.)	Top-3	Regret
Vendor counters (scaled)	$+0.57$	3.7	0.53	0.31
Additive (isolated ops)	$+0.41$	11.6	0.80	0.32
Measured (repeat)	$\mathbf{+0.78}$	**0.9**	**0.87**	**0.00**

B. Does measured profiling pick better interventions?

Ground truth. On five models we apply 150 interventions: bypassing a region or an operation type, SiLU $\rightarrow$ ReLU, removing LayerNorms, and moving the final selection to the CPU. We measure each intervention's saving twice, in opposite orders. The ground truth is the mean of the two runs.

Predictors. We compare three ways to predict these savings:

- *vendor counters*: the durations of the removed operations, scaled to the latency;
- an *additive* model in the style of nn-Meter: each operation compiled alone on the NPU, minus the cost of a graph reduced to its inputs;
- *our measurement*: run 2 used to predict run 1, which is the reproducibility a single run of the tool achieves.

Metrics. Over the 73 significant interventions, we report Spearman's ρ, the mean absolute error as a percentage of the latency, the overlap of the top three interventions, and the *regret*: the share of the best saving lost by applying the predictor's first choice.

Table V gives the results. Measurement never misses the best intervention: its regret is at most 0.01 on every model. The vendor counters have a regret of 0.62 on D-FINE-N and 0.82 on EfficientNet-B0. The additive model has a regret of 0.83 on ResNet-50, where its rank correlation is even negative (-0.28). Summed over all operations of the four larger models, the counters give 126 to 349 ms and the additive model 101 to 245 ms, for real latencies of 18 to 31 ms.

Limit. On the smallest model (MobileNetV2, 7.2 ms), many savings are significant but close to each other, and their fine order stays at the noise level (measured $\rho = +0.62$). Adaptive rounds raised the number of significant interventions on this model from 3 to 11.

C. Optimizing detectors for the NPU

Table VI reports the optimizer with the network on the NPU (Section IV-D).

TABLE VI
OPTIMIZER RESULTS, NETWORK ON THE NPU (FP16 IRS; AP ON VAL2017 [0, 2500), ON WHICH NOTHING WAS DECIDED). "BEFORE" IS THE DEFAULT TWO-TILE COMPILATION.

Model	Before	After	Applied changes	AP: CPU FP32 / before / after
YOLO26-N	26.6 ms	**9.30 ms (2.86×)**	final selection on the CPU	41.7 / 37.0 / 41.6
YOLO26-S	33.1 ms, device lost	**16.2 ms (2.04×)**	final selection on the CPU	49.4 / — / 49.4
D-FINE-N	26.0 ms	26.0 ms (1.00×)	none: the original is exact	44.5 / 44.3 / 44.3
D-FINE-S	46.3 ms	42.9 ms (1.08×)	mixed INT8 (7 of 19 groups in float)	50.2 / 50.1 / 49.9
DEIMv2-N	24.0 ms	41.2 ms (0.58×)	repair: one tile (original AP -0.44, bound -0.69)	45.0 / 44.0 / 44.9
RT-DETRv2-R18	47.4 ms	**40.6 ms (1.17×)**	repair: INT8, transformer scheme	49.7 / 46.0 / 49.6
RF-DETR-N	83.4 ms	81.7 ms (1.02×)	INT8, transformer scheme	50.0 / 50.0 / 49.7

YOLO26. The optimizer moves 16 operations, the final selection, to the CPU. This makes YOLO26-N 2.86× faster and YOLO26-S 2.04× faster on the NPU, and both now beat the iGPU (10.9 and 23.8 ms, Table I). The rewrite also removes both two-tile faults: the silent loss of 4.6 AP of YOLO26-N, and the device hang of YOLO26-S. The tail compiled alone on two tiles does not hang, so the faults arise when the compiler combines the selection with the rest of the graph. Mixed INT8 would then save up to 2.7 ms more on YOLO26-S, but every mix loses about 0.5 AP on the decision images, with lower bounds of -0.73 to -0.89. The test rejects them all, as it does on YOLO26-N, where INT8 would save at most 0.4 ms.

DETR family. Without leaving the NPU, the DETRs mostly need repairs, and the guard decides what they may cost:

- *RT-DETRv2* loses 2.4 AP in two-tile mode on the decision images, and 3.7 on the report images. INT8 with the transformer scheme repairs it and is faster: 47.4 → 40.6 ms, within 0.2 AP of the CPU.
- *DEIMv2-N* loses 0.44 AP on the decision images (lower bound -0.69), and 1.0 on the report images. Neither INT8 scheme stays within the budget (-22.5 and -1.2 AP), and the decoder alone on one tile is slower than the whole graph on one tile. The cheapest exact deployment therefore runs on one tile: 41.2 ms instead of 24.0. With a budget of one point, the original would be kept; the report gives both.
- *D-FINE-N* loses only 0.18 AP: the original is exact, and nothing else is both faster and within the budget. Full INT8 saves only 0.3 ms and costs 5.9 AP, most of it in the backbone.
- *D-FINE-S* and *RF-DETR-N* are exact on the NPU. Full INT8 costs D-FINE-S 6.0 AP; keeping 7 of 19 groups in float, the *rest* group included, brings it within the budget (-0.13, bound -0.36), and this mix is even 1.3 ms faster than full INT8. RF-DETR-N gains only 2 %, with INT8 in the transformer scheme (-0.23, bound -0.39). On the report images, both lose 0.27 AP.

On the NPU alone, none of them beats its best placement of Table I.

D. Beyond detection: image classifiers

The same optimizer runs on classifiers, with the top-1 agreement as guard and top-1 accuracy as the judged metric (Table VII). On the report slice, CPU FP32 top-1 is 11 to 13 points below each model's ImageNet accuracy, as expected [43]. The compiler is exact on all three (within 0.15 points of the CPU), so only INT8 can make them faster. On ResNet-50, full INT8 is 1.82× faster but loses 0.30 points (bound -0.90); keeping 5 of 20 groups in float passes the test (-0.00, bound -0.49) and keeps 1.60×. On MobileNetV2, full INT8 saves 20 % and loses 0.35 points; six groups in float, the *rest* group included, cost only 0.03 ms and pass ($+0.05$, bound -0.32). On EfficientNet-B0, full INT8 saves only 6 % and loses 1.25 points, no group recovers more than 0.2 points when kept in float, and the original is kept. Depthwise convolutions rewritten as dense ones are slower on both mobile networks.

TABLE VII
CLASSIFIERS, NETWORK ON THE NPU (224 PX). TOP-1 ON IMAGENETV2 [0, 5000), ON WHICH NOTHING WAS DECIDED: CPU FP32 / BEFORE / AFTER. THE MIXES KEEP 5 (RESNET-50) AND 6 (MOBILENETV2) OF 20 GROUPS IN FLOAT.

Model	Before (ms)	After (ms)	Applied	Top-1 (%)
ResNet-50	3.86	**2.41** (1.60×)	mixed INT8	69.9 / 69.9 / 69.2
MobileNetV2	1.27	**1.04** (1.22×)	mixed INT8	59.5 / 59.5 / 59.6
EfficientNet-B0	2.75	2.75 (1.00×)	none	65.8 / 65.8 / 65.8

The report slice also exposes a limit of the test: ResNet-50's mix shows no loss on the decision images, but loses 0.64 points on the report images. The search tested five growing mixes on the same images and kept the first that passed, after four with point estimates of -0.15 to -0.55; keeping the first success among noisy tests favors an underestimated loss.

E. Reference point: offloading the decoder

When the decoder may leave the NPU, the optimizer moves it to the iGPU on every DETR, 1.4 to 2.1× faster than the original on the NPU (Table VIII). It rediscovers the best placement of Table I on D-FINE-N, and beats it on D-FINE-S (with mixed INT8) and on RT-DETRv2 (cut at the end of the encoder, then INT8). On DEIMv2-N and RF-DETR-N, the optimized hybrid deployment is still slower than the iGPU alone. Hybrid latencies are also less stable: an earlier run measured the same DEIMv2-N and RF-DETR-N cuts at 13.1 and 39.4 ms, while the originals on the NPU varied by less than 2 %. This is why OptiNPU keeps the network on the

TABLE VIII
WITH THE DECODER ALLOWED ON THE IGPU: OPTINPU'S NPU+IGPU DEPLOYMENT (AP ON VAL2017 [0, 2500)) AGAINST THE FASTEST PLACEMENT OF TABLE I (HYBRID = NPU+IGPU).

Model	OptiNPU	AP CPU / after	Fastest (Table I)
D-FINE-N	15.2 ms	44.5 / 44.4	hybrid 15.5 ms
D-FINE-S	30.3 ms‡	50.2 / 50.0	hybrid 34.0 ms
DEIMv2-N	16.6 ms	45.0 / 44.9	iGPU 15.1 ms
RT-DETRv2-R18	26.1 ms*†	49.7 / 49.6	hybrid 34.9 ms
RF-DETR-N	40.1 ms†	50.0 / 49.7	iGPU 23.0 ms

*cut at the end of the encoder. †+ INT8 (transformer scheme). ‡+ mixed INT8.

NPU by default: offloading competes with other devices rather than optimizing for the NPU.

F. Case studies

1) Where the time goes in YOLO26-N: The profiler attributes 72 % of the latency (18.6 ms) to the head. The vendor counters point at the final selection, which runs on the SHAVE cores: `Divide` 19.5 ms, `GatherElements` 15.4 ms, `TopK` 4.1 ms. These durations overlap and add up to more than the whole inference. Only the bypass measurement gives the real saving, which the selection-to-CPU rewrite then achieves.

2) Mixed precision is not additive: **The loss is concentrated.** On YOLO26-S, full INT8 loses 6.6 AP. Most of the loss sits in one attention block: keeping it in float recovers 4.5 AP for 0.04 ms.

Latency is not additive. On RF-DETR-N, whose backbone runs on the NPU, NNCF's CNN scheme loses 4.2 AP, and the optimizer refined the search down to the 12 DINOv2 layers. Keeping the *whole* encoder stack in float costs 4.2 ms. Keeping a *single* middle layer in float, between INT8 layers, costs 13 to 16 ms. Precision changes and the re-tiling between layers of different precisions cost more than the arithmetic. A cost model that sums per-layer costs would choose the single layer; measuring the whole mix avoids that mistake.

Module groups miss operations. On D-FINE-N, keeping 18 of 20 module groups in float still left a 3.1-point loss. With every group in float, 64 quantizers remained, almost all on the decoder's box and reference-point arithmetic, which belongs to no module containing a convolution. The *rest* group fixes this, and it becomes the most useful group of D-FINE-N: keeping it in float recovers 2.85 AP and even saves 0.47 ms.

3) Repairing on the NPU: On RT-DETRv2, the two-tile fault sits in the decoder's self-attention. Rewriting the attention in the IR changes nothing, because the compiler normalizes all its variants. Compiling the decoder apart on one tile, with the rest on two, repairs the model on the NPU (Table IX). The repair is expensive, however: cutting the graph into two NPU inferences alone costs 8.9 ms, and one tile slows the decoder down by 19 ms. INT8 with the transformer scheme also removes the fault (AP -0.29 instead of -2.9), because the compiler then partitions the attention differently. The optimizer measures these repairs and picks the fastest one: here INT8 (40.6 ms), faster than the original. Two rules made this possible. First, approximate candidates may repair an inexact state. Second, mixed precision may be searched on an inexact state when full INT8 already keeps the mean loss within the budget and only misses its lower bound. Without these rules, the optimizer took the one-tile decoder and ended at 71.0 ms.

TABLE IX
REPAIRING RT-DETRV2 (FP16) WITHOUT LEAVING THE NPU (30 GUARD IMAGES).

Deployment on the NPU	Latency	Agreement
Whole graph, 2 tiles (default)	47.1 ms	0.721
Cut at the query selection, both parts on 2 tiles	56.0 ms	0.721
Encoder on 1 tile, decoder on 2	72.3 ms	0.721
Encoder on 2 tiles, decoder on 1	75.4 ms	**0.995**
Whole graph, 1 tile	80.6 ms	0.995

G. Retraining rewrites, measured before training

Thanks to the premise, OptiNPU reports the exact latency of rewrites that need retraining:

- SiLU → ReLU would make the optimized YOLO26-N 21 % faster (7.33 ms), YOLO26-S 17 % faster (13.4 ms) and EfficientNet-B0 35 % faster (1.79 ms);
- pruning 50 % or 75 % of the weights would make the optimized ResNet-50 23 % or 32 % faster (1.86 or 1.63 ms);
- on the five DETR-family models, the best of these rewrites brings only 3 to 8 %.

OptiNPU does not retrain the model: it tells, before any training, which retraining is worth its cost. A gain of 17 to 35 % justifies fine-tuning YOLO26 or EfficientNet-B0 with ReLU; 3 to 8 % hardly justifies retraining a DETR.

VI. DISCUSSION AND LIMITATIONS

One NPU. We measured a single NPU (3720), with a single driver and compiler version. Its faults and costs may change with a driver update; this is precisely why OptiNPU measures instead of encoding rules. Porting it to another NPU supported by OpenVINO only requires a device name; another runtime would need new sandboxed jobs. [TODO: second NPU or newer driver if available.]

What we do not measure. We do not report energy, although low power is the reason to use the NPU. [TODO: energy measurement, if feasible on this platform.]

Accuracy guard. The guard relies on samples:

- agreement on 30 images can miss AP losses (Section IV-C), so AP decides when annotations exist;
- without annotations, an approximate rewrite must reach the agreement of an exact one, a conservative rule;
- keeping the first of several mixes that passes favors an underestimated loss (Section V-D); a confirmation on held-out images would remove this bias;
- the non-inferiority test uses 1 000 val2017 images and the report 2 500 others; the remaining images serve for calibration and the guard, or are held out.

Cost of the search. The search applies one change at a time, so it can miss combinations that only pay off together. A whole run, final evaluation included, takes 12 to 24 minutes

for a classifier and from 35 minutes (RT-DETRv2) to 1 h 45 (D-FINE-N) for a detector on our laptop.

Scope. Beyond detectors and classifiers, other models can use the generic output-agreement task, without a metric test.

VII. Conclusion

On a client NPU, latency cannot be predicted from FLOPs, vendor counters or per-operation costs, and the compiler can be silently wrong. Two facts make a measurement-only approach practical: latency does not depend on dense weight values, and paired, randomized, adaptive rounds measure small savings reliably. OptiNPU turns these facts into a profiler that picks the right intervention, an accuracy guard grounded in the task, and an optimizer that repairs and accelerates detectors without leaving the NPU. It repairs the four detectors that the compiler gets wrong and makes YOLO26-N and -S 2.86 and 2.04× faster, ahead of the iGPU; DETR-family models gain at most 1.17× on the NPU alone. Mixed precision makes ResNet-50 1.60× and MobileNetV2 1.22× faster, and the measured what-ifs tell which retraining is worth its cost.

Acknowledgment

[TODO: acknowledgments, if any.]

References

[1] N. Carion, F. Massa, G. Synnaeve, N. Usunier, A. Kirillov, and S. Zagoruyko, "End-to-end object detection with transformers," in *Proc. ECCV*, 2020.

[2] Y. Zhao, W. Lv, S. Xu, J. Wei, G. Wang, Q. Dang, Y. Liu, and J. Chen, "DETRs beat YOLOs on real-time object detection," in *Proc. CVPR*, 2024.

[3] W. Lv, Y. Zhao, Q. Chang, K. Huang, G. Wang, and Y. Liu, "RT-DETRv2: Improved baseline with bag-of-freebies for real-time detection transformer," arXiv:2407.17140, 2024.

[4] Y. Peng, H. Li, P. Wu, Y. Zhang, X. Sun, and F. Wu, "D-FINE: Redefine regression task in DETRs as fine-grained distribution refinement," in *Proc. ICLR*, 2025.

[5] S. Huang, Z. Lu, X. Cun, Y. Yu, X. Zhou, and X. Shen, "DEIM: DETR with improved matching for fast convergence," in *Proc. CVPR*, 2025.

[6] S. Huang, Y. Hou, L. Liu, X. Yu, and X. Shen, "Real-time object detection meets DINOv3," arXiv:2509.20787, 2025.

[7] I. Robinson, P. Robicheaux, M. Popov, D. Ramanan, and N. Peri, "RF-DETR: Neural architecture search for real-time detection transformers," in *Proc. ICLR*, 2026.

[8] G. Jocher, J. Qiu, M. Liu, S. Lyu, F. C. Akyon, and M. E. Kalfaoglu, "Ultralytics YOLO26: Unified real-time end-to-end vision models," arXiv:2606.03748, 2026.

[9] T.-Y. Lin *et al.*, "Microsoft COCO: Common objects in context," in *Proc. ECCV*, 2014.

[10] L. L. Zhang, S. Han, J. Wei, N. Zheng, T. Cao, Y. Yang, and Y. Liu, "nn-Meter: Towards accurate latency prediction of deep-learning model inference on diverse edge devices," in *Proc. ACM MobiSys*, 2021.

[11] C. Li *et al.*, "HW-NAS-Bench: Hardware-aware neural architecture search benchmark," in *Proc. ICLR*, 2021.

[12] Ł. Dudziak, T. Chau, M. S. Abdelfattah, R. Lee, H. Kim, and N. D. Lane, "BRP-NAS: Prediction-based NAS using GCNs," in *Proc. NeurIPS*, 2020.

[13] T.-J. Yang, A. Howard, B. Chen, X. Zhang, A. Go, M. Sandler, V. Sze, and H. Adam, "NetAdapt: Platform-aware neural network adaptation for mobile applications," in *Proc. ECCV*, 2018.

[14] H. Cai, L. Zhu, and S. Han, "ProxylessNAS: Direct neural architecture search on target task and hardware," in *Proc. ICLR*, 2019.

[15] M. Tan, B. Chen, R. Pang, V. Vasudevan, M. Sandler, A. Howard, and Q. V. Le, "MnasNet: Platform-aware neural architecture search for mobile," in *Proc. CVPR*, 2019.

[16] Y. He, J. Lin, Z. Liu, H. Wang, L.-J. Li, and S. Han, "AMC: AutoML for model compression and acceleration on mobile devices," in *Proc. ECCV*, 2018.

[17] Z. Yao *et al.*, "HAWQ-V3: Dyadic neural network quantization," in *Proc. ICML*, 2021.

[18] Intel Corporation, "OpenVINO toolkit," https://github.com/openvinotoolkit/openvino, 2026, version 2026.4.1.

[19] Y. Xiong, H. Liu, S. Gupta, B. Akin, G. Bender, Y. Wang, P.-J. Kindermans, M. Tan, V. Singh, and B. Chen, "MobileDets: Searching for object detection architectures for mobile accelerators," in *Proc. CVPR*, 2021.

[20] S. Gupta and B. Akin, "Accelerator-aware neural network design using AutoML," arXiv:2003.02838, 2020.

[21] K. Wang, Z. Liu, Y. Lin, J. Lin, and S. Han, "HAQ: Hardware-aware automated quantization with mixed precision," in *Proc. CVPR*, 2019.

[22] Z. Dong, Z. Yao, A. Gholami, M. W. Mahoney, and K. Keutzer, "HAWQ: Hessian AWare quantization of neural networks with mixed-precision," in *Proc. ICCV*, 2019.

[23] A. Kozlov, I. Lazarevich, V. Shamporov, N. Lyalyushkin, and Y. Gorbachev, "Neural network compression framework for fast model inference," arXiv:2002.08679, 2020.

[24] T. Chen *et al.*, "TVM: An automated end-to-end optimizing compiler for deep learning," in *Proc. USENIX OSDI*, 2018.

[25] L. Zheng *et al.*, "Ansor: Generating high-performance tensor programs for deep learning," in *Proc. USENIX OSDI*, 2020.

[26] Z. Jia, O. Padon, J. Thomas, T. Warszawski, M. Zaharia, and A. Aiken, "TASO: Optimizing deep learning computation with automatic generation of graph substitutions," in *Proc. ACM SOSP*, 2019.

[27] H. Wang *et al.*, "PET: Optimizing tensor programs with partially equivalent transformations and automated corrections," in *Proc. USENIX OSDI*, 2021.

[28] J. Liu, J. Lin, F. Ruffy, C. Tan, J. Li, A. Panda, and L. Zhang, "NNSmith: Generating diverse and valid test cases for deep learning compilers," in *Proc. ACM ASPLOS*, 2023.

[29] F. Jia *et al.*, "CoDL: Efficient CPU-GPU co-execution for deep learning inference on mobile devices," in *Proc. ACM MobiSys*, 2022.

[30] J. S. Jeong *et al.*, "Band: Coordinated multi-DNN inference on heterogeneous mobile processors," in *Proc. ACM MobiSys*, 2022.

[31] A. Ignatov *et al.*, "AI benchmark: All about deep learning on smartphones in 2019," in *Proc. ICCV Workshops*, 2019.

[32] M. Almeida, S. Laskaridis, A. Mehrotra, L. Dudziak, I. Leontiadis, and N. D. Lane, "Smart at what cost? Characterising mobile deep neural networks in the wild," in *Proc. ACM IMC*, 2021.

[33] V. J. Reddi *et al.*, "MLPerf inference benchmark," in *Proc. ISCA*, 2020.

[34] T. Hoefler and R. Belli, "Scientific benchmarking of parallel computing systems: Twelve ways to tell the masses when reporting performance results," in *Proc. SC*, 2015.

[35] T. Mytkowicz, A. Diwan, M. Hauswirth, and P. F. Sweeney, "Producing wrong data without doing anything obviously wrong!" in *Proc. ACM ASPLOS*, 2009.

[36] X. Zhu, W. Su, L. Lu, B. Li, X. Wang, and J. Dai, "Deformable DETR: Deformable transformers for end-to-end object detection," in *Proc. ICLR*, 2021.

[37] S. Wellek, *Testing Statistical Hypotheses of Equivalence and Noninferiority*, 2nd ed. Chapman & Hall/CRC, 2010.

[38] M. Oquab *et al.*, "DINOv2: Learning robust visual features without supervision," *Transactions on Machine Learning Research*, 2024.

[39] O. Russakovsky *et al.*, "ImageNet large scale visual recognition challenge," *International Journal of Computer Vision*, 2015.

[40] K. He, X. Zhang, S. Ren, and J. Sun, "Deep residual learning for image recognition," in *Proc. CVPR*, 2016.

[41] M. Sandler, A. Howard, M. Zhu, A. Zhmoginov, and L.-C. Chen, "MobileNetV2: Inverted residuals and linear bottlenecks," in *Proc. CVPR*, 2018.

[42] M. Tan and Q. V. Le, "EfficientNet: Rethinking model scaling for convolutional neural networks," in *Proc. ICML*, 2019.

[43] B. Recht, R. Roelofs, L. Schmidt, and V. Shankar, "Do ImageNet classifiers generalize to ImageNet?" in *Proc. ICML*, 2019.