



Red Hat Enterprise Linux 10

Risk reduction and recovery operations

Backing up data, log monitoring, and managing security updates

Red Hat Enterprise Linux 10 Risk reduction and recovery operations

Backing up data, log monitoring, and managing security updates

Legal Notice

Copyright © 2025 Red Hat, Inc.

The text of and illustrations in this document are licensed by Red Hat under a Creative Commons Attribution–Share Alike 3.0 Unported license ("CC-BY-SA"). An explanation of CC-BY-SA is available at

<http://creativecommons.org/licenses/by-sa/3.0/>

. In accordance with CC-BY-SA, if you distribute this document or an adaptation of it, you must provide the URL for the original version.

Red Hat, as the licensor of this document, waives the right to enforce, and agrees not to assert, Section 4d of CC-BY-SA to the fullest extent permitted by applicable law.

Red Hat, Red Hat Enterprise Linux, the Shadowman logo, the Red Hat logo, JBoss, OpenShift, Fedora, the Infinity logo, and RHCE are trademarks of Red Hat, Inc., registered in the United States and other countries.

Linux[®] is the registered trademark of Linus Torvalds in the United States and other countries.

Java[®] is a registered trademark of Oracle and/or its affiliates.

XFS[®] is a trademark of Silicon Graphics International Corp. or its subsidiaries in the United States and/or other countries.

MySQL[®] is a registered trademark of MySQL AB in the United States, the European Union and other countries.

Node.js[®] is an official trademark of Joyent. Red Hat is not formally related to or endorsed by the official Joyent Node.js open source or commercial project.

The OpenStack[®] Word Mark and OpenStack logo are either registered trademarks/service marks or trademarks/service marks of the OpenStack Foundation, in the United States and other countries and are used with the OpenStack Foundation's permission. We are not affiliated with, endorsed or sponsored by the OpenStack Foundation, or the OpenStack community.

All other trademarks are the property of their respective owners.

Abstract

Use the Relax-and-Recover (ReaR) disaster recovery tool to minimize the impact of disaster events and have a structured plan to restore systems and data after a failure. Learn how to manage and monitor your security updates for improved system stability, security and performance. Use log files to examine recorded system events to identify, troubleshoot, and avoid issues and monitor system functions.

Table of Contents

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION	4
CHAPTER 1. RECOVERING AND RESTORING A SYSTEM	5
1.1. SETTING UP REAR AND MANUALLY CREATING A BACKUP	5
1.2. USING A REAR RESCUE IMAGE ON THE 64-BIT IBM Z ARCHITECTURE	6
1.3. REAR EXCLUSIONS	7
CHAPTER 2. TROUBLESHOOTING PROBLEMS BY USING LOG FILES	9
2.1. SERVICES THAT HANDLE SYSLOG MESSAGES	9
2.2. SUBDIRECTORIES THAT STORE SYSLOG MESSAGES	9
2.3. COMMANDS FOR VIEWING LOGS	9
2.4. ADDITIONAL RESOURCES	10
CHAPTER 3. REVIEWING AND FILTERING LOGS IN THE WEB CONSOLE	11
3.1. REVIEWING LOGS IN THE WEB CONSOLE	11
3.2. FILTERING LOGS IN THE WEB CONSOLE	11
3.3. TEXT SEARCH OPTIONS FOR FILTERING LOGS IN THE WEB CONSOLE	13
3.4. USING A TEXT SEARCH BOX TO FILTER LOGS IN THE WEB CONSOLE	14
3.5. OPTIONS FOR LOGS FILTERING	15
CHAPTER 4. CONFIGURING THE SYSTEMD JOURNAL BY USING RHEL SYSTEM ROLES	17
4.1. CONFIGURING PERSISTENT LOGGING BY USING THE JOURNALD RHEL SYSTEM ROLE	17
CHAPTER 5. CONFIGURING A REMOTE LOGGING SOLUTION	19
5.1. THE RSYSLOG LOGGING SERVICE	19
5.2. INSTALLING RSYSLOG DOCUMENTATION	19
5.3. CONFIGURING A SERVER FOR REMOTE LOGGING OVER TCP	20
5.4. CONFIGURING REMOTE LOGGING TO A SERVER OVER TCP	22
5.5. CONFIGURING TLS-ENCRYPTED REMOTE LOGGING	23
5.6. CONFIGURING A SERVER FOR RECEIVING REMOTE LOGGING INFORMATION OVER UDP	27
5.7. CONFIGURING REMOTE LOGGING TO A SERVER OVER UDP	29
5.8. LOAD BALANCING HELPER IN RSYSLOG	31
5.9. CONFIGURING RELIABLE REMOTE LOGGING	31
5.10. SUPPORTED RSYSLOG MODULES	33
5.11. CONFIGURING THE NETCONSOLE SERVICE TO LOG KERNEL MESSAGES TO A REMOTE HOST	33
5.12. ADDITIONAL RESOURCES	34
CHAPTER 6. CONFIGURING LOGGING BY USING RHEL SYSTEM ROLES	35
6.1. FILTERING LOCAL LOG MESSAGES BY USING THE LOGGING RHEL SYSTEM ROLE	35
6.2. APPLYING A REMOTE LOGGING SOLUTION BY USING THE LOGGING RHEL SYSTEM ROLE	37
6.3. USING THE LOGGING RHEL SYSTEM ROLE WITH TLS	40
6.3.1. Configuring client logging with TLS	41
6.3.2. Configuring server logging with TLS	43
6.4. USING THE LOGGING RHEL SYSTEM ROLES WITH RELP	46
6.4.1. Configuring client logging with RELP	46
6.4.2. Configuring server logging with RELP	49
CHAPTER 7. AUDITING THE SYSTEM	52
7.1. LINUX AUDIT	52
7.2. AUDIT SYSTEM ARCHITECTURE	53
7.3. AUDIT SETTINGS FOR A SECURE ENVIRONMENT	54
7.4. STARTING AND CONTROLLING AUDITD	55
7.5. AUDIT LOG ENTRIES	56

7.6. EXAMPLES OF AUDIT RULES DEFINED WITH AUDITCTL	60
7.7. AUDIT PERSISTENT RULES	61
7.8. PRE-CONFIGURED AUDIT RULES FILES FOR COMPLIANCE WITH STANDARDS	62
7.9. DISABLING AUGENRULES	63
7.10. SETTING UP AUDIT TO MONITOR SOFTWARE UPDATES	63
7.11. MONITORING USER LOGIN TIMES WITH AUDIT	65
7.12. ADDITIONAL RESOURCES	66
CHAPTER 8. MANAGING AND MONITORING SECURITY UPDATES	67
8.1. IDENTIFYING SECURITY UPDATES	67
8.1.1. What are security advisories?	67
8.1.2. Displaying security updates that are not installed on a host	68
8.1.3. Displaying security updates that are installed on a host	69
8.1.4. Displaying a specific advisory by using DNF	69
8.2. INSTALLING SECURITY UPDATES	70
8.2.1. Installing all available security updates	70
8.2.2. Installing a security update provided by a specific advisory	70
8.2.3. Installing security updates automatically	71

PROVIDING FEEDBACK ON RED HAT DOCUMENTATION

We appreciate your feedback on our documentation. Let us know how we can improve it.

Submitting feedback through Jira (account required)

1. Log in to the [Jira](#) website.
2. Click **Create** in the top navigation bar
3. Enter a descriptive title in the **Summary** field.
4. Enter your suggestion for improvement in the **Description** field. Include links to the relevant parts of the documentation.
5. Click **Create** at the bottom of the dialogue.

CHAPTER 1. RECOVERING AND RESTORING A SYSTEM

Red Hat Enterprise Linux provides the Relax-and-Recover (ReaR) utility to recover and restore a system by using an existing backup. You can use the utility as a disaster recovery solution and also for system migration.

The utility enables you to perform the following tasks:

- Produce a bootable image and restore the system from an existing backup, by using the image.
- Replicate the original storage layout.
- Restore user and system files.
- Restore the system to a different hardware.

Additionally, for disaster recovery, you can also integrate certain backup software with ReaR.

1.1. SETTING UP REAR AND MANUALLY CREATING A BACKUP

Use the following steps to install the package for using the Relax-and-Recover (ReaR) utility, create a rescue system, configure and generate a backup.

Prerequisites

- Necessary configurations as per the backup restore plan are ready.
Note that you can use the **NETFS** backup method, a fully-integrated and built-in method with ReaR.

Procedure

1. Install the ReaR utility:

```
# dnf install rear
```

2. Modify the ReaR configuration file in an editor of your choice, for example:

```
# vi /etc/rear/local.conf
```

3. Add the backup setting details to **/etc/rear/local.conf**. For example, in the case of the **NETFS** backup method, add the following lines:

```
BACKUP=NETFS
BACKUP_URL=backup.location
```

Replace *backup.location* with the URL of your backup location.

4. To configure ReaR to keep the previous backup archive when the new one is created, also add the following line to the configuration file:

```
NETFS_KEEP_OLD_BACKUP_COPY=y
```

5. To make the backups incremental, meaning that only the changed files are backed up on each run, add the following line:

```
BACKUP_TYPE=incremental
```

6. Create a rescue system:

```
# rear mkrescue
```

7. Create a backup as per the restore plan. For example, in the case of the **NETFS** backup method, enter:

```
# rear mkbakuponly
```

Alternatively, you can create the rescue system and the backup in a single step by running the following command:

```
# rear mkbakup
```

This command combines the functionality of the **rear mkrescue** and **rear mkbakuponly** commands.

1.2. USING A REAR RESCUE IMAGE ON THE 64-BIT IBM Z ARCHITECTURE

Basic Relax and Recover (ReaR) functionality is available on the 64-bit IBM Z architecture and is fully supported. You can create a ReaR rescue image on IBM Z only in the z/VM environment. Backing up and recovering logical partitions (LPARs) has not been tested.

The only output method currently available is Initial Program Load (IPL). IPL produces a kernel and an initial RAM disk (initrd) that can be used with the **zIPL** boot loader.

Prerequisites

- You installed the **rear** package.

Procedure

1. Add the following variables to the **/etc/rear/local.conf** to configure ReaR for producing a rescue image on the 64-bit IBM Z architecture:
 - a. To configure the **IPL** output method, add **OUTPUT=IPL**.
 - b. To configure the backup method and destination, add **BACKUP** and **BACKUP_URL** variables. For example:

```
BACKUP=NETFS
```

```
BACKUP_URL=nfs://<nfsserver name>/<share path>
```



IMPORTANT

The local backup storage is currently not supported on the 64-bit IBM Z architecture.

- c. Optional: You can also configure the **OUTPUT_URL** variable to save the kernel and **initrd** files. By default, the **OUTPUT_URL** is aligned with **BACKUP_URL**.
2. To perform backup and rescue image creation:

```
# rear mkbbackup
```

3. This creates the kernel and **initrd** files at the location specified by the **BACKUP_URL** or **OUTPUT_URL** (if set) variable, and a backup by using the specified backup method.



WARNING

The rescue process reformats all the DASDs (Direct Attached Storage Devices) connected to the system. Do not attempt a system recovery if there is any valuable data present on the system storage devices. This also includes the device prepared with the **zipl** boot loader, ReaR kernel, and **initrd** that were used to boot into the rescue environment. Ensure to keep a copy.

4. To recover the system, use the previously created ReaR kernel and **initrd** files, and boot from a Direct Attached Storage Device (DASD) or a Fibre Channel Protocol (FCP)-attached SCSI device prepared with the **zipl** boot loader, kernel, and **initrd**. For more information, see [Using a Prepared DASD](#).
5. When the rescue kernel and **initrd** get booted, it starts the ReaR rescue environment. Proceed with system recovery.

Additional resources

- [Installing under z/VM](#)
- [Using a Prepared DASD](#)

1.3. REAR EXCLUSIONS

The ReaR utility recreates the storage layout of the original system, where the rescue image has been produced, on the disks of the recovered system according to the description in the **/var/lib/rear/layout/disklayout.conf** layout file during the recovery process. The storage layout includes partitions, volume groups, logical volumes, file systems, and other storage components.

ReaR creates the layout file when creating the rescue image and embeds this file in the image. You can also create the layout file by using the **rear savelayout** command. This allows you to quickly create the layout file and examine it, without creating the entire rescue image.

The layout file describes the entire storage layout of the original system with certain exceptions, as ReaR excludes some storage components from the layout file and from being recreated during recovery. The exclusion of storage components from layout is controlled by the following configuration variables:

- **AUTOEXCLUDE_DISKS**

- **AUTOEXCLUDE_MULTIPATH**
- **AUTOEXCLUDE_PATH**
- **EXCLUDE_RECREATE**

Excluding some file systems from the layout file by the configuration variables also excludes their content from the backup. You can also exclude files or a directory tree from the backup without excluding a file system from the layout file by using the **BACKUP_PROG_EXCLUDE** configuration variable.

When all files and directories in a file system are excluded in this way, the file system is recreated during recovery, but it will be empty, because the backup does not contain any data to restore into it. This is useful for file systems that contain temporary data and are not required to be preserved, or for data that is backed up by using methods independent of ReaR.

The **BACKUP_PROG_EXCLUDE** variable is an array of glob-style wildcard patterns that are passed to tar or rsync. Note that the patterns are required to be quoted in order to prevent their expansion by the shell when it reads the configuration file. The default value of this variable is set in the **/usr/share/rear/conf/default.conf** file. The default value contains, for example, the **/tmp/*** pattern that excludes all the files and directories under the **/tmp** directory, but not the **/tmp** directory itself.

If you need to exclude other files and directories, append further patterns with the **+** character to the variable instead of overriding it to preserve the default values. For example, to exclude all files and directories under the directory **/data/tmp** in addition to the default values, use:

```
BACKUP_PROG_EXCLUDE+=( '/data/tmp/*' )
```

You can view the default values for the configuration variables in the **/usr/share/rear/conf/default.conf** file and can change these values in the local **/etc/rear/local.conf** configuration file.

You can also configure which files are backed up by the internal **NETFS** and **RSYNC** backup methods. By default, files on all mounted local disk-based file systems are backed up by the **rear mkbackup** or **rear mkbackuponly** commands, if the file systems are included in the layout file.

The **rear mkbackup** command lists the backup exclude patterns in the log. You can find the log file in the **/var/log/rear** directory. This can be used to verify the excluded rules before performing a full system recovery. For example, the log can contain the following entries:

```
2025-04-29 10:17:41.312431050 Making backup (using backup method NETFS)
2025-04-29 10:17:41.314369109 Backup include list (backup-include.txt contents):
2025-04-29 10:17:41.316197323 /
2025-04-29 10:17:41.318052001 Backup exclude list (backup-exclude.txt contents):
2025-04-29 10:17:41.319857125 /tmp/*
2025-04-29 10:17:41.321644442 /dev/shm/*
2025-04-29 10:17:41.323436363 /var/lib/rear/output/*
```

In the previous output, the whole root file system is included in the backup, with the exception of all files and directories under the **/tmp**, **/dev/shm**, and **/var/lib/rear/output** directories.

Additional resources

- **Layout configuration** chapter in the ReaR user guide installed with the **rear** package at **/usr/share/doc/rear/relax-and-recover-user-guide.html**
- **glob(3)** man page on your system

CHAPTER 2. TROUBLESHOOTING PROBLEMS BY USING LOG FILES

You can use information from log files for troubleshooting and monitoring system functions. Log files contain messages about the system, including the kernel and the services and applications running on it. The logging system in Red Hat Enterprise Linux is based on the built-in **syslog** protocol. Various programs then use **syslog** to record events and organize them into log files.

2.1. SERVICES THAT HANDLE SYSLOG MESSAGES

The following services handle **syslog** messages:

The **systemd-journald** daemon

Collects messages from the following sources and forwards them to **Rsyslog** for further processing:

- Kernel
- Early stages of the boot process
- Standard and error output of daemons as they start up and run
- **syslog**

The **Rsyslog** service

Sorts **syslog** messages by type and priority and writes them to the files in the **/var/log** directory. The **/var/log** directory persistently stores the log messages.

2.2. SUBDIRECTORIES THAT STORE SYSLOG MESSAGES

The following subdirectories under the **/var/log** directory store **syslog** messages:

/var/log/messages

all **syslog** messages except the following

/var/log/secure

security and authentication-related messages and errors

/var/log/maillog

mail server-related messages and errors

/var/log/cron

log files related to periodically executed tasks

/var/log/boot.log

log files related to system startup

2.3. COMMANDS FOR VIEWING LOGS

You can view and manage log files by using the Journal, which is a component of **systemd**. It addresses problems connected with traditional logging, is closely integrated with the rest of the system, and supports various logging technologies and access management for the log files.

You can use the **journalctl** command to view messages in the system journal, for example:

```
$ journalctl -b | grep kvm
```

```
May 15 11:31:41 localhost.localdomain kernel: kvm-clock: Using msrs 4b564d01 and 4b564d00
```

```
May 15 11:31:41 localhost.localdomain kernel: kvm-clock: cpu 0, msr 76401001, primary cpu clock
```

Viewing system information

journalctl

Shows all collected journal entries.

journalctl FILEPATH

Shows logs related to a specific file. For example, the **journalctl /dev/sda** command displays logs related to the **/dev/sda** file system.

journalctl -b

Shows logs for the current boot.

journalctl -k -b -1

Shows kernel logs for the current boot.

Viewing information about specific services

journalctl -b _SYSTEMD_UNIT=<name.service>

Filters log to show entries matching the **systemd** service.

journalctl -b _SYSTEMD_UNIT=<name.service> _PID=<number>

Combines matches. For example, this command shows logs for **systemd-units** that match **<name.service>** and the PID **<number>**.

journalctl -b _SYSTEMD_UNIT=<name.service> _PID=<number> + _SYSTEMD_UNIT=<name2.service>

The plus sign (+) separator combines two expressions in a logical OR. For example, this command shows all messages from the **<name.service>** service process with the **PID** plus all messages from the **<name2.service>** service (from any of its processes).

journalctl -b _SYSTEMD_UNIT=<name.service> _SYSTEMD_UNIT=<name2.service>

This command shows all entries matching either expression, referring to the same field. Here, this command shows logs matching a systemd-unit **<name.service>** or a systemd-unit **<name2.service>**.

Viewing logs related to specific boots

journalctl --list-boots

Shows a tabular list of boot numbers, their IDs, and the timestamps of the first and last message pertaining to the boot. You can use the ID in the next command to view detailed information.

journalctl --boot=ID _SYSTEMD_UNIT=<name.service>

Shows information about the specified boot ID.

2.4. ADDITIONAL RESOURCES

- **journalctl(1)** man page on your system
- [Configuring a remote logging solution](#)

CHAPTER 3. REVIEWING AND FILTERING LOGS IN THE WEB CONSOLE

The Red Hat Enterprise Linux web console provides a graphical interface for accessing, reviewing, and filtering logs. You can use the most common functions without memorizing the corresponding commands and options.

3.1. REVIEWING LOGS IN THE WEB CONSOLE


The RHEL 10 web console Logs section is a UI for the **journalctl** utility. You can access system logs in the web console interface.

Prerequisites


- You have installed the RHEL 10 web console.
For instructions, see [Installing and enabling the web console](#).

Procedure

- Log in to the RHEL 10 web console.
For details, see [Logging in to the web console](#).
- Click **Logs**.



- Open log entry details by clicking on your selected log entry in the list.



NOTE

You can use the **Pause** button to pause new log entries from appearing. Once you resume new log entries, the web console will load all log entries that were reported after you used the **Pause** button.

You can filter the logs by time, priority or identifier. For more information, see [Filtering logs in the web console](#).

3.2. FILTERING LOGS IN THE WEB CONSOLE


You can filter log entries in the web console.

Prerequisites


- You have installed the RHEL 10 web console.
For instructions, see [Installing and enabling the web console](#).

Procedure


- Log in to the RHEL 10 web console.
For details, see [Logging in to the web console](#).
- Click **Logs**.
- By default, web console shows the latest log entries. To filter by a specific time range, click the **Time** drop-down menu and choose a preferred option.



- Error and above** severity logs list is shown by default. To filter by different priority, click the **Error and above** drop-down menu and choose a preferred priority.



- By default, web console shows logs for all identifiers. To filter logs for a particular identifier, click the **All** drop-down menu and select an identifier.



6. To open a log entry, click on a selected log.

3.3. TEXT SEARCH OPTIONS FOR FILTERING LOGS IN THE WEB CONSOLE

The text search option functionality provides a big variety of options for filtering logs. If you decide to filter logs by using the text search, you can use the predefined options that are defined in the three drop-down menus, or you can type the whole search yourself.

Drop-down menus

There are three drop-down menus that you can use to specify the main parameters of your search:

- **Time:** This drop-down menu contains predefined searches for different time ranges of your search.
- **Priority:** This drop-down menu provides options for different priority levels. It corresponds to the **journalctl --priority** option. The default priority value is **Error and above**. It is set every time you do not specify any other priority.
- **Identifier:** In this drop-down menu, you can select an identifier that you want to filter. Corresponds to the **journalctl --identifier** option.

Quantifiers

There are six quantifiers that you can use to specify your search. They are covered in the Options for filtering logs table.

Log fields

If you want to search for a specific log field, it is possible to specify the field together with its content.

Free-form text search in logs messages


You can filter any text string of your choice in the logs messages. The string can also be in the form of a regular expressions.

Advanced logs filtering I

Filter all log messages identified by 'systemd' that happened since October 22, 2020 midnight and journal field 'JOB_TYPE' is either 'start' or 'restart'.

1. Type **identifier:systemd since:2020-10-22 JOB_TYPE=start,restart** to search field.


2. Check the results.



Advanced logs filtering II

Filter all log messages that come from 'cockpit.service' systemd unit that happened in the boot before last and the message body contains either "error" or "fail".

1. Type **service:cockpit boot:-1 error|fail** to the search field.
2. Check the results.



3.4. USING A TEXT SEARCH BOX TO FILTER LOGS IN THE WEB CONSOLE

You can filter logs according to different parameters by using the text search box in the web console. The search combines usage of the filtering drop-down menus, quantifiers, log fields, and free-form string search.

Prerequisites

- You have installed the RHEL 10 web console.
For instructions, see [Installing and enabling the web console](#).

Procedure

1. Log in to the RHEL 10 web console.
For details, see [Logging in to the web console](#).
2. Click **Logs**.
3. Use the drop-down menus to specify the three main quantifiers – time range, priority, and identifier(s) – you want to filter.
The **Priority** quantifier always has to have a value. If you do not specify it, it automatically filters the **Error and above** priority. Notice that the options you set reflect in the text search box.
4. Specify the log field you want to filter.

You can add several log fields.

5. You can use a free-form string to search for anything else. The search box also accepts regular expressions.

3.5. OPTIONS FOR LOGS FILTERING

You can use **journalctl** options for filtering logs in the web console. Some of these options are provided as parts of the drop-down menus in the web console interface.

Table 3.1. Table

Option name	Usage	Notes
priority	Filter output by message priorities. Takes a single numeric or textual log level. The log levels are the usual syslog log levels. If a single log level is specified, all messages with this log level or a lower (therefore more important) log level are shown.	Covered in the Priority drop-down menu.
identifier	Show messages for the specified syslog identifier <code>SYSLOG_IDENTIFIER</code> . Can be specified multiple times.	Covered in the Identifier drop-down menu.
follow	Shows only the most recent journal entries, and continuously prints new entries as they are appended to the journal.	Not covered in a drop-down.
service	Show messages for the specified systemd unit. Can be specified multiple times.	Is not covered in a drop-down. Corresponds to the journalctl --unit parameter.
boot	Show messages from a specific boot. A positive integer looks up the boots starting from the beginning of the journal, and an equal-or-less-than zero integer looks up boots starting from the end of the journal. Therefore, 1 means the first boot found in the journal in chronological order, 2 the second and so on; while -0 is the last boot, -1 the boot before last, and so on.	Covered only as Current boot or Previous boot in the Time drop-down menu. Other options need to be written manually.

Option name	Usage	Notes
since	<p>Start showing entries on or newer than the specified date, or on or older than the specified date, respectively. Date specifications should be of the format "2012-10-30 18:17:16". If the time part is omitted, "00:00:00" is assumed. If only the seconds component is omitted, ":00" is assumed. If the date component is omitted, the current day is assumed. Alternatively the strings "yesterday", "today", "tomorrow" are understood, which refer to 00:00:00 of the day before the current day, the current day, or the day after the current day, respectively. "now" refers to the current time. Finally, relative times may be specified, prefixed with "-" or "+", referring to times before or after the current time, respectively.</p>	Not covered in a drop-down.

CHAPTER 4. CONFIGURING THE `SYSTEMD` JOURNAL BY USING RHEL SYSTEM ROLES

With the **journal** RHEL system role you can automate the **systemd** journal, and configure persistent logging by using the Red Hat Ansible Automation Platform.

4.1. CONFIGURING PERSISTENT LOGGING BY USING THE `JOURNALD` RHEL SYSTEM ROLE

By default, the **systemd** journal stores logs only in a small ring buffer in `/run/log/journal`, which is not persistent. Rebooting the system also removes journal database logs. You can configure persistent logging consistently on multiple systems by using the **journal** RHEL system role.

Prerequisites

- You have prepared the control node and the managed nodes
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Configure journald
  hosts: managed-node-01.example.com
  tasks:
    - name: Configure persistent logging
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.journald
      vars:
        journald_persistent: true
        journald_max_disk_size: <size>
        journald_per_user: true
        journald_sync_interval: <interval>
```

The settings specified in the example playbook include the following:

journald_persistent: true

Enables persistent logging.

journald_max_disk_size: <size>

Specifies the maximum size of disk space for journal files in MB, for example, **2048**.

journald_per_user: true

Configures **journal** to keep log data separate for each user.

journald_sync_interval: <interval>

Sets the synchronization interval in minutes, for example, **1**.

For details about all variables used in the playbook, see the `/usr/share/ansible/roles/rhel-system-roles.journald/README.md` file on the control node.

2. Validate the playbook syntax:

```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```

Additional resources

- `/usr/share/ansible/roles/rhel-system-roles.journald/README.md` file
- `/usr/share/doc/rhel-system-roles/journald/` directory

CHAPTER 5. CONFIGURING A REMOTE LOGGING SOLUTION

To ensure that logs from various machines in your environment are recorded centrally on a logging server, you can configure the **Rsyslog** application to record logs that fit specific criteria from the client system to the server.

5.1. THE RSYSLOG LOGGING SERVICE

The Rsyslog application, in combination with the **systemd-journald** service, provides local and remote logging support in Red Hat Enterprise Linux. The **rsyslogd** daemon continuously reads **syslog** messages received by the **systemd-journald** service from the Journal. **rsyslogd** then filters and processes these **syslog** events and records them to **rsyslog** log files or forwards them to other services according to its configuration.

The **rsyslogd** daemon also provides extended filtering, encryption protected relaying of messages, input and output modules, and support for transportation using the TCP and UDP protocols.

In **/etc/rsyslog.conf**, which is the main configuration file for **rsyslog**, you can specify the rules according to which **rsyslogd** handles the messages. Generally, you can classify messages by their source and topic (facility) and urgency (priority), and then assign an action that should be performed when a message fits these criteria.

In **/etc/rsyslog.conf**, you can also see a list of log files maintained by **rsyslogd**. Most log files are located in the **/var/log/** directory. Some applications, such as **httpd** and **samba**, store their log files in a subdirectory within **/var/log/**.

Additional resources

- **rsyslogd(8)** and **rsyslog.conf(5)** man pages on your system
- Documentation installed with the **rsyslog-doc** package in the **/usr/share/doc/rsyslog/html/index.html** file

5.2. INSTALLING RSYSLOG DOCUMENTATION

The Rsyslog application has extensive online documentation that is available at <https://www.rsyslog.com/doc/>, but you can also install the **rsyslog-doc** documentation package locally.

Prerequisites

- You have activated the **AppStream** repository on your system.
- You are authorized to install new packages using **sudo**.

Procedure

- Install the **rsyslog-doc** package:

```
# dnf install rsyslog-doc
```

Verification

- Open the **/usr/share/doc/rsyslog/html/index.html** file in a browser of your choice, for example:

■

```
$ firefox /usr/share/doc/rsyslog/html/index.html &
```

5.3. CONFIGURING A SERVER FOR REMOTE LOGGING OVER TCP

The Rsyslog application enables you to both run a logging server and configure individual systems to send their log files to the logging server. To use remote logging through TCP, configure both the server and the client. The server collects and analyzes the logs sent by one or more client systems.

With the Rsyslog application, you can maintain a centralized logging system where log messages are forwarded to a server over the network. To avoid message loss when the server is not available, you can configure an action queue for the forwarding action. This way, messages that failed to be sent are stored locally until the server is reachable again. Note that such queues cannot be configured for connections that use the UDP protocol.

The **omfwd** plug-in provides forwarding over UDP or TCP. The default protocol is UDP. Because the plug-in is built in, it does not have to be loaded.

By default, **rsyslog** uses TCP on port **514**.

Prerequisites

- Rsyslog is installed on the server system.
- You are logged in as **root** on the server.
- The **policyscoreutils-python-utils** package is installed for the optional step using the **semanage** command.
- The **firewalld** service is running.

Procedure

1. Optional: To use a different port for **rsyslog** traffic, add the **syslogd_port_t** SELinux type to port. For example, enable port **30514**:

```
# semanage port -a -t syslogd_port_t -p tcp 30514
```

2. Optional: To use a different port for **rsyslog** traffic, configure **firewalld** to allow incoming **rsyslog** traffic on that port. For example, allow TCP traffic on port **30514**:

```
# firewall-cmd --zone=<zone-name> --permanent --add-port=30514/tcp
success
# firewall-cmd --reload
```

3. Create a new file in the **/etc/rsyslog.d/** directory named, for example, **remotelog.conf**, and insert the following content:

```
# Define templates before the rules that use them
# Per-Host templates for remote systems
template(name="TmplAuthpriv" type="list") {
    constant(value="/var/log/remote/auth/")
    property(name="hostname")
    constant(value="")
    property(name="programname" SecurePath="replace")
}
```



```

    constant(value=".log")
  }

  template(name="TplMsg" type="list") {
    constant(value="/var/log/remote/msg/")
    property(name="hostname")
    constant(value="/")
    property(name="programname" SecurePath="replace")
    constant(value=".log")
  }

  # Provides TCP syslog reception
  module(load="imtcp")

  # Adding this ruleset to process remote messages
  ruleset(name="remote1"){
    authpriv.* action(type="omfile" DynaFile="TplAuthpriv")
    *.info;mail.none;authpriv.none;cron.none
    action(type="omfile" DynaFile="TplMsg")
  }

  input(type="imtcp" port="30514" ruleset="remote1")

```

4. Save the changes to the **/etc/rsyslog.d/remotelog.conf** file.

5. Test the syntax of the **/etc/rsyslog.conf** file:

```

# rsyslogd -N 1
rsyslogd: version 8.1911.0-2.el8, config validation run...
rsyslogd: End of config validation run. Bye.

```

6. Make sure the **rsyslog** service is running and enabled on the logging server:

```
# systemctl status rsyslog
```

7. Restart the **rsyslog** service.

```
# systemctl restart rsyslog
```

8. Optional: If **rsyslog** is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

Your log server is now configured to receive and store log files from the other systems in your environment.

Additional resources

- **rsyslogd(8)**, **rsyslog.conf(5)**, **semanage(8)**, and **firewall-cmd(1)** man pages on your system
- Documentation installed with the **rsyslog-doc** package in the **/usr/share/doc/rsyslog/html/index.html** file

5.4. CONFIGURING REMOTE LOGGING TO A SERVER OVER TCP

You can configure a system for forwarding log messages to a server over the TCP protocol. The **omfwd** plug-in provides forwarding over UDP or TCP. The default protocol is UDP. Because the plug-in is built in, you do not have to load it.

Prerequisites

- The **rsyslog** package is installed on the client systems that should report to the server.
- You have configured the server for remote logging.
- The specified port is permitted in SELinux and open in firewall.
- The system contains the **polycoreutils-python-utils** package, which provides the **semanage** command for adding a non-standard port to the SELinux configuration.

Procedure

1. Create a new file in the **/etc/rsyslog.d/** directory named, for example, **10-remotelog.conf**, and insert the following content:

```
*.* action(type="omfwd"
        queue.type="linkedlist"
        queue.filename="example_fwd"
        action.resumeRetryCount="-1"
        queue.saveOnShutdown="on"
        target="example.com" port="30514" protocol="tcp"
    )
```

Where:

- The **queue.type="linkedlist"** setting enables a LinkedList in-memory queue,
- The **queue.filename** setting defines a disk storage. The backup files are created with the **example_fwd** prefix in the working directory specified by the preceding global **workDirectory** directive.
- The **action.resumeRetryCount -1** setting prevents **rsyslog** from dropping messages when retrying to connect if server is not responding,
- The **queue.saveOnShutdown="on"** setting saves in-memory data if **rsyslog** shuts down.
- The last line forwards all received messages to the logging server. Port specification is optional.

With this configuration, **rsyslog** sends messages to the server but keeps messages in memory if the remote server is not reachable. A file on disk is created only if **rsyslog** runs out of the configured memory queue space or needs to shut down, which benefits the system performance.



NOTE

Rsyslog processes configuration files **/etc/rsyslog.d/** in the lexical order.

2. Restart the **rsyslog** service.

```
# systemctl restart rsyslog
```

Verification

To verify that the client system sends messages to the server:

1. On the client system, send a test message:

```
# logger test
```

2. On the server system, view the `/var/log/messages` log, for example:

```
# cat /var/log/remote/msg/hostname/root.log
Feb 25 03:53:17 hostname root[6064]: test
```

Where *hostname* is the host name of the client system. Note that the log contains the user name of the user that entered the **logger** command, in this case **root**.

Additional resources


- **rsyslogd(8)** and **rsyslog.conf(5)** man pages on your system
- Documentation installed with the **rsyslog-doc** package in the `/usr/share/doc/rsyslog/html/index.html` file

5.5. CONFIGURING TLS-ENCRYPTED REMOTE LOGGING

By default, Rsyslog sends remote-logging communication in the plain text format. If your scenario requires to secure this communication channel, you can encrypt it by using TLS.

To use encrypted transport through TLS, configure both the server and the client. The server collects and analyzes the logs sent by one or more client systems.

You can use either the **ossli** network stream driver (OpenSSL) or the **gtls** stream driver (GnuTLS).



NOTE

If you have a separate system with higher security, for example, a system that is not connected to any network or has stricter authorizations, use the separate system as the certifying authority (CA).

You can customize your connection settings with stream drivers on the server side on the **global**, **module**, and **input** levels, and on the client side on the **global** and **action** levels. The more specific configuration overrides the more general configuration. This means, for example, that you can use **ossli** in global settings for most connections and **gtls** on the input and action settings only for specific connections.

Prerequisites

- You have **root** access to both the client and server systems.
- The following packages are installed on the server and the client systems:
 - The **rsyslog** package.

- For the **ossl** network stream driver, the **rsyslog-openssl** package.
- For the **gtls** network stream driver, the **rsyslog-gnutls** package.
- For generating certificates by using the **certtool** command, the **gnutls-utils** package.
- On your logging server, the following certificates are in the **/etc/pki/ca-trust/source/anchors/** directory and your system configuration is updated by using the **update-ca-trust** command:
 - **ca-cert.pem** - a CA certificate that can verify keys and certificates on logging servers and clients.
 - **server-cert.pem** - a public key of the logging server.
 - **server-key.pem** - a private key of the logging server.
- On your logging clients, the following certificates are in the **/etc/pki/ca-trust/source/anchors/** directory and your system configuration is updated by using **update-ca-trust**:
 - **ca-cert.pem** - a CA certificate that can verify keys and certificates on logging servers and clients.
 - **client-cert.pem** - a public key of a client.
 - **client-key.pem** - a private key of a client.
 - If the server runs RHEL 9.2 or later and FIPS mode is enabled, clients must either support the Extended Master Secret (EMS) extension or use TLS 1.3. TLS 1.2 connections without EMS fail. For more information, see the [TLS extension "Extended Master Secret" enforced](#) article (Red Hat Knowledgebase).

Procedure

1. Configure the server for receiving encrypted logs from your client systems:
 - a. Create a new file in the **/etc/rsyslog.d/** directory named, for example, **securelogser.conf**.
 - b. To encrypt the communication, the configuration file must contain paths to certificate files on your server, a selected authentication method, and a stream driver that supports TLS encryption. Add the following lines to the **/etc/rsyslog.d/securelogser.conf** file:

```
# Set certificate files
global(
    DefaultNetstreamDriverCAFile="/etc/pki/ca-trust/source/anchors/ca-cert.pem"
    DefaultNetstreamDriverCertFile="/etc/pki/ca-trust/source/anchors/server-cert.pem"
    DefaultNetstreamDriverKeyFile="/etc/pki/ca-trust/source/anchors/server-key.pem"
)

# TCP listener
module(
    load="imtcp"
    PermittedPeer=["client1.example.com", "client2.example.com"]
    StreamDriver.AuthMode="x509/name"
    StreamDriver.Mode="1"
    StreamDriver.Name="ossl"
)
```

```
# Start up listener at port 514
input(
    type="imtcp"
    port="514"
)
```



NOTE

If you prefer the GnuTLS driver, use the **StreamDriver.Name="gtls"** configuration option. See the documentation installed with the **rsyslog-doc** package for more information about less strict authentication modes than **x509/name**.

- c. Optional: To customize the connection configuration, replace the **input** section with the following:

```
input(
    type="imtcp"
    Port="50515"
    StreamDriver.Name="<driver>"
    streamdriver.CAFile="/etc/rsyslog.d/<ca1>.pem"
    streamdriver.CertFile="/etc/rsyslog.d/<server1-cert>.pem"
    streamdriver.KeyFile="/etc/rsyslog.d/<server1-key>.pem"
)
```

- Replace **<driver>** with **ossl** or **gtls** depending on the driver you want to use.
- Replace **<ca1>** with the CA certificate, **<server1-cert>** with the certificate, and **<server1-key>** with the key of the customized connection.

- d. Save the changes to the **/etc/rsyslog.d/securelogser.conf** file.

- e. Verify the syntax of the **/etc/rsyslog.conf** file and any files in the **/etc/rsyslog.d/** directory:

```
# rsyslogd -N 1
rsyslogd: version 8.1911.0-2.el8, config validation run (level 1)...
rsyslogd: End of config validation run. Bye.
```

- f. Make sure the **rsyslog** service is running and enabled on the logging server:

```
# systemctl status rsyslog
```

- g. Restart the **rsyslog** service:

```
# systemctl restart rsyslog
```

- h. Optional: If Rsyslog is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

2. Configure clients for sending encrypted logs to the server:

- a. On a client system, create a new file in the **/etc/rsyslog.d/** directory named, for example,

securelogcli.conf.

- b. Add the following lines to the **/etc/rsyslog.d/securelogcli.conf** file:

```
# Set certificate files
global(
    DefaultNetstreamDriverCAFile="/etc/pki/ca-trust/source/anchors/ca-cert.pem"
    DefaultNetstreamDriverCertFile="/etc/pki/ca-trust/source/anchors/client-cert.pem"
    DefaultNetstreamDriverKeyFile="/etc/pki/ca-trust/source/anchors/client-key.pem"
)

# Set up the action for all messages
*. * action(
    type="omfwd"
    StreamDriver="ossll"
    StreamDriverMode="1"
    StreamDriverPermittedPeers="server.example.com"
    StreamDriverAuthMode="x509/name"
    target="server.example.com" port="514" protocol="tcp"
)
```

**NOTE**

If you prefer the GnuTLS driver, use the **StreamDriver.Name="gtls"** configuration option.

- c. Optional: To customize the connection configuration, replace the **action** section with the following:

```
local1.* action(
    type="omfwd"
    StreamDriver="<driver>"
    StreamDriverMode="1"
    StreamDriverAuthMode="x509/certvalid"
    streamDriver.CAFile="/etc/rsyslog.d/<ca1>.pem"
    streamDriver.CertFile="/etc/rsyslog.d/<client1-cert>.pem"
    streamDriver.KeyFile="/etc/rsyslog.d/<client1-key>.pem"
    target="server.example.com" port="514" protocol="tcp"
)
```

- Replace **<driver>** with **ossll** or **gtls** depending on the driver you want to use.
- Replace **<ca1>** with the CA certificate, **<client1-cert>** with the certificate, and **<client1-key>** with the key of the customized connection.

- d. Save the changes to the **/etc/rsyslog.d/securelogcli.conf** file.
- e. Verify the syntax of the **/etc/rsyslog.conf** file and other files in the **/etc/rsyslog.d/** directory:

```
# rsyslogd -N 1
rsyslogd: version 8.1911.0-2.el8, config validation run (level 1)...
rsyslogd: End of config validation run. Bye.
```

- f. Make sure the **rsyslog** service is running and enabled on the logging server:

```
# systemctl status rsyslog
```

- g. Restart the **rsyslog** service:

```
# systemctl restart rsyslog
```

- h. Optional: If Rsyslog is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

Verification

To verify that the client system sends messages to the server, follow these steps:

1. On the client system, send a test message:

```
# logger test
```

2. On the server system, view the **/var/log/messages** log, for example:

```
# cat /var/log/remote/msg/<hostname>/root.log
Feb 25 03:53:17 <hostname> root[6064]: test
```

Where **<hostname>** is the hostname of the client system. Note that the log contains the user name of the user that entered the logger command, in this case **root**.

Additional resources

- **certtool(1)**, **openssl(1)**, **update-ca-trust(8)**, **rsyslogd(8)**, and **rsyslog.conf(5)** man pages on your system
- Documentation installed with the **rsyslog-doc** package at **/usr/share/doc/rsyslog/html/index.html**
- [Using the logging system role with TLS](#)

5.6. CONFIGURING A SERVER FOR RECEIVING REMOTE LOGGING INFORMATION OVER UDP

The **Rsyslog** application enables you to configure a system to receive logging information from remote systems. To use remote logging through UDP, configure both the server and the client. The receiving server collects and analyzes the logs sent by one or more client systems. By default, **rsyslog** uses UDP on port **514** to receive log information from remote systems.

Follow this procedure to configure a server for collecting and analyzing logs sent by one or more client systems over the UDP protocol.

Prerequisites

- Rsyslog is installed on the server system.

- You are logged in as **root** on the server.
- The **policycoreutils-python-utils** package is installed for the optional step that uses the **semanage** command.
- The **firewalld** service is running.

Procedure

1. Optional: To use a different port for **rsyslog** traffic than the default port **514**:

- a. Add the **syslogd_port_t** SELinux type to the SELinux policy configuration, replacing **portno** with the port number you want **rsyslog** to use:

```
# semanage port -a -t syslogd_port_t -p udp portno
```

- b. Configure **firewalld** to allow incoming **rsyslog** traffic, replacing **portno** with the port number and **zone** with the zone you want **rsyslog** to use:

```
# firewall-cmd --zone=zone --permanent --add-port=portno/udp
success
# firewall-cmd --reload
```

- c. Reload the firewall rules:

```
# firewall-cmd --reload
```

2. Create a new **.conf** file in the **/etc/rsyslog.d/** directory, for example, **remotelogserv.conf**, and insert the following content:

```
# Define templates before the rules that use them
# Per-Host templates for remote systems
template(name="TmplAuthpriv" type="list") {
    constant(value="/var/log/remote/auth/")
    property(name="hostname")
    constant(value="/")
    property(name="programname" SecurePath="replace")
    constant(value=".log")
}

template(name="TmplMsg" type="list") {
    constant(value="/var/log/remote/msg/")
    property(name="hostname")
    constant(value="/")
    property(name="programname" SecurePath="replace")
    constant(value=".log")
}

# Provides UDP syslog reception
module(load="imudp")

# This ruleset processes remote messages
ruleset(name="remote1"){
    authpriv.*  action(type="omfile" DynaFile="TmplAuthpriv")
    *.info;mail.none;authpriv.none;cron.none
```



```

    action(type="omfile" DynaFile="TplMsg")
  }

  input(type="imudp" port="514" ruleset="remote1")

```

Where **514** is the port number **rsyslog** uses by default. You can specify a different port instead.

3. Verify the syntax of the **/etc/rsyslog.conf** file and all **.conf** files in the **/etc/rsyslog.d/** directory:

```

# rsyslogd -N 1
rsyslogd: version 8.1911.0-2.el8, config validation run...

```

4. Restart the **rsyslog** service.

```
# systemctl restart rsyslog
```

5. Optional: If **rsyslog** is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

Additional resources

- **rsyslogd(8)**, **rsyslog.conf(5)**, **semanage(8)**, and **firewall-cmd(1)** man pages on your system
- Documentation installed with the **rsyslog-doc** package in the **/usr/share/doc/rsyslog/html/index.html** file

5.7. CONFIGURING REMOTE LOGGING TO A SERVER OVER UDP

You can configure a system for forwarding log messages to a server over the UDP protocol. The **omfwd** plug-in provides forwarding over UDP or TCP. The default protocol is UDP. Because the plug-in is built in, you do not have to load it.

Prerequisites

- The **rsyslog** package is installed on the client systems that should report to the server.
- You have configured the server for remote logging as described in [Configuring a server for receiving remote logging information over UDP](#).

Procedure

1. Create a new **.conf** file in the **/etc/rsyslog.d/** directory, for example, **10-remotelogcli.conf**, and insert the following content:

```

*. * action(type="omfwd"
    queue.type="linkedlist"
    queue.filename="example_fwd"
    action.resumeRetryCount="-1"
    queue.saveOnShutdown="on"
    target="example.com" port="portno" protocol="udp"
)

```

Where:

- The **queue.type="linkedlist"** setting enables a LinkedList in-memory queue.
- The **queue.filename** setting defines a disk storage. The backup files are created with the **example_fwd** prefix in the working directory specified by the preceding global **workDirectory** directive.
- The **action.resumeRetryCount -1** setting prevents **rsyslog** from dropping messages when retrying to connect if the server is not responding.
- The **enabled queue.saveOnShutdown="on"** setting saves in-memory data if **rsyslog** shuts down.
- The **portno** value is the port number you want **rsyslog** to use. The default value is **514**.
- The last line forwards all received messages to the logging server, port specification is optional.
With this configuration, **rsyslog** sends messages to the server but keeps messages in memory if the remote server is not reachable. A file on disk is created only if **rsyslog** runs out of the configured memory queue space or needs to shut down, which benefits the system performance.



NOTE

Rsyslog processes configuration files **/etc/rsyslog.d/** in the lexical order.

2. Restart the **rsyslog** service.

```
# systemctl restart rsyslog
```

3. Optional: If **rsyslog** is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

Verification

To verify that the client system sends messages to the server, follow these steps:

1. On the client system, send a test message:

```
# logger test
```

2. On the server system, view the **/var/log/remote/msg/hostname/root.log** log, for example:

```
# cat /var/log/remote/msg/hostname/root.log
Feb 25 03:53:17 hostname root[6064]: test
```

Where **hostname** is the host name of the client system. Note that the log contains the user name of the user that entered the logger command, in this case **root**.

Additional resources

- **rsyslogd(8)** and **rsyslog.conf(5)** man pages.

- Documentation installed with the **rsyslog-doc** package at `/usr/share/doc/rsyslog/html/index.html`.

5.8. LOAD BALANCING HELPER IN RSYSLOG

When used in a cluster, you can improve Rsyslog load balancing by modifying the **RebindInterval** setting.

RebindInterval specifies an interval at which the current connection is broken and is re-established. This setting applies to TCP, UDP, and RELP traffic. The load balancers perceive it as a new connection and forward the messages to another physical target system.

RebindInterval is helpful in scenarios when a target system has changed its IP address. The Rsyslog application caches the IP address when the connection is established, therefore, the messages are sent to the same server. If the IP address changes, the UDP packets are lost until the Rsyslog service restarts. Re-establishing the connection ensures the IP is resolved by DNS again.

Example usage of RebindInterval for TCP, UDP, and RELP traffic

```
action(type="omfwd" protocol="tcp" RebindInterval="250" target="example.com" port="514" ...)
action(type="omfwd" protocol="udp" RebindInterval="250" target="example.com" port="514" ...)
action(type="omrelp" RebindInterval="250" target="example.com" port="6514" ...)
```

5.9. CONFIGURING RELIABLE REMOTE LOGGING

With the Reliable Event Logging Protocol (RELP), you can send and receive **syslog** messages over TCP with a much reduced risk of message loss. RELP provides reliable delivery of event messages, which makes it useful in environments where message loss is not acceptable. To use RELP, configure the **imrelp** input module, which runs on the server and receives the logs, and the **omrelp** output module, which runs on the client and sends logs to the logging server.

Prerequisites

- You have installed the **rsyslog**, **librelp**, and **rsyslog-relp** packages on the server and the client systems.
- The specified port is permitted in SELinux and open in the firewall.

Procedure

1. Configure the client system for reliable remote logging:
 - a. On the client system, create a new **.conf** file in the `/etc/rsyslog.d/` directory named, for example, **relpclient.conf**, and insert the following content:

```
module(load="omrelp")
*.* action(type="omrelp" target="_target_IP_" port="_target_port_")
```

Where:

- **target_IP** is the IP address of the logging server.

- **target_port** is the port of the logging server.
- b. Save the changes to the **/etc/rsyslog.d/relpclient.conf** file.
 - c. Restart the **rsyslog** service.

```
# systemctl restart rsyslog
```

- d. Optional: If **rsyslog** is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

2. Configure the server system for reliable remote logging:

- a. On the server system, create a new **.conf** file in the **/etc/rsyslog.d/** directory named, for example, **relpserv.conf**, and insert the following content:

```
ruleset(name="relp"){  
    *.* action(type="omfile" file="_log_path_")  
}  
  
module(load="imrelp")  
input(type="imrelp" port="_target_port_" ruleset="relp")
```

Where:

- **log_path** specifies the path for storing messages.
 - **target_port** is the port of the logging server. Use the same value as in the client configuration file.
- b. Save the changes to the **/etc/rsyslog.d/relpserv.conf** file.
 - c. Restart the **rsyslog** service.

```
# systemctl restart rsyslog
```

- d. Optional: If **rsyslog** is not enabled, ensure the **rsyslog** service starts automatically after reboot:

```
# systemctl enable rsyslog
```

Verification

To verify that the client system sends messages to the server:

1. On the client system, send a test message:

```
# logger test
```

2. On the server system, view the log at the specified **log_path**, for example:

```
# cat /var/log/remote/msg/hostname/root.log
Feb 25 03:53:17 hostname root[6064]: test
```

Where **hostname** is the host name of the client system. Note that the log contains the user name of the user that entered the logger command, in this case **root**.

Additional resources

- **rsyslogd(8)** and **rsyslog.conf(5)** man pages on your system
- Documentation installed with the **rsyslog-doc** package in the **/usr/share/doc/rsyslog/html/index.html** file

5.10. SUPPORTED RSYSLOG MODULES

To expand the functionality of the Rsyslog application, you can use specific modules. Modules provide additional inputs (Input Modules), outputs (Output Modules), and other functionalities. A module can also provide additional configuration directives that become available after you load the module.

You can list the input and output modules installed on your system by entering the following command:

```
# ls /usr/lib64/rsyslog/{i,o}m*
```

You can view the list of all available **rsyslog** modules in the **/usr/share/doc/rsyslog/html/configuration/modules/idx_output.html** file after you install the **rsyslog-doc** package.

5.11. CONFIGURING THE NETCONSOLE SERVICE TO LOG KERNEL MESSAGES TO A REMOTE HOST

When logging to disk or using a serial console is not possible, you can use the **netconsole** kernel module and the same-named service to log kernel messages over a network to a remote **rsyslog** service.

Prerequisites

- A system log service, such as **rsyslog** is installed on the remote host.
- The remote system log service is configured to receive incoming log entries from this host.

Procedure

1. Install the **netconsole-service** package:

```
# dnf install netconsole-service
```

2. Edit the **/etc/sysconfig/netconsole** file and set the **SYSLOGADDR** parameter to the IP address of the remote host:

```
# SYSLOGADDR=192.0.2.1
```

3. Enable and start the **netconsole** service:

```
# systemctl enable --now netconsole
```

Verification

- Display the **/var/log/messages** file on the remote system log server.

5.12. ADDITIONAL RESOURCES

- Documentation installed with the **rsyslog-doc** package in the **/usr/share/doc/rsyslog/html/index.html** file
- **rsyslog.conf(5)** and **rsyslogd(8)** man pages on your system
- [Configuring system logging without journald or with minimized journald usage](#) (Red Hat Knowledgebase)
- [Negative effects of the RHEL default logging setup on performance and their mitigations](#) (Red Hat Knowledgebase)

CHAPTER 6. CONFIGURING LOGGING BY USING RHEL SYSTEM ROLES

You can use the **logging** RHEL system role to configure your local and remote hosts as logging servers in an automated fashion to collect logs from many client systems.

Logging solutions provide multiple ways of reading logs and multiple logging outputs.

For example, a logging system can receive the following inputs:

- Local files
- **systemd/journal**
- Another logging system over the network

In addition, a logging system can have the following outputs:

- Logs stored in the local files in the **/var/log/** directory
- Logs sent to Elasticsearch engine
- Logs forwarded to another logging system

With the **logging** RHEL system role, you can combine the inputs and outputs to fit your scenario. For example, you can configure a logging solution that stores inputs from **journal** in a local file, whereas inputs read from files are both forwarded to another logging system and stored in the local log files.

6.1. FILTERING LOCAL LOG MESSAGES BY USING THE **LOGGING** RHEL SYSTEM ROLE

You can use the property-based filter of the **logging** RHEL system role to filter your local log messages based on various conditions. As a result, you can achieve for example:

- **Log clarity:** In a high-traffic environment, logs can grow rapidly. The focus on specific messages, like errors, can help to identify problems faster.
- **Optimized system performance:** Excessive amount of logs is usually connected with system performance degradation. Selective logging for only the important events can prevent resource depletion, which enables your systems to run more efficiently.
- **Enhanced security:** Efficient filtering through security messages, like system errors and failed logins, helps to capture only the relevant logs. This is important for detecting breaches and meeting compliance standards.

Prerequisites

- [You have prepared the control node and the managed nodes](#)
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Deploy the logging solution
  hosts: managed-node-01.example.com
  tasks:
    - name: Filter logs based on a specific value they contain
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
      vars:
        logging_inputs:
          - name: files_input
            type: basics
        logging_outputs:
          - name: files_output0
            type: files
            property: msg
            property_op: contains
            property_value: error
            path: /var/log/errors.log
          - name: files_output1
            type: files
            property: msg
            property_op: "!contains"
            property_value: error
            path: /var/log/others.log
        logging_flows:
          - name: flow0
            inputs: [files_input]
            outputs: [files_output0, files_output1]
```

The settings specified in the example playbook include the following:

logging_inputs

Defines a list of logging input dictionaries. The **type: basics** option covers inputs from **systemd** journal or Unix socket.

logging_outputs

Defines a list of logging output dictionaries. The **type: files** option supports storing logs in the local files, usually in the `/var/log/` directory. The **property: msg**; **property: contains**; and **property_value: error** options specify that all logs that contain the **error** string are stored in the `/var/log/errors.log` file. The **property: msg**; **property: !contains**; and **property_value: error** options specify that all other logs are put in the `/var/log/others.log` file. You can replace the **error** value with the string by which you want to filter.

logging_flows

Defines a list of logging flow dictionaries to specify relationships between **logging_inputs** and **logging_outputs**. The **inputs: [files_input]** option specifies a list of inputs, from which processing of logs starts. The **outputs: [files_output0, files_output1]** option specifies a list of outputs, to which the logs are sent.

For details about all variables used in the playbook, see the `/usr/share/ansible/roles/rhel-system-roles.logging/README.md` file on the control node.

2. Validate the playbook syntax:


```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```

Verification

1. On the managed node, test the syntax of the `/etc/rsyslog.conf` file:

```
# rsyslogd -N 1
rsyslogd: version 8.1911.0-6.el8, config validation run...
rsyslogd: End of config validation run. Bye.
```

2. On the managed node, verify that the system sends messages that contain the **error** string to the log:

- a. Send a test message:

```
# logger error
```

- b. View the `/var/log/errors.log` log, for example:

```
# cat /var/log/errors.log
Aug  5 13:48:31 hostname root[6778]: error
```

Where **hostname** is the host name of the client system. Note that the log contains the user name of the user that entered the logger command, in this case **root**.

Additional resources

- `/usr/share/ansible/roles/rhel-system-roles/logging/README.md` file
- `/usr/share/doc/rhel-system-roles/logging/` directory
- `rsyslog.conf(5)` and `syslog(3)` manual pages

6.2. APPLYING A REMOTE LOGGING SOLUTION BY USING THE LOGGING RHEL SYSTEM ROLE

You can use the **logging** RHEL system role to configure a remote logging solution, where one or more clients take logs from the **systemd-journal** service and forward them to a remote server. The server receives remote input from the **remote_rsyslog** and **remote_files** configurations, and outputs the logs to local files in directories named by remote host names.

As a result, you can cover use cases where you need for example:

- Centralized log management: Collecting, accessing, and managing log messages of multiple machines from a single storage point simplifies day-to-day monitoring and troubleshooting tasks. Also, this use case reduces the need to log into individual machines to check the log

messages.

- Enhanced security: Storing log messages in one central place increases chances they are in a secure and tamper-proof environment. Such an environment makes it easier to detect and respond to security incidents more effectively and to meet audit requirements.
- Improved efficiency in log analysis: Correlating log messages from multiple systems is important for fast troubleshooting of complex problems that span multiple machines or services. That way you can quickly analyze and cross-reference events from different sources.

Prerequisites

- [You have prepared the control node and the managed nodes](#)
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.
- Define the ports in the SELinux policy of the server or client system and open the firewall for those ports. The default SELinux policy includes ports 601, 514, 6514, 10514, and 20514. To use a different port, see [modify the SELinux policy on the client and server systems](#).

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Deploy the logging solution
  hosts: managed-node-01.example.com
  tasks:
    - name: Configure the server to receive remote input
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
      vars:
        logging_inputs:
          - name: remote_udp_input
            type: remote
            udp_ports: [ 601 ]
          - name: remote_tcp_input
            type: remote
            tcp_ports: [ 601 ]
        logging_outputs:
          - name: remote_files_output
            type: remote_files
        logging_flows:
          - name: flow_0
            inputs: [remote_udp_input, remote_tcp_input]
            outputs: [remote_files_output]

- name: Deploy the logging solution
  hosts: managed-node-02.example.com
  tasks:
    - name: Configure the server to output the logs to local files in directories named by
      remote host names
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
```

```

vars:
  logging_inputs:
    - name: basic_input
      type: basics
  logging_outputs:
    - name: forward_output0
      type: forwards
      severity: info
      target: <host1.example.com>
      udp_port: 601
    - name: forward_output1
      type: forwards
      facility: mail
      target: <host1.example.com>
      tcp_port: 601
  logging_flows:
    - name: flows0
      inputs: [basic_input]
      outputs: [forward_output0, forward_output1]

```

The settings specified in the first play of the example playbook include the following:

logging_inputs

Defines a list of logging input dictionaries. The **type: remote** option covers remote inputs from the other logging system over the network. The **udp_ports: [601]** option defines a list of UDP port numbers to monitor. The **tcp_ports: [601]** option defines a list of TCP port numbers to monitor. If both **udp_ports** and **tcp_ports** is set, **udp_ports** is used and **tcp_ports** is dropped.

logging_outputs

Defines a list of logging output dictionaries. The **type: remote_files** option makes output store logs to the local files per remote host and program name originated the logs.

logging_flows

Defines a list of logging flow dictionaries to specify relationships between **logging_inputs** and **logging_outputs**. The **inputs: [remote_udp_input, remote_tcp_input]** option specifies a list of inputs, from which processing of logs starts. The **outputs: [remote_files_output]** option specifies a list of outputs, to which the logs are sent.

The settings specified in the second play of the example playbook include the following:

logging_inputs

Defines a list of logging input dictionaries. The **type: basics** option covers inputs from **systemd** journal or Unix socket.

logging_outputs

Defines a list of logging output dictionaries. The **type: forwards** option supports sending logs to the remote logging server over the network. The **severity: info** option refers to log messages of the informative importance. The **facility: mail** option refers to the type of system program that is generating the log message. The **target: <host1.example.com>** option specifies the hostname of the remote logging server. The **udp_port: 601/tcp_port: 601** options define the UDP/TCP ports on which the remote logging server listens.

logging_flows

Defines a list of logging flow dictionaries to specify relationships between **logging_inputs** and **logging_outputs**. The **inputs: [basic_input]** option specifies a list of inputs, from which processing of logs starts. The **outputs: [forward_output0, forward_output1]** option

specifies a list of outputs, to which the logs are sent.

For details about all variables used in the playbook, see the **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file on the control node.

2. Validate the playbook syntax:

```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```

Verification

1. On both the client and the server system, test the syntax of the **/etc/rsyslog.conf** file:

```
# rsyslogd -N 1
rsyslogd: version 8.1911.0-6.el8, config validation run (level 1), master config
/etc/rsyslog.conf
rsyslogd: End of config validation run. Bye.
```

2. Verify that the client system sends messages to the server:

- a. On the client system, send a test message:

```
# logger test
```

- b. On the server system, view the **/var/log/<host2.example.com>/messages** log, for example:

```
# cat /var/log/<host2.example.com>/messages
Aug  5 13:48:31 <host2.example.com> root[6778]: test
```

Where **<host2.example.com>** is the host name of the client system. Note that the log contains the user name of the user that entered the logger command, in this case **root**.

Additional resources

- **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file
- **/usr/share/doc/rhel-system-roles/logging/** directory
- **rsyslog.conf(5)** and **syslog(3)** manual pages

6.3. USING THE LOGGING RHEL SYSTEM ROLE WITH TLS

Transport Layer Security (TLS) is a cryptographic protocol designed to allow secure communication over the computer network.

You can use the **logging** RHEL system role to configure a secure transfer of log messages, where one or more clients take logs from the **systemd-journal** service and transfer them to a remote server while using TLS.

Typically, TLS for transferring logs in a remote logging solution is used when sending sensitive data over less trusted or public networks, such as the Internet. Also, by using certificates in TLS you can ensure that the client is forwarding logs to the correct and trusted server. This prevents attacks like "man-in-the-middle".

6.3.1. Configuring client logging with TLS

You can use the **logging** RHEL system role to configure logging on RHEL clients and transfer logs to a remote logging system by using TLS encryption.

This procedure creates a private key and a certificate. Next, it configures TLS on all hosts in the clients group in the Ansible inventory. The TLS protocol encrypts the message transmission for secure transfer of logs over the network.



NOTE

You do not have to call the **certificate** RHEL system role in the playbook to create the certificate. The **logging** RHEL system role calls it automatically when the **logging_certificates** variable is set.

In order for the CA to be able to sign the created certificate, the managed nodes must be enrolled in an IdM domain.

Prerequisites

- [You have prepared the control node and the managed nodes](#)
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.
- The managed nodes are enrolled in an IdM domain.
- If the logging server you want to configure on the manage node runs RHEL 9.2 or later and the FIPS mode is enabled, clients must either support the Extended Master Secret (EMS) extension or use TLS 1.3. TLS 1.2 connections without EMS fail. For more information, see the Red Hat Knowledgebase solution [TLS extension "Extended Master Secret" enforced](#).

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Configure remote logging solution by using TLS for secure transfer of logs
  hosts: managed-node-01.example.com
  tasks:
    - name: Deploying files input and forwards output with certs
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
      vars:
        logging_certificates:
          - name: logging_cert
```

```

    dns: ['www.example.com']
    ca: ipa
    principal: "logging/{{ inventory_hostname }}@IDM.EXAMPLE.COM"
logging_pki_files:
  - ca_cert: /local/path/to/ca_cert.pem
    cert: /local/path/to/logging_cert.pem
    private_key: /local/path/to/logging_cert.pem
logging_inputs:
  - name: input_name
    type: files
    input_log_path: /var/log/containers/*.log
logging_outputs:
  - name: output_name
    type: forwards
    target: your_target_host
    tcp_port: 514
    tls: true
    pki_authmode: x509/name
    permitted_server: 'server.example.com'
logging_flows:
  - name: flow_name
    inputs: [input_name]
    outputs: [output_name]

```

The settings specified in the example playbook include the following:

logging_certificates

The value of this parameter is passed on to **certificate_requests** in the **certificate** RHEL system role and used to create a private key and certificate.

logging_pki_files

Using this parameter, you can configure the paths and other settings that logging uses to find the CA, certificate, and key files used for TLS, specified with one or more of the following sub-parameters: **ca_cert**, **ca_cert_src**, **cert**, **cert_src**, **private_key**, **private_key_src**, and **tls**.



NOTE

If you are using **logging_certificates** to create the files on the managed node, do not use **ca_cert_src**, **cert_src**, and **private_key_src**, which are used to copy files not created by **logging_certificates**.

ca_cert

Represents the path to the CA certificate file on the managed node. Default path is **/etc/pki/tls/certs/ca.pem** and the file name is set by the user.

cert

Represents the path to the certificate file on the managed node. Default path is **/etc/pki/tls/certs/server-cert.pem** and the file name is set by the user.

private_key

Represents the path to the private key file on the managed node. Default path is **/etc/pki/tls/private/server-key.pem** and the file name is set by the user.

ca_cert_src

Represents the path to the CA certificate file on the control node which is copied to the target host to the location specified by **ca_cert**. Do not use this if using **logging_certificates**.

cert_src

Represents the path to a certificate file on the control node which is copied to the target host to the location specified by **cert**. Do not use this if using **logging_certificates**.

private_key_src

Represents the path to a private key file on the control node which is copied to the target host to the location specified by **private_key**. Do not use this if using **logging_certificates**.

tls

Setting this parameter to **true** ensures secure transfer of logs over the network. If you do not want a secure wrapper, you can set **tls: false**.

For details about all variables used in the playbook, see the **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file on the control node.

2. Validate the playbook syntax:

```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```


Additional resources

- **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file
- **/usr/share/doc/rhel-system-roles/logging/** directory
- **/usr/share/ansible/roles/rhel-system-roles.certificate/README.md** file
- **/usr/share/doc/rhel-system-roles/certificate/** directory
- [Requesting certificates from a CA and creating self-signed certificates by using RHEL system roles](#)
- **rsyslog.conf(5)** and **syslog(3)** manual pages

6.3.2. Configuring server logging with TLS

You can use the **logging** RHEL system role to configure logging on RHEL servers and set them to receive logs from a remote logging system by using TLS encryption.

This procedure creates a private key and a certificate. Next, it configures TLS on all hosts in the server group in the Ansible inventory.



NOTE

You do not have to call the **certificate** RHEL system role in the playbook to create the certificate. The **logging** RHEL system role calls it automatically.

In order for the CA to be able to sign the created certificate, the managed nodes must be enrolled in an IdM domain.

Prerequisites

- You have prepared the control node and the managed nodes
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.
- The managed nodes are enrolled in an IdM domain.
- If the logging server you want to configure on the manage node runs RHEL 9.2 or later and FIPS mode is enabled, clients must either support the Extended Master Secret (EMS) extension or use TLS 1.3. TLS 1.2 connections without EMS fail. For more information, see the Red Hat Knowledgebase solution [TLS extension "Extended Master Secret" enforced](#).

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Configure remote logging solution by using TLS for secure transfer of logs
  hosts: managed-node-01.example.com
  tasks:
    - name: Deploying remote input and remote_files output with certs
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
      vars:
        logging_certificates:
          - name: logging_cert
            dns: ['www.example.com']
            ca: ipa
            principal: "logging/{{ inventory_hostname }}@IDM.EXAMPLE.COM"
        logging_pki_files:
          - ca_cert: /local/path/to/ca_cert.pem
            cert: /local/path/to/logging_cert.pem
            private_key: /local/path/to/logging_cert.pem
        logging_inputs:
          - name: input_name
            type: remote
            tcp_ports: [514]
            tls: true
            permitted_clients: ['clients.example.com']
        logging_outputs:
          - name: output_name
            type: remote_files
            remote_log_path: /var/log/remote/%FROMHOST%/PROGRAMNAME:::secpath-
              replace%.log
            async_writing: true
```



```

client_count: 20
io_buffer_size: 8192
logging_flows:
- name: flow_name
  inputs: [input_name]
  outputs: [output_name]

```

The settings specified in the example playbook include the following:

logging_certificates

The value of this parameter is passed on to **certificate_requests** in the **certificate** RHEL system role and used to create a private key and certificate.

logging_pki_files

Using this parameter, you can configure the paths and other settings that logging uses to find the CA, certificate, and key files used for TLS, specified with one or more of the following sub-parameters: **ca_cert**, **ca_cert_src**, **cert**, **cert_src**, **private_key**, **private_key_src**, and **tls**.



NOTE

If you are using **logging_certificates** to create the files on the managed node, do not use **ca_cert_src**, **cert_src**, and **private_key_src**, which are used to copy files not created by **logging_certificates**.

ca_cert

Represents the path to the CA certificate file on the managed node. Default path is **/etc/pki/tls/certs/ca.pem** and the file name is set by the user.

cert

Represents the path to the certificate file on the managed node. Default path is **/etc/pki/tls/certs/server-cert.pem** and the file name is set by the user.

private_key

Represents the path to the private key file on the managed node. Default path is **/etc/pki/tls/private/server-key.pem** and the file name is set by the user.

ca_cert_src

Represents the path to the CA certificate file on the control node which is copied to the target host to the location specified by **ca_cert**. Do not use this if using **logging_certificates**.

cert_src

Represents the path to a certificate file on the control node which is copied to the target host to the location specified by **cert**. Do not use this if using **logging_certificates**.

private_key_src

Represents the path to a private key file on the control node which is copied to the target host to the location specified by **private_key**. Do not use this if using **logging_certificates**.

tls

Setting this parameter to **true** ensures secure transfer of logs over the network. If you do not want a secure wrapper, you can set **tls: false**.

For details about all variables used in the playbook, see the **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file on the control node.

2. Validate the playbook syntax:

```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```

Additional resources

- [/usr/share/ansible/roles/rhel-system-roles/logging/README.md](#) file
- [/usr/share/doc/rhel-system-roles/logging/](#) directory
- [Requesting certificates from a CA and creating self-signed certificates by using RHEL system roles](#)
- [rsyslog.conf\(5\)](#) and [syslog\(3\)](#) manual pages

6.4. USING THE LOGGING RHEL SYSTEM ROLES WITH RELP

Reliable Event Logging Protocol (RELP) is a networking protocol for data and message logging over the TCP network. It ensures reliable delivery of event messages and you can use it in environments that do not tolerate any message loss.

The RELP sender transfers log entries in the form of commands and the receiver acknowledges them once they are processed. To ensure consistency, RELP stores the transaction number to each transferred command for any kind of message recovery.

You can consider a remote logging system in between the RELP Client and RELP Server. The RELP Client transfers the logs to the remote logging system and the RELP Server receives all the logs sent by the remote logging system. To achieve that use case, you can use the **logging** RHEL system role to configure the logging system to reliably send and receive log entries.

6.4.1. Configuring client logging with RELP

You can use the **logging** RHEL system role to configure a transfer of log messages stored locally to the remote logging system with RELP.

This procedure configures RELP on all hosts in the **clients** group in the Ansible inventory. The RELP configuration uses Transport Layer Security (TLS) to encrypt the message transmission for secure transfer of logs over the network.

Prerequisites

- [You have prepared the control node and the managed nodes](#)
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Configure client-side of the remote logging solution by using RELP
  hosts: managed-node-01.example.com
  tasks:
    - name: Deploy basic input and RELP output
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
  vars:
    logging_inputs:
      - name: basic_input
        type: basics
    logging_outputs:
      - name: relp_client
        type: relp
        target: logging.server.com
        port: 20514
        tls: true
        ca_cert: /etc/pki/tls/certs/ca.pem
        cert: /etc/pki/tls/certs/client-cert.pem
        private_key: /etc/pki/tls/private/client-key.pem
        pki_authmode: name
        permitted_servers:
          - '*.server.example.com'
    logging_flows:
      - name: example_flow
        inputs: [basic_input]
        outputs: [relp_client]
```

The settings specified in the example playbook include the following:

target

This is a required parameter that specifies the host name where the remote logging system is running.

port

Port number the remote logging system is listening.

tls

Ensures secure transfer of logs over the network. If you do not want a secure wrapper you can set the **tls** variable to **false**. By default **tls** parameter is set to true while working with RELP and requires key/certificates and triplets **{ca_cert, cert, private_key}** and/or **{ca_cert_src, cert_src, private_key_src}**.

- If the **{ca_cert_src, cert_src, private_key_src}** triplet is set, the default locations **/etc/pki/tls/certs** and **/etc/pki/tls/private** are used as the destination on the managed node to transfer files from control node. In this case, the file names are identical to the original ones in the triplet
- If the **{ca_cert, cert, private_key}** triplet is set, files are expected to be on the default path before the logging configuration.
- If both triplets are set, files are transferred from local path from control node to specific path of the managed node.

ca_cert

Represents the path to CA certificate. Default path is **/etc/pki/tls/certs/ca.pem** and the file name is set by the user.

cert

Represents the path to certificate. Default path is **/etc/pki/tls/certs/server-cert.pem** and the file name is set by the user.

private_key

Represents the path to private key. Default path is **/etc/pki/tls/private/server-key.pem** and the file name is set by the user.

ca_cert_src

Represents local CA certificate file path which is copied to the managed node. If **ca_cert** is specified, it is copied to the location.

cert_src

Represents the local certificate file path which is copied to the managed node. If **cert** is specified, it is copied to the location.

private_key_src

Represents the local key file path which is copied to the managed node. If **private_key** is specified, it is copied to the location.

pki_authmode

Accepts the authentication mode as **name** or **fingerprint**.

permitted_servers

List of servers that will be allowed by the logging client to connect and send logs over TLS.

inputs

List of logging input dictionary.

outputs

List of logging output dictionary.

For details about all variables used in the playbook, see the **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file on the control node.

2. Validate the playbook syntax:

```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```

Additional resources

- **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file
- **/usr/share/doc/rhel-system-roles/logging/** directory
- **rsyslog.conf(5)** and **syslog(3)** manual pages

6.4.2. Configuring server logging with RELP

You can use the **logging** RHEL system role to configure a server for receiving log messages from the remote logging system with RELP.

This procedure configures RELP on all hosts in the **server** group in the Ansible inventory. The RELP configuration uses TLS to encrypt the message transmission for secure transfer of logs over the network.

Prerequisites

- You have prepared the control node and the managed nodes
- You are logged in to the control node as a user who can run playbooks on the managed nodes.
- The account you use to connect to the managed nodes has **sudo** permissions on them.

Procedure

1. Create a playbook file, for example `~/playbook.yml`, with the following content:

```
---
- name: Configure server-side of the remote logging solution by using RELP
  hosts: managed-node-01.example.com
  tasks:
    - name: Deploying remote input and remote_files output
      ansible.builtin.include_role:
        name: redhat.rhel_system_roles.logging
      vars:
        logging_inputs:
          - name: relp_server
            type: relp
            port: 20514
            tls: true
            ca_cert: /etc/pki/tls/certs/ca.pem
            cert: /etc/pki/tls/certs/server-cert.pem
            private_key: /etc/pki/tls/private/server-key.pem
            pki_authmode: name
            permitted_clients:
              - '*client.example.com'
        logging_outputs:
          - name: remote_files_output
            type: remote_files
        logging_flows:
          - name: example_flow
            inputs: [relp_server]
            outputs: [remote_files_output]
```

The settings specified in the example playbook include the following:

port

Port number the remote logging system is listening.

tls

Ensures secure transfer of logs over the network. If you do not want a secure wrapper you can set the **tls** variable to **false**. By default **tls** parameter is set to true while working with

RELPE and requires key/certificates and triplets **{ca_cert, cert, private_key}** and/or **{ca_cert_src, cert_src, private_key_src}**.

- If the **{ca_cert_src, cert_src, private_key_src}** triplet is set, the default locations **/etc/pki/tls/certs** and **/etc/pki/tls/private** are used as the destination on the managed node to transfer files from control node. In this case, the file names are identical to the original ones in the triplet
- If the **{ca_cert, cert, private_key}** triplet is set, files are expected to be on the default path before the logging configuration.
- If both triplets are set, files are transferred from local path from control node to specific path of the managed node.

ca_cert

Represents the path to CA certificate. Default path is **/etc/pki/tls/certs/ca.pem** and the file name is set by the user.

cert

Represents the path to the certificate. Default path is **/etc/pki/tls/certs/server-cert.pem** and the file name is set by the user.

private_key

Represents the path to private key. Default path is **/etc/pki/tls/private/server-key.pem** and the file name is set by the user.

ca_cert_src

Represents local CA certificate file path which is copied to the managed node. If **ca_cert** is specified, it is copied to the location.

cert_src

Represents the local certificate file path which is copied to the managed node. If **cert** is specified, it is copied to the location.

private_key_src

Represents the local key file path which is copied to the managed node. If **private_key** is specified, it is copied to the location.

pki_authmode

Accepts the authentication mode as **name** or **fingerprint**.

permitted_clients

List of clients that will be allowed by the logging server to connect and send logs over TLS.

inputs

List of logging input dictionary.

outputs

List of logging output dictionary.

For details about all variables used in the playbook, see the **/usr/share/ansible/roles/rhel-system-roles.logging/README.md** file on the control node.

2. Validate the playbook syntax:

```
$ ansible-playbook --syntax-check ~/playbook.yml
```

Note that this command only validates the syntax and does not protect against a wrong but valid configuration.

3. Run the playbook:

```
$ ansible-playbook ~/playbook.yml
```

Additional resources

- `/usr/share/ansible/roles/rhel-system-roles.logging/README.md` file
- `/usr/share/doc/rhel-system-roles/logging/` directory
- `rsyslog.conf(5)` and `syslog(3)` manual pages

CHAPTER 7. AUDITING THE SYSTEM

Audit does not provide additional security to your system; rather, it can be used to discover violations of security policies used on your system. These violations can further be prevented by additional security measures such as SELinux.

7.1. LINUX AUDIT

With Linux Audit, you can track security-relevant information about your system. By following pre-configured rules, Audit generates log entries to record as much information as possible about the events that are happening on your system. This information is crucial for mission-critical environments to determine the violator of the security policy and the actions they performed.

Audit can record, for example, the following information in its log files:

- Date and time, type, and outcome of an event
- Sensitivity labels of subjects and objects
- Association of an event with the identity of the user who triggered the event
- All modifications to Audit configuration and attempts to access Audit log files
- All uses of authentication mechanisms, such as SSH, Kerberos, and others
- Changes to any trusted database, such as **/etc/passwd**
- Attempts to import or export information into or from the system
- Include or exclude events based on user identity, subject and object labels, and other attributes

The use of the Audit system is also a requirement for a number of security-related certifications. Audit is designed to meet or exceed the requirements of the following certifications or compliance guides:

- Controlled Access Protection Profile (CAPP)
- Labeled Security Protection Profile (LSPP)
- Rule Set Base Access Control (RSBAC)
- National Industrial Security Program Operating Manual (NISPOM)
- Federal Information Security Management Act (FISMA)
- Payment Card Industry - Data Security Standard (PCI-DSS)
- Security Technical Implementation Guides (STIG)

Audit has also been evaluated by National Information Assurance Partnership (NIAP) and Best Security Industries (BSI).

Use cases

Watching file access

Audit can track whether a file or a directory has been accessed, modified, executed, or the file's attributes have been changed. This is useful, for example, to detect access to important files and have an Audit trail available in case one of these files is corrupted.

Monitoring system calls

Audit can be configured to generate a log entry every time a particular system call is used. This can be used, for example, to track changes to the system time by monitoring the **settimeofday**, **clock_gettime**, and other time-related system calls.

Recording commands run by a user

Audit can track whether a file has been executed, so rules can be defined to record every execution of a particular command. For example, a rule can be defined for every executable in the **/bin** directory. The resulting log entries can then be searched by user ID to generate an audit trail of executed commands per user.

Recording execution of system pathnames

Aside from watching file access which translates a path to an inode at rule invocation, Audit can now watch the execution of a path even if it does not exist at rule invocation, or if the file is replaced after rule invocation. This allows rules to continue to work after upgrading a program executable or before it is even installed.

Recording security events

The **pam_faillock** authentication module is capable of recording failed login attempts. Audit can be set up to record failed login attempts as well and provides additional information about the user who attempted to log in.

Searching for events

Audit provides the **ausearch** utility, which can be used to filter the log entries and provide a complete audit trail based on several conditions.

Running summary reports

The **aureport** utility can be used to generate, among other things, daily reports of recorded events. A system administrator can then analyze these reports and investigate suspicious activity further.

Monitoring network access

The **nftables**, **iptables**, and **ebtables** utilities can be configured to trigger Audit events, allowing system administrators to monitor network access.



NOTE

Audit may affect system performance depending on the amount of information collected.

7.2. AUDIT SYSTEM ARCHITECTURE

The Audit system consists of two main parts: the user-space applications and utilities, and the kernel-side system call processing. The kernel component receives system calls from user-space applications and filters them through one of the following filters: **user**, **task**, **fstype**, or **exit**.

After a system call passes the **exclude** filter, it is sent through one of the aforementioned filters, which, based on the Audit rule configuration, sends it to the Audit daemon for further processing.

The user-space Audit daemon collects the information from the kernel and creates entries in a log file. Other Audit user-space utilities interact with the Audit daemon, the kernel Audit component, or the Audit log files:

- The **auditctl** Audit control utility interacts with the kernel Audit component to manage rules and to control many settings and parameters of the event generation process.

- The remaining Audit utilities take the contents of the Audit log files as input and generate output based on user's requirements. For example, the **aureport** utility generates a report of all recorded events.

In RHEL 10, the Audit dispatcher daemon (**auditd**) functionality is integrated in the Audit daemon (**auditd**). Configuration files of plugins for the interaction of real-time analytical programs with Audit events are located in the **/etc/audit/plugins.d/** directory by default.

7.3. AUDIT SETTINGS FOR A SECURE ENVIRONMENT

The default **auditd** configuration should be suitable for most environments. However, if your environment must meet strict security policies, you can change the following settings for the Audit daemon configuration in the **/etc/audit/auditd.conf** file:

log_file

The directory that holds the Audit log files (usually **/var/log/audit/**) should reside on a separate mount point. This prevents other processes from consuming space in this directory and provides accurate detection of the remaining space for the Audit daemon.

max_log_file

Specifies the maximum size of a single Audit log file, must be set to make full use of the available space on the partition that holds the Audit log files. The **max_log_file** parameter specifies the maximum file size in megabytes. The value given must be numeric.

max_log_file_action

Decides what action is taken once the limit set in **max_log_file** is reached, should be set to **keep_logs** to prevent Audit log files from being overwritten.

space_left

Specifies the amount of free space left on the disk for which an action that is set in the **space_left_action** parameter is triggered. Must be set to a number that gives the administrator enough time to respond and free up disk space. The **space_left** value depends on the rate at which the Audit log files are generated. If the value of **space_left** is specified as a whole number, it is interpreted as an absolute size in megabytes (MiB). If the value is specified as a number between 1 and 99 followed by a percentage sign (for example, 5%), the Audit daemon calculates the absolute size in megabytes based on the size of the file system containing **log_file**.

space_left_action

It is recommended to set the **space_left_action** parameter to **email** or **exec** with an appropriate notification method.

admin_space_left

Specifies the absolute minimum amount of free space for which an action that is set in the **admin_space_left_action** parameter is triggered, must be set to a value that leaves enough space to log actions performed by the administrator. The numeric value for this parameter should be lower than the number for **space_left**. You can also append a percent sign (for example, 1%) to the number to have the audit daemon calculate the number based on the disk partition size.

admin_space_left_action

Should be set to **single** to put the system into single-user mode and allow the administrator to free up some disk space.

disk_full_action

Specifies an action that is triggered when no free space is available on the partition that holds the Audit log files, must be set to **halt** or **single**. This ensures that the system is either shut down or operating in single-user mode when Audit can no longer log events.

disk_error_action

Specifies an action that is triggered in case an error is detected on the partition that holds the Audit log files, must be set to **syslog**, **single**, or **halt**, depending on your local security policies regarding the handling of hardware malfunctions.

flush

Should be set to **incremental_async**. It works in combination with the **freq** parameter, which determines how many records can be sent to the disk before forcing a hard synchronization with the hard drive. The **freq** parameter should be set to **100**. These parameters assure that Audit event data is synchronized with the log files on the disk while keeping good performance for bursts of activity.

The remaining configuration options should be set according to your local security policy.

7.4. STARTING AND CONTROLLING AUDITD

After **auditd** is configured, start the service to collect Audit information and store it in the log files. Use the following command as the root user to start **auditd**:

```
# service auditd start
```

To configure **auditd** to start at boot time:

```
# systemctl enable auditd
```

You can temporarily disable **auditd** with the **# auditctl -e 0** command and re-enable it with **# auditctl -e 1**.

You can perform other actions on **auditd** by using the **service auditd <action>** command, where **<action>** can be one of the following:

stop

Stops **auditd**.

restart

Restarts **auditd**.

reload or force-reload

Reloads the configuration of **auditd** from the **/etc/audit/auditd.conf** file.

rotate

Rotates the log files in the **/var/log/audit/** directory.

resume

Resumes logging of Audit events after it has been previously suspended, for example, when there is not enough free space on the disk partition that holds the Audit log files.

condrestart or try-restart

Restarts **auditd** only if it is already running.

status

Displays the running status of **auditd**.



NOTE

The **service** command is the only way to correctly interact with the **auditd** daemon. You need to use the **service** command so that the **audit** value is properly recorded. You can use the **systemctl** command only for two actions: **enable** and **status**.

7.5. AUDIT LOG ENTRIES

By default, the Audit system stores log entries in the `/var/log/audit/audit.log` file; if log rotation is enabled, rotated **audit.log** files are stored in the same directory.

Add the following Audit rule to log every attempt to read or modify the `/etc/ssh/sshd_config` file:

```
# auditctl -w /etc/ssh/sshd_config -p warx -k sshd_config
```

If the **auditd** daemon is running, for example, using the following command creates a new event in the Audit log file:

```
$ cat /etc/ssh/sshd_config
```

This event in the **audit.log** file looks as follows:

```
type=SYSCALL msg=audit(1364481363.243:24287): arch=c000003e syscall=2 success=no exit=-13
a0=7fffd19c5592 a1=0 a2=7fffd19c4b50 a3=a items=1 ppid=2686 pid=3538 auid=1000 uid=1000
gid=1000 euid=1000 suid=1000 fsuid=1000 egid=1000 sgid=1000 fsgid=1000 tty=pts0 ses=1
comm="cat" exe="/bin/cat" subj=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023
key="sshd_config"
type=CWD msg=audit(1364481363.243:24287): cwd="/home/shadowman"
type=PATH msg=audit(1364481363.243:24287): item=0 name="/etc/ssh/sshd_config" inode=409248
dev=fd:00 mode=0100600 ouid=0 ogid=0 rdev=00:00 obj=system_u:object_r:etc_t:s0
nametype=NORMAL cap_fp=none cap_fi=none cap_fe=0 cap_fver=0
type=PROCTITLE msg=audit(1364481363.243:24287) :
proctitle=636174002F6574632F7373682F737368645F636F6E666967
```

The above event consists of four records, which share the same time stamp and serial number. Records always start with the **type=** keyword. Each record consists of several **name=value** pairs separated by a white space or a comma. A detailed analysis of the above event follows:

First Record

type=SYSCALL

The **type** field contains the type of the record. In this example, the **SYSCALL** value specifies that this record was triggered by a system call to the kernel.

msg=audit(1364481363.243:24287):

The **msg** field records:

- A time stamp and a unique ID of the record in the form **audit(time_stamp:ID)**. Multiple records can share the same time stamp and ID if they were generated as part of the same Audit event. The time stamp is using the Unix time format - seconds since 00:00:00 UTC on 1 January 1970.
- Various event-specific **name=value** pairs provided by the kernel or user-space applications.

arch=c000003e

The **arch** field contains information about the CPU architecture of the system. The value, **c000003e**, is encoded in hexadecimal notation. When searching Audit records with the **ausearch** command, use the **-i** or **--interpret** option to automatically convert hexadecimal values into their human-readable equivalents. The **c000003e** value is interpreted as **x86_64**.

syscall=2

The **syscall** field records the type of the system call that was sent to the kernel. The value, **2**, can be matched with its human-readable equivalent in the **/usr/include/asm/unistd_64.h** file. In this case, **2** is the **open** system call. Note that the **ausyscall** utility allows you to convert system call numbers to their human-readable equivalents. Use the **ausyscall --dump** command to display a listing of all system calls along with their numbers. For more information, see the **ausyscall(8)** man page.

success=no

The **success** field records whether the system call recorded in that particular event succeeded or failed. In this case, the call did not succeed.

exit=-13

The **exit** field contains a value that specifies the exit code returned by the system call. This value varies for a different system call. You can interpret the value to its human-readable equivalent with the following command:

```
# ausearch --interpret --exit -13
```

Note that the previous example assumes that your Audit log contains an event that failed with exit code **-13**.

a0=7fffd19c5592, a1=0, a2=7fffd19c5592, a3=a

The **a0** to **a3** fields record the first four arguments, encoded in hexadecimal notation, of the system call in this event. These arguments depend on the system call that is used; they can be interpreted by the **ausearch** utility.

items=1

The **items** field contains the number of PATH auxiliary records that follow the syscall record.

ppid=2686

The **ppid** field records the Parent Process ID (PPID). In this case, **2686** was the PPID of the parent process such as **bash**.

pid=3538

The **pid** field records the Process ID (PID). In this case, **3538** was the PID of the **cat** process.

audit=1000

The **audit** field records the Audit user ID, that is the loginuid. This ID is assigned to a user upon login and is inherited by every process even when the user's identity changes, for example, by switching user accounts with the **su - john** command.

uid=1000

The **uid** field records the user ID of the user who started the analyzed process. The user ID can be interpreted into user names with the following command: **ausearch -i --uid UID**.

gid=1000

The **gid** field records the group ID of the user who started the analyzed process.

euid=1000

The **euid** field records the effective user ID of the user who started the analyzed process.

suid=1000

The **suid** field records the set user ID of the user who started the analyzed process.

fsuid=1000

The **fsuid** field records the file system user ID of the user who started the analyzed process.

egid=1000

The **egid** field records the effective group ID of the user who started the analyzed process.

sgid=1000

The **sgid** field records the set group ID of the user who started the analyzed process.

fsgid=1000

The **fsgid** field records the file system group ID of the user who started the analyzed process.

tty=pts0

The **tty** field records the terminal from which the analyzed process was invoked.

ses=1

The **ses** field records the session ID of the session from which the analyzed process was invoked.

comm="cat"

The **comm** field records the command-line name of the command that was used to invoke the analyzed process. In this case, the **cat** command was used to trigger this Audit event.

exe="/bin/cat"

The **exe** field records the path to the executable that was used to invoke the analyzed process.

subj=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023

The **subj** field records the SELinux context with which the analyzed process was labeled at the time of execution.

key="sshd_config"

The **key** field records the administrator-defined string associated with the rule that generated this event in the Audit log.

Second Record**type=CWD**

In the second record, the **type** field value is **CWD** - current working directory. This type is used to record the working directory from which the process that invoked the system call specified in the first record was executed.

The purpose of this record is to record the current process's location in case a relative path winds up being captured in the associated PATH record. This way the absolute path can be reconstructed.

msg=audit(1364481363.243:24287)

The **msg** field holds the same time stamp and ID value as the value in the first record. The time stamp is using the Unix time format - seconds since 00:00:00 UTC on 1 January 1970.

cwd="/home/user_name"

The **cwd** field contains the path to the directory in which the system call was invoked.

Third Record**type=PATH**

In the third record, the **type** field value is **PATH**. An Audit event contains a **PATH**-type record for every path that is passed to the system call as an argument. In this Audit event, only one path (**/etc/ssh/sshd_config**) was used as an argument.

msg=audit(1364481363.243:24287):

The **msg** field holds the same time stamp and ID value as the value in the first and second record.

item=0

The **item** field indicates which item, of the total number of items referenced in the **SYSCALL** type record, the current record is. This number is zero-based; a value of **0** means it is the first item.

name="/etc/ssh/sshd_config"

The **name** field records the path of the file or directory that was passed to the system call as an argument. In this case, it was the **/etc/ssh/sshd_config** file.

inode=409248

The **inode** field contains the inode number associated with the file or directory recorded in this event. The following command displays the file or directory that is associated with the **409248** inode number:

```
# find / -inum 409248 -print
/etc/ssh/sshd_config
```

dev=fd:00

The **dev** field specifies the minor and major ID of the device that contains the file or directory recorded in this event. In this case, the value represents the **/dev/fd/0** device.

mode=0100600

The **mode** field records the file or directory permissions, encoded in numerical notation as returned by the **stat** command in the **st_mode** field. See the **stat(2)** man page for more information. In this case, **0100600** can be interpreted as **-rw-----**, meaning that only the root user has read and write permissions to the **/etc/ssh/sshd_config** file.

oid=0

The **oid** field records the object owner's user ID.

ogid=0

The **ogid** field records the object owner's group ID.

rdev=00:00

The **rdev** field contains a recorded device identifier for special files only. In this case, it is not used as the recorded file is a regular file.

obj=system_u:object_r:etc_t:s0

The **obj** field records the SELinux context with which the recorded file or directory was labeled at the time of execution.

nametype=NORMAL

The **nametype** field records the intent of each path record's operation in the context of a given syscall.

cap_fp=none

The **cap_fp** field records data related to the setting of a permitted file system-based capability of the file or directory object.

cap_fi=none

The **cap_fi** field records data related to the setting of an inherited file system-based capability of the file or directory object.

cap_fe=0

The **cap_fe** field records the setting of the effective bit of the file system-based capability of the file or directory object.

cap_fver=0

The **cap_fver** field records the version of the file system-based capability of the file or directory object.

Fourth Record

type=PROCTITLE

The **type** field contains the type of the record. In this example, the **PROCTITLE** value specifies that this record gives the full command-line that triggered this Audit event, triggered by a system call to the kernel.

proctitle=636174002F6574632F7373682F737368645F636F6E666967

The **proctitle** field records the full command-line of the command that was used to invoke the analyzed process. The field is encoded in hexadecimal notation to not allow the user to influence the Audit log parser. The text decodes to the command that triggered this Audit event. When searching Audit records with the **ausearch** command, use the **-i** or **--interpret** option to automatically convert hexadecimal values into their human-readable equivalents. The

636174002F6574632F7373682F737368645F636F6E666967 value is interpreted as **cat /etc/ssh/sshd_config**.

7.6. EXAMPLES OF AUDIT RULES DEFINED WITH AUDITCTL

The Audit system operates on a set of rules that define what is captured in the log files. Audit rules can be set either on the command line using the **auditctl** utility or in the **/etc/audit/rules.d/** directory.

The **auditctl** command enables you to control the basic functionality of the Audit system and to define rules that decide which Audit events are logged.

File-system rules examples

1. To define a rule that logs all write access to, and every attribute change of, the **/etc/passwd** file:

```
# auditctl -w /etc/passwd -p wa -k passwd_changes
```

2. To define a rule that logs all write access to, and every attribute change of, all the files in the **/etc/selinux/** directory:

```
# auditctl -w /etc/selinux/ -p wa -k selinux_changes
```

System-call rules examples

1. To define a rule that creates a log entry every time the **adjtimex** or **settimeofday** system calls are used by a program, and the system uses the 64-bit architecture:

```
# auditctl -a always,exit -F arch=b64 -S adjtimex -S settimeofday -k time_change
```

2. To define a rule that creates a log entry every time a file is deleted or renamed by a system user whose ID is 1000 or larger:

```
# auditctl -a always,exit -S unlink -S unlinkat -S rename -S renameat -F auid>=1000 -F auid!=4294967295 -k delete
```

Note that the **-F auid!=4294967295** option is used to exclude users whose login UID is not set.

Executable-file rules

To define a rule that logs all execution of the **/bin/id** program, execute the following command:

```
# auditctl -a always,exit -F exe=/bin/id -F arch=b64 -S execve -k execution_bin_id
```


Additional resources

- **auditctl(8)** man page on your system

7.7. AUDIT PERSISTENT RULES

To define Audit rules that are persistent across reboots, you must either directly include them in the **/etc/audit/rules.d/audit.rules** file or use the **augenrules** program that reads rules located in the **/etc/audit/rules.d/** directory.

Note that the **/etc/audit/audit.rules** file is generated whenever the **auditd** service starts. Files in **/etc/audit/rules.d/** use the same **auditctl** command-line syntax to specify the rules. Empty lines and text following a hash sign (**#**) are ignored.

Furthermore, you can use the **auditctl** command to read rules from a specified file using the **-R** option, for example:

```
# auditctl -R /usr/share/audit/sample-rules/30-stig.rules
```

The **augenrules** script reads rules located in the **/etc/audit/rules.d/** directory and compiles them into an **audit.rules** file. This script processes all files that end with **.rules** in a specific order based on their natural sort order. The files in this directory are organized into groups with the following meanings:

10

Kernel and auditctl configuration

20

Rules that could match general rules but you want a different match

30

Main rules

40

Optional rules

50

Server-specific rules

70

System local rules

90

Finalize (immutable)

The rules are not meant to be used all at once. They are pieces of a policy that should be thought out and individual files copied to **/etc/audit/rules.d/**. For example, to set a system up in the STIG configuration, copy rules **10-base-config**, **30-stig**, **31-privileged**, and **99-finalize**.

Once you have the rules in the **/etc/audit/rules.d/** directory, load them by running the **augenrules** script with the **--load** directive:

```
# augenrules --load
/sbin/augenrules: No change
No rules
enabled 1
failure 1
```

```
pid 742
rate_limit 0
...
```

Additional resources

- **audit.rules(8)** and **augenrules(8)** man pages on your system

7.8. PRE-CONFIGURED AUDIT RULES FILES FOR COMPLIANCE WITH STANDARDS

To configure Audit for compliance with a specific certification standard, such as OSPP, PCI DSS, or STIG, you can use the set of pre-configured rules files installed with the **audit** package as a starting point. The sample rules are located in the **/usr/share/audit/sample-rules** directory.



WARNING

The Audit sample rules in the **sample-rules** directory are not exhaustive nor up to date because security standards are dynamic and subject to change. These rules are provided only to demonstrate how Audit rules can be structured and written. They do not ensure immediate compliance with the latest security standards. To bring your system into compliance with the latest security standards according to specific security guidelines, use the [SCAP-based security compliance tools](#).

30-nispom.rules

Audit rule configuration that meets the requirements specified in the Information System Security chapter of the National Industrial Security Program Operating Manual.

30-ospp-v42*.rules

Audit rule configuration that meets the requirements defined in the OSPP (Protection Profile for General Purpose Operating Systems) profile version 4.2.

30-pci-dss-v31.rules

Audit rule configuration that meets the requirements set by Payment Card Industry Data Security Standard (PCI DSS) v3.1.

30-stig.rules

Audit rule configuration that meets the requirements set by Security Technical Implementation Guides (STIG).

To use these configuration files, copy them to the **/etc/audit/rules.d/** directory and use the **augenrules --load** command, for example:

```
# cd /usr/share/audit/sample-rules/
# cp 10-base-config.rules 30-stig.rules 31-privileged.rules 99-finalize.rules /etc/audit/rules.d/
# augenrules --load
```

You can order Audit rules using a numbering scheme. See the **/usr/share/audit/sample-rules/README-rules** file for more information.

Additional resources

- **audit.rules(7)** man page on your system

7.9. DISABLING AUGENRULES

You can disable the **augenrules** utility, which switches Audit to use rules defined in the **/etc/audit/audit.rules** file.

Procedure

1. Copy the **/usr/lib/systemd/system/auditd.service** file to the **/etc/systemd/system/** directory:

```
# cp -f /usr/lib/systemd/system/auditd.service /etc/systemd/system/
```

2. Edit the **/etc/systemd/system/auditd.service** file in a text editor of your choice, for example:

```
# vi /etc/systemd/system/auditd.service
```

3. Comment out the line containing **augenrules**, and uncomment the line containing the **auditctl -R** command:

```
#ExecStartPost=/sbin/augenrules --load
ExecStartPost=/sbin/auditctl -R /etc/audit/audit.rules
```

4. Reload the **systemd** daemon to fetch changes in the **auditd.service** file:

```
# systemctl daemon-reload
```

5. Restart the **auditd** service:

```
# service auditd restart
```

Additional resources

- **augenrules(8)** and **audit.rules(8)** man pages on your system
- [Auditd service restart overrides changes made to /etc/audit/audit.rules](#) (Red Hat Knowledgebase)

7.10. SETTING UP AUDIT TO MONITOR SOFTWARE UPDATES

You can use the pre-configured rule **44-installers.rules** to configure Audit to monitor the following utilities that install software:

- **dnf** ^[1]
- **yum**
- **pip**
- **npm**

- **cpan**
- **gem**
- **luarocks**

To monitor the **rpm** utility, install the **rpm-plugin-audit** package. Audit will then generate **SOFTWARE_UPDATE** events when it installs or updates a package. You can list these events by entering **ausearch -m SOFTWARE_UPDATE** on the command line.



NOTE

Pre-configured rule files cannot be used on systems with the **ppc64le** and **aarch64** architectures.

Prerequisites

- **auditd** is configured in accordance with [Section 7.3, "Audit settings for a secure environment"](#).

Procedure

1. Copy the pre-configured rule file **44-installers.rules** from the **/usr/share/audit/sample-rules/** directory to the **/etc/audit/rules.d/** directory:

```
# cp /usr/share/audit/sample-rules/44-installers.rules /etc/audit/rules.d/
```

2. Load the audit rules:

```
# augenrules --load
```

Verification

1. List the loaded rules:

```
# auditctl -l
-p x-w /usr/bin/dnf-3 -k software-installer
-p x-w /usr/bin/yum -k software-installer
-p x-w /usr/bin/pip -k software-installer
-p x-w /usr/bin/npm -k software-installer
-p x-w /usr/bin/cpan -k software-installer
-p x-w /usr/bin/gem -k software-installer
-p x-w /usr/bin/luarocks -k software-installer
```

2. Perform an installation, for example:

```
# dnf reinstall -y vim-enhanced
```

3. Search the Audit log for recent installation events, for example:

```
# ausearch -ts recent -k software-installer
_____
time->Thu Dec 16 10:33:46 2021
type=PROCTITLE msg=audit(1639668826.074:298):
```

```

proctitle=2F7573722F6C6962657865632F706C61746666F726D2D707974686F6E002F75737
22F62696E2F646E66007265696E7374616C6C002D790076696D2D656E68616E636564
type=PATH msg=audit(1639668826.074:298): item=2 name="/lib64/ld-linux-x86-64.so.2"
inode=10092 dev=fd:01 mode=0100755 ouid=0 ogid=0 rdev=00:00
obj=system_u:object_r:ld_so_t:s0 nametype=NORMAL cap_fp=0 cap_fi=0 cap_fe=0
cap_fver=0 cap_frootid=0
type=PATH msg=audit(1639668826.074:298): item=1 name="/usr/libexec/platform-python"
inode=4618433 dev=fd:01 mode=0100755 ouid=0 ogid=0 rdev=00:00
obj=system_u:object_r:bin_t:s0 nametype=NORMAL cap_fp=0 cap_fi=0 cap_fe=0
cap_fver=0 cap_frootid=0
type=PATH msg=audit(1639668826.074:298): item=0 name="/usr/bin/dnf" inode=6886099
dev=fd:01 mode=0100755 ouid=0 ogid=0 rdev=00:00 obj=system_u:object_r:rpm_exec_t:s0
nametype=NORMAL cap_fp=0 cap_fi=0 cap_fe=0 cap_fver=0 cap_frootid=0
type=CWD msg=audit(1639668826.074:298): cwd="/root"
type=EXECVE msg=audit(1639668826.074:298): argc=5 a0="/usr/libexec/platform-python"
a1="/usr/bin/dnf" a2="reinstall" a3="-y" a4="vim-enhanced"
type=SYSCALL msg=audit(1639668826.074:298): arch=c000003e syscall=59 success=yes
exit=0 a0=55c437f22b20 a1=55c437f2c9d0 a2=55c437f2aeb0 a3=8 items=3 ppid=5256
pid=5375 auid=0 uid=0 gid=0 euid=0 suid=0 fsuid=0 egid=0 sgid=0 fsgid=0 tty=pts0 ses=3
comm="dnf" exe="/usr/libexec/platform-python3.6"
subj=unconfined_u:unconfined_r:unconfined_t:s0-s0:c0.c1023 key="software-installer"

```

7.11. MONITORING USER LOGIN TIMES WITH AUDIT

To monitor which users logged in at specific times, you can use the **ausearch** or **aureport** tools, which provide different ways of presenting the same information. This does not require configuring Audit in any specific way.

Prerequisites

- **auditd** is configured in accordance with [Section 7.3, "Audit settings for a secure environment"](#).

Procedure

To display user login times, use any one of the following commands:

- Search the audit log for the **USER_LOGIN** message type:

```

# ausearch -m USER_LOGIN -ts '12/02/2020' '18:00:00' -sv no
time->Mon Nov 22 07:33:22 2021
type=USER_LOGIN msg=audit(1637584402.416:92): pid=1939 uid=0 auid=4294967295
ses=4294967295 subj=system_u:system_r:sshd_t:s0-s0:c0.c1023 msg='op=login acct="
(unknown)" exe="/usr/sbin/sshd" hostname=? addr=10.37.128.108 terminal=ssh res=failed'

```

- You can specify the date and time with the **-ts** option. If you do not use this option, **ausearch** provides results from today, and if you omit time, **ausearch** provides results from midnight.
- You can use the **-sv yes** option to filter out successful login attempts and **-sv no** for unsuccessful login attempts.
- Pipe the raw output of the **ausearch** command into the **aulast** utility, which displays the output in a format similar to the output of the **last** command. For example:

```
# ausearch --raw | aulast --stdin
```

```

root    ssh      10.37.128.108  Mon Nov 22 07:33 - 07:33 (00:00)
root    ssh      10.37.128.108  Mon Nov 22 07:33 - 07:33 (00:00)
root    ssh      10.22.16.106  Mon Nov 22 07:40 - 07:40 (00:00)
reboot  system boot 4.18.0-348.6.el8 Mon Nov 22 07:33

```

- Display the list of login events by using the **aureport** command with the **--login -i** options.

```
# aureport --login -i
```

```
Login Report
```

```
=====
```

```
# date time auid host term exe success event
```

```
=====
```

```

1. 11/16/2021 13:11:30 root 10.40.192.190 ssh /usr/sbin/sshd yes 6920
2. 11/16/2021 13:11:31 root 10.40.192.190 ssh /usr/sbin/sshd yes 6925
3. 11/16/2021 13:11:31 root 10.40.192.190 ssh /usr/sbin/sshd yes 6930
4. 11/16/2021 13:11:31 root 10.40.192.190 ssh /usr/sbin/sshd yes 6935
5. 11/16/2021 13:11:33 root 10.40.192.190 ssh /usr/sbin/sshd yes 6940
6. 11/16/2021 13:11:33 root 10.40.192.190 /dev/pts/0 /usr/sbin/sshd yes 6945

```

Additional resources

- **aureport(8)**, **aureport(8)**, and **aureport(8)** man pages on your system

7.12. ADDITIONAL RESOURCES

- [RHEL Audit System Reference](#) (Red Hat Knowledgebase)
- [Auditd execution options in a container](#) (Red Hat Knowledgebase)
- The [Linux Audit Documentation Project page](#) (Github.com)
- **/usr/share/doc/audit/** directory on your system
- **auditd(8)**, **auditctl(8)**, **aureport(8)**, **audit.rules(7)**, **auditd.conf(5)**, **auditd.conf(5)**, **aureport-expression(5)**, **aureport(8)**, **aureport(8)**, **ausyscall(8)**, **auditd(8)**, and **auditd(8)** man pages on your system

[1] Because **dnf** is a symlink in RHEL, the path in the **dnf** Audit rule must include the target of the symlink. To receive correct Audit events, modify the **44-installers.rules** file by changing the **path=/usr/bin/dnf** path to **/usr/bin/dnf-3**.

CHAPTER 8. MANAGING AND MONITORING SECURITY UPDATES

Learn how to install security updates and display additional details about the updates to keep your Red Hat Enterprise Linux systems secured against newly discovered threats and vulnerabilities.

8.1. IDENTIFYING SECURITY UPDATES

Keeping enterprise systems secure from current and future threats requires regular security updates. Red Hat Product Security provides the guidance you need to confidently deploy and maintain enterprise solutions.

8.1.1. What are security advisories?

Red Hat Security Advisories (RHSA) document the information about security flaws being fixed in Red Hat products and services.

Each RHSA includes the following information:

- Severity
- Type and status
- Affected products
- Summary of fixed issues
- Links to the tickets about the problem. Note that not all tickets are public.
- Common Vulnerabilities and Exposures (CVE) numbers and links with additional details, such as attack complexity.

Red Hat Customer Portal provides a list of Red Hat Security Advisories published by Red Hat. You can display details of a specific advisory by navigating to the advisory's ID from the list of Red Hat Security Advisories.

Figure 8.1. List of security advisories

Security Updates > Security Advisories

Security Advisories Red Hat CVE Database Security Labs

Red Hat Enterprise Linux All Variants All Versions All Architectures

Keyword GO All Low Moderate Important Critical

Notifications Preferences

Advisory	Synopsis	Severity	Products	Publish Date
RHSA-2022:1491	Important: java-1.8.0-openjdk security update	Important	Red Hat CodeReady Linux Builder for ARM 64 Red Hat Enterprise Linux for x86_64 Red Hat Enterprise Linux for Power, little endian Red Hat CodeReady Linux Builder for Power, little endian Red Hat Enterprise Linux for ARM 64 Red Hat CodeReady Linux Builder for x86_64 Red Hat Enterprise Linux for IBM z Systems	25 Apr 2022
RHSA-2022:1488	Important: java-1.8.0-openjdk security update	Important	Red Hat Enterprise Linux Server for Power LE - Update Services for SAP Solutions	25 Apr 2022

Optionally, you can also filter the results by specific product, variant, version, and architecture. For example, to display only advisories for Red Hat Enterprise Linux 9, you can set the following filters:

- Product: Red Hat Enterprise Linux
- Variant: All Variants
- Version: 9
- Optionally, select a minor version.

Additional resources

- [List of Red Hat Security Advisories](#)
- [Anatomy of a Red Hat Security Advisory](#)

8.1.2. Displaying security updates that are not installed on a host

You can list all available security updates for your system by using the **dnf** utility.

Prerequisites

- A Red Hat subscription is attached to the host.

Procedure

- List all available security updates which have not been installed on the host:


```
# dnf updateinfo list updates security
...
RHSA-2019:0997 Important/Sec. platform-python-3.6.8-2.el8_0.x86_64
RHSA-2019:0997 Important/Sec. python3-libs-3.6.8-2.el8_0.x86_64
RHSA-2019:0990 Moderate/Sec. systemd-239-13.el8_0.3.x86_64
...
```

8.1.3. Displaying security updates that are installed on a host

You can list installed security updates for your system by using the **dnf** utility.

Procedure

- List all security updates which are installed on the host:

```
# dnf updateinfo list security --installed
...
RHSA-2019:1234 Important/Sec. libssh2-1.8.0-7.module+el8+2833+c7d6d092
RHSA-2019:4567 Important/Sec. python3-libs-3.6.7.1.el8.x86_64
RHSA-2019:8901 Important/Sec. python3-libs-3.6.8-1.el8.x86_64
...
```

If multiple updates of a single package are installed, **dnf** lists all advisories for the package. In the previous example, two security updates for the **python3-libs** package have been installed since the system installation.

8.1.4. Displaying a specific advisory by using DNF

You can use the **dnf** utility to display a specific advisory information that is available for an update.

Prerequisites

- A Red Hat subscription is attached to the host.
- You know the ID of the security advisory.
- The update provided by the advisory is not installed.

Procedure

- Display a specific advisory, for example:

```
# dnf updateinfo info RHSA-2019:0997
=====
Important: python3 security update
=====
Update ID: RHSA-2019:0997
Type: security
Updated: 2019-05-07 05:41:52
Bugs: 1688543 - CVE-2019-9636 python: Information Disclosure due to urlsplit improper
NFKC normalization
CVEs: CVE-2019-9636
Description: ...
```

8.2. INSTALLING SECURITY UPDATES

In Red Hat Enterprise Linux, you can install a specific security advisory and all available security updates. You can also configure the system to download and install security updates automatically.

8.2.1. Installing all available security updates

To keep the security of your system up to date, you can install all currently available security updates using the **dnf** utility.

Prerequisites

- A Red Hat subscription is attached to the host.

Procedure

1. Install security updates using **dnf** utility:

```
# dnf update --security
```

Without the **--security** parameter, **dnf update** installs all updates, including bug fixes and enhancements.

2. Confirm and start the installation by pressing **y**:

```
...
Transaction Summary
=====
Upgrade ... Packages

Total download size: ... M
Is this ok [y/d/N]: y
```

3. Optional: List processes that require a manual restart of the system after installing the updated packages:

```
# dnf needs-restarting
1107 : /usr/sbin/rsyslogd -n
1199 : -bash
```

The previous command lists only processes that require a restart, and not services. That is, you cannot restart processes listed using the **systemctl** utility. For example, the **bash** process in the output is terminated when the user that owns this process logs out.

8.2.2. Installing a security update provided by a specific advisory

In certain situations, you might want to install only specific updates. For example, if a specific service can be updated without scheduling a downtime, you can install security updates for only this service, and install the remaining security updates later.

Prerequisites

- A Red Hat subscription is attached to the host.

- You know the ID of the security advisory that you want to update.
For more information, see the [Identifying the security advisory updates](#) section.

Procedure

1. Install a specific advisory, for example:

```
# dnf update --advisory=RHSA-2019:0997
```

2. Alternatively, update to apply a specific advisory with a minimal version change by using the **dnf upgrade-minimal** command, for example:

```
# dnf upgrade-minimal --advisory=RHSA-2019:0997
```

3. Confirm and start the installation by pressing **y**:

```
...
Transaction Summary
=====
Upgrade ... Packages

Total download size: ... M
Is this ok [y/d/N]: y
```

4. Optional: List the processes that require a manual restart of the system after installing the updated packages:

```
# dnf needs-restarting
1107 : /usr/sbin/rsyslogd -n
1199 : -bash
```

The previous command lists only processes that require a restart, and not services. This means that you cannot restart all processes listed by using the **systemctl** utility. For example, the **bash** process in the output is terminated when the user that owns this process logs out.

8.2.3. Installing security updates automatically

You can configure your system so that it automatically downloads and installs all security updates.

Prerequisites

- A Red Hat subscription is attached to the host.
- The **dnf-automatic** package is installed.

Procedure

1. In the **/etc/dnf/automatic.conf** file, in the **[commands]** section, make sure the **upgrade_type** option is set to either **default** or **security**:

```
[commands]
# What kind of upgrade to perform:
# default                = all available upgrades
```

```
# security                = only the security upgrades  
upgrade_type = security
```

2. Enable and start the **systemd** timer unit:

```
# systemctl enable --now dnf-automatic-install.timer
```

Verification

1. Verify that the timer is enabled:

```
# systemctl status dnf-automatic-install.timer
```

Additional resources

- **dnf-automatic(8)** man page on your system