

–Supplemental Material–

Prune but Preserve: Decoupling Redundancy Suppression and Semantic Preservation for Efficient Time Series Clustering

Zexi Tan¹, Haoyi Xiao¹, Linhao Ouyang¹, Yiqun Zhang¹, Mengke Li², Yang Lu³ and Cuie Yang⁴

¹Guangdong University of Technology, ²Shenzhen University, ³Xiamen University,

⁴State Key Laboratory of Synthetical Automation for Process Industries
{tanzexi, xiaohaoyi1}@mails.gdut.edu.cn, hhdhlrrff@gmail.com, yqzhang@gdut.edu.cn
mengkeli@szu.edu.cn, luyang@xmu.edu.cn, yangcuie@mail.neu.edu.cn

I. BASELINE DESCRIPTIONS

The baseline set is organized around the empirical question studied in the main paper, namely at which stage redundancy should be reduced for unsupervised MTS clustering. It covers five streams: full-sequence representation learning, input-side token exclusion, partial-observation clustering, structural sub-sequence indexing, and foundation-style time series modeling. This design separates the benefit of source-level patch admission from gains brought by contrastive objectives, spectral modeling, graph structure, incomplete-view learning, or general temporal pretraining. For embedding-output baselines, k -means gives final assignments with the label-provided cluster number k , following the same unsupervised protocol as the main paper.

FCACC [1] is a fuzzy cluster-aware contrastive clustering method for time series. It constructs augmented views and introduces cluster-aware hard negatives to reduce the gap between instance contrast and cluster assignment. FCACC represents a clustering-oriented full-sequence baseline, testing whether cluster-aware contrast can reduce background influence without source-level patch admission. The official implementation is available at [FCACC](#).

TFMCC [2] performs time-frequency augmented multi-level contrastive clustering. Temporal and spectral augmentations enhance cluster-relevant patterns at different representation levels, but the complete sequence still enters the encoding pipeline. TFMCC tests whether temporal-spectral contrast can handle redundancy as effectively as pruning before encoder-side interaction. The official implementation is available at [TFMCC](#).

GTM [3] learns general time series representations through frequency-domain attention and shared temporal modeling. As GTM is designed for transferable representation rather than clustering-specific reduction, k -means is applied to its embeddings for final assignment. The comparison examines whether broad temporal pretraining can replace explicit patch

admission under redundancy-dominated MTS records. The official implementation is available at [GTM](#).

EMTC [4] is the closest input-side exclusion baseline for MTS clustering. It suppresses redundancy through importance-aware variate-wise masking and enriches retained content with multi-endogenous views. Its comparison with SIGMA directly tests whether confidence-calibrated admission, routed semantic restoration, and prototype-guided refinement improve clustering after sparse token admission. The official implementation is available at [EMTC](#).

FEI [5] introduces a frequency-domain information bottleneck by masking frequency components and predicting the corresponding embeddings. This design encourages informative spectral structure without manually defined positive and negative pairs. FEI serves as a spectral-reduction baseline, assessing whether patch-level admission still helps beyond frequency-oriented representation learning. The official implementation is available at [FEI](#).

MVCIMTS [6] is a contrastive multi-view clustering method for MTS. It treats variates as views and learns complementary information through multi-view contrast. Since its partial observation comes from variables instead of temporal patches, MVCIMTS tests whether variable-wise incompleteness brings the same clustering benefit as temporal admission followed by routed restoration. The official implementation is available at [MVCIMTS](#).

k -Graph [7] converts subsequences into graph representations and clusters graph-derived features. By building graphs across multiple subsequence lengths, k -Graph captures recurring local patterns and structural similarity. It provides a data-centric baseline for datasets whose clusters depend on shape correspondence or repeated subsequence structure. The official implementation is available at [\$k\$ -Graph](#).

TimesURL [8] is a universal self-supervised representation method for time series. It combines contrastive learning with temporal constraints to obtain general embeddings. In the prune-and-preserve comparison, TimesURL represents a

full-sequence self-supervised baseline because redundancy is not controlled through an admissible patch set. The official implementation is available at [TimesURL](#).

UNITS [9] is a unified multi-task time series model. It represents task information as tokens in a shared modeling framework and learns transferable representations across domains, temporal scales, and sampling patterns. UNITS provides a foundation-style baseline for testing whether task-unified pre-training is sufficient for redundancy-dominated MTS clustering. Its comparison with SIGMA highlights the role of source-level admission and routed semantic preservation in cluster-oriented representation learning. The official implementation is available at [UNITS](#).

II. IMPLEMENTATION DETAILS

All experiments follow the unsupervised clustering protocol in the main paper. For each UEA dataset, training and test splits are concatenated before clustering, and labels are accessed only for metric computation. Each experiment is repeated with five random seeds, and the mean and standard deviation are reported. This protocol keeps the supplemental material consistent with the main-paper evaluation and makes the supplementary tables comparable to the representative results in Section IV of the full paper.

SIGMA uses Confidence-Calibrated Masked Admission as the default admission strategy. In the masking ablation, source-level admission is removed while all other settings remain unchanged, isolating the effect of controlling patch participation before encoder-side feature interaction. Unless otherwise specified, no input perturbation is added, and Gaussian noise is introduced only in the robustness study.

For patch-level admission, the patch length is set to $\ell_p = 4$. Given $m = \lceil T/\ell_p \rceil$ patches, the retained ratio is $r_a = 0.5$, and the retained patch number is $m_a = \lceil r_a m \rceil$. Thus, the encoder processes a compact patch subset after admission. This setting reduces redundant patch participation before feature interaction while keeping enough temporal context for semantic restoration.

For endogenous-view representation learning, the number of views is $n_v = 2$. Each view encoder uses hidden dimension $d_h = 32$, and the fused clustering embedding has dimension $d_z = 64$. The prototype alignment temperature is $\tau_p = 0.1$. These values give SIGMA a compact representation budget while allowing admitted content to be organized into complementary latent views.

SIGMA is trained for $e_{\max} = 200$ epochs with mini-batch size $b = 64$. Adam is adopted with learning rate $\alpha = 0.001$. The loss weights are $\lambda_{\text{rec}} = 1.0$, $\lambda_{\text{orth}} = 0.1$, and $\lambda_{\text{pa}} = 1.0$, corresponding to reconstruction, inter-view orthogonality, and prototype alignment, respectively. Reconstruction anchors temporal content after admission, orthogonality discourages view homogenization, and prototype alignment sharpens the fused cluster space. Under this configuration, admission control, semantic restoration, and cluster refinement keep distinct roles within the prune-and-preserve pipeline.

III. SUPPLEMENTARY RESULTS

This section provides the full experimental record behind the condensed evaluation in the main paper. All results follow the unsupervised clustering protocol in Section II, so the added tables and figures serve as expanded checks rather than separate evaluation settings. The supplementary material includes complete 30-dataset results, Bonferroni-Dunn rank tests, detailed architecture and route ablations, loss-evolution curves, admission-based scalability tests, and additional robustness and compactness diagnostics.

The presentation follows the experimental questions in the main paper. Complete benchmark tables and rank tests extend Q1 from representative datasets to the full UEA benchmark. Architecture, route-internal, and newly added fine-grained mechanism ablations expand Q2 by tracing the contributions of admission, confidence calibration, endogenous-view generation, reconstruction routing, and prototype refinement at progressively finer levels. The additional CKA-based semantic preservation evaluation complements the prune-but-preserve analysis by examining whether compact representations retain representation-level structural information across representative clustering methods. Larger-scale and mask-rate tests further examine Q3, while the robustness diagnostics complement Q4 under noise perturbation and embedding compression. Together, these supplementary results provide more detailed evidence for the effectiveness, mechanism attribution, semantic preservation, efficiency, and robustness claims in the main paper without changing the evaluation protocol.

A. Complete Clustering Results on 30 UEA Datasets

TABLE I and TABLE II report the complete Q1 results on all 30 UEA datasets. ACC, F1, NMI, and ARI are computed under the same unsupervised protocol as the main paper. This subsection checks whether the trends reported on representative datasets extend to the full benchmark.

The complete records show that SIGMA performs well on datasets where cluster-related changes appear in compact fragments. For example, SIGMA reaches 0.9875 ACC and 0.9666 ARI on BasicMotions, obtains 0.8525 ACC and 0.7578 ARI on JapaneseVowels, and improves ACC and ARI to 0.6841 and 0.5305 on PenDigits. On SelfRegulationSCP1, SIGMA also gives the best ACC, F1, and ARI. These cases are consistent with the main-paper claim that reducing patch participation before encoding can preserve grouping cues.

The full tables also show that different datasets still favor different modeling biases. FCACC performs well on CharacterTrajectories, Cricket, NATOPS, and UWaveGestureLibrary. EMTC remains competitive on AtrialFibrillation, FingerMovements, HandMovementDirection, and MotorImagery. TFMCC leads several shape-sensitive or spectral-sensitive cases, including DuckDuckGeese, ERing, and RacketSports, and FEI performs well on Epilepsy, Libras, and PhonemeSpectra. Therefore, the full benchmark does not suggest that one design dominates every temporal pattern. Instead, Fig. 1 summarizes the aggregate behavior, where SIGMA obtains the lowest average rank on ACC, F1, NMI, and ARI. The complete tables

TABLE III
ABLATION STUDIES ON MODULE DESIGNS OF SIGMA, PART I. RED “+”
MARKS DEGRADATION FROM COMPLETE SIGMA.

Datasets (1-15)	Components		Metrics			
	CCMA	MEVG	ACC	F1	NMI	ARI
ArticulatoryWord Recognition	✓	✓	0.7329 ± 0.0395	0.7696 ± 0.0443	0.8037 ± 0.0246	0.6029 ± 0.0470
	✓	✓	0.7155 ± 0.0137	0.7451 ± 0.0215	0.7824 ± 0.0132	0.5728 ± 0.0248
	✓	✓	0.7739 ± 0.0437	0.7997 ± 0.0481	0.8255 ± 0.0189	0.6570 ± 0.0427
	✓	✓	0.6918 ± 0.0306	0.7336 ± 0.0245	0.7709 ± 0.0187	0.5517 ± 0.0369
	✓	✓	0.4933 ± 0.0327	0.4720 ± 0.0232	0.1215 ± 0.0474	0.0443 ± 0.0492
AtrialFibrillation	✓	✓	0.4867 ± 0.0163	0.4331 ± 0.0116	0.1050 ± 0.0047	0.0404 ± 0.0051
	✓	✓	0.4800 ± 0.0400	0.4681 ± 0.0854	0.1365 ± 0.0448	0.0664 ± 0.0421
	✓	✓	0.4600 ± 0.0327	0.4024 ± 0.0485	0.1000 ± 0.0087	0.0346 ± 0.0071
	✓	✓	0.9675 ± 0.0150	0.9671 ± 0.0154	0.9273 ± 0.0277	0.9169 ± 0.0363
	✓	✓	0.9825 ± 0.0127	0.9824 ± 0.0129	0.9497 ± 0.0366	0.9533 ± 0.0338
BasicMotions	✓	✓	0.8900 ± 0.1317	0.9203 ± 0.0746	0.8924 ± 0.0754	0.8361 ± 0.1360
	✓	✓	0.8700 ± 0.0100	0.9098 ± 0.0102	0.9138 ± 0.0287	0.8202 ± 0.0263
	✓	✓	0.7879 ± 0.0499	0.8091 ± 0.0408	0.8463 ± 0.0284	0.7214 ± 0.0576
	✓	✓	0.7824 ± 0.0547	0.8177 ± 0.0436	0.8416 ± 0.0367	0.7078 ± 0.0644
	✓	✓	0.7371 ± 0.0227	0.7610 ± 0.0346	0.8038 ± 0.0198	0.6417 ± 0.0303
Character Trajectories	✓	✓	0.7369 ± 0.0590	0.7699 ± 0.0708	0.8138 ± 0.0468	0.6556 ± 0.0750
	✓	✓	0.8244 ± 0.0255	0.8463 ± 0.0115	0.8522 ± 0.0167	0.7259 ± 0.0299
	✓	✓	0.8489 ± 0.0349	0.8739 ± 0.0420	0.8737 ± 0.0444	0.7589 ± 0.0659
	✓	✓	0.7811 ± 0.0658	0.8191 ± 0.0588	0.8346 ± 0.0364	0.6817 ± 0.0702
	✓	✓	0.8078 ± 0.0114	0.8292 ± 0.0241	0.8376 ± 0.0130	0.6937 ± 0.0195
Cricket	✓	✓	0.3900 ± 0.0141	0.3730 ± 0.0193	0.1749 ± 0.0375	0.0795 ± 0.0345
	✓	✓	0.3700 ± 0.0179	0.3600 ± 0.0253	0.1143 ± 0.0234	0.0526 ± 0.0108
	✓	✓	0.3280 ± 0.0421	0.2966 ± 0.0425	0.0869 ± 0.0246	0.0196 ± 0.0205
	✓	✓	0.3680 ± 0.0194	0.3449 ± 0.0235	0.1229 ± 0.0145	0.0306 ± 0.0112
	✓	✓	0.7307 ± 0.0629	0.7287 ± 0.0680	0.5996 ± 0.0590	0.5124 ± 0.0760
ERing	✓	✓	0.6867 ± 0.0669	0.7180 ± 0.0341	0.5238 ± 0.0426	0.5008 ± 0.0669
	✓	✓	0.7300 ± 0.0485	0.7113 ± 0.0475	0.5198 ± 0.0400	0.5026 ± 0.0569
	✓	✓	0.7173 ± 0.0259	0.7082 ± 0.0253	0.5112 ± 0.0390	0.5033 ± 0.0415
	✓	✓	0.4193 ± 0.0788	0.3646 ± 0.0438	0.1612 ± 0.0594	0.1515 ± 0.0726
	✓	✓	0.4131 ± 0.0101	0.3546 ± 0.0347	0.1196 ± 0.0211	0.1907 ± 0.0156
EigenWorms	✓	✓	0.4125 ± 0.0451	0.3577 ± 0.0359	0.1329 ± 0.0256	0.1469 ± 0.0344
	✓	✓	0.3822 ± 0.0462	0.3397 ± 0.0392	0.0713 ± 0.0600	0.1368 ± 0.0716
	✓	✓	0.4655 ± 0.0229	0.4573 ± 0.0233	0.2355 ± 0.0362	0.1668 ± 0.0336
	✓	✓	0.4640 ± 0.0291	0.4448 ± 0.0300	0.2217 ± 0.0332	0.1511 ± 0.0259
	✓	✓	0.4420 ± 0.0368	0.4505 ± 0.0382	0.2330 ± 0.0451	0.1551 ± 0.0279
Epilepsy	✓	✓	0.3829 ± 0.0238	0.4047 ± 0.0243	0.2118 ± 0.0298	0.1637 ± 0.0212
	✓	✓	0.3061 ± 0.0208	0.2766 ± 0.0066	0.0199 ± 0.0156	0.0108 ± 0.0123
	✓	✓	0.3015 ± 0.0099	0.2577 ± 0.0082	0.0114 ± 0.0033	0.0049 ± 0.0030
	✓	✓	0.3058 ± 0.0183	0.2581 ± 0.0252	0.0184 ± 0.0066	0.0104 ± 0.0062
	✓	✓	0.2950 ± 0.0092	0.2397 ± 0.0108	0.0124 ± 0.0061	0.0045 ± 0.0039
EthanolConcentration	✓	✓	0.5107 ± 0.0042	0.5100 ± 0.0049	0.0004 ± 0.0003	0.0004 ± 0.0004
	✓	✓	0.5051 ± 0.0028	0.5050 ± 0.0028	0.0001 ± 0.0001	0.0000 ± 0.0001
	✓	✓	0.5101 ± 0.0023	0.5092 ± 0.0027	0.0003 ± 0.0001	0.0003 ± 0.0002
	✓	✓	0.5063 ± 0.0076	0.5061 ± 0.0077	0.0003 ± 0.0005	0.0003 ± 0.0007
	✓	✓	0.5188 ± 0.0085	0.5142 ± 0.0086	0.0013 ± 0.0007	0.0006 ± 0.0010
FingerMovements	✓	✓	0.5168 ± 0.0101	0.5123 ± 0.0056	0.0013 ± 0.0015	0.0008 ± 0.0017
	✓	✓	0.5168 ± 0.0128	0.5125 ± 0.0160	0.0013 ± 0.0014	0.0005 ± 0.0019
	✓	✓	0.5130 ± 0.0074	0.5127 ± 0.0073	0.0006 ± 0.0007	0.0003 ± 0.0002
	✓	✓	0.3333 ± 0.0143	0.3298 ± 0.0171	0.0205 ± 0.0063	0.0060 ± 0.0052
	✓	✓	0.3051 ± 0.0154	0.3027 ± 0.0162	0.0139 ± 0.0036	0.0008 ± 0.0029
HandMovement Direction	✓	✓	0.3179 ± 0.0249	0.3148 ± 0.0246	0.0201 ± 0.0119	0.0049 ± 0.0111
	✓	✓	0.3060 ± 0.0126	0.3034 ± 0.0116	0.0144 ± 0.0029	0.0011 ± 0.0025
	✓	✓	0.2386 ± 0.0181	0.2433 ± 0.0195	0.3461 ± 0.0286	0.1006 ± 0.0180
	✓	✓	0.2102 ± 0.0132	0.2103 ± 0.0137	0.3030 ± 0.0188	0.0770 ± 0.0111
	✓	✓	0.2444 ± 0.0113	0.2460 ± 0.0156	0.3503 ± 0.0160	0.1050 ± 0.0109
Handwriting	✓	✓	0.2224 ± 0.0130	0.2234 ± 0.0113	0.3212 ± 0.0209	0.0852 ± 0.0100
	✓	✓	0.6636 ± 0.0589	0.5679 ± 0.0507	0.0391 ± 0.0232	0.0689 ± 0.0404
	✓	✓	0.5826 ± 0.0369	0.5002 ± 0.0271	0.0438 ± 0.0108	0.0952 ± 0.0277
	✓	✓	0.5841 ± 0.0410	0.5474 ± 0.0747	0.0328 ± 0.0106	0.0620 ± 0.0591
	✓	✓	0.5066 ± 0.0091	0.4463 ± 0.0947	0.0365 ± 0.0108	0.0346 ± 0.0516

In the first stage, the loss decreases on all six datasets, indicating that admitted patches can support sequence recovery after part of the input is removed. After $\mathcal{L} * \text{orth}$ and $\mathcal{L} * \text{pa}$ enter training, several curves rise or fluctuate for a short period because the objective no longer measures reconstruction alone. The model begins to adjust view diversity and prototype alignment, so a temporary increase is expected before the route-level terms settle. In later epochs, Duck-DuckGeese, FaceDetection, Heartbeat, JapaneseVowels, and PEMS-SF show smoother refinement. EthanolConcentration has a wider variance band near the transition, but the curve also becomes controlled afterward. The additional curves support the staged training order by showing that route-level refinement does not cause persistent divergence.

D. Mask-Rate Scalability Analysis

The main paper reports runtime and GPU memory when N , T , and D increase. This subsection checks the source of the runtime saving more directly. If admission reduces encoder-side computation, then increasing the mask rate should lower

TABLE IV
ABLATION STUDIES ON MODULE DESIGNS OF SIGMA, PART II. RED “+”
MARKS DEGRADATION FROM COMPLETE SIGMA.

Datasets (16-30)	Components		Metrics			
	CCMA	MEVG	ACC	F1	NMI	ARI
InsectWingbeat	✓	✓	0.1344 ± 0.0023	0.1202 ± 0.0033	0.0153 ± 0.0012	0.0061 ± 0.0007
	✓	✓	0.1351 ± 0.0015	0.1206 ± 0.0036	0.0147 ± 0.0008	0.0064 ± 0.0001
	✓	✓	0.1304 ± 0.0032	0.1115 ± 0.0076	0.0132 ± 0.0011	0.0048 ± 0.0013
	✓	✓	0.1323 ± 0.0039	0.1099 ± 0.0069	0.0139 ± 0.0017	0.0050 ± 0.0011
JapaneseVowels	✓	✓	0.8647 ± 0.0447	0.8626 ± 0.0432	0.8195 ± 0.0260	0.7682 ± 0.0565
	✓	✓	0.8162 ± 0.0393	0.8557 ± 0.0416	0.8044 ± 0.0126	0.7321 ± 0.0429
	✓	✓	0.8050 ± 0.0347	0.8440 ± 0.0294	0.8220 ± 0.0239	0.7847 ± 0.0385
	✓	✓	0.7800 ± 0.0306	0.7802 ± 0.0270	0.8140 ± 0.0272	0.7648 ± 0.0553
LSST	✓	✓	0.2042 ± 0.0087	0.1805 ± 0.0063	0.1456 ± 0.0063	0.0555 ± 0.0044
	✓	✓	0.2018 ± 0.0106	0.1753 ± 0.0156	0.1375 ± 0.0125	0.0361 ± 0.0074
	✓	✓	0.1996 ± 0.0131	0.1792 ± 0.0080	0.1358 ± 0.0022	0.0267 ± 0.0093
	✓	✓	0.1748 ± 0.0134	0.1624 ± 0.0031	0.1053 ± 0.0062	0.0189 ± 0.0052
Libras	✓	✓	0.3156 ± 0.0374	0.3162 ± 0.0405	0.4101 ± 0.0302	0.1502 ± 0.0253
	✓	✓	0.2839 ± 0.0032	0.2979 ± 0.0079	0.3439 ± 0.0107	0.1012 ± 0.0057
	✓	✓	0.3272 ± 0.0278	0.3460 ± 0.0497	0.4212 ± 0.0370	0.1600 ± 0.0271
	✓	✓	0.2883 ± 0.0069	0.2959 ± 0.0148	0.3481 ± 0.0125	0.1084 ± 0.0080
MotorImagery	✓	✓	0.5323 ± 0.0147	0.5271 ± 0.0154	0.0039 ± 0.0034	0.0025 ± 0.0046
	✓	✓	0.5260 ± 0.0178	0.5196 ± 0.0260	0.0053 ± 0.0044	0.0041 ± 0.0050
	✓	✓	0.5307 ± 0.0224	0.5249 ± 0.0284	0.0042 ± 0.0048	0.0032 ± 0.0066
	✓	✓	0.5238 ± 0.0115	0.4965 ± 0.0034	0.0035 ± 0.0038	0.0007 ± 0.0027
NATOPS	✓	✓	0.4756 ± 0.0180	0.4638 ± 0.0129	0.4697 ± 0.0383	0.3103 ± 0.0385
	✓	✓	0.4533 ± 0.0457	0.4550 ± 0.0494	0.4481 ± 0.0457	0.2797 ± 0.0460
	✓	✓	0.4528 ± 0.0511	0.4554 ± 0.0583	0.4444 ± 0.0859	0.2844 ± 0.0753
	✓	✓	0.4750 ± 0.0072	0.4097 ± 0.0059	0.4053 ± 0.0118	0.3082 ± 0.0133
PEMS-SF	✓	✓	0.3905 ± 0.0724	0.4364 ± 0.0969	0.3625 ± 0.1185	0.2028 ± 0.0839
	✓	✓	0.2768 ± 0.0192	0.2752 ± 0.0175	0.2469 ± 0.0372	0.1170 ± 0.0271
	✓	✓	0.3159 ± 0.0708	0.3722 ± 0.0819	0.3329 ± 0.0928	0.1465 ± 0.0908
	✓	✓	0.2550 ± 0.0164	0.2553 ± 0.0131	0.2111 ± 0.0293	0.0900 ± 0.0244
PenDigits	✓	✓	0.6796 ± 0.0497	0.6724 ± 0.0488	0.6440 ± 0.0381	0.5249 ± 0.0488
	✓	✓	0.5957 ± 0.0208	0.5949 ± 0.0207	0.5736 ± 0.0164	0.4065 ± 0.0264
	✓	✓	0.6614 ± 0.0378	0.6457 ± 0.0436	0.6188 ± 0.0319	0.4953 ± 0.0431
	✓	✓	0.5954 ± 0.0262	0.5955 ± 0.0250	0.5702 ± 0.0197	0.4034 ± 0.0284
PhonemeSpectra	✓	✓	0.1125 ± 0.0040	0.1119 ± 0.0039	0.1765 ± 0.0084	0.0333 ± 0.0020
	✓	✓	0.1044 ± 0.0026	0.1061 ± 0.0013	0.1636 ± 0.0047	0.0296 ± 0.0047
	✓	✓	0.1044 ± 0.0018	0.1029 ± 0.0008	0.1576 ± 0.0107	0.0277 ± 0.0029
	✓	✓	0.1036 ± 0.0016	0.1027 ± 0.0021	0.1568 ± 0.0039	0.0289 ± 0.0014
RacketSports	✓	✓	0.5908 ± 0.0704	0.5918 ± 0.0700	0.3431 ± 0.0775	0.2754 ± 0.0886
	✓	✓	0.5330 ± 0.0454	0.5263 ± 0.0497	0.3037 ± 0.0637	0.2443 ± 0.0751
	✓	✓	0.5340 ± 0.0979	0.5410 ± 0.0966	0.3100 ± 0.1019	0.2449 ± 0.1091
	✓	✓	0.4026 ± 0.0949	0.4012 ± 0.0964	0.2912 ± 0.1121	0.1290 ± 0.1141
SelfRegulation SCP1	✓	✓	0.7747 ± 0.0140	0.7738 ± 0.0136	0.2371 ± 0.0269	0.3014 ± 0.0296
	✓	✓	0.7647 ± 0.0254	0.7635 ± 0.0258	0.2224 ± 0.0410	0.2816 ± 0.0510
	✓	✓	0.7740 ± 0.0170	0.7730 ± 0.0160	0.2387 ± 0.0412	0.3002 ± 0.0376
	✓	✓	0.7647 ± 0.0103	0.7644 ± 0.0099	0.2150 ± 0.0213	0.2794 ± 0.0224
SelfRegulation SCP2	✓	✓	0.5253 ± 0.0151	0.5162 ± 0.0079	0.0036 ± 0.0050	0.0010 ± 0.0042
	✓	✓	0.5279 ± 0.0107	0.5270 ± 0.0093	0.0026 ± 0.0022	0.0010 ± 0.0029
	✓	✓	0.5147 ± 0.0106	0.5141 ± 0.0105	0.0010 ± 0.0013	0.0010 ± 0.0017
	✓	✓	0.5142 ± 0.0032	0.5141 ± 0.0033	0.0006 ± 0.0003	0.0008 ± 0.0004
Spoken ArabicDigits	✓	✓	0.4260 ± 0.0202	0.4328 ± 0.0168	0.3868 ± 0.0165	0.2365 ± 0.0194
	✓	✓	0.3712 ± 0.0196	0.3778 ± 0.0219	0.3407 ± 0.0153	0.1844 ± 0.0124
	✓	✓	0.4177 ± 0.0191	0.4002 ± 0.0231	0.3457 ± 0.0383	0.1802 ± 0.0395
	✓	✓	0.3637 ± 0.0203	0.3691 ± 0.0204	0.3226 ± 0.0119	0.1621 ± 0.0086
StandWalkJump	✓	✓	0.4000 ± 0.0637	0.3740 ± 0.0724	0.0441 ± 0.0480	0.0171 ± 0.0522
	✓	✓	0.3800 ± 0.0277	0.3549 ± 0.0372	0.0408 ± 0.0276	0.0133 ± 0.0277
	✓	✓	0.3822 ± 0.0502	0.3544 ± 0.0506	0.0417 ± 0.0306	0.0135 ± 0.0349
	✓	✓	0.3148 ± 0.0544	0.2852 ± 0.0626	0.0347 ± 0.0419	0.0101 ± 0.0161
UWaveGesture Library	✓	✓	0.4164 ± 0.0435	0.4043 ± 0.0445	0.3456 ± 0.0479	0.1996 ± 0.0452
	✓	✓	0.3373 ± 0.0086	0.3156 ± 0.0090	0.1918 ± 0.0200	0.0954 ± 0.0114
	✓	✓	0.3945 ± 0.0411	0.3881 ± 0.0581	0.2768 ± 0.0378	0.1487 ± 0.0261
	✓	✓	0.3127 ± 0.0232	0.2967 ± 0.0177	0.1782 ± 0.0133	0.0860 ± 0.0156

TABLE V
ABLATION STUDIES ON ROUTE DESIGNS OF SIGMA, PART I. RED “+” MARKS DEGRADATION FROM COMPLETE SIGMA.

Datasets (1-15)	Components		Metrics				
	Recon	Contra	ACC	F1	NMI	ARI	
ArticulatoryWord Recognition	✓	✓	0.7329 ± 0.0395	0.7696 ± 0.0443	0.8037 ± 0.0246	0.6029 ± 0.0470	
	✓	✓	0.6035 ± 0.0317	0.6212 ± 0.0261	0.7016 ± 0.0278	0.4614 ± 0.0399	
	✓	✓	0.6247 ± 0.0562	0.6514 ± 0.0558	0.6747 ± 0.0426	0.5445 ± 0.0793	
	✓	✓	0.1419 ± 0.0485	0.2366 ± 0.0323	0.2485 ± 0.0639	0.0353 ± 0.0299	
AtrialFibrillation	✓	✓	0.4933 ± 0.0327	0.4720 ± 0.0232	0.1215 ± 0.0474	0.0443 ± 0.0492	
	✓	✓	0.4933 ± 0.0249	0.4763 ± 0.0291	0.0833 ± 0.0242	0.0169 ± 0.0203	
	✓	✓	0.4733 ± 0.0389	0.4520 ± 0.0542	0.0765 ± 0.0312	0.0190 ± 0.0333	
	✓	✓	0.4600 ± 0.0389	0.4518 ± 0.0598	0.0937 ± 0.0356	0.0212 ± 0.0325	
BasicMotions	✓	✓	0.9675 ± 0.0150	0.9671 ± 0.0154	0.9273 ± 0.0277	0.9169 ± 0.0363	
	✓	✓	0.9050 ± 0.1226	0.9319 ± 0.0784	0.9161 ± 0.0911	0.8633 ± 0.1575	
	✓	✓	0.6600 ± 0.0366	0.8105 ± 0.0355	0.7754 ± 0.0499	0.6063 ± 0.0482	
	✓	✓	0.5100 ± 0.0289	0.6355 ± 0.0519	0.5518 ± 0.0478	0.3927 ± 0.0402	
Character Trajectories	✓	✓	0.7879 ± 0.0499	0.8091 ± 0.0408	0.8463 ± 0.0284	0.7214 ± 0.0576	
	✓	✓	0.6714 ± 0.0832	0.7199 ± 0.0942	0.7443 ± 0.0645	0.5830 ± 0.0923	
	✓	✓	0.7389 ± 0.0708	0.7674 ± 0.0674	0.8189 ± 0.0503	0.6750 ± 0.0821	
	✓	✓	0.0651 ± 0.0000	0.1222 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
Cricket	✓	✓	0.8244 ± 0.0255	0.8463 ± 0.0115	0.8522 ± 0.0167	0.7259 ± 0.0299	
	✓	✓	0.7900 ± 0.1095	0.8001 ± 0.1052	0.8279 ± 0.0699	0.6912 ± 0.1158	
	✓	✓	0.7511 ± 0.0708	0.7828 ± 0.0339	0.7682 ± 0.0476	0.5964 ± 0.0836	
	✓	✓	0.1000 ± 0.0333	0.2018 ± 0.0960	0.0721 ± 0.1442	0.0121 ± 0.0241	
DuckDuckGeese	✓	✓	0.3900 ± 0.0141	0.3730 ± 0.0193	0.1749 ± 0.0375	0.0795 ± 0.0345	
	✓	✓	0.4740 ± 0.0546	0.4690 ± 0.0553	0.2439 ± 0.0457	0.1618 ± 0.0523	
	✓	✓	0.3880 ± 0.0306	0.3682 ± 0.0377	0.1562 ± 0.0375	0.0621 ± 0.0248	
	✓	✓	0.2000 ± 0.0000	0.3333 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
ERing	✓	✓	0.7307 ± 0.0629	0.7287 ± 0.0680	0.5996 ± 0.0590	0.5124 ± 0.0760	
	✓	✓	0.6533 ± 0.0419	0.6553 ± 0.0421	0.5735 ± 0.0240	0.4854 ± 0.0353	
	✓	✓	0.6020 ± 0.0937	0.6006 ± 0.0951	0.5408 ± 0.0702	0.4688 ± 0.1070	
	✓	✓	0.1667 ± 0.0000	0.2857 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
EigenWorms	✓	✓	0.4193 ± 0.0788	0.3646 ± 0.0438	0.1612 ± 0.0594	0.1515 ± 0.0726	
	✓	✓	0.4556 ± 0.0523	0.4150 ± 0.0632	0.2774 ± 0.0369	0.2479 ± 0.0381	
	✓	✓	0.3382 ± 0.0317	0.3009 ± 0.0439	0.0843 ± 0.0295	0.0512 ± 0.0158	
	✓	✓	0.2247 ± 0.0000	0.2962 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
Epilepsy	✓	✓	0.4655 ± 0.0229	0.4573 ± 0.0233	0.2355 ± 0.0362	0.1668 ± 0.0336	
	✓	✓	0.5716 ± 0.0429	0.5746 ± 0.0356	0.3998 ± 0.0509	0.3182 ± 0.0499	
	✓	✓	0.4320 ± 0.0292	0.4259 ± 0.0276	0.2047 ± 0.0333	0.1442 ± 0.0279	
	✓	✓	0.4291 ± 0.0352	0.4217 ± 0.0355	0.1670 ± 0.0517	0.1224 ± 0.0370	
Ethanol Concentration	✓	✓	0.3061 ± 0.0208	0.2766 ± 0.0066	0.0199 ± 0.0156	0.0108 ± 0.0123	
	✓	✓	0.2916 ± 0.0080	0.2541 ± 0.0078	0.0129 ± 0.0041	0.0032 ± 0.0014	
	✓	✓	0.3015 ± 0.0143	0.2759 ± 0.0252	0.0108 ± 0.0187	0.0044 ± 0.0006	
	✓	✓	0.1179 ± 0.0130	0.1277 ± 0.0507	0.0042 ± 0.0022	0.0038 ± 0.0027	
FaceDetection	✓	✓	0.5107 ± 0.0042	0.5100 ± 0.0049	0.0004 ± 0.0003	0.0004 ± 0.0004	
	✓	✓	0.5090 ± 0.0055	0.5086 ± 0.0056	0.0003 ± 0.0003	0.0003 ± 0.0004	
	✓	✓	0.5000 ± 0.0000	0.4667 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
	✓	✓	0.5000 ± 0.0000	0.4667 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
FingerMovements	✓	✓	0.5188 ± 0.0085	0.5142 ± 0.0086	0.0013 ± 0.0007	0.0006 ± 0.0010	
	✓	✓	0.5135 ± 0.0097	0.5114 ± 0.0111	0.0008 ± 0.0009	0.0013 ± 0.0012	
	✓	✓	0.5031 ± 0.0102	0.5088 ± 0.0102	0.0009 ± 0.0002	0.0002 ± 0.0016	
	✓	✓	0.5000 ± 0.0000	0.4667 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	
HandMovement Direction	✓	✓	0.3333 ± 0.0143	0.3298 ± 0.0171	0.0205 ± 0.0063	0.0060 ± 0.0052	
	✓	✓	0.3077 ± 0.0162	0.3061 ± 0.0171	0.0148 ± 0.0062	0.0005 ± 0.0053	
	✓	✓	0.3111 ± 0.0208	0.3077 ± 0.0221	0.0215 ± 0.0075	0.0053 ± 0.0072	
	✓	✓	0.3068 ± 0.0068	0.2901 ± 0.0134	0.0201 ± 0.0043	0.0021 ± 0.0020	
Handwriting	✓	✓	0.2386 ± 0.0181	0.2433 ± 0.0195	0.3461 ± 0.0286	0.1006 ± 0.0180	
	✓	✓	0.1706 ± 0.0061	0.1741 ± 0.0083	0.2227 ± 0.0045	0.0385 ± 0.0019	
	✓	✓	0.2054 ± 0.0071	0.2071 ± 0.0059	0.2809 ± 0.0091	0.0663 ± 0.0054	
	✓	✓	0.1428 ± 0.0060	0.1408 ± 0.0057	0.1813 ± 0.0062	0.0217 ± 0.0024	
Heartbeat	✓	✓	0.6636 ± 0.0589	0.5679 ± 0.0507	0.0391 ± 0.0232	0.0689 ± 0.0404	
	✓	✓	0.5628 ± 0.0376	0.5053 ± 0.0802	0.0459 ± 0.0155	0.0065 ± 0.0412	
	✓	✓	0.5002 ± 0.0176	0.5537 ± 0.1522	0.0170 ± 0.0068	0.0161 ± 0.0034	
	✓	✓	0.5213 ± 0.0000	0.4381 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000	

TABLE VI
ABLATION STUDIES ON ROUTE DESIGNS OF SIGMA, PART II. RED “+” MARKS DEGRADATION FROM COMPLETE SIGMA.

Datasets (16-30)	Components		Metrics			
	Recon	Contra	ACC	F1	NMI	ARI
InsectWingbeat	✓	✓	0.1344 ± 0.0023	0.1202 ± 0.0033	0.0153 ± 0.0012	0.0061 ± 0.0007
	✓	✓	0.1206 ± 0.0063	0.1104 ± 0.0111	0.0053 ± 0.0027	0.0025 ± 0.0014
	✓	✓	0.1000 ± 0.0000	0.1018 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
	✓	✓	0.1000 ± 0.0000	0.1018 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
JapaneseVowels	✓	✓	0.8647 ± 0.0447	0.8626 ± 0.0432	0.8195 ± 0.0260	0.7682 ± 0.0565
	✓	✓	0.8059 ± 0.0310	0.8042 ± 0.0270	0.7824 ± 0.0315	0.7327 ± 0.0522
	✓	✓	0.6441 ± 0.1450	0.6632 ± 0.1467	0.5833 ± 0.1473	0.4328 ± 0.1564
	✓	✓	0.1844 ± 0.0000	0.3113 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
LSST	✓	✓	0.2042 ± 0.0087	0.1805 ± 0.0063	0.1456 ± 0.0063	0.0555 ± 0.0044
	✓	✓	0.3362 ± 0.0017	0.2228 ± 0.0094	0.1699 ± 0.0142	0.0714 ± 0.0062
	✓	✓	0.1969 ± 0.0139	0.1776 ± 0.0102	0.1427 ± 0.0084	0.0537 ± 0.0075
	✓	✓	0.1155 ± 0.0000	0.0797 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
Libras	✓	✓	0.3156 ± 0.0374	0.3162 ± 0.0405	0.4101 ± 0.0302	0.1502 ± 0.0253
	✓	✓	0.3000 ± 0.0283	0.3072 ± 0.0231	0.3518 ± 0.0285	0.1016 ± 0.0259
	✓	✓	0.3061 ± 0.0210	0.3003 ± 0.0315	0.3402 ± 0.0261	0.1022 ± 0.0231
	✓	✓	0.2644 ± 0.0235	0.2673 ± 0.0222	0.3222 ± 0.0456	0.0927 ± 0.0307
MotorImagery	✓	✓	0.5323 ± 0.0147	0.5271 ± 0.0154	0.0039 ± 0.0034	0.0025 ± 0.0046
	✓	✓	0.5079 ± 0.0044	0.4726 ± 0.0036	0.0004 ± 0.0004	0.0016 ± 0.0004
	✓	✓	0.5270 ± 0.0074	0.5048 ± 0.0179	0.0034 ± 0.0023	0.0009 ± 0.0017
	✓	✓	0.1000 ± 0.0313	0.2218 ± 0.0950	0.0631 ± 0.0442	0.0221 ± 0.0235
NATOPS	✓	✓	0.4756 ± 0.0180	0.4638 ± 0.0129	0.4697 ± 0.0383	0.3103 ± 0.0385
	✓	✓	0.4972 ± 0.0478	0.4940 ± 0.0434	0.4796 ± 0.0594	0.3245 ± 0.0508
	✓	✓	0.4328 ± 0.0428	0.4242 ± 0.0431	0.3578 ± 0.0955	0.2377 ± 0.0650
	✓	✓	0.1967 ± 0.0600	0.3526 ± 0.1337	0.0770 ± 0.1539	0.0221 ± 0.0441
PEMS-SF	✓	✓	0.3905 ± 0.0724	0.4364 ± 0.0969	0.3625 ± 0.1185	0.2028 ± 0.0839
	✓	✓	0.2368 ± 0.0216	0.2476 ± 0.0355	0.1705 ± 0.0511	0.0609 ± 0.0218
	✓	✓	0.2700 ± 0.0273	0.2785 ± 0.0369	0.1930 ± 0.0781	0.0771 ± 0.0412
	✓	✓	0.1477 ± 0.0000	0.2574 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
PenDigits	✓	✓	0.6796 ± 0.0497	0.6724 ± 0.0488	0.6440 ± 0.0381	0.5249 ± 0.0488
	✓	✓	0.7139 ± 0.0446	0.7030 ± 0.0448	0.6472 ± 0.0277	0.5420 ± 0.0420
	✓	✓	0.1041 ± 0.0000	0.1885 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
	✓	✓	0.1041 ± 0.0000	0.1885 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
PhonemeSpectra	✓	✓	0.1125 ± 0.0040	0.1119 ± 0.0039	0.1765 ± 0.0084	0.0333 ± 0.0020
	✓	✓	0.0985 ± 0.0017	0.0967 ± 0.0012	0.1443 ± 0.0051	0.0243 ± 0.0012
	✓	✓	0.0256 ± 0.0000	0.0500 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
	✓	✓	0.0256 ± 0.0000	0.0500 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
RacketSports	✓	✓	0.5908 ± 0.0704	0.5918 ± 0.0700	0.3431 ± 0.0775	0.2754 ± 0.0886
	✓	✓	0.6389 ± 0.0424	0.6436 ± 0.0345	0.4214 ± 0.0229	0.3526 ± 0.0483
	✓	✓	0.4488 ± 0.0172	0.4449 ± 0.0185	0.1929 ± 0.0490	0.1187 ± 0.0352
	✓	✓	0.4244 ± 0.0367	0.3947 ± 0.0725	0.1550 ± 0.0234	0.1061 ± 0.0245
Self RegulationSCP1	✓	✓	0.7747 ± 0.0140	0.7738 ± 0.0136	0.2371 ± 0.0269	0.3014 ± 0.0296
	✓	✓	0.7458 ± 0.0132	0.7421 ± 0.0156	0.2011 ± 0.0274	0.2411 ± 0.0261
	✓	✓	0.7337 ± 0.0714	0.7246 ± 0.0859	0.1956 ± 0.0777	0.2376 ± 0.1041
	✓	✓	0.7480 ± 0.0175	0.7477 ± 0.0176	0.1878 ± 0.0261	0.2458 ± 0.0341
Self RegulationSCP2	✓	✓	0.5253 ± 0.0151	0.5162 ± 0.0079	0.0036 ± 0.0050	0.0010 ± 0.0042
	✓	✓	0.5347 ± 0.0139	0.5325 ± 0.0152	0.0041 ± 0.0021	0.0030 ± 0.0029
	✓	✓	0.5158 ± 0.0173	0.5106 ± 0.0157	0.0017 ± 0.0031	0.0003 ± 0.0040
	✓	✓	0.5200 ± 0.0061	0.5191 ± 0.0059	0.0013 ± 0.0007	0.0009 ± 0.0009
Spoken ArabicDigits	✓	✓	0.4260 ± 0.0202	0.4328 ± 0.0168	0.3868 ± 0.0165	0.2365 ± 0.0194
	✓	✓	0.3631 ± 0.0512	0.3642 ± 0.0468	0.3212 ± 0.0486	0.1523 ± 0.0453
	✓	✓	0.1000 ± 0.0000	0.1819 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
	✓	✓	0.1000 ± 0.0000	0.1819 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000
StandWalkJump	✓	✓	0.4000 ± 0.0637	0.3740 ± 0.0724	0.0441 ± 0.0480	0.0171 ± 0.0522
	✓	✓	0.3593 ± 0.0378	0.3537 ± 0.0361	0.0330 ± 0.0194	0.0124 ± 0.0251
	✓	✓	0.3519 ± 0.0363	0.3355 ± 0.0497	0.0343 ± 0.0236	0.0138 ± 0.0199
	✓	✓	0.3296 ± 0.0181	0.2740 ± 0.0214	0.0124 ± 0.0506	0.0016 ± 0.0243
UWaveGesture Library	✓	✓	0.4164 ± 0.0435	0.4043 ± 0.0445	0.3456 ± 0.0479	0.1996 ± 0.0452
	✓	✓	0.4023 ± 0.0342	0.3992 ± 0.0359	0.2887 ± 0.0371	0.1684 ± 0.0280
	✓	✓	0.6318 ± 0.0456	0.6520 ± 0.0381	0.5779 ± 0.0160	0.4497 ± 0.0166
	✓	✓	0.1250 ± 0.0000	0.2222 ± 0.0000	0.0000 ± 0.0000	0.0000 ± 0.0000




Fig. 2. Additional loss-evolution curves during SIGMA training on six UEA datasets. Each curve reports the mean loss across five random seeds, and the shaded band denotes standard deviation. Panels (a) to (f) correspond to DuckDuckGeese, EthanolConcentration, FaceDetection, Heartbeat, JapaneseVowels, and PEMS-SF, respectively. Vertical dashed lines mark the reconstruction-only, dual-route, and prototype-guided refinement stages.




Fig. 3. Scalability under increasing mask rates. The three panels vary N , T , and D , respectively. For each setting, execution time is normalized by the cost at zero mask rate. Shaded bands denote standard deviation, and endpoint annotations report the reduction at 90% mask rate.




Fig. 4. **Robustness and compactness diagnostics.** F1-score on AtrialFibrillation and Libras under (a) increasing Gaussian noise and (b) reduced embedding dimensions from 64 to 4.

reliable clustering, we introduce Centered Kernel Alignment (CKA) [10], a representation-similarity measure that compares the relational structure of learned representation spaces without relying on reconstruction loss or clustering labels. Higher CKA indicates stronger preservation of representation-level structure, providing a complementary criterion to the reconstruction-derived SF used in the main paper. TABLE VII compares SIGMA with FCACC, TFMCC, and EMTC on seven representative datasets under the same evaluation protocol. SIGMA achieves the highest CKA on all seven datasets, with an average score of 0.5163, compared with 0.3758 for FCACC, 0.3706 for TFMCC, and 0.2049 for EMTC. The advantage is particularly clear on ERing, JapaneseVowels, and SelfRegulationSCP1, where SIGMA reaches 0.6478, 0.8197, and 0.6633, respectively. These results provide loss-independent evidence that the compact representations produced after source-side admission retain substantially more

TABLE VII

CKA-BASED SEMANTIC PRESERVATION COMPARISON ON SEVEN REPRESENTATIVE DATASETS. HIGHER CKA INDICATES STRONGER REPRESENTATION-LEVEL STRUCTURAL CONSISTENCY, AND **BOLD** DENOTES THE BEST MEAN RESULT.

Datasets	FCACC	TFMCC	EMTC	SIGMA (ours)
ArticularyWordRecognition	0.3591 $\pm$ 0.0199	0.3366 $\pm$ 0.0092	0.1254 $\pm$ 0.0429	0.4799 $\pm$ 0.0379
BasicMotions	0.2998 $\pm$ 0.0030	0.2789 $\pm$ 0.0560	0.2028 $\pm$ 0.0210	0.3329 $\pm$ 0.0036
CharacterTrajectories	0.3134 $\pm$ 0.0097	0.3346 $\pm$ 0.0216	0.1772 $\pm$ 0.1083	0.3887 $\pm$ 0.0504
ERing	0.4369 $\pm$ 0.0029	0.3835 $\pm$ 0.0132	0.4001 $\pm$ 0.1442	0.6478 $\pm$ 0.0198
JapaneseVowels	0.6933 $\pm$ 0.0219	0.6136 $\pm$ 0.0187	0.1106 $\pm$ 0.0311	0.8197 $\pm$ 0.0141
MotorImagery	0.2535 $\pm$ 0.0721	0.2037 $\pm$ 0.0072	0.1803 $\pm$ 0.0092	0.2820 $\pm$ 0.0278
SelfRegulationSCP1	0.2745 $\pm$ 0.0076	0.4431 $\pm$ 0.1270	0.2377 $\pm$ 0.0053	0.6633 $\pm$ 0.0432

representation-level structure, complementing SF and strengthening the empirical support for the semantic-preservation side of the prune-but-preserve design.

G. Fine-Grained Mechanism Ablation

To further isolate the mechanisms underlying SIGMA beyond the module- and route-level ablations, we conduct a finer-grained study on the same ten representative datasets by modifying one internal design at a time. For CCMA, we separately remove hard admission, adaptive ranking, and confidence calibration; for MEVG, we remove multi-view modeling or replace independent encoders with shared ones. All remaining training settings are kept unchanged. As shown in TABLE VIII, the complete SIGMA obtains the highest average performance over the ten datasets on all four metrics, reaching 0.5274 ACC, 0.5156 F1, 0.3361 NMI, and 0.2754 ARI. The largest ARI reductions arise from removing adaptive ranking and confidence calibration, which decrease the average ARI by 22.9% and 20.6%, respectively, indicating that dynamically identifying informative patches and retaining their confidence information are the main mechanisms within CCMA. Removing hard admission further reduces ARI by 11.3%, supporting the benefit of controlling patch participation before contextual interaction. Within MEVG, removing multi-view modeling or independent encoders decreases average ARI by 9.6% and 9.6%, respectively, showing that view diversity and view-specific encoding provide complementary gains. These controlled variants clarify that the observed improvement does not arise uniformly from an accumulation of components: adaptive ranking and confidence calibration contribute most strongly, while hard admission, multi-view modeling, and encoder specialization provide additional coordinated improvements.

IV. SUPPLEMENTARY RESULTS

This section provides the full experimental record behind the condensed evaluation in the main paper under the same unsupervised protocol defined in Section II. Complete benchmark tables and Bonferroni-Dunn ranks extend Q1 to all 30 UEA datasets. Architecture, route-internal, and fine-grained mechanism ablations expand Q2 by examining SIGMA from module, objective, and internal-mechanism levels. The additional CKA-based evaluation further examines semantic preservation

by comparing representation-level structural consistency with representative clustering methods. Larger-scale and mask-rate tests examine Q3, while additional robustness diagnostics complement Q4 under noise perturbation and embedding compression. Together, these supplementary results provide more detailed evidence for clustering effectiveness, mechanism attribution, semantic preservation, computational efficiency, and robustness without introducing a separate evaluation setting.

REFERENCES

- [1] C. Wang, M. Du, X. Jiang, and Y. Dong, “Fuzzy cluster-aware contrastive clustering for time series,” *Pattern Recognition*, vol. 173, p. 112899, 2026.
- [2] C. Wang, M. Du, and X. Jiang, “Time-frequency augmented multi-level contrastive clustering for time series,” in *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, vol. 40, no. 31, 2026, pp. 26 142–26 150.
- [3] C. He, X. Huang, G. Jiang, Z. Li, D. Lian, H. Xie, E. Chen, X. Liang, Z. Zheng, and P. P. C. Lee, “GTM: A general time-series model for enhanced representation learning of time-series data,” in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2026. [Online]. Available: <https://openreview.net/forum?id=PWM6FERWz9>
- [4] Z. Tan, X. Luo, Y. Liu, and Y. Zhang, “Mask the redundancy: Evolving masking representation learning for multivariate time-series clustering,” in *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, vol. 40, no. 30, 2026, pp. 25 787–25 795.
- [5] E. Fu and Y. Hu, “Frequency-masked embedding inference: A non-contrastive approach for time series representation learning,” in *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, vol. 39, no. 16, 2025, pp. 16 639–16 647.
- [6] Y. Li, M. Du, X. Jiang, and N. Zhang, “Contrastive learning-based multi-view clustering for incomplete multivariate time series,” *Information Fusion*, vol. 117, p. 102812, 2025.
- [7] P. Boniol, D. Tiano, A. Bonifati, and T. Palpanas, “*k*-graph: A graph embedding for interpretable time series clustering,” *IEEE Transactions on Knowledge and Data Engineering*, vol. 37, no. 5, pp. 2680–2694, 2025.
- [8] J. Liu and S. Chen, “Timesurl: Self-supervised contrastive learning for universal time series representation learning,” in *Proceedings of the AAAI Conference on Artificial Intelligence (AAAI)*, vol. 38, no. 12, 2024, pp. 13 918–13 926.
- [9] S. Gao, T. Koker, O. Queen, T. Hartvigsen, T. Tsiligkaridis, and M. Zitnik, “Units: A unified multi-task time series model,” in *Proceedings of the Annual Conference on Neural Information Processing Systems (NeurIPS)*, vol. 37, 2024, pp. 140 589–140 631.
- [10] S. Kornblith, “Similarity of neural network representations revisited,” in *Proceedings of the International Conference on Learning Representations (ICLR)*, 2019. [Online]. Available: <https://openreview.net/forum?id=xtOydkE1Ku>

TABLE VIII

FINE-GRAINED MECHANISM ABLATION ON TEN REPRESENTATIVE DATASETS. EACH VARIANT REMOVES OR REPLACES ONE INTERNAL MECHANISM WHILE KEEPING THE REMAINING SETTINGS UNCHANGED. THE BEST MEAN RESULT FOR EACH DATASET AND METRIC IS HIGHLIGHTED IN BOLD.

Dataset	Metric	w/o Hard Admission	w/o Adaptive Ranking	w/o Confidence Calibration	w/o Multi-View	w/o Independent Encoders	SIGMA (full)
ArticulatoryWordRecognition	ACC	0.7089 $\pm$ 0.0207	0.7075 $\pm$ 0.0355	0.6623 $\pm$ 0.0514	0.6880 $\pm$ 0.0399	0.6838 $\pm$ 0.0177	0.7603 $\pm$ 0.0232
	F1	0.7509 $\pm$ 0.0169	0.7592 $\pm$ 0.0332	0.6796 $\pm$ 0.0427	0.7071 $\pm$ 0.0410	0.7127 $\pm$ 0.0134	0.7929 $\pm$ 0.0392
	NMI	0.7769 $\pm$ 0.0164	0.7883 $\pm$ 0.0253	0.7305 $\pm$ 0.0317	0.7532 $\pm$ 0.0312	0.7524 $\pm$ 0.0148	0.8276 $\pm$ 0.0165
	ARI	0.5629 $\pm$ 0.0255	0.5724 $\pm$ 0.0442	0.5058 $\pm$ 0.0511	0.5336 $\pm$ 0.0533	0.5373 $\pm$ 0.0203	0.6466 $\pm$ 0.0257
BasicMotions	ACC	0.9825 $\pm$ 0.0127	0.6375 $\pm$ 0.0079	0.9750 $\pm$ 0.0224	0.9875 $\pm$ 0.0112	0.9850 $\pm$ 0.0094	0.9875 $\pm$ 0.0079
	F1	0.9824 $\pm$ 0.0129	0.7890 $\pm$ 0.0070	0.9748 $\pm$ 0.0227	0.9875 $\pm$ 0.0112	0.9850 $\pm$ 0.0094	0.9875 $\pm$ 0.0079
	NMI	0.9496 $\pm$ 0.0366	0.7530 $\pm$ 0.0186	0.9450 $\pm$ 0.0403	0.9665 $\pm$ 0.0097	0.9593 $\pm$ 0.0246	0.9665 $\pm$ 0.0191
	ARI	0.9531 $\pm$ 0.0339	0.5903 $\pm$ 0.0160	0.9369 $\pm$ 0.0537	0.9666 $\pm$ 0.0193	0.9600 $\pm$ 0.0247	0.9666 $\pm$ 0.0208
DuckDuckGeese	ACC	0.3880 $\pm$ 0.0319	0.3840 $\pm$ 0.0441	0.3860 $\pm$ 0.0233	0.3240 $\pm$ 0.0441	0.3620 $\pm$ 0.0549	0.4020 $\pm$ 0.0325
	F1	0.3680 $\pm$ 0.0372	0.3689 $\pm$ 0.0408	0.3726 $\pm$ 0.0284	0.3007 $\pm$ 0.0512	0.3348 $\pm$ 0.0578	0.3819 $\pm$ 0.0291
	NMI	0.1449 $\pm$ 0.0204	0.1351 $\pm$ 0.0242	0.1577 $\pm$ 0.0234	0.1050 $\pm$ 0.0377	0.1443 $\pm$ 0.0647	0.1718 $\pm$ 0.0577
	ARI	0.0691 $\pm$ 0.0134	0.0587 $\pm$ 0.0196	0.0567 $\pm$ 0.0129	0.0192 $\pm$ 0.0206	0.0586 $\pm$ 0.0595	0.1000 $\pm$ 0.0580
EthanolConcentration	ACC	0.2969 $\pm$ 0.0096	0.2970 $\pm$ 0.0126	0.2901 $\pm$ 0.0027	0.2953 $\pm$ 0.0189	0.2947 $\pm$ 0.0089	0.2969 $\pm$ 0.0153
	F1	0.2650 $\pm$ 0.0108	0.2696 $\pm$ 0.0121	0.2679 $\pm$ 0.0024	0.2705 $\pm$ 0.0203	0.2709 $\pm$ 0.0157	0.2732 $\pm$ 0.0102
	NMI	0.0110 $\pm$ 0.0032	0.0118 $\pm$ 0.0047	0.0138 $\pm$ 0.0044	0.0123 $\pm$ 0.0063	0.0176 $\pm$ 0.0044	0.0190 $\pm$ 0.0157
	ARI	0.0050 $\pm$ 0.0031	0.0050 $\pm$ 0.0039	0.0039 $\pm$ 0.0022	0.0055 $\pm$ 0.0060	0.0073 $\pm$ 0.0036	0.0097 $\pm$ 0.0119
FaceDetection	ACC	0.5054 $\pm$ 0.0042	0.5147 $\pm$ 0.0061	0.5095 $\pm$ 0.0066	0.5097 $\pm$ 0.0018	0.5135 $\pm$ 0.0060	0.5198 $\pm$ 0.0044
	F1	0.5053 $\pm$ 0.0041	0.5147 $\pm$ 0.0061	0.5083 $\pm$ 0.0065	0.5087 $\pm$ 0.0023	0.5135 $\pm$ 0.0061	0.5192 $\pm$ 0.0046
	NMI	0.0001 $\pm$ 0.0001	0.0007 $\pm$ 0.0005	0.0004 $\pm$ 0.0004	0.0003 $\pm$ 0.0001	0.0006 $\pm$ 0.0004	0.0012 $\pm$ 0.0005
	ARI	0.0001 $\pm$ 0.0002	0.0009 $\pm$ 0.0006	0.0004 $\pm$ 0.0006	0.0003 $\pm$ 0.0001	0.0008 $\pm$ 0.0006	0.0015 $\pm$ 0.0006
HandMovementDirection	ACC	0.2957 $\pm$ 0.0128	0.3171 $\pm$ 0.0272	0.3008 $\pm$ 0.0064	0.3167 $\pm$ 0.0144	0.3103 $\pm$ 0.0113	0.3179 $\pm$ 0.0100
	F1	0.2940 $\pm$ 0.0136	0.3146 $\pm$ 0.0306	0.2977 $\pm$ 0.0085	0.3127 $\pm$ 0.0129	0.3034 $\pm$ 0.0181	0.3145 $\pm$ 0.0104
	NMI	0.0138 $\pm$ 0.0031	0.0164 $\pm$ 0.0067	0.0129 $\pm$ 0.0067	0.0176 $\pm$ 0.0045	0.0171 $\pm$ 0.0047	0.0208 $\pm$ 0.0050
	ARI	-0.0015 $\pm$ 0.0028	0.0028 $\pm$ 0.0073	-0.0022 $\pm$ 0.0046	0.0031 $\pm$ 0.0082	0.0016 $\pm$ 0.0033	0.0052 $\pm$ 0.0047
Handwriting	ACC	0.2066 $\pm$ 0.0105	0.1510 $\pm$ 0.0073	0.2206 $\pm$ 0.0106	0.2432 $\pm$ 0.0084	0.2378 $\pm$ 0.0137	0.2530 $\pm$ 0.0126
	F1	0.2037 $\pm$ 0.0112	0.1479 $\pm$ 0.0073	0.2175 $\pm$ 0.0096	0.2549 $\pm$ 0.0162	0.2382 $\pm$ 0.0159	0.2591 $\pm$ 0.0132
	NMI	0.3000 $\pm$ 0.0205	0.1911 $\pm$ 0.0101	0.3242 $\pm$ 0.0181	0.3613 $\pm$ 0.0182	0.3439 $\pm$ 0.0180	0.3652 $\pm$ 0.0139
	ARI	0.0747 $\pm$ 0.0087	0.0273 $\pm$ 0.0039	0.0888 $\pm$ 0.0093	0.1080 $\pm$ 0.0125	0.1000 $\pm$ 0.0100	0.1134 $\pm$ 0.0113
Heartbeat	ACC	0.6637 $\pm$ 0.0059	0.6775 $\pm$ 0.0260	0.6440 $\pm$ 0.0372	0.6592 $\pm$ 0.0462	0.6805 $\pm$ 0.0075	0.6817 $\pm$ 0.0546
	F1	0.5227 $\pm$ 0.0909	0.5782 $\pm$ 0.0080	0.5538 $\pm$ 0.0574	0.5863 $\pm$ 0.0143	0.5871 $\pm$ 0.0225	0.5944 $\pm$ 0.0367
	NMI	0.0477 $\pm$ 0.0024	0.0418 $\pm$ 0.0043	0.0234 $\pm$ 0.0176	0.0480 $\pm$ 0.0077	0.0292 $\pm$ 0.0136	0.0382 $\pm$ 0.0220
	ARI	0.0360 $\pm$ 0.0631	0.0934 $\pm$ 0.0182	0.0436 $\pm$ 0.0287	0.0808 $\pm$ 0.0135	0.0872 $\pm$ 0.0182	0.0981 $\pm$ 0.0485
JapaneseVowels	ACC	0.7947 $\pm$ 0.0207	0.8238 $\pm$ 0.0666	0.6959 $\pm$ 0.0468	0.8419 $\pm$ 0.0418	0.8147 $\pm$ 0.0916	0.8525 $\pm$ 0.0431
	F1	0.8445 $\pm$ 0.0394	0.8241 $\pm$ 0.0589	0.7182 $\pm$ 0.0556	0.8158 $\pm$ 0.0271	0.8338 $\pm$ 0.0651	0.8494 $\pm$ 0.0383
	NMI	0.7897 $\pm$ 0.0276	0.7780 $\pm$ 0.0202	0.6570 $\pm$ 0.0370	0.7800 $\pm$ 0.0301	0.7723 $\pm$ 0.0517	0.8113 $\pm$ 0.0180
	ARI	0.6928 $\pm$ 0.0463	0.7244 $\pm$ 0.0650	0.4966 $\pm$ 0.0397	0.7141 $\pm$ 0.0602	0.6920 $\pm$ 0.0945	0.7578 $\pm$ 0.0423
LSST	ACC	0.1918 $\pm$ 0.0080	0.2014 $\pm$ 0.0194	0.2005 $\pm$ 0.0169	0.1930 $\pm$ 0.0133	0.1916 $\pm$ 0.0207	0.2019 $\pm$ 0.0029
	F1	0.1696 $\pm$ 0.0117	0.1556 $\pm$ 0.0133	0.1698 $\pm$ 0.0144	0.1680 $\pm$ 0.0069	0.1586 $\pm$ 0.0171	0.1840 $\pm$ 0.0147
	NMI	0.1452 $\pm$ 0.0088	0.1527 $\pm$ 0.0111	0.1248 $\pm$ 0.0129	0.1294 $\pm$ 0.0153	0.1107 $\pm$ 0.0213	0.1396 $\pm$ 0.0043
	ARI	0.0517 $\pm$ 0.0067	0.0472 $\pm$ 0.0061	0.0559 $\pm$ 0.0045	0.0591 $\pm$ 0.0167	0.0435 $\pm$ 0.0153	0.0549 $\pm$ 0.0028