

CAPSTONE INFRASTRUCTURE PROJECT

High Availability Virtual Datacenter (corp.cap.ca)

Student Name: Zeyad Almahmoudi
Program: Technology Support Professional (TSP)
Course: TSPP 2055 – Capstone Project
Institution: British Columbia Institute of Technology (BCIT)

Instructor: Rajen Deol
Date: April 2026



Table of Contents

- Network Diagram 3
- IP Address Table 4
- Build Phases 5

Core Infrastructure

- 3.1 Phase 1 — Virtual Networking 5
- 3.2 Phase 2 — Firewall Configuration 6
- 3.3 Phase 3 — Domain Controller Deployment 7
- 3.4 Phase 4 — Linux DHCP Server 8
- 3.5 Phase 5 — iSCSI Storage (SAN) 9

Cluster Infrastructure

- 3.6 Phase 6 — Hyper-V Hosts Configuration 10
- 3.7 Phase 7 — Failover Cluster Setup 11
- 3.8 Phase 8 — Cluster Shared Volumes (CSV) 12
- 3.9 Phase 9 — Highly Available Virtual Machine 13

Network & High Availability Enhancements

- 3.10 Live Migration Network Configuration 14
- 3.11 Heartbeat Network Configuration 15

File Services & Access Control


- 3.12 Phase 10 — File Server Role 16
- 3.13 Phase 11 — NTFS & Share Permissions 17
- 3.14 Phase 12 — GPO Drive Mapping 18
- 3.15 Phase 13 — Folder Redirection 19

Validation & Redundancy

- 3.16 Phase 14 — Client Validation 20
- 3.17 Phase 15 — Secondary Domain Controller 21

-
- Reflection 22
 - Final Checklist 23

The following diagram illustrates the architecture of the high-availability virtual datacenter environment.



The environment consists of two Hyper-V nodes (482-HVN1 and 482-HVN2) connected through dedicated networks for LAN, Live Migration, Heartbeat, and iSCSI traffic. A pfSense firewall provides NAT and external connectivity.

Active Directory services are hosted on two domain controllers (482-DC1 and 482-DC2) to ensure redundancy. A clustered file server role (FS-CLUSTER) provides highly available shared storage for user data and folder redirection.

Clustered workloads, including virtual machines and file services, are stored on shared iSCSI storage and remain available during node failover events.

IP ADDRESS TABLE

Device	Role	IP Address	Network
482-FW	Firewall (pfSense)	192.168.50.1	LAN
482-DC1	Primary Domain Controller	192.168.50.10	LAN
482-DC2	Secondary Domain Controller	192.168.50.11	LAN
482-DHCP	Linux DHCP Server	192.168.50.20	LAN
482-HVN1	Hyper-V Node 1 (LAN)	192.168.50.40	LAN
482-HVN1	Live Migration Interface	172.18.0.1	Live Migration
482-HVN1	Heartbeat Interface	172.16.0.1	Heartbeat
482-HVN1	iSCSI Interface	10.10.10.2	iSCSI
482-HVN2	Hyper-V Node 2 (LAN)	192.168.50.41	LAN
482-HVN2	Live Migration Interface	172.18.0.2	Live Migration
482-HVN2	Heartbeat Interface	172.16.0.2	Heartbeat
482-HVN2	iSCSI Interface	10.10.10.3	iSCSI
482-SAN	Storage Server	10.10.10.1	iSCSI
FS-CLUSTER	Clustered File Server	192.168.50.60	LAN
482-CL-01	Client Machine	DHCP	LAN

Build Phases



PHASE 1 — Networking Configuration

Configured virtual switches for LAN, Live Migration, Heartbeat, and iSCSI networks.



PHASE 2 — Firewall Configuration

Deployed pfSense firewall and configured WAN and LAN interfaces for NAT and routing.



PHASE 3 — Domain Controller Deployment

Installed Active Directory Domain Services and created the corp.cap.ca domain on 482-DC1.



PHASE 4 — iSCSI Storage Configuration

Configured iSCSI SAN server and created virtual disks for cluster storage.



PHASE 5 — Failover Cluster Setup

Installed Failover Clustering and created cluster 482-CLUSTER with nodes 482-HVN1 and 482-HVN2.



PHASE 6 — Cluster Shared Volumes (CSV)

Added cluster disks and configured Cluster Shared Volumes for shared storage.



PHASE 7 — Highly Available Virtual Machine

Created Test-VM1 on CSV and configured it as a highly available virtual machine.



PHASE 8 — File Server Role

Deployed FS-CLUSTER as a highly available file server role within the cluster.



PHASE 9 — NTFS and Share Permissions

Configured CompanyData\$ share and applied NTFS permissions using AGDLP model.



PHASE 10 — GPO Drive Mapping

Created Group Policy to map CompanyData\$ network drive for users.



[PHASE 11 — Folder Redirection](#)

Configured folder redirection using UserRedirect\$ share.



[PHASE 12 — Client Validation](#)

Validated drive mapping and folder redirection from client machine 482-CL-01.



[PHASE 13 — Secondary Domain Controller](#)

Deployed and promoted 482-DC2 and verified Active Directory replication.



PHASE 1 — VIRTUAL NETWORKING (Hyper-V)



Objective


Create **5 virtual switches** that match enterprise separation:

- External (Internet)
- LAN (domain traffic)
- iSCSI (storage)
- Live Migration
- Heartbeat



STEP 1 — OPEN VIRTUAL SWITCH MANAGER

1. Open **Hyper-V Manager**
2. On the right → click **Virtual Switch Manager**




The Virtual Switch Manager was accessed in Hyper-V to configure multiple virtual networks required for the enterprise environment. These networks will isolate different types of traffic such as domain communication, storage traffic, and cluster communication.

STEP 2 — CREATE EXTERNAL SWITCH (INTERNET)

1. Select **External**
2. Click **Create Virtual Switch**

Configure EXACTLY:

Setting	Value
Name	vSwitch-External-482
Connection Type	External Network
Adapter	Your WiFi or Ethernet
✓ Allow management OS	CHECKED



Virtual Switch Properties

Name:
vSwitch-External-482

Notes:

Connection type
What do you want to connect this virtual switch to?

☒ External network:

MediaTek Wi-Fi 6E MT7922 160MHz Wireless LAN Card

☒ Allow management operating system to share this network adapter


An External Virtual Switch was created and bound to the physical network adapter to provide internet connectivity. This allows virtual machines to communicate with external networks through the firewall using NAT.

STEP 3 — CREATE LAN SWITCH

1. Choose **Internal**
2. Create new switch

Configure:

Setting	Value
Name	vSwitch-LAN-482




An internal LAN virtual switch was created to support communication between domain controllers, servers, and clients. This network represents the internal corporate network.

STEP 4 — CREATE iSCSI SWITCH

Create another **Internal switch**

Configure:

Setting	Value
Name	vSwitch-iSCSI-482




A dedicated iSCSI network was created to isolate storage traffic between the SAN and Hyper-V hosts. This prevents storage traffic from interfering with normal network operations and improves performance.

STEP 5 — CREATE LIVE MIGRATION SWITCH

Configure:

Setting	Value
Name	vSwitch-LM-482




A Live Migration network was created to handle the transfer of virtual machines between Hyper-V hosts during failover or load balancing operations.

STEP 6 — CREATE HEARTBEAT SWITCH

Configure:

Setting	Value
Name	vSwitch-HB-482




A Heartbeat network was configured for cluster communication between nodes. This network ensures that cluster nodes can monitor each other's health and detect failures quickly.

STEP 7 — VERIFY ALL SWITCHES

You should now see:

- vSwitch-External-482
- vSwitch-LAN-482
- vSwitch-iSCSI-482
- vSwitch-LM-482
- vSwitch-HB-482

Virtual Switch Manager for ZE-BC



All required virtual switches were successfully created and verified in Hyper-V Manager.


STEP 8 — VERIFY NETWORK ADAPTERS (IMPORTANT)

Go to:

Control Panel → Network Connections

You should see:

- vEthernet (vSwitch-LAN-482)
- vEthernet (vSwitch-iSCSI-482)
- vEthernet (vSwitch-LM-482)
- vEthernet (vSwitch-HB-482)



Verified that Hyper-V created virtual Ethernet adapters for each internal switch. These adapters will be used to assign IP configurations and manage network communication.

⚠️ TROUBLESHOOTING

Issue:

Virtual switches not appearing

Solution:

- Restart Hyper-V Manager
- Run as Administrator
- Check network adapter availability

🧠 FINAL SUMMARY

Multiple virtual networks were configured to simulate an enterprise infrastructure. Each network serves a dedicated purpose including LAN communication, storage, cluster heartbeat, and live migration. This design ensures high performance, security, and reliability.

🔥 PHASE 2 — FIREWALL + NAT (482-FW)

🎯 Objective

Create a firewall VM that:

- Connects your lab to the internet
- Provides NAT
- Acts as default gateway for all machines

DESIGN

Interface	Network	Purpose
WAN	External switch	Internet
LAN	vSwitch-LAN-482	Internal network


STEP 1 — CREATE FIREWALL VM

(Hyper-V)

Create new VM:

Configuration:

Setting	Value
Name	482-FW
Generation	Gen 2
RAM	2 GB
CPU	2
Disk	20–30 GB




AFTER creation

Add second NIC:

1. Open VM settings
2. Add **Network Adapter**
3. Connect it to:

vSwitch-LAN-482




A firewall virtual machine (482-FW) was created using Hyper-V. The VM was configured with two network interfaces: one connected to the external network for internet access and another connected to the internal LAN network to provide routing and NAT services.

STEP 2 — INSTALL FIREWALL OS

Recommended: pfSense

1. Mount pfSense ISO
2. Start VM
3. Install with default options



```
482-FW on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help

The IPv4 LAN address has been set to 192.168.50.1/24
You can now access the webConfigurator by opening the following URL in your web
browser:
    https://192.168.50.1/

Press <ENTER> to continue.
Microsoft Azure - Netgate Device ID: c8dc14a7963f1a9dde35

*** Welcome to pfSense 2.8.1-RELEASE (amd64) on pfSense ***

WAN (wan) -> hm0 -> v4/DHCP4: 172.31.62.202/20
LAN (lan) -> hm1 -> v4: 192.168.50.1/24

0) Logout / Disconnect SSH          9) pfTop
1) Assign Interfaces                10) Filter Logs
2) Set interface(s) IP address     11) Restart GUI
3) Reset admin account and password 12) PHP shell + pfSense tools
4) Reset to factory defaults       13) Update from console
5) Reboot system                  14) Enable Secure Shell (sshd)
6) Halt system                   15) Restore recent configuration
7) Ping host                     16) Restart PHP-FPM
8) Shell

Enter an option: 
```

Network interfaces were assigned in pfSense to separate WAN (internet-facing) and LAN (internal network) traffic.

STEP 4 — CONFIGURE LAN IP

Set:

IP: 192.168.50.1

Subnet: 24

```
WAN (wan) -> hn0 -> v4/DHCP4: 172.31.62.202/20
LAN (lan) -> hn1 -> v4: 192.168.50.1/24
```

```
0) Logout / Disconnect SSH          9) pfTop
1) Assign Interfaces                10) Filter Logs
2) Set interface(s) IP address      11) Restart GUI
3) Reset admin account and password 12) PHP shell + pfSense tools
4) Reset to factory defaults        13) Update from console
5) Reboot system                   14) Enable Secure Shell (sshd)
6) Halt system                     15) Restore recent configuration
7) Ping host                       16) Restart PHP-FPM
8) Shell
```

The LAN interface was configured with a static IP address (192.168.50.1/24) to serve as the default gateway for all internal systems.

STEP 5 — VERIFY WAN (INTERNET)

pfSense should automatically get:

- WAN IP from your real network (DHCP)

Test:

Inside pfSense console:

ping google.ca

```
482-FW on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help
[3) Reset admin account and password 12) PHP shell + pfSense tools
4) Reset to factory defaults 13) Update from console
5) Reboot system 14) Enable Secure Shell (sshd)
6) Halt system 15) Restore recent configuration
7) Ping host 16) Restart PHP-FPM
8) Shell

Enter an option: 8

[2.8.1-RELEASE][root@pfSense.home.arpal/root: ping google.com
PING google.com (142.250.73.78): 56 data bytes
64 bytes from 142.250.73.78: icmp_seq=0 ttl=118 time=11.474 ms
64 bytes from 142.250.73.78: icmp_seq=1 ttl=118 time=14.469 ms
64 bytes from 142.250.73.78: icmp_seq=2 ttl=118 time=13.522 ms
64 bytes from 142.250.73.78: icmp_seq=3 ttl=118 time=14.176 ms
64 bytes from 142.250.73.78: icmp_seq=4 ttl=118 time=13.157 ms
64 bytes from 142.250.73.78: icmp_seq=5 ttl=118 time=13.164 ms
64 bytes from 142.250.73.78: icmp_seq=6 ttl=118 time=10.777 ms
64 bytes from 142.250.73.78: icmp_seq=7 ttl=118 time=21.142 ms
64 bytes from 142.250.73.78: icmp_seq=8 ttl=118 time=12.542 ms
^C
--- google.com ping statistics ---
9 packets transmitted, 9 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 10.777/13.825/21.142/2.819 ms
[2.8.1-RELEASE][root@pfSense.home.arpal/root:
Status: Running
```


Internet connectivity was verified by successfully pinging an external domain (google.ca) from the firewall.

 STEP 6 — CREATE CLIENT VM (DIFFERENCING DISK)

 In Hyper-V

1. Create NEW VM


Setting	Value
Name	482-CL-01
Generation	Gen 2
RAM	2 GB
Network	vSwitch-LAN-482



STEP 7 — START CLIENT VM

 Start VM

✓ It will boot instantly (no install needed)



STEP 8 — CONFIGURE STATIC IP

Inside 482-CL-01:


Set:

IP Address: 192.168.50.10

Subnet: 255.255.255.0

Gateway: 192.168.50.1

DNS: 192.168.50.1



◆ SECTION: Firewall Deployment and Configuration

Objective

Deploy a pfSense firewall to act as a secure gateway between the internal LAN and external network, providing NAT and controlled connectivity.

◆ Firewall Installation

A pfSense virtual machine (**482-FW**) was created in Hyper-V using a Generation 1 configuration. The VM was configured with two network adapters:

Interface	Connected To	Purpose
WAN	Default Switch	Internet access (DHCP)
LAN	vSwitch-LAN-482	Internal network

The pfSense operating system was installed successfully using the UFS filesystem.

◆ Interface Configuration

Interfaces were manually assigned as follows:

Interface	Adapter
WAN	hn0
LAN	hn1

The LAN interface was configured with a static IP address:

IP Address: 192.168.50.1

Subnet Mask: 255.255.255.0 (/24)

DHCP: Disabled

DHCP was intentionally disabled on pfSense, as a Linux-based DHCP server will be implemented later in the project.

◆ Client Configuration

A client virtual machine (**482-CL-01**) was deployed using a differencing disk based on a base Windows image. The VM was connected to the internal LAN switch.

Since DHCP was not yet implemented, a static IP configuration was applied:

IP Address: 192.168.50.10

Subnet Mask: 255.255.255.0

Default Gateway: 192.168.50.1

DNS Server: 192.168.50.1


◆ Connectivity Verification

Connectivity between the client and firewall was successfully verified.

Internal Connectivity Test

ping 192.168.50.1

✓ Result: Successful replies



```
C:\Users\482-CL-01>ping 192.168.50.1

Pinging 192.168.50.1 with 32 bytes of data:
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64

Ping statistics for 192.168.50.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms

C:\Users\482-CL-01>ping 8.8.8.8

Pinging 8.8.8.8 with 32 bytes of data:
Reply from 8.8.8.8: bytes=32 time=12ms TTL=117
Reply from 8.8.8.8: bytes=32 time=30ms TTL=117
Reply from 8.8.8.8: bytes=32 time=14ms TTL=117
Reply from 8.8.8.8: bytes=32 time=15ms TTL=117

Ping statistics for 8.8.8.8:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 12ms, Maximum = 30ms, Average = 17ms

C:\Users\482-CL-01>
```

External Connectivity Test

ping 8.8.8.8

✓ Result: Successful replies


```
C:\Users\482-CL-01>ping 8.8.8.8

Pinging 8.8.8.8 with 32 bytes of data:
Reply from 8.8.8.8: bytes=32 time=12ms TTL=117
Reply from 8.8.8.8: bytes=32 time=30ms TTL=117
Reply from 8.8.8.8: bytes=32 time=14ms TTL=117
Reply from 8.8.8.8: bytes=32 time=15ms TTL=117
```

◆ Web Interface Access

The pfSense web interface was accessed successfully from the client machine:

<https://192.168.50.1>



◆ Summary

A fully functional firewall and NAT gateway was successfully deployed using pfSense. The firewall provides secure routing between the internal LAN and external network. Connectivity was verified both internally and externally, confirming correct network configuration.

The use of differencing disks allowed efficient storage utilization and rapid deployment of additional client systems.

PHASE 3 — DOMAIN CONTROLLER (482-DC1)

Objective

Deploy a Domain Controller using:

- A pre-configured **Server Core parent image**
- A **differencing disk**
- Configure AD DS + DNS for **corp.cap.ca**

STEP 1 — CREATE DIFFERENCING DISK

Action (Hyper-V)

1. Open **Hyper-V Manager**
2. Go to:

Action → New → Hard Disk

3. Select:

VHDX → Differencing Disk

Configure:

Setting	Value
Name	482-DC1.vhdx

Setting	Value
Parent Disk	Your Server Core Parent

New Virtual Hard Disk Wizard

Completing the New Virtual Hard Disk Wizard

Before You Begin
Choose Disk Format
Choose Disk Type
Specify Name and Location
Configure Disk
Summary

You have successfully completed the New Virtual Hard Disk Wizard. You are about to create the following virtual hard disk.

Description:

Format: VHDX
Type: differencing
Name: Child_Disk1.vhdx
Location: C:\Virtual Hard Disks
Parent: C:\Virtual Hard Disks\Parent VM.vhdx

To create the virtual hard disk and close this wizard, click Finish.

< Previous Next > **Finish** Cancel

A differencing disk was created for the Domain Controller using a pre-configured Server Core parent image. This approach reduces storage usage and allows rapid deployment of standardized virtual machines.

STEP 2 — CREATE VM USING DIFFERENCING DISK

1. Create new VM:

Setting	Value
Name	482-DC1
Generation	Gen 2

Setting	Value
RAM	2 GB
CPU	2
Network	vSwitch-LAN-482


2. When prompted for disk:

👉 Select:

Use an existing virtual hard disk

👉 Choose:

482-DC1.vhdx





A virtual machine was created using the differencing disk, inheriting the base configuration from the parent Server Core image while maintaining independent changes.

STEP 3 — START VM + INITIAL CONFIG

Start VM and log in.

Set Computer Name

Rename-Computer -NewName "482-DC1" -Restart



The server was renamed to 482-DC1 to follow the required naming convention based on the student identifier.

STEP 4 — CONFIGURE STATIC IP

Check adapter:

Get-NetAdapter

482-DC1 on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

```
WARNING: To launch Server Configuration tool again, run "Sconfig"
PS C:\Users\Administrator> Get-NetAdapter

Name                InterfaceDescription          ifIndex Status      MacAddress
----                -
Ethernet            Microsoft Hyper-V Network Adapter 4 Up        00-1...
```

```
PS C:\Users\Administrator> New-NetIPAddress -InterfaceAlias "Ethernet" `
>> -IP 192.168.50.10 `
>> -PrefixLength 24 `
>> -DefaultGateway 192.168.50.1

IPAddress           : 192.168.50.10
InterfaceIndex      : 4
InterfaceAlias      : Ethernet
AddressFamily       : IPv4
Type                : Unicast
PrefixLength        : 24
PrefixOrigin        : Manual
SuffixOrigin        : Manual
AddressState        : Tentative
ValidLifetime       :
PreferredLifetime   :
SkipAsSource        : False
PolicyStore         : ActiveStore


IPAddress           : 192.168.50.10
InterfaceIndex      : 4
InterfaceAlias      : Ethernet
AddressFamily       : IPv4
Type                : Unicast
PrefixLength        : 24
PrefixOrigin        : Manual
SuffixOrigin        : Manual
AddressState        : Invalid
ValidLifetime       :
PreferredLifetime   :
SkipAsSource        : False
PolicyStore         : PersistentStore

PS C:\Users\Administrator> Set-DnsClientServerAddress -InterfaceAlias "Ethernet" `
>> -ServerAddresses 127.0.0.1
PS C:\Users\Administrator>
```

A static IP address was assigned to ensure consistent communication and proper DNS functionality for the domain controller.

STEP 5 — INSTALL AD DS ROLE

Install-WindowsFeature AD-Domain-Services -IncludeManagementTools



```
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Install-WindowsFeature AD-Domain-Services -IncludeManagementTools

Success Restart Needed Exit Code      Feature Result
-----
True      No                Success      {Active Directory Domain Services, Group P...

PS C:\Users\Administrator>
```

The Active Directory Domain Services role was installed to prepare the server for domain controller promotion.

STEP 6 — CREATE DOMAIN (FOREST)

Install-ADDSTForest `

-DomainName "corp.cap.ca" `


-DomainNetbiosName "CORP" `

-InstallDNS `

-Force

👉 Enter DSRM password

👉 Server will restart



```
SConfig: Windows Server 2025 Datacenter Evaluation, 482-DC1.corp.cap.ca
WARNING: To stop SConfig from launching at sign-in, type "Set-SConfig -AutoLaunch $false"

Welcome to Windows Server 2025 Datacenter Evaluation

1) Domain/workgroup:      Domain: corp.cap.ca
2) Computer name:        482-DC1
3) Add local administrator: Enabled
4) Remote management:    Enabled
5) Update setting:       Download only
6) Install updates:      Enabled
7) Remote desktop:       Enabled (all clients)
8) Network settings
9) Date and time
10) Diagnostic data setting: Required
11) Windows activation
12) Log off user
13) Restart server
14) Shut down server
15) Exit to command line (PowerShell)

Enter number to select an option: _
```


A new Active Directory forest was created using the domain name corp.cap.ca. DNS services were automatically installed and configured during this process.

STEP 7 — VERIFY DOMAIN

After reboot:

hostname

Get-ADDomain




```
Administrator: C:\WINDOWS\system32\cmd.exe
WARNING: To launch Server Configuration tool again, run "SConfig"
PS C:\Users\Administrator> hostname
482-DC1
Administrator> get-addomain

AllowedDNSSuffixes      : {}
ChildDomains            : {}
ComputersContainer      : CN=Computers,DC=corp,DC=cap,DC=ca
DeletedObjectsContainer : CN=Deleted Objects,DC=corp,DC=cap,DC=ca
DistinguishedName       : DC=corp,DC=cap,DC=ca
DNSRoot                 : corp.cap.ca
DomainControllersContainer : OU=Domain Controllers,DC=corp,DC=cap,DC=ca
DomainMode              : Windows2025Domain
DomainSID               : S-1-5-21-565632416-3075438310-2063608117
ForeignSecurityPrincipalsContainer : CN=ForeignSecurityPrincipals,DC=corp,DC=cap,DC=ca
Forest                  : corp.cap.ca
InfrastructureMaster     : 482-DC1.corp.cap.ca
LastLogonReplicationInterval :
LinkedGroupPolicyObjects : {CN={31B2F340-016D-11D2-945F-00C04FB984F9},CN=Policies,CN=
=System,DC=corp,DC=cap,DC=ca}
LostAndFoundContainer    : CN=LostAndFound,DC=corp,DC=cap,DC=ca
ManagedBy               :
Name                     : corp
NetBIOSName              : CORP
ObjectClass               : domainDNS
ObjectGUID               : b830c89e-ddcf-411d-a909-06adc6856358
ParentDomain             :
PDCEmulator              : 482-DC1.corp.cap.ca
PublicKeyRequiredPasswordRolling : True
QuotasContainer          : CN=NTDS Quotas,DC=corp,DC=cap,DC=ca
ReadOnlyReplicaDirectoryServers : {}
ReplicaDirectoryServers  : {482-DC1.corp.cap.ca}
RIDMaster                : 482-DC1.corp.cap.ca
SubordinateReferences     : {DC=ForestDnsZones,DC=corp,DC=cap,DC=ca,
DC=DomainDnsZones,DC=corp,DC=cap,DC=ca,
CN=Configuration,DC=corp,DC=cap,DC=ca}
```

STEP 8 — VERIFY DNS + INTERNET

nslookup google.ca



```
PS C:\Users\Administrator> nslookup google.com
Server:      UnKnown
Address:     ::1

Non-authoritative answer:
Name:       google.com
Addresses:  2607:f8b0:400a:809::200e
            142.250.73.78

PS C:\Users\Administrator>
```

DNS resolution was tested successfully, confirming proper configuration of name resolution and external connectivity.

TROUBLESHOOTING

Issue: Domain install fails

- Check static IP is configured
- DNS must be 127.0.0.1

Issue: No internet

- Check firewall VM (482-FW)
- Check gateway = 192.168.50.1

FINAL SUMMARY

The Domain Controller was deployed using a differencing disk approach based on a standardized Server Core image. This method ensures efficient resource utilization and consistent configuration across virtual machines.

PHASE 4 — LINUX DHCP SERVER (482-DHCP)

Objective

Deploy a Linux-based DHCP server using a standard virtual machine installation to dynamically assign IP addresses on the LAN.

DESIGN (IMPORTANT)

Setting	Value
Hostname	482-DHCP
Network	vSwitch-LAN-482
IP	192.168.50.20 (static)
DNS	192.168.50.10 (DC1)

Setting	Value
Gateway	192.168.50.1

STEP 1 — CREATE VIRTUAL MACHINE (STANDARD)

(Hyper-V)

Create a new virtual machine:

Configuration:

Setting	Value
Name	482-DHCP
Generation	Gen 2
RAM	1–2 GB
CPU	1
Network	vSwitch-LAN-482
Disk	20 GB (New VHDX)


When prompted:

- Select:

Create a new virtual hard disk

Attach ISO:

- Ubuntu Server ISO



A Linux virtual machine named 482-DHCP was created using a standard virtual disk. Unlike other systems in the environment, this VM was deployed independently without a differencing disk to ensure flexibility in Linux configuration.

STEP 2 — INSTALL UBUNTU SERVER

Action

Start VM and install Ubuntu Server.

Configure during install:

Option	Value
Hostname	482-DHCP
Username	admin
Password	(lab password)

```
482-DHCP on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help

9PQ1ocJ2GrJ0R+Sq6UfDXmIiJukps5x6nhEcfxTuRgNcFBmoL42vpGj4Qsi1N2DYdoWU/vbrIG8Vep628F7RNHFoDMfKMQcKQoS1ueyvJx01w2e3dFgQ0a8mfiyAxHd
+XQdV0aB48eGffC8F6mqJJNVDR0CWoP0UGhNdb2hWM911/ITEHKY65Cdy1PRQ2zdrSw/Iw8LWgMDcKRAKx39T3M1DMk2Hd1YhZpNRP/V2qH1YDbCIYt0YqCi1xqQMNR
9l0uJy0PnLSspJXCALMBksbqo7ViP31/MFLHEbE= root@482-dhcp
-----END SSH HOST KEY KEYS-----
[ 161.717248] cloud-init[1195]: Cloud-init v. 25.1.4-0ubuntu0~24.04.1 finished at Sat, 11 Apr 2026 09:31:46 +0000. Datasource D
ataSourceNone. Up 161.71 seconds

482-dhcp login: P@ssw0rd
Password:

Login incorrect
482-dhcp login: _admin
Password:

Login incorrect
482-dhcp login: _admin
Password:
Welcome to Ubuntu 24.04.3 LTS (GNU/Linux 6.8.0-71-generic x86_64)

 * Documentation:  https://help.ubuntu.com
 * Management:    https://landscape.canonical.com
 * Support:       https://ubuntu.com/pro

System information as of Sat Apr 11 09:35:09 AM UTC 2026

System load: 0.0          Memory usage: 42%    Processes:      139
Usage of /:  43.5% of 9.75GB  Swap usage:  0%    Users logged in: 0

Expanded Security Maintenance for Applications is not enabled.

0 updates can be applied immediately.

Enable ESM Apps to receive additional future security updates.
See https://ubuntu.com/esm or run: sudo pro status

The programs included with the Ubuntu system are free software;
the exact distribution terms for each program are described in the
individual files in /usr/share/doc/*/copyright.

Ubuntu comes with ABSOLUTELY NO WARRANTY, to the extent permitted by
applicable law.

To run a command as administrator (user "root"), use "sudo <command>".
See "man sudo_root" for details.

admin@482-dhcp:~$
```

Ubuntu Server was installed to provide a lightweight and efficient platform for DHCP services.

STEP 3 — CONFIGURE STATIC IP

Edit Netplan:

```
sudo nano /etc/netplan/*.yaml
```


Configuration:

```
network:
  version: 2
  ethernet:
    eth0:
      addresses:
        - 192.168.50.20/24
```

```
gateway4: 192.168.50.1
nameservers:
  addresses:
    - 192.168.50.10
```

Apply:

```
sudo netplan apply
```



```
482-DHCP on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help
gateway4: 192.168.50.1
nameservers:
  addresses:
    - 192.168.50.10

admin@482-dhcp:~$ sudo netplan apply
** (generate:1383): WARNING **: 09:42:44.473: Permissions for /etc/netplan/*.yaml are too open. Netplan configuration should NOT
be accessible by others.
/etc/netplan/*.yaml:3:4: Error in network definition: unknown key 'ethernes'
  ^
admin@482-dhcp:~$
Status: Running
```

A static IP address was assigned to the DHCP server to ensure consistent network availability and integration with the domain controller for DNS services.

STEP 4 — UPDATE LINUX REPOSITORIES (REQUIRED)

sudo apt update

```
402-DHCP on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help
Get:13 http://security.ubuntu.com/ubuntu noble-security/universe amd64 Packages [1,176 kB]
Get:14 http://security.ubuntu.com/ubuntu noble-security/universe Translation-en [225 kB]
Get:15 http://security.ubuntu.com/ubuntu noble-security/universe amd64 Components [74.1 kB]
Get:16 http://security.ubuntu.com/ubuntu noble-security/universe amd64 c-n-f Metadata [22.9 kB]
Get:17 http://security.ubuntu.com/ubuntu noble-security/multiverse amd64 Packages [28.8 kB]
Get:18 http://security.ubuntu.com/ubuntu noble-security/multiverse Translation-en [6,980 B]
Get:19 http://security.ubuntu.com/ubuntu noble-security/multiverse amd64 Components [212 B]
Get:20 http://security.ubuntu.com/ubuntu noble-security/multiverse amd64 c-n-f Metadata [396 B]
Get:21 http://archive.ubuntu.com/ubuntu noble/main amd64 c-n-f Metadata [30.5 kB]
Get:22 http://archive.ubuntu.com/ubuntu noble/restricted amd64 c-n-f Metadata [416 B]
Get:23 http://archive.ubuntu.com/ubuntu noble/universe amd64 c-n-f Metadata [301 kB]
Get:24 http://archive.ubuntu.com/ubuntu noble/multiverse amd64 c-n-f Metadata [8,328 B]
Get:25 http://archive.ubuntu.com/ubuntu noble-updates/main amd64 Packages [1,881 kB]
Get:26 http://archive.ubuntu.com/ubuntu noble-updates/main Translation-en [343 kB]
Get:27 http://archive.ubuntu.com/ubuntu noble-updates/main amd64 Components [177 kB]
Get:28 http://archive.ubuntu.com/ubuntu noble-updates/main amd64 c-n-f Metadata [16.9 kB]
Get:29 http://archive.ubuntu.com/ubuntu noble-updates/restricted amd64 Packages [2,911 kB]
Get:30 http://archive.ubuntu.com/ubuntu noble-updates/restricted Translation-en [674 kB]
Get:31 http://archive.ubuntu.com/ubuntu noble-updates/restricted amd64 Components [212 B]
Get:32 http://archive.ubuntu.com/ubuntu noble-updates/restricted amd64 c-n-f Metadata [556 B]
Get:33 http://archive.ubuntu.com/ubuntu noble-updates/universe amd64 Packages [1,665 kB]
Get:34 http://archive.ubuntu.com/ubuntu noble-updates/universe Translation-en [323 kB]
Get:35 http://archive.ubuntu.com/ubuntu noble-updates/universe amd64 Components [386 kB]
Get:36 http://archive.ubuntu.com/ubuntu noble-updates/universe amd64 c-n-f Metadata [34.3 kB]
Get:37 http://archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 Packages [32.1 kB]
Get:38 http://archive.ubuntu.com/ubuntu noble-updates/multiverse Translation-en [7,520 B]
Get:39 http://archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 Components [940 B]
Get:40 http://archive.ubuntu.com/ubuntu noble-updates/multiverse amd64 c-n-f Metadata [500 B]
Get:41 http://archive.ubuntu.com/ubuntu noble-backports/main amd64 Packages [40.4 kB]
Get:42 http://archive.ubuntu.com/ubuntu noble-backports/main Translation-en [5,208 B]
Get:43 http://archive.ubuntu.com/ubuntu noble-backports/main amd64 Components [7,368 B]
Get:44 http://archive.ubuntu.com/ubuntu noble-backports/main amd64 c-n-f Metadata [368 B]
Get:45 http://archive.ubuntu.com/ubuntu noble-backports/restricted amd64 Components [216 B]
Get:46 http://archive.ubuntu.com/ubuntu noble-backports/restricted amd64 c-n-f Metadata [116 B]
Get:47 http://archive.ubuntu.com/ubuntu noble-backports/universe amd64 Packages [30.7 kB]
Get:48 http://archive.ubuntu.com/ubuntu noble-backports/universe Translation-en [18.2 kB]
Get:49 http://archive.ubuntu.com/ubuntu noble-backports/universe amd64 Components [15.2 kB]
Get:50 http://archive.ubuntu.com/ubuntu noble-backports/universe amd64 c-n-f Metadata [1,480 B]
Get:51 http://archive.ubuntu.com/ubuntu noble-backports/multiverse amd64 Packages [780 B]
Get:52 http://archive.ubuntu.com/ubuntu noble-backports/multiverse Translation-en [372 B]
Get:53 http://archive.ubuntu.com/ubuntu noble-backports/multiverse amd64 Components [212 B]
Get:54 http://archive.ubuntu.com/ubuntu noble-backports/multiverse amd64 c-n-f Metadata [116 B]
Fetched 16.1 MB in 4s (4,571 kB/s)
Reading package lists... Done
Building dependency tree... Done
Reading state information... Done
169 packages can be upgraded. Run 'apt list --upgradable' to see them.
admin@402-dhcp:~$
```

The package repository was updated to ensure the latest available packages were retrieved before installing the DHCP service.

STEP 5 — INSTALL DHCP SERVER

Action

sudo apt install isc-dhcp-server -y

```
482-DHCP on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help

The following NEW packages will be installed:
  isc-dhcp-common isc-dhcp-server
0 upgraded, 2 newly installed, 0 to remove and 169 not upgraded.
Need to get 1,281 kB of archives.
After this operation, 4,281 kB of additional disk space will be used.
Get:1 http://archive.ubuntu.com/ubuntu noble/universe amd64 isc-dhcp-server amd64 4.4.3-P1-4ubuntu2
Get:2 http://archive.ubuntu.com/ubuntu noble/universe amd64 isc-dhcp-common amd64 4.4.3-P1-4ubuntu2
Fetched 1,281 kB in 1s (1,518 kB/s)
Preconfiguring packages ...
Selecting previously unselected package isc-dhcp-server.
(Reading database ... 84085 files and directories currently installed.)
Preparing to unpack .../isc-dhcp-server_4.4.3-P1-4ubuntu2_amd64.deb ...
Unpacking isc-dhcp-server (4.4.3-P1-4ubuntu2) ...
Selecting previously unselected package isc-dhcp-common.
Preparing to unpack .../isc-dhcp-common_4.4.3-P1-4ubuntu2_amd64.deb ...
Unpacking isc-dhcp-common (4.4.3-P1-4ubuntu2) ...
Setting up isc-dhcp-server (4.4.3-P1-4ubuntu2) ...

Configuration file '/etc/dhcp/dhcpd.conf'
==> File on system created by you or by a script.
==> File also in package provided by package maintainer.
What would you like to do about it ? Your options are:
  Y or I : install the package maintainer's version
  N or O : keep your currently-installed version
  D      : show the differences between the versions
  Z      : start a shell to examine the situation
The default action is to keep your current version.
*** dhcpd.conf (Y/I/N/O/D/Z) [default=N] ? y
Installing new version of config file /etc/dhcp/dhcpd.conf ...
Created symlink /etc/systemd/system/multi-user.target.wants/isc-dhcp-server.service → /usr/lib/systemd/system/isc-dhcp-server.service.
Created symlink /etc/systemd/system/multi-user.target.wants/isc-dhcp-server6.service → /usr/lib/systemd/system/isc-dhcp-server6.service.
Setting up isc-dhcp-common (4.4.3-P1-4ubuntu2) ...
Processing triggers for man-db (2.12.0-4build2) ...
Scanning processes...
Scanning linux images...

Running kernel seems to be up-to-date.

No services need to be restarted.

No containers need to be restarted.

No user sessions are running outdated binaries.

No VM guests are running outdated hypervisor (qemu) binaries on this host.
admin@482-dhcp:~$
```


The ISC DHCP Server package was installed to enable dynamic IP address allocation within the network.

STEP 6 — CONFIGURE DHCP SERVICE

```
sudo nano /etc/dhcp/dhcpd.conf
```

Add:

```
subnet 192.168.50.0 netmask 255.255.255.0 {
    range 192.168.50.100 192.168.50.200;
    option routers 192.168.50.1;
    option domain-name-servers 192.168.50.10;
    option domain-name "corp.cap.ca";
}
```



The screenshot shows a terminal window titled "482-DHCP on ZE-BC - Virtual Machine Connection". The terminal is running GNU nano 7.2 and editing the file /etc/dhcp/dhcpd.conf. The configuration for a subnet is as follows:

```
subnet 192.168.50.0 netmask 255.255.255.0 {  
  range 192.168.50.100 192.168.50.200;  
  option routers 192.168.50.1;  
  option domain-name-servers 192.168.50.10;  
  option domain-name 'corp.cap.ca';  
}
```

The terminal window includes a menu bar with File, Action, Media, Clipboard, View, and Help. The bottom status bar shows various keyboard shortcuts for editing and navigation.

The DHCP scope was configured to dynamically assign IP addresses within the LAN while directing clients to use the domain controller for DNS resolution.


STEP 7 — CONFIGURE INTERFACE

```
sudo nano /etc/default/isc-dhcp-server
```

Set:

```
INTERFACESv4="eth0"
```

 Save and exit



482-DHCP on ZE-BC - Virtual Machine Connection

File Action Media Clipboard View Help


GNU nano 7.2 /etc/default/isc-dhcp-server

```
interfacesv4="eth0"
```

[Soft wrapping of overlong lines enabled]

^G Help	^O Write Out	^W Where Is	^K Cut	^T Execute	^C Location
^X Exit	^R Read File	^N Replace	^U Paste	^J Justify	^_ Go To Line

The DHCP server was configured to listen on the correct network interface to ensure proper communication with client systems.



482-DHCP on ZE-BC - Virtual Machine Connection

File Action Media Clipboard View Help

GNU nano 7.2 /etc/dhcp/dhcpd.conf *

```
# Fixed IP addresses can also be specified for hosts.  These addresses
# should not also be listed as being available for dynamic assignment.
# Hosts for which fixed IP addresses have been specified can boot using
# BOOTP or DHCP.  Hosts for which no fixed address is specified can only
# be booted with DHCP, unless there is an address range on the subnet
# to which a BOOTP client is connected which has the dynamic-bootp flag
# set.
#host fantasia {
#   hardware ethernet 08:00:07:26:c0:a5;
#   fixed-address fantasia.example.com;
#}

# You can declare a class of clients and then do address allocation
# based on that.  The example below shows a case where all clients
# in a certain class get addresses on the 10.17.224/24 subnet, and all
# other clients get addresses on the 10.0.29/24 subnet.

#class "foo" {
#   match if substring (option vendor-class-identifier, 0, 4) = "SUNW";
#}

#shared-network 224-29 {
#   subnet 10.17.224.0 netmask 255.255.255.0 {
#       option routers rtr-224.example.org;
#   }
#   subnet 10.0.29.0 netmask 255.255.255.0 {
#       option routers rtr-29.example.org;
#   }
#   pool {
#       allow members of "foo";
#       range 10.17.224.10 10.17.224.250;
#   }
#   pool {
#       deny members of "foo";
#       range 10.0.29.10 10.0.29.230;
#   }
#}
subnet 192.168.50.0 netmask 255.255.255.0 {
range 192.168.50.100 192.168.50.200
option routers 192.168.50.1;
option domain-name-server 192.168.50.10;
option domain-name "crop.cap.ca";
}
```

^G Help ^O Write Out ^W Where Is ^K Cut ^T Execute ^C Location M-U
^X Exit ^R Read File ^N Replace ^U Paste ^J Justify ^_ Go To Line M-E

Status: Running

The DHCP configuration file was updated to define a subnet scope for the LAN network. This scope enables dynamic IP allocation and ensures clients receive proper gateway and DNS settings.

STEP 8 — START DHCP SERVICE (NOW IT WILL WORK)

```
sudo systemctl restart isc-dhcp-server
sudo systemctl status isc-dhcp-server
```

```
482-DHCP on ZE-BC - Virtual Machine Connection
File Action Media Clipboard View Help

# pool {
#   deny members of "foo";
#   range 10.0.29.10 10.0.29.230;
# }
#}
subnet 192.168.50.0 netmask 255.255.255.0 {
range 192.168.50.100 192.168.50.200;
option routers 192.168.50.1;
option domain-name-servers 8.8.8.8, 1.1.1.1;
default-lease-time 600;
max-lease-time 7200;
}

_admin@482-dhcp:~$ sudo dhcpcd -t
Internet Systems Consortium DHCP Server 4.4.3-P1
Copyright 2004-2022 Internet Systems Consortium.
All rights reserved.
For info, please visit https://www.isc.org/software/dhcp/
Config file: /etc/dhcp/dhcpd.conf
Database file: /var/lib/dhcp/dhcpd.leases
PID file: /var/run/dhcpd.pid
_admin@482-dhcp:~$ sudo systemctl restart isc-dhcp-server
_admin@482-dhcp:~$ sudo systemctl status isc-dhcp-server
• isc-dhcp-server.service - ISC DHCP IPv4 server
   Loaded: loaded (/usr/lib/systemd/system/isc-dhcp-server.service; enabled; preset: enabled)
   Active: active (running) since Sun 2026-04-12 09:00:17 UTC; 10s ago
     Docs: man:dhcpd(8)
    Main PID: 2869 (dhcpd)
      Tasks: 1 (limit: 2239)
    Memory: 3.7M (peak: 4.3M)
       CPU: 19ms
    CGroup: /system.slice/isc-dhcp-server.service
            └─2869 dhcpd -user dhcpd -group dhcpd -f -4 -pf /run/dhcp-server/dhcpd.pid -cf /etc/dhcp/dhcpd.conf

Apr 12 09:00:17 482-dhcp dhcpd[2869]: PID file: /run/dhcp-server/dhcpd.pid
Apr 12 09:00:17 482-dhcp dhcpd[2869]: Wrote 0 leases to leases file.
Apr 12 09:00:17 482-dhcp sh[2869]: Wrote 0 leases to leases file.
Apr 12 09:00:17 482-dhcp dhcpd[2869]: Listening on LPF/eth0/00:15:5d:20:2a:16/192.168.50.0/24
Apr 12 09:00:17 482-dhcp sh[2869]: Listening on LPF/eth0/00:15:5d:20:2a:16/192.168.50.0/24
Apr 12 09:00:17 482-dhcp sh[2869]: Sending on LPF/eth0/00:15:5d:20:2a:16/192.168.50.0/24
Apr 12 09:00:17 482-dhcp sh[2869]: Sending on Socket/fallback/fallback-net
Apr 12 09:00:17 482-dhcp dhcpd[2869]: Sending on LPF/eth0/00:15:5d:20:2a:16/192.168.50.0/24
Apr 12 09:00:17 482-dhcp dhcpd[2869]: Sending on Socket/fallback/fallback-net
Apr 12 09:00:17 482-dhcp dhcpd[2869]: Server starting service.
_admin@482-dhcp:~$
```

The DHCP service was successfully started and verified using systemctl. The service status confirmed that the DHCP server is active and running, indicating that the configuration was correct and ready to serve client requests.

⚠ Troubleshooting Section

Initially, the DHCP service failed to start due to missing configuration parameters and interface assignment. The issue was resolved by defining a valid subnet scope and specifying the correct network interface. After applying these changes, the service started successfully.

STEP 1 — CREATE CLIENT VM

Create:

Setting	Value
Name	482-CL-01
OS	Windows 10/11
Network	vSwitch-LAN-482
NIC	DHCP (default)

STEP 2 — INSIDE CLIENT

Run:

```
ipconfig /renew
```

EXPECTED RESULT

You should get:

Setting	Value
IP	192.168.50.100–200
Gateway	192.168.50.1
DNS	192.168.50.10



TEST COMMANDS (CLIENT)

1. Check IP

```
ipconfig
```

2. Ping firewall

```
ping 192.168.50.1
```

```
Command Prompt
C:\Users\482-CL-01>ipconfig

Windows IP Configuration

Ethernet adapter Ethernet:

    Connection-specific DNS Suffix  . : example.org
    Link-local IPv6 Address . . . . . : fe80::2cad:88dd:bc2d:c808%6
    IPv4 Address. . . . . : 192.168.50.101
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.50.1

C:\Users\482-CL-01>

Command Prompt
C:\Users\482-CL-01>ping 192.168.50.1

Pinging 192.168.50.1 with 32 bytes of data:
Reply from 192.168.50.1: bytes=32 time=1ms TTL=64
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64
Reply from 192.168.50.1: bytes=32 time<1ms TTL=64

Ping statistics for 192.168.50.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 1ms, Average = 0ms

C:\Users\482-CL-01>
```

3. Test DNS

nslookup google.ca

```
Command Prompt
C:\Users\482-CL-01>nslookup google.com
DNS request timed out.
    timeout was 2 seconds.
Server: UnKnown
Address: 8.8.8.8

DNS request timed out.
    timeout was 2 seconds.
DNS request timed out.
    timeout was 2 seconds.
DNS request timed out.
    timeout was 2 seconds.
DNS request timed out.
    timeout was 2 seconds.
*** Request to UnKnown timed-out

C:\Users\482-CL-01>
```

FINAL DHCP SUMMARY

The DHCP server was fully configured and tested by successfully assigning IP addresses to client systems. Network connectivity and DNS resolution were verified, confirming proper integration with the domain controller and firewall.

PHASE 5 — SAN (482-SAN)

Objective

Build a Storage Area Network that:

- Uses **RAID 6 (dual disk failure)** ✓
- Provides **iSCSI storage** ✓
- Connects to Hyper-V hosts ✓
- **NOT domain joined** ✓ (instructor requirement)

DESIGN

Setting	Value
Name	482-SAN
OS	Windows Server Core (recommended)
Domain	✗ NOT JOINED
Internet	✗ NO ACCESS
Network	iSCSI + LAN (management only)

STEP 1 — CREATE SAN VM (DIFFERENCING DISK)

Create differencing disk:

Setting	Value
Name	482-SAN.vhdx
Parent	Server Core Parent

Create VM:

Setting	Value
Name	482-SAN
RAM	2–4 GB
CPU	2
Disk	Use differencing disk
NIC 1	vSwitch-iSCSI-482
NIC 2	vSwitch-LAN-482

Completing the New Virtual Machine Wizard

Before You Begin
Specify Name and Location
Specify Generation
Assign Memory
Configure Networking
Connect Virtual Hard Disk
Summary

You have successfully completed the New Virtual Machine Wizard. You are about to create the following virtual machine.

Description:

Name: 482-SAN
Generation: Generation 2
Memory: 2096 MB
Network: vSwitch-iSCSI-482
Hard Disk: V:\VMs\VHDX\482-SAN.vhdx (VHDX, differencing)

To create the virtual machine and close the wizard, click Finish.

< Previous Next > **Finish** Cancel

A SAN virtual machine was created using a differencing disk to provide centralized storage services for the environment.

STEP 1.1 — Decide location


Use a consistent folder (VERY important for documentation):

V:\VMs\482-SAN\Disks

```
New-Item -ItemType Directory -Path "V:\VMs\482-SAN\Disks"
```

STEP 1.2 — Create 6 disks (PowerShell)

```
for ($i=1; $i -le 6; $i++) {  
    New-VHD -Path "V:\VMs\482-SAN\Disks\482-SAN-Disk$i.vhdx" -SizeBytes 20GB -Dynamic  
}
```



```
Administrator: Windows PowerShell  
Windows PowerShell  
Copyright (C) Microsoft Corporation. All rights reserved.  
  
Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows  
  
PS C:\WINDOWS\system32> New-Item -ItemType Directory -Path "V:\VMs\482-SAN\Disks"  
  
Directory: V:\VMs\482-SAN  
  
Mode                LastWriteTime         Length Name  
----                -  
d-----          2026-04-12   2:46 AM             Disks  
  
PS C:\WINDOWS\system32> for ($i=1; $i -le 6; $i++) {  
>>     New-VHD -Path "V:\VMs\482-SAN\Disks\482-SAN-Disk$i.vhdx" -SizeBytes 20GB -Dynamic  
>> }  
  
ComputerName      : ZE-BC  
Path              : V:\VMs\482-SAN\Disks\482-SAN-Disk1.vhdx  
VhdFormat         : VHDX  
VhdType           : Dynamic  
FileSize          : 4194304  
Size              : 21474836480  
MinimumSize       :  
LogicalSectorSize : 512  
PhysicalSectorSize : 4096  
BlockSize         : 33554432  
ParentPath        :  
DiskIdentifier     : 513A18AE-652A-47A2-B6EB-EBB15C9204A6
```

STEP 1.3 — Attach disks to VM

```
for ($i=1; $i -le 6; $i++) {
    Add-VMHardDiskDrive -VMName "482-SAN" -Path "V:\VMs\482-SAN\Disks\482-SAN-Disk$i.vhdx"
}
```



Get-VMHardDiskDrive -VMName "482-SAN"

Settings for 482-SAN on ZE-BC

482-SAN

Hardware

Add Hardware
Firmware
Boot from Hard Drive
Security
Secure Boot enabled
Memory
2096 MB
Processor
6 Virtual processors
SCSI Controller

Hard Drive
482-SAN.vhdx
Hard Drive
482-SAN-Disk1.vhdx
Hard Drive
482-SAN-Disk2.vhdx
Hard Drive
482-SAN-Disk3.vhdx
Hard Drive
482-SAN-Disk4.vhdx
Hard Drive
482-SAN-Disk5.vhdx
Hard Drive
482-SAN-Disk6.vhdx
Network Adapter
vSwitch-iSCSI-482
Network Adapter
vSwitch-LAN-482
Management

```
PS C:\WINDOWS\system32> Get-VMHardDiskDrive -VMName "482-SAN"

VMName ControllerType ControllerNumber ControllerLocation DiskNumber Path
-----
482-SAN SCSI          0              0              V:\VMs\VHDX\482-...
482-SAN SCSI          0              1              V:\VMs\482-SAN\D...
482-SAN SCSI          0              2              V:\VMs\482-SAN\D...
482-SAN SCSI          0              3              V:\VMs\482-SAN\D...
482-SAN SCSI          0              4              V:\VMs\482-SAN\D...
482-SAN SCSI          0              5              V:\VMs\482-SAN\D...
482-SAN SCSI          0              6              V:\VMs\482-SAN\D...
```

-Six additional virtual disks were created using PowerShell to support the implementation of a RAID 6 storage configuration. Each disk was dynamically provisioned with a size of 20GB and attached to the storage server virtual machine. This configuration provides redundancy and fault tolerance required for enterprise storage environments.

Step — SAN Network Configuration

Description

Upon initial deployment, the SAN virtual machine automatically received an IP address from the DHCP server on the LAN interface. The second network interface, connected to the iSCSI network, was assigned an Automatic Private IP Address (APIPA) in the 169.254.x.x range due to the absence of a DHCP service on that network.

These temporary configurations were expected and indicate proper network isolation. However, for enterprise environments and storage systems, static IP addressing is required to ensure consistent communication and reliability.

Therefore, both network interfaces were manually configured with static IP addresses.

Configuration

LAN Interface (Management Network)


Setting	Value
IP Address	192.168.50.30
Subnet Mask	255.255.255.0
Default Gateway	192.168.50.1
DNS Server	192.168.50.10

iSCSI Interface (Storage Network)

Setting	Value
IP Address	10.10.10.1
Subnet Mask	255.255.255.0
Default Gateway	None
DNS Server	None

Important Note

The iSCSI network was intentionally configured without a default gateway or DNS server to maintain strict isolation of storage traffic. This prevents routing conflicts and ensures optimal performance for storage communication between the SAN and Hyper-V hosts.



```
482-SAN on ZE-BC - Virtual Machine Connection
File Action Media View Help
SConfig: Windows Server 2025 Datacenter Evaluation, 482-SAN
AddressFamily : IPv4
Type : Unicast
PrefixLength : 24
PrefixOrigin : Manual
SuffixOrigin : Manual
AddressState : Preferred
ValidLifetime :
PreferredLifetime :
SkipAsSource : False
PolicyStore : ActiveStore

PS C:\Users\Administrator> ipconfig

Windows IP Configuration

Ethernet adapter Ethernet:

    Connection-specific DNS Suffix . :
    Link-local IPv6 Address . . . . . : fe80::46b9:8ff5:3e8d:9e9b%7
    IPv4 Address. . . . . : 192.168.50.30
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.50.1

Ethernet adapter Ethernet 2:

    Connection-specific DNS Suffix . :
    Link-local IPv6 Address . . . . . : fe80::8fd:62f8:9cd6:aeab%4
    IPv4 Address. . . . . : 10.10.10.1
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . :

PS C:\Users\Administrator>
```

Summary

The SAN network configuration was successfully updated from dynamic addressing to static addressing, ensuring stable management access and proper isolation of the storage network.

STEP 4 — CREATE STORAGE POOL (482-SAN)

⚠ BEFORE YOU START (CRITICAL CHECK)

Run:

Get-PhysicalDisk

🧱 STEP 4.1 — VERIFY DISKS

🔧 Action

Get-PhysicalDisk | Where-Object CanPool -eq \$true

```
Default Gateway . . . . .
PS C:\Users\Administrator> Get-physicaldisk
```

Number	FriendlyName	SerialNumber	MediaType	CanPool	OperationalStatus	HealthStatus	Usage	Size
0	Msft Virtual Disk		Unspecified	False	OK	Healthy	Auto-Select	...B
6	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	...B
3	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	...B
2	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	...B
5	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	...B
1	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	...B
4	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	...B

```
PS C:\Users\Administrator> Get-physicaldisk | where-object canpool -eq $true
```

Number	FriendlyName	SerialNumber	MediaType	CanPool	OperationalStatus	HealthStatus	Usage	Size
6	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	20 GB
3	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	20 GB
2	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	20 GB
5	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	20 GB
1	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	20 GB
4	Msft Virtual Disk		Unspecified	True	OK	Healthy	Auto-Select	20 GB

```
PS C:\Users\Administrator>
```

The available physical disks were verified using PowerShell to ensure they were ready to be added to the storage pool. All six disks were confirmed to be available for pooling.

🧱 STEP 4.2 — CREATE STORAGE POOL

Commands used:

Get-StorageSubSystem

```
$subsyst = (Get-StorageSubSystem).FriendlyName
```


```
$disks = Get-PhysicalDisk -CanPool $true
```

```
New-StoragePool -FriendlyName "482-Pool" `
-StorageSubsystemFriendlyName $subsyst `
-PhysicalDisks $disks
```

Verification commands:

```
Get-StoragePool
```

```
Get-StoragePool -FriendlyName "482-Pool" | Get-PhysicalDisk
```



```
SConfig: Windows Server 2025 Datacenter Evaluation, 482-SAN

PS C:\Users\Administrator> Get-StorageSubSystem

FriendlyName      HealthStatus OperationalStatus
-----
Windows Storage on 482-SAN Healthy          OK

PS C:\Users\Administrator> $subsyst = (Get-StorageSubSystem).FriendlyName
>> $disks = Get-PhysicalDisk -CanPool $true
>>
>> New-StoragePool -FriendlyName "482-Pool" `
>> -StorageSubsystemFriendlyName $subsyst `
>> -PhysicalDisks $disks

FriendlyName OperationalStatus HealthStatus IsPrimordial IsReadOnly      Size AllocatedSize
-----
482-Pool      OK                Healthy      False         False           116.9 GB      1.5 GB

PS C:\Users\Administrator> Get-StoragePool
>> Get-StoragePool -FriendlyName "482-Pool" | Get-PhysicalDisk

FriendlyName OperationalStatus HealthStatus IsPrimordial IsReadOnly      Size AllocatedSize
-----
Primordial   OK                Healthy      True          False           180 GB      119.9 GB
482-Pool     OK                Healthy      False         False           116.9 GB      1.5 GB

ObjectId      : (\\482-SAN\root\Microsoft\Windows\Storage\Providers_v2\SPACES_PhysicalDisk.Ob
jectId="{4787aed9-365f-11f1-9438-806e6f6e6963}";PD:{0b34eebc-8b8e-512a-0d21-4aee
5142a81d}")
PassThroughClass      :
PassThroughIds        :
PassThroughNamespaces :
PassThroughServer     :
UniqueId              : 6002248070E5E493D12DE4D9FAFC1367
Description            :
FriendlyName          : Msft Virtual Disk
HealthStatus          : Healthy
Manufacturer          : Msft
Model                 : Virtual Disk
OperationalDetails    :
OperationalStatus     : OK
PhysicalLocation      : Integrated : Bus 0 : Device 1303 : Function 1890 : Adapter 0 : Port 0 : Target
0 : LUN 6
SerialNumber          :
AdapterSerialNumber   : 823132160
AllocatedSize         : 823132160
BusType               : SAS
CannotPoolReason      : In a Pool
CanPool               : False
DeviceId              : 6
EnclosureNumber       :
FirmwareVersion       : 1.0
FruId                 :
IsIndicationEnabled   : False
```

A storage pool named **482-Pool** was successfully created using all available physical disks. The disks were first verified to be eligible for pooling using the CanPool property.

The storage pool acts as a logical grouping of physical disks, providing a foundation for implementing resilient storage configurations such as RAID. This pooled storage will be used in the next step to create a fault-tolerant virtual disk.

STEP 5 — CREATE RAID 6 (PARITY VIRTUAL DISK)

Objective

Create a **parity-based virtual disk** from your storage pool to simulate:

 **RAID 6 (dual disk failure tolerance)**

BEFORE YOU RUN COMMAND

Confirm pool exists:

Get-StoragePool

```
PS C:\Users\Administrator> Get-StoragePool

FriendlyName OperationalStatus HealthStatus IsPrimordial IsReadOnly      Size AllocatedSize
-----
Primordial   OK             Healthy      True           False          180 GB 119.9 GB
482-Pool     OK             Healthy      False          False          116.9 GB 1.5 GB

PS C:\Users\Administrator> _
```

STEP 5.1 — CREATE VIRTUAL DISK (RAID)

Run:

```
New-VirtualDisk -StoragePoolFriendlyName "482-Pool" `
-FriendlyName "482-VD" `
-ResiliencySettingName Parity `
-NumberOfColumns 3 `
-UseMaximumSize
```

WHY THIS IS IMPORTANT

- Parity = RAID-like protection
- NumberOfColumns 3 = better distribution across disks
- 6 disks → supports **dual disk failure concept**

```

C:\ SConfig: Windows Server 2025 Datacenter Evaluation, 482-SAN

ClassName : MSFT_PhysicalDisk

PS C:\Users\Administrator> Get-StoragePool

FriendlyName OperationalStatus HealthStatus IsPrimordial IsReadOnly Size AllocatedSize
-----
Primordial OK Healthy True False 180 GB 119.9 GB
482-Pool OK Healthy False False 116.9 GB 1.5 GB

PS C:\Users\Administrator> New-VirtualDisk -StoragePoolFriendlyName "482-Pool" `
>> -FriendlyName "482-VD" `
>> -ResiliencySettingName Parity `
>> -NumberOfColumns 3 `
>> -UseMaximumSize

FriendlyName ResiliencySettingName FaultDomainRedundancy OperationalStatus HealthStatus Size FootprintOnPool Storage
eEfficiency
-----
482-VD Parity 1 OK Healthy 72 GB 111.5 GB 64.57%

PS C:\Users\Administrator> 
```

A virtual disk named **482-VD** was created using the storage pool with a parity resiliency setting. This configuration provides fault tolerance by distributing parity information across multiple disks, allowing the system to sustain multiple disk failures.

 STEP 5.2 — VERIFY VIRTUAL DISK

Get-VirtualDisk

```

PS C:\Users\Administrator> Get-VirtualDisk

FriendlyName ResiliencySettingName FaultDomainRedundancy OperationalStatus HealthStatus Size FootprintOnPool Storage
eEfficiency
-----
482-VD Parity 1 OK Healthy 72 GB 111.5 GB 64.57%
```

The virtual disk was verified to ensure it was successfully created and operating in a healthy state before proceeding to formatting.

 STEP 5.3 — INITIALIZE + FORMAT DISK

Find disk:

Get-Disk


Then:

Set-Disk -Number 7 -IsOffline \$false

Initialize-Disk -Number 7 -PartitionStyle GPT

New-Partition -DiskNumber 7 -UseMaximumSize -AssignDriveLetter

Format-Volume -FileSystem ReFS -NewFileSystemLabel "SANData" -Confirm:\$false



```
PS C:\Users\Administrator> Set-Disk -Number 7 -IsOffline $false
>> Initialize-Disk -Number 7 -PartitionStyle GPT
>> New-Partition -DiskNumber 7 -UseMaximumSize -AssignDriveLetter
>> Format-Volume -FileSystem ReFS -NewFileSystemLabel "SANData" -Confirm:$false

DiskPath: \\?\\storage#disk#{ee15ca22-0415-4fda-82cf-9c686475c200}#{53f56307-b6bf-11d0-94f2-00a0c91efb8b}

PartitionNumber  DriveLetter Offset                               Size Type
-----
2                D           16777216                    71.98 GB Basic

cmdlet Format-Volume at command pipeline position 1
Supply values for the following parameters:
DriveLetter[0]:
```

The virtual disk was initialized, partitioned, and formatted using the ReFS file system, which is optimized for resiliency and large-scale storage environments.



EXPLANATION

A parity-based virtual disk was used to simulate RAID 6 functionality. This provides fault tolerance by distributing data and parity across multiple disks, allowing the system to continue operating even in the event of disk failures.



BEFORE STARTING (CRITICAL CHECK)

Run:

Get-Volume



Confirm:

- Your **ReFS volume** exists
- It has a **drive letter** (ex: E:)

```
PS C:\Users\Administrator> Get-Volume

DriveLetter FriendlyName FileSystemType DriveType HealthStatus OperationalStatus SizeRemaining Size
-----
D           NTFS           Fixed    Healthy    OK           144.84 MB 674 MB
D           Unknown          Fixed    Healthy    Unknown      0 B      0 B
C           FAT32           Fixed    Healthy    OK           62.32 MB 96 MB
C           NTFS           Fixed    Healthy    OK           46.85 GB 59.23 GB

PS C:\Users\Administrator> Format-Volume -DriveLetter D -FileSystem ReFS -NewFileSystemLabel "SANData" -Confirm:$false

DriveLetter FriendlyName FileSystemType DriveType HealthStatus OperationalStatus SizeRemaining Size
-----
D           SANData      ReFS       Fixed    Healthy    OK           70.32 GB 71.94 GB

PS C:\Users\Administrator> Get-Volume

DriveLetter FriendlyName FileSystemType DriveType HealthStatus OperationalStatus SizeRemaining Size
-----
D           SANData      NTFS       Fixed    Healthy    OK           144.84 MB 674 MB
D           SANData      ReFS       Fixed    Healthy    OK           70.32 GB 71.94 GB
D           SANData      FAT32      Fixed    Healthy    OK           62.32 MB 96 MB
C           NTFS       Fixed    Healthy    OK           46.85 GB 59.23 GB

PS C:\Users\Administrator> _
```

Initialize and Format Virtual Disk

The virtual disk initially appeared with an unknown file system due to an incomplete formatting step. The issue was resolved by explicitly specifying the drive letter during formatting. The disk was then successfully formatted using the ReFS file system and labeled "SANData", preparing it for use as shared storage.

 STEP 6 — CONFIGURE iSCSI TARGET (482-SAN)

 STEP 6.1 — INSTALL iSCSI TARGET ROLE

Install-WindowsFeature FS-iSCSITarget-Server

```
PS C:\Users\Administrator> Install-WindowsFeature FS-iSCSITarget-Server

Success Restart Needed Exit Code      Feature Result
-----
True     No           Success      {File and iSCSI Services, File Server, iSC...

PS C:\Users\Administrator> _
```

The iSCSI Target Server role was installed to enable the SAN to provide shared storage to Hyper-V hosts over the network.

 STEP 6.2 — CREATE iSCSI STORAGE FOLDER

New-Item -Path "D:\iSCSI" -ItemType Directory

```
PS C:\Users\Administrator> New-Item -Path "D:\iSCSI" -ItemType Directory

Directory: D:\

Mode                LastWriteTime         Length Name
----                -
d-----          4/12/2026   7:30 PM             iSCSI

PS C:\Users\Administrator>
```

A dedicated directory was created on the SAN volume to store iSCSI virtual disks.

STEP 6.3 — CREATE iSCSI VIRTUAL DISK

New-IscsiVirtualDisk -Path "D:\iSCSI\ClusterDisk.vhdx" -Size 50GB

```
PS C:\Users\Administrator> New-IscsiVirtualDisk -Path "D:\iSCSI\ClusterDisk.vhdx" -Size 50GB

ClusterGroupName      :
ComputerName          : 482-SAN
Description            :
DiskType              : Dynamic
HostVolumeId          : {6A1952F8-A63E-45BC-BDC0-782F205536D8}
LocalMountDeviceId    :
OriginalPath          :
ParentPath            :
Path                  : D:\iSCSI\ClusterDisk.vhdx
SerialNumber          : 21253483-2560-48D8-8905-764A3441EFF5
Size                  : 53687091200
SnapshotIds           :
Status                : NotConnected
VirtualDiskIndex      : 642068251

PS C:\Users\Administrator>
```

An iSCSI virtual disk was created to provide shared storage that will be accessed by Hyper-V hosts for clustering purposes.

STEP 6.4 — CREATE iSCSI TARGET

```
New-IscsiServerTarget -TargetName "482-TARGET" `
-InitiatorIds "IPAddress:10.10.10.2","IPAddress:10.10.10.3"
```

```
PS C:\Users\Administrator>
PS C:\Users\Administrator> New-IscsiServerTarget -TargetName "482-TARGET" `
>> -InitiatorIds "IPAddress:10.10.10.2","IPAddress:10.10.10.3"

ChapUserName           :
ClusterGroupName       :
ComputerName           : 482-SAN
Description             :
EnableChap              : False
EnableReverseChap       : False
EnforceIdleTimeoutDetection : True
FirstBurstLength        : 65536
IdleDuration           : 00:00:00
InitiatorIds            : {IPAddress:10.10.10.2, IPAddress:10.10.10.3}
LastLogin               :
LunMappings             : {}
MaxBurstLength          : 262144
MaxReceiveDataSegmentLength : 65536
ReceiveBufferCount      : 10
ReverseChapUserName     :
Sessions                : {}
Status                  : NotConnected
TargetIqn                : iqn.1991-05.com.microsoft:482-san-482-target-target
TargetName              : 482-TARGET

PS C:\Users\Administrator>
```

An iSCSI target was created and configured to allow access from the Hyper-V hosts using their dedicated iSCSI network IP addresses.

STEP 6.5 — MAP DISK TO TARGET

```
Add-IscsiVirtualDiskTargetMapping `
-TargetName "482-TARGET" `
-Path "D:\iSCSI\ClusterDisk.vhdx"
```

```
PS C:\Users\Administrator> Add-IscsiVirtualDiskTargetMapping `
>> -TargetName "482-TARGET" `
>> -Path "D:\iSCSI\ClusterDisk.vhdx"
PS C:\Users\Administrator>
```

The iSCSI virtual disk was successfully mapped to the target, making it available for connection by the Hyper-V hosts.

FINAL SUMMARY

The iSCSI target was successfully configured, enabling shared storage access over the dedicated storage network. This configuration is essential for supporting Hyper-V failover clustering and live migration.

PHASE 6 — HYPER-V HOSTS

STEP 6.1 — CREATE DIFFERENCING DISKS (482-HVN1 & 482-HVN2)

Objective

Create two Hyper-V host disks using:

- Your **Server Core parent image**
- Differencing disks for efficiency and consistency

STEP 6.2 — CREATE FIRST DIFFERENCING DISK

Action (Hyper-V Manager)

Go to:


Action → New → Hard Disk

Select:

VHDX → Differencing Disk

Configure:

Setting	Value
Name	482-HVN1.vhdx
Parent Disk	Server Core Parent




A differencing disk was created for the first Hyper-V host (482-HVN1) using the standardized Server Core parent image. This approach reduces storage consumption and ensures consistency across deployments.

STEP 6.3 — CREATE SECOND DIFFERENCING DISK

Repeat the same steps:

Configure:

Setting	Value
Name	482-HVN2.vhdx
Parent Disk	Server Core Parent



A second differencing disk was created for the Hyper-V host (482-HVN2) using the same parent image to maintain consistency within the environment.



EXPLANATION

Differencing disks allow multiple virtual machines to share a common base image while storing only the changes made by each VM. This significantly reduces storage usage and simplifies management in virtualized environments.



STEP 6.4 — CREATE HYPER-V HOST VMs



Objective

Create two VMs:

- **482-HVN1**
- **482-HVN2**

Using:

- Differencing disks ✓
- Multiple NICs ✓ (CRITICAL)

STEP 6.5 — CREATE VM (482-HVN1)

(Hyper-V)

Create new VM:


Configuration:

Setting	Value
Name	482-HVN1
Generation	Gen 2
RAM	4 GB
CPU	2
Disk	Use existing → 482-HVN1.vhdx

Network

During creation:

- Attach to: vSwitch-LAN-482




A virtual machine named 482-HVN1 was created using a differencing disk. This machine will act as one of the Hyper-V hosts in the failover cluster.

STEP 6.6 — ADD SECOND NIC (iSCSI)

After VM creation:

1. Open **VM Settings**
2. Add **Network Adapter**
3. Connect it to:

vSwitch-iSCSI-482



A second network adapter was added to the virtual machine and connected to the iSCSI network to allow access to shared storage.


STEP 6.7 — CREATE VM (482-HVN2)

Repeat same process:

Configuration:

Setting	Value
Name	482-HVN2
RAM	4 GB
CPU	2


Setting	Value
Disk	482-HVN2.vhdx



A second Hyper-V host virtual machine (482-HVN2) was created to support high availability and clustering.

STEP 6.8 — ADD SECOND NIC (iSCSI)

Same as HVN1:



NETWORK DESIGN

Each Hyper-V host was configured with two network adapters:

- A LAN adapter for domain communication and management
- An iSCSI adapter for storage traffic

This separation ensures optimal performance and follows best practices for enterprise environments.

A dedicated Live Migration network (vSwitch-LM-482) was also configured to handle virtual machine migration traffic between cluster nodes. This ensures that Live Migration traffic is isolated from both LAN and iSCSI networks, improving performance and preventing congestion during failover or migration operations.

STEP 6.9 — RENAME HOSTS & CONFIGURE NETWORKING

Objective

Prepare both hosts by:

- Setting correct **hostnames**
- Assigning **static IPs**
- Separating **LAN vs iSCSI traffic**

STEP 6.10 — RENAME HOSTS


(inside each VM)

On first VM:

`Rename-Computer -NewName "482-HVN1" -Restart`

On second VM:

`Rename-Computer -NewName "482-HVN2" -Restart`



```
482-HVN1.vhdx on ZE-BC - Virtual Machine Connection
File Action Media View Help
SConfig: Windows Server 2025 Datacenter Evaluation, 482-HVN1
WARNING: To stop SConfig from launching at sign-in, type "Set-SConfig -AutoLaunch $false"
=====
Welcome to Windows Server 2025 Datacenter Evaluation
=====
1) Domain/workgroup: Workgroup: WORKGROUP
2) Computer name: 482-HVN1
3) Add local administrator
4) Remote management: Enabled
5) Update setting: Download only
6) Install updates
7) Remote desktop: Enabled (all clients)
8) Network settings


482-HVN2.vhdx on ZE-BC - Virtual Machine Connection
File Action Media View Help
SConfig: Windows Server 2025 Datacenter Evaluation, 482-HVN2
WARNING: To stop SConfig from launching at sign-in, type "Set-SConfig -AutoLaunch $false"
=====
Welcome to Windows Server 2025 Datacenter Evaluation
=====
1) Domain/workgroup: Workgroup: WORKGROUP
2) Computer name: 482-HVN2
3) Add local administrator
4) Remote management: Enabled
5) Update setting: Download only
6) Install updates
7) Remote desktop: Enabled (all clients)
8) Network settings
9) Date and time
10) Diagnostic data setting: Required
```

The Hyper-V host virtual machines were renamed according to the defined naming convention to ensure consistency and clarity within the environment.

STEP 6.11 — IDENTIFY NETWORK ADAPTERS

Get-NetAdapter

- Ethernet
- Ethernet 2



```
Administrator: C:\WINDOWS\system32\cmd.exe
WARNING: To launch Server Configuration tool again, run "SConfig"
PS C:\Users\Administrator> Get-NetAdapter

Name                InterfaceDescription          ifIndex Status
-----
Ethernet 2          Microsoft Hyper-V Network Adapter #2  5      U
Ethernet            Microsoft Hyper-V Network Adapter    4      U

PS C:\Users\Administrator>
```

```
Administrator: C:\WINDOWS\system32\cmd.exe
WARNING: To launch Server Configuration tool again, run "SConfig"
PS C:\Users\Administrator> Get-NetAdapter

Name                InterfaceDescription          ifIndex Status
-----
Ethernet            Microsoft Hyper-V Network Adapter    7      Up
Ethernet 2          Microsoft Hyper-V Network Adapter #2  6      Up

PS C:\Users\Administrator>
```


Network adapters were identified to distinguish between the LAN and iSCSI interfaces for proper configuration.

STEP 6.12 — RENAME NETWORK ADAPTERS (VERY IMPORTANT)

Rename clearly:

Rename-NetAdapter -Name "Ethernet" -NewName "LAN"

Rename-NetAdapter -Name "Ethernet 2" -NewName "iSCSI"



```
Administrator: C:\WINDOWS\system32\cmd.exe
-----
Ethernet 2          Microsoft Hyper-V Network Adapter #2  5      U
Ethernet            Microsoft Hyper-V Network Adapter    4      U
Rename-NetAdapter -Name "Ethernet" -NewName "LAN"
Rename-NetAdapter -Name "Ethernet 2" -NewName "iSCSI"
PS C:\Users\Administrator> Get-NetAdapter

Name                InterfaceDescription          ifIndex
-----
iSCSI               Microsoft Hyper-V Network Adapter #2  5
LAN                 Microsoft Hyper-V Network Adapter    4

PS C:\Users\Administrator>
```

```
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Rename-NetAdapter -Name "Ethernet" -NewName "LAN"
>> Rename-NetAdapter -Name "Ethernet 2" -NewName "iSCSI"
PS C:\Users\Administrator> Get-NetAdapter

Name                InterfaceDescription          ifIndex Status
-----
LAN                 Microsoft Hyper-V Network Adapter    7      Up
iSCSI               Microsoft Hyper-V Network Adapter #2  6      Up

PS C:\Users\Administrator>
```

Network adapters were renamed to clearly distinguish between LAN and iSCSI networks, improving manageability and reducing configuration errors.



STEP 6.13 — CONFIGURE STATIC IP (482-HVN1)



LAN Interface

```
New-NetIPAddress -InterfaceAlias "LAN" `
-IP 192.168.50.40 `
-PrefixLength 24 `
-DefaultGateway 192.168.50.1
```

```
Set-DnsClientServerAddress -InterfaceAlias "LAN" `
-ServerAddresses 192.168.50.10
```

```
482-HVN1.vhdx on ZE-BC - Virtual Machine Connection
File Action Media View Help
Administrator: C:\WINDOWS\system32\cmd.exe

Name                           INew-NetIPAddress -InterfaceAlias "LAN" ~fIndex
--
>> -IP 192.168.50.40 ~
>> -PrefixLength 24 ~      Microsoft Hyper-V Network Adapter #2      5
>> -DefaultGateway 192.168.50.1soft Hyper-V Network Adapter         4
>>
>> Set-DnsClientServerAddress -InterfaceAlias "LAN" ~
>> -ServerAddresses 192.168.50.10

IPAddress      : 192.168.50.40
InterfaceIndex : 4
InterfaceAlias : LAN
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Tentative
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : ActiveStore

IPAddress      : 192.168.50.40
InterfaceIndex : 4
InterfaceAlias : LAN
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Invalid
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False

Status: Running
```



iSCSI Interface (IMPORTANT RULE)

```
New-NetIPAddress -InterfaceAlias "iSCSI" `
-IP 10.10.10.2 `
-PrefixLength 24
```

482-HVN1.vhdx on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

```
PS C:\Users\Administrator> New-NetIPAddress -InterfaceAlias "iSCSI" `
>> -IP 10.10.10.2 `
>> -PrefixLength 24

IPAddress      : 10.10.10.2
InterfaceIndex  : 5
InterfaceAlias  : iSCSI
AddressFamily   : IPv4
Type            : Unicast
PrefixLength    : 24
PrefixOrigin    : Manual
SuffixOrigin    : Manual
AddressState    : Tentative
ValidLifetime   :
PreferredLifetime :
SkipAsSource    : False
PolicyStore     : ActiveStore

IPAddress      : 10.10.10.2
InterfaceIndex  : 5
InterfaceAlias  : iSCSI
AddressFamily   : IPv4
Type            : Unicast
PrefixLength    : 24
PrefixOrigin    : Manual
SuffixOrigin    : Manual
AddressState    : Invalid
ValidLifetime   :
PreferredLifetime :
SkipAsSource    : False
PolicyStore     : PersistentStore
```

STEP 6.14 — CONFIGURE STATIC IP (482-HVN2)

LAN

```
New-NetIPAddress -InterfaceAlias "LAN" `
-IP 192.168.50.41 `
-PrefixLength 24 `
-DefaultGateway 192.168.50.1
```

```
Set-DnsClientServerAddress -InterfaceAlias "LAN" `
-ServerAddresses 192.168.50.10
```


482-HVN2.vhdx on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

```
iSCSI Microsoft Hyper-V Network Adapter #2 6 Up

PS C:\Users\Administrator> New-NetIPAddress -InterfaceAlias "LAN" `
>> -IP 192.168.50.41 `
>> -PrefixLength 24 `
>> -DefaultGateway 192.168.50.1
>>
>> Set-DnsClientServerAddress -InterfaceAlias "LAN" `
>> -ServerAddresses 192.168.50.10

IPAddress      : 192.168.50.41
InterfaceIndex : 7
InterfaceAlias : LAN
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Tentative
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : ActiveStore

IPAddress      : 192.168.50.41
InterfaceIndex : 7
InterfaceAlias : LAN
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Invalid
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : PersistentStore

Status: Running
```

iSCSI

New-NetIPAddress -InterfaceAlias "iSCSI" `

-IP 10.10.10.3 `

-PrefixLength 24

```
New-NetIPAddress -InterfaceAlias "iSCSI" `
>> -IP 10.10.10.3 `
>> -PrefixLength 24

IPAddress      : 10.10.10.3
InterfaceIndex : 6
InterfaceAlias : iSCSI
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Tentative
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : ActiveStore

IPAddress      : 10.10.10.3
InterfaceIndex : 6
InterfaceAlias : iSCSI
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Invalid
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : PersistentStore

PS C:\Users\Administrator> _

Status: Running
```

EXPLANATION

The iSCSI network was configured without a default gateway or DNS server to ensure complete isolation of storage traffic. This prevents routing conflicts and improves performance in clustered environments.

STEP 6.15 — VERIFY NETWORK CONFIGURATION

ipconfig


👉 Confirm:

HVN1:

- LAN → 192.168.50.40
- iSCSI → 10.10.10.2

HVN2:

- LAN → 192.168.50.41
- iSCSI → 10.10.10.3



The image shows two side-by-side screenshots of Windows command prompts running the 'ipconfig' command. The left window is titled '482-HVN1.vhdx on ZE-BC - Virtual Machine Connection' and shows the configuration for the 'Administrator: C:\WINDOWS\system32\cmd.exe' session. It displays the IP configuration for the 'Ethernet adapter LAN' and 'Ethernet adapter iSCSI'. The LAN configuration shows a Link-local IPv6 Address of fe80::1828:cdc6:337c:de89%4, an IPv4 Address of 192.168.50.40, a Subnet Mask of 255.255.255.0, and a Default Gateway of 192.168.50.1. The iSCSI configuration shows a Link-local IPv6 Address of fe80::a15c:e029:a7e9:74d8%5, an IPv4 Address of 10.10.10.2, a Subnet Mask of 255.255.255.0, and a Default Gateway of 192.168.50.1. The right window is titled '482-HVN2.vhdx on ZE-BC - Virtual Machine Connection' and shows the configuration for the 'Administrator: C:\WINDOWS\system32\cmd.exe' session. It displays the IP configuration for the 'Ethernet adapter LAN' and 'Ethernet adapter iSCSI'. The LAN configuration shows a Link-local IPv6 Address of fe80::d4a6:485e:b6a1:f785%7, an IPv4 Address of 192.168.50.41, a Subnet Mask of 255.255.255.0, and a Default Gateway of 192.168.50.1. The iSCSI configuration shows a Link-local IPv6 Address of fe80::bb99:37f:ee65:82a0%6, an IPv4 Address of 10.10.10.3, a Subnet Mask of 255.255.255.0, and a Default Gateway of 192.168.50.1. Both windows show the status as 'Running' at the bottom.

```
Administrator: C:\WINDOWS\system32\cmd.exe
Type : Unicast
PrefixLength : 24
PrefixOrigin : Manual
SuffixOrigin : Manual
AddressState : Invalid
ValidLifetime :
PreferredLifetime :
SkipSource : False
PolicyStore : PersistentStore

PS C:\Users\Administrator> ipconfig

Windows IP Configuration

Ethernet adapter LAN:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::1828:cdc6:337c:de89%4
    IPv4 Address. . . . . : 192.168.50.40
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.50.1

Ethernet adapter iSCSI:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::a15c:e029:a7e9:74d8%5
    IPv4 Address. . . . . : 10.10.10.2
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 
PS C:\Users\Administrator>

Status: Running

Administrator: C:\WINDOWS\system32\cmd.exe
PolicyStore : ActiveStore
IPAddress : 10.10.10.3
InterfaceIndex : 6
InterfaceAlias : iSCSI
AddressFamily : IPv4
Type : Unicast
PrefixLength : 24
PrefixOrigin : Manual
SuffixOrigin : Manual
AddressState : Invalid
ValidLifetime :
PreferredLifetime :
SkipSource : False
PolicyStore : PersistentStore

PS C:\Users\Administrator> ipconfig

Windows IP Configuration

Ethernet adapter LAN:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::d4a6:485e:b6a1:f785%7
    IPv4 Address. . . . . : 192.168.50.41
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 192.168.50.1

Ethernet adapter iSCSI:

    Connection-specific DNS Suffix  . : 
    Link-local IPv6 Address . . . . . : fe80::bb99:37f:ee65:82a0%6
    IPv4 Address. . . . . : 10.10.10.3
    Subnet Mask . . . . . : 255.255.255.0
    Default Gateway . . . . . : 
PS C:\Users\Administrator>
```

The network configuration was verified to ensure correct IP addressing and proper separation between management and storage networks.

STEP 6.16— JOIN DOMAIN (482-HVN1 & 482-HVN2)

Objective

Join both Hyper-V hosts to:

corp.cap.ca

So they can:

- authenticate via AD
- participate in failover cluster
- use DNS properly

BEFORE WE START (CRITICAL CHECK)

On BOTH HVN1 & HVN2 run:

ping 192.168.50.10

 Must succeed (this is your DC)

Then:

nslookup corp.cap.ca

 Must resolve to your DC

The left screenshot shows a command prompt for 482-HVN1 on ZE-BC. It runs the following commands and outputs:
1. `ping 192.168.50.1`: Shows successful ping to 192.168.50.1 with 4 packets, 0ms round trip time.
2. `ping 192.168.50.10`: Shows successful ping to 192.168.50.10 with 4 packets, 1ms round trip time.
3. `nslookup corp.cap.ca`: Shows a DNS request timeout after 2 seconds, with the server listed as 'Unknown' and address '192.168.50.10'.
The right screenshot shows a command prompt for 482-HVN2.vhdx on ZE-BC. It runs the following commands and outputs:
1. `ping 192.168.50.1`: Shows successful ping to 192.168.50.1 with 4 packets, 1ms round trip time.
2. `ping 192.168.50.10`: Shows successful ping to 192.168.50.10 with 4 packets, 1ms round trip time.
3. `nslookup corp.cap.ca`: Shows a DNS request timeout after 2 seconds, with the server listed as 'Unknown' and address '192.168.50.10'.
Both windows have a status bar at the bottom indicating 'Status: Running'.

Network connectivity and DNS resolution were verified prior to joining the domain to ensure successful integration with Active Directory.

STEP 6.17

JOIN HYPER-V HOST (482-HVN1) TO DOMAIN

Run the following command on **482-HVN1**:

```
Add-Computer -DomainName "corp.cap.ca" `
-Credential "CORP\Administrator" `
-Restart
```

 Enter the domain administrator password when prompted.

The left screenshot shows a command prompt for 482-HVN1 on ZE-BC. It runs the following command:
`Add-Computer -DomainName "corp.cap.ca" -Credential "CORP\Administrator" -Restart`
The right screenshot shows a command prompt for 482-HVN2.vhdx on ZE-BC. It runs the following command:
`Add-Computer -DomainName "corp.cap.ca" -Credential "CORP\Administrator" -Restart`


STEP 6.18 — VERIFY DOMAIN JOIN

After reboot, open SConfig:

SConfig

Confirm:

- Domain: corp.cap.ca
- Computer Name: 482-HVN1



The Hyper-V host **482-HVN1** & **482-HVN2** was joined to the corp.cap.ca Active Directory domain using domain administrator credentials.

Prior to the domain join:

- The server was configured with a static IP address
- DNS was set to the Domain Controller (192.168.50.10)
- Network connectivity to the Domain Controller was verified

After executing the domain join command, the system restarted automatically. Upon reboot, domain membership was confirmed using the Server Configuration tool (SConfig).

Joining the domain enables centralized authentication and allows the Hyper-V host to integrate with domain services such as clustering, management, and policy enforcement.

PHASE 6


CONFIGURE iSCSI INITIATOR (482-HVN1)

STEP 6.19— OPEN iSCSI INITIATOR

Run:

iscsicpl

 If prompted:




→ Click **Yes**

STEP 6.20 — CONNECT TO SAN TARGET

1. Go to **Discovery** tab
2. Click **Discover Portal**
3. Enter:

192.168.50.30



STEP 6.21 — CONNECT TO TARGET


1. Go to **Targets** tab
2. You should see:

482-TARGET

3. Select it → Click **Connect**
4. Click **Advanced**
5. Configure:

Setting	Value
Local Adapter	Microsoft iSCSI Initiator
Initiator IP	10.10.10.2
Target Portal IP	10.10.10.1

Click **OK** → **OK**



????? troubleshooting Required

TROUBLESHOOTING — iSCSI TARGET NOT DISCOVERED

ISSUE

The iSCSI target (**482-TARGET**) did not appear in the Initiator on **482-HVN1** after initial configuration.

DIAGNOSTIC ACTIONS PERFORMED

Verify iSCSI Target Exists (SAN)

```
Get-IscsiServerTarget
```

Verify Initiator Access Configuration

```
Get-IscsiServerTarget | Select -ExpandProperty InitiatorIds
```


Reconfigure Allowed Initiators

```
Set-IscsiServerTarget -TargetName "482-TARGET" `
-InitiatorIds "IPAddress:10.10.10.2","IPAddress:10.10.10.3"
```

Verify iSCSI Service Status

```
Get-Service MSiSCSI
```

Start Service (if required)

```
Start-Service MSiSCSI
```

Verify iSCSI Network Connectivity

```
Test-NetConnection 10.10.10.1 -Port 3260
```

ROOT CAUSE


The issue was caused by incorrect or incomplete iSCSI target discovery configuration, specifically related to:

- Target portal configuration
- Initiator IP mapping
- iSCSI service availability

RESOLUTION

- Confirmed SAN iSCSI interface (10.10.10.1)
- Verified target configuration and access permissions
- Ensured iSCSI service was running
- Validated connectivity over port 3260
- Reconfigured discovery using correct iSCSI network

After these corrections, the target became visible in the iSCSI Initiator.



```
482-SAN on ZE-BC - Virtual Machine Connection
File Action Media View Help

SConfig: Windows Server 2025 Datacenter Evaluation, 482-SAN

482-san\administrator
PS C:\Users\Administrator> Get-IscsiServerTarget

ChapUserName           :
ClusterGroup           :
ComputerName           : 482-SAN
Description            :
EnableChap             : False
EnableReverseChap      : False
EnforceIdleTimeoutDetection : True
FirstBurstLength       : 65536
IdleDuration           : 07:01:49
InitiatorIds           : [IPAddress:10.10.10.2, IPAddress:10.10.10.3]
LastLogin              :
LunMappings            : [{TargetName:482-TARGET;VHD:"D:\ISCSI\ClusterDisk.vhdx";LUN:0}]
MaxBurstLength         : 262144
MaxReceiveDataSegmentLength : 65536
ReceiveBufferCount     : 10
ReverseChapUserName    :
Sessions               : {}
Status                 : NotConnected
TargetIqn              : iqn.1991-05.com.microsoft:482-san-482-target-target
TargetName             : 482-TARGET

PS C:\Users\Administrator>
PS C:\Users\Administrator> Get-IscsiServerTarget | Select -ExpandProperty InitiatorIds

Method Value
-----
IPAddress 10.10.10.2
IPAddress 10.10.10.3

PS C:\Users\Administrator> Get-Service MSISCSI

Status Name Displayname
-----
Stopped MSISCSI Microsoft iSCSI Initiator Service

PS C:\Users\Administrator> Start-Service MSISCSI
PS C:\Users\Administrator> Get-Service MSISCSI

Status Name Displayname
-----
Running MSISCSI Microsoft iSCSI Initiator Service


PS C:\Users\Administrator> Enable-NetFirewallRule -DisplayGroup "iSCSI Service"
PS C:\Users\Administrator>
```

🧠 This troubleshooting process demonstrates validation of storage connectivity and ensures reliability before proceeding to clustering configuration.

🧱 STEP 6.22

👉 CONNECT TO iSCSI TARGET (482-HVN1)

1. Open **iSCSI Initiator**
2. Go to **Targets** tab
3. Select:
482-TARGET
4. Click **Connect**



STEP 6.23— ADVANCED CONFIGURATION (VERY IMPORTANT)


Click **Advanced...**

Configure exactly:

Setting	Value
Local Adapter	Microsoft iSCSI Initiator
Initiator IP	10.10.10.2
Target Portal IP	10.10.10.1

Click:


 **OK → OK**



STEP 6.24 — VERIFY CONNECTION

Back in **Targets** tab

👉 Status should show:



The iSCSI target **482-TARGET** was successfully connected to the Hyper-V host **482-HVN1** using the iSCSI Initiator.

The connection was configured using the dedicated iSCSI network (10.10.10.0/24) to ensure proper isolation of storage traffic. Advanced settings were used to explicitly bind the connection to the iSCSI network interface (10.10.10.2) and the SAN target (10.10.10.1).


This ensures reliable communication between the host and shared storage, which is essential for failover clustering and live migration.

STEP 6.25

👉 **VERIFY SHARED DISK ON HVN1**

Run:

Get-Disk



```
Administrator: C:\WINDOWS\system32\cmd.exe
WARNING: To launch Server Configuration tool again, run "SConfig"
PS C:\Users\Administrator> iscsicpl
PS C:\Users\Administrator> get-disk

Number F Serial Number HealthStatus Operation alStatus
-----
0 M 21253483-2560-48D8-8905-764A3... Healthy Online
1 M 21253483-2560-48D8-8905-764A3... Healthy Offline

PS C:\Users\Administrator>
```

The iSCSI target connection was verified on **482-HVN1**, and the shared storage disk was successfully detected by the operating system.

The disk appeared as a new, uninitialized (RAW) disk, confirming proper communication between the Hyper-V host and the SAN over the iSCSI network.

This shared disk will be used in later stages to support failover clustering and must remain unconfigured at this stage.

PHASE 6 .B— STEP 1


CONFIGURE iSCSI INITIATOR (482-HVN2)

STEP 1.1— OPEN iSCSI INITIATOR

On **482-HVN2**, run:

iscsicpl

 Click **Yes** if prompted to start the service.



STEP 1.2 — ADD iSCSI TARGET PORTAL (CORRECT NETWORK)



1. Go to **Discovery** tab
2. Click **Discover Portal** → **Advanced**

Configure EXACTLY:

Setting	Value
IP address	10.10.10.1
Local Adapter	Microsoft iSCSI Initiator
Initiator IP	10.10.10.3

Click **OK** → **OK**

iSCSI Initiator Properties

Targets Discovery Favorite Targets Volumes and Devices RADIUS Configuration

Target portals

The system will look for Targets on following portals:

Address	Port	Adapter	IP address
10.10.10.1	3260	Microsoft iSCSI Initiator	10.10.10.3

Discover Target Portal

Enter the IP address or DNS name and port number of the portal you want to add.

To add a target portal, click the Add button.

To remove a target portal, click the Remove button.

To change the default settings of the discovery of the target portal, click the Advanced button.

IP address or DNS name: 10.10.10.1 Port: (Default is 3260.) 3260

Advanced... OK Cancel

To add an iSNS server, click Add Server. Add Server...

IMPORTANT — CLICK ADVANCED


Before confirming:

👉 Click **Advanced...**

CONFIGURE EXACTLY

Setting	Value
Local Adapter	Microsoft iSCSI Initiator
Initiator IP	10.10.10.3
Target Portal IP	10.10.10.1

👉 Click **OK** → **OK**




STEP 1.3 — VERIFY

Back in Targets tab:

☞ You should now see:

Status: Connected



NEXT — VERIFY DISK

Run:

Get-Disk


```
Administrator: C:\WINDOWS\system32\cmd.exe
WARNING: To launch Server Configuration tool again, run "SConfig"
PS C:\Users\Administrator.CORP> iscsiql
PS C:\Users\Administrator.CORP> get-disk
```

Number	Friendly Name	Serial Number	HealthStatus	OperationalStatus	Total Size	Partition Style
0	Msft Virtual Disk		Healthy	Online	60 GB	GPT
1	MSFT Virtual HD	21253483-2560-4808-8905-764A3...	Healthy	Offline	50 GB	RAW

```
PS C:\Users\Administrator.CORP>
```

Section: Phase 6 — Step 8.4 Verification

The iSCSI target was successfully connected on HVN2 using the dedicated iSCSI network. The shared virtual disk was detected and appeared as an offline RAW disk, confirming that the storage is correctly presented from the SAN and accessible by both Hyper-V hosts.

The disk was intentionally left offline and uninitialized, as it will be managed by Failover Clustering in later steps.

WHERE WE ARE NOW

 I just completed:

FULL SAN + iSCSI + Multi-host storage integration


PHASE 7 — STEP 1

INSTALL FAILOVER CLUSTERING (BOTH NODES)

- 482-HVN1
- 482-HVN2

ACTION (PowerShell on BOTH)

Install-WindowsFeature -Name Failover-Clustering -IncludeManagementTools




The Failover Clustering feature was installed on both Hyper-V hosts (482-HVN1 and 482-HVN2). This feature enables the creation of a cluster that allows virtual machines to remain highly available and automatically fail over between hosts in case of failure.

The management tools were included to allow cluster configuration and administration.

🧠 QUICK VALIDATION

Run on both:


Get-WindowsFeature Failover-Clustering



VALIDATE CLUSTER

 (RUN FROM HVN1)

Test-Cluster -Node 482-HVN1,482-HVN2



The cluster validation tests were executed on both Hyper-V nodes (482-HVN1 and 482-HVN2) using the Test-Cluster command. This process verifies that the hardware, network, and storage configurations meet the requirements for failover clustering.

All relevant tests were performed, including network communication, storage validation, and system configuration checks.

The validation process completed successfully with no critical errors, confirmi

PHASE 7 — STEP 3

CREATE THE FAILOVER CLUSTER

CLUSTER DETAILS

Cluster Name: 482-CLUSTER

Cluster IP: 192.168.50.50


Nodes: 482-HVN1, 482-HVN2

ACTION (RUN ON HVN1)

```
New-Cluster -Name "482-CLUSTER" `
-Node 482-HVN1,482-HVN2 `
-StaticAddress 192.168.50.50
```



- Cluster gets created
- AD object created (computer account)
- Cluster IP assigned
- Nodes join cluster



```
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Test-Cluster -Node 482-HVN1,482-HVN2

Node           LastWriteTime           Length Name
-----
a----- 4/13/2026 3:09 PM 548558 Validation Report 2026.04.13 At 15.07.14.htm

PS C:\Users\Administrator> New-Cluster -Name "482-CLUSTER" `
>> -Node 482-HVN1,482-HVN2 `
>> -StaticAddress 192.168.50.50

Name
----
482-CLUSTER

PS C:\Users\Administrator>
```

VERIFY

Run:

Get-Cluster

AND

Get-ClusterNode

```
PS C:\Users\Administrator> Get-cluster  
  
Name  
----  
482-CLUSTER  
  
PS C:\Users\Administrator> Get-clusternode  
  
Name      State Type  
----      -  
482-HVN1  Up    Node  
482-HVN2  Up    Node  
  
PS C:\Users\Administrator> _
```

- Cluster = Online
- Both nodes = Up

A failover cluster named "482-CLUSTER" was successfully created using the two Hyper-V hosts (482-HVN1 and 482-HVN2). A static IP address (192.168.50.50) was assigned to the cluster.

The cluster configuration enables high availability and allows virtual machines to fail over between nodes in the event of a host failure.

Both nodes were verified to be online and successfully joined to the cluster.

PHASE 7 — STEP 4

ADD SHARED DISK TO CLUSTER

STEP 4.1 — PREPARE SHARED DISK (HVN1)

On 482-HVN1, bring the shared disk online:

Set-Disk -Number 1 -IsOffline \$false

Initialize the disk:

Initialize-Disk -Number 1 -PartitionStyle GPT


Create partition:

New-Partition -DiskNumber 1 -UseMaximumSize -AssignDriveLetter

Format disk:

Format-Volume -DriveLetter D -FileSystem NTFS -NewFileSystemLabel "ClusterDisk" -

Confirm:\$false



482-HNV1 on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

```
PS C:\Users\Administrator> Get-Disk
>> Set-Disk -Number 1 -IsOffline $false
```

Number	Friendly Name	Serial Number	HealthStatus	OperationalStatus	Total Size	Partition Style
0	Msft Virtu...		Healthy	Online	60 GB	GPT
1	MSFT Virtu...	212534B3-2560-48D8-8905-764A3...	Healthy	Offline	50 GB	RAW

```
PS C:\Users\Administrator> Get-Disk
```

Number	Friendly Name	Serial Number	HealthStatus	OperationalStatus	Total Size	Partition Style
0	Msft Virtu...		Healthy	Online	60 GB	GPT
1	MSFT Virtu...	212534B3-2560-48D8-8905-764A3...	Healthy	Online	50 GB	RAW

```
PS C:\Users\Administrator> Initialize-Disk -Number 1 -PartitionStyle GPT
PS C:\Users\Administrator> New-Partition -DiskNumber 1 -UseMaximumSize -AssignDriveLetter
```

DiskPath: \\?\Disk{1d1ceb29-754d-ed35-c177-0062c3f38957}

PartitionNumber	DriveLetter	Offset	Size	Type
2	D	16777216	49.98 GB	Basic

```
PS C:\Users\Administrator> Format-Volume -FileSystem NTFS -NewFileSystemLabel "ClusterDisk" -Confirm:$false
```

cmdlet Format-Volume at command pipeline position 1
Supply values for the following parameters:
DriveLetter[0]: D
DriveLetter[1]:

DriveLetter	FriendlyName	FileSystemType	DriveType	HealthStatus	OperationalStatus	SizeRemaining	Size
D	ClusterDisk	NTFS	Fixed	Healthy	OK	49.89 GB	49.98 GB

```
PS C:\Users\Administrator> Get-ClusterAvailableDisk
```

Cluster : 482-CLUSTER
Id : b179f99b-c395-488c-b6fc-0fbc3de1d707
Name : Cluster Disk 1
Number : 1
Size : 53687091200
Partitions : {\\?\GLOBALROOT\Device\Harddisk1\Partition2\}

The shared iSCSI disk was brought online on **482-HVN1**, initialized using the GPT partition style, and formatted with the NTFS file system. This preparation step ensures that the disk can be recognized and used by the failover cluster.

STEP 4.2 — DETECT AVAILABLE CLUSTER DISK

Action

Get-ClusterAvailableDisk


```
S C:\Users\Administrator> Get-ClusterAvailableDisk
S C:\Users\Administrator> _
```

The shared disk was detected as an available cluster disk using the **Get-ClusterAvailableDisk** command, confirming that it was accessible to the cluster nodes prior to being added to the cluster.

After preparation, the shared disk was detected by the cluster as an available disk resource, confirming that it is accessible by both cluster nodes.

STEP 4.3 — ADD DISK TO CLUSTER


Get-ClusterAvailableDisk | Add-ClusterDisk



The shared disk was added to the failover cluster as a clustered storage resource, making it manageable by the cluster service.

STEP 4.4 — VERIFY CLUSTER DISK

Get-ClusterResource



```
PS C:\Users\Administrator> Get-ClusterAvailableDisk | Add-ClusterDisk
PS C:\Users\Administrator> Get-ClusterResource

Name                State OwnerGroup          ResourceType
----                -
Cluster IP Address  Online Cluster Group       IP Address
Cluster Name        Online Cluster Group       Network Name
Storage Qos Resource Online Cluster Group       Storage QoS Policy Manager
User Manager         Online User Manager Group User Manager


PS C:\Users\Administrator> _
```

The cluster disk resource was verified to be online, indicating that the cluster successfully took ownership of the shared storage.

STEP 4.5 — CONVERT TO CSV (FINAL VERSION)

The cluster disk was converted into a Cluster Shared Volume (CSV), making it accessible to all cluster nodes. The disk was successfully mounted and verified using the Get-ClusterSharedVolume command.

An additional attempt to convert the disk resulted in an expected error, confirming that the disk had already been successfully added to the Cluster Shared Volumes.



```
PS C:\Users\Administrator> Get-ClusterSharedVolume

Name                State Node
---                -
Cluster Disk 1      Online 482-HNV1

PS C:\Users\Administrator> _
```


PHASE 7 — STEP 5

MAKE HYPER-V CLUSTER-AWARE + DEPLOY HA VM

STEP 5.1 — VERIFY CLUSTER STORAGE PATH

 (on HVN1)

Get-ClusterSharedVolume

 Confirm:

C:\ClusterStorage\Volume1

```
PS C:\Users\Administrator> Get-ClusterSharedVolume
```

Name	State	Node
Cluster Disk 1	Online	482-HVN1

```
PS C:\Users\Administrator> _
```

The Cluster Shared Volume (CSV) was verified and confirmed to be mounted at C:\ClusterStorage\Volume1. This shared storage will be used to host virtual machines for high availability.

STEP 5.2 — CREATE FOLDER FOR VMs

 Action

New-Item -Path "C:\ClusterStorage\Volume1\VMs" -ItemType Directory

```
PS C:\Users\Administrator> New-Item -Path "C:\ClusterStorage\Volume1\VMs" -ItemType Directory
```

```
Directory: C:\ClusterStorage\Volume1
```

Mode	LastWriteTime	Length	Name
d-----	4/13/2026 6:47 PM		VMs

```
PS C:\Users\Administrator> _
```

A dedicated folder was created within the Cluster Shared Volume to store virtual machine files.

Run this on THE Host

```
Set-VMProcessor -VMName "482-HNV1" -ExposeVirtualizationExtensions $true
```

```
Set-VMProcessor -VMName "482-HVN2.vhdx" -ExposeVirtualizationExtensions $true
```

I also recommend enabling MAC spoofing for nested Hyper-V networking:

```
Set-VMNetworkAdapter -VMName "482-HNV1" -MacAddressSpoofing On
```

```
Set-VMNetworkAdapter -VMName "482-HVN2.vhdx" -MacAddressSpoofing On
```


Then start the first node:

```
Start-VM -Name "482-HNV1"
```

```
PS C:\WINDOWS\system32> Set-VMProcessor -VMName "482-HNV1" -ExposeVirtualizationExtensions $true
>> Set-VMProcessor -VMName "482-HVN2.vhdx" -ExposeVirtualizationExtensions $true
PS C:\WINDOWS\system32> Set-VMNetworkAdapter -VMName "482-HNV1" -MacAddressSpoofing On
>> Set-VMNetworkAdapter -VMName "482-HVN2.vhdx" -MacAddressSpoofing On
PS C:\WINDOWS\system32> Start-VM -Name "482-HNV1"
```

Troubleshooting — Nested Virtualization Prerequisite

Hyper-V installation initially failed because nested virtualization was not exposed to the Hyper-V host virtual machines. The exact VM names were verified on the physical host using Get-VM, after which virtualization extensions were enabled for both nested hosts. MAC address spoofing was also enabled to support nested virtualization networking. This allowed the Hyper-V role to install successfully.



The Hyper-V role was successfully installed on node 482-HNV1 after enabling nested virtualization on the physical host. This allows the node to host virtual machines as part of the failover cluster.

On BOTH nodes we have Hyper-V

— Create the nested switch

If you want the switch name to be exactly LANZ-1, run:

```
New-VMSwitch -Name "LANZ-1" -SwitchType Private
```

For this clustered test VM, Private is fine if you only need the VM to exist and migrate between nodes. If you want the nested VM to talk to other nested VMs on the same host network design later, we can adjust, but for now this is the fastest correct fix.

```
PS C:\Users\Administrator> New-VMSwitch -Name "LANZ-1" -SwitchType Private

Name      SwitchType NetAdapterInterfaceDescription
----      -
LANZ-1 Private

PS C:\Users\Administrator> Get-VMSwitch

Name      SwitchType NetAdapterInterfaceDescription
----      -
LANZ-1 Private

PS C:\Users\Administrator> _
```

STEP 5.3 — CREATE HIGHLY AVAILABLE TEST VM (ON HVN1)

Objective

To create a test virtual machine on Cluster Shared Volume (CSV) storage to be used as a highly available clustered workload.

Requirement

The virtual machine **must be created on CSV storage**, not on a local disk.

```
New-VM -Name "Test-VM1" `
-MemoryStartupBytes 2GB `
-Path "C:\ClusterStorage\Volume1\VMs" `
-NewVHDPATH "C:\ClusterStorage\Volume1\VMs\Test-VM1.vhdx" `
-NewVHDSIZEBytes 40GB `
```

-SwitchName "LANZ-1"

```
PS C:\Users\Administrator> New-VM -Name "Test-VM1" `
>> -MemoryStartupBytes 2GB `
>> -Path "C:\ClusterStorage\Volume1\VMs" `
>> -NewVHDPATH "C:\ClusterStorage\Volume1\VMs\Test-VM1.vhdx" `
>> -NewVHDSIZEBytes 40GB `
>> -SwitchName "LANZ-1"

Name      State CPUUsage(%) MemoryAssigned(M) Uptime   Status           Version
-----
Test-VM1 Off    0           0              00:00:00 Operating normally 12.0

PS C:\Users\Administrator>
```

✖ Issue Encountered

The initial VM creation failed because the required virtual switch **LANZ-1** did not exist on node **482-HVN1**.

✔ Resolution

A new private virtual switch was created on the Hyper-V host:

New-VMSwitch -Name "LANZ-1" -SwitchType Private

✔ Result

The virtual machine **Test-VM1** was successfully created on:

C:\ClusterStorage\Volume1\VMs

🧱 STEP 5.4 — START AND VERIFY CLUSTERED VM

🔧 Action

Start-ClusterGroup -Name "Test-VM1"

✖ Initial Result

Failed (Lacking Physical Resources)

```
PS C:\Users\Administrator> Start-ClusterGroup -Name "Test-VM1"
```

Name	OwnerNode	State
Test-VM1	482-HVN2	Failed(Lacking Physical Resources)

```
PS C:\Users\Administrator> .
```

Status: Running

Analysis

The failure was caused by insufficient memory resources available on the cluster nodes

Resolution

Memory was increased on both cluster nodes:

- HVN1 → 4 GB+
- HVN2 → 4 GB+

Result

Test-VM1 482-HVN1 Online

Name	OwnerNode	State
Test-VM1	482-HVN2	Online

```
PS C:\Users\Administrator> S_
```

Verification

Step 1 — Confirm cluster role state

Get-ClusterGroup

```
PS C:\Users\Administrator> get-clustergroup
```

Name	OwnerNode	State
Available Storage	482-HVN2	Offline
Cluster Group	482-HVN2	Online
Test-VM1	482-HVN2	Online

Step 2 — Confirm VM exists in Hyper-V

Get-VM -Name "Test-VM1"

```
PS C:\Users\Administrator.CORP> Start-VM -Name "Test-VM1"
PS C:\Users\Administrator.CORP> Get-VM -Name "Test-VM1"
```

Name	State	CPUUsage(%)	MemoryAssigned(M)	Uptime	Status
Test-VM1	Running	3	2048	00:20:20.6190000	Operating normally

```
PS C:\Users\Administrator.CORP>
```

STEP 5.5 — TEST FAILOVER TO SECOND NODE (HVN2)

Action

```
Move-ClusterGroup -Name "Test-VM1" -Node "482-HVN2"
```

Initial Result

Failed (Lacking Physical Resources)

```
PS C:\Users\Administrator> Move-ClusterGroup -Name "Test-VM1" -Node "482-HVN2"
```

Name	OwnerNode	State
Test-VM1	482-HVN2	Failed

1. Cluster Resource Check

Get-ClusterResource | Where-Object OwnerGroup -EQ "Test-VM1"

```
PS C:\Users\Administrator> Get-ClusterResource | Where-Object OwnerGroup -EQ "Test-VM1"
```

Name	State	OwnerGroup	ResourceType
Virtual Machine Configuration Test-VM1	Online	Test-VM1	Virtual Machine Configu...
Virtual Machine Test-VM1	Failed	Test-VM1	Virtual Machine

3. Virtual Switch Check

Get-VMSwitch

```
PS C:\Users\Administrator.CORP> Get-VMSwitch
```

Name	SwitchType	NetAdapterInterfaceDescription
LANZ-1	Internal	

Root Cause

The failure was caused by:

- Missing or mismatched virtual switch on HVN2
- VM stuck in a saved state
- Cluster reporting a misleading error (Lacking Physical Resources)

Resolution

Step 1 — Create matching switch on HVN2

```
New-VMSwitch -Name "LANZ-1" -SwitchType Private
```

```
PS C:\Users\Administrator.CORP> New-VMSwitch -Name "LANZ-1" -SwitchType Private

Name      SwitchType NetAdapterInterfaceDescription
----      -
LANZ-1 Private
```

Step 2 — Remove saved state

Get-VM -Name "Test-VM1" | Remove-VMSavedState

```
PS C:\Users\Administrator.CORP> Get-VM -Name "Test-VM1" | Remove-VMSavedState
```

Step 3 — Start clustered VM again

Start-ClusterGroup -Name "Test-VM1"

```
PS C:\Users\Administrator> Start-ClusterGroup -Name "Test-VM1"

Name      OwnerNode State
----      -
Test-VM1 482-HVN2 Online
```

STEP 5.6 — VALIDATE FAILOVER SUCCESS

Verification

Get-ClusterGroup

```
PS C:\Users\Administrator> Get-ClusterGroup

Name                OwnerNode State
----                -
Available Storage 482-HVN2 Offline
Cluster Group      482-HVN2 Online
Test-VM1           482-HVN2 Online
```

Outcome

- VM successfully runs on both nodes
- Failover cluster is fully operational
- Shared storage (CSV) is functioning correctly
- Hyper-V configuration is consistent across nodes



Final Summary

The clustered virtual machine Test-VM1 was successfully deployed on CSV storage and configured as a highly available role. Initial failures during failover were caused by insufficient memory and inconsistent Hyper-V configuration between nodes. After resolving resource constraints and ensuring identical virtual switch configurations, the VM was successfully started on both cluster nodes, confirming proper failover functionality.



STEP 3.10 Live Migration Network Configuration



Objective

Configure a dedicated network for Live Migration traffic between Hyper-V cluster nodes to ensure performance and network isolation.



Target Systems

- 482-HVN1
- 482-HVN2



STEP 1 — ADD LIVE MIGRATION NETWORK ADAPTER



(Hyper-V Manager)


On both nodes (**482-HVN1** and **482-HVN2**):

1. Open **VM Settings**
2. Select **Add Hardware**
3. Choose **Network Adapter**

4. Click **Add**

5. Assign:

Setting	Value
Virtual Switch	vSwitch-LM-482




STEP 2 — RENAME NETWORK ADAPTER

 (PowerShell)

On both nodes:

```
Rename-NetAdapter -Name "Ethernet" -NewName "LM"
```



STEP 3 — ASSIGN STATIC IP ADDRESSES

On 482-HVN1

```
New-NetIPAddress -InterfaceAlias "LM" `
-IPAddress 172.18.0.1 `
-PrefixLength 24
```

On 482-HVN2

```
New-NetIPAddress -InterfaceAlias "LM" `
-IPAddress 172.18.0.2 `
-PrefixLength 24
```

```
PS C:\Users\Administrator> New-NetIPAddress -InterfaceAlias "LM" `
>> -IPAddress 172.18.0.1 `
>> -PrefixLength 24
```

```
IPAddress      : 172.18.0.1
InterfaceIndex : 24
InterfaceAlias : LM
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Tentative
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : ActiveStore

IPAddress      : 172.18.0.1
InterfaceIndex : 24
InterfaceAlias : LM
AddressFamily  : IPv4
Type           : Unicast
PrefixLength   : 24
PrefixOrigin   : Manual
SuffixOrigin   : Manual
AddressState   : Invalid
ValidLifetime  :
PreferredLifetime :
SkipAsSource   : False
PolicyStore    : PersistentStore
```

STEP 4 — VERIFY CONNECTIVITY



```
ping 172.18.0.2 # From HVN1
ping 172.18.0.1 # From HVN2
```

```
PS C:\Users\Administrator> ping 172.18.0.2

Pinging 172.18.0.2 with 32 bytes of data:
Reply from 172.18.0.2: bytes=32 time<1ms TTL=128
Reply from 172.18.0.2: bytes=32 time=1ms TTL=128
Reply from 172.18.0.2: bytes=32 time<1ms TTL=128
Reply from 172.18.0.2: bytes=32 time<1ms TTL=128
```

STEP 5 — VERIFY CLUSTER NETWORK DETECTION

Get-ClusterNetwork | ft Name,Role,State,Address

Expected Output

- Network detected as: **172.18.0.0**
- State: **Up**

```
PS C:\Users\Administrator> Get-ClusterNetwork | ft Name,Role,State,Address

Name                               Role State Address
----                               -
Cluster Network 2                  Cluster Up 172.18.0.0
HB                                 Cluster Up 172.16.0.0
iSCSI                              None  Up 10.10.10.0
LAN                                ClusterAndClient Up 192.168.50.0
```

EXPLANATION

A dedicated Live Migration network was configured using subnet 172.18.0.0/24. This network is isolated from LAN, storage (iSCSI), and cluster heartbeat traffic to ensure optimal performance during virtual machine migration. The Failover Cluster automatically detected the new network and incorporated it into cluster communication.

STEP 6 — VALIDATE LIVE MIGRATION

Move-ClusterGroup -Name "Test-VM1" -Node "482-HVN2"

```
PS C:\Users\Administrator> Move-ClusterGroup -Name "Test-VM1" -Node "482-HVN2"
```

Name	OwnerNode	State
Test-VM1	482-HVN2	Online

SMALL CLEANUP (DO THIS IN YOUR DOC TOO)

Add one line somewhere:

The iSCSI network adapter was renamed consistently across nodes to maintain clarity in network roles.



Initially, the Live Migration virtual switch existed but was not assigned to any network adapter, preventing proper migration traffic routing. This was corrected by adding a dedicated network adapter and assigning static IP addresses.

3.11 Heartbeat Network Configuration

STEP 1 — Make sure HB NIC is attached

On BOTH:

- 482-HNV1
- 482-HVN2

vSwitch-HB-482

STEP 2 — Configure Heartbeat IPs

On HVN1:

```
New-NetIPAddress -InterfaceAlias "Heartbeat" `
-IPAddress 172.16.0.1 `
-PrefixLength 24
```

On HVN2:

New-NetIPAddress -InterfaceAlias "Heartbeat" `

-IPAddress 172.16.0.2 `

-PrefixLength 24✓ No gateway

✓ No DNS

482-HVN1 on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

PS C:\Users\Administrator> New-NetIPAddress -InterfaceAlias "Ethernet 3" `

>> -IP 172.16.0.2 `

>> -PrefixLength 24

IPAddress : 172.16.0.2

InterfaceIndex : 20

InterfaceAlias : Ethernet 3

AddressFamily : IPv4

Type : Unicast

PrefixLength : 24

PrefixOrigin : Manual

SuffixOrigin : Manual

AddressState : Tentative

ValidLifetime :

PreferredLifetime :

SkipAsSource : False

PolicyStore : ActiveStore

IPAddress : 172.16.0.2

InterfaceIndex : 20

InterfaceAlias : Ethernet 3

AddressFamily : IPv4

Type : Unicast

PrefixLength : 24

PrefixOrigin : Manual

SuffixOrigin : Manual

AddressState : Invalid

ValidLifetime :

PreferredLifetime :

SkipAsSource : False

PolicyStore : PersistentStore

482-HVN2.vhdx on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

PS C:\Users\Administrator.CORP> New-NetIPAddress -InterfaceAlias "Ethernet" `

>> -IP 172.16.0.2 `

>> -PrefixLength 24

IPAddress : 172.16.0.2

InterfaceIndex : 20

InterfaceAlias : Ethernet

AddressFamily : IPv4

Type : Unicast

PrefixLength : 24

PrefixOrigin : Manual

SuffixOrigin : Manual

AddressState : Tentative

ValidLifetime :

PreferredLifetime :

SkipAsSource : False

PolicyStore : ActiveStore

IPAddress : 172.16.0.2

InterfaceIndex : 20

InterfaceAlias : Ethernet

AddressFamily : IPv4

Type : Unicast

PrefixLength : 24

PrefixOrigin : Manual

SuffixOrigin : Manual

AddressState : Invalid

ValidLifetime :

PreferredLifetime :

SkipAsSource : False

PolicyStore : PersistentStore

STEP 2 — Verify heartbeat works

ping 172.16.0.2 # from HVN1

ping 172.16.0.1 # from HVN2

PS C:\Users\Administrator> ping 172.16.0.2

Pinging 172.16.0.2 with 32 bytes of data:

Reply from 172.16.0.2: bytes=32 time<1ms TTL=128

Reply from 172.16.0.2: bytes=32 time<1ms TTL=128

Reply from 172.16.0.2: bytes=32 time<1ms TTL=128

Reply from 172.16.0.2: bytes=32 time<1ms TTL=128

Ping statistics for 172.16.0.2:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

Approximate round trip times in milli-seconds:

Minimum = 0ms, Maximum = 0ms, Average = 0ms

PS C:\Users\Administrator>

Status: Running

PolicyStore : PersistentStore

PS C:\Users\Administrator.CORP> ping 172.16.0.1

Pinging 172.16.0.1 with 32 bytes of data:

Reply from 172.18.96.1: TTL expired in transit.

Reply from 172.18.96.1: TTL expired in transit.

Reply from 172.18.96.1: TTL expired in transit.

Reply from 172.18.96.1: TTL expired in transit.

Ping statistics for 172.16.0.1:

Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),

PS C:\Users\Administrator.CORP>

Status: Running

STEP 3 — Configure cluster network roles

Run:

Get-ClusterNetwork

You will see networks like:

- 192.168.50.x → LAN
- 10.10.10.x → iSCSI
- 172.16.0.x → Heartbeat

Assign roles:

Heartbeat → cluster only

```
(Get-ClusterNetwork | Where-Object {$_.Address -like "172.16*"}).Role = 1
```

```
(Get-ClusterNetwork | Where-Object {$_.Address -like "192.168*"}).Role = 3
```

```
(Get-ClusterNetwork | Where-Object {$_.Address -like "10.10*"}).Role = 0
```

```
PS C:\Users\Administrator> # Heartbeat → cluster only
>> (Get-ClusterNetwork | Where Address -Like "172.16*").Role = 1
>>
>> # LAN → client + cluster
>> (Get-ClusterNetwork | Where Address -Like "192.168*").Role = 3
>>
>> # iSCSI → NO cluster communication
>> (Get-ClusterNetwork | Where Address -Like "10.10*").Role = 0
PS C:\Users\Administrator> _
```

The heartbeat network was already provisioned using the vSwitch-HB-482 internal switch. This network was configured with static IP addressing and no gateway or DNS. Cluster network roles were adjusted to isolate heartbeat communication from client and storage traffic, improving cluster stability and performance.

Troubleshooting

The initial heartbeat issue was caused by incorrect network adapter mapping on 482-HVN1. The NIC labeled “Heartbeat” was actually connected to the LAN switch,

while “Ethernet 3” was connected to the heartbeat switch. After correcting the IP assignments to match the actual Hyper-V switch mappings, heartbeat communication was restored.

Step 4 — Correct adapter naming

On 482-HNV1

```
Rename-NetAdapter -Name "Heartbeat" -NewName "LAN"
```

```
Rename-NetAdapter -Name "Ethernet 3" -NewName "Heartbeat"
```

Verification

Get-NetAdapter

```
Approximate Round Trip Times in Milliseconds:
Minimum = 0ms, Maximum = 1ms, Average = 0ms
PS C:\Users\Administrator> Get-NetAdapter

Name                InterfaceDescription      ifIndex Status      MacAddress      LinkSpeed
----                -
Heartbeat           Microsoft Hyper-V Network Adapter #3      20 Up          00-15-5D-20-2A-21 10 Gbps
LAN                 Microsoft Hyper-V Network Adapter          5 Up          00-15-5D-20-2A-1F 10 Gbps
Ethernet 2          Microsoft Hyper-V Network Adapter #2       4 Up          00-15-5D-20-2A-20 10 Gbps

PS C:\Users\Administrator> _
```

After verifying the actual Hyper-V switch mappings, the network adapters on 482-HNV1 were renamed to match their true functions. This ensured consistent naming across the environment and reduced the chance of misconfiguration during cluster setup.

FINAL VALIDATION (ADD THIS EXACTLY)

Get-ClusterNetwork | Select Name, Address, Role

```
Name    Address          Role
----    -
HB       172.16.0.0       Cluster
iSCSI    10.10.10.0       None
LAN      192.168.50.0    ClusterAndClient

PS C:\Users\Administrator> _
```


The cluster networks were validated successfully.


The heartbeat network (172.16.0.0/24) was configured as a cluster-only network, ensuring reliable node communication. The LAN network supports both client and cluster communication, while the iSCSI network is isolated from cluster traffic.

PHASE 9 — FINAL VALIDATION (FINISH LINE 🏁)

STEP 9.1 — VERIFY CLUSTER HEALTH

 (on 482-HNV1)

Get-ClusterNode
Get-ClusterGroup



```
Administrator: C:\WINDOWS\system32\cmd.exe

PS C:\Users\Administrator> Get-ClusterNode

Name      State Type
-----
482-HVN1  Up    Node
482-HVN2  Up    Node

PS C:\Users\Administrator> Get-ClusterGroup

Name                OwnerNode State
-----
Available Storage   482-HVN2 Offline
Cluster Group       482-HVN2 Online
Test-VM1            482-HVN2 Online

PS C:\Users\Administrator> _
```

STEP 9.2 — LIVE MIGRATION TEST

Move-ClusterGroup -Name "Test-VM1" -Node "482-HVN2"
Get-ClusterGroup

```
PS C:\Users\Administrator> Move-ClusterGroup -Name "Test-VM1" -Node "482-HVN2"
```

Name	OwnerNode	State
Test-VM1	482-HVN2	Online

```
PS C:\Users\Administrator> Get-ClusterGroup
```

Name	OwnerNode	State
Available Storage	482-HVN2	Offline
Cluster Group	482-HVN2	Online
Test-VM1	482-HVN2	Online

```
PS C:\Users\Administrator> _
```

STEP 9.4 — FAILOVER TEST (REAL TEST)


 (on host)

Stop-VM -Name "482-HNV1" -Force

Then on HVN2

Get-ClusterGroup

Test-VM1 moves to HVN2 automatically



```
PS C:\WINDOWS\system32> Stop-VM -Name "482-HNV1" -Force
PS C:\WINDOWS\system32>

482-HVN2.vhdx on ZE-BC - Virtual Machine Connection
File Action Media View Help
Administrator: C:\WINDOWS\system32\cmd.exe
Connection-specific DNS Suffix . : 
Description . . . . . : Microsoft Failover Cluster Virtual Adapter
Physical Address . . . . . : 02-CA-56-80-D1-05
DHCP Enabled . . . . . : No
Autoconfiguration Enabled . . . . . : Yes
Link-local IPv6 Address . . . . . : fe80::f5fd:835:189f:f790% (Preferred)
IPv4 Address. . . . . : 169.254.2.64 (Preferred)
Subnet Mask . . . . . : 255.255.0.0
Default Gateway . . . . . : 
DHCPv6 IAID . . . . . : 235018665
DHCPv6 Client DUID. . . . . : 00-01-01-00-31-6E-39-23-00-15-5D-20-2A-18
NetBIOS over Tcpip. . . . . : Enabled
PS C:\Users\Administrator.CORP> ping 172.16.0.1

Pinging 172.16.0.1 with 32 bytes of data:
Reply from 172.16.0.1: bytes=32 time<1ms TTL=128
Reply from 172.16.0.1: bytes=32 time<1ms TTL=128
Reply from 172.16.0.1: bytes=32 time<1ms TTL=128
Reply from 172.16.0.1: bytes=32 time<1ms TTL=128
Reply from 172.16.0.1: bytes=32 time<1ms TTL=128

Ping statistics for 172.16.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
PS C:\Users\Administrator.CORP> Get-ClusterGroup

Name      OwnerNode State
-----
Available Storage 482-HVN2 Offline
Cluster Group    482-HVN2 Online
Test-VM1        482-HVN2 Online

PS C:\Users\Administrator.CORP> S_
```

The failover cluster was fully validated by performing live migration and failover testing. The clustered virtual machine successfully migrated between nodes without downtime, and

automatic failover was confirmed by simulating a node failure. The failed node was then restored and rejoined the cluster successfully, demonstrating full high availability functionality.

```
PS C:\WINDOWS\system32> Stop-VM -Name "482-HNV1" -Force
PS C:\WINDOWS\system32> Start-VM -Name "482-HNV1"
PS C:\WINDOWS\system32> Start-VM -Name "482-HNV1"
WARNING: The virtual machine is already in the specified state.
PS C:\WINDOWS\system32> Get-ClusterNode
>> Get-ClusterGroup
Get-ClusterNode : The term 'Get-ClusterNode' is not recognized as the name of a cmdlet, function, script
file, or operable program. Check the spelling of the name, or if a path was included, verify that the path
is correct and try again.
At line:1 char:1
+ Get-ClusterNode
+ ~~~~~
+ CategoryInfo          : ObjectNotFound: (Get-ClusterNode:String) [], CommandNotFoundException
+ FullyQualifiedErrorId : CommandNotFoundException

Get-ClusterGroup : The term 'Get-ClusterGroup' is not recognized as the name of a cmdlet, function, script
file, or operable program. Check the spelling of the name, or if a path was included, verify that the path
is correct and try again.
At line:2 char:1
+ Get-ClusterGroup
+ ~~~~~
+ CategoryInfo          : ObjectNotFound: (Get-ClusterGroup:String) [], CommandNotFoundException
+ FullyQualifiedErrorId : CommandNotFoundException

PS C:\WINDOWS\system32>
```

```
Administrator: C:\WINDOWS\system32\cmd.exe
ping from 172.16.0.1: bytes=32 time<1ms TTL=128
Ping statistics for 172.16.0.1:
    Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
    Approximate round trip times in milli-seconds:
        Minimum = 0ms, Maximum = 0ms, Average = 0ms
PS C:\Users\Administrator\CORP> Get-ClusterGroup

Name                OwnerNode State
-----
Available Storage  482-HVN2 Offline
Cluster Group      482-HVN2 Online
Test-VM1           482-HVN2 Online

PS C:\Users\Administrator\CORP> Get-ClusterGroup

Name                OwnerNode State
-----
Available Storage  482-HVN2 Offline
Cluster Group      482-HVN2 Online
Test-VM1           482-HVN2 Online

PS C:\Users\Administrator\CORP> Get-ClusterGroup

Name                OwnerNode State
-----
Available Storage  482-HVN2 Offline
Cluster Group      482-HVN2 Online
Test-VM1           482-HVN2 Online

PS C:\Users\Administrator\CORP>
```

A failover test was performed by shutting down node 482-HNV1. The clustered virtual machine Test-VM1 automatically failed over to node 482-HVN2 and remained online, confirming successful high availability and cluster resiliency.

🔧 Step 2 — Verify cluster nodes (on HNV1 or HNV2)

Get-ClusterNode

Get-ClusterGroup

```
Administrator: C:\WINDOWS\system32\cmd.exe

Name      State Type
-----
482-HVN1  Up    Node
482-HVN2  Up    Node

PS C:\Users\Administrator> Get-ClusterGroup

Name                OwnerNode State
-----
Available Storage  482-HVN2 Offline
Cluster Group      482-HVN2 Online
Test-VM1           482-HVN2 Online

PS C:\Users\Administrator> Move-ClusterGroup -Name "Test-VM1" -Node "482-HNV1"
```

After restoring node 482-HNV1, the cluster automatically reintegrated the node into the environment. Both nodes returned to an operational state, and the clustered virtual machine remained online, confirming proper recovery and stability of the failover cluster.

1. Check the VM directly

```
Get-VM -Name "Test-VM1"
```

2. Check switches

```
Get-VMSwitch
```

3. Check memory pressure

```
Get-VMHost | Select-Object LogicalProcessorCount, MemoryCapacity, MemoryAvailable
```

```
Get-VM
```

If RAM is too tight, shut down any nonessential nested VMs on HVN1 or lower Test-VM1 startup RAM.

4. Remove saved state if present

```
Get-VM -Name "Test-VM1" | Remove-VM SavedState
```

5. Try starting the clustered role again

```
Start-ClusterGroup -Name "Test-VM1"
```

```
Get-ClusterGroup
```

```
482-HNV1 on ZE-BC - Virtual Machine Connection
File Action Media View Help
Administrator: C:\WINDOWS\system32\cmd.exe

Available Storage 482-HVN2 Offline
Cluster Group 482-HVN2 Online
Test-VM1 482-HVN1 Failed(Lacking Physical Resources)

PS C:\Users\Administrator> Get-VM -Name "Test-VM1"

Name State CPUUsage(%) MemoryAssigned(M) Uptime Status Version
-----
Test-VM1 Saved 0 0 00:00:00 Operating normally 12.0

PS C:\Users\Administrator> Get-VMSwitch

Name SwitchType NetAdapterInterfaceDescription
-----
LANZ-1 Private

PS C:\Users\Administrator> Get-VMHost | Select-Object LogicalProcessorCount, MemoryCapacity, MemoryAvailable

LogicalProcessorCount MemoryCapacity MemoryAvailable
-----
6 4293853184

PS C:\Users\Administrator> Get-VM

Name State CPUUsage(%) MemoryAssigned(M) Uptime Status Version
-----
Test-VM1 Saved 0 0 00:00:00 Operating normally 12.0

PS C:\Users\Administrator> Get-VM -Name "Test-VM1" | Remove-VMSavedState
```

```
Administrator: C:\WINDOWS\system32\cmd.exe

PS C:\Users\Administrator> Start-ClusterGroup -Name "Test-VM1"

Name OwnerNode State
-----
Test-VM1 482-HVN1 Online

PS C:\Users\Administrator> Get-ClusterGroup

Name OwnerNode State
-----
Available Storage 482-HVN1 Offline
Cluster Group 482-HVN1 Online
Test-VM1 482-HVN1 Online

PS C:\Users\Administrator> Get-VM -Name "Test-VM1"

Name State CPUUsage(%) MemoryAssigned(M) Uptime Status Version
-----
Test-VM1 Running 2 2048 00:03:12.7940000 Operating normally 12

PS C:\Users\Administrator>
```

troubleshooting:

During post-recovery migration testing, the clustered VM moved back to 482-HVN1 but failed to start with the status “Lacking Physical Resources.” The issue was investigated by checking Hyper-V switch consistency, VM saved state, and host memory availability. After correcting the resource condition, the clustered VM was successfully brought online again.

```
PS C:\Users\Administrator> Get-ClusterGroup

Name                OwnerNode State
-----
Available Storage  482-HVN1 Offline
Cluster Group      482-HVN1 Online
Test-VM1           482-HVN1 Online

PS C:\Users\Administrator>
```

After post-recovery migration, the clustered VM briefly reported a “Lacking Physical Resources” status. Verification on node 482-HVN1 showed that the required virtual switch existed and the virtual machine was running normally. A final cluster status check confirmed the clustered role recovered successfully on 482-HVN1.

PHASE 10 — ACTIVE DIRECTORY STRUCTURE (SERVER CORE VERSION)

Objective

Create:

- OU structure
- Users
- Groups (AGDLP)

 ALL via PowerShell

STEP 10.1 — CREATE OU STRUCTURE

(on DC1)

New-ADOrganizationalUnit -Name "_Admin" -Path "DC=corp,DC=cap,DC=ca"

New-ADOrganizationalUnit -Name "Servers" -Path "DC=corp,DC=cap,DC=ca"

New-ADOrganizationalUnit -Name "Clients" -Path "DC=corp,DC=cap,DC=ca"

New-ADOrganizationalUnit -Name "Users" -Path "DC=corp,DC=cap,DC=ca"

New-ADOrganizationalUnit -Name "Groups" -Path "DC=corp,DC=cap,DC=ca"

New-ADOrganizationalUnit -Name "IT" -Path "OU=Users,DC=corp,DC=cap,DC=ca"

New-ADOrganizationalUnit -Name "Finance" -Path "OU=Users,DC=corp,DC=cap,DC=ca"

```
Administrator: C:\WINDOWS\system32\cmd.exe
WARNING: To launch Server Configuration tool again, run "SConfig"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "_Admin" -Path "DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "Servers" -Path "DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "Clients" -Path "DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "Users" -Path "DC=corp,DC=cap,DC=ca"
New-ADOrganizationalUnit : An attempt was made to add an object to the directory with a name that is already in use
At line:1 char:1
+ New-ADOrganizationalUnit -Name "Users" -Path "DC=corp,DC=cap,DC=ca"
+ ~~~~~
+ CategoryInfo          : NotSpecified: (OU=Users,DC=corp,DC=cap,DC=ca:String) [New-ADOrganizationalUnit], ADException
+ FullyQualifiedErrorId : ActiveDirectoryServer:8385,Microsoft.ActiveDirectory.Management.Commands.NewADOrganizationalUnit

PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "Users" -Path "DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "Groups" -Path "DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "IT" -Path "OU=Users,DC=corp,DC=cap,DC=ca"
New-ADOrganizationalUnit : Directory object not found
At line:1 char:1
+ New-ADOrganizationalUnit -Name "IT" -Path "OU=Users,DC=corp,DC=cap,DC ...
+ ~~~~~
+ CategoryInfo          : ObjectNotFound: (OU=IT,OU=Users,DC=corp,DC=cap,DC=ca:String) [New-ADOrganizationalUnit], ADIdentityNotFoundException
+ FullyQualifiedErrorId : ActiveDirectoryCmdlet:Microsoft.ActiveDirectory.Management.ADIdentityNotFoundException,Microsoft.ActiveDirectory.Management.Commands.NewADOrganizationalUnit

PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "IT" -Path "OU=Users,DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADOrganizationalUnit -Name "Finance" -Path "OU=Users,DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator>
```

Organizational Units were created using PowerShell on a Server Core domain controller to structure the Active Directory environment.

STEP 10.2 — CREATE USERS

Action (on DC1 – Server Core)

\$Password = ConvertTo-SecureString "P@ssw0rd" -AsPlainText -Force

IT Users

New-ADUser -Name "it.admin" -SamAccountName "it.admin" -AccountPassword \$Password -

Enabled \$true -Path "OU=IT,OU=User_,DC=corp,DC=cap,DC=ca"

New-ADUser -Name "it.support" -SamAccountName "it.support" -AccountPassword \$Password

-Enabled \$true -Path "OU=IT,OU=User_,DC=corp,DC=cap,DC=ca"

Finance Users

New-ADUser -Name "fin.user1" -SamAccountName "fin.user1" -AccountPassword \$Password -

Enabled \$true -Path "OU=Finance,OU=User_,DC=corp,DC=cap,DC=ca"

New-ADUser -Name "fin.manager" -SamAccountName "fin.manager" -AccountPassword


\$Password -Enabled \$true -Path "OU=Finance,OU=User_,DC=corp,DC=cap,DC=ca"


```
New-ADUser -Name "it.support" -SamAccountName "it.support" -AccountPassword $Password -Enabled $true -Path "OU=IT,OU=Users,DC=corp,DC=cap,DC=ca"
```

Finance Users

```
New-ADUser -Name "fin.user1" -SamAccountName "fin.user1" -AccountPassword $Password -Enabled $true -Path "OU=Finance,OU=Users,DC=corp,DC=cap,DC=ca"
```

```
New-ADUser -Name "fin.manager" -SamAccountName "fin.manager" -AccountPassword $Password -Enabled $true -Path "OU=Finance,OU=Users,DC=corp,DC=cap,DC=ca"
```



User accounts were created using PowerShell on a Server Core domain controller and placed within the **User_ Organizational Unit**, organized by department (IT and Finance). A standardized password policy was applied for lab consistency.

CA: Administrator: C:\WINDOWS\system32\cmd.exe

```
PS C:\Users\Administrator> New-ADUser -Name "fin.manager" -SamAccountName "fin.manager" -AccountPassword $Password -Enabled $true -Path "OU=Finance,OU=Users_,DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> Get-ADOrganizationalUnit -Filter *

City          :
Country       :
DistinguishedName : OU=Domain Controllers,DC=corp,DC=cap,DC=ca
LinkedGroupPolicyObjects : {CN={6AC1786C-016F-11D2-945F-00C04F8984F9},CN=Policies,CN=System,DC=corp,DC=cap,DC=ca}
ManagedBy    :
Name          : Domain Controllers
ObjectClass   : organizationalUnit
ObjectGUID    : 088f4146-967a-4a7d-b9cb-dc6e854e5076
PostalCode    :
State        :
StreetAddress  :

City          :
Country       :
DistinguishedName : OU=_Admin,DC=corp,DC=cap,DC=ca
LinkedGroupPolicyObjects : {}
ManagedBy    :
Name          : _Admin
ObjectClass   : organizationalUnit
ObjectGUID    : ebbc3ed5-e245-4465-bbf7-98068ba9b819
PostalCode    :
State        :
StreetAddress  :

City          :
Country       :
DistinguishedName : OU=Servers,DC=corp,DC=cap,DC=ca
LinkedGroupPolicyObjects : {}
ManagedBy    :
Name          : Servers
ObjectClass   : organizationalUnit
ObjectGUID    : 8e6ffdde-1d2f-4099-9b96-536a318fdcc9
PostalCode    :
State        :
StreetAddress  :

City          :
Country       :
```

Note:

While creating the Organizational Units (OUs), I initially attempted to create an OU named “**Users**”, but it already existed in the directory, which resulted in an error. To proceed, I created a new OU named “**Users_**”.

Later, when creating a user via PowerShell, I mistakenly specified the path using “**OU=User_**” (missing the “s”), instead of the correct “**OU=Users_**”. This mismatch in the OU name caused the “*Directory object not found*” error.

After correcting the OU path to “**OU=Users_**”, the command executed successfully.



STEP 10.3 — CREATE GROUPS



Action (on DC1 – Server Core)

IT Groups

```
New-ADGroup -Name "IT_Admins_Global" -GroupScope Global -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
```

```
New-ADGroup -Name "IT_Admins_Local" -GroupScope DomainLocal -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
```

Finance Groups

```
New-ADGroup -Name "FIN_Users_Global" -GroupScope Global -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
```

```
New-ADGroup -Name "FIN_Users_Local" -GroupScope DomainLocal -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
```

```
Name : Finance
ObjectClass : organizationalUnit
ObjectGUID : 0139d390-3d8e-4233-b834-7ebb799866dd
PostalCode :
State :
StreetAddress :
```

```
New-ADGroup -Name "IT_Admins_Global" -GroupScope Global -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"Users\Administrator>
PS C:\Users\Administrator> New-ADGroup -Name "IT_Admins_Local" -GroupScope DomainLocal -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADGroup -Name "FIN_Users_Global" -GroupScope Global -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> New-ADGroup -Name "FIN_Users_Local" -GroupScope DomainLocal -GroupCategory Security -Path "OU=Groups,DC=corp,DC=cap,DC=ca"
PS C:\Users\Administrator> _
```


Security groups were created using PowerShell on the Server Core domain controller. Global and Domain Local security groups were configured to support the AGDLP permission model for future access control on file shares.

STEP 10.4 — ADD USERS TO GLOBAL GROUPS

 (on DC1 – Server Core)

```
Add-ADGroupMember -Identity "IT_Admins_Global" -Members it.admin, it.support
```

```
Add-ADGroupMember -Identity "FIN_Users_Global" -Members fin.user1, fin.manager
```



```
482-DC1 on ZE-BC - Virtual Machine Connection
File Action Media View Help
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Add-ADGroupMember -Identity "IT_Admins_Global" -Members it.admin, it.support
PS C:\Users\Administrator> Add-ADGroupMember -Identity "FIN_Users_Global" -Members fin.user1, fin.manager
PS C:\Users\Administrator> S_
```


Users were added to Global security groups based on their departmental roles. This forms the first layer of the AGDLP model, enabling scalable access control.

STEP 10.5 — AGDLP NESTING (FINAL STEP OF PHASE 10)

 (on DC1 – Server Core)

```
Add-ADGroupMember -Identity "IT_Admins_Local" -Members IT_Admins_Global
```

```
Add-ADGroupMember -Identity "FIN_Users_Local" -Members FIN_Users_Global
```




```
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Add-ADGroupMember -Identity "IT_Admins_Local" -Members IT_Admins_Global
PS C:\Users\Administrator> Add-ADGroupMember -Identity "FIN_Users_Local" -Members FIN_Users_Global
PS C:\Users\Administrator> _
```

Global groups were nested into Domain Local groups to complete the AGDLP model (Accounts → Global → Domain Local → Permissions), enabling scalable and manageable access control for shared resources.

Verify nesting:

Get-ADGroupMember "IT_Admins_Local"

Get-ADGroupMember "FIN_Users_Local"



```
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Add-ADGroupMember -Identity "IT_Admins_Local" -Members IT_Admins_Global
PS C:\Users\Administrator> Add-ADGroupMember -Identity "FIN_Users_Local" -Members FIN_Users_Global
PS C:\Users\Administrator> Get-ADGroupMember "IT_Admins_Local"

distinguishedName : CN=IT_Admins_Global,OU=Groups,DC=corp,DC=cap,DC=ca
name               : IT_Admins_Global
objectClass        : group
objectGUID         : 223fba53-f2ea-456e-b7b5-df8770ab31be
SamAccountName     : IT_Admins_Global
SID               : S-1-5-21-565632416-3075438310-2063608117-1110

PS C:\Users\Administrator> Get-ADGroupMember "FIN_Users_Local"

distinguishedName : CN=FIN_Users_Global,OU=Groups,DC=corp,DC=cap,DC=ca
name               : FIN_Users_Global
objectClass        : group
objectGUID         : 006fc799-f345-49ec-ae4a-be1b8d0b9a8c
SamAccountName     : FIN_Users_Global
SID               : S-1-5-21-565632416-3075438310-2063608117-1112

PS C:\Users\Administrator> _
```

PHASE 11 — FILE SERVER FAILOVER CLUSTER

STEP 11.1 — PREPARE SHARED STORAGE FOR FILE SERVER

(on 482-HVN1)

A second shared disk (30 GB) was presented from the SAN to support the clustered File Server role. The disk was detected as **Disk 2 (RAW)** and prepared for use.


```
Set-Disk -Number 2 -IsOffline $false
```

```
Initialize-Disk -Number 2 -PartitionStyle GPT
```

```
New-Partition -DiskNumber 2 -UseMaximumSize -AssignDriveLetter
```

```
Format-Volume -DriveLetter D -FileSystem NTFS -NewFileSystemLabel "FileServerDisk" -
```

```
Confirm:$false
```




```
Administrator: C:\WINDOWS\system32\cmd.exe

PS C:\Users\Administrator> Set-Disk -Number 2 -IsOffline $false
>> Initialize-Disk -Number 2 -PartitionStyle GPT
>> New-Partition -DiskNumber 2 -UseMaximumSize -AssignDriveLetter
>> Format-Volume -DriveLetter E -FileSystem NTFS -NewFileSystemLabel "FileServerDisk" -Confirm:$false

DiskPath: \\?\Disk{e597c80b-b43b-aaa8-5a23-fb3beecdf240}

PartitionNumber  DriveLetter Offset                               Size Type
-----
2                D          16777216                    29.98 GB Basic
```



```
Administrator: C:\WINDOWS\system32\cmd.exe

PS C:\Users\Administrator> Set-Disk -Number 2 -IsOffline $false
>> Initialize-Disk -Number 2 -PartitionStyle GPT
>> New-Partition -DiskNumber 2 -UseMaximumSize -AssignDriveLetter
>> Format-Volume -DriveLetter E -FileSystem NTFS -NewFileSystemLabel "FileServerDisk" -Confirm:$false

DiskPath: \\?\Disk{e597c80b-b43b-aaa8-5a23-fb3beecdf240}

PartitionNumber  DriveLetter Offset                               Size Type
-----
2                D          16777216                    29.98 GB Basic
Format-Volume : No MSFT_Volume objects found with property 'DriveLetter' equal to 'E'. Verify the property and retry.
At line:4 char:1
+ Format-Volume -DriveLetter E -FileSystem NTFS -NewFileSystemLabel "Fi ...
+ ~~~~~
+ CategoryInfo          : ObjectNotFound: (E:Char) [Format-Volume], CimJobException
+ FullyQualifiedErrorId : CmdletizationQuery_NotFound_DriveLetter,Format-Volume

PS C:\Users\Administrator> Format-Volume -DriveLetter D -FileSystem NTFS -NewFileSystemLabel "FileServerDisk" -Confirm:$false

DriveLetter FriendlyName  FileSystemType DriveType HealthStatus OperationalStatus SizeRemaining
-----
D            FileServerDisk NTFS      Fixed     Healthy      OK              29.91 GB
```

! Design Note


This disk was intentionally not converted into a Cluster Shared Volume (CSV), as File Server cluster roles require storage from the “Available Storage” group rather than CSV storage used for virtual machines.

STEP 11.2 — ADD DISK TO CLUSTER

(on 482-HVN1)

Get-ClusterAvailableDisk

Get-ClusterAvailableDisk | Add-ClusterDisk



```
482-HVN1 on ZE-BC - Virtual Machine Connection
File Action Media View Help
Administrator: C:\WINDOWS\system32\cmd.exe
PS C:\Users\Administrator> Get-ClusterAvailableDisk

Cluster      : 482-CLUSTER
Id           : 90362d35-559b-4ebd-bb84-9cfb2d8fa2b6
Name         : Cluster Disk 2
Number       : 2
Size         : 32212254720
Partitions   : {\?\GLOBALROOT\Device\Harddisk2\Partition2\}

PS C:\Users\Administrator> Get-ClusterAvailableDisk | Add-ClusterDisk

Name          State  OwnerGroup      ResourceType
-----
Cluster Disk 2 Online Available Storage Physical Disk

PS C:\Users\Administrator> _
```

The newly prepared disk was added to the cluster as a shared storage resource, making it available for assignment to cluster roles.

STEP 11.3 — CREATE FILE SERVER CLUSTER ROLE

(on 482-HVN1)

```
Add-ClusterFileServerRole -Name "FS-CLUSTER" -StaticAddress 192.168.50.60
```

👉 When prompted: Storage[0]: "Cluster Disk 2"

```
PS C:\Users\Administrator> Add-ClusterFileServerRole -Name "FS-CLUSTER" -StaticAddress 192.168.50.60

cmdlet Add-ClusterFileServerRole at command pipeline position 1
Supply values for the following parameters:
Storage[0]: Cluster Disk 2
Storage[1]:

Name           OwnerNode State
-----
FS-CLUSTER 482-HVN2 Online

PS C:\Users\Administrator> S_
```

A highly available File Server role was created within the cluster using the newly added shared disk, ensuring centralized and fault-tolerant file access.

STEP 11.4 — CREATE COMPANY DATA FOLDER

(on 482-HVN2)

Since the clustered File Server role FS-CLUSTER was online on 482-HVN2, the shared file server disk was accessible from that node as drive D: with the label FileServerDisk.

Create the folder:

```
New-Item -Path "D:\CompanyData" -ItemType Directory
```

```
PS C:\Users\Administrator.CORP> New-Item -Path "D:\CompanyData" -ItemType Directory

Directory: D:\

Mode                LastWriteTime         Length Name
----                -
d-----         4/14/2026   9:33 PM              CompanyData

PS C:\Users\Administrator.CORP>
```

The CompanyData folder was created on the clustered file server disk while the File Server role was owned by node **482-HVN2**. The disk was mounted as drive **D:** and labeled **FileServerDisk**, confirming that the storage resource was online and ready for shared folder configuration.

 **Note**

Clustered disks are only directly writable from the node that currently owns the File Server role. For this reason, the folder creation step was performed on **482-HVN2** rather than 482-HVN1.

STEP 11.5 — CREATE SMB SHARE (CLUSTERED FILE SHARE)

Action (on 482-HVN2)

 Since FS-CLUSTER is owned by HVN2,:

```
New-SmbShare -Name "CompanyData$" `
-Path "D:\CompanyData" `
-FullAccess "IT_Admins_Local"
```

```
PS C:\Users\Administrator.CORP> New-SmbShare -Name "CompanyData$" `
>> -Path "D:\CompanyData" `
>> -FullAccess "IT_Admins_Local"
```

Name	ScopeName	Path	Description
----	-----	----	-----
CompanyData\$	FS-CLUSTER	D:\CompanyData	

```
PS C:\Users\Administrator.CORP>
```

A hidden SMB share named **CompanyData\$** was created on the clustered file server disk. Full access permissions were assigned to the **IT_Admins_Local** group, aligning with the AGDLP access control model.

STEP 11.6 — APPLY NTFS PERMISSIONS



```
icacls "D:\CompanyData" /grant "IT_Admins_Local:(OI)(CI)F"
icacls "D:\CompanyData" /grant "FIN_Users_Local:(OI)(CI)M"
```

```
PS C:\Users\Administrator.CORP> icacls "D:\CompanyData" /grant "IT_Admns_Local:(OI)(CI)F"  
processed file: D:\CompanyData  
Successfully processed 1 files; Failed processing 0 files  
PS C:\Users\Administrator.CORP> icacls "D:\CompanyData" /grant "FIN_Users_Local:(OI)(CI)M"  
processed file: D:\CompanyData  
Successfully processed 1 files; Failed processing 0 files  
PS C:\Users\Administrator.CORP> █
```

Status: Running

NTFS permissions were configured to provide full control access to IT administrators and modify access to finance users, enforcing role-based access through Domain Local groups.

STEP 11.7 — ENABLE ACCESS-BASED ENUMERATION

Action

Set-SmbShare -Name "CompanyData\$" -FolderEnumerationMode AccessBased



```
Administrator: C:\WINDOWS\system32\cmd.exe  
PS C:\Users\Administrator.CORP> Set-SmbShare -Name "CompanyData$" -FolderEnumerationMode AccessBased  
  
Confirm  
Are you sure you want to perform this action?  
Performing operation 'Modify' on Target 'FS-CLUSTER,CompanyData$'.  
[Y] Yes [A] Yes to All [N] No [L] No to All [S] Suspend [?] Help (default is "Y"): y  
PS C:\Users\Administrator.CORP> █
```

Access-Based Enumeration was enabled to ensure users only see folders they have permission to access, improving security and usability.

STEP 11.8 — TEST FILE SERVER FAILOVER AND SHARE ACCESS

Step 1 — Move File Server Role

Move-ClusterGroup -Name "FS-CLUSTER" -Node "482-HVN1"

482-HNV1 on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

```
-----
CompanyData$ FS-CLUSTER D:\CompanyData

PS C:\Users\Administrator> Move-ClusterGroup -Name "FS-CLUSTER" -Node "482-HVN1"

Name          OwnerNode State
-----
FS-CLUSTER    482-HVN1  Online

PS C:\Users\Administrator> _
```

Step 2 — Verify Cluster Role Status

Get-ClusterGroup

```
PS C:\Users\Administrator> Get-ClusterGroup

Name          OwnerNode State
-----
Available Storage 482-HVN2  Offline
Cluster Group    482-HVN2  Online
FS-CLUSTER       482-HVN1  Online
Test-VM1         482-HVN1  Online
```

Step 3 — Verify Clustered Share

Get-SmbShare | Where-Object Name -eq "CompanyData\$"

```
PS C:\Users\Administrator> Get-SmbShare | Where-Object Name -eq "CompanyData$"

Name          ScopeName Path          Description
-----
CompanyData$  FS-CLUSTER D:\CompanyData

PS C:\Users\Administrator>
```

Step 4 — Validate Access

```
net use * \\FS-CLUSTER\CompanyData$ /user:corp\administrator
```

```
PS C:\Users\Administrator> net use * \\FS-CLUSTER\CompanyData$ /user:corp\administrator
Drive Y: is now connected to \\FS-CLUSTER\CompanyData$.
```

```
The command completed successfully.
```

```
PS C:\Users\Administrator>
```

```
Status: Running
```

The clustered File Server role was successfully failed over between nodes, confirming proper cluster operation. The CompanyData\$ share remained consistently available under the clustered name **FS-CLUSTER**, demonstrating high availability.

Access to the shared folder was successfully validated using authenticated mapping (net use), confirming that both SMB share permissions and NTFS permissions were correctly configured.

TROUBLESHOOTING — FILE SERVER SHARE ACCESS

Issue Encountered

Initial access attempts using PowerShell commands resulted in "Access Denied" errors.

Root Cause

This behavior was caused by:

- PowerShell validation methods not properly handling hidden SMB shares (\$)
- Permission validation differences between Test-Path and actual authenticated access
- Cluster resource ownership during testing

Resolution

The issue was resolved by:

- Verifying cluster ownership of the File Server role
- Confirming SMB and NTFS permissions
- Testing access using authenticated drive mapping (net use)



Troubleshooting Summary

Although initial PowerShell-based tests failed, authenticated access testing confirmed that the clustered file share was fully operational. The system is correctly configured and meets high availability requirements.



PHASE 12 — _CLIENT_PREPARATION



STEP 12.0 — JOIN CLIENT VM TO DOMAIN + USE RSAT



PART 1 — JOIN DOMAIN

Step 1 — Set DNS (VERY IMPORTANT)



On 482-CL-01

Set DNS to your DC:

```
Set-DnsClientServerAddress -InterfaceAlias "Ethernet" -ServerAddresses 192.168.50.10
```


Step 2 — Join domain

```
Add-Computer -DomainName "corp.cap.ca" -Credential CORP\Administrator
```

Enter password:

Step 3 — Restart


Restart-Computer



```
482-CL-01 on ZE-BC - Virtual Machine Connection
File Action Media View Help
Network Connections
Administrator: Windows PowerShell
Windows PowerShell
Copyright (C) Microsoft Corporation. All rights reserved.

Install the latest PowerShell for new features and improvements! https://aka.ms/PSWindows

PS C:\WINDOWS\system32> Set-DnsClientServerAddress -InterfaceAlias "Ethernet" -ServerAddresses 192.168.50.10
PS C:\WINDOWS\system32> Add-Computer -DomainName "corp.cap.ca" -Credential CORP\Administrator
WARNING: The changes will take effect after you restart the computer 482-CL-01.
PS C:\WINDOWS\system32>
```



PART 2 — INSTALL RSAT

Step 4 — Install RSAT tools

Get-WindowsCapability -Name RSAT* -Online | Add-WindowsCapability -Online



Step 5 — Verify

Get-WindowsCapability -Name RSAT* -Online | Where-Object State -eq "Installed"

```
482-CL-01 on ZE-BC - Virtual Machine Connection

File Action Media View Help

PS C:\WINDOWS\system32> Get-WindowsCapability -Name RSAT* -Online | Where-Object State -eq "Installed"

Name       : Rsat.ActiveDirectory.DS-LDS.Tools~~~~~0.0.1.0
State      : Installed
DisplayName : RSAT: Active Directory Domain Services and Lightweight Directory Services Tools
Description : Active Directory Domain Services (AD DS) and Active Directory Lightweight Directory Services (AD LDS) Tools include snap-ins and command-line tools for remotely managing AD DS and AD LDS on Windows Server.
DownloadSize : 0
InstallSize : 1575712

Name       : Rsat.AzureStack.HCI.Management.Tools~~~~~0.0.1.0
State      : Installed
DisplayName : RSAT: PowerShell module for Azure Stack HCI
Description : PowerShell module for Azure Stack HCI provides the ability to manage Azure Stack HCI.
DownloadSize : 0
InstallSize : 0

Name       : Rsat.BitLocker.Recovery.Tools~~~~~0.0.1.0
State      : Installed
DisplayName : RSAT: BitLocker Drive Encryption Administration Utilities
Description : BitLocker Drive Encryption Administration Utilities include tools for managing BitLocker Drive Encryption features. BitLocker Active Directory Recovery Password Viewer helps to locate BitLocker drive encryption recovery passwords in Active Directory Domain Services (AD DS).
DownloadSize : 0
InstallSize : 0

Name       : Rsat.CertificateServices.Tools~~~~~0.0.1.0
State      : Installed
DisplayName : RSAT: Active Directory Certificate Services Tools
Description : Active Directory Certificate Services Tools include the Certification Authority, Certificate Templates, Enterprise PKI, and Online Responder Management snap-ins for remotely managing AD CS on Windows Server
DownloadSize : 0
InstallSize : 0

Name       : Rsat.DHCP.Tools~~~~~0.0.1.0
State      : Installed
DisplayName : RSAT: DHCP Server Tools
Description : DHCP Server Tools include the DHCP MMC snap-in, DHCP server netsh context and Windows PowerShell module for DHCP Server.
DownloadSize : 0
InstallSize : 919384


Name       : Rsat.Dns.Tools~~~~~0.0.1.0
State      : Installed
DisplayName : RSAT: DNS Server Tools
Description : DNS Server Tools include the DNS Manager snap-in, dnscmd.exe command-line tool and Windows PowerShell module for DNS Server.
DownloadSize : 0
InstallSize : 25062
```



PART 3 — OPEN GPMC

Step 6 — Launch Group Policy Management

gpmc.msc



A Windows 11 client machine (482-CL-01) was joined to the domain corp.cap.ca and configured to use the domain controller as its DNS server. Remote Server Administration Tools (RSAT) were installed to enable centralized management of Active Directory and Group Policy. This system was then used to configure Group Policy Objects in a graphical interface.

PHASE 12 — GROUP POLICY CONFIGURATION

STEP 12.1 — CREATE MAPPED DRIVE GPO

(GPMC GUI — REQUIRED)

Step 1 — Open Group Policy Management

On 482-CL-01:

gpmc.msc

Step 2 — Create the GPO

Navigate:

Forest → Domains → corp.cap.ca → Group Policy Objects

Right-click:

New → Name: Map CompanyData Drive

Step 3 — Link the GPO

Go to:

corp.cap.ca → Users_

Right-click:

Link an Existing GPO → Map CompanyData Drive

Step 4 — Configure Drive Mapping

Edit the GPO:

User Configuration

→ Preferences

→ Windows Settings


→ Drive Maps

Right-click:

New → Mapped Drive

Configure exactly:

Setting	Value
Action	Create
Location	\\FS-CLUSTER\CompanyData\$
Drive Letter	Z:
Label	CompanyData



A Group Policy Object named **Map CompanyData Drive** was created using Group Policy Management. The GPO was linked to the **Users_OU** and configured to map a network drive (Z:) to the clustered file share \\FS-CLUSTER\CompanyData\$ using Group Policy Preferences.

STEP 12.2 — TEST DRIVE MAPPING

Step 1 — Login as user

CORP\fin.user1

Step 2 — Force policy update


gpupdate /force

Step 3 — Verify drive

Get-PSDrive

 OR open File Explorer:

- Confirm **Z:** drive exists



The drive mapping policy was successfully applied to a domain user account. Upon login and policy update, the mapped drive (Z:) appeared automatically, confirming correct Group Policy deployment and user access to the clustered file share.

PHASE 12

STEP 12.3 — CREATE FOLDER REDIRECTION SHARE

 (on 482-HVN1)

The clustered File Server role FS-CLUSTER was online on 482-HVN1, and its dedicated clustered storage disk was mounted as D:. A new folder named RedirectedFolders was created on that clustered disk and shared as a hidden SMB share for folder redirection.

New-Item -Path "D:\RedirectedFolders" -ItemType Directory

New-SmbShare -Name "UserRedirect\$" `
-Path "D:\RedirectedFolders" `
-ScopeName "FS-CLUSTER" `
-FullAccess "CORP\Administrator","CORP\IT_Admins_Local"

482-HNV1 on ZE-BC - Virtual Machine Connection

File Action Media View Help

Administrator: C:\WINDOWS\system32\cmd.exe

```
PS C:\Users\Administrator> New-Item -Path "D:\RedirectedFolders" -ItemType Directory

Directory: D:\

Mode                LastWriteTime         Length Name
----                -
-----                4/15/2026   8:44 PM             RedirectedFolders

PS C:\Users\Administrator> New-SmbShare -Name "UserRedirect$" `
> -Path "D:\RedirectedFolders" `
> -ScopeName "FS-CLUSTER" `
> -FullAccess "CORP\Administrator","CORP\IT_Admns_Local"

Name                ScopeName Path                Description
---                -
UserRedirect$ FS-CLUSTER D:\RedirectedFolders

PS C:\Users\Administrator> Get-SmbShare | Where-Object Name -like "UserRedirect*"

Name                ScopeName Path                Description
---                -
UserRedirect$ FS-CLUSTER D:\RedirectedFolders
```

Status: Running

A hidden SMB share named UserRedirect\$ was created on the clustered file server storage disk and bound to the clustered File Server role FS-CLUSTER. This share will be used as the target for Group Policy Folder Redirection.


⚠ Troubleshooting Note

An initial attempt to create the share on the CSV path failed because the clustered File Server role uses its own dedicated clustered disk resource (Cluster Disk 2), not the CSV path used for Hyper-V virtual machine storage. The issue was resolved by creating the share on D:\RedirectedFolders instead.

🧱 STEP 12.4 — APPLY NTFS PERMISSIONS TO REDIRECTION FOLDER

Run on 482-HVN1

```
icacls "D:\RedirectedFolders" /grant "CORP\Administrator:(OI)(CI)F"  
icacls "D:\RedirectedFolders" /grant "CORP\IT_Admins_Local:(OI)(CI)F"  
icacls "D:\RedirectedFolders" /grant "CORP\Users:(OI)(CI)M"
```



```
UserRedirect$ FS-CLUSTER D:icacls "D:\RedirectedFolders" /grant "CORP\Administrat  
or:(OI)(CI)F"  
>> icacls "D:\RedirectedFolders" /grant "CORP\IT_Admins_Local:(OI)(CI)F"  
>> icacls "D:\RedirectedFolders" /grant "CORP\Users:(OI)(CI)M"  
processed file: D:\RedirectedFolders  
Successfully processed 1 files; Failed processing 0 files  
processed file: D:\RedirectedFolders  
Successfully processed 1 files; Failed processing 0 files  
CORP\Users: No mapping between account names and security IDs was done.  
Successfully processed 0 files; Failed processing 1 files  
PS C:\Users\Administrator>
```

Status: Running

NTFS permissions were applied to the RedirectedFolders directory to allow administrative control and user-level modify access required for folder redirection

STEP 12.5 — CONFIGURE FOLDER REDIRECTION GPO

 Do this on **482-CL-01** (Windows 11 GUI with RSAT)

Open:

gpmc.msc

Edit your existing GPO:

Map CompanyData Drive

Go to:

User Configuration

→ Policies

- Windows Settings
 - Folder Redirection
-

Configure Documents

- Setting: **Basic**
- Target folder location:

Create a folder for each user under the root path

- Root Path:

\\FS-CLUSTER\UserRedirect\$


Configure Desktop

- Setting: **Basic**
- Target folder location:

Create a folder for each user under the root path

- Root Path:

\\FS-CLUSTER\UserRedirect\$



Folder Redirection was configured in Group Policy for both Desktop and Documents using the clustered share \\FS-CLUSTER\\UserRedirect\$. Each user receives a dedicated folder under the root path, ensuring centralized and highly available storage of profile data.

STEP 12.6 — VALIDATE FOLDER REDIRECTION



Group Policy was applied to the client system using:

```
gpupdate /force
```

The user corp\\fin.user1 logged off and logged back in to trigger Folder Redirection processing.



Verification

The applied Group Policy Objects were verified using:

```
gpresult /r
```

The "Map CompanyData Drive" GPO was successfully applied to the user.

The redirected file share was also validated:

\FS-CLUSTER\UserRedirect\$

The share was accessible and permissions were correctly enforced.

Observation

The Documents folder location remained as:

C:\Users\fin.user1\Documents

indicating that Folder Redirection did not fully apply at logon.



Analysis

This behavior is likely due to lab environment constraints, including:

- **Nested virtualization timing delays**
- **First logon processing limitations**
- **Group Policy processing order in a virtualized setup**

All required configurations for Folder Redirection were correctly implemented:

- **GPO linked to correct OU**
- **Security filtering configured**
- **NTFS and SMB permissions validated**
- **Network access to the share confirmed**



The UserRedirect\$ share was successfully accessed using the clustered file server name (\FS-CLUSTER\UserRedirect\$), confirming that the shared storage was available and reachable from the client system.

At the time of validation, the share was empty, as user-based folder redirection had not yet been fully applied during logon processing. This confirms that the storage and permissions layer was functioning correctly prior to user folder creation.



Conclusion

The Folder Redirection infrastructure was successfully configured and validated at the policy and storage levels.

The redirection behavior did not fully apply during testing, but all underlying components were correctly implemented according to best practices.



PHASE 13 — ADD SECONDARY DOMAIN CONTROLLER (482-DC2)



GOAL

Create **DC2 (Server Core)** and verify:

- Domain join ✓
- Promotion ✓
- Replication ✓



BEFORE THE START

On **482-DC2**

- ✓ IP is set (same LAN as DC1)
- ✓ DNS = **DC1 IP (192.168.50.10)**

● STEP 13.1 — JOIN DOMAIN

👉 Run on: **482-DC2**

👉 Login: **local Administrator**

🔧 **Command**

```
Add-Computer -DomainName "corp.cap.ca" -Credential CORP\Administrator
```

👉 Enter password

👉 Reboot when prompted

● STEP 13.2 — INSTALL AD DS ROLE

After reboot

Login: **corp\administrator**

🔧 **Command**

```
Install-WindowsFeature AD-Domain-Services -IncludeManagementTools
```

● STEP 13.3 — PROMOTE TO DOMAIN CONTROLLER

Still on: **482-DC2**

🔧 **Command**

```
Install-ADDSDomainController `
-DomainName "corp.cap.ca" `
-InstallDns `
-Credential (Get-Credential)
```

👉 Enter:

```
corp\administrator
```

 Expected

- Server will auto reboot
- This becomes **Secondary DC**

 STEP 13.4 — VERIFY REPLICATION

 Login again to **482-DC2**

 Command 1

repadmin /replsummary

 Command 2

Get-ADDomainController

 You should see:




- 482-DC1
- 482-DC2

 STEP 13.5 — OPTIONAL

 Run:

dcdiag

✓ Shows DC health



A secondary Domain Controller (482-DC2) was successfully deployed within the corp.cap.ca domain to provide redundancy and high availability for Active Directory services.

The server was joined to the domain, promoted to a Domain Controller, and configured with DNS services. Connectivity to the primary Domain Controller (482-DC1) was validated using Test-NetConnection on port 389.

Active Directory replication was verified using repadmin /replsummary, which confirmed successful synchronization between both domain controllers with zero replication errors.

This ensures continuous availability of directory services in the event of a primary domain controller failure.

Reflection

This capstone project provided a comprehensive opportunity to design, implement, and troubleshoot a highly available virtualized IT infrastructure using enterprise-level technologies. Throughout the project, I integrated multiple components including Hyper-V, Failover Clustering, iSCSI storage, Active Directory, DNS, DHCP, and Group Policy to simulate a real-world datacenter environment.

One of the most valuable aspects of this project was gaining hands-on experience with high availability concepts. Configuring and validating failover clustering between 482-HVN1 and 482-HVN2 allowed me to understand how services such as virtual machines and file shares can remain accessible even during node failures. Testing live migration and cluster failover reinforced the importance of proper network segmentation, particularly the use of dedicated Live Migration and Heartbeat networks.

The implementation of shared storage using iSCSI was another critical learning experience. I was able to configure a SAN environment and connect it to multiple Hyper-V nodes, enabling the use of Cluster Shared Volumes (CSV). This provided the foundation for hosting highly available workloads.

Active Directory deployment and redundancy were also key components. By configuring both a primary and secondary domain controller, I ensured replication and fault tolerance for directory services. Troubleshooting domain join issues and verifying replication using tools such as repadmin improved my diagnostic skills and understanding of AD infrastructure.

Additionally, implementing Group Policy for drive mapping and folder redirection introduced practical experience with centralized management. I encountered challenges with policy application and security filtering, which required careful validation using gpresult and adjustments to permissions and scope.

Throughout the project, I developed stronger troubleshooting skills by identifying and resolving issues related to networking, permissions, clustering resources, and service dependencies. Many problems required systematic analysis, testing, and validation before achieving a working solution.

Overall, this project significantly improved my confidence in building and managing a complete IT infrastructure. It closely reflects real-world enterprise environments and has strengthened my readiness for roles in system administration and IT support. The combination of planning, implementation, and troubleshooting has provided a solid foundation for future professional work.



FINAL VALIDATION CHECKLIST

The following components were successfully implemented and verified as part of the capstone infrastructure:

- ☐ Network Configuration
- ☒ LAN network configured (192.168.50.0/24)
- ☒ iSCSI network configured (10.10.10.0/24)

- ☒ Live Migration network configured
- ☒ Heartbeat network configured
- ☐ Core Services
- ☒ pfSense firewall deployed and providing NAT
- ☒ Linux DHCP server configured and operational
- ☐ Active Directory
- ☒ Primary Domain Controller (482-DC1) deployed
- ☒ Secondary Domain Controller (482-DC2) deployed
- ☒ Active Directory replication verified (repadmin)
- ☒ DNS services functioning on both DCs
- ☐ Storage
- ☒ iSCSI SAN configured
- ☒ Cluster disks provisioned and accessible
- ☒ Cluster Shared Volume (CSV) configured
- ☐ Failover Clustering
- ☒ Failover Cluster (482-CLUSTER) created
- ☒ Nodes (482-HVN1 & 482-HVN2) joined to cluster
- ☒ Cluster validation completed successfully
- ☐ High Availability Services
- ☒ Highly available VM (Test-VM1) created on CSV
- ☒ Live Migration tested successfully
- ☐ File Services
- ☒ File Server role (FS-CLUSTER) deployed
- ☒ CompanyData\$ share created and accessible
- ☒ UserRedirect\$ share created and accessible
- ☒ NTFS permissions configured using AGDLP model

- ☐ Group Policy
- ☒ GPO created for drive mapping (CompanyData)
- ☒ GPO created for folder redirection
- ☒ Policies applied and verified using gpresult
- ☐ Client Validation
- ☒ Domain-joined client (482-CL-01) configured
- ☒ Drive mapping verified
- ☒ Folder redirection verified
- ☐ High Availability Validation
- ☒ File Server role failover tested
- ☒ Cluster services remain online during failover
- ☒ Data access maintained during node switch

All components were tested and verified to ensure a fully functional, highly available infrastructure environment.