

Class 14: RNASeq mini-project

Zeyu Qi(A17342618)

Table of contents

Background	1
Data Import	1
Sanity Check	4
Setup DESeq object	5
Run DESeq analysis pipeline	5
Extract the results	6
Data Viz	7
Add Annotation data	9
Pathway analysis	11
Save results	17

Background

The data for our hands-on session comes from GEO entry: GSE37704, which is associated with the following publication:

Trapnell C, Hendrickson DG, Sauvageau M, Goff L et al. “Differential analysis of gene regulation at transcript resolution with RNA-seq”. Nat Biotechnol 2013 Jan;31(1):46-53. PMID: 23222703

Data Import

Read counts and metatdata CSV file

```
library(DESeq2)
```

Loading required package: S4Vectors

Loading required package: stats4

Loading required package: BiocGenerics

Loading required package: generics

Attaching package: 'generics'

The following objects are masked from 'package:base':

as.difftime, as.factor, as.ordered, intersect, is.element, setdiff,
setequal, union

Attaching package: 'BiocGenerics'

The following objects are masked from 'package:stats':

IQR, mad, sd, var, xtabs

The following objects are masked from 'package:base':

anyDuplicated, aperm, append, as.data.frame, basename, cbind,
colnames, dirname, do.call, duplicated, eval, evalq, Filter, Find,
get, grep, grepl, is.unsorted, lapply, Map, mapply, match, mget,
order, paste, pmax, pmax.int, pmin, pmin.int, Position, rank,
rbind, Reduce, rownames, sapply, saveRDS, table, tapply, unique,
unsplit, which.max, which.min

Attaching package: 'S4Vectors'

The following object is masked from 'package:utils':

findMatches

The following objects are masked from 'package:base':

expand.grid, I, unname

Loading required package: IRanges

Loading required package: GenomicRanges

Loading required package: Seqinfo

Loading required package: SummarizedExperiment

Loading required package: MatrixGenerics

Loading required package: matrixStats

Attaching package: 'MatrixGenerics'

The following objects are masked from 'package:matrixStats':

colAlls, colAnyNAs, colAnys, colAvgPerRowSet, colCollapse,
colCounts, colCummaxs, colCummins, colCumprods, colCumsums,
colDiffs, colIQRDiffs, colIQRs, colLogSumExps, colMadDiffs,
colMads, colMaxs, colMeans2, colMedians, colMins, colOrderStats,
colProds, colQuantiles, colRanges, colRanks, colSdDiffs, colSds,
colSums2, colTabulates, colVarDiffs, colVars, colWeightedMads,
colWeightedMeans, colWeightedMedians, colWeightedSds,
colWeightedVars, rowAlls, rowAnyNAs, rowAnys, rowAvgPerColSet,
rowCollapse, rowCounts, rowCummaxs, rowCummins, rowCumprods,
rowCumsums, rowDiffs, rowIQRDiffs, rowIQRs, rowLogSumExps,
rowMadDiffs, rowMads, rowMaxs, rowMeans2, rowMedians, rowMins,
rowOrderStats, rowProds, rowQuantiles, rowRanges, rowRanks,
rowSdDiffs, rowSds, rowSums2, rowTabulates, rowVarDiffs, rowVars,
rowWeightedMads, rowWeightedMeans, rowWeightedMedians,
rowWeightedSds, rowWeightedVars

Loading required package: Biobase

Welcome to Bioconductor

Vignettes contain introductory material; view with
'browseVignettes()'. To cite Bioconductor, see
'citation("Biobase")', and for packages 'citation("pkgname")'.

Attaching package: 'Biobase'

The following object is masked from 'package:MatrixGenerics':

rowMedians

The following objects are masked from 'package:matrixStats':

anyMissing, rowMedians

```
countData <- read.csv("GSE37704_featurecounts.csv", row.names = 1)
colData <- read.csv("GSE37704_metadata.csv", row.names = 1)
```

Sanity Check

Q. Complete the code below to remove the troublesome first column from countData

```
# Note we need to remove the odd first $length col
countData <- as.matrix(countData[, -1])
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000186092	0	0	0	0	0	0
ENSG00000279928	0	0	0	0	0	0
ENSG00000279457	23	28	29	29	28	46
ENSG00000278566	0	0	0	0	0	0
ENSG00000273547	0	0	0	0	0	0
ENSG00000187634	124	123	205	207	212	258

Q. Complete the code below to filter countData to exclude genes (i.e. rows) where we have 0 read count across all samples (i.e. columns).

```
# Filter count data where you have 0 read count across all samples.
countData = countData[rowSums(countData) != 0, ]
head(countData)
```

	SRR493366	SRR493367	SRR493368	SRR493369	SRR493370	SRR493371
ENSG00000279457	23	28	29	29	28	46
ENSG00000187634	124	123	205	207	212	258
ENSG00000188976	1637	1831	2383	1226	1326	1504
ENSG00000187961	120	153	180	236	255	357
ENSG00000187583	24	48	65	44	48	64
ENSG00000187642	4	9	16	14	16	16

Setup DESeq object

```
dds = DESeqDataSetFromMatrix(countData=countData,
                              colData=colData,
                              design=~condition)
```

Warning in DESeqDataSet(se, design = design, ignoreRank): some variables in design formula are characters, converting to factors

Run DESeq analysis pipeline

```
dds = DESeq(dds)
```

estimating size factors

estimating dispersions

gene-wise dispersion estimates

mean-dispersion relationship

final dispersion estimates

fitting model and testing

```
dds
```

```

class: DESeqDataSet
dim: 15975 6
metadata(1): version
assays(4): counts mu H cooks
rownames(15975): ENSG00000279457 ENSG00000187634 ... ENSG00000276345
               ENSG00000271254
rowData names(22): baseMean baseVar ... deviance maxCooks
colnames(6): SRR493366 SRR493367 ... SRR493370 SRR493371
colData names(2): condition sizeFactor

```

Extract the results

Big table with log2 fold changes and p-values

```

res = results(dds)
summary(res)

```

```

out of 15975 with nonzero total read count
adjusted p-value < 0.1
LFC > 0 (up)      : 4349, 27%
LFC < 0 (down)    : 4396, 28%
outliers [1]      : 0, 0%
low counts [2]    : 1237, 7.7%
(mean count < 0)
[1] see 'cooksCutoff' argument of ?results
[2] see 'independentFiltering' argument of ?results

```

```
head(res)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 6 rows and 6 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.9136	0.1792571	0.3248215	0.551863	5.81042e-01
ENSG00000187634	183.2296	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.1881	-0.6927205	0.0548465	-12.630156	1.43993e-36
ENSG00000187961	209.6379	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.2551	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.9798	0.5428105	0.5215598	1.040744	2.97994e-01

```

      padj
      <numeric>
ENSG00000279457 6.86555e-01
ENSG00000187634 5.15718e-03
ENSG00000188976 1.76553e-35
ENSG00000187961 1.13413e-07
ENSG00000187583 9.19031e-01
ENSG00000187642 4.03379e-01

```

Data Viz

Volcano plot


```

library(ggplot2)

ggplot(res) +
  aes(log2FoldChange,
      -log(padj)) +
  geom_point()

```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).



Q. Improve this plot by completing the below code, which adds color, axis labels and cutoff lines:


```
# Make a color vector for all genes
mycols <- rep("gray", nrow(res) )

# Color blue the genes with fold change above 2
mycols[ abs(res$log2FoldChange) > 2 ] <- "blue"

# Color gray those with adjusted p-value more than 0.01
mycols[ res$padj > 0.01 ] <- "gray"

ggplot(res) +
  aes(log2FoldChange,
      -log(padj)) +
  geom_point(color = mycols) +
  xlab("Log2(FoldChange)") +
  ylab("-Log(P-value)") +
  geom_vline(xintercept = c(-2,2)) +
  geom_hline(yintercept = -log(0.01))
```

Warning: Removed 1237 rows containing missing values or values outside the scale range (`geom\_point()`).



Add Annotation data

Add gene symbol and entrez ids

Q. Use the `mapIds()` function multiple times to add SYMBOL, ENTREZID and GENENAME annotation to our results by completing the code below.

```
library("AnnotationDbi")
library("org.Hs.eg.db")
```

```
columns(org.Hs.eg.db)
```

[1]	"ACCNUM"	"ALIAS"	"ENSEMBL"	"ENSEMBLPROT"	"ENSEMBLTRANS"
[6]	"ENTREZID"	"ENZYME"	"EVIDENCE"	"EVIDENCEALL"	"GENENAME"
[11]	"GENETYPE"	"GO"	"GOALL"	"IPI"	"MAP"
[16]	"OMIM"	"ONTOLOGY"	"ONTOLOGYALL"	"PATH"	"PFAM"
[21]	"PMID"	"PROSITE"	"REFSEQ"	"SYMBOL"	"UCSCKG"
[26]	"UNIPROT"				

```
res$symbol = mapIds(org.Hs.eg.db,
                     keys=row.names(res),
                     keytype="ENSEMBL",
                     column="SYMBOL",
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$entrez = mapIds(org.Hs.eg.db,
                     keys=row.names(res),
                     keytype="ENSEMBL",
                     column="ENTREZID",
                     multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
res$name = mapIds(org.Hs.eg.db,
                  keys=row.names(res),
                  keytype="ENSEMBL",
                  column="GENENAME",
                  multiVals="first")
```

'select()' returned 1:many mapping between keys and columns

```
head(res, 10)
```

log2 fold change (MLE): condition hoxa1 kd vs control sirna

Wald test p-value: condition hoxa1 kd vs control sirna

DataFrame with 10 rows and 9 columns

	baseMean	log2FoldChange	lfcSE	stat	pvalue
	<numeric>	<numeric>	<numeric>	<numeric>	<numeric>
ENSG00000279457	29.913579	0.1792571	0.3248215	0.551863	5.81042e-01
ENSG00000187634	183.229650	0.4264571	0.1402658	3.040350	2.36304e-03
ENSG00000188976	1651.188076	-0.6927205	0.0548465	-12.630156	1.43993e-36
ENSG00000187961	209.637938	0.7297556	0.1318599	5.534326	3.12428e-08
ENSG00000187583	47.255123	0.0405765	0.2718928	0.149237	8.81366e-01
ENSG00000187642	11.979750	0.5428105	0.5215598	1.040744	2.97994e-01
ENSG00000188290	108.922128	2.0570638	0.1969053	10.446970	1.51281e-25
ENSG00000187608	350.716868	0.2573837	0.1027266	2.505522	1.22271e-02
ENSG00000188157	9128.439422	0.3899088	0.0467164	8.346302	7.04333e-17
ENSG00000237330	0.158192	0.7859552	4.0804729	0.192614	8.47261e-01
	padj	symbol	entrez	name	
	<numeric>	<character>	<character>	<character>	
ENSG00000279457	6.86555e-01	NA	NA	NA	
ENSG00000187634	5.15718e-03	SAMD11	148398	sterile alpha motif ..	
ENSG00000188976	1.76553e-35	NOC2L	26155	NOC2 like nucleolar ..	
ENSG00000187961	1.13413e-07	KLHL17	339451	kelch like family me..	
ENSG00000187583	9.19031e-01	PLEKHN1	84069	pleckstrin homology ..	
ENSG00000187642	4.03379e-01	PERM1	84808	PPARGC1 and ESRR ind..	
ENSG00000188290	1.30538e-24	HES4	57801	hes family bHLH tran..	
ENSG00000187608	2.37452e-02	ISG15	9636	ISG15 ubiquitin like..	
ENSG00000188157	4.21970e-16	AGRN	375790	agrin	
ENSG00000237330	NA	RNF223	401934	ring finger protein ..	

Q. Finally for this section let's reorder these results by adjusted p-value and save them to a CSV file in your current project directory.

```
res = res[order(res$pvalue),]
write.csv(res, file="deseq_results.csv")
```

Pathway analysis

KEGG, GO, and REACTOME

```
library(pathview)
```

```
#####
Pathview is an open source software package distributed under GNU General
Public License version 3 (GPLv3). Details of GPLv3 is available at
http://www.gnu.org/licenses/gpl-3.0.html. Particullary, users are required to
formally cite the original Pathview paper (not just mention it) in publications
or products. For details, do citation("pathview") within R.
```

The pathview downloads and uses KEGG data. Non-academic uses may require a KEGG license agreement (details at <http://www.kegg.jp/kegg/legal.html>).

```
#####
```

```
library(gage)
```

```
library(gageData)

data(kegg.sets.hs)
data(sigmet.idx.hs)

# Focus on signaling and metabolic pathways only
kegg.sets.hs = kegg.sets.hs[sigmet.idx.hs]

# Examine the first 3 pathways
head(kegg.sets.hs, 3)
```

```
$`hsa00232 Caffeine metabolism`
[1] "10"    "1544" "1548" "1549" "1553" "7498" "9"
```

```
$`hsa00983 Drug metabolism - other enzymes`
```

```

[1] "10"      "1066"    "10720"   "10941"   "151531"  "1548"    "1549"    "1551"
[9] "1553"    "1576"    "1577"    "1806"    "1807"    "1890"    "221223"  "2990"
[17] "3251"    "3614"    "3615"    "3704"    "51733"   "54490"   "54575"   "54576"
[25] "54577"   "54578"   "54579"   "54600"   "54657"   "54658"   "54659"   "54963"
[33] "574537"  "64816"   "7083"    "7084"    "7172"    "7363"    "7364"    "7365"
[41] "7366"    "7367"    "7371"    "7372"    "7378"    "7498"    "79799"   "83549"
[49] "8824"    "8833"    "9"       "978"

```

```
$`hsa00230 Purine metabolism`
```

```

[1] "100"      "10201"   "10606"   "10621"   "10622"   "10623"   "107"     "10714"
[9] "108"      "10846"   "109"     "111"     "11128"   "11164"   "112"     "113"
[17] "114"      "115"     "122481"  "122622"  "124583"  "132"     "158"     "159"
[25] "1633"     "171568"  "1716"    "196883"  "203"     "204"     "205"     "221823"
[33] "2272"     "22978"   "23649"   "246721"  "25885"   "2618"    "26289"   "270"
[41] "271"     "27115"   "272"     "2766"    "2977"    "2982"    "2983"    "2984"
[49] "2986"     "2987"   "29922"   "3000"    "30833"   "30834"   "318"     "3251"
[57] "353"      "3614"    "3615"    "3704"    "377841"  "471"     "4830"    "4831"
[65] "4832"     "4833"   "4860"    "4881"    "4882"    "4907"    "50484"   "50940"
[73] "51082"    "51251"   "51292"   "5136"    "5137"    "5138"    "5139"    "5140"
[81] "5141"     "5142"   "5143"    "5144"    "5145"    "5146"    "5147"    "5148"
[89] "5149"     "5150"   "5151"    "5152"    "5153"    "5158"    "5167"    "5169"
[97] "51728"    "5198"   "5236"    "5313"    "5315"    "53343"   "54107"   "5422"
[105] "5424"     "5425"   "5426"    "5427"    "5430"    "5431"    "5432"    "5433"
[113] "5434"     "5435"   "5436"    "5437"    "5438"    "5439"    "5440"    "5441"
[121] "5471"     "548644" "55276"   "5557"    "5558"    "55703"   "55811"   "55821"
[129] "5631"     "5634"   "56655"   "56953"   "56985"   "57804"   "58497"   "6240"
[137] "6241"     "64425"   "646625"  "654364"  "661"     "7498"    "8382"    "84172"
[145] "84265"    "84284"   "84618"   "8622"    "8654"    "87178"   "8833"    "9060"
[153] "9061"     "93034"   "953"     "9533"    "954"     "955"     "956"     "957"
[161] "9583"     "9615"

```

```

foldchanges = res$log2FoldChange
names(foldchanges) = res$entrez
head(foldchanges)

```

```

      1266      54855      1465      2034      2150      6659
-2.422719  3.201955 -2.313738 -1.888019  3.344508  2.392288

```

```

# Get the results
keggres = gage(foldchanges, gsets=kegg.sets.hs)
attributes(keggres)

```

```
$names
[1] "greater" "less"    "stats"
```

```
# Look at the first few down (less) pathways
head(keggres$less)
```

	p.geomean	stat.mean	p.val
hsa04110 Cell cycle	8.995727e-06	-4.378644	8.995727e-06
hsa03030 DNA replication	9.424076e-05	-3.951803	9.424076e-05
hsa03013 RNA transport	1.375901e-03	-3.028500	1.375901e-03
hsa03440 Homologous recombination	3.066756e-03	-2.852899	3.066756e-03
hsa04114 Oocyte meiosis	3.784520e-03	-2.698128	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	8.961413e-03	-2.405398	8.961413e-03

	q.val	set.size	exp1
hsa04110 Cell cycle	0.001448312	121	8.995727e-06
hsa03030 DNA replication	0.007586381	36	9.424076e-05
hsa03013 RNA transport	0.073840037	144	1.375901e-03
hsa03440 Homologous recombination	0.121861535	28	3.066756e-03
hsa04114 Oocyte meiosis	0.121861535	102	3.784520e-03
hsa00010 Glycolysis / Gluconeogenesis	0.212222694	53	8.961413e-03

```
pathview(gene.data=foldchanges, pathway.id="hsa04110")
```

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/edwardqi/Desktop/BIMM 143/class14

Info: Writing image file hsa04110.pathview.png

Info: Working in directory /Users/edwardqi/Desktop/BIMM 143/class14

Info: Writing image file hsa04110.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/edwardqi/Desktop/BIMM 143/class14

Info: Writing image file hsa03030.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/edwardqi/Desktop/BIMM 143/class14

Info: Writing image file hsa03013.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/edwardqi/Desktop/BIMM 143/class14

Info: Writing image file hsa03440.pathview.png

'select()' returned 1:1 mapping between keys and columns

Info: Working in directory /Users/edwardqi/Desktop/BIMM 143/class14

Info: Writing image file hsa04114.pathview.png

```
data(go.sets.hs)
data(go.subs.hs)

# Focus on Biological Process subset of GO
gobpsets = go.sets.hs[go.subs.hs$BP]

gobpres = gage(foldchanges, gsets=gobpsets)

lapply(gobpres, head)
```

\$greater

		p.geomean	stat.mean	p.val
G0:0007156	homophilic cell adhesion	8.519724e-05	3.824205	8.519724e-05
G0:0002009	morphogenesis of an epithelium	1.396681e-04	3.653886	1.396681e-04
G0:0048729	tissue morphogenesis	1.432451e-04	3.643242	1.432451e-04
G0:0007610	behavior	1.925222e-04	3.565432	1.925222e-04
G0:0060562	epithelial tube morphogenesis	5.932837e-04	3.261376	5.932837e-04
G0:0035295	tube development	5.953254e-04	3.253665	5.953254e-04
		q.val	set.size	exp1
G0:0007156	homophilic cell adhesion	0.1951953	113	8.519724e-05
G0:0002009	morphogenesis of an epithelium	0.1951953	339	1.396681e-04
G0:0048729	tissue morphogenesis	0.1951953	424	1.432451e-04
G0:0007610	behavior	0.1967577	426	1.925222e-04
G0:0060562	epithelial tube morphogenesis	0.3565320	257	5.932837e-04
G0:0035295	tube development	0.3565320	391	5.953254e-04

\$less

		p.geomean	stat.mean	p.val
G0:0048285	organelle fission	1.536227e-15	-8.063910	1.536227e-15
G0:0000280	nuclear division	4.286961e-15	-7.939217	4.286961e-15
G0:0007067	mitosis	4.286961e-15	-7.939217	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.169934e-14	-7.797496	1.169934e-14
G0:0007059	chromosome segregation	2.028624e-11	-6.878340	2.028624e-11
G0:0000236	mitotic prometaphase	1.729553e-10	-6.695966	1.729553e-10
		q.val	set.size	exp1
G0:0048285	organelle fission	5.841698e-12	376	1.536227e-15
G0:0000280	nuclear division	5.841698e-12	352	4.286961e-15
G0:0007067	mitosis	5.841698e-12	352	4.286961e-15
G0:0000087	M phase of mitotic cell cycle	1.195672e-11	362	1.169934e-14
G0:0007059	chromosome segregation	1.658603e-08	142	2.028624e-11
G0:0000236	mitotic prometaphase	1.178402e-07	84	1.729553e-10

\$stats


		stat.mean	exp1
G0:0007156	homophilic cell adhesion	3.824205	3.824205
G0:0002009	morphogenesis of an epithelium	3.653886	3.653886
G0:0048729	tissue morphogenesis	3.643242	3.643242
G0:0007610	behavior	3.565432	3.565432
G0:0060562	epithelial tube morphogenesis	3.261376	3.261376
G0:0035295	tube development	3.253665	3.253665


```
sig_genes <- res[res$padj <= 0.05 & !is.na(res$padj), "symbol"]
print(paste("Total number of significant genes:", length(sig_genes)))
```

```
[1] "Total number of significant genes: 8147"
```

```
write.table(sig_genes, file="significant_genes.txt", row.names=FALSE, col.names=FALSE, quote=
```

Q: What pathway has the most significant “Entities p-value”? Do the most significant pathways listed match your previous KEGG results? What factors could cause differences between the two methods?



Cell cycle has the most significant Entities p-value. Some significant pathways match with previous KEGG results. Differences can happen because KEGG and Reactome define pathways differently, include different genes, use different pathway sizes, and may apply different enrichment statistics or p-value correction methods.

Save results

```
write.csv(res, file="myresults")
```